

JTIC FILE COPY

AD-A207 242

USAFETAC/OS-89/200

SURFACE OBSERVATION CLIMATIC SUMMARIES

FOR

K. I. SAWYER AFB MI

PREPARED BY

DL-A, USAFETAC
ASHEVILLE, NORTH CAROLINA
28801-2723

MARCH 1989

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION IS UNLIMITED

USAF
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

SCOTT AIR FORCE AFB, ILLINOIS, 62225-5438

089

**Best
Available
Copy**

①

USAFETAC/DS-89/200

SURFACE OBSERVATION CLIMATIC SUMMARIES

FOR

K. I. SAWYER AFB MI

PREPARED BY

DL-A, USAFETAC
ASHEVILLE, NORTH CAROLINA
28801-2723

MARCH 1989

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION IS UNLIMITED

DTIC
ELECTE
APR 26 1989
S H D

USAF
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER

SCOTT AIR FORCE AFB, ILLINOIS, 62225-5438

089 4 26 098

REVIEW AND APPROVAL STATEMENT

USAFETAC/DS-89/200, SURFACE OBSERVATION CLIMATIC SUMMARIES FOR K. I. SAWYER AFB MI, MARCH 1989, HAS BEEN REVIEWED AND IS APPROVED FOR PUBLIC RELEASE. THERE IS NO OBJECTION TO UNLIMITED DISTRIBUTION OF THIS DOCUMENT TO THE PUBLIC AT LARGE, OR BY THE DEFENSE TECHNICAL INFORMATION CENTER (DTIC) TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS).

JOSEPH L. BOYTE
CHIEF, CLIMATIC APPLICATIONS, OL-A

FOR THE COMMANDER

WALTER S. BURGMANN
SCIENTIFIC AND TECHNICAL INFORMATION
PROGRAM MANAGER

REPORT DOCUMENTATION PAGE

- 1A. REPORT SECURITY CLASSIFICATION: UNCLASSIFIED
3. DISTRIBUTION/AVAILABILITY OF REPORT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION
4. PERFORMING ORGANIZATION REPORT NUMBER: USAFETAC/DS-89/200
- 6A. NAME OF PERFORMING ORGANIZATION: OPERATING LOCATION A, USAFETAC
- 6B. OFFICE SYMBOL: CA
- 6C. ADDRESS: FEDERAL BUILDING, ASHEVILLE, NC 28801-2723
11. TITLE: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) FOR K. I. SAWYER AFB MICHIGAN
- 13A. TYPE OF REPORT: DATA SUMMARY
- 13B. TIME COVERED: OCTOBER 1956 TO JULY 1988
14. DATE OF REPORT: MARCH 1989
15. PAGE COUNT: 375
16. SUPPLEMENTARY NOTATION: EFFECTIVE 1 JULY 1989, THIS PRODUCT REPLACED TWO USAFETAC DOCUMENTS FORMERLY KNOWN AS THE REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS (RUSSWOS) AND THE LIMITED SURFACE OBSERVATIONS CLIMATIC SUMMARY (LISOCS). EXISTING RUSSWOS AND LISOCS WILL CONTINUE IN USE, BUT WILL EVENTUALLY BE REPLACED BY A SOCS.
17. COSATI CODES: FIELD--04, GROUP--02
18. SUBJECT TERMS: *CLIMATOLOGY, METEOROLOGICAL DATA, ATMOSPHERIC PHENOMENA, WEATHER, CEILING, CLOUD COVER, SNOW DEPTH, HUMIDITY, PRESSURE, PRECIPITATION, SNOW, TEMPERATURE, VISIBILITY, WIND, SOCS, *K. I. SAWYER AFB MICHIGAN.
19. ABSTRACT: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) PROVIDE STATISTICAL CLIMATIC SUMMARIES OF SURFACE WEATHER OBSERVATIONS TAKEN AND RECORDED AT SPECIFIED USAF, CIVILIAN, AND FOREIGN OBSERVING STATIONS. HOURLY OBSERVATIONS ARE SUMMARIZED FOR A 10-YEAR PERIOD OF RECORD (POR). "SUMMARY OF DAY" (SOD) INFORMATION IS SUMMARIZED FROM ALL AVAILABLE DATA IN THE OL-A CLIMATIC DATABASE.
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.
21. ABSTRACT SECURITY CLASSIFICATION: UNCLASSIFIED
- 22A. NAME OF RESPONSIBLE INDIVIDUAL: WILLIAM R. BOBB
- 22B. TELEPHONE: 704 259-0402 AUTOVON 697-8358
- 22C. OFFICE SYMBOL: OL-A7CA,

DD FORM 1473

REPORT DOCUMENTATION PAGE

SECURITY CLASSIFICATION: UNCLASSIFIED

AVAILABILITY OF REPORT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.

ORGANIZATION REPORT NUMBER: USAFETAC/DS-89/200

FORMING ORGANIZATION: OPERATING LOCATION A, USAFETAC

DL: CA

FEDERAL BUILDING, ASHEVILLE, NC 28801-2723

SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) FOR K. I. SAWYER AFB MICHIGAN

REPORT: DATA SUMMARY

PERIOD: OCTOBER 1956 TO JULY 1988

DATE: MARCH 1989 15. PAGE COUNT: 375

NOTE: EFFECTIVE 1 JULY 1989, THIS PRODUCT REPLACED TWO USAFETAC PRODUCTS KNOWN AS THE REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS (RUSO) AND LIMITED SURFACE OBSERVATIONS CLIMATIC SUMMARY (LISOCS). EXISTING PRODUCTS WILL CONTINUE IN USE, BUT WILL EVENTUALLY BE REPLACED BY A SOCS.

FIELD: FIELD--04, GROUP--02

CONTENTS: *CLIMATOLOGY, METEOROLOGICAL DATA, ATMOSPHERIC PHENOMENA, CLOUD COVER, SNOW DEPTH, HUMIDITY, PRESSURE, PRECIPITATION, VISIBILITY, WIND, SOCS, *K. I. SAWYER AFB MICHIGAN.



SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) PROVIDE STATISTICAL ANALYSES OF SURFACE WEATHER OBSERVATIONS TAKEN AND RECORDED AT SPECIFIED DOMESTIC AND FOREIGN OBSERVING STATIONS. HOURLY OBSERVATIONS ARE SUMMARIZED FROM THE DATE OF RECORD (POR). "SUMMARY OF DAY" (SOD) INFORMATION IS SUMMARIZED IN THE DATA IN THE DL-A CLIMATIC DATABASE.

AVAILABILITY OF ABSTRACT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.

SECURITY CLASSIFICATION: UNCLASSIFIED

RESponsible INDIVIDUAL: WILLIAM R. BOBB

704 259-0402 AUTOVON 697-8358 22C. OFFICE SYMBOL: DL-A7CA, USAFETAC

Distribution For	
GRA&I	<input checked="" type="checkbox"/>
TAE	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
Distribution/Availability Codes	
Avail and/or Special	
Dist	

PREFACE

EFFECTIVE 1 JULY 1988, THE SURFACE OBSERVATION CLIMATIC SUMMARY (SOCS) REPLACED TWO OTHER USAFETAC PRODUCTS OF LONG STANDING: THE RUSSWO (REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS) AND LISOCS (LIMITED SURFACE OBSERVATION CLIMATIC SUMMARY). RUSSWOS AND LISOCS NOW IN EXISTENCE WILL CONTINUE TO BE USED UNTIL THEY ARE EVENTUALLY REPLACED BY SOCS.

THIS PRODUCT HAS BEEN ISSUED IN OTHER FORMS UNDER SEVERAL OTHER NAMES. IT WAS INTRODUCED IN THE EARLY 1940'S AS THE "SFCSUM," OR "SURFACE SUMMARY." THE ORIGINAL "USSWO," OR "UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS," DEBUTED IN 1946. THE USSWO GRADUALLY EVOLVED INTO THE "RUSSWO" AND THE "LISOCS." IT FINALLY BECAME THE NEW "SURFACE OBSERVATION CLIMATIC SUMMARY" OR "SOCS" IN JULY 1988.

THE SOCS (LIKE ITS PREDECESSORS) IS PREPARED BY USAFETAC'S OPERATING LOCATION A AT ASHEVILLE, NC 28801-2723. HERE, CLIMATOLOGISTS USE STATE-OF-THE-ART COMPUTER TECHNOLOGY TO SUMMARIZE WEATHER OBSERVATIONS COLLECTED FROM SELECTED MILITARY, CIVILIAN, AND FOREIGN REPORTING STATIONS. SUMMARIES ARE PREPARED FROM DATA THAT HAS BEEN COLLECTED, QUALITY-CONTROLLED, AND STORED IN OL-A'S WORLDWIDE SURFACE WEATHER OBSERVATION DATABASE.

ALTHOUGH PREVIOUS VERSIONS OF THIS PRODUCT ONLY OFFERED SIX PARTS, SOCS PROVIDES EIGHT (A-H). THE ADDITIONS ARE THE CROSSWIND AND HEATING-COOLING DEGREE DAY SUMMARIES. PRECEDING EACH PART IS A BRIEF DISCUSSION OF THAT PARTICULAR PART, A DESCRIPTION OF THE DATA, AND AN EXPLANATION OF HOW THE DATA IS PRESENTED.

CONTENTS:

INTRODUCTION.....1
STATION PERIOD OF RECORD.....1
DATA SOURCES.....1
TERMS EXPLAINED.....1
TIME CONVENTIONS.....2
ABBREVIATIONS.....2
SUMMARY DESCRIPTIONS.....2

STATION HISTORY.....3

PART A - ATMOSPHERIC PHENOMENA SUMMARIES.....A-1-1
SPECIFIED PHENOMENA
PERCENT OCCURRENCE FREQUENCY (FROM HOURLY OBS).....A-2-1
PERCENT OCCURRENCE FREQUENCY (FROM SOD DATA).....A-3-1
PERCENT OCCURRENCE FREQUENCY (THUNDERSTORMS).....A-4-1
VERSUS WIND DIRECTION--PERCENT OCCURRENCE FREQUENCY.....A-5-1

PART B - PRECIPITATION, SNOWFALL, AND SNOW DEPTH.....B-1-1
PRECIPITATION
PERCENT OCCURRENCE FREQUENCY.....B-2-1
MONTHLY TOTALS.....B-2-2
DAILY EXTREMES.....B-2-3
SNOWFALL
PERCENT OCCURRENCE FREQUENCY.....B-3-1
MONTHLY TOTALS.....B-3-2
DAILY EXTREMES.....B-3-3
SNOW DEPTH
PERCENT OCCURRENCE FREQUENCY.....B-4-1
DAILY EXTREMES.....B-4-2
SNOWFALL/SNOW DEPTH
FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR.....B-5-1

PART C - SURFACE WIND:
PEAK WINDS (FROM SOD DATA).....C-2-1
PEAK WINDS--PERCENT OCCURRENCE FREQUENCY (FROM SOD DATA).....C-3-1
WIND DIRECTION VS WIND SPEED--PDF (FROM HOURLY OBS).....C-4-1

PART D - CEILING, VISIBILITY AND SKY COVER
CEILING VS VISIBILITY--PDF (FROM HOURLY OBS).....D-2-1
SKY COVER--PDF (FROM HOURLY OBS).....D-3-1

CONT

↓

PART E - TEMPERATURE AND RELATIVE HUMIDITY.....	E-1-1
TEMPERATURES--CUMULATIVE PDF (FROM SOD DATA)	
MAXIMA.....	F-2-1
MINIMA.....	E-2-2
MEAN.....	E-2-3
MONTHLY TEMPERATURES (FROM SOD DATA)	
MAXIMA.....	E-3-1
MINIMA.....	E-3-2
MEAN.....	E-4-1
DRY BULB, WET BULB, DEW POINT TEMPERATURES (FROM HOURLY OBS)	
DRY BULB.....	E-5-1
WET BULB.....	E-5-2
DEW POINT.....	E-5-3
RELATIVE HUMIDITY (FROM HOURLY OBS)	
CUMULATIVE PERCENT OCCURRENCE FREQUENCY.....	E-6-1
PART F - PRESSURE (FROM HOURLY OBS).....	F-1-1
SEA LEVEL PRESSURE.....	F-2-1
ALTIMETER SETTING.....	F-3-1
STATION PRESSURE.....	F-4-1
PART G - CROSSWIND SUMMARIES (FROM HOURLY OBS).....	G-1-1
PERCENT OCCURRENCE FREQUENCY.....	G-2-1
PART H - DEGREE DAY SUMMARIES (FROM HOURLY OBS).....	H-1-1
HEATING DEGREE DAYS.....	H-2-1
COOLING DEGREE DAYS.....	H-3-1

INTRODUCTION

STATION PERIOD OF RECORD.

HOURLY OBSERVATIONS: AUG 78 - JUL 89 (AIRWAYS).

SUMMARY OF DAY DATA: OCT 56 - DEC 57, APR 58 - OCT 58, OCT 59 - JUL 88 (FULL TIME).

HOURS SUMMARIZED: 0000 LST THROUGH 2300 LST.

DATA SOURCES. THESE SUMMARIES ARE COMPILED FROM "HOURLY OBSERVATIONS" AND/OR SUMMARY OF DAY DATA," DEPENDING ON THE PHENOMENA OR OCCURRENCE BEING SUMMARIZED. THE TWO SOURCES ARE DEFINED IN "TERMS EXPLAINED."

TERMS EXPLAINED:

BIVARIATE DISTRIBUTION: A BIVARIATE DISTRIBUTION GIVES THE JOINT DISTRIBUTIONS OF TWO RELATED VARIABLES. AN EXAMPLE IS THE BIVARIATE DISTRIBUTION OF CEILING AND VISIBILITIES IN PART D. EACH ROW AND EACH COLUMN OF A BIVARIATE DISTRIBUTION IS A FREQUENCY DISTRIBUTION. JOINT FREQUENCIES ARE FOUND AT THE ROW-COLUMN INTERSECTIONS.

HOURLY OBSERVATIONS: ALL RECORD OR RECORD-SPECIAL OBSERVATIONS ON AWS FORMS 10/10A (OR EQUIVALENT) AT SCHEDULED HOURLY INTERVALS.

SUMMARY OF DAY (SOD) DATA: DATA COMPILED FROM ALL AVAILABLE OBSERVATIONAL SOURCES, INCLUDING HOURLY OBSERVATIONS, SPECIAL OBSERVATIONS, REMARKS, AND ACTUAL "SUMMARY OF DAY" DATA RECORDED IN COLUMNS 44 -73 OF AWS FORMS 10/10A (OR EQUIVALENT) FOR ANY GIVEN DAY.

MEAN: THE SUM OF ALL THE VALUES DIVIDED BY THE NUMBER OF VALUES.

MEASURABLE AMOUNT: ANY PRECIPITATION OR SNOWFALL AMOUNT GREATER THAN A TRACE.

MEDIAN: THE MIDDLE VALUE WHEN THE VALUES ARE IN ASCENDING ORDER. IF THE NUMBER OF VALUES IS EVEN, THE MEDIAN IS HALFWAY BETWEEN THE TWO MIDDLE VALUES.

PERCENT OCCURRENCE FREQUENCY (POF): IN STATISTICS, FREQUENCY IS THE NUMBER OF TIMES A GIVEN COUNT OR EVENT OCCURS. IN THE SOCS, THIS IS EXPRESSED AS THE PERCENT OCCURRENCE FREQUENCY (POF), WHERE THE FREQUENCY (NUMBER OF OCCURRENCES) IS GIVEN AS A PERCENT OF ALL POSSIBLE OCCURRENCES IN THE SAMPLE (PERIOD SUMMARIZED). FOR EXAMPLE, IF SNOW FELL ON 5 OUT OF 100 DAYS WE COULD EXPRESS THE "PERCENT OCCURRENCE FREQUENCY" OF SNOW AS 5 PERCENT OVER THE 100-DAY PERIOD. MAY BE USED INTERCHANGEABLY WITH "PERCENT FREQUENCY OF OCCURRENCE."

PERIOD OF RECORD: THE SIZE OF THE OBSERVATIONAL DATA SAMPLE, IN YEARS.

PRECIPITATION: A TERM THAT INCLUDES BOTH LIQUID PRECIPITATION AND WATER EQUIVALENT.

STANDARD DEVIATION: A MEASURE OF DISPERSION OR THE VARIABILITY OF THE QUANTITY CONCERNED ABOUT ITS ARITHMETIC MEAN. THE LARGER THE STANDARD DEVIATION, THE GREATER THE VARIABILITY.

TIME CONVENTIONS: ALL TIMES IN THE SOCS ARE EXPRESSED IN LOCAL STANDARD TIME (LST). USERS SHOULD MAKE ADJUSTMENTS FOR DAYLIGHT SAVING TIMES IN THEIR AREAS. IN SUMMARIES THAT SHOW DIURNAL VARIATIONS, THE DATA IS SUMMARIZED USING THE FOLLOWING STANDARD 3-HOUR PERIODS (ALL LST):

0000-0200	1200-1400
0300-0500	1500-1700
0600-0800	1800-2000
0900-1100	2100-2300

ABBREVIATIONS USED:

AMT	AMOUNT	LT	LESS THAN
ANN	ANNUAL	M	METER
BARO	BAROMETER	MM	MILLIGRAM
C	CENTIGRADE (CÉLSIUS)	MPS	METERS PER SECOND
DEG	DEGREE	MSL	MEAN SEA LEVEL
DB	DRY BULB TEMPERATURE	MEAS	MEASURABLE
DP	DEW POINT TEMPERATURE	NO.	NUMBER
EQ	EQUAL	OBS	OBSERVATION
F	FAHRENHEIT	OBST	OBSTRUCTION
FPZG	FREEZING	POF	PERCENT OCCURRENCE FREQUENCY
FT	FEET	PRECIP	PRECIPITATION
GE	GREATER THAN OR EQUAL TO	SD	STANDARD DEVIATION
GMT	GREENWICH MEAN TIME	SOD	SUMMARY OF DAY
GT	GREATER THAN	TEMP	TEMPERATURE
HG	INCHES OF MERCURY	TSTM	THUNDERSTORM
HT	HEIGHT	VSBY	VISIBILITY
KTS	KNOTS	VSN	VISION
LF	LESS THAN OR EQUAL TO	WB	WET BULB TEMPERATURE
LST	LOCAL STANDARD TIME	WBAN	AWS FORM 10/10A
		UTC	*COORDINATED UNIVERSAL TIME

SUMMARY DESCRIPTION: A BRIEF DESCRIPTION OF THE DATA PRECEDES EACH PART IN THE SOCS.

* UTC REPLACED GMT ON 1 AUGUST 1988

STATION NO.	STATION NAME	LATITUDE	LONGITUDE	FLD ELEV (FT)	CA
727435	K I SAWYER AFB, MI	N 46 21	W 087 24	1220	KS

STATION LOCATION AND INSTRUMENTATION HISTORY

NMRR OF LOC	GEOGRAPHICAL LOCATION & NAME	TYPE OF STATION	AT THIS LOCATION		LATITUDE	LONGITUDE	ELEV FLD (
			FROM	TO			
1	K I SAWYER AIRPORT, MI	FAA	OCT 56	DEC 56	N 46 21	W 087 24	1195
2	K I SAWYER AFB, MI	AFB	JAN 57	OCT 58	SAME	SAME	1204
3	SAME	SAME	SEP 59	OCT 59	SAME	SAME	1230
4	SAME	SAME	NOV 59	DEC 73	SAME	SAME	SAME
5	SAME	SAME	JAN 74	OCT 82	SAME	SAME	SAME
6	SAME	SAME	NOV 82	JAN 83	SAME	SAME	1220

NMRR OF LOC	DATE OF CHANGE	SURFACE WIND EQUIPMENT INFORMATION				REMARKS, COMMENT, OR
		LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	
1	OCT 56	ATOP CONTROL TOWER	AN/GMO-1	ML-204A	83 FT	
2	JAN 57	4000' NW TWR, 225' E OF TAXIWAY	AN/GMO-11	RO-2	13 FT	
3	SEP 61	ON RWNY COMPLEX	SAME	SAME	15 FT	
4	MAR 64	1,1900' FM S END RWY 2,1000' FM N END OF RWNY	SAME SAME	SAME	13 FT 13 FT	
5	JAN 70	1,600' E CTRLN, 1200' FM S END OF RWY 19	AN/GMO-20	RO-362	SAME	
		2,575' E OF CTRLN, 2075' N OF END OF RWY 01	SAME		SAME	
6	JAN 83	1. SAME 2. SAME	SAME SAME	SAME	SAME SAME	

STATION NAME _____ LATITUDE _____ LONGITUDE _____ FLD ELEV (FT) _____ CALL SIGN _____ WMO NMBR _____
 N 46 21 W 087 24 1220 KSAW

STATION LOCATION AND INSTRUMENTATION HISTORY

TYPE OF STATION	AT THIS LOCATION		LATITUDE	LONGITUDE	ELEV ABOVE MSL		OBS PER DAY
	FROM	TO			FLD (FT)	BARO (FT)	
FAA	OCT 56	DEC 56	N 46 21	W 087 24	1195	1190	12
AFB	JAN 57	OCT 58	SAME	SAME	1204	SAME	24
SAME	SEP 59	OCT 59	SAME	SAME	1230	SAME	24
SAME	NOV 59	DEC 73	SAME	SAME	SAME	1240	24
SAME	JAN 74	OCT 82	SAME	SAME	SAME	1190	24
SAME	NOV 82	JAN 88	SAME	SAME	1220	SAME	24

EQUIPMENT INFORMATION

	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	REMARKS, ADDITIONAL EQUIPMENT, OR REASON FOR CHANGE
TAXIWAY	AN/GMQ-1	ML-204A	83 FT	
	AN/GMQ-11	RO-2	13 FT	
	SAME	SAME	15 FT	
	SAME	SAME	13 FT	
PNWY	SAME	SAME	13 FT	
FM S END OF	AN/GMQ-20	RO-362	SAME	
75 FT OF END	SAME		SAME	
	SAME	SAME	SAME	
	SAME		SAME	

pppppppp	AAAAAA	RRRRRRRR	TTTTTTTTTT	AAAAAA
pppppppp	AAAAAAAA	RRRRRRRR	TTTTTTTTTT	AAAAAAAA
pp pp	AA AA	RR RR	TT	AA AA
pp pp	AA AA	RR RR	TT	AA AA
pppppppp	AA AA	RRRRRRRR	TT	AA AA
pppppppp	AAAAAAAAAA	RRRRRRRR	TT	AAAAAAAAAA
pp	AAAAAAAAAA	RR RR	TT	AAAAAAAAAA
pp	AA AA	RR RR	TT	AA AA
pp	AA AA	RR RR	TT	AA AA
pp	AA AA	RR RR	TT	AA AA

PART A

ATMOSPHERIC PHENOMENA SUMMARIES

THIS PART SUMMARIZES SPECIFIED ATMOSPHERIC PHENOMENA IN CATEGORIES AS FOLLOWS:

THUNDERSTORMS: ALL REPORTED OCCURRENCES OF THUNDERSTORMS, TORNADOES, AND WATERSPOUTS.

LIQUID PRECIPITATION: RAIN OR DRIZZLE FALLING TO THE GROUND BUT NOT FREEZING.

FREEZING PRECIPITATION: FREEZING RAIN OR FREEZING DRIZZLE (GLAZE).

FROZEN PRECIPITATION: SNOW, SNOW PELLETS, SLEET, SNOW GRAINS, ICE CRYSTALS, ICE PELLETS. IN JANUARY 1968, SNOW PELLETS BECAME KNOWN AS SMALL HAIL.

HAIL: ALL OCCURRENCES OF HAIL.

ALL PRECIPITATION: INCLUDES ALL OBSERVATIONS REPORTING PRECIPITATION. BECAUSE MORE THAN ONE TYPE OF PRECIPITATION MAY BE INCLUDED IN THE SAME OBSERVATION, THE SUM OF PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY.

FOG: INCLUDES ALL REPORTED FOG, ICE FOG, AND GROUND FOG.

SMOKE AND/OR HAZE: SMOKE, HAZE, OR COMBINATIONS OF THE TWO.

BLOWING SNOW: ALL REPORTS OF BLOWING SNOW, INCLUDING DRIFTING SNOW, WHEN REPORTED.

DUST AND/OR SAND: DUST, SAND, BLOWING DUST, BLOWING SAND, OR COMBINATIONS OF THESE.

BLOWING SPRAY: THE "ALL OBSTRUCTIONS TO VISION" CATEGORY ACCOUNTS FOR BLOWING SPRAY, IF AND AS REPORTED.

ALL OBSTRUCTIONS TO VISION: THIS CATEGORY INCLUDES ALL REPORTS OF OBSTRUCTIONS TO VISION. SINCE THE OCCURRENCE OF MORE THAN ONE OBSTRUCTION TO VISION MAY BE REPORTED IN THE SAME OBSERVATION, THE SUM OF THE PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY.

SPECIFIED PHENOMENA--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY (POF) FOR THE ATMOSPHERIC PHENOMENA SHOWN. THE DATA WAS TAKEN FROM HOURLY OBSERVATIONS ONLY, AND IS SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

SPECIFIED PHENOMENA--PERCENT OCCURRENCE FREQUENCY (POF).

THIS TABLE IS THE ONLY ONE IN PART A THAT IS PRODUCED FROM SUMMARY OF DAY DATA. DATA IS SUMMARIZED MONTHLY AND ANNUALLY FOR ALL YEARS COMBINED.

THUNDERSTORMS--PERCENT OCCURRENCE FREQUENCY.

THIS TABLE GIVES THE PERCENT OCCURRENCE FREQUENCY OF THUNDERSTORMS REPORTED ON THE HOURLY OBSERVATION. DATA IS SUMMARIZED SAME AS FOR FIRST TABLE IN THIS PART.

SPECIFIED PHENOMENA VS WIND DIRECTION--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES INCLUDE SUMMARY OF MONTH FOR ALL HOURS AND YEARS COMBINED. WIND DIRECTION CATEGORIES ARE AS SPECIFIED BY THE LOCAL WEATHER STATION.

NOTE 1: REPORTING PRACTICES HAVE CHANGED WITH TIME. METAR AND SYNOPTIC REPORTING STATIONS RECORD (ON AWS FORMS 10/10A) AND TRANSMIT LONGLINE ONLY THE HIGHEST ORDER ATMOSPHERIC PHENOMENA THAT AFFECTS VISIBILITY. METAR STATIONS STARTED THIS PROCEDURE IN JANUARY 1968, BUT SYNOPTIC STATIONS ALWAYS DID IT THAT WAY. IN JANUARY 1970, METAR STATIONS STARTED RECORDING ALL ATMOSPHERIC PHENOMENA THAT AFFECTED VISIBILITY, BUT CONTINUED TO TRANSMIT ONLY THE HIGHEST ORDER. FOR EXAMPLE, IF THE RECORDED OBSERVATION INCLUDED RAIN, FOG AND HAZE, ONLY THE RAIN WAS TRANSMITTED. BECAUSE OF THESE PROCEDURES, THE USAFETAC DATABASE WOULD SHOW ONLY RAIN AS AN OBSTRUCTION. THEREFORE, THE OBSTRUCTION TO VISION (AND TO A LESSER EXTENT, PRECIPITATION) SUMMARIES FOR METAR AND SYNOPTIC STATIONS ARE HIGHLY QUESTIONABLE.

NOTE 2: FOREIGN METAR REPORTING STATIONS FREQUENTLY DO NOT TRANSMIT OBSTRUCTIONS TO VISION WHEN VISIBILITIES EXCEED 1000 METERS.

NOTE 3: A VALUE OF ".0" IN ANY SUMMARY REPRESENTS ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL
LST TO UTC: + 5 MONTH: JAN

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OBS
00-02		.6	1.9	44.8		47.4	9.0	.1	8.9		65.5	930
03-05		1.1	1.6	44.9		47.6	10.8		9.7		68.1	930
06-08		1.3	1.5	44.7		47.5	10.6		9.7		67.8	930
09-11		1.5	1.7	43.7		46.9	13.9	.4	9.8		71.0	930
12-14		1.2	1.1	41.8		44.1	10.9	.6	11.3		66.9	930
15-17		.9	1.6	42.3		44.7	7.6	.8	11.2		64.3	930
18-20		.6	1.4	40.2		42.3	8.2	.9	9.0		60.3	930
21-23		1.2	1.5	41.9		44.6	7.7	.3	8.8		61.5	930

ALL HOURS 1.0 1.5 43.1 45.6 9.8 .4 9.8 65.7 7440

MONTH: FEB

00-02		1.1	2.6	32.9		36.5	15.3	.5	5.9		58.2	849
03-05	.1	1.3	1.3	33.5		36.5	14.4	.2	6.8		58.0	849
06-08	.4	1.4	2.0	32.9		36.3	16.0	1.2	7.1		60.5	849
09-11	.1	1.5	1.5	33.2		36.3	16.3	3.1	9.1		64.7	849
12-14		1.6	.1	33.2		35.0	11.9	2.6	9.2		58.7	849
15-17		2.4	.2	32.4		35.0	10.7	2.4	6.8		54.9	849
18-20		2.0	1.1	28.4		31.4	12.4	2.0	3.9		49.7	849
21-23		2.1	1.4	28.9		32.4	13.8	.7	5.2		52.1	849

ALL HOURS .1 1.7 1.3 31.9 34.9 13.8 1.6 6.7 57.1 6792

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: JAN

MIN	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
0		47.4	9.0	.1	8.9		65.5	930
1		47.6	10.8		9.7		68.1	930
2		47.5	10.6		9.7		67.8	930
3		46.9	13.9	.4	9.8		71.0	930
4		44.1	10.9	.6	11.3		66.9	930
5		44.7	7.6	.8	11.2		64.3	930
6		42.3	8.2	.9	9.0		60.3	930
7		44.6	7.7	.3	8.8		61.5	930
8		45.6	9.8	.4	9.8		65.7	7440

MONTH: FEB

0		36.5	15.3	.5	5.9		58.2	849
1		36.5	14.4	.2	6.8		58.0	849
2		36.3	16.0	1.2	7.1		60.5	849
3		36.3	16.3	3.1	9.1		64.7	849
4		35.0	11.9	2.6	9.2		58.7	849
5		35.0	10.7	2.4	6.8		54.9	849
6		31.4	12.4	2.0	3.9		49.7	849
7		32.4	13.8	.7	5.2		52.1	849
8		34.9	13.8	1.6	6.7		57.1	6792

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAR

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TO NO
00-02		3.4	2.7	26.0		32.2	15.7	.5	6.2		54.6	
03-05	.1	4.7	2.5	27.1		34.3	15.9	.6	7.0		57.8	
06-08		4.8	2.5	28.1		35.4	18.0	.9	8.2		62.4	
09-11		4.3	1.1	28.7		34.1	17.6	1.1	9.8		62.6	
12-14		4.5	.5	27.1		32.2	13.7	1.9	9.2		57.0	
15-17	.1	4.1	.5	23.2		27.8	12.6	2.2	8.9		51.5	
18-20	.2	4.3	1.6	22.8		28.7	14.4	1.3	6.1		50.5	
21-23	.2	4.4	1.3	23.7		29.4	15.1	.4	5.3		50.1	
ALL HOURS	.1	4.3	1.6	25.8		31.7	15.4	1.1	7.6		55.8	7

MONTH: APR

00-02	.9	9.6	.3	10.0		19.9	10.6	.1	2.0		32.6	
03-05	.6	9.6	.6	10.9		21.0	13.6	.2	2.0		36.8	
06-08	.6	10.4	.3	13.0		23.8	20.1	1.0	2.4		47.3	
09-11	.4	8.7	.2	13.9		22.8	15.1	1.4	2.7		42.0	
12-14	.3	7.1		11.8		18.9	10.9	1.1	1.9		32.8	
15-17	.2	7.9		9.7		17.6	9.8	1.0	1.6	.2	30.1	
18-20	.4	8.9		8.0		16.9	9.2	1.0	1.2	.1	28.4	
21-23	.6	8.8	.2	9.6		18.6	10.7	.3	1.3		30.9	
ALL HOURS	.5	8.9	.2	10.8		19.9	12.5	.8	1.9	.0	35.1	7

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: MAR

FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
26.0		32.2	15.7	.5	6.2		54.6	930
27.1		34.3	15.9	.6	7.0		57.8	930
28.1		35.4	18.0	.9	8.2		62.4	930
28.7		34.1	17.6	1.1	9.8		62.6	930
27.1		32.2	13.7	1.9	9.2		57.0	930
23.2		27.8	12.6	2.2	8.9		51.5	930
22.8		28.7	14.4	1.3	6.1		50.5	930
23.7		29.4	15.1	.4	5.3		50.1	930
25.8		31.7	15.4	1.1	7.6		55.8	7440

MONTH: APR

10.0		19.9	10.6	.1	2.0		32.6	900
10.9		21.0	13.6	.2	2.0		36.8	900
13.0		23.8	20.1	1.0	2.4		47.3	900
13.9		22.8	15.1	1.4	2.7		42.0	900
11.8		18.9	10.9	1.1	1.9		32.8	900
9.7		17.6	9.8	1.0	1.6	.2	30.1	900
8.0		16.9	9.2	1.0	1.2	.1	28.4	900
9.6		18.6	10.7	.3	1.3		30.9	900
10.8		19.9	12.5	.8	1.9	.0	35.1	7200

OPERATING LOCATION "A"
USAF/TAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAY

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN
00-02	.9	9.7		.3		10.0	15.8	1.1			26.9
03-05	1.1	11.2		.5		11.7	17.4	1.1			30.2
06-08	.4	12.0		.6		12.7	13.4	.9			31.9
09-11		12.5		.9		13.3	14.4	3.2			31.0
12-14	.3	11.4		.9		12.3	10.1	4.0			26.3
15-17	.4	8.8		1.1		9.9	8.8	3.2			21.9
18-20	1.2	10.2		.6		10.9	8.7	3.9			23.4
21-23	.9	9.6		.4		10.0	11.8	2.4			24.2

ALL HOURS .6 10.7 .7 11.3 13.2 2.5 27.0

MONTH: JUN

00-02	2.3	11.3				11.3	10.8	1.3			23.4
03-05	1.4	10.3				10.3	11.3	1.7			23.3
06-08	1.1	8.1				8.1	13.9	3.8			25.8
09-11	.3	6.9				6.9	7.1	4.2			18.2
12-14	1.4	8.8				8.8	5.1	3.2			17.1
15-17	2.3	9.0				9.0	4.2	2.9			16.1
18-20	2.7	8.4				8.4	4.2	3.4			16.1
21-23	1.9	11.0				11.0	7.9	2.7			21.6

ALL HOURS 1.7 9.2 9.2 8.1 2.9 20.2

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: MAY

PROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
.3		10.0	15.8	1.1			26.9	930
.5		11.7	17.4	1.1			30.2	930
.6		12.7	13.4	.9			31.9	930
.9		13.3	14.4	3.2			31.0	930
.9		12.3	10.1	4.0			26.3	930
1.1		9.9	8.8	3.2			21.9	930
.6		10.9	8.7	3.9			23.4	930
.4		10.0	11.8	2.4			24.2	930
.7		11.3	13.2	2.5			27.0	7440

MONTH: JUN

		11.3	10.8	1.3			23.4	900
		10.3	11.3	1.7			23.3	900
		8.1	13.9	3.8			25.8	900
		6.9	7.1	4.2			18.2	900
		8.8	5.1	3.2			17.1	900
		9.0	4.2	2.9			16.1	900
		8.4	4.2	3.4			16.1	900
		11.0	7.9	2.7			21.6	900
		9.2	8.1	2.9			20.2	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: JUL

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO.
00-02	1.3	6.9				6.9	12.7	3.0			22.6	
03-05	.6	4.9				4.9	19.0	2.6			26.6	
06-08	1.1	5.4				5.4	22.7	5.6			33.7	
09-11	.9	7.3				7.3	9.6	7.5			24.4	
12-14	2.0	6.7				6.7	5.1	7.3			19.0	
15-17	3.5	7.5				7.5	3.4	6.8			17.7	
18-20	2.8	7.9				7.9	5.7	7.0			20.6	
21-23	2.7	7.0				7.0	8.8	4.2			20.1	
ALL HOURS	1.9	6.7				6.7	10.9	5.5			23.1	74

MONTH: AUG

00-02	2.3	10.9				10.9	22.8	1.7			35.4	
03-05	1.2	9.2				9.2	29.7	1.8			40.8	
06-08	1.4	11.5				11.5	33.4	1.9			46.9	
09-11	1.1	11.2				11.2	18.1	5.6			34.8	
12-14	.4	8.7		.1		8.8	8.9	5.1		.1	22.9	
15-17	2.3	9.6				9.6	7.7	6.5			23.8	
18-20	2.6	9.4				9.4	10.3	8.0			27.6	
21-23	2.7	11.9				11.9	16.0	4.5			32.5	
ALL HOURS	1.7	10.3		.0		10.3	18.4	4.4		.0	33.1	74

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
ELEVATION: + 5 MONTH: JUL

PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
		6.9	12.7	3.0			22.6	930
		4.9	19.0	2.6			26.6	930
		5.4	22.7	5.6			33.7	930
		7.3	9.6	7.5			24.4	930
		6.7	5.1	7.3			19.0	930
		7.5	3.4	6.8			17.7	930
		7.9	5.7	7.0			20.6	928
		7.0	8.8	4.2			20.1	927
		6.7	10.9	5.5			23.1	7435

MONTH: AUG

		10.9	22.8	1.7			35.4	930
		9.2	29.7	1.8			40.8	930
		11.5	33.4	1.9			46.9	930
		11.2	18.1	5.6			34.8	930
		8.8	8.9	5.1		.1	22.9	930
		9.6	7.7	6.5			23.8	930
		9.4	10.3	8.0			27.6	930
		11.9	16.0	4.5			32.5	930
		10.3	18.4	4.4		.0	33.1	7440

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHEN
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: SEP

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN
00-02	1.2	16.9				16.9	24.9	3.3			45.1
03-05	.8	17.4				17.4	28.6	2.3			48.3
06-08	1.3	17.9		.1		18.0	30.2	2.4			50.7
09-11	1.1	17.8		.1		17.9	23.0	4.9			45.9
12-14	1.4	16.0				16.0	14.4	6.7			37.1
15-17	.7	15.7		.1		15.8	13.3	5.3			34.4
18-20	2.1	14.6				14.6	17.0	5.9			37.4
21-23	1.9	16.1				16.1	21.1	4.7			41.9

ALL HOURS	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN
ALL HOURS	1.3	16.5		.0		16.6	21.6	4.4			42.6

MONTH: OCT

00-02	.2	15.2	.1	5.1		20.3	18.5	1.1	.2		40.1
03-05	.4	14.1		6.9		21.0	21.5		.2		42.7
06-08		12.7		5.6		18.3	26.2	.3			44.8
09-11		13.5		5.5		19.0	22.6	1.5			43.1
12-14	.5	14.6		5.3		19.9	13.3	1.0			34.2
15-17	.3	14.2		5.4		19.6	12.7	3.1	.1		35.5
18-20	.2	17.4		4.7		22.2	13.7	2.4	.6		38.8
21-23	.5	16.5		4.9		21.4	14.8	1.1	.3		37.6

ALL HOURS	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN
ALL HOURS	.3	14.8	.0	5.4		20.2	17.9	1.3	.2		39.6

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP

FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
		16.9	24.9	3.3			45.1	900
		17.4	28.6	2.3			48.3	900
.1		18.0	30.2	2.4			50.7	900
.1		17.9	23.0	4.9			45.8	900
		16.0	14.4	6.7			37.1	900
.1		15.8	13.3	5.3			34.4	900
		14.6	17.0	5.9			37.4	900
		15.1	21.1	4.7			41.9	900
.5		15.5	21.6	4.4			42.6	7200

MONTH: OCT

5.1		20.3	18.5	1.1	.2		40.1	930
5.4		21.0	21.5		.2		42.7	930
5.6		18.3	26.2	.3			44.8	930
5.5		19.0	22.6	1.5			43.1	930
5.3		19.9	13.3	1.0			34.2	930
5.4		19.6	12.7	3.1	.1		35.5	930
4.7		22.2	13.7	2.4	.6		38.8	930
4.4		21.4	14.8	1.1	.3		37.6	930
4.4		20.2	17.9	1.3	.2		39.6	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: NOV

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FGG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN
00-02		8.6	.3	21.6		30.4	16.4	.3	.3		47.6
03-05		7.2	.7	22.1		30.0	17.3	.3	.6		48.2
06-08		9.0	.8	24.0		33.3	20.3	.6	1.3		56.0
09-11		7.9	.9	24.6		33.3	20.9	2.2	2.1		58.6
12-14	.1	9.9	.2	24.8		34.9	17.1	1.8	2.3		56.1
15-17		10.6	.1	23.6		34.2	13.4	2.3	1.4		51.4
18-20		9.7	.3	22.1		32.1	15.3	1.9	.9		50.2
21-23	.1	9.4	.2	21.7		31.3	15.6	.8	.2		47.9
ALL HOURS	.0	9.0	.4	23.0		32.5	17.1	1.3	1.2		52.0

MONTH: DEC

00-02		3.5	1.7	38.9		44.2	14.2	.6	6.7		65.7
03-05		3.9	1.3	39.0		44.2	13.9	.3	5.6		64.0
06-08		3.9	2.0	37.1		43.0	14.6	.3	6.3		64.3
09-11		3.8	1.6	36.2		41.6	17.1	.6	6.8		66.1
12-14		4.0	.8	36.2		41.0	14.9	.9	8.0		64.7
15-17		3.2	.6	34.2		38.1	13.1	1.6	5.4		58.2
18-20		2.9	1.1	35.1		39.0	14.0	.5	4.8		59.4
21-23		3.1	1.6	38.4		43.1	14.5	.9	4.7		63.2
ALL HOURS		3.5	1.3	36.9		41.4	14.5	.7	6.0		63.1

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TC: + 5 MONTH: NOV

MOZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
1.6		30.4	16.4	.3	.3		47.6	900
2.1		30.0	17.3	.3	.6		48.2	900
4.0		33.3	20.3	.6	1.3		56.0	900
4.6		33.3	20.9	2.2	2.1		58.6	900
4.8		34.9	17.1	1.8	2.3		56.1	900
3.6		34.2	13.4	2.3	1.4		51.4	900
2.1		32.1	15.3	1.9	.9		50.2	900
1.7		31.3	15.6	.8	.2		47.9	900
3.0		32.5	17.1	1.3	1.2		52.0	7200

MONTH: DEC

1.9		44.2	14.2	.6	6.7		65.7	930
2.0		44.2	13.9	.3	5.6		64.0	930
2.1		43.0	14.6	.3	6.3		64.3	930
2.2		41.6	17.1	.6	6.8		66.1	930
2.2		41.0	14.9	.9	8.0		64.7	930
4.2		38.1	13.1	1.6	5.4		58.2	930
5.1		39.0	14.0	.5	4.8		58.4	930
4.4		43.1	14.5	.9	4.7		63.2	930
5.9		41.8	14.5	.7	6.0		63.1	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
HOURS: ALL

MONTH	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TO N
JAN		1.0	1.5	43.1		45.6	9.8	.4	9.8		65.7	
FEB	.1	1.7	1.3	31.9		34.9	13.8	1.6	6.7		57.1	
MAR	.1	4.3	1.6	25.8		31.7	15.4	1.1	7.6		55.8	
APR	.5	8.9	.2	10.8		19.9	12.5	.8	1.9	.0	35.1	
MAY	.6	10.7		.7		11.3	13.2	2.5			27.0	
JUN	1.7	9.2				9.2	8.1	2.9			20.2	
JUL	1.9	6.7				6.7	10.9	5.5			23.1	
AUG	1.7	10.3		.0		10.3	18.4	4.4		.0	33.1	
SEP	1.3	16.5		.0		16.6	21.6	4.4			42.6	
OCT	.3	14.8	.0	5.4		20.2	17.9	1.3	.2		39.6	
NOV	.0	9.0	.4	23.0		32.5	17.1	1.3	1.2		52.0	
DEC		3.5	1.3	36.9		41.8	14.5	.7	6.0		63.1	
ANNUAL	.7	8.1	.5	14.8		23.4	14.4	2.2	2.8	.0	42.8	8

PERCENTAGE FREQUENCY OF VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 HOURS: ALL

1P	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
	43.1		45.6	9.8	.4	9.8		65.7	7440
	31.9		34.9	13.8	1.6	6.7		57.1	6792
	25.8		31.7	15.4	1.1	7.6		55.8	7440
	10.8		19.9	12.5	.8	1.9	.0	35.1	7200
	.7		11.3	13.2	2.5			27.0	7440
			9.2	8.1	2.9			20.2	7200
			6.7	10.9	5.5			23.1	7435
	.0		10.3	18.4	4.4		.0	33.1	7440
	.0		16.6	21.6	4.4			42.6	7200
	5.4		20.2	17.9	1.3	.2		39.6	7440
	23.0		32.5	17.1	1.3	1.2		52.0	7200
	36.9		41.8	14.5	.7	6.0		63.1	7440
	14.8		23.4	14.4	2.2	2.8	.0	42.8	87667

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF DAYS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 57
MONTH: ALL HOURS: \

MONTH	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND
JAN	.1	12.9	10.0	79.2		81.2	32.2	8.0	28.5	
FEB	.2	12.4	9.1	74.5		76.6	32.1	11.8	23.0	
MAR	1.8	22.4	9.7	57.8	.1	67.4	37.7	10.9	17.4	
APR	4.9	38.7	4.0	31.5	.4	56.1	37.6	7.7	6.1	
MAY	11.0	48.6	.7	7.9	.8	51.3	37.0	11.0	.5	
JUN	19.9	54.6		.3	.9	54.6	41.0	15.8		
JUL	22.2	47.5		.1	1.3	47.5	41.5	19.9		
AUG	19.5	53.8		.2	.4	53.8	48.7	21.7		
SEP	13.0	61.4		2.8	1.0	61.9	55.9	18.4		
OCT	4.7	53.4	.1	23.2	.3	62.5	49.0	16.1	1.5	
NOV	1.2	33.3	4.8	57.8	.3	72.4	42.8	9.3	8.6	
DEC	.3	19.1	12.2	77.6		82.5	36.8	7.5	20.0	
ANNUAL	8.3	38.5	4.1	33.8	.5	63.7	41.1	13.2	8.6	

PERCENTAGE FREQUENCY OF DAYS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712, 5804-5810, 5910-8807
TO UTC: +05 MONTH: ALL HOURS: ALL

FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
10.0	79.2		81.2	32.2	8.0	28.5		86.9	910
9.1	74.5		76.6	32.1	11.8	23.0		80.8	847
9.7	57.8	.1	67.4	37.7	10.9	17.4		73.7	930
4.0	31.5	.4	56.1	37.6	7.7	6.1		60.4	915
.7	7.9	.8	51.3	37.0	11.0	.5		57.5	961
	.3	.9	54.6	41.0	15.8			63.2	930
	.1	1.3	47.5	41.5	19.9			61.4	960
	.2	.4	53.8	48.7	21.7			68.3	930
	2.8	1.0	61.9	55.9	18.4			75.1	900
.1	23.2	.3	62.5	49.0	16.1	1.5		76.5	937
4.8	57.8	.3	72.4	42.8	9.3	8.6		80.7	900
12.2	77.6		82.5	36.8	7.5	20.0		87.8	911
4.1	33.8	.5	63.7	41.1	13.2	8.6		72.5	11031

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF THUNDERSTORMS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78

HOURS (LST)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
00-02				.9	.9	2.3	1.3	2.3	1.2	.2	
03-05		.1	.1	.6	1.1	1.4	.6	1.2	.8	.4	
06-08		.4		.6	.4	1.1	1.1	1.4	1.3		
09-11		.1		.4		.3	.9	1.1	1.1		
12-14				.3	.3	1.4	2.0	.4	1.4	.5	.1
15-17			.1	.2	.4	2.3	3.5	2.3	.7	.3	
18-20			.2	.4	1.2	2.7	2.8	2.6	2.1	.2	
21-23			.2	.6	.9	1.9	2.7	2.7	1.9	.5	.1
ALL HOURS		.1	.1	.5	.6	1.7	1.9	1.7	1.3	.3	.0
TOTAL OBS	7440	6792	7440	7200	7440	7200	7435	7440	7200	7440	7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF THUNDERSTORMS
FROM HOURLY OBSERVATIONS

K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5

	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
9	.9	2.3	1.3	2.3	1.2	.2		
6	1.1	1.4	.6	1.2	.8	.4		
5	.4	1.1	1.1	1.4	1.3			
4		.3	.9	1.1	1.1			
3	.3	1.4	2.0	.4	1.4	.5	.1	
2	.4	2.3	3.5	2.3	.7	.3		
4	1.2	2.7	2.8	2.6	2.1	.2		
5	.9	1.9	2.7	2.7	1.9	.5	.1	
5	.6	1.7	1.9	1.7	1.3	.3	.0	
0	7440	7200	7435	7440	7200	7440	7200	7440

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: JAN HOURS: ALL

PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	N
TSTMS								
LIQUID PRECIP	10.0		26.3	6.3	52.5	5.0		
FREEZING PRECIP	1.7		53.8	6.8	24.8	6.0	6.8	
FROZEN PRECIP	7.8		29.6	4.4	10.3	8.7	39.1	
FOG	10.5		22.9	5.5	40.1	11.7	9.2	
FOG WITH VIS GE 1/2 MILES	10.3		22.0	5.7	40.9	11.6	9.5	
TOTAL OBS	897	0	1225	250	1239	1328	2501	

MONTH: FEB HOURS: ALL

TSTMS				40.0	40.0		20.0	
LIQUID PRECIP	8.8		17.5	16.7	36.8	14.9	5.3	
FREEZING PRECIP	5.5		38.5	12.1	34.1	5.5	4.4	
FROZEN PRECIP	8.8		36.0	6.2	13.9	7.1	28.0	
FOG	11.6		22.6	10.6	36.2	13.2	5.7	
FOG WITH VIS GE 1/2 MILES	11.6		20.9	10.9	36.5	14.0	6.1	
TOTAL OBS	997	0	1545	395	1403	951	1511	

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: JAN HOURS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
26.3	6.3	52.5	5.0		80
53.8	6.8	24.8	6.0	6.8	117
29.6	4.4	10.3	8.7	39.1	3229
22.9	5.5	40.1	11.7	9.2	715
22.0	5.7	40.9	11.6	9.5	672
1225	250	1239	1328	2501	7440

MONTH: FEB HOURS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
40.0	40.0		20.0		5
17.5	16.7	36.8	14.9	5.3	114
38.5	12.1	34.1	5.5	4.4	91
36.0	6.2	13.9	7.1	28.0	2174
22.6	10.6	36.2	13.2	5.7	930
20.9	10.9	36.5	14.0	6.1	852
1545	395	1403	951	1511	6792

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

PHENOMENA	STATION NUMBER: 727435		STATION NAME: K. I. SAWYER AFB MI				PERIOD OF RECORD: AUG 78	
	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	
TSTMS			16.7		83.3			
LIQUID PRECIP	1.9		23.3	11.4	49.2	11.0	3.2	
FREEZING PRECIP	3.4		57.6	21.2	14.4	.8	2.5	
FROZEN PRECIP	2.8		58.3	5.1	11.1	2.2	20.5	
FOG	4.7		35.8	11.2	37.0	6.6	4.6	
FOG WITH VIS GE 1/2 MILES	4.3		37.2	10.5	35.6	7.2	5.2	
TOTAL OBS	790	0	2462	579	1645	674	1290	

PHENOMENA	STATION NUMBER: 727435		STATION NAME: K. I. SAWYER AFB MI				PERIOD OF RECORD: APR 78	
	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	
TSTMS	2.8		16.7	27.8	33.3	5.6	13.9	
LIQUID PRECIP	4.5		38.1	16.6	26.2	3.8	10.7	
FREEZING PRECIP			36.7		13.3			
FROZEN PRECIP	.5		60.7	5.3	4.1	2.7	26.7	
FOG	6.8		42.3	10.1	27.2	6.1	7.5	
FOG WITH VIS GE 1/2 MILES	4.9		43.2	12.1	25.6	5.6	8.6	
TOTAL OBS	748	0	2853	633	1346	560	1060	

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
16.7		83.3			6
23.3	11.4	49.2	11.0	3.2	317
57.6	21.2	14.4	.8	2.5	118
58.3	5.1	11.1	2.2	20.5	1953
35.8	11.2	37.0	6.6	4.6	1119
37.2	10.5	35.6	7.2	5.2	975
2462	579	1645	674	1290	7440

MONTH: APR HOURS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
16.7	27.8	33.3	5.6	13.9	36
38.1	16.6	26.2	3.8	10.7	625
96.7		13.3			15
60.7	5.3	4.1	2.7	26.7	786
42.3	10.1	27.2	6.1	7.5	897
43.2	12.1	25.6	5.6	8.6	730
2853	633	1346	560	1060	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAY HOURS: ALL

PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349
TSTMS			14.6	8.3	56.3	8.3	12.5
LIQUID PRECIP	4.5		40.1	13.7	25.2	6.7	9.8
FREEZING PRECIP							
FROZEN PRECIP			19.6	15.7	9.8	5.9	49.0
FOG	6.7		37.0	10.4	32.1	8.7	5.1
FOG WITH VIS GE 1/2 MILES	6.5		35.3	11.0	33.4	8.2	5.5
TOTAL OBS	1024	0	2647	533	1764	707	765

MONTH: JUN HOURS: ALL

TSTMS	4.9		16.4	10.7	32.8	25.4	9.8
LIQUID PRECIP	4.0		32.5	5.9	30.9	10.5	16.2
FREEZING PRECIP							
FROZEN PRECIP							
FOG	10.1		31.6	5.1	34.6	10.8	7.9
FOG WITH VIS GE 1/2 MILES	10.3		28.9	5.4	35.3	11.8	8.3
TOTAL OBS	837	0	2014	433	1739	1016	1161

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI		PERIOD OF RECORD: AUG 78 - JUL 88				
ST TO UTC: + 5		MONTH: MAY HOURS: ALL				
WIND DIRECTION	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
.....	14.6	8.3	56.3	8.3	12.5	48
.....	40.1	13.7	25.2	6.7	9.8	786
.....	19.6	15.7	9.8	5.9	49.0	51
.....	37.0	10.4	32.1	8.7	5.1	974
.....	35.3	11.0	33.4	8.2	5.5	901
.....	2647	533	1764	707	765	7440

MONTH: JUN HOURS: ALL

.....	16.4	10.7	32.8	25.4	9.8	122
.....	32.5	5.9	30.9	10.5	16.2	579
.....	31.6	5.1	34.6	10.8	7.9	573
.....	28.9	5.4	35.3	11.8	8.3	516
.....	2014	433	1739	1016	1161	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: JUL HOURS: ALL

PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349
TSTMS	2.9		22.3	12.2	29.8	22.3	11.5
LIQUID PRECIP	2.9		28.5	14.4	23.2	17.3	13.7
FREEZING PRECIP							
FROZEN PRECIP							
FOG	14.6		22.2	9.2	24.5	19.9	9.6
FOG WITH VIS GE 1/2 MILES	14.0		21.7	10.1	24.5	20.0	9.7
TOTAL OBS	1210	0	1897	500	1458	1448	922

					MONTH: AUG	HOURS: ALL
TSTMS	5.4		10.1	15.5	38.0	19.4
LIQUID PRECIP	5.0		24.5	10.7	34.9	12.8
FREEZING PRECIP						
FROZEN PRECIP			100.0			
FOG	12.3		22.2	7.9	33.1	19.1
FOG WITH VIS GE 1/2 MILES	10.9		20.5	7.6	35.5	19.7
TOTAL OBS	1041	0	1635	498	1607	1444

AVERAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME: + 5 MONTH: JUL HOURS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
22.3	12.2	28.8	22.3	11.5	139
28.5	14.4	23.2	17.3	13.7	410
22.2	9.2	24.5	19.9	9.6	803
21.7	10.1	24.5	20.0	9.7	734
1897	500	1458	1448	922	7435

MONTH: AUG HOURS: ALL

10.1	15.5	38.0	19.4	11.6	129
24.5	10.7	34.9	12.8	12.2	682
100.0					1
22.2	7.9	33.1	19.1	5.5	1363
20.5	7.6	35.5	19.7	5.8	1214
1685	498	1607	1444	1165	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 7
LST TO UTC: + 5 MONTH: SEP HOURS: ALL

PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349
TSTMS	6.3		25.3	20.0	22.1	22.1	4.2
LIQUID PRECIP	4.3		41.5	14.8	22.4	8.3	8.7
FREEZING PRECIP							
FROZEN PRECIP	33.3						66.7
FOG	9.3		29.9	9.1	34.9	14.2	2.7
FOG WITH VIS GE 1/2 MILES	8.9		29.1	10.1	35.3	13.8	2.8
TOTAL OBS	395	0	1686	523	1575	1375	1146

					MONTH: OCT	HOURS: ALL
TSTMS			54.5		36.4	9.1
LIQUID PRECIP	5.2		31.7	8.1	25.4	10.8
FREEZING PRECIP					100.0	
FROZEN PRECIP	3.9		42.6	4.1	5.1	5.8
FOG	10.7		24.3	7.9	39.6	12.6
FOG WITH VIS GE 1/2 MILES	9.9		24.0	8.2	40.7	11.9
TOTAL OBS	996	0	1337	399	1941	1266

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TO UTC: + 5 MONTH: SEP HOURS: ALL

WIND DIRECTION	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
	25.3	20.0	22.1	22.1	4.2	95
	41.5	14.8	22.4	8.3	8.7	1152

66.7 3

29.9 9.1 34.9 14.2 2.7 1543

29.1 10.1 35.3 13.8 2.8 1371

1686 523 1575 1375 1146 7200

MONTH: OCT HOURS: ALL

54.5 36.4 9.1 22

31.7 8.1 25.4 10.8 18.8 1112

100.0 1

42.6 4.1 5.1 5.8 38.5 413

24.3 7.9 39.6 12.6 5.0 1331

24.0 8.2 40.7 11.9 5.3 1211

1337 399 1941 1266 1501 7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435		STATION NAME: K. I. SAWYER AFB MI				PERIOD OF RECORD: AUG 78	
		LST TO UTC: + 5				MONTH: NOV	HOURS: ALL
PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349
TSTMS					33.3		66.7
LIQUID PRECIP	3.7		29.0	11.8	38.4	6.2	10.9
FREEZING PRECIP	31.3		18.8	28.1	3.1	6.3	12.5
FROZEN PRECIP	5.3		35.1	7.4	6.4	11.5	34.3
FOG	8.6		24.2	8.3	38.9	13.4	6.7
FOG WITH VIS GE 1/2 MILES	8.7		25.5	8.3	36.7	13.3	7.6
TOTAL OBS	719	0	1362	391	1527	1403	1798

						MONTH: DEC	HOURS: ALL
TSTMS							
LIQUID PRECIP	7.7		39.1	5.9	36.9	5.5	4.8
FREEZING PRECIP	7.0		16.0	10.0	35.0	12.0	20.0
FROZEN PRECIP	6.6		24.0	6.7	11.7	12.3	38.8
FOG	11.5		22.9	6.9	35.5	13.4	9.8
FOG WITH VIS GE 1/2 MILES	11.6		22.2	7.4	32.9	14.8	11.2
TOTAL OBS	724	0	1001	329	1379	1651	2356

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
 VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: NOV HOURS: ALL

WIND DIRECTION	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
			33.3		66.7	3
	29.0	11.8	38.4	6.2	10.9	677
	18.8	28.1	3.1	6.3	12.5	32
	35.1	7.4	6.4	11.5	34.3	1676
	24.2	8.3	38.9	13.4	6.7	1227
	25.5	8.3	36.7	13.3	7.6	1083
TOTAL	1362	391	1527	1403	1798	7200

MONTH: DEC HOURS: ALL

	39.1	5.9	36.9	5.5	4.8	271
	16.0	10.0	35.0	12.0	20.0	100
	24.0	6.7	11.7	12.3	38.8	2770
	22.9	6.9	35.5	13.4	9.8	1077
	22.2	7.4	32.9	14.8	11.2	925
TOTAL	1001	329	1379	1651	2356	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTHS: ALL

PHENOMENA	CALM	VARIABLE	350 - 059	060 - 149	150 - 209	210 - 269	270 - 349
TSTMS	4.0		18.8	14.0	33.9	19.2	10.1
LIQUID PRECIP	4.6		33.4	11.7	29.6	9.2	11.6
FREEZING PRECIP	5.9		42.4	13.3	24.5	5.7	8.2
FROZEN PRECIP	6.1		36.7	5.8	10.3	8.1	33.1
FOG	9.7		27.9	8.7	34.8	12.7	6.2
FOG WITH VIS GE 1/2 MILES	9.3		27.3	9.0	34.8	12.9	6.7
TOTAL OBS	10868	0	21714	5463	18623	13823	17176

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTHS: ALL

350 - 059	060 - 149	150 - 209	210 - 269	270 - 349	NO OF OBS
18.8	14.0	33.9	19.2	10.1	605
33.4	11.7	29.6	9.2	11.6	6805
42.4	13.3	24.5	5.7	8.2	474
36.7	5.8	10.3	8.1	33.1	13056
27.9	8.7	34.8	12.7	6.2	12552
27.3	9.0	34.8	12.9	6.7	11184
21714	5463	18623	13823	17176	87667

pppppppp	AAAAAA	RRRRRRRR	TTTTTTTTT	BBBBBBBBB
pppppppp	AAAAAAAA	RRRRRRRR	TTTTTTTTT	BBBBBBBBB
pp pp	AA AA	RR RR	TT	BB BB
pp pp	AA AA	RR RR	TT	BB BB
pppppppp	AA AA	RRRRRRRR	TT	BBBBBBBBB
pppppppp	AAAAAAAA	RRRRRRRR	TT	BBBBBBBBB
pp	AAAAAAAA	RR RR	TT	BB BB
pp	AA AA	RR RR	TT	BB BB
pp	AA AA	RR RR	TT	BBBBBBBBB
pp	AA AA	RR RR	TT	BBBBBBBBB

PART B

PRECIPITATION, SNOWFALL, SNOW DEPTH SUMMARIES

ALL TABLES IN PART B ARE CREATED FROM SUMMARY OF DAY (SOD) DATA.

PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY OF PRECIPITATION, SNOWFALL AND SNOW DEPTH. DATA IS SUMMARIZED FOR ALL YEARS COMBINED. SUMMARIES INCLUDE THE PERCENT OF DAYS WITH MEASURABLE AMOUNTS, PERCENT OF DAYS WITH NO AMOUNTS, PERCENT OF DAYS WITH TRACES, AND PERCENT OF DAYS WITH SPECIFIED AMOUNTS. SUMMARIES ALSO PROVIDE AN OBSERVATION COUNT. A VALUE OF ".0" INDICATES ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.

MONTHLY TOTALS.

THESE TABLES GIVE THE TOTAL MONTHLY PRECIPITATION AND SNOWFALL RESPECTIVELY. THEY ARE SUMMARIZED BY MONTH FOR ALL YEARS. THE TABLES ALSO GIVE THE GREATEST AMOUNTS, LEAST AMOUNTS, MEAN, MEDIAN, STANDARD DEVIATIONS, AND TOTAL AVAILABLE OBSERVATIONS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. NOTE: LEAST AMOUNTS ARE DERIVED FROM COMPLETE MONTHS (YEARS) ONLY. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO SNOWFALL FOR THE MONTH.

DAILY EXTREMES.

THESE TABLES GIVE THE MAXIMUM DAILY REPORTED AMOUNTS (BY INDIVIDUAL YEAR-MONTH) FOR PRECIPITATION, SNOWFALL, AND SNOW DEPTH, RESPECTIVELY. THEY SHOW THE GREATEST AMOUNTS FOR EACH MONTH AND THE TOTAL NUMBER OF AVAILABLE OBSERVATIONS FOR EACH MONTH AND YEAR. AN ASTERISK (*) INDICATES A MONTH FOR WHICH LESS THAN 90% OF DATA ARE AVAILABLE. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO SNOWFALL FOR THE MONTH, AND "0" MEANS NO SNOW DEPTH FOR THE MONTH.

SNOWFALL/SNOW DEPTH--FIRST AND LAST DAYS OF OCCURRENCE BY SNOW YEAR.

THIS SUMMARY GIVES THE FIRST AND LAST OCCURRENCES OF SNOWFALL AND SNOW DEPTH FOR THE SNOW-YEAR DURING THE PERIOD OF RECORD. FOR THIS SUMMARY, THE SNOW-YEAR IS CONSIDERED TO RUN FROM 1 AUGUST TO 31 JULY. TABLES SUMMARIZE THE DATA BY SNOW-YEAR, BY MONTH, AND BY DAY. THE FIRST (OR LAST) ENTRY IN COLUMN 69 OF AWS FORMS 10/10A (OR EQUIVALENT) AS EITHER A TRACE OR A MEASURABLE AMOUNT DEFINES THE FIRST (OR LAST) SNOWFALL FOR THE YEAR. THE FIRST (OR LAST) ENTRY IN COLUMN 69 OTHER THAN ".0" OR "TRACE" DEFINES THE FIRST (OR LAST) MEASURABLE SNOWFALL. FINALLY, THE 1200 GMT ENTRY COLUMN 70 OF AWS FORM 10/10A (OR EQUIVALENT) DEFINES THE FIRST (OR LAST) OCCURRENCE OF SNOW DEPTH. THE LAST SNOW DEPTH IS CONSIDERED THE LAST SNOW MELT. THIS SUMMARY IS NOT PROVIDED WHEN NO SNOWFALL OCCURS DURING THE GIVEN PER.

NOTE 1. IF THE MINIMUM AMOUNT RECORDED IN THE MONTHLY TOTALS OR DAILY EXTREMES IS A TRACE, THE WORD "TRACE" WILL APPEAR IN THE APPROPRIATE COLUMN.

NOTE 2. TABLES INCLUDE STATISTICAL DATA ONLY WHEN 10 SETS OF MONTHLY DATA, OR MORE, ARE AVAILABLE.

NOTE 3. THE OBSERVATION COUNTS OR THE STATION HISTORY MIGHT PROVIDE CLUES AS TO WHY CERTAIN DATA ARE MISSING. FOR EXAMPLE, ONLY A FEW MISSING OBSERVATIONS MIGHT IMPLY MISSING DATA BECAUSE OF EQUIPMENT MALFUNCTION, BUT MORE THAN SEVERAL MISSING OBSERVATIONS USUALLY MEANS THE STATION IS (OR HAS BEEN) CLOSED.

NOTE 4. IN DAILY AND MONTHLY AMOUNTS SUMMARIES, THE LAST ENTRY ON THE PAGE GIVES THE GREATEST AMOUNT FOR THE PERIOD OF RECORD.

NOTE 5. BEFORE JANUARY 1956, SNOWFALL OCCURRENCES IN THE SUMMARY OF DAY INCLUDED HAIL.

NOTE 6. SNOW DEPTH REPORTING TIMES FOR USAF, NAVY AND CIVIL STATIONS ARE AS FOLLOWS:

AIR FORCE		NAVY AND NATIONAL WEATHER SERVICE	
THROUGH 1945:	0800 LST	THROUGH JUN 1952:	0030 GMT
JAN 1946 TO MAY 1957:	1230 LST	JUN 1952 TO MAY 1957:	1230 GMT
JUN 1957 TO PRESENT:	1200 GMT	JUN 1957 TO PRESENT:	1200 GMT

CONVERSIONS:

- 1 INCH = 25.39998 MILLIMETERS

- 1 MILLIMETER = .03937 INCHES

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF PRECIPITATION IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 57
MONTH: ALL HOURS:

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	
NONE	17.7	23.2	32.3	44.0	47.5	44.5	52.0	44.8	37.3	36.9	2
TRACE	27.8	27.0	26.0	17.8	15.0	15.9	15.6	19.2	18.6	20.1	2
.01	9.3	7.3	5.7	2.3	3.5	3.2	2.6	3.0	4.0	4.5	
.02-.05	16.8	16.6	12.3	8.8	8.5	8.7	5.9	8.4	10.2	10.4	1
.06-.10	9.2	9.6	7.2	5.8	4.7	5.1	3.9	3.4	4.8	6.0	
.11-.25	12.0	8.6	8.0	10.2	9.4	8.9	6.5	7.7	8.9	11.4	10
.26-.50	5.5	4.5	4.5	6.3	5.5	7.6	6.7	6.3	7.1	5.7	
.51-1.00	1.2	2.2	2.7	3.7	4.4	4.2	4.6	4.5	6.2	2.9	
1.01-2.50	.4	.5	1.3	1.1	1.6	1.7	2.2	2.4	2.9	1.8	
2.51-5.00						.1	.1	.1		.1	
5.01-10.00											
10.01-20.00											
OVER 20.00											
DAYS WITH MEAS AMTS	54.6	49.3	41.7	38.2	37.6	39.6	32.4	35.9	44.1	42.9	47
TOTAL NO. OF OBSERVATIONS	911	848	930	916	961	930	961	930	900	929	9

PERCENTAGE FREQUENCY OF OCCURRENCE OF PRECIPITATION IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
MONTH: ALL HOURS: ALL

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
32.3	44.0	47.5	44.5	52.0	44.8	37.3	36.9	27.8	17.1	35.7
26.0	17.8	15.0	15.9	15.6	19.2	18.6	20.1	24.8	28.9	21.3
5.7	2.3	3.5	3.2	2.6	3.0	4.0	4.5	6.0	7.7	4.9
12.3	8.8	8.5	8.7	5.9	8.4	10.2	10.4	12.4	16.6	11.2
7.2	5.8	4.7	5.1	3.9	3.4	4.8	6.0	8.8	8.6	6.4
8.0	10.2	9.4	8.9	6.5	7.7	8.9	11.4	10.0	10.4	9.3
4.5	6.3	5.5	7.6	6.7	6.3	7.1	5.7	5.2	7.6	6.1
2.7	3.7	4.4	4.2	4.6	4.5	6.2	2.9	3.7	2.6	3.6
1.3	1.1	1.6	1.7	2.2	2.4	2.9	1.8	1.2	.5	1.5
			.1	.1	.1		.1	.1		.0

41.7	39.2	37.6	39.6	32.4	35.9	44.1	42.9	47.4	54.0	43.0
930	916	961	930	961	930	900	929	900	911	11027

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD:
MONTH: ALL HOUR:

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
57	.37*	.86	.62	1.73	3.11	1.38	1.81	2.35	5.17	1.46	6.1	2.9
58				.75*	1.29	2.18	4.63	3.05	2.03	1.09	2.3	2.9
59												2.3
60	1.38	2.18	2.08	5.12	5.48	5.01	3.91	3.67	5.05	2.69	2.3	2.9
61	1.05	1.76	2.63	3.44	3.14	4.09	2.52	3.16	4.97	2.02	2.4	2.4
62	2.71	3.45	1.29	1.80	2.83	1.70	1.12	4.34	4.64	2.16	1.3	1.3
63	1.90	1.50	1.46	2.47	1.70	3.85	2.61	2.20	2.64	.91	3.6	3.6
64	1.75	2.45	2.60	2.41	3.36	1.98	3.94	4.90	4.49	1.27	2.4	2.4
65	1.17	1.96	2.52	1.55	4.35	.93	1.95	2.43	3.94	1.07	3.1	3.1
66	1.33	.88	3.48	1.51	1.88	4.10	1.06	6.03	2.07	3.16	3.9	3.9
67	4.19	2.31	1.77	2.58	2.46	6.37	2.88	3.34	1.31	6.10	1.6	1.6
68	1.27	2.32	.99	2.92	3.06	9.29	2.81	2.42	5.19	3.07	1.2	1.2
69	3.26	1.65	3.25	3.24	2.62	4.26	2.45	.34	2.65	4.72	1.1	1.1
70	1.39	.82	1.26	1.42	5.21	.49	9.00	.56	4.25	3.81	2.5	2.5
71	4.96	2.97	2.62	.65	1.82	2.63	2.76	1.29	3.39	5.30	3.1	3.1
72	1.11	1.14	2.38	2.81	1.85	1.09	3.62	4.23	3.86	2.10	2.7	2.7
73	1.08	3.31	2.63	4.65	6.87	3.76	4.09	4.66	3.34	4.05	1.2	1.2
74	.81	1.85	1.14	2.86	2.20	3.93	2.12	4.25	3.74	2.05	2.8	2.8
75	3.09	1.74	2.77	2.64	3.01	5.57	3.59	4.92	3.57	1.11	4.0	4.0
76	1.74	1.21	4.13	2.31	3.92	3.60	1.43	1.44	1.23	1.53	.9	.9
77	1.48	1.45	4.21	4.31	1.96	3.65	4.76	5.88	6.70	2.68	3.2	3.2
78	2.68	1.37	.81	2.34	3.67	2.93	8.31	4.22	5.88	2.16	2.4	2.4
79	2.49	1.22	4.81	2.53	3.01	6.12	6.44	2.83	1.69	5.50	2.0	2.0
80	2.72	1.68	.48	2.95	2.33	2.01	2.64	2.71	5.79	.98	1.3	1.3
81	1.18	1.91	1.26	2.15	2.55	4.90	1.35	3.98	2.98	3.05	1.0	1.0
82	3.24	.31	1.31	2.63	2.83	1.29	5.13	3.52	7.66	3.20	2.1	2.1
83	1.95	1.31	3.19	2.53	6.29	3.05	2.55	3.77	5.38	7.14	3.8	3.8
84	1.02	2.96	2.13	3.14	1.01	4.89	2.75	7.82	4.48	3.04	3.0	3.0
85	2.04	3.29	3.39	5.99	3.95	1.34	3.13	4.29	5.99	3.88	7.0	7.0
86	2.82	1.47	3.47	2.47	.10	1.61	2.81	3.98	3.48	3.62	1.4	1.4
87	1.15	1.48	.93	2.15	2.88	1.71	4.59	3.16	3.02	3.58	3.8	3.8
88	3.09	1.19	4.10	1.13	1.06	.63	3.11					

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
.62	1.73	3.11	1.38	1.81	2.35	5.17	1.46	6.16	.87*	25.89*	
	.75*	1.29	2.13	4.63	3.05	2.03	1.09			15.02*	
.08	5.12	5.48	5.01	3.91	3.67	5.05	2.69	2.95	1.96	4.91*	
								2.35	1.56	40.48	
.65	3.44	3.14	4.09	2.52	3.16	4.97	2.02	2.45	2.56	33.79	
.29	1.80	2.83	1.70	1.12	4.34	4.64	2.16	1.30	2.92	30.26	
.45	2.47	1.70	3.85	2.61	2.20	2.64	.91	3.65	3.06	27.95	
.10	2.41	3.36	1.98	3.94	4.90	4.49	1.27	2.45	2.42	34.02	
.52	1.55	4.35	.93	1.95	2.43	3.94	1.07	3.10	2.13	27.10	
.48	1.51	1.88	4.10	1.06	6.03	2.07	3.16	3.97	2.00	31.47	
.77	2.58	2.46	6.37	2.88	3.34	1.31	6.10	1.66	.72	35.69	
.39	2.92	3.06	9.29	2.81	2.42	5.19	3.07	1.24	5.83	40.41	
.32	3.24	2.62	4.26	2.45	.34	2.65	4.72	1.18	3.10	32.72	
.75	1.42	5.21	.49	9.00	.56	4.25	3.81	2.58	2.37	33.16	
.62	.65	1.82	2.63	2.76	1.29	3.39	5.30	3.16	2.35	33.80	
.33	2.81	1.85	1.09	3.62	4.23	3.86	2.10	2.78	4.41	31.38	
.63	4.65	6.87	3.76	4.09	4.66	3.34	4.05	1.28	2.97	42.69	
.14	2.86	2.20	3.93	2.12	4.25	3.74	2.05	2.83	1.20	28.98	
.77	2.64	3.01	5.57	3.59	4.92	3.57	1.11	4.05	1.78	37.84	
.17	3.31	3.92	3.60	1.43	1.44	1.23	1.53	.98	1.79	25.41	
.21	4.31	1.96	3.65	4.76	5.88	6.70	2.68	3.29	3.95	44.32	
.21	2.34	3.67	2.93	8.31	4.22	5.88	2.16	2.46	1.26	38.09	
.01	2.53	3.01	6.12	6.44	2.83	1.69	5.50	2.04	1.37	40.05	
.45	2.95	2.33	2.01	2.64	2.71	5.79	.98	1.30	1.87	27.46	
.28	2.15	2.55	4.90	1.35	3.98	2.98	3.05	1.04	3.52	29.87	
.21	2.63	2.33	1.29	5.13	3.52	7.66	3.20	2.17	3.00	36.29	
.17	2.53	6.29	3.05	2.55	3.77	5.38	7.14	3.85	2.06	43.07	
.13	3.14	1.01	4.89	2.75	7.82	4.48	3.04	3.05	2.52	38.86	
.10	5.99	3.95	1.34	3.13	4.29	5.99	3.88	7.04	3.28	47.61	
.47	2.47	.10	1.61	2.91	3.98	3.48	3.62	1.40	.88	28.11	
.25	2.15	2.88	1.71	4.59	3.16	3.02	3.58	3.85	3.67	32.22	
.10	1.13	1.06	.63	3.11						14.31*	

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 570
MONTH: ALL HOURS: A

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV
.....

.....

LEAST	.81	.31	.43	.65	.10	.49	1.06	.34	1.23	.91	.98
GREATEST	4.96	3.45	4.81	5.99	6.87	9.29	9.00	7.82	7.66	7.14	7.04
MEAN	2.07	1.80	2.33	2.68	2.96	3.24	3.42	3.52	4.02	2.95	2.72
MEDIAN	1.75	1.67	2.45	2.53	2.83	3.05	2.81	3.60	3.90	2.87	2.52
SD	1.043	.791	1.195	1.148	1.512	2.000	1.862	1.599	1.597	1.616	1.422
TOTAL OBS	911	848	930	916	961	930	961	930	900	929	900

.....

THE GREATEST VALUE OF 9.29 OCCURRED ON 06/68

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MI

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

.....
MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL
.....

.43	.65	.10	.49	1.06	.34	1.23	.91	.98	.72	25.41
4.41	5.99	6.87	9.29	9.00	7.82	7.66	7.14	7.04	5.83	47.61
2.33	2.68	2.96	3.24	3.42	3.52	4.02	2.95	2.72	2.50	34.75
2.45	2.53	2.83	3.05	2.81	3.60	3.90	2.87	2.52	2.37	33.80
1.195	1.148	1.512	2.000	1.862	1.599	1.597	1.616	1.422	1.113	5.860
930	916	961	930	961	930	900	929	900	911	11027

.....
ONE OF 9.29 OCCURRED ON 06/68

.....
IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 570
LST TO UTC: +05 MONTH: ALL HOURS: A

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
57	.13*	.20	.16	.38	1.17	.40	.84	1.10	1.59	.38	2.56
58				.20*	.28	.54	.88	.97	1.01	.18	
59											.90
60	.24	.55	.72	1.45	1.25	1.84	1.93	2.35	1.63	1.52	.77
61	.28	.68	1.10	1.53	1.03	2.29	.97	1.54	1.44	.81	1.02
62	.50	.88	.68	.48	1.01	.72	.82	1.13	1.21	.52	.34
63	.57	.19	.67	.79	.40	.95	.78	.85	1.02	.27	.90
64	.68	.47	1.05	.38	.96	.55	1.13	.95	.96	.68	.73
65	.31	1.17	1.09	.31	1.30	.20	1.01	.54	.66	.25	.62
66	.43	.38	.52	.26	.74	1.32	.39	1.24	1.09	1.93	1.52
67	1.32	.45	.76	.86	.76	1.46	.87	.75	.36	1.56	.52
68	.39	.51	.29	.45	.84	1.97	.56	.87	1.32	.92	.30
69	.70	.67	1.80	.72	.62	.69	.58	.26	1.00	1.37	.54
70	.26	.21	.47	.89	2.18	.15	1.92	.36	1.00	1.75	.65
71	1.76	.95	1.39	.45	.68	.51	1.52	.39	1.38	1.27	.66
72	.32	.28	.45	1.22	.83	.60	.92	1.64	1.11	.52	1.26
73	.26	1.05	1.09	1.15	2.14	.63	.88	1.24	1.47	1.13	.45
74	.18	.49	.47	.87	.55	.99	.93	1.52	1.54	.61	.97
75	.83	.63	1.24	.98	.60	.97	1.29	2.00	.76	.43	.68
76	.22	.51	1.06	.75	2.34	1.20	.49	.90	.46	.33	.32
77	.36	.41	1.42	1.12	1.18	1.37	1.99	2.74	2.31	.97	.76
78	.33	.53	.16	.64	1.29	1.47	3.29	1.36	2.15	1.06	1.28
79	.85	.26	1.48	.75	1.31	1.81	2.02	.83	.71	1.28	.64
80	.51	.32	.25	1.03	1.01	.69	.56	1.05	1.33	.17	.66
81	.30	.44	.21	1.19	.79	1.32	.40	2.39	.94	1.11	.36
82	1.38	.12	.23	.88	.71	.44	1.90	1.40	1.89	.89	1.17
83	.37	.60	.84	1.02	2.39	.51	1.10	1.76	1.70	2.71	1.47
84	.17	1.31	.74	1.58	.30	2.63	.87	2.24	1.21	1.18	1.06
85	.40	1.44	.93	2.20	.91	.34	1.27	.98	1.32	1.54	2.08
86	.52	.55	.97	.64	.06	.45	.72	.94	.45	1.16	.38
87	.21	.55	.31	.85	.74	.43	1.51	1.62	.77	.91	1.36
88	1.56	.39	.81	.27	.34	.29	1.47				

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
.16	.38	1.17	.40	.84	1.10	1.59	.38	2.56	.33*	2.56*
	.20*	.28	.54	.88	.97	1.01	.18			1.01*
.72	1.45	1.25	1.84	1.93	2.35	1.63	1.52	.90	.57	.90*
								.77	.34	2.35
1.10	1.53	1.03	2.29	.97	1.54	1.44	.81	1.02	.89	2.29
.58	.48	1.01	.72	.82	1.13	1.21	.52	.34	.57	1.21
.67	.79	.40	.95	.78	.85	1.02	.27	.90	.66	1.02
1.05	.38	.96	.55	1.13	.95	.96	.68	.73	.40	1.13
1.09	.31	1.30	.20	1.01	.54	.66	.25	.62	.57	1.30
.52	.26	.74	1.32	.39	1.24	1.09	1.93	1.52	.34	1.93
.76	.86	.76	1.46	.87	.75	.36	1.56	.52	.16	1.56
.29	.45	.84	1.97	.56	.87	1.32	.92	.30	.65	1.97
1.40	.72	.62	.69	.58	.26	1.00	1.37	.54	.63	1.80
.47	.89	2.18	.15	1.92	.36	1.00	1.75	.65	.42	2.18
1.39	.45	.68	.51	1.52	.39	1.38	1.27	.66	.65	1.76
.45	1.22	.83	.60	.92	1.64	1.11	.52	1.26	1.70	1.70
1.09	1.15	2.14	.63	.88	1.24	1.47	1.13	.45	.54	2.14
.47	.87	.55	.99	.93	1.52	1.54	.61	.97	.40	1.54
1.24	.98	.60	.97	1.29	2.00	.76	.43	.68	1.18	2.00
1.06	.75	2.34	1.20	.49	.90	.46	.33	.32	.59	2.34
1.42	1.12	1.18	1.37	1.89	2.74	2.31	.97	.76	.78	2.74
.16	.64	1.29	1.47	3.29	1.36	2.15	1.06	1.28	.37	3.29
1.48	.75	1.31	1.81	2.02	.83	.71	1.28	.64	.31	2.02
.25	1.03	1.01	.69	.56	1.05	1.33	.17	.66	.35	1.33
.21	1.19	.79	1.32	.40	2.39	.94	1.11	.36	1.14	2.39
.23	.88	.71	.44	1.90	1.40	1.89	.89	1.17	.74	1.90
.84	1.02	2.39	.51	1.10	1.76	1.70	2.71	1.47	.45	2.71
.74	1.58	.30	2.63	.87	2.24	1.21	1.18	1.06	.47	2.63
.94	2.20	.91	.34	1.27	.98	1.32	1.54	2.08	1.10	2.20
.97	.64	.06	.45	.72	.94	.45	1.16	.38	.33	1.16
.31	.85	.74	.43	1.51	1.62	.77	.91	1.36	1.03	1.62
.81	.27	.34	.29	1.47						1.56*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 1
LST TO UTC: +05 MONTH: ALL HOURS: 24

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV

.....
GREATEST 1.76 1.44 1.80 2.20 3.39 2.63 3.29 2.74 2.31 2.71 2.50
.....
TOTAL DRS 911 849 930 916 961 930 961 930 900 929 900
.....

THE GREATEST VALUE OF 3.29 OCCURRED ON 07/19/78

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
TIME ZONE: +05 MONTH: ALL HOURS: ALL

.....
MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL
.....

.....
90 2.20 2.39 2.63 3.29 2.74 2.31 2.71 2.56 1.70 3.29
.....
930 916 961 930 961 930 900 929 900 911 11027
.....

OF 3.29 OCCURRED ON 07/19/78

BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOWFALL IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD
MONTH: ALL HOURLY

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
NONE	20.0	24.6	41.2	68.0	91.7	99.7	99.9	99.8	97.1	77.6
TRACE	26.0	27.2	24.8	14.2	5.0	.3	.1	.2	2.7	14.2
0.1-0.4	18.0	15.4	10.0	7.0	1.5				.1	2.7
0.5-1.4	17.5	15.8	11.5	5.9	1.0					3.3
1.5-2.4	5.8	6.7	3.9	1.6	.7					.8
2.5-3.4	4.3	2.9	2.3	1.1	.1				.1	.5
3.5-4.4	2.9	3.1	1.3	.9						.6
4.5-6.4	2.9	1.1	1.6	.7						.2
6.5-10.4	2.1	2.2	2.3	.7						
10.5-15.4	.3	.7	.9							
15.5-25.4	.3	.1	.3							
25.5-50.4										
OVER 50.4										
DAYS WITH MEAS AMTS	54.0	48.1	34.0	17.8	3.3				.2	8.2
TOTAL NO. OF OBSERVATIONS	911	848	930	916	961	930	961	930	900	950

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOWFALL IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712, 5804-5810, 5910-8807
LST TO UTC: +05 MONTH: ALL HOURS: ALL

FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
24.5	41.2	68.0	91.7	99.7	99.9	99.8	97.1	77.6	41.8	21.4	65.8
7.2	24.8	14.2	5.0	.3	.1	.2	2.7	14.2	24.8	27.6	13.7
15.4	10.0	7.0	1.5				.1	2.7	10.2	15.9	6.6
15.8	11.5	5.9	1.0					3.3	11.8	14.9	6.7
9.7	3.9	1.6	.7					.8	4.6	7.1	2.6
2.9	2.3	1.1	.1				.1	.5	1.8	4.2	1.4
3.1	1.3	.9						.6	1.3	2.5	1.0
1.1	1.6	.7						.2	2.0	2.6	.9
2.2	2.3	.7							1.6	2.6	.9
.7	.9								.2	1.0	.3
.1	.3									.1	.1
7.1	34.0	17.8	3.3				.2	8.2	33.4	51.0	20.4
449	930	916	961	930	961	930	900	950	900	911	11048

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD
MONTH: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
57	3.3*	9.1	5.4	12.0	TRACE	.0	.0	.0	.0	TRACE
58				.6*	.4	.0	.0	.0	TRACE	.2
59										TRACE*
60	21.5	40.1	30.6	11.0	4.9	TRACE	.0	.0	TRACE	2.0
61	13.9	21.5	24.2	3.8	1.8	.0	.0	.0	TRACE	TRACE
62	28.6	34.3	10.8	1.8	1.4	.0	.0	.0	TRACE	9.1
63	18.4	14.7	13.7	2.3	2.0	.0	.0	.0	.0	TRACE
64	14.0	26.6	25.1	4.1	.0	.0	.0	.0	.0	3.2
65	12.5	18.9	28.1	3.6	TRACE	.0	.0	.0	TRACE	2.1
66	12.6	6.8	27.7	9.8	1.0	.0	.0	.0	TRACE	.6
67	37.5	23.8	14.4	2.4	3.8	.0	TRACE	.0	TRACE	10.8
68	16.1	30.3	3.7	3.3	TRACE	.0	.0	.0	TRACE	5.6
69	44.3	29.4	37.5	.4	TRACE	TRACE	.0	.0	.0	6.5
70	40.6	20.2	17.2	.9	2.2	.0	.0	.0	TRACE	TRACE
71	92.8	34.0	26.3	2.6	1.0	.0	.0	.0	.0	.0
72	17.0	22.5	37.2	17.1	.0	.0	.0	.0	.0	2.3
73	13.9	31.1	.2	11.6	3.9	.0	.0	.0	TRACE	TRACE
74	9.9	31.1	8.1	17.1	2.3	.0	.0	.0	3.4	8.7
75	36.4	28.3	44.6	1.0	.0	.0	.0	.0	TRACE	TRACE
76	36.4	16.7	40.2	1.3	1.2	.0	.0	.0	TRACE	14.8
77	20.1	12.7	17.4	15.8	TRACE	.0	.0	.0	.0	TRACE
78	48.6	25.5	14.0	3.0	.0	.0	.0	.0	.0	2.1
79	42.4	21.1	29.0	16.0	1.5	.0	.0	.0	.0	11.3
80	23.9	20.4	4.5	3.1	TRACE	.0	.0	.0	TRACE	3.0
81	31.0	22.8	19.1	1.7	.2	TRACE	.0	.0	.0	6.8
82	40.8	4.9	16.6	20.0	.0	.0	.0	.0	.0	3.4
83	31.0	30.1	37.4	14.6	TRACE	.0	.0	.0	TRACE	TRACE
84	19.2	26.6	24.0	.2	TRACE	.0	.0	.0	TRACE	.1
85	49.5	48.1	45.6	25.6	.0	.0	.0	.0	TRACE	TRACE
86	47.4	22.3	34.9	3.9	.1	.0	.0	TRACE	TRACE	.8
87	16.6	20.4	10.2	13.9	.0	.0	.0	.0	.0	3.0
88	49.9	20.1	38.2	3.1	.0	.0	.0			

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712,5804-5810,5910-8807
TC: +05 MONTH: ALL HOURS: ALL

APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
12.0	TRACE	.0	.0	.0	.0	TRACE	26.8	11.3*	67.9*
.5*	.4	.0	.0	.0	TRACE	.2			1.2*
						TRACE*	29.2	17.6	46.8*
11.0	4.9	TRACE	.0	.0	TRACE	2.0	11.5	15.9	137.5
3.8	1.8	.0	.0	.0	TRACE	TRACE	12.5	29.1	106.8
1.8	1.4	.0	.0	.0	TRACE	9.1	9.9	24.3	120.2
2.3	2.0	.0	.0	.0	.0	TRACE	19.7	27.0	97.8
4.1	.0	.0	.0	.0	.0	3.2	7.0	30.5	110.5
3.6	TRACE	.0	.0	.0	TRACE	2.1	15.0	10.8	91.0
9.8	1.0	.0	.0	.0	TRACE	.6	40.6	29.7	128.8
2.4	3.8	.0	TRACE	.0	TRACE	10.8	22.4	8.3	123.4
3.3	TRACE	.0	.0	.0	TRACE	5.6	20.7	70.9	150.6
.4	TRACE	TRACE	.0	.0	.0	6.5	7.0	55.4	180.5
.7	2.2	.0	.0	.0	TRACE	TRACE	15.0	49.5	145.6
2.5	1.0	.0	.0	.0	.0	.0	28.6	22.9	208.2
17.1	.0	.0	.0	.0	.0	2.3	8.1	36.1	140.3
11.6	3.9	.0	.0	.0	TRACE	TRACE	10.4	54.5	125.6
17.1	2.3	.0	.0	.0	3.4	8.7	16.3	16.9	113.8
1.0	.0	.0	.0	.0	TRACE	TRACE	37.2	12.8	160.3
1.3	1.2	.0	.0	.0	TRACE	14.8	17.1	24.1	151.8
15.8	TRACE	.0	.0	.0	.0	TRACE	18.3	64.1	148.4
3.0	.0	.0	.0	.0	.0	2.1	14.9	29.2	137.3
15.0	1.5	.0	.0	.0	.0	11.3	15.6	14.2	151.1
3.1	TRACE	.0	.0	.0	TRACE	3.0	7.1	28.8	90.8
1.7	.2	TRACE	.0	.0	.0	6.8	7.7	61.3	150.6
20.0	.0	.0	.0	.0	.0	3.4	5.1	9.0	99.8
14.5	TRACE	.0	.0	.0	TRACE	TRACE	11.4	31.7	156.2
.2	TRACE	.0	.0	.0	TRACE	.1	17.3	23.2	110.6
25.6	.0	.0	.0	.0	TRACE	TRACE	25.1	54.5	248.4
3.9	.1	.0	.0	TRACE	TRACE	.8	11.3	10.6	131.3
13.9	.0	.0	.0	.0	.0	3.0	16.3	38.1	118.5
3.1	.0	.0	.0						111.3*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 5
MONTH: ALL HOURS:

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV
.....

.....

LEAST	9.9	4.9	.2	.2	.0	.0	.0	.0	.0	.0	5.
GREATEST	92.8	48.1	45.6	25.6	4.9	TRACE	TRACE	TRACE	3.4	14.8	40.
MEAN	30.6	23.8	22.9	7.6	.9	TRACE	TRACE	TRACE	.1	3.2	16.
MEDIAN	28.6	22.7	24.1	3.7	TRACE	.0	.0	.0	TRACE	2.1	15.
SD	17.805	9.357	12.953	7.086	1.343	.000	.000	.000	.621	4.114	8.88
TOTAL OBS	911	848	930	916	961	930	961	930	900	950	90

.....

THE GREATEST VALUE OF 92.8 OCCURRED ON 01/71

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR TH

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5910-8807
MONTH: ALL HOURS: ALL

	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
	.2	.2	.0	.0	.0	.0	.0	.0	5.1	8.3	90.8
	45.6	25.6	4.9	TRACE	TRACE	TRACE	3.4	14.8	40.6	70.9	248.4
	22.9	7.6	.9	TRACE	TRACE	TRACE	.1	3.2	16.8	31.1	137.0
	24.1	3.7	TRACE	.0	.0	.0	TRACE	2.1	15.3	28.8	134.3
	2.953	7.086	1.343	.000	.000	.000	.621	4.114	8.887	17.945	34.612
	930	916	961	930	961	930	900	950	900	911	11048

92.8 OCCURRED ON 01/71

IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER:	STATION NAME: K. I. SAWYER AFB MI										PERIOD OF RECORD
	LST TO UTC: +05										MONTH: ALL
YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	HO
57	1.3*	2.2	1.5	3.8	TRACE	.0	.0	.0	.0	TRACE	
58				.5*	.2	.0	.0	.0	TRACE	.2	
59										TRACE*	
60	5.8	9.3	13.0	4.2	1.7	TRACE	.0	.0	TRACE	1.1	
61	3.9	11.1	11.0	3.1	.9	.0	.0	.0	TRACE	TRACE	
62	5.0	8.8	6.3	.8	1.4	.0	.0	.0	TRACE	3.9	
63	5.7	1.8	6.7	1.3	1.4	.0	.0	.0	.0	TRACE	
64	6.4	5.1	8.7	1.7	.0	.0	.0	.0	.0	1.3	
65	2.9	12.7	8.3	2.5	TRACE	.0	.0	.0	TRACE	1.7	
66	5.6	3.3	6.3	2.7	.4	.0	.0	.0	TRACE	.4	
67	11.0	5.2	6.7	.7	1.8	.0	TRACE	.0	TRACE	4.8	
68	4.2	6.6	1.4	1.3	TRACE	.0	.0	.0	TRACE	2.6	
69	14.5	11.5	21.0	.2	TRACE	TRACE	.0	.0	.0	4.1	
70	9.0	3.9	7.5	.6	2.2	.0	.0	.0	TRACE	TRACE	
71	23.8	9.6	9.4	1.9	1.0	.0	.0	.0	.0	.0	
72	4.1	6.5	10.3	5.4	.0	.0	.0	.0	.0	1.2	
73	4.5	10.5	.2	4.1	3.0	.0	.0	.0	TRACE	TRACE	
74	3.4	7.1	1.6	6.7	2.3	.0	.0	.0	3.0	4.4	
75	8.6	8.1	17.2	1.0	.0	.0	.0	.0	TRACE	TRACE	
76	5.0	4.3	13.6	1.3	1.1	.0	.0	.0	TRACE	3.5	
77	4.3	3.5	6.7	5.9	TRACE	.0	.0	.0	.0	TRACE	
78	10.3	6.5	3.0	1.7	.0	.0	.0	.0	.0	1.0	
79	8.3	4.4	10.1	5.4	1.5	.0	.0	.0	.0	5.1	
80	4.9	3.2	2.6	1.1	TRACE	.0	.0	.0	TRACE	1.2	
81	7.7	6.4	3.0	.6	.2	TRACE	.0	.0	.0	4.4	
82	17.1	1.8	2.5	9.3	.0	.0	.0	.0	.0	2.5	
83	7.4	15.2	13.7	4.0	TRACE	.0	.0	.0	TRACE	TRACE	
84	4.7	11.5	8.1	.2	TRACE	.0	.0	.0	TRACE	.1	
85	10.1	17.9	19.8	8.1	.0	.0	.0	.0	TRACE	TRACE	
86	10.2	8.4	11.8	2.3	.1	.0	.0	TRACE	TRACE	.7	
87	2.7	10.4	4.5	9.9	.0	.0	.0	.0	.0	1.1	
88	19.6	6.6	12.0	1.5	.0	.0	.0				

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME UTC: +05

PERIOD OF RECORD: 5701-5712, 5804-5810, 5910-8807
MONTH: ALL HOURS: ALL

	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
1.5	3.8	TRACE	.0	.0	.0	.0	.0	TRACE	10.8	4.7*	10.8*
	.6*	.2	.0	.0	.0	.0	TRACE	.2			.6*
13.0	4.2	1.7	TRACE	.0	.0	.0	TRACE	1.1	3.9	3.4	13.0
11.0	3.1	.9	.0	.0	.0	.0	TRACE	TRACE	7.0	9.5	11.1
5.3	.8	1.4	.0	.0	.0	.0	TRACE	3.9	3.4	4.8	8.8
5.7	1.3	1.4	.0	.0	.0	.0	.0	TRACE	6.6	7.0	7.0
8.7	1.7	.0	.0	.0	.0	.0	.0	1.3	3.0	7.8	8.7
5.3	2.5	TRACE	.0	.0	.0	.0	TRACE	1.7	3.8	3.6	12.7
5.3	2.7	.4	.0	.0	.0	.0	TRACE	.4	11.8	8.0	11.8
5.7	.7	1.8	.0	TRACE	.0	.0	TRACE	4.8	7.5	2.3	11.0
1.4	1.3	TRACE	.0	.0	.0	.0	TRACE	2.6	8.2	13.0	13.0
21.0	.2	TRACE	TRACE	.0	.0	.0	.0	4.1	3.0	7.7	21.0
7.5	.5	2.2	.0	.0	.0	.0	TRACE	TRACE	7.3	11.0	11.0
9.4	1.9	1.0	.0	.0	.0	.0	.0	.0	7.6	6.4	23.8
10.3	5.4	.0	.0	.0	.0	.0	.0	1.2	2.0	7.1	10.8
.2	4.1	3.0	.0	.0	.0	.0	TRACE	TRACE	4.6	8.7	10.5
1.5	5.7	2.3	.0	.0	.0	.0	3.0	4.4	6.5	6.0	7.1
17.2	1.0	.0	.0	.0	.0	.0	TRACE	TRACE	8.3	3.0	17.2
13.5	1.3	1.1	.0	.0	.0	.0	TRACE	3.5	4.0	8.0	13.6
5.7	5.9	TRACE	.0	.0	.0	.0	.0	TRACE	7.7	14.5	14.5
3.0	1.7	.0	.0	.0	.0	.0	.0	1.0	3.6	7.2	10.3
10.1	5.4	1.5	.0	.0	.0	.0	.0	5.1	4.8	3.7	10.1
2.4	1.1	TRACE	.0	.0	.0	.0	TRACE	1.2	2.3	5.1	5.1
3.0	.6	.2	TRACE	.0	.0	.0	.0	4.4	4.0	13.4	13.4
2.5	9.3	.0	.0	.0	.0	.0	.0	2.5	1.5	3.2	17.1
13.7	4.0	TRACE	.0	.0	.0	.0	TRACE	TRACE	5.3	11.3	15.2
5.1	.2	TRACE	.0	.0	.0	.0	TRACE	.1	8.8	4.9	11.5
19.8	9.1	.0	.0	.0	.0	.0	TRACE	TRACE	6.2	16.2	19.8
11.5	2.3	.1	.0	.0	.0	TRACE	TRACE	.7	2.8	3.3	11.8
4.5	9.9	.0	.0	.0	.0	.0	.0	1.1	5.5	13.5	13.5
12.0	1.5	.0	.0	.0	.0	.0	.0				19.6*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD:
MONTH: ALL HOUR

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT
.....

.....
GREATEST 23.8 17.9 21.0 9.9 3.0 TRACE TRACE TRACE 3.0 5.1 1
.....
TOTAL DRS 911 348 930 915 961 930 961 930 900 950
.....

THE GREATEST VALUE OF 23.8 OCCURRED ON 01/04/71

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

K. I. SAWYER AFB MI

PERIOD OF RECORD: 5701-5712,5804-5810,5910-8807
MONTH: ALL HOURS: ALL

05
.....
APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL
.....

.....
2.9 3.0 TRACE TRACE TRACE 3.0 5.1 11.8 16.2 23.8
.....
15 961 930 961 930 900 950 900 911 11048
.....

23.8 OCCURRED ON 01/04/71

ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOW DEPTH IN INCHES
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5
 LST TO UTC: +05 MONTH: ALL HOURS:

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
NONE	.2		4.2	47.7	95.6	100.0	100.0	100.0	99.9	91.5
TRACE	.2	.7	4.5	14.8	3.0					3.1
1	1.2	.5	3.7	7.4	.6					2.1
2	1.7	1.9	4.5	4.6	.4					1.2
3	3.2	.7	5.4	2.5	.2					.6
4-6	10.1	5.8	10.3	8.8	.1				.1	1.4
7-12	27.3	18.8	19.1	5.3						
13-24	38.7	40.8	31.6	7.1						
25-36	13.9	28.2	15.9	1.6						
37-48	3.3	2.6	.6							
49-60	.1									
61-120										
OVER 120										
DAYS WITH MEAS AMTS	99.6	99.3	91.2	37.4	1.4				.1	5.4
TOTAL NO. OF OBSERVATIONS	930	848	930	916	961	930	961	930	900	979

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOW DEPTH IN INCHES
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5610-5712, 5804-5810, 5910-8807
TIME ZONE: UTC: +05 MONTH: ALL HOURS: ALL

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
4.2	47.7	95.6	100.0	100.0	100.0	99.9	91.5	40.9	1.8	57.4
4.5	14.8	3.0					3.1	12.3	2.1	3.4
3.7	7.4	.6					2.1	12.3	5.6	2.8
4.5	4.6	.4					1.2	8.7	5.6	2.4
5.4	2.5	.2					.6	5.8	8.9	2.3
10.3	8.8	.1				.1	1.4	10.5	25.3	6.0
19.1	5.3							7.1	22.8	8.3
31.6	7.1							2.3	24.3	11.8
15.9	1.6							.2	3.4	5.1
.6									.1	.5
										.0
91.2	37.4	1.4				.1	5.4	46.9	96.1	39.1
930	916	961	930	961	930	900	979	930	943	11158

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 56
MONTH: ALL HOURS: 1

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
56										0*	27
57	26	27	18	7	0	0	0	0	0	TRACE	8
58				TRACE*	0	0	0	0	0	TRACE	
59										5*	17
60	17	42	39	11	4	0	0	0	0	TRACE	4
61	11	20	19	1	TRACE	0	0	0	0	0	9
62	27	36	34	6	TRACE	0	0	0	0	4	3
63	16	14	15	2	TRACE	0	0	0	0	0	5
64	13	27	17	11	0	0	0	0	0	2	6
65	15	29	29	30	0	0	0	0	0	1	8
66	17	17	15	15	0	0	0	0	0	0	17
67	43	34	30	3	3	0	0	0	0	5	7
68	13	29	30	1	0	0	0	0	0	5	12
69	50	43	29	22	0	0	0	0	0	6	4
70	26	25	23	5	2	0	0	0	0	0	6
71	36	34	23	21	1	0	0	0	0	0	10
72	18	23	35	28	1	0	0	0	0	1	2
73	15	18	12	5	2	0	0	0	0	0	2
74	17	23	17	12	1	0	0	0	0	4	8
75	24	26	33	22	0	0	0	0	0	0	22
76	21	23	34	4	TRACE	0	0	0	0	5	8
77	19	18	22	13	0	0	0	0	0	0	10
78	32	37	23	6	0	0	0	0	0	TRACE	8
79	37	38	29	24	TRACE	0	0	0	0	5	5
80	11	17	16	1	0	0	0	0	0	1	2
81	16	13	7	1	0	0	0	0	0	1	5
82	35	32	28	10	0	0	0	0	0	2	2
83	14	24	20	11	0	0	0	0	0	TRACE	5
84	17	26	13	7	TRACE	0	0	0	0	0	7
85	22	30	23	29	0	0	0	0	0	0	10
86	33	33	35	1	0	0	0	0	0	TRACE	4
87	13	15	8	17	0	0	0	0	0	TRACE	3
88	49	38	39	6	0	0	0	0	0		

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI
UTC: +05

PERIOD OF RECORD: 5610-5712, 5804-5810, 5910-8807
MONTH: ALL HOURS: ALL

YEAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
							0*	27	28	28*
	7	0	0	0	0	0	TRACE	8	12*	27*
	TRACE*	0	0	0	0	0	TRACE			TRACE*
							5*	17	18	18*
	11	4	0	0	0	0	TRACE	4	6	42
	1	TRACE	0	0	0	0	0	9	19	20
	6	TRACE	0	0	0	0	4	3	12	36
	2	TRACE	0	0	0	0	0	5	19	19
	11	0	0	0	0	0	2	6	15	27
	30	0	0	0	0	0	1	8	9	30
	15	0	0	0	0	0	0	17	32	32
	3	3	0	0	0	0	5	7	5	43
	1	0	0	0	0	0	5	12	38	38
	22	0	0	0	0	0	6	4	20	50
	5	2	0	0	0	0	0	6	34	34
	21	1	0	0	0	0	0	10	13	36
	28	1	0	0	0	0	1	2	13	35
	6	2	0	0	0	0	0	2	23	23
	12	1	0	0	0	4	4	8	10	23
	22	0	0	0	0	0	0	22	7	33
	4	TRACE	0	0	0	0	5	8	18	34
	13	0	0	0	0	0	0	10	33	33
	6	0	0	0	0	0	TRACE	8	17	37
	24	TRACE	0	0	0	0	5	5	7	38
	1	0	0	0	0	0	1	2	15	17
	1	0	0	0	0	0	1	5	21	21
	10	0	0	0	0	0	2	2	5	35
	11	0	0	0	0	0	TRACE	5	23	24
	7	TRACE	0	0	0	0	0	7	7	26
	29	0	0	0	0	0	0	10	35	35
	1	0	0	0	0	0	TRACE	4	6	35
	17	0	0	0	0	0	TRACE	3	18	18
	6	0	0	0	0	0				48*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 50
MONTH: ALL HOURS:

YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV

GREATEST	50	43	39	30	4	0	0	0	4	6	27
TOTAL OBS	930	848	930	916	961	930	961	930	900	979	930

THE GREATEST VALUE OF 50 OCCURRED ON 01/10/69

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI
C: +05

PERIOD OF RECORD: 5610-5712, 5804-5810, 5910-8807
MONTH: ALL HOURS: ALL

.....
APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL
.....

.....
30 4 0 0 0 4 6 27 38 50
.....
916 961 930 961 930 900 979 930 943 11158
.....

50 OCCURRED ON 01/10/69

0 ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI

PERIOD OF RECORD: 5
 SNOW-YEAR: 1 AUG -

SNOW-YEAR	FIRST SNOWFALL	FIRST MEASURABLE SNOWFALL	FIRST MEASURABLE SNOW DEPTH	LAST SNOWFALL	LAST MEASURABLE SNOWFALL	L MEAS SNOW
56 - 57	JAN 20	JAN 20	NOV 08	MAY 09	APR 13	A
57 - 58	OCT 24	NOV 05	NOV 09	MAY 10	MAY 10	D
58 - 59	SEP 30	OCT 01		OCT 11	OCT 01	
59 - 60	OCT 09	NOV 04	OCT 25	JUN 16	MAY 09	M
60 - 61	SEP 30	OCT 19	NOV 07	MAY 25	MAY 25	A
61 - 62	SEP 28	NOV 07	NOV 17	MAY 08	MAY 08	A
62 - 63	SEP 19	OCT 23	OCT 23	MAY 22	MAY 22	A
63 - 64	OCT 04	NOV 01	NOV 02	APR 14	APR 14	A
64 - 65	OCT 04	OCT 08	OCT 08	MAY 29	APR 26	A
65 - 66	SEP 25	OCT 23	OCT 24	MAY 28	MAY 28	A
66 - 67	SEP 30	OCT 16	NOV 01	JUL 04	MAY 20	M
67 - 68	SEP 27	OCT 10	OCT 10	MAY 17	APR 25	A
68 - 69	SEP 25	OCT 27	OCT 29	JUN 03	APR 28	A
69 - 70	OCT 11	OCT 15	OCT 22	MAY 05	MAY 05	M
70 - 71	SEP 28	NOV 13	NOV 15	MAY 26	MAY 12	M
71 - 72	NOV 02	NOV 03	NOV 04	APR 24	APR 23	M
72 - 73	OCT 12	OCT 21	OCT 21	MAY 16	MAY 16	M
73 - 74	SEP 12	NOV 02	NOV 08	MAY 18	MAY 05	M
74 - 75	SEP 21	SEP 21	SEP 22	APR 23	APR 19	A
75 - 76	SEP 12	NOV 12	NOV 13	MAY 07	MAY 03	A
76 - 77	SEP 21	OCT 15	OCT 16	MAY 06	APR 07	A
77 - 78	OCT 06	NOV 10	NOV 11	APR 20	APR 20	A
78 - 79	OCT 07	OCT 07	NOV 11	MAY 05	MAY 05	A
79 - 80	OCT 06	OCT 07	OCT 13	MAY 08	APR 24	A
80 - 81	SEP 26	OCT 03	OCT 13	JUN 20	MAY 09	A
81 - 82	OCT 01	OCT 01	OCT 21	APR 20	APR 20	A
82 - 83	OCT 15	OCT 16	OCT 16	MAY 04	APR 17	A
83 - 84	SEP 13	NOV 09	NOV 10	MAY 13	APR 30	A
84 - 85	SEP 26	OCT 30	NOV 10	APR 26	APR 17	A
85 - 86	SEP 12	NOV 03	NOV 11	MAY 01	MAY 01	A

FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI

PERIOD OF RECORD: 5610-5712, 5804-5810, 5910-8807
SNOW-YEAR: 1 AUG - 31 JUL

FIRST MEASURABLE SNOWFALL	FIRST MEASURABLE SNOW DEPTH	LAST SNOWFALL	LAST MEASURABLE SNOWFALL	LAST MEASURABLE SNOW DEPTH
JAN 20	NOV 08	MAY 09	APR 13	APR 15
NOV 05	NOV 09	MAY 10	MAY 10	DEC 13
OCT 01		OCT 11	OCT 01	
NOV 04	OCT 25	JUN 16	MAY 09	MAY 11
OCT 19	NOV 07	MAY 25	MAY 25	APR 02
NOV 07	NOV 17	MAY 08	MAY 08	APR 12
OCT 23	OCT 23	MAY 22	MAY 22	APR 30
NOV 01	NOV 02	APR 14	APR 14	APR 15
OCT 08	OCT 08	MAY 28	APR 26	APR 20
OCT 23	OCT 24	MAY 28	MAY 28	APR 26
OCT 16	NOV 01	JUL 04	MAY 20	MAY 11
OCT 10	NOV 10	MAY 17	APR 25	APR 25
OCT 27	OCT 28	JUN 03	APR 28	APR 14
OCT 15	OCT 22	MAY 05	MAY 05	MAY 05
NOV 13	NOV 15	MAY 26	MAY 12	MAY 12
NOV 03	NOV 04	APR 24	APR 23	MAY 01
OCT 21	OCT 21	MAY 16	MAY 16	MAY 04
NOV 02	NOV 08	MAY 18	MAY 05	MAY 06
SEP 21	SEP 22	APR 23	APR 19	APR 19
NOV 12	NOV 13	MAY 07	MAY 03	APR 02
OCT 15	OCT 16	MAY 06	APR 07	APR 10
NOV 10	NOV 11	APR 20	APR 20	APR 21
OCT 07	NOV 11	MAY 05	MAY 05	APR 17
OCT 07	OCT 13	MAY 08	APR 24	APR 24
OCT 03	OCT 13	JUN 20	MAY 09	APR 05
OCT 01	OCT 21	APR 20	APR 20	APR 23
OCT 16	OCT 16	MAY 04	APR 17	APR 20
NOV 09	NOV 10	MAY 13	APR 30	APR 11
OCT 30	NOV 10	APR 26	APR 17	APR 18
NOV 03	NOV 11	MAY 01	MAY 01	APR 21

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI

PERIOD OF RECORD:
SNOW-YEAR: 1 AUG

SNOW-YEAR	FIRST SNOWFALL	FIRST MEASURABLE SNOWFALL	FIRST MEASURABLE SNOW DEPTH	LAST SNOWFALL	LAST MEASURABLE SNOWFALL	MEI SNOW
86 - 87	AUG 27	OCT 14	NOV 16	APR 03	APR 02	
87 - 88	OCT 02	OCT 02	NOV 10	APR 27	APR 27	

MEDIAN-DATE SEP 30 OCT 22 NOV 02 MAY 08 APR 29

FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR
FROM SUMMARY OF DAY DATA

STATION: K. I. SAWYER AFB MI

PERIOD OF RECORD: 5610-5712, 5804-5810, 5910-8807
SNOW-YEAR: 1 AUG - 31 JUL

.....
FIRST LAST LAST LAST
MEASURABLE MEASURABLE MEASURABLE
SNOW DEPTH SNOWFALL SNOW DEPTH
.....

14 NOV 16 APR 03 APR 02 APR 07
02 NOV 10 APR 27 APR 27 APR 05

22 NOV 02 MAY 08 APR 29 APR 20

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTT	CCCCC
Pppppppp	AAAAAAAAA	RRRRRRRR	TTTTTTTTT	CCCCCCC
pp pp	AA AA	RR RR	TT	CC CC
pp pp	AA AA	RR RR	TT	CC
Pppppppp	AA AA	RRRRRRRR	TT	CC
Pppppppp	AAAAAAAAA	RRRRRRRR	TT	CC
PP	AAAAAAAAA	RR RR	TT	CC
PP	AA AA	RR RR	TT	CC CC
PP	AA AA	RR RR	TT	CCCCCCC
Pp	AA AA	RR RR	TT	CCCCC

PART C

SURFACE WIND SUMMARIES

PEAK WINDS.

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA. SPEEDS ARE IN KNOTS. DIRECTIONS ARE TO 16 COMPASS POINTS FROM THE BEGINNING OF PERIOD OF RECORD THROUGH JUNE 1968, BUT IN JULY 1968, ALL STATIONS EXCEPT THOSE OF THE NATIONAL WEATHER SERVICE STARTED RECORDING DIRECTIONS IN TENS OF DEGREES. DATA IS SUMMARIZED BY MONTH FOR EACH YEAR FOR THE ENTIRE PERIOD OF RECORD AVAILABLE. GIVEN: THE GREATEST MONTHLY VALUE FOR ALL YEARS COMBINED, THE GREATEST YEARLY VALUE FOR ALL YEARS COMBINED, AND THE DATE OF THE ABSOLUTE PEAK WIND RECORDED FOR THE ENTIRE PERIOD OF RECORD. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF PEAK SPEEDS ARE AVAILABLE.

PEAK WINDS--PERCENT OCCURRENCE FREQUENCY.

ALSO FROM SUMMARY OF DAY DATA. DATA IS SUMMARIZED BY MONTH, FOR ALL YEARS COMBINED, FOR ELEVEN WIND SPEED GROUPS. THE 1-4 KNOT SPEED GROUP INCLUDES CALM WINDS. IF THE PEAK WIND IS REPORTED FOR A PARTICULAR DAY AS "CALM," THAT COUNT GOES INTO THE "1-4 KNOT" CATEGORY. TABLES INCLUDE MEANS, MEDIANS, AND TOTAL OBSERVATION COUNTS. THE VALUES IN THIS SUMMARY ACCOUNT FOR A PEAK WIND BEING RECORDED FOR EACH DAY OF EACH MONTH.

WIND DIRECTION VS WIND SPEED--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS. THEY SUMMARIZE THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

THESE TABLES GIVE A BIVARIATE DISTRIBUTION OF THE PERCENT OCCURRENCE FREQUENCY (POF) FOR ELEVEN WIND SPEED GROUPS VERSUS TWELVE WIND DIRECTION SECTORS GIVEN IN 30 DEGREE INCREMENTS. "CALM" AND "VARIABLE" WINDS ARE GIVEN SEPARATELY. CARDINAL WIND DIRECTIONS (N,E,S,W) APPEAR FOR REFERENCE. TOTAL PERCENTAGES, MEANS, AND MEDIANS FOR EACH SECTOR, ALONG WITH TOTAL OBSERVATION COUNTS, ARE PRINTED BELOW EACH SUMMARY.

ALSO PROVIDED: A BIVARIATE DISTRIBUTION OF WIND DIRECTION VERSUS WIND SPEED FOR SPECIFIED CEILING/VISIBILITY CONDITIONS. THESE CONDITIONS ARE:

WHEN THE VISIBILITY IS GREATER THAN OR EQUAL TO 1/2 MILES (0800 METERS) THE CEILING MUST BE GREATER THAN OR EQUAL TO 200 FEET BUT LESS THAN 1500 FEET. IF THIS CONDITION IS NOT MET, THEN THE FOLLOWING CONDITION IS TESTED: WHEN THE CEILING IS GREATER THAN OR EQUAL TO 200 FEET, THE VISIBILITY MUST BE GREATER THAN OR EQUAL TO 1/2 (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS).

CONVERSION: 1 KNOT = .514791 METERS PER SECOND

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

PEAK SURFACE WINDS IN KNOTS
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: +05

PERIOD OF RECORD: 62
 MONTH: ALL HOURS:

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
62		N 33	N 26	N 37	W 34	W 30	WNW 33	N 33	SSW 43	W 33	SSW 31
63	NW 34	S 39	NNW 45	SSW 44	S 29	WNW 42	SSW 25	NE 31	NE 36	SSW 31	NNW 36
64	SSW 40	SW 36	S 39	SSW 59	S 37	WSW 43	NNE 35	WSW 35	SW 39	W 41	WNW 32
65	NNW 38	N 38	N 35	WSW 33	SSW 33	NW 32	WNW 32	N 29	SW 26	N 37	NW 46
66	S 34	S 31	NNE 43	ESE 32	WNW 38	W 31	WNW 40	NNE 27	NNW 29	SW 38	N 57
67	NW 37	N 38	S 36	N 35	SSW 39	SW 32	NNW 32	NNE 35	N 31	N 35	S 33
68	S 37	NNW 44	S 46	NW 57	SW 50	ESE 38	23/ 33	18/ 43	16/ 29	20/ 37	29/ 40
69	16/ 37	36/ 35	36/ 43	36/ 38	30/ 42	22/ 46	19/ 32	25/ 41	19/ 34	34/ 32	35/ 39
70	36/ 36	36/ 40	36/ 35	27/ 42	29/ 37	02/ 32	33/ 35	27/ 32	27/ 38	18/ 41	26/ 50
71	33/ 43	18/ 40	01/ 43	35/ 40	23/ 39	20/ 32	30/ 32	25/ 40	22/ 32	20/ 44	20/ 42
72	34/ 45	36/ 32	36/ 43	09/ 29	36/ 40	01/ 32	23/ 39	36/ 26	26/ 39	29/ 54	02/ 38
73	36/ 34	18/ 37	16/ 42	03/ 41	35/ 40	22/ 31	21/ 32	20/ 38	20/ 31	21/ 36	32/ 36
74	32/ 35	34/ 35	27/ 33	35/ 36	13/ 32	33/ 35	27/ 34	22/ 30	21/ 33	36/ 39	35/ 30
75	18/ 50	33/ 30	03/ 36	02/ 28	27/ 60	22/ 40	34/ 32	21/ 37	32/ 30	25/ 38	29/ 43
76	20/ 37	35/ 37	01/ 39	21/ 34	21/ 34	19/ 54	01/ 31	27/ 32	24/ 35	31/ 32	30/ 32
77	31/ 36	36/ 32	32/ 35	35/ 32	24/ 38	31/ 43	30/ 41	33/ 32	24/ 42	28/ 34	23/ 46
78	36/ 58	36/ 31	20/ 35	33/ 42	01/ 36	19/ 38	27/ 47	20/ 30	32/ 36	36/ 36	24/ 37
79	35/ 29	31/ 32	36/ 50	31/ 42	18/ 40	35/ 40	03/ 38	18/ 32	20/ 37	35/ 41	19/ 40
80	27/ 42	20/ 29	29/ 37	36/ 38	35/ 36	35/ 34	19/ 29	20/ 37	24/ 39	22/ 43	33/ 29
81	19/ 27	36/ 33	32/ 30	32/ 36	36/ 35	24/ 34	20/ 27	27/ 22	33/ 40	33/ 39	30/ 33
82	01/ 41	35/ 33	28/ 37	32/ 44	18/ 28	17/ 29	32/ 36	35/ 29	03/ 32	35/ 50	33/ 39
83	36/ 41	02/ 42	36/ 41	08/ 37	36/ 30	17/ 34	22/ 35	27/ 32	20/ 29	33/ 31	20/ 34
84	20/ 30	36/ 36	36/ 44	36/ 41	24/ 43	21/ 38	23/ 40	29/ 34	19/ 34	21/ 53	19/ 40
85	33/ 35	24/ 38	36/ 40	35/ 39	32/ 32	28/ 38	24/ 33	23/ 37	18/ 33	35/ 36	25/ 35
86	36/ 39	36/ 23	36/ 53	36/ 35	24/ 37	23/ 36	20/ 29	32/ 27	31/ 28	19/ 34	19/ 47
87	36/ 32	35/ 56	01/ 36	32/ 40	18/ 43	30/ 23	23/ 56	34/ 27	35/ 25	35/ 42	34/ 34
88	36/ 41	34/ 36	22/ 33	36/ 34	32/ 31	23/ 31	22/ 34				

PEAK SURFACE WINDS IN KNOTS
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI
UTC: +05

PERIOD OF RECORD: 6202-6806,6807-8807
MONTH: ALL HOURS: ALL

	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
1	N 37	W 34	W 30	WNW 33	N 33	SSW 43	W 33	SSW 31	NW 38	SSW*43
2	SSW 44	S 29	WNW 42	SSW 25	NE 31	NE 36	SSW 31	NNW 36	N 36	NNW 45
3	SSW 59	S 37	WSW 43	NNE 35	WSW 35	SW 39	W 41	WNW 32	S 37	SSW 59
4	WSW 33	SSW 33	NW 32	WNW 32	N 29	SW 26	N 37	NW 46	N 39	NW 46
5	ESE 32	WNW 38	W 31	WNW 40	NNE 27	NNW 29	SW 38	N 57	SSE 36	N 57
6	N 35	SSW 39	SW 32	NNW 32	NNE 35	N 31	N 35	S 33	S 37	SSW 39
7	NW 57	SW 50	ESE 38	23/ 38	18/ 43	16/ 29	20/ 37	29/ 40	36/ 43	NW 57
8	36/ 38	30/ 42	22/ 46	19/ 32	25/ 41	19/*34	34/ 32	36/ 39	36/ 41	22/*46
9	27/ 42	29/ 37	02/ 32	33/ 35	27/ 32	27/ 38	18/ 41	26/ 50	02/ 38	26/ 50
10	35/ 40	23/ 39	20/ 32	30/ 32	25/ 40	22/ 32	20/ 44	20/ 42	29/ 38	01/ 49
11	09/ 29	36/ 40	01/ 32	23/ 39	36/ 26	25/ 39	29/ 54	02/ 38	32/ 35	29/ 54
12	03/ 41	35/ 40	22/ 31	21/ 32	20/ 38	20/ 31	21/ 36	32/ 36	22/ 37	16/ 42
13	35/ 36	13/ 32	33/ 35	27/ 34	22/ 30	21/ 33	36/ 39	35/ 30	36/ 36	36/ 39
14	02/ 29	27/ 60	22/ 40	34/ 32	21/ 37	32/ 30	25/ 38	29/ 43	20/ 34	27/ 60
15	21/ 34	21/ 34	19/ 54	01/ 31	27/ 32	24/ 35	31/ 32	30/ 32	35/ 36	19/ 54
16	35/ 38	24/ 38	31/ 43	30/ 41	33/ 32	24/ 42	28/ 34	23/ 46	34/ 29	23/ 46
17	33/ 42	01/ 36	19/ 38	27/ 47	20/ 30	32/ 36	36/ 36	24/ 37	32/ 30	36/ 58
18	31/ 42	19/ 40	35/ 40	03/ 38	18/ 32	20/ 37	35/ 41	19/ 40	21/ 36	36/ 50
19	35/ 38	35/ 36	35/ 34	19/ 29	20/ 37	24/ 39	22/ 43	33/ 29	29/ 35	22/ 43
20	32/ 36	36/ 35	24/ 34	20/ 27	27/ 22	33/ 40	33/ 39	30/ 33	19/ 28	33/ 40
21	32/ 44	18/ 28	17/ 29	32/ 36	35/ 29	03/ 32	35/ 50	33/ 39	19/ 34	35/ 50
22	08/ 37	36/ 30	17/ 34	22/ 35	27/ 32	20/ 29	33/ 31	20/ 34	33/ 37	02/ 42
23	36/ 41	24/ 43	21/ 38	23/ 40	29/ 34	19/ 34	21/ 53	19/ 40	24/ 45	21/ 53
24	35/ 39	32/ 32	28/ 38	24/ 33	23/ 37	18/ 33	35/ 36	28/ 35	36/ 49	36/ 49
25	36/ 35	24/ 37	23/ 36	20/ 29	32/ 27	31/ 28	19/ 34	19/ 47	20/ 30	36/ 53
26	32/ 40	18/ 43	30/ 23	23/ 56	34/ 27	35/ 25	35/ 42	34/ 34	01/ 42	35/ 56
27	36/ 34	32/ 31	23/ 31	22/ 34						36/*41

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PEAK SURFACE WINDS IN KNOTS
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD: 6202
MONTH: ALL HOURS: AT

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV
.....

.....
GREATEST 36/ 58 35/ 56 36/ 53 SSW 59 27/ 60 19/ 54 23/ 56 18/ 43 SSW 43 29/ 54 N 57 3
.....
TOTAL OBS 204 762 834 809 834 806 831 802 770 801 778
.....

THE PEAK WIND OF 60 FROM 27/ OCCURRED ON 05/19/75

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH
 †THE VALUE IS 100 OR GREATER WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH

PEAK SURFACE WINDS IN KNOTS
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI
TC: +05

PERIOD OF RECORD: 6202-6806, 6907-8807
MONTH: ALL HOURS: ALL

.....
APR MAY JUN JUL AUG SEP OCT NOV DEC ANN
.....

.....
SSW 59 27/ 60 19/ 54 23/ 56 18/ 43 SSW 43 29/ 54 N 57 36/ 49 27/ 60
.....
309 334 806 831 802 770 801 778 803 9634
.....

FROM 27/ OCCURRED UN 05/19/75

BASED ON A MONTH WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH
OR GREATER WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF DAILY PEAK WINDS
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: +05

PERIOD OF RECORD: 620
 MONTH: ALL HOURS: A

MONTH	WIND SPEEDS IN KNOTS										
	CALM-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
JAN	.2	5.2	15.0	25.2	24.6	15.4	8.3	4.0	1.5	.4	.0
FEB	.3	6.4	20.7	25.3	20.5	13.8	8.8	3.0	1.0	.1	.0
MAR	.0	3.6	15.3	26.9	24.5	14.6	8.2	4.7	2.0	.2	.0
APR	.0	1.2	13.2	26.1	27.7	15.6	9.8	4.2	1.9	.4	.0
MAY	.0	1.3	14.5	27.9	30.0	15.9	7.1	2.3	.7	.2	.0
JUN	.0	2.9	17.1	32.4	26.2	13.3	5.7	1.5	.9	.1	.0
JUL	.0	2.2	19.7	31.8	29.0	10.3	5.4	1.0	.5	.1	.0
AUG	.0	2.6	23.7	32.2	26.2	9.2	4.5	1.2	.4	.0	.0
SEP	.0	2.6	18.1	30.6	26.8	15.2	4.2	2.2	.4	.0	.0
OCT	.0	3.0	17.4	25.7	23.7	15.7	8.7	3.9	1.5	.4	.0
NOV	.0	4.5	17.6	29.3	21.9	14.4	7.3	2.7	1.9	.4	.0
DEC	.2	5.0	19.4	22.5	26.0	14.7	7.8	3.5	.7	.0	.0
ANNUAL	.1	3.4	17.6	28.0	25.6	14.0	7.2	2.8	1.1	.2	.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF DAILY PEAK WINDS
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: +05

PERIOD OF RECORD: 6202-6806,6807-8807
MONTH: ALL HOURS: ALL

WIND SPEEDS IN KNOTS									MEAN	MEDIAN	TOTAL
10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	WIND	WIND	OBS
15.0	25.2	24.6	15.4	8.3	4.0	1.5	.4	.0	21.0	20.0	804
20.7	25.3	20.5	13.8	8.8	3.0	1.0	.1	.0	19.9	19.0	762
15.3	26.9	24.5	14.6	8.2	4.7	2.0	.2	.0	21.2	20.0	834
13.2	26.1	27.7	15.6	9.9	4.2	1.9	.4	.0	22.0	21.0	809
14.5	27.9	30.0	15.9	7.1	2.3	.7	.2	.0	21.1	20.0	834
17.1	32.4	26.2	13.3	5.7	1.5	.9	.1	.0	19.9	19.0	806
19.7	31.8	29.0	10.3	5.4	1.0	.5	.1	.0	19.4	19.0	831
23.7	32.2	26.2	9.2	4.5	1.2	.4	.0	.0	18.8	18.0	802
18.1	30.6	26.8	15.2	4.2	2.2	.4	.0	.0	19.8	19.0	770
17.4	25.7	23.7	15.7	8.7	3.9	1.5	.4	.0	21.1	20.0	801
17.6	29.3	21.9	14.4	7.3	2.7	1.9	.4	.0	20.4	19.0	778
19.4	22.5	26.0	14.7	7.8	3.5	.7	.0	.0	20.3	20.0	803
17.6	28.0	25.6	14.0	7.2	2.8	1.1	.2	.0	20.4	20.0	9634

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: JAN HOURS: 00-00

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.1	2.3	2.6	2.4	1.2	.1						9.6
020-040	.8	1.9	1.3	.2								4.2
050-070	1.2	.1	.2									1.5
(E) 080-100	.9	.2	.2									1.2
110-130	.3			.1								.9
140-160	.2	.1	.2									.5
(S) 170-190	1.0	2.2	2.9	1.1	.1							7.2
200-220	4.3	4.1	3.8	1.0								13.1
230-250	4.3	5.4	.6	.1								10.4
(W) 260-280	3.9	5.4	1.5	.2								11.1
290-310	2.9	6.6	2.3	.2								11.9
320-340	1.7	5.3	4.8	1.7	.3							13.9
VARIABLE												
CALM	////////////////////										14.5	
TOTALS	23.0	33.6	20.5	7.0	1.6	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 00-02

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
2.6	2.4	1.2	.1							9.6	12.1	12.0
1.3	.2									4.2	7.8	8.0
.2										1.5	3.9	3.0
.2										1.2	5.1	4.0
	.1									.9	4.9	3.0
.2										.5	6.8	7.0
1.2	1.1	.1								7.2	10.1	10.0
1.4	1.0									13.1	7.4	6.0
.6	.1									10.4	5.4	5.0
1.6	.2									11.1	6.3	6.0
1.3	.2									11.9	6.9	7.0
1.3	1.7	.3								13.9	9.7	9.0
////////////////////////////////////										14.5	////////////////////////////////	
1.2	7.0	1.6	.1							100.0	6.8	7.0
TOTAL NUMBER OF OBSERVATIONS										930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - 8
LST TO UTC: + 5 MONTH: JAN HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS						TOTAL %	M H					
	1-4	5-9	10-14	15-19	20-24	25-29			30-34	35-39	40-49	50-64	GE 65
(N) 350-010	1.5	1.6	3.8	1.2	1.4		9.5	1					
020-040	2.0	1.3	1.0	.4	.1		4.8						
050-070	.3	.6					1.0						
(E) 080-100	.5	.1					.6						
110-130	.4	.5	.1				1.1						
140-160	.1	.3					.4						
(S) 170-190	1.3	2.0	2.0	1.4	.4		7.7						
200-220	4.0	4.1	3.0	.8			11.8						
230-250	5.6	5.4	.5	.3			11.8						
(W) 260-280	2.0	5.5	1.0	.2			8.7						
290-310	3.7	7.2	2.3	.5			13.7						
320-340	2.9	4.3	4.7	2.5	.4		14.8						
VARIABLE													
CALM	////////////////////////////////////											14.0	//
TOTALS	24.8	32.9	14.4	7.3	2.3							100.0	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: JAN HOURS: 03-05

WIND SPEED IN KNOTS		TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24			
1.2	1.4	9.5	11.5	11.0
.4	.1	4.8	7.3	6.0
		1.0	5.0	5.0
		.6	2.8	2.5
		1.1	6.0	5.0
		.4	5.3	6.0
1.4	.4	7.7	9.8	9.5
.8		11.8	7.3	6.0
.3		11.8	5.5	5.0
.2		8.7	6.6	7.0
.5		13.7	7.0	7.0
2.5	.4	14.8	9.8	10.0

//////////////////////////////////// 14.0 //////////////////////////////////
7.3 2.3 100.0 6.9 7.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: JAN HOURS: 06-0

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.8	2.0	3.4	1.7	1.0							10.0
020-040	.3	1.2	.9	.1	.3							3.2
050-070	.6	1.3	.2									2.2
(E) 080-100	.2	.3	.1									.6
110-130	.2	.6										.9
140-160	1.0	.6										1.6
(S) 170-190	1.9	2.9	1.4	1.5	1.2	.1						9.5
200-220	4.0	4.9	2.2	.6	.1							11.8
230-250	3.7	3.4	.7	.2								8.1
(W) 260-280	3.4	5.1	.5									9.0
290-310	2.6	4.9	2.3	.5	.1							10.4
320-340	2.5	6.3	4.4	1.3	.2							16.2
.....												
VARIABLE												
CALM	////////////////////////////////////											16.5
TOTALS	22.7	33.5	17.0	5.4	3.5	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: JAN HOURS: 06-08

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.4	1.7	1.0							10.0	10.9	11.0
.9	.1	.3							3.2	8.9	9.5
.2									2.2	6.0	6.0
.1									.6	5.5	5.5
									.9	5.9	6.5
									1.6	4.7	4.0
1.1	1.5	1.2	.1						9.5	10.7	9.0
1.2	.6	.1							11.8	7.0	6.0
.1	.2								8.1	5.5	5.0
.2									9.0	5.4	6.0
1.4	.5	.1							10.4	7.5	7.0
1.1	1.3	.0							16.2	9.5	9.0
									16.5	////////////////////	
1.0	6.4	3.5	.1						100.0	6.8	7.0
TOTAL NUMBER OF OBSERVATIONS										930	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: 09-1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	.6	2.6	3.9	2.7	.8	.4						11.0
020-040	1.1	1.7	1.1	.3	.2	.1						4.5
050-070	.8	.3	.1									1.6
(E) 080-100	.5	.3										.9
110-130	.1	.2	.1									.4
140-160	.6	.6	.6									1.9
(S) 170-190	2.3	2.6	2.9	1.1	1.2	.1	.1					10.2
200-220	3.7	4.9	3.4	.1	.5							13.1
230-250	2.3	3.9	1.4	.1	.1							8.3
(W) 260-280	2.9	4.3	1.2	.5								9.5
290-310	2.5	4.8	1.7	.6	.1	.1						9.9
320-340	2.0	5.6	5.3	1.6	.4							16.0
VARIABLE												
CALM	////////////////////										12.7	
TOTALS	19.9	32.8	23.2	7.0	3.3	.7	.1					100.0
TOTAL NUMBER OF OBSERVATIONS 930												

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI
ELEVATION: 45

PERIOD OF RECORD: AUG 78 - JUL 89
MONTH: JAN HOURS: 09-11

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
0.7	.6	.4						11.0	12.7	12.0
.3	.2	.1						4.5	9.0	8.0
								1.6	5.0	5.0
								.9	3.4	2.5
								.4	7.3	7.5
								1.9	6.8	7.0
1.1	1.2	.1	.1					10.2	10.5	10.0
.1	.5							13.1	7.8	7.0
.1	.1							2.3	5.4	6.0
.5								9.5	6.7	6.0
.5	.1	.1						9.9	7.7	7.0
1.0	.4							16.0	9.7	10.0
								12.7		
7.0	3.3	.7	.1					100.0	7.6	6.0
TOTAL NUMBER OF OBSERVATIONS								930		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: JAN HOURS: 12-1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS									TOTAL %		
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49		50-64	GE 65
(N) 350-010	2.2	4.0	5.4	2.6	1.2	.4	.1					15.8
020-040	1.4	1.7	1.3	.3								4.7
050-070	1.1	.3	.2									1.6
(E) 080-100	.4	.5	.1									1.1
110-130	.9	.3										1.2
140-160	.5	.4	.9	.2								2.0
(S) 170-190	1.3	2.9	3.1	2.7	1.0							11.5
200-220	2.0	4.3	5.2	1.3	.5	.1						13.4
230-250	1.4	3.1	2.0	.3								6.9
(W) 260-280	1.7	3.1	2.9	.6	.2							8.6
290-310	1.1	4.2	3.8	1.3	.3							10.6
320-340	2.2	4.9	7.6	2.3	.5							17.5
.....												
VARIABLE												
CALM	////////////////////										4.9	
TOTALS	16.7	29.7	32.5	11.6	3.7	.5	.1					100.0

TOTAL NUMBER OF OBSERVATIONS 930

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: JAN HOURS: 12-14

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
1-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
2.6	1.2	.4	.1					15.8	11.6	11.0
.3								4.7	8.0	7.0
								1.6	4.3	4.0
								1.1	5.5	5.0
								1.2	4.2	4.0
.2								2.0	8.8	10.0
0.7	1.0							11.5	11.1	11.0
1.3	.5	.1						13.4	10.1	10.0
.3								6.9	7.6	7.0
.6	.2							8.6	8.7	8.0
1.4	.3							10.6	9.8	10.0
0.3	.5							17.5	10.2	10.0
////////////////////////////////////								4.9	////////////////////////////////	
1.5	3.7	.5	.1					100.0	9.3	10.0
NUMBER OF OBSERVATIONS								930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 1
MONTH: JAN HOURS: 16

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.1	3.3	4.3	1.6	.6	.5						13.
020-040	2.2	2.5	1.3	.4								7.
050-070	1.4	.6										2.
(E) 080-100	.9	.8	.1									1.
110-130	.2	.4										.
140-160	.4	.4	1.1	.4	.1							2.
(S) 170-190	1.6	4.6	4.6	1.3	.5	.1						13.
200-220	2.2	3.0	4.1	1.3	.1							10.
230-250	.8	4.0	1.5	.3								6.
(W) 260-280	1.1	3.1	2.0	.5	.1	.1						7.
290-310	1.2	6.1	4.1	1.0								13.
320-340	.3	5.7	6.6	2.7	.5	.1						16.
VARIABLE												
CALM	////////////////////										5.	
TOTALS	17.3	34.5	29.7	10.0	1.9	.5						100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TD UTC: + 5 MONTH: JAN HOURS: 15-17

WIND SPEED IN KNOTS

0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
4.3	1.6	.6	.5						13.5	10.1	10.0
1.3	.4								7.1	6.3	5.0
									2.0	4.4	4.0
.1									1.7	4.7	4.5
									.6	5.0	5.0
1.1	.4	.1							2.5	10.5	10.0
4.6	1.3	.5	.1						13.3	10.3	10.0
4.1	1.3	.1							10.6	9.3	10.0
1.5	.3								6.6	7.8	7.0
2.0	.5	.1	.1						7.0	8.8	8.0
4.1	1.0								13.1	8.5	8.0
6.6	2.7	.5	.1						16.3	11.0	10.5

5.5

2.7	10.0	1.9	.3						100.0	8.7	9.0
-----	------	-----	----	--	--	--	--	--	-------	-----	-----

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: JAN HOURS: 11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.0	2.6	2.9	1.3	1.0	.2						10.
020-040	1.3	1.7	1.2	.3								4.
050-070	1.8	.9										2.
(E) 080-100	.5	.5	.3	.1								1.
110-130	.5	.3										.
140-160	.8	.6	1.0	.1								2.
(S) 170-190	1.3	4.0	4.5	1.4	.5							12.
200-220	3.3	4.4	3.5	.8								12.
230-250	2.2	2.5	.9									5.
(W) 260-280	2.9	3.8	.6	.2	.2							7.
290-310	4.7	5.8	1.8	.1								12.
320-340	3.5	5.5	3.5	2.0	.8							15.
.....												
VARIABLE												
CALM	////////////////////											12.
TOTALS	25.3	32.6	20.2	6.3	2.5	.2						100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: JAN HOURS: 18-20

WIND SPEED IN KNOTS

14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
2.0	1.3	1.0	.2						10.0	10.1	10.0
1.2	.3								4.5	7.5	6.5
									2.7	3.5	3.0
.3	.1								1.5	6.6	6.0
									.9	4.3	4.0
1.0	.1								2.5	8.2	8.0
.5	1.4	.5							12.3	9.8	10.0
.5	.8								12.0	7.8	7.0
.4									5.5	6.1	6.0
.6	.2	.2							7.7	6.5	6.0
1.2	.1								12.5	6.0	5.0
1.5	2.0	.8							15.4	9.2	8.0
									12.6		
1.2	6.3	2.5	.2						100.0	6.9	7.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 71
MONTH: JAN HOURS: 21

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.7	1.6	3.0	2.5	1.2	.2						10.
020-040	1.1	1.3	.5									2.
050-070	1.0	.3										1.
(E) 080-100	1.4		.1	.1	.1							1.
110-130	.3											.
140-160	1.1	.6	.2	.1								2.
(S) 170-190	1.4	2.7	3.5	1.2	.2							9.
200-220	2.6	4.2	4.3	1.1		.1						12.
230-250	3.0	3.2	1.7	.2								8.
(W) 260-280	3.3	4.5	1.6									9.
290-310	2.5	6.9	2.2	.4								11.
320-340	1.5	7.1	4.3	.9	.3	.1						14.
VARIABLE												
CALM	////////////////////////////////////										15.	
TOTALS	21.0	32.4	22.0	6.5	1.8	.4						100.

TOTAL NUMBER OF OBSERVATIONS 930

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 21-23

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
0-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
2.5	1.2	.2						10.2	12.1	12.0
								2.9	6.6	5.0
								1.3	3.7	4.0
.1	.1							1.7	5.5	3.0
								.3	3.0	3.0
.1								2.6	6.6	6.0
1.2	.2							9.0	10.0	10.5
1.1		.1						12.3	8.8	9.0
.2								8.2	6.7	6.0
								9.5	5.9	6.0
.4								11.9	7.0	7.0
.9	.3	.1						14.3	8.9	8.0
								15.8		
5.5	1.3	.4						100.0	6.9	8.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURENCE SURFACE WIND DIRECTION VERSU
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFS MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: JAN HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										T	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.8	2.5	3.7	2.0	1.0	.2	.0					1
020-040	1.4	1.7	1.1	.3	.1	.0						
050-070	1.0	.6	.1									
(E) 080-100	.7	.3	.1	.0	.0							
110-130	.4	.3	.0	.0								
140-160	.6	.5	.6	.1	.0							
(S) 170-190	1.7	3.0	3.2	1.5	.6	.0	.0					10
200-220	3.3	4.2	3.7	.9	.2	.0						12
230-250	3.0	3.9	1.2	.2	.0							
(W) 260-280	2.7	4.4	1.4	.3	.1	.0						
290-310	2.7	5.8	2.5	.6	.1	.0						11
320-340	2.2	5.6	5.3	1.9	.5	.0						15
VARIABLE												
CALM	////////////////////										12	
TOTALS	21.5	32.8	22.9	7.8	2.6	.2						100

TOTAL NUMBER OF OBSERVATIONS 7440

INDICENTAGE FREQUENCY OF OCCUPRECE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
IC: + 5

PERIOD OF RECORD: AUG 73 - JUL 88
MONTH: JAN HOURS: ALL

WIND SPEED IN KNOTS											
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
10	2.0	1.0	.2	.0					11.2	11.4	11.0
20	.3	.1	.0						4.5	7.6	7.0
30									1.7	4.5	4.0
40	.0	.0							1.2	5.1	4.0
50	.0								.8	5.1	4.0
60	.1	.0							1.8	7.7	8.0
70	1.6	.5	.0	.0					10.1	10.3	10.0
80	.9	.2	.0						12.3	9.2	8.0
90	.2	.0							8.2	6.2	6.0
100	.3	.1	.0						9.9	6.8	6.0
110	.6	.1	.0						11.8	7.5	7.0
120	1.9	.5	.0						15.6	9.7	10.0
									12.1	7.5	8.0
									100.0	7.5	8.0
TOTAL NUMBER OF OBSERVATIONS 7440											

OPERATING LOCATION NAME
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 72743F

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JAN HOURS:

.....
CATEGORY A: CEILING OF 200 BUT LESS THAN 1500 FEET WITH VISIBILITY OF 1/2 MILE (0800 METERS)
AND/OR
VISIBILITY OF 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEI
.....

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	1.5	4.9	6.2	4.6	.3	.1					
020-040	2.3	3.1	2.5	.6	.0						
050-070	1.9	1.5	.2								
(E) 080-100	1.2	.4	.3	.0	.0						
110-130	.5	.5	.0	.0							
140-160	.3	.7	1.0	.2	.0						
(S) 170-190	1.5	2.2	4.5	2.5	1.4	.1					
200-220	1.5	3.4	2.8	.8	.0	.0					
230-250	2.0	1.4	.2	.3	.0						
(W) 260-280	1.3	1.7	.2	.2	.1	.0					
290-310	1.3	1.2	1.5	.7	.1						
320-340	1.3	6.1	7.7	3.5	1.1	.0					
VARIABLE											
CALM	////////////////////////////////////										
TOTALS	17.5	23.9	29.1	13.5	3.4	.2					10

TOTAL NUMBER OF OBSERVATIONS 2136

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 MONTH: JAN HOURS: ALL

WIND SPEEDS LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 WIND SPEEDS (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND DIRECTION	WIND SPEED IN KNOTS						TOTAL	MEAN WIND	MEDIAN WIND
	10-19	20-24	25-29	30-34	35-39	40-49			
0							20.1	11.5	12.0
7	4.6	.3	.1				3.7	7.9	7.0
5	.6	.0					3.6	4.9	4.0
4							2.4	5.7	5.0
0	.3	.0					1.0	6.0	5.5
4	.0						2.8	8.3	8.5
9	.2	.0					12.9	11.8	12.0
0	2.5	1.3	.1				3.6	8.7	8.0
0	.0	.0	.0				3.9	5.7	4.0
6	.3	.0					3.6	6.7	5.0
4	.2	.1	.0				5.4	8.9	8.0
2	.7	.1					20.2	10.9	10.0
0	3.5	1.1	.0				6.7	9.0	10.0
0	13.5	3.4	.2				100.0	9.0	10.0
TOTAL NUMBER OF OBSERVATIONS 2136									

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: FEB HOURS: 00

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.1	3.3	4.8	1.2	.5							12.
020-040	1.1	1.5	1.3	.5	.4							4.
050-070	.1	.6	.1									.
(E) 080-100	.7	.1										.
110-130	1.1	.2										1.
140-160	1.9	1.9	.2	.2								4.
(S) 170-190	3.9	5.3	2.1	.2	.2							11.
200-220	5.3	4.4	3.5	.9	.2							14.
230-250	2.7	1.2	.5									4.
(W) 260-280	4.2	2.5	.1									6.
290-310	2.3	3.5	1.1	.2								7.
320-340	2.1	3.2	1.6	1.4		.1	.2					8.
.....												
VARIABLE												
CALM	////////////////////////////////////										21.	
TOTALS	29.0	28.0	15.3	4.6	1.3	.1	.2					100.
.....												
TOTAL NUMBER OF OBSERVATIONS 849												
.....												

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: FEB HOURS: 00-02

WIND SPEED IN KNOTS				TOTAL	MEAN	MEDIAN
1-19	20-24	25-29	30-34	%	WIND	WIND
1.2	.5			12.8	9.1	10.0
.5	.4			4.9	9.1	8.0
				.8	6.9	7.0
				.8	2.7	2.0
				1.3	3.8	3.0
.2				4.2	5.8	5.5
.2	.2			11.8	6.8	6.0
.9	.2			14.4	7.3	6.0
				4.4	4.9	4.0
				6.8	4.1	4.0
.2				7.7	6.0	6.0
1.4	.1	.2		8.7	9.2	7.5
////////////////////////////////////				21.3	////////////////////////////////	
.6	1.3	.1	.2	100.0	5.6	6.0
NUMBER OF OBSERVATIONS				849		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: FEB HOURS: 03-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.5	4.4	4.2	1.8	.5	.1		.2	.1			13.8
020-040	1.3	1.6	1.2	.4	.4							4.8
050-070	1.2	.7										1.9
(E) 080-100	.6	.4										.9
110-130	1.1	.4										1.4
140-160	1.4	1.9	.6									3.9
(S) 170-190	3.5	4.0	3.3									10.8
200-220	5.7	4.2	3.9	.1	.2							14.1
230-250	2.6	1.5	.2									4.4
(W) 260-280	4.5	2.1	.5									7.1
290-310	3.9	3.2	.7	.2								8.0
320-340	1.8	2.6	3.1	.9	.2							8.6
VARIABLE												
CALM	////////////////////										20.3	
TOTALS	30.1	27.0	17.7	3.4	1.3	.1		.2	.1			100.0

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: FEB HOURS: 03-05

WIND SPEED IN KNOTS											
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.2	1.8	.5	.1		.2	.1			13.8	10.4	10.0
1.2	.4	.4							4.8	8.8	8.0
									1.9	3.9	3.5
									.9	3.9	3.5
									1.4	4.4	4.0
									3.9	5.9	5.0
									10.8	7.0	6.0
	.1	.2							14.1	6.6	5.5
									4.4	4.5	4.0
									7.1	4.2	4.0
	.2								8.0	5.8	5.0
	.9	.2							8.6	9.0	9.0
									20.3		
.7	3.4	1.3	.1		.2	.1			100.0	5.7	6.0
TOTAL NUMBER OF OBSERVATIONS										849	

OPERATING LOCATION *A*
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: FEB HOURS: 06

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.9	3.7	3.3	1.5	1.2			.2	.1			13.
020-040	.7	2.5	1.2	.5	.1							4.
050-070	1.6	.2										1.
(E) 080-100	1.1	.5										1.
110-130	1.3	.4										2.
140-160	2.0	.7	.1									2.
(S) 170-190	4.4	3.2	2.8	.6								11.
200-220	4.7	5.7	2.5	.7								13.
230-250	3.2	3.2										6.
(W) 260-280	3.3	1.1	.5									4.
290-310	3.8	3.2	.5	.5								8.
320-340	1.5	3.3	3.3	1.2	.2	.1						9.
.....												
VARIABLE												
CALM	////////////////////											20.
TOTALS	31.0	27.7	14.5	5.0	1.5	.1		.2	.1			100.

TOTAL NUMBER OF OBSERVATIONS 849

NO
8

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: FEB HOURS: 06-08

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.3	1.5	1.2			.2	.1			13.0	10.7	9.0
1.2	.5	.1							4.9	8.9	8.5
									1.9	2.9	2.0
									1.5	3.6	4.0
									2.1	3.1	3.0
.1									2.8	4.3	3.5
2.4	.6								11.0	7.0	6.0
2.5	.7								13.5	6.8	6.0
									6.4	4.4	4.5
.5									4.8	4.3	4.0
.3	.5								8.2	5.9	5.0
3.3	1.2	.2	.1						9.7	9.7	9.5
									20.1	////////////////	
14.5	5.0	1.5	.1		.2	.1			100.0	5.7	6.0
TOTAL NUMBER OF OBSERVATIONS										849	

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: FEB HOURS: 09-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.4	2.8	4.9	2.2	.8	.7	.2					13.0
020-040	.9	1.8	2.0	.4	.2	.1						5.4
050-070	2.0	.5	.5	.1								3.1
(E) 080-100	.9	.2										1.1
110-130	1.5	.5										2.0
140-160	1.5	1.2	.7									3.4
(S) 170-190	3.4	4.0	2.6	.9	.1							11.0
200-220	3.9	6.1	3.8	1.2								15.0
230-250	2.6	3.4	.9									6.9
(W) 260-280	2.7	2.7	.9									6.3
290-310	2.9	2.8	1.4	.7	.1							9.0
320-340	1.3	4.4	4.1	.9	.2							11.9
VARIABLE												
CALM	////////////////////										13.0	
TOTALS	25.0	30.4	21.8	6.4	1.4	.8	.2					100.0

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: FEB HOURS: 09-11

WIND SPEED	WIND SPEED IN KNOTS					TOTAL %	MEAN WIND	MEDIAN WIND
	14-19	20-24	25-29	30-34	35-39			
4-9	2.2	.8	.7	.2		13.2	12.4	12.0
10-14	.4	.2	.1			5.4	9.5	9.5
15-19	.1					3.1	5.2	4.0
20-24						1.2	3.5	3.0
25-29						2.0	3.4	3.0
30-34						3.4	5.7	5.0
35-39	.9	.1				11.1	7.7	7.0
40-49	1.2					15.0	7.9	8.0
50-64						6.9	5.9	5.0
65-69						6.4	6.0	6.0
70-74	.7	.1				8.0	7.2	6.0
75-79	.9	.2				11.0	9.3	9.0
80-84						13.4		
85-89	6.4	1.4	.8	.2		100.0	7.1	8.0
TOTAL NUMBER OF OBSERVATIONS						849		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: FEB HOURS: 12-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							GE 65	TOTAL %		
	1-4	5-9	10-14	15-19	20-24	25-29	30-34			35-39	40-49
(N) 350-010	2.7	5.1	6.2	2.5	1.6	.4					18.5
020-040	2.2	2.4	1.2	.4	.1	.2					6.5
050-070	.5	1.3									1.8
(E) 080-100	1.1	.9									2.0
110-130	1.5	.2	.2								2.0
140-160	.3	1.3	.9								3.5
(S) 170-190	2.1	5.2	4.7	1.3	.4						13.7
200-220	1.4	6.8	2.8	1.3	.8						13.2
230-250	1.3	3.7	2.1	.2							7.3
(W) 260-280	1.5	2.5	1.4	.1							5.5
290-310	.9	2.4	3.3	1.2	.1						7.9
320-340	1.4	4.4	3.3	1.8	.6						11.4
VARIABLE											
CALM	////////////////////										6.7
TOTALS	17.4	36.7	26.1	8.8	3.6	.6					100.0

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: FEB HOURS: 12-14

WIND DIRECTION	WIND SPEED IN KNOTS						TOTAL %	MEAN WIND	MEDIAN WIND
	10-14	15-19	20-24	25-29	30-34	35-39			
12	6.2	2.5	1.6	.4			18.5	11.1	10.0
7	1.2	.4	.1	.2			6.5	7.6	6.0
4							1.3	6.0	6.0
3							2.0	3.9	4.0
3	.2						2.0	3.9	3.0
5	.9						3.5	6.9	7.0
9	4.7	1.3	.4				13.7	9.3	9.0
0	2.6	1.3	.8				13.2	9.8	8.0
7	2.1	.2					7.3	7.8	8.0
7	1.4	.1					5.5	7.1	7.0
10	3.3	1.2	.1				7.9	10.1	10.0
10	3.3	1.8	.6				11.4	10.2	9.0
////							6.7	////	////
8	26.1	3.3	3.6	.5			100.0	8.5	8.0

TOTAL NUMBER OF OBSERVATIONS 849

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 73
MONTH: FEB HOURS: 15-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.7	3.1	4.7	1.4	1.9	.4						19.2
020-040	3.1	6.6	2.6		.2	.1						12.6
050-070	1.3	1.8	.1									3.2
(E) 080-100	.7	.4										1.1
110-130	.7	.6										1.3
140-160	1.8	2.7	.8									5.3
(S) 170-190	1.8	5.4	4.6	1.8	.5							14.0
200-220	.3	4.7	3.7	.9	.6							10.7
230-250	1.4	2.2	1.4	.1		.2						5.4
(W) 260-280	.7	2.1	1.5	.1								4.7
290-310	1.2	2.1	2.4	.9	.1							6.7
320-340	1.2	4.2	4.2	1.8	.2							11.7
.....												
VARIABLE												
CALM	////////////////////											4.1
TOTALS	17.6	40.9	26.0	7.0	3.5	.7						100.0

TOTAL NUMBER OF OBSERVATIONS 849

SP

JUL PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI		PERIOD OF RECORD: AUG 73 - JUL 88									
TIME: + 5		MONTH: FEB HOURS: 15-17									
WIND SPEED IN KNOTS											
9.	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
7.	1.4	1.9	.4						19.2	9.9	8.0
4.		.2	.1						12.6	7.2	6.0
3.									3.2	4.7	5.0
4.									1.1	3.4	3.0
6.									1.3	4.5	4.0
9.									5.3	6.5	6.0
10.	1.8	.5							14.0	9.7	9.0
3.	.9	.6							10.7	10.2	9.0
7.	.1		.2						5.4	8.3	8.0
9.	.1								4.7	7.2	6.5
10.	.9	.1							6.7	9.4	10.0
...	1.8	.2							11.7	10.1	10.0
///									4.1	///	///
8.	7.0	3.5	.7						100.0	8.4	8.0
TOTAL NUMBER OF OBSERVATIONS 849											

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERS.
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AU
MONTH: FEB HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	4.7	4.9	3.2	1.3	1.1	.1					
020-040	4.7	3.8	.5		.4						
050-070	4.6	2.5									
(E) 080-100	2.4	.4									
110-130	.2	.1									
140-160	2.2	3.1	.2								
(S) 170-190	2.4	5.1	2.4	1.9	.7	.1					
200-220	2.1	4.7	1.2	.6	.6						
230-250	1.2	1.2	.2	.4							
(W) 260-280	1.6	.2	.7								
290-310	3.2	3.1	2.0	.5	.1						
320-340	2.0	4.7	3.1	1.3	.2						
VARIABLE											
CALM	////////////////////										
TOTALS	32.2	34.4	14.1	6.0	3.1	.2					

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: FEB HOURS: 18-20

		WIND SPEED IN KNOTS								TOTAL	MEAN	MEDIAN					
		10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND				
0	0	3.2	1.3	1.1	.1						15.5	8.4	7.0				
1	0	.5		.4							9.3	5.5	4.0				
2	0										7.1	4.0	4.0				
3	0										2.7	3.3	3.0				
4	0										1.1	2.7	2.0				
5	0	.2									5.5	5.3	6.0				
6	0	2.4	1.9	.7	.1						12.5	9.3	8.0				
7	0	1.4	.6	.6							9.8	8.4	8.0				
8	0	.2	.4								3.5	6.8	6.0				
9	0	.7									2.6	5.5	4.0				
10	0	2.0	.5	.1							9.8	7.2	6.0				
11	0	4.1	1.3	.2							11.3	8.8	8.0				
////////////////////////////////////											10.2	////////////////////////////////////					
////////////////////////////////////											14.1	6.0	3.1	.2	100.0	6.5	6.0
TOTAL NUMBER OF OBSERVATIONS											849						

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: FEB HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.2	3.8	4.1	1.3	.9							13.3
020-040	2.4	1.1	.7		.4							4.5
050-070	1.9	.6	.1									2.6
(E) 080-100	1.4	.1										1.5
110-130	2.1	.1										2.2
140-160	2.1	2.1	.2									4.5
(S) 170-190	2.9	6.0	2.4	.7	.6							12.6
200-220	4.1	3.3	3.1	1.4	.1							12.0
230-250	2.0	1.2	.2	.1								3.5
(W) 260-280	2.4	2.0	.2									4.6
290-310	3.2	2.8	1.4	.9								8.4
320-340	3.1	4.0	2.2	.6	.4							10.2
.....												
VARIABLE												
CALM	////////////////////											20.0
TOTALS	30.8	27.1	14.6	5.0	2.4							100.0

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: FEB HOURS: 21-23

WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		%	WIND	WIND
4.1	1.3	.9								13.3	9.4	9.0
.7		.4								4.5	6.6	4.0
.1										2.6	4.1	3.5
										1.5	3.3	3.0
										2.2	3.4	3.0
.2										4.5	5.2	5.0
2.4	.7	.6								12.6	8.2	7.0
3.1	1.4	.1								12.0	8.0	8.0
.2	.1									3.5	4.8	4.0
.2										4.6	4.6	4.0
1.4	.9									8.4	7.1	6.0
2.2	.6	.4								10.2	7.8	7.0

20.0

14.6 5.0 2.4 100.0 5.8 6.0

TOTAL NUMBER OF OBSERVATIONS 849

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: FEB HOURS: A

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TO
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	
(N) 350-010	2.9	4.5	4.4	1.6	1.1	.2	.0	.1	.0		14
020-040	2.0	2.7	1.3	.3	.3	.1					6
050-070	1.6	1.0	.1	.0							2
(E) 080-100	1.1	.4									1
110-130	1.3	.3	.0								1
140-160	1.7	1.9	.5	.0							4
(S) 170-190	3.0	4.8	3.1	.9	.3	.0					12
200-220	3.5	5.0	3.1	.9	.3						12
230-250	2.1	2.3	.7	.1		.0					5
(W) 260-280	2.7	1.9	.7	.0							5
290-310	2.7	2.9	1.6	.6	.1						8
320-340	1.9	3.8	3.1	1.2	.3	.0	.0				10
VARIABLE											
CAL	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	14
TOTALS	26.4	31.5	18.6	5.6	2.4	.3		.1			100

TOTAL NUMBER OF OBSERVATIONS 6792

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: FEB HOURS: ALL

WIND SPEED IN KNOTS											
10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
4.4	1.6	1.1	.2	.0	.1	.0			14.9	10.2	10.0
1.3	.3	.3	.1						6.6	7.6	7.0
.1	.0								2.8	4.4	4.0
									1.5	3.5	3.0
.0									1.7	3.6	3.0
.5	.0								4.2	5.7	5.0
3.1	.9	.3	.0						12.2	8.2	8.0
3.1	.9	.3							12.8	8.0	8.0
.7	.1		.0						5.2	6.0	5.0
.7	.0								5.3	5.3	5.0
1.6	.6	.1							8.0	7.3	6.0
3.1	1.2	.3	.0	.0					10.3	9.3	9.0

//////////////////////////////////// 14.5 //////////////////////////////////

18.6 5.6 2.4 .3 .1 100.0 6.7 7.0

TOTAL NUMBER OF OBSERVATIONS 6792

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: FEB HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.1	6.3	8.3	3.2	.9	.2						22.0
020-040	3.4	4.4	3.0	.3	.2							11.2
050-070	1.6	1.0	.1									2.7
(E) 080-100	1.6	.8										2.3
110-130	1.6	.6	.1									2.3
140-160	2.1	3.4	1.4	.1								6.9
(S) 170-190	2.3	4.8	3.9	1.3	.5							12.8
200-220	2.6	5.1	2.5	.8	.5							11.5
230-250	1.7	1.1	.1									2.9
(W) 260-280	1.9	.5										1.5
290-310	1.5	1.0	1.2	1.4								5.0
320-340	1.0	3.1	4.8	2.2	.2							11.4
VARIABLE												
CALM	////////////////////										7.4	
TOTALS	23.5	32.1	25.4	9.3	2.3	.2						100.0

TOTAL NUMBER OF OBSERVATIONS 1671

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: FEB HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS),
AND/OR
1500 TO 3000 FEET (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND DIRECTION	WIND SPEED IN KNOTS							TOTAL	MEAN WIND	MEDIAN WIND
	14-19	20-24	25-29	30-34	35-39	40-49	50-64			
0-35	.3	3.2	.9	.2				22.0	10.4	10.0
36-70	.0	.3	.2					11.2	7.4	7.0
71-105	.1							2.7	4.4	4.0
106-140								2.3	3.7	4.0
141-175	.1							2.3	4.3	4.0
176-210	.4	.1						6.9	6.6	6.0
211-245	.9	1.3	.5					12.8	9.2	9.0
246-280	.5	.8	.5					11.5	8.5	8.0
281-315	.1							2.9	4.5	4.0
316-350								1.5	3.9	4.0
351-385	.2	1.4						5.0	9.8	10.0
386-420	.1	2.2	.2					11.4	10.8	11.0
421-455								7.4		
456-490	.4	9.3	2.3	.2				100.0	8.0	8.0

TOTAL NUMBER OF OBSERVATIONS 1671

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAR HOURS: 00-02

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.3	3.5	6.6	2.8	1.6	.6	.1					18.6
020-040	1.5	3.3	1.9	.9	.2							7.8
050-070	1.3	1.2	.2									2.7
(E) 080-100	1.0	.1	.3									1.4
110-130	1.0	1.7	.2									2.9
140-160	.8	1.2	.8									2.7
(S) 170-190	3.3	4.7	2.3	1.0	.8							12.6
200-220	3.8	5.7	1.8	.9	.1							12.3
230-250	1.7	1.4	.3									3.4
(W) 260-230	1.3	.9	.3		.1							3.1
290-310	2.6	3.3	.5	.1	.1	.1						6.8
320-340	1.3	3.2	3.4	.2								8.2
.....												
VARIABLE												
CALM	////////////////////											17.5 /
TOTALS	23.4	30.2	19.1	5.9	2.9	.7	.1					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI		PERIOD OF RECORD: AUG 78 - JUL 88									
TO UTC: + 5		MONTH: MAR HOURS: 00-02									
WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
6.5	2.8	1.6	.6	.1					18.6	11.6	12.0
1.9	.9	.2							7.8	8.8	8.0
.2									2.7	4.8	5.0
.3									1.4	5.2	4.0
.2									2.9	6.0	6.0
.8									2.7	7.4	6.0
2.3	1.0	.8							12.6	8.6	8.0
1.2	.9	.1							12.3	7.1	6.0
.3									3.4	5.3	4.5
.3		.1							3.1	5.1	4.0
.5	.1	.1	.1						6.8	6.1	5.0
3.4	.2								8.2	8.5	8.0
									17.5		
19.1	5.9	2.9	.7	.1					100.0	6.8	7.0
TOTAL NUMBER OF OBSERVATIONS										930	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAR HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.4	3.5	4.7	3.4	1.6	.4	.4					16.6
020-040	.9	3.9	1.9	.5	.2							7.4
050-070	1.1	1.3	.5									2.9
(E) 080-100	.9	.6	.3	.1								1.8
110-130	.3	1.2	.1									2.0
140-160	.3	2.3	.2	.1								2.9
(S) 170-190	2.3	5.7	1.9	1.3	.3							12.0
200-220	4.1	4.3	2.4	.4								11.2
230-250	2.5	.4	.3									3.2
(W) 260-280	2.9	1.0	.4	.1								4.4
290-310	2.5	2.7	.5	.2								5.9
320-340	2.5	4.4	3.0	.5	.2							10.5
VARIABLE												
CALM	////////////////////										18.9	
TOTALS	23.6	31.3	16.2	6.6	2.3	.4	.4					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAR HOURS: 03-05

WIND SPEED IN KNOTS											
10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
4.7	3.4	1.6	.4	.4					16.6	12.1	11.0
1.9	.5	.2							7.4	8.5	8.0
.5									2.9	6.0	6.0
.3	.1								1.8	6.5	6.0
.1									2.0	5.4	5.0
.2	.1								2.9	7.1	8.0
1.9	1.3	.3							12.0	8.2	7.5
2.4	.4								11.2	6.6	6.0
.3									3.2	4.4	4.0
.4	.1								4.4	4.8	4.0
.5	.2								5.9	5.7	5.0
3.0	.5	.2							10.6	8.1	8.0
									18.9		
15.2	6.6	2.3	.4	.4					100.0	6.5	7.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 71
MONTH: MAR HOURS: 06-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS									TOTAL %		
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49		50-64	GE 65
(N) 350-010	1.9	3.3	5.8	2.8	1.8	.3	.5	.1				17.1
020-040	2.2	3.4	2.2	.6	.2							3.6
050-070	1.1	1.0										2.0
(E) 080-100	.6	1.2	.5									2.4
110-130	.9	.9	.5									2.2
140-160	1.0	1.1	.9									2.8
(S) 170-190	3.9	3.4	3.4	.9	.1							11.7
200-220	4.3	4.1	2.4	.4								11.2
230-250	2.0	1.1	.3	.3								3.6
(W) 260-280	2.2	1.7										3.9
290-310	2.5	2.9	.8		.1							6.2
320-340	1.4	3.3	3.9	1.0								9.6
VARIABLE												
CALM	////////////////////										18.6	
TOTALS	23.9	27.9	20.6	6.0	2.2	.3	.5	.1				100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TC: + 5 MONTH: MAR HOURS: 06-08

WIND SPEED IN KNOTS											
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
7	2.8	1.8	.3	.5	.1				17.1	12.5	12.0
4	.6	.2							8.6	7.9	7.0
4									2.0	4.7	4.0
6									2.4	6.7	6.0
6									2.2	6.8	8.0
4									2.8	6.5	6.5
6	.9	.1							11.7	8.0	8.0
5	.4								11.2	6.7	6.5
4	.3								3.8	5.8	4.0
6									3.9	4.3	4.0
2		.1							6.2	6.2	5.0
0	1.0								9.6	9.3	10.0
////////////////////////////////////									18.6	////////////////////////////////////	
6	5.0	2.2	.3	.5	.1				100.0	6.7	7.0
TOTAL NUMBER OF OBSERVATIONS 930											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: MAR HOURS: 09-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS									TOTAL %		
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49		50-64	GE 65
(N) 350-010	1.6	6.3	6.9	5.8	2.4	.9	.2					24.1
020-040	1.2	3.0	2.7	1.3								8.2
050-070	1.9	2.2	.8									4.9
(E) 080-100	1.2	.8	.2									2.2
110-130	.4	1.8	.1									2.4
140-160	1.1	2.3	1.5	.1								4.9
(S) 170-190	2.3	4.9	4.6	1.7	.1							13.7
200-220	1.8	4.4	2.9	1.1	.2							10.4
230-250	1.1	2.2	1.5	.3	.3	.1						5.5
(W) 260-280	.9	2.4	.5									3.8
290-310	.5	2.6	1.3	.6								5.1
320-340	.6	2.7	4.6	1.4	.1							9.5
VARIABLE												
CALM	////////////////////										5.6	
TOTALS	14.5	35.5	27.7	12.3	3.1	1.0	.2					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 CO: + 5 MONTH: MAR HOURS: 09-11

WIND SPEED IN KNOTS

WIND	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND	
12	5.8	2.4	.9	.2					24.1	12.9	12.0	
6	1.3								8.2	9.2	9.0	
5									4.8	6.0	6.0	
5									2.2	5.0	4.0	
7									2.4	6.3	7.0	
6	.1								4.9	7.5	7.5	
4	1.7	.1							13.7	9.4	9.0	
4	1.1	.2							10.4	8.7	8.0	
6	.3	.3	.1						5.5	8.5	7.0	
6									3.8	6.9	7.0	
1	.6								5.1	9.4	8.0	
1	1.4	.1							9.5	10.7	10.0	
6	////////////////////								5.6	////////////////		
6	12.3	3.1	1.0	.2					100.0	9.2	9.0	
0	TOTAL NUMBER OF OBSERVATIONS 930											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL
 LST TO UTC: + 5 MONTH: MAR HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND SPEED	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64			GE 65
(N) 350-010	1.8	4.6	8.3	6.6	2.7	.9	.3					25.4	13.0
020-040	1.7	5.7	4.1	.5								12.3	8.0
050-070	1.3	2.0	.4	.1								3.9	6.0
(E) 090-100	.5	1.3	.1	.2								2.2	7.0
110-130	.6	1.8	.2									2.7	6.0
140-160	1.1	2.3	1.5	.1	.1							5.1	7.0
(S) 170-190	2.2	5.5	5.3	2.8	.5							16.3	10.0
200-220	.5	2.2	3.5	1.3	.9							8.5	12.0
230-250	.4	1.3	1.4	.3	.1	.1						4.2	9.0
(A) 260-280	.5	1.0	1.5	.5	.2							3.9	10.0
290-310	.5	1.5	2.7	.3	.2							5.3	10.0
320-340	.3	2.0	3.4	1.5	.3							7.7	11.0

VARIABLE

CALM	////////////////////										2.7	///	
TOTALS	11.3	31.9	32.4	14.3	5.1	1.0	.3					100.0	10.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: + 5 MONTH: MAR HOURS: 12-14

		WIND SPEED IN KNOTS					TOTAL %	MEAN WIND	MEDIAN WIND		
14	15-19	20-24	25-29	30-34	35-39	40-49				50-64	GE 65
.3	6.6	2.7	.9	.3					25.4	13.3	13.0
.1	.5								12.3	8.2	8.0
.4	.1								3.9	6.1	5.0
.1	.2								2.2	7.2	6.5
.2									2.7	6.1	7.0
.5	.1	.1							5.1	7.9	8.0
.3	2.8	.6							16.3	10.4	10.0
.5	1.3	.9							8.5	12.0	12.0
.4	.3	.1	.1						4.2	9.6	8.0
.5	.5	.2							3.9	10.2	10.0
.7	.3	.2							5.3	10.4	10.0
.4	1.5	.3							7.7	11.6	12.0
									//////////////////////////////////// 2.7 //////////////////////////////////////		
.4	14.3	5.1	1.0	.3					100.0	10.3	10.0
TOTAL NUMBER OF OBSERVATIONS										930	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAR HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	
(N) 350-010	.8	5.9	7.3	4.7	2.9	.5	.3					23.0
020-040	1.6	10.3	7.1	.8	.1							19.9
050-070	1.4	2.5	.6									4.5
(F) 080-100	.4	1.6	.7									2.3
110-130	1.0	1.2										2.2
140-160	1.2	3.4	1.9	.4								7.0
(S) 170-190	1.3	4.0	4.7	3.1	.3	.1						13.5
200-220	.2	2.2	3.4	1.8	.5							8.2
230-250	.5	.9	1.2	.1								2.7
(W) 260-280	.5	.5	.5	.1	.6	.1						2.5
290-310	.1	1.9	2.7	.6	.2							5.6
320-340	.1	1.5	3.1	1.5	.2							6.5
VARIABLE												
CALM	////////////////////											2.3
TOTALS	9.1	35.9	33.2	13.1	4.5	.7	.3					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI		PERIOD OF RECORD: AUG 78 - JUL 88										
TIME ZONE: + 5		MONTH: MAR HOURS: 15-17										
WIND SPEED IN KNOTS												
	0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
0-14	7.3	4.7	2.9	.5	.3					23.0	13.2	12.0
15-19	7.1	.8	.1							19.9	8.8	8.0
20-24	.6									4.5	6.4	6.0
25-29	.2									2.3	6.7	6.0
30-34										2.2	5.0	5.5
35-39	1.0	.4								7.0	8.2	8.0
40-49	4.7	3.1	.3	.1						13.5	11.4	11.0
50-64	3.4	1.8	.5							8.2	11.9	12.0
GE 65	1.2	.1								2.7	8.6	7.0
TOTAL	2.5	.1	.6	.1						2.5	12.3	10.0
MEAN	2.7	.6	.2							5.6	11.1	10.0
MEDIAN	3.1	1.5	.2							6.5	11.9	10.5
										2.3		
TOTAL	13.2	13.1	4.8	.7	.3					100.0	10.3	10.0
TOTAL NUMBER OF OBSERVATIONS 930												

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AU
 LST TO UTC: + 5 MONTH: MAR HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	2.7	4.5	5.3	3.7	1.6	.4	.5	.1			
020-040	3.9	10.4	4.5	.3	.1						
050-070	3.4	2.7	.1								
(E) 080-100	1.9	1.9									
110-130	.4	1.5									
140-160	1.3	3.3	1.3	.4							
(S) 170-190	.9	4.4	5.7	1.5	.6						
200-220	1.1	2.5	1.7	.5	.1						
230-250	.4	.5	1.3	.1							
(W) 260-280	.5	.9	.6	.2	.1						
290-310	.6	2.0	2.0	.3							
320-340	.6	3.8	4.2	1.0							
.....											
VARIABLE											
CALM	////////////////////////////////////										
TOTALS	17.6	39.0	27.2	5.0	2.5	.4	.5	.1			1
.....											
TOTAL NUMBER OF OBSERVATIONS 930											
.....											

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: MAR HOURS: 18-20

WIND SPEED IN KNOTS						TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49			
3.7	1.6	.4	.5	.1		18.8	12.1	11.0
.3	.1					19.1	7.5	7.0
						6.2	4.4	4.0
						3.9	4.6	4.5
						1.9	6.0	7.0
.4						7.3	7.7	8.0
1.5	.6					13.1	10.6	10.0
.5	.1					6.0	8.7	7.0
.1						2.4	9.1	10.5
.2	.1					2.4	8.6	8.5
.3						5.1	9.3	9.0
1.0						9.6	9.8	10.0
////////////////////////////////////						4.2	////////////////////////////////////	
3.0	2.5	.4	.5	.1		100.0	8.6	8.0
TOTAL NUMBER OF OBSERVATIONS						930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAR HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.0	5.1	3.8	3.0	1.4	1.0	.2					17.4
020-040	1.7	4.2	1.7	1.1	.2							8.9
050-070	1.2	1.0	.1									2.3
(F) 080-100	1.0	1.5	.1	.1								2.7
110-130	1.2	1.4	.5									3.1
140-160	2.3	1.7	1.1	.2								5.3
(S) 170-190	2.0	5.1	4.4	1.4	.6							14.4
200-220	2.0	3.9	3.2									9.1
230-250	.9	1.0	.5		.1							2.5
(W) 260-280	2.2	1.0	.2									3.3
290-310	1.7	2.3	.5	.8								5.3
320-340	2.5	4.9	2.5	.6								10.5
.....												
VARIABLE	////////////////////////////////////											15.2 /
CALM	////////////////////////////////////											15.2 /
TOTALS	22.5	33.1	18.6	7.2	2.3	1.0	.2					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
C: + 5 MONTH: MAR HOURS: 21-23

WIND SPEED IN KNOTS								TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
3.0	1.4	1.0	.2					17.4	11.5	10.0
1.1	.2							8.9	8.4	8.0
								2.3	5.0	4.0
.1								2.7	5.7	5.0
								3.1	6.0	5.0
.2								5.3	6.4	5.0
1.4	.6							14.4	9.3	8.5
								9.1	7.4	8.0
	.1							2.5	7.5	8.0
								3.3	4.2	3.0
.3								5.3	7.3	6.0
.6								10.5	7.6	7.0
////////////////////////////////////								15.2	////////////////////////////////////	
7.2	2.3	1.0	.2					100.0	7.1	7.0
TOTAL NUMBER OF OBSERVATIONS								930		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: MAR HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.2	4.7	6.1	4.1	2.0	.6	.3	.0				20.1
020-040	1.8	5.5	3.3	.8	.1							11.5
050-070	1.6	1.7	.3	.0								3.7
(E) 080-100	.9	1.1	.2	.1								2.3
110-130	.8	1.4	.2									2.4
140-160	1.1	2.2	1.2	.2	.0							4.7
(S) 170-190	2.4	4.7	4.1	1.7	.4	.0						13.4
200-220	2.2	3.7	2.7	.8	.2							9.6
230-250	1.2	1.2	.9	.1	.1	.0						3.5
(W) 260-280	1.4	1.2	.5	.1	.1	.0						3.4
290-310	1.4	2.4	1.4	.4	.1	.0						5.6
320-340	1.2	3.2	3.5	1.0	.1							9.0
VARIABLE												
CALM	////////////////////										10.6	
TOTALS	18.2	33.0	24.4	9.3	3.1	.6	.3					100.0

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 C: + 5 MONTH: MAR HOURS: ALL

WIND SPEED IN KNOTS						TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	35-39	40-49			
4.1	2.0	.6	.3	.0		20.1	12.5	12.0
.3	.1					11.5	8.3	8.0
.0						3.7	5.4	5.0
.1						2.3	5.8	5.0
						2.4	6.0	6.0
.2	.0					4.7	7.5	7.0
1.7	.4	.0				13.4	9.5	9.0
.4	.2					9.6	8.4	8.0
.1	.1	.0				3.5	7.4	6.0
.1	.1	.0				3.4	6.8	5.0
.4	.1	.0				5.6	8.1	7.0
1.0	.1					9.0	9.5	10.0

//////////////////////////////////// 10.6 //////////////////////////////////

9.3 3.1 .6 .3 100.0 8.2 8.0

TOTAL NUMBER OF OBSERVATIONS 7440

OPERATING LOCATION "A"
USAF/TAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAR HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	
(N) 350-010	2.5	7.5	11.5	9.8	3.8	.2		35.3
020-040	2.4	7.1	6.9	2.1	.3			18.8
050-070	1.5	1.3	.5	.1				3.5
(E) 080-100	1.1	1.4	.1	.1				2.7
110-130	.6	1.4	.2					2.2
140-160	.9	2.1	1.9	.3				5.3
(S) 170-190	1.4	3.3	4.0	1.6	.7	.1		11.0
200-220	.7	2.0	2.7	.7				6.1
230-250	.4	.2	.2	.2				.9
(W) 260-280	.5	.4	.1					1.0
290-310	.6	1.3	.1					2.0
320-340	.4	3.2	3.4	1.2	.1			8.3
VARIABLE								
CALM	////////////////////							2.9
TOTALS	13.5	31.2	31.6	16.1	4.9	.3		100.0

TOTAL NUMBER OF OBSERVATIONS 1873

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
ELEVATION: + 5 MONTH: MAR HOURS: ALL

WIND SPEEDS LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
WIND SPEEDS (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS				TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34			
9.8	3.8	.2		35.3	12.6	13.0
2.1	.3			18.8	9.4	9.0
.1				3.5	5.8	5.0
.1				2.7	5.5	5.0
				2.2	6.0	6.0
.3				5.3	8.4	8.0
1.6	.7	.1		11.0	10.9	10.0
.7				6.1	9.6	10.0
.2				.9	7.6	5.5
				1.0	5.4	5.0
				2.0	6.6	7.0
1.2	.1			8.3	10.6	10.0
////////////////////////////////////				2.9	////////////////////////////////	
16.1	4.9	.3		100.0	10.1	10.0

TOTAL NUMBER OF OBSERVATIONS 1873

OPERATING LOCATION "AM"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: APR HOURS: 0

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TO	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.4	6.3	4.1	2.1	1.0	.1						17
020-040	2.7	6.0	2.6	1.1	.3	.1						12
050-070	.3	1.2										1
(E) 080-100	.4	.3										
110-130	.4	1.9	.6									2
140-160	.6	2.2	.3	.1								3
(S) 170-190	1.7	5.3	2.1									9
200-220	3.6	5.1	1.7	.4								10
230-250	1.4	1.0										2
(W) 260-280	1.2	.4	.2									1
290-310	4.0	2.2		.1	.2	.1						6
320-340	3.6	2.4	1.1	.3	.3	.2						8
.....												
VARIABLE												
CALM	////////////////////											21
TOTALS	23.3	35.3	12.7	4.1	1.8	.5						100

TOTAL NUMBER OF OBSERVATIONS 900

IN

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

02

STATION: K. I. SAWYER AFB MI
TIME: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 00-02

WIND SPEED IN KNOTS			TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29			
2.1	1.0	.1	17.6	9.3	8.0
1.1	.3	.1	12.8	8.3	7.0
			1.6	5.2	5.0
			.8	4.0	3.0
			2.9	7.1	7.0
.1			3.2	6.8	6.0
			9.6	7.5	8.0
.4			10.8	6.8	6.0
			2.4	4.8	4.0
			1.9	4.9	4.0
.1	.2	.1	6.7	5.4	4.0
.3	.3	.2	8.0	6.9	5.0
////////////////////////////////////			21.9	////////////////////////////////	
4.1	1.8	.5	100.0	5.8	6.0
TOTAL NUMBER OF OBSERVATIONS			900		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: APR HOURS: 03-09

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.4	5.7	4.1	3.1	1.0	.1						18.4
020-040	2.3	5.8	2.7	.6								11.8
050-070	1.4	1.1		.1								2.7
(E) 080-100	.4	.3		.1	.1							1.8
110-130	.3	1.6	.2	.1								2.2
140-160	.7	1.8	.4									2.9
(S) 170-190	3.3	2.3	2.9		.1							9.1
200-220	4.9	5.9	.4	.3								11.6
230-250	1.9	1.9										3.8
(W) 260-280	1.4	.5										2.0
290-310	2.3	1.3	.2	.4	.2							5.4
320-340	1.9	3.8	1.4	.2	.3							7.7
VARIABLE												
CALM	////////////////////////////////////										20.7	
TOTALS	26.6	33.6	12.3	4.9	1.7	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 CO: + 5 MONTH: APR HOURS: 03-05

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
3.1	1.0	.1						18.4	9.6	8.0
.6								11.8	7.5	7.0
.1								2.7	5.1	4.0
.1	.1							1.8	6.5	5.0
.1								2.2	7.6	8.0
								2.9	6.2	6.0
	.1							9.1	6.9	7.0
.3								11.6	5.7	6.0
								3.8	4.7	4.5
								2.0	4.1	4.0
.4	.2							5.4	6.3	4.0
.2	.3							7.7	7.7	6.0

//////////////////////////////////// 20.7 //////////////////////////////////////
 4.9 1.7 .1 100.0 5.7 6.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 75
 LST TO UTC: + 5 MONTH: APR HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	6.0	6.7	5.2	3.2	1.3							22.4
020-040	2.0	3.6	2.4	.9	.2							9.1
050-070	.9	1.8		.1								2.8
(E) 090-100	.7	1.4										2.1
110-130	.6	1.2	.4	.3								2.6
140-160	.7	2.4	.4									3.6
(S) 170-170	2.4	3.0	2.3	.2	.1							8.1
200-220	4.1	4.9	1.4	.3	.1							10.9
230-250	1.6	2.3	.1									4.0
(W) 260-280	1.7	1.1	.4									3.2
290-310	2.0	2.2	.3	.1	.6							5.2
320-340	3.1	2.3	2.1	.8	.2	.1						8.7
VARIABLE												
CALM	////////////////////										17.3	
TOTALS	25.8	32.9	15.0	5.9	2.5	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: APR HOURS: 06-08

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
3.2	1.3							22.4	9.0	8.0
.9	.2							9.1	8.6	8.0
.1								2.8	6.0	5.0
								2.1	5.4	6.0
.3								2.6	7.9	6.0
								3.6	6.6	6.0
.2	.1							8.1	7.7	8.0
.3	.1							10.9	6.3	6.0
								4.0	5.2	5.0
								3.2	5.4	4.0
.1	.6							5.2	7.0	5.0
.3	.2	.1						8.7	8.2	7.5
								17.3		
5.9	2.5	.1						100.0	6.3	7.0
TOTAL NUMBER OF OBSERVATIONS								900		

OPERATING LOCATION "A"
 USAF TAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - J
 LST TO UTC: + 5 MONTH: APR HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %	M #
	1-4	5-9	10-14	15-19	20-24	25-29	30-34		
(N) 350-010	2.6	6.2	8.4	4.0	2.3	.2		23.8	1
020-040	1.9	7.7	5.9	1.2	.1			16.7	
050-070	1.1	1.3	.3					2.6	
(E) 080-100	2.1	1.4	.3					3.9	
110-130	1.7	.9	.7	.2				3.4	
140-160	.9	2.3	1.0	.1				4.3	
(S) 170-190	1.7	4.7	4.0	1.1	.2			11.7	
200-220	1.3	4.6	2.4	.9	.2	.1		9.4	
230-250	.7	.6	1.9					3.0	
(W) 260-280	.6	1.0	1.2	.1				2.9	
290-310	.9	2.4	1.2	.3				4.8	
320-340	1.0	2.4	3.0	1.3	.6	.3		8.7	1
VARIABLE									
CALM	////////////////////							4.7	//
TOTALS	16.4	35.5	30.1	9.1	3.4	.6		100.0	

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: APR HOURS: 09-11

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
4.0	2.3	.2						23.8	11.5	11.0
1.2	.1							16.7	8.8	8.0
								2.6	5.7	6.0
								3.9	4.8	4.0
.2								3.4	6.4	5.0
.1								4.3	7.4	8.0
1.1	.2							11.7	9.3	9.0
.8	.2	.1						9.4	8.8	8.0
								3.0	9.0	10.0
.1								2.9	8.6	9.0
.3								4.8	8.1	7.0
1.3	.6	.3						8.7	11.6	11.0
								4.7		
9.1	3.4	.6						100.0	8.9	9.0
TOTAL NUMBER OF OBSERVATIONS								900		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: APR HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	
(N) 350-010	1.2	5.1	9.7	4.2	2.8	.1		23.1
020-040	1.9	8.6	9.4	1.2	.1			21.1
050-070	1.4	2.0	.7					4.1
(E) 080-100	1.0	1.0						2.0
110-130	2.0	.9	1.1					4.0
140-160	1.4	3.0	2.9	.7				8.0
(S) 170-190	1.0	4.0	5.1	1.6	.4			12.1
200-220	1.1	2.9	1.2	.8	.4			7.0
230-250	.8	.8	.6	.7	.1			2.9
(W) 260-280	.6	.9	1.0	.1				2.6
290-310	.2	1.4	1.2	.6	.3			3.8
320-340	.4	1.2	3.1	1.3	.9			7.0
VARIABLE								
CALM	////////////////////							2.3
TOTALS	12.9	31.8	36.6	11.2	5.0	.1		100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: APR HOURS: 12-14

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
4.2	2.8	.1						23.1	12.6	12.0
1.2	.1							21.1	9.4	10.0
								4.1	5.6	5.0
								2.0	4.5	4.5
								4.0	6.3	4.5
								8.0	9.0	9.0
1.5	.4							12.1	10.4	10.0
.8	.4							7.0	9.5	9.0
.7	.1							2.9	9.9	8.5
.1								2.6	8.3	9.0
.6	.3							3.8	10.6	10.0
1.3	.9							7.0	12.6	12.0

//////////////////////////////////// 2.3 //////////////////////////////////////
11.2 5.0 .1 100.0 9.9 10.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: APR HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	.3	4.1	10.9	5.4	1.6							22.3
020-040	2.0	13.9	10.2	2.0	.2							28.3
050-070	1.2	3.4	1.2									5.9
(E) 080-100	.3	1.1	.1									2.0
110-130	.7	1.2	.7	.1								2.7
140-160	.7	3.0	2.2	1.1	.3	.1						7.4
(S) 170-190	.3	4.3	5.4	1.7	.1							11.9
200-220	.7	1.4	1.7	.4								4.2
230-250	.3	1.0	.8	.4	.2							2.8
(W) 260-280		.6	.4	.2								1.2
290-310	.3	.9	1.7	.6	.3							3.8
320-340	.3	.3	2.9	1.7	.7	.2	.2					6.8
.....												
VARIABLE												
CALM	////////////////////											.7
TOTALS	7.6	35.7	38.2	13.6	3.4	.3	.2					100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME: + 5 MONTH: APR HOURS: 15-17

WIND SPEED IN KNOTS				TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34			
	1.6			22.3	12.8	13.0
2.0	.2			28.3	9.4	9.0
				5.9	6.8	6.0
				2.0	5.4	5.0
.1				2.7	7.6	8.0
1.1	.3	.1		7.4	10.3	10.0
1.7	.1			11.9	10.6	10.0
.4				4.2	9.5	9.5
.4	.2			2.8	11.0	11.0
.2				1.2	10.6	12.0
.6	.3			3.8	11.6	11.0
1.7	.7	.2	.2	6.8	13.8	13.0
////////////////////////////////////				.7	////////////////////////////////	
13.6	3.4	.3	.2	100.0	10.5	10.0
TOTAL NUMBER OF OBSERVATIONS				900		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: APR HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.2	9.7	7.7	2.6	.6							22.7
020-040	3.7	12.6	4.2	.7	.7							21.8
050-070	4.6	4.2	.1	.1								9.0
(E) 080-100	1.4	1.4	.6	.1								3.6
110-130	1.6	1.1	.4									3.1
140-160	1.4	4.6	1.9	.4								6.3
(S) 170-190	.3	5.0	4.6	1.2	.2							11.3
200-220	.4	.8	1.6	.3								3.1
230-250	.2	.6	.7		.1							1.6
(W) 260-280	.7	.3	.2									1.2
290-310	.8	1.2	.4	.2	.2							2.9
320-340	.9	3.3	3.9	1.1	.3	.3						9.9

VARIABLE

CALM	////////////////////										1.6	
TOTALS	19.2	44.8	26.3	6.7	2.1	.3						100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 CO: + 5 MONTH: APR HOURS: 18-20

WIND SPEED IN KNOTS				TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	%	WIND	WIND
2.6	.6			22.7	9.7	9.0
.7	.7			21.8	7.9	7.0
.1				9.0	5.0	4.0
.1				3.6	5.9	5.0
				3.1	5.2	4.5
.4				6.3	7.3	7.0
1.2	.2			11.3	10.1	10.0
.3				3.1	9.5	10.0
	.1			1.6	9.1	9.5
				1.2	5.1	4.0
.2	.2			2.9	8.4	6.5
1.1	.3	.3		9.9	10.4	10.0
////////////////////////////////////				1.6	////////////////////////////////	
6.7	2.1	.3		100.0	8.3	8.0
TOTAL NUMBER OF OBSERVATIONS				900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. T. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: APR HOURS: 2

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	5.2	7.1	4.6	2.2	.2							19.3
020-040	3.3	5.4	1.8	.6	1.0							12.1
050-070	2.6	1.2	.3	.1								4.2
(E) 080-100	1.9	.9	.2									3.0
110-130	1.3	1.4	.1									2.8
140-160	1.6	2.7	.4	.2								4.9
(S) 170-170	2.6	6.2	4.2	.4								13.4
200-220	1.3	3.2	1.4	.2								6.1
230-250	1.6	.3	.1	.1								2.1
(W) 260-280	.9	.9	.2									2.0
290-310	3.2	2.4	.1									5.7
320-340	3.7	3.9	1.1	.2	.4	.2						9.5
VARIABLE												
CALM	////////////////////										14.0	
TOTALS	29.7	35.6	14.6	4.0	1.5	.2						100.0
TOTAL NUMBER OF OBSERVATIONS 900												

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 89
 TIME ZONE: UTC: + 5 MONTH: APR HOURS: 21-23

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
	2.2	.2							19.3	8.1	7.5
1.4	.6	1.0							12.1	7.9	6.0
.3	.1								4.2	4.4	4.0
.2									3.0	4.5	4.0
.1									2.9	4.9	5.0
.4	.2								4.9	6.3	6.0
.2	.4								13.4	7.9	8.0
1.4	.2								6.7	7.1	6.5
.1	.1								2.1	4.1	3.0
.2									2.0	5.6	5.5
.1									5.8	4.2	4.0
1.1	.2	.4	.2						9.6	7.0	5.5
////////////////////////////////////									14.0	////////////////////////////////////	
.5	4.0	1.5	.2						100.0	5.9	6.0
TOTAL NUMBER OF OBSERVATIONS 900											

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727436 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: APR HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	
(N) 350-010	3.2	6.4	6.8	3.4	1.3	.1		21.2
020-040	2.5	7.9	4.9	1.0	.3	.0		16.7
050-070	1.7	2.0	.3	.1				4.1
(E) 080-100	1.1	1.1	.2	.0	.0			2.4
110-130	1.1	1.3	.5	.1				3.0
140-160	1.0	2.3	1.2	.3	.0	.0		5.3
(S) 170-190	1.7	4.5	3.8	.8	.2			10.9
200-220	2.2	3.6	1.5	.5	.1	.0		6.0
230-250	1.1	1.1	.5	.2	.1			2.8
(W) 260-280	.9	.7	.5	.1				2.1
290-310	1.8	1.8	.7	.3	.2	.0		4.8
320-340	1.9	2.5	2.3	.9	.5	.2	.0	9.3
VARIABLE								
CALM	////////////////////							10.4
TOTALS	20.2	35.7	23.3	7.7	2.7	.3		100.0

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: + 5 MONTH: APR HOURS: ALL

WIND SPEED IN KNOTS					TOTAL %	MEAN WIND	MEDIAN WIND
-14	15-19	20-24	25-29	30-34			
0.0	3.4	1.3	.1		21.2	10.4	10.0
4.0	1.0	.3	.0		16.7	8.6	8.0
.3	.1				4.1	5.5	5.0
.2	.0	.0			2.4	5.2	5.0
.0	.1				3.0	6.5	6.0
1.0	.3	.0	.0		5.3	8.0	7.0
3.0	.3	.2			10.9	8.9	9.0
1.0	.5	.1	.0		8.0	7.4	7.0
.0	.2	.1			2.8	7.1	6.0
.5	.1				2.1	6.6	6.0
.7	.3	.2	.0		4.8	7.3	6.0
1.3	.0	.5	.2	.0	8.3	9.6	8.5

//////////////////////////////////// 10.4 //////////////////////////////////
 3.3 7.7 2.7 .3 100.0 7.7 8.0

TOTAL NUMBER OF OBSERVATIONS 7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: APR HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	2.6	8.3	11.2	6.0	2.0	.1						30.2
020-040	2.3	6.8	5.4	1.9	1.1	.1						17.6
050-070	.9	2.4	.3	.2								3.8
(E) 080-100	1.3	2.4	.4	.1								4.2
110-130	.6	1.5	1.2									3.3
140-160	.9	3.0	1.5	.2	.2	.1						5.9
(S) 170-190	.7	4.9	3.3	.8	.2							10.1
200-220	.7	2.5	1.0	.1								4.5
230-250	.4	.4	.1									.8
(W) 260-280	.5	.6	.3									1.4
290-310	1.5	1.5	.9	.3								4.2
320-340	1.4	2.9	3.8	.9	.8	.5	.2					10.5

VARIABLE

CALM // 3.5

TOTALS 14.2 37.2 29.4 10.5 4.3 .8 .2 100.0

TOTAL NUMBER OF OBSERVATIONS 1107

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
1 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%			
1.2	6.0	2.0	.1						30.2	11.2	11.0	
6.4	1.9	1.1	.1						17.6	9.9	9.0	
.3	.2								3.8	6.3	5.5	
.4	.1								4.2	6.0	6.0	
1.2									3.3	7.4	8.0	
1.9	.2	.2	.1						5.9	8.6	8.0	
3.3	.8	.2							10.1	9.3	9.0	
1.0	.1								4.5	7.1	7.0	
.1									.8	5.9	5.0	
.3									1.4	6.3	6.0	
.2	.3								4.2	7.1	6.0	
7.0	.9	.8	.5	.2					10.5	11.7	11.0	
////////////////////////////////////										3.5	////////////////////////////////	
7.4	10.5	4.3	.8	.2					100.0	9.3	9.0	
TOTAL NUMBER OF OBSERVATIONS 1107												

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: MAY HOURS: 00-02

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	8.4	5.9	3.2	.6								18.2
020-040	1.4	2.8	.9	.1								5.2
050-070	.8	.9										1.6
(E) 080-100	.4	.1										.5
110-130	.3	.8	.2									1.3
140-160	1.3	1.6	.6									3.5
(S) 170-190	3.1	6.6	2.3	.2								12.2
200-220	5.5	4.7	1.6									11.8
230-250	1.8	.8	.6									3.2
(W) 260-280	.6	1.4	.9	.1								3.0
290-310	1.3	1.2	.6									3.1
320-340	3.0	1.7	.5									5.3
.....												
VARIABLE												
CALM	////////////////////											31.1
TOTALS	27.9	29.5	11.4	1.0								100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
: + 5 MONTH: MAY HOURS: 00-02

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
.6								18.2	6.1	5.0
.1								5.2	6.9	7.0
								1.6	4.9	5.0
								.5	2.6	2.0
								1.3	6.2	6.0
								3.5	6.2	6.0
.2								12.2	6.7	6.0
								11.8	5.2	5.0
								3.2	5.4	4.0
.1								3.0	7.5	7.5
								3.1	5.7	6.0
								5.3	4.6	4.0
								31.1	4.1	6.0
1.0								100.0	4.1	6.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAY HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	6.2	6.3	4.2	.5	.1							17.5
020-040	2.3	3.4	.9	.1								6.6
050-070	.6	.5										1.2
(E) 080-100	.2	.2										.4
110-130	.3	.5										.9
140-160	1.4	2.3	.6									4.3
(S) 170-190	3.2	5.2	1.2	.2								9.8
200-220	4.7	5.7	.3	.1								11.3
230-250	3.3	.8	.3	.1								4.5
(W) 260-280	2.3	1.1	.6	.2								4.2
290-310	1.9	.9	.3	.1								3.2
320-340	2.4	2.2	1.4	.1								6.0
.....												
VARIABLE												
CALM	////////////////////										30.1	
TOTALS	29.5	29.1	10.2	1.5	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 C: + 5 MONTH: MAY HOURS: 03-05

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
.5	.1							17.5	6.9	6.0
.1								6.6	6.0	6.0
								1.2	4.0	4.0
								.4	5.5	5.0
								.9	4.8	5.0
								4.3	6.1	6.0
.2								9.8	6.3	6.0
.1								11.3	5.2	5.0
.1								4.5	4.3	3.0
.2								4.2	5.6	4.0
.1								3.2	5.3	4.0
.1								6.0	6.3	6.0
								30.1		
1.5	.1							100.0	4.2	5.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: MAY HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.5	6.8	5.1	.8	.3	.1						16.6
020-040	3.0	4.7	1.9	.2	.1							10.0
050-070	1.1	.5										1.6
(E) 080-100	.5	.9										1.4
110-130	.3	1.5	.2									2.0
140-160	1.4	1.9	.4									3.8
(S) 170-190	2.9	5.7	2.2	.3								11.1
200-220	5.8	5.1	1.5	.2								13.5
230-250	2.3	1.6	.9									4.7
(W) 250-280	3.1	1.5	.3	.1								5.1
290-310	2.7	1.4	.3									4.4
320-340	1.5	2.6	2.2	.2								6.5
.....												
VARIABLE												
CALM	////////////////////////////////////										19.4	
TOTALS	29.1	34.2	15.0	1.8	.4	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: MAY HOURS: 06-08

WIND SPEED IN KNOTS

15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.8	.3	.1						16.6	8.2	8.0
.2	.1							10.0	6.9	7.0
								1.6	3.9	4.0
								1.4	5.4	6.0
								2.0	6.4	6.0
								3.3	6.0	6.0
.3								11.1	7.0	7.0
.2								13.5	5.4	4.5
								4.7	5.4	5.0
.1								5.1	4.8	4.0
								4.4	4.6	3.0
.2								6.5	7.5	7.0
								19.4		
1.3	.4	.1						100.0	5.2	6.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: MAY HOURS: 09-1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.0	4.7	6.0	3.2	.8							15.7
020-040	3.2	8.8	5.1	1.1								18.2
050-070	2.2	1.7	.3									4.2
(E) 080-100	1.5	1.2										2.7
110-130	1.2	.9										2.0
140-160	2.2	3.4	1.4									7.0
(S) 170-190	1.6	7.3	5.4	1.1	.2							15.6
200-220	3.5	5.4	2.6	.6								12.2
230-250	1.5	2.3	.6	.6								5.1
(W) 260-280	1.1	2.2	1.6	.1								4.9
290-310	.3	2.7	1.2									4.6
320-340	.5	2.6	1.7	.6	.1							5.6
.....												
VARIABLE												
CALM	////////////////////											2.3
TOTALS	20.3	43.2	25.9	7.3	1.1							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC + 5 MONTH: MAY HOURS: 09-11

WIND SPEED IN KNOTS												
	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
0.0		3.2	.8							15.7	11.0	10.0
0.1		1.1								18.2	8.0	8.0
0.3										4.2	4.9	4.0
										2.7	4.4	4.0
										2.0	4.4	4.0
0.4										7.0	6.4	6.0
0.4		1.1	.2							15.6	9.1	9.0
0.6		.6								12.2	7.1	7.0
0.7		.6								5.1	7.8	7.0
0.8		.1								4.9	7.7	8.0
1.0										4.6	7.4	8.0
0.7		.0	.1							5.6	9.5	9.0
////////////////////////////////////										2.3	////////////////////////////////////	
0.8		7.3	1.1							100.0	8.0	8.0
TOTAL NUMBER OF OBSERVATIONS										930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAY HOURS: 12-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	.3	3.0	5.7	2.4	1.3	.2						13.3
020-040	2.7	10.3	11.1	1.2	.1							25.4
050-070	2.2	3.8	1.2	.1								7.2
(E) 080-100	1.0	1.1	.1									2.2
110-130	1.1	1.3	.6									3.0
140-160	1.1	3.3	1.8	.1	.1							6.5
(S) 170-190	1.9	5.9	7.6	.9	.5	.3						17.2
200-220	.3	3.3	2.7	1.1	.5							8.4
230-250	.9	1.7	1.9	.4								4.4
(W) 260-280	.5	1.3	.3	.1								2.4
290-310	.8	1.8	1.4									4.0
320-340	.4	1.9	2.0	1.0								5.4
.....												
VARIABLE												
CALM	////////////////////											.8
TOTALS	14.3	38.2	36.4	7.3	2.5	.6						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: MAY HOURS: 12-14

WIND SPEED IN KNOTS											
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.7	2.4	1.3	.2						13.3	12.3	12.0
.1	1.2	.1							25.4	9.1	9.0
.2	.1								7.2	6.5	6.0
.1									2.2	5.3	5.5
.5									3.0	6.1	6.0
.4	.1	.1							6.5	7.6	7.0
.5	.9	.5	.3						17.2	10.2	10.0
.7	1.1	.5							8.4	10.3	10.0
.1	.4								4.4	9.0	10.0
.3	.1								2.4	6.7	6.5
.4									4.0	7.7	8.0
.0	1.0								5.4	10.1	10.0
////////////////////////////////////									.8	////////////////////////////////////	
.4	7.3	2.5	.5						100.0	9.2	9.0
TOTAL NUMBER OF OBSERVATIONS 930											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SP
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. T. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 79 - JUL
 MONTH: MAY HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64			GE 65
(N) 350-010	.2	3.3	6.0	3.2	1.0							13.8	12.
020-040	2.7	16.3	14.7	1.5								35.3	9.
050-070	1.7	6.1	1.3	.2								9.4	7.
(E) 090-100	.2	1.1	.1	.1								1.6	6.
110-130	.4	.8	.1									1.3	5.
140-160	1.1	3.7	4.7	.3	.1							9.9	9.
(S) 170-190	.8	4.4	6.7	1.3	.4							13.5	10.
200-220	.2	2.6	1.5	.5	.4							5.3	13.
230-250	.5	.8	1.1	.3	.1	.1						2.9	3.
(W) 260-280		.4	1.0		.1							1.5	10.
290-310	.5	.5	.4		.1							1.6	7.
320-340	.2	1.6	1.4	.4	.1							3.8	10.
VARIABLE													
CALM	////////////////////////////////////										.2	///	
TOTALS	3.6	41.6	39.0	7.8	2.3	.1						100.0	9.
TOTAL NUMBER OF OBSERVATIONS 230													

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: MAY HOURS: 15-17

DIRECTION	WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
0	3.2	1.0							13.8	12.3	12.0
7	1.5								35.3	9.1	9.0
8	.2								9.4	7.1	7.0
1	.1								1.6	6.9	6.0
1									1.3	5.3	5.0
7	.3	.1							9.9	9.5	10.0
7	1.3	.4							13.5	10.3	11.0
	.5	.4							5.3	10.5	9.0
1	.3	.1	.1						2.9	9.9	10.0
		.1							1.5	10.5	10.0
4		.1							1.6	7.9	6.0
8	.4	.1							3.8	10.3	10.0

//////////////////////////////////// .2 //////////////////////////////////////
 7.8 2.3 .1 100.0 9.7 9.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - J
LST TO UTC: + 5 MONTH: MAY HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS						TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29		
(N) 350-010	3.4	6.2	4.9	1.3	.6		16.6	
020-040	5.7	17.4	5.7	.8			29.6	
050-070	5.6	4.7	.3				10.6	
(E) 080-100	1.5	.9					2.5	
110-130	1.1	.9					1.9	
140-160	2.9	6.3	2.6	.2			12.0	
(S) 170-190	1.0	5.1	4.5	1.7	.4		12.7	
200-220	.3	1.0	1.3	.3			3.2	
230-250	.1	1.0	.6	.1			1.8	
(W) 260-280	.2	.4	.6				1.3	
290-310	.2	1.1	.9				2.2	
320-340	.3	.9	1.4	.3	.1		3.0	
.....								
VARIABLE								
CALM	////////////////////							2.6
TOTALS	22.7	45.9	22.8	4.7	1.1		100.0	
.....								
TOTAL NUMBER OF OBSERVATIONS 930								
.....								

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 18-20

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
0.9	1.3	.6							16.6	8.9	8.0
5.7	.8								29.6	7.2	7.0
.3									10.6	4.8	4.0
									2.5	4.0	3.0
									1.9	4.8	4.0
2.6	.2								12.0	7.0	7.0
1.5	1.7	.4							12.7	10.2	10.0
1.3	.3								3.2	9.1	9.5
1.6	.1								1.8	8.8	9.0
.5									1.3	8.8	10.0
.7									2.2	8.3	8.5
1.4	.3	.1							3.0	10.3	10.0
									2.6	////////	////////
2.7	4.7	1.1							100.0	7.5	7.0
TOTAL NUMBER OF OBSERVATIONS										930	

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: MAY HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	9.9	6.7	2.7	.9								20.1
020-040	3.2	2.7	1.1	.1								7.1
050-070	2.3	1.0	.1									3.3
(E) 080-100	1.1	.3										1.4
110-130	1.0	.8										1.7
140-160	3.0	2.8	.5									6.3
(S) 170-190	4.5	9.0	3.3	.6	.1							17.6
200-220	2.5	2.9	1.0	.1								6.5
230-250	1.4	.5	.5	.1								2.6
(W) 260-280	1.3	.3		.1								1.7
290-310	.9	1.1	.1									2.0
320-340	2.8	2.5	.4	.1								5.8
VARIABLE												
CALM	////////////////////										23.6	
TOTALS	33.9	30.6	9.7	2.0	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAY HOURS: 21-23

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
2.7	.9									20.1	5.7	5.0
1.1	.1									7.1	5.6	5.0
.1										3.3	3.8	4.0
										1.4	3.1	2.0
										1.7	4.3	4.0
.5										6.3	5.4	5.0
4.3	.6	.1								17.6	7.1	7.0
1.0	.1									6.5	6.0	6.0
.1	.1									2.6	5.6	4.0
	.1									1.7	3.9	2.0
.1										2.0	5.2	5.0
.4	.1									5.8	5.4	5.0

//////////////////////////////////// 23.8 //////////////////////////////////////
 4.7 2.0 .1 100.0 4.4 5.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 79
 LST TO UTC: + 5 MONTH: MAY HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.2	5.4	4.7	1.5	.5	.0						16.5
020-040	3.0	3.3	5.1	.6	.0							17.2
050-070	2.0	2.4	.4	.0								4.9
(E) 080-100	.3	.7	.0	.0								1.6
110-130	.7	.9	.1									1.8
140-160	1.8	3.2	1.6	.1	.0							6.7
(S) 170-190	2.4	6.1	4.1	.8	.2	.0						13.7
200-220	3.1	3.3	1.6	.4	.1							9.0
230-250	1.5	1.1	.8	.2	.0	.0						3.7
(W) 260-280	1.2	1.1	.7	.1	.0							3.0
290-310	1.1	1.3	.7	.0	.0							3.1
320-340	1.4	2.0	1.4	.3	.0							5.2
VARIABLE												
CALM	////////////////////										13.8	
TOTALS	23.2	36.3	21.2	4.1	.8							100.0

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: MAY HOURS: ALL

WIND SPEED IN KNOTS											
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
.7	1.6	.5	.0						16.5	8.6	8.0
.1	.6	.0							17.2	3.0	8.0
.4	.0								4.9	5.5	5.0
.0	.0								1.6	4.7	4.0
.1									1.8	5.4	5.0
.0	.1	.0							6.7	7.1	7.0
.1	.8	.2	.0						13.7	8.6	8.0
.0	.4	.1							9.0	6.8	6.0
.0	.2	.0	.0						3.7	6.9	6.0
.7	.1	.0							3.0	6.6	6.0
.7	.0	.0							3.1	6.4	6.0
.0	.3	.0							5.2	7.7	7.0
									13.8		
.2	4.1	.8							100.0	6.5	7.0
TOTAL NUMBER OF OBSERVATIONS 7440											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: MAY HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	
(N) 350-010	2.9	10.8	9.9	3.0	1.6	.1		28.2
020-040	3.1	9.5	3.2	.8				15.6
050-070	2.1	.7						2.8
(E) 090-100	1.2	1.3		.1				2.7
110-130	1.1	2.2	.6					3.9
140-160	2.2	5.3	1.0					8.5
(S) 170-190	1.3	7.1	4.0	.4		.1		13.0
200-220	1.9	5.4	1.2	.2				8.8
230-250	.9	1.2	.4					2.6
(W) 260-280	.7	.4	.9	.1				2.1
290-310	.8	1.1	.2					2.1
320-340	.7	2.2	1.9	.4				5.2
VARIABLE								
CALM	////////////////////////////////////							4.6
TOTALS	18.9	46.2	23.3	5.0	1.6	.2		100.0

TOTAL NUMBER OF OBSERVATIONS 901

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: MAY HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
1 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
7.9	3.0	1.6	.1							28.2	10.3	10.0
1.2	.8									15.6	7.5	7.0
										2.8	3.7	3.0
	.1									2.7	5.1	5.0
.2										3.9	6.3	6.0
1.0										8.5	6.2	6.0
7.0	.4		.1							13.0	8.5	8.0
1.2	.2									8.8	6.8	6.0
.4										2.6	6.3	6.0
.9	.1									2.1	7.5	9.0
.2										2.1	6.1	6.0
1.0	.4									5.2	8.6	8.0
////////////////////////////////////										4.6	////////////////////////////////	
3.3	5.0	1.6	.2							100.0	7.7	8.0

TOTAL NUMBER OF OBSERVATIONS 901

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: JUN HOURS: 00-02

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	5.7	2.9	3.1	.1								11.8
020-040	1.1	1.2	.2									2.6
050-070	.9	.6										1.4
(E) 080-100	.2											.2
110-130	.7	.2										.9
140-160	1.0	1.1	.4									2.6
(S) 170-190	3.3	7.3	3.9	.2								15.2
200-220	7.2	7.2	2.1	.4								17.0
230-250	3.2	1.1	.1									4.4
(W) 260-280	3.3	1.1	.2									4.7
290-310	4.2	1.0										5.2
320-340	3.2	1.2	1.0									6.1
.....												
VARIABLE												
CALM	////////////////////////////////////											27.9
TOTALS	34.6	25.6	10.9	.7								100.0
.....												
TOTAL NUMBER OF OBSERVATIONS 900												
.....												

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: JUN HOURS: 00-02

WIND SPEED IN KNOTS

0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.1	.1								11.8	6.3	5.0
.2									2.6	5.0	5.0
									1.4	3.5	3.0
									.2	3.5	3.5
									.9	3.5	3.0
.4									2.6	6.1	7.0
3.5	.2								15.2	7.0	7.0
2.1	.4								17.0	5.8	5.0
.1									4.4	4.0	4.0
.2									4.7	3.9	3.0
									5.2	3.6	3.0
1.0									6.1	5.4	4.0
									27.9		
10.0	.7								100.0	4.0	5.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: JUN HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	
(N) 350-010	6.3	3.1	2.8	.2								12.4
020-040	1.7	2.6	.1		.1							4.4
050-070	.4	.1										.6
(E) 080-100		.1										.1
110-130	.4	.4										.9
140-160	.9	1.2	.4									2.6
(S) 170-190	4.6	6.0	2.3	.3								13.2
200-220	6.6	6.2	1.9	.2								14.9
230-250	3.4	1.3	.2									5.0
(W) 260-280	4.4	1.3	.2									6.0
290-310	5.2	2.4	.1									7.3
320-340	4.4	1.4	.3		.1							6.3
.....												
VARIABLE												
CALM	////////////////////////////////////											25.8
TOTALS	39.3	25.1	8.3	.7	.2							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
IC: + 5 MONTH: JUN HOURS: 03-05

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.2								12.4	5.9	4.0
	.1							4.4	5.9	5.0
								.6	3.4	3.0
								.1	5.0	5.0
								.9	4.6	5.0
								2.6	6.0	6.0
.3								13.2	6.7	6.0
.2								14.9	5.7	5.0
								5.0	3.9	3.0
								6.0	3.6	3.0
								7.3	4.0	4.0
	.1							6.3	4.2	3.0
								25.8	////////////////	
.7	.2							100.0	3.9	4.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: JUN HOURS: 06

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.2	4.8	3.0	.4	.2							11.6
020-040	2.3	4.2	.9	.2								7.6
050-070	1.0	.6	.1									1.7
(E) 080-100	.7	.2										.9
110-130	.7											.7
140-160	2.0	1.8	.6		.1							4.4
(S) 170-190	3.1	7.4	3.2	.3								14.1
200-220	5.6	3.4	3.6	.4								13.0
230-250	4.2	3.0	.8									8.0
(W) 260-280	3.8	2.6	.7									7.0
290-310	4.3	3.6	.9	.2								9.0
320-340	3.7	3.0	1.3									8.0
VARIABLE												
CALM	////////////////////										13.9	
TOTALS	34.6	34.6	15.1	1.5	.3							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 06-08

WIND SPEED IN KNOTS											
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
	.4	.2							11.7	7.5	8.0
.0									7.7	6.2	6.0
.1									1.7	4.1	3.0
									.9	3.3	3.0
									.7	2.8	2.5
.5		.1							4.4	6.1	5.0
.2	.3								14.1	7.2	7.0
.6	.4								13.0	6.5	5.0
.7									8.0	5.0	4.0
.7									7.0	4.8	4.0
.9	.2								9.0	5.4	5.0
.3									8.0	5.6	5.5
									13.9		
.1	1.5	.3							100.0	5.3	6.0
TOTAL NUMBER OF OBSERVATIONS 900											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: JUN HOURS: 09

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.6	6.0	4.3	1.3	.1							13.
020-040	2.4	6.2	2.9	.4								12.
050-070	2.2	2.6	.2									5.
(E) 080-100	1.3	.8										2.
110-130	.9	.8										1.
140-160	.9	1.2	1.1	.1								3.
(S) 170-190	2.4	5.0	6.1	1.2	.2							15.
200-220	2.8	4.4	5.4	1.3	.2							14.
230-250	2.1	4.6	2.3	.3	.3							9.
(W) 260-280	1.1	3.4	.9									5.
290-310	1.6	3.3	2.1	.4								7.
320-340	1.6	3.3	3.3	.3								8.
VARIABLE												
CALM	////////////////////										1.	
TOTALS	21.4	41.6	28.6	5.3	.8							100.

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TC: + 5 MONTH: JUN HOURS: 09-11

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
1.3	.1							13.3	9.2	9.0
.4								12.0	7.6	7.0
								5.0	5.0	5.0
								2.6	3.9	4.0
								1.7	4.5	4.0
.1								3.3	7.6	7.5
1.2	.2							15.0	9.3	10.0
1.3	.2							14.2	9.0	9.0
.3	.3							9.7	7.8	7.0
								5.4	6.8	6.0
.4								7.4	8.0	7.0
.3								8.6	8.4	8.0
								1.8		
5.3	.8							100.0	7.9	8.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: JUN HOURS: 12-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	.9	3.8	4.8	1.2								10.7
020-040	2.7	13.0	4.8	.6	.1							21.1
050-070	2.3	4.8	.9									8.0
(E) 080-100	.9	.7										1.6
110-130	1.4	.9	.2									2.6
140-160	.6	1.4	1.8	.5	.2							4.6
(S) 170-190	1.9	3.7	6.1	2.0	.3	.1						14.1
200-220	1.0	5.1	4.8	1.4	.4	.1						12.9
230-250	1.1	2.7	3.1	.7	.2							7.0
(W) 260-280	.4	1.6	1.4	.4	.1							4.0
290-310	.3	2.2	2.6	.4	.1							5.7
320-340	1.1	2.4	2.4	.4	.3							6.8
.....												
VARIABLE												
CALM	////////////////////											.3
TOTALS	14.6	42.3	32.9	7.7	1.7	.2						100.0

TOTAL NUMBER OF OBSERVATIONS 900

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: JUN HOURS: 12-14

WIND SPEED IN KNOTS				TOTAL	MEAN	MEDIAN				
5-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
								10.7	10.1	10.0
	.6	.1						21.1	7.9	8.0
								8.0	6.2	6.0
								1.6	4.4	4.0
								2.6	4.8	4.0
	.5	.2						4.6	10.0	10.0
1.0	.3	.1						14.1	10.4	10.0
1.4	.4	.1						12.9	10.2	10.0
.7	.2							7.8	9.2	10.0
.4	.1							4.0	9.1	9.5
.4	.1							5.7	9.6	10.0
.4	.3							6.8	9.4	9.0
								.3	////////////////	
7.7	1.7	.2						100.0	8.9	8.0
TOTAL NUMBER OF OBSERVATIONS 900										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: JUN HOURS: 18-20

DIRECTION (DEGPRES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.4	7.0	4.0	.3	.2							15.0
020-040	7.3	11.4	3.7	.2								22.7
050-070	4.9	4.8	.3									10.0
(E) 080-100	2.2	.9	.1									3.2
110-130	1.0	.7										1.7
140-160	1.1	4.2	3.2	.3								8.9
(S) 170-190	.9	5.9	5.4	1.6	.3							14.1
200-220	1.1	2.7	2.3	.9	.2							7.2
230-250	.9	1.3	.4		.2							2.9
(W) 260-280	.3	1.1	.4	.1								2.4
290-310	.3	2.4	2.2	.4								5.9
320-340	.6	1.4	1.8	.3								4.1
.....												
VARIABLE												
CALM	////////////////////											1.9
TOTALS	25.0	43.8	23.8	4.1	.9							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 18-20

WIND SPEED IN KNOTS

0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
4.0	.3	.2							15.0	7.4	7.0
3.7	.2								22.7	6.3	6.0
.3									10.0	4.9	5.0
.1									3.2	4.1	4.0
									1.7	4.1	4.0
3.2	.3								8.9	8.2	8.0
5.4	1.6	.3							14.1	10.0	10.0
2.3	.9	.2							7.2	9.5	9.0
.4		.2							2.9	7.5	7.0
.4	.1								2.4	7.1	6.5
2.2	.4								5.9	8.9	9.0
1.8	.3								4.1	9.0	10.0

////////////////////////////////////									1.9	////////////////////////////////////	
23.8	4.1	.9							100.0	7.3	7.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: JUN HOURS: 21-24

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	8.6	2.8	2.3	.6								14.2
020-040	3.1	2.1	.3	.2								5.8
050-070	1.8	.4										2.2
(E) 080-100	1.2	.2										1.4
110-130	1.2	.2										1.4
140-160	1.7	3.8	.4									5.9
(S) 170-190	4.9	9.4	4.7	.3								19.3
200-220	3.6	5.1	2.2	.1								11.0
230-250	1.7	.6	.2									2.4
(W) 260-280	2.2	.9										3.1
290-310	2.6	1.6	.2									4.3
320-340	4.0	2.1	1.1	.1								7.3
.....												
VARIABLE												
CALM	////////////////////											21.4
TOTALS	36.5	29.2	11.4	1.3								100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 C: + 5 MONTH: JUN HOURS: 21-23

WIND SPEED IN KNOTS								TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
.6								14.2	5.2	3.0
.2								5.8	5.2	4.0
								2.2	3.5	4.0
								1.4	2.8	2.0
								1.4	3.2	3.0
								5.9	5.9	6.0
.3								19.3	7.3	8.0
.1								11.0	6.4	6.0
								2.4	4.4	4.0
								3.1	3.6	3.0
								4.3	4.3	4.0
.1								7.3	5.1	4.0
////////////////////////////////////								21.4	////////////////////////////////	
1.3								100.0	4.4	5.0
TOTAL NUMBER OF OBSERVATIONS								900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: JUN HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.8	4.2	3.5	.7	.1	.0						12.3
020-040	2.9	7.3	2.8	.3	.0							13.4
050-070	2.0	2.3	.4									4.7
(E) 080-100	1.0	.5	.0									1.5
110-130	.9	.5	.1									1.4
140-160	1.1	2.2	1.3	.3	.1							4.9
(S) 170-190	2.9	6.0	4.5	1.1	.1	.0						14.6
200-220	3.6	4.7	3.3	.6	.2	.0						12.6
230-250	2.2	2.0	1.2	.2	.1	.0						5.7
(W) 260-280	2.1	1.6	.6	.1	.0							4.5
290-310	2.4	2.3	1.4	.3	.0							6.4
320-340	2.3	2.1	1.6	.2	.1							6.4
VARIABLE												
CALM	////////////////////										11.6	
TOTALS	27.2	35.7	20.7	4.0	.7							100.0

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: JUN HOURS: ALL

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
								%	WIND	WIND
.7	.1	.0						12.3	7.6	7.0
.3	.0							13.4	7.2	7.0
								4.7	5.4	5.0
								1.5	4.0	4.0
								1.4	4.3	4.0
.3	.1							4.9	7.8	8.0
1.1	.1	.0						14.6	8.5	8.0
.6	.2	.0						12.6	7.8	7.0
.2	.1	.0						5.7	6.7	6.0
.1	.0							4.5	5.8	5.0
.3	.0							6.4	6.7	6.0
.2	.1							6.4	7.0	6.0
								11.6	6.4	7.0
4.0	.7							100.0	6.4	7.0

TOTAL NUMBER OF OBSERVATIONS 7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: JUN HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING G

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOTAL %				
	1-4	5-9	10-14	15-19	20-24	25-29	30-34		35-39	40-49	50-64	GE 65
(N) 350-010	1.7	6.1	11.1	2.7	.8	.2						22.6
020-040	2.3	3.1	2.7	.7	.2							14.0
050-070	2.0	1.3										3.3
(E) 090-100	.3	.2										.5
110-130	.7	.3										1.5
140-160	.8	1.2	2.8	.5								5.3
(S) 170-190	2.2	6.5	7.5	.3								16.4
200-220	1.8	5.5	5.3	.5	.2							13.3
230-250	1.3	1.2	.5		.2							3.2
(W) 260-280	1.0	1.2	.3									2.5
290-310	1.0	1.2										2.2
320-340	2.0	4.5	2.5	.7	.7							10.3
VARIABLE												
CALM	////////////////////											5.0
TOTALS	17.1	37.8	32.7	5.4	2.1	.2						100.0

TOTAL NUMBER OF OBSERVATIONS 602

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: JUN HOURS: ALL

AT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS),
AND/OR
1 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
11.1	2.7	.8	.2						22.6	10.9	11.0
2.7	.7	.2							14.0	7.8	8.0
									3.3	4.0	4.0
									.5	4.3	3.0
									1.5	4.8	5.0
2.8	.5								5.3	9.7	10.0
7.5	.3								16.4	8.9	9.0
5.3	.5	.2							13.3	8.7	8.0
.5		.2							3.2	6.4	6.0
.3									2.5	5.5	5.0
									2.2	5.0	5.0
2.5	.7	.7							10.3	8.9	8.0
									5.0	////////	////////
2.7	5.4	2.1	.2						100.0	8.3	8.0

TOTAL NUMBER OF OBSERVATIONS 602

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JUL HOURS: 00-02

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.9	2.8	1.4									9.0
020-040	2.0	.9	.5									3.4
050-070	.9	.1										1.0
(E) 080-100	.9	.1										1.0
110-130	.6											.6
140-160	1.1	.5										1.6
(S) 170-190	5.9	2.9	1.4									10.2
200-220	8.6	7.0	2.3									17.8
230-250	4.0	2.5	.3									6.8
(W) 260-280	3.0	.9										3.9
290-310	2.6	1.4	.2									4.2
320-340	3.7	1.2	.2									5.1
VARIABLE												
CALM	////////////////////										35.4	
TOTALS	38.1	20.3	6.3									100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: JUL HOURS: 00-02

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
								9.0	5.1	4.0
								3.4	5.4	4.0
								1.0	3.0	3.0
								1.0	2.8	2.0
								.6	1.8	1.5
								1.6	3.7	3.0
								10.2	5.0	4.0
								17.8	5.4	5.0
								6.8	4.3	4.0
								3.9	3.0	2.5
								4.2	4.2	4.0
								5.1	3.7	2.0

35.4

100.0 3.0 4.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - J
LST TO UTC: + 5 MONTH: JUL HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	5.1	3.2	1.5	.1								9.9
020-040	1.6	.6	.3									2.6
050-070	.5	.3										.9
(E) 080-100	.8	.2										1.0
110-130	.4	.2										.6
140-160	.8	.3										1.1
(S) 170-190	4.0	3.2	1.4									8.6
200-220	8.4	6.2	.8	.1								15.5
230-250	3.8	2.0	.1									5.9
(W) 260-280	3.5	.5	.1									4.2
290-310	2.8	1.3										4.1
320-340	4.0	2.3	.5									6.8

.....												
VARIABLE												
CALM	////////////////////											38.9
TOTALS	35.7	20.3	4.7	.2								100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: JUL HOURS: 03-05

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
	.1									9.9	5.4	4.0
										2.6	5.0	4.0
										.9	4.4	4.0
										1.0	3.4	3.0
										.6	3.3	3.5
										1.1	4.0	4.0
										8.6	5.8	5.0
	.1									15.5	4.8	4.0
										5.9	4.1	4.0
										4.2	3.2	3.0
										4.1	3.5	3.0
										6.8	4.1	3.0
////////////////////////////////////										38.9	////////////////////////////////	
	.7	.2								100.0	2.8	4.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: JUL HOURS: 06-06

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.5	5.4	2.3	.3								11.5
020-040	2.3	1.2	.4									3.9
050-070	.8	.3										1.1
(E) 080-100	.4	.4										.9
110-130	.6	.3										1.0
140-160	.9	1.0										1.8
(S) 170-190	3.4	3.2	1.5									8.2
200-220	7.6	8.8	1.8									18.3
230-250	5.1	4.1										9.1
(W) 260-280	3.7	1.9										5.6
290-310	3.2	2.4	.1									5.7
320-340	4.6	2.9	.4									8.0
VARIABLE												
CALM	////////////////////										25.1	
TOTALS	36.1	31.9	6.5	.3								100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: JUL HOURS: 06-08

WIND SPEED IN KNOTS								TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
.3								11.5	6.8	7.0
								3.9	5.0	4.0
								1.1	3.9	4.0
								.9	3.5	4.0
								1.0	3.6	3.0
								1.8	4.7	5.0
								8.2	5.9	5.0
								18.3	5.5	5.0
								9.1	4.3	4.0
								5.6	3.8	3.0
								5.7	4.2	4.0
								8.0	4.5	4.0
								25.1		
.3								100.0	3.9	5.0
TOTAL NUMBER OF OBSERVATIONS								930		

OPERATING LOCATION "A"
 USAFETAC, ASHFVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: JUL HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.5	4.8	3.4	.5	.1							10.4
020-040	4.1	6.7	2.8									13.5
050-070	1.9	2.3	.2									4.9
(E) 080-100	1.5	.9										2.4
110-130	1.6	.8										2.4
140-160	1.5	1.6	.1									3.2
(S) 170-190	2.5	5.3	2.5	.3								10.5
200-220	2.6	9.6	4.1	.6								16.9
230-250	2.7	5.8	3.7	.2								12.4
(W) 260-280	2.3	4.4	1.2	.1								8.0
290-310	1.6	3.1	1.5	.1								6.3
320-340	1.4	2.8	1.5	.4								6.1
VARIABLE												
CALM	////////////////////										2.9	
TOTALS	25.2	48.6	21.0	2.2	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: JUL HOURS: 09-11

WIND SPEED IN KNOTS											
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
8	.5	.1							10.4	8.5	9.0
6									13.5	6.6	6.0
5									4.9	5.1	5.0
3									2.4	3.7	3.0
3									2.4	3.8	4.0
5									3.2	5.1	5.0
7	.3								10.5	7.3	7.0
7	.6								16.9	7.7	7.0
7	.2								12.4	7.7	8.0
6	.1								8.0	6.3	6.0
6	.1								6.3	6.9	7.0
7	.4								6.1	7.6	7.0
									2.9		
6	2.2	.1							100.0	6.8	7.0
TOTAL NUMBER OF OBSERVATIONS 930											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 1
 MONTH: JUL HOURS: 12

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							GE 65	TOT			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34			35-39	40-49	50-64
(N) 350-010	.5	2.3	4.4	.5								7.
020-040	3.1	13.4	5.6	.5								22.
050-070	2.9	4.3	.1									7.
(E) 080-100	1.1	1.1										2.
110-130	1.3	.6										1.
140-160	1.3	1.1	.3									2.
(S) 170-190	1.7	5.5	4.2	1.4	.1							12.
200-220	1.8	5.9	8.1	1.4	.1	.1						17.
230-250	1.9	3.2	3.5	.5								9.
(W) 260-280	.8	3.1	1.6	.3								5.
290-310	.6	2.0	2.3	.1								5.
320-340	.8	1.9	1.0	.2	.1							4.
VARIABLE												
CALM	////////////////////										1.	
TOTALS	17.8	44.4	31.1	4.9	.3	.1						100.

TOTAL NUMBER OF OBSERVATIONS 930

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: JUL HOURS: 12-14

WIND SPEED IN KNOTS										
0-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.5								7.7	10.2	10.0
.5								22.7	7.9	8.0
								7.3	5.5	6.0
								2.2	5.0	4.5
								1.9	3.6	3.5
								2.7	5.7	5.0
1.4	.1							12.9	9.0	9.0
1.4	.1	.1						17.4	9.7	10.0
.5								9.2	8.5	8.0
.3								5.8	8.0	8.0
.1								5.1	8.6	9.0
.2	.1							4.0	8.4	8.0
								1.1		
4.9	.3	.1						100.0	8.2	8.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 7
LST TO UTC: + 5 MONTH: JUL HOURS: 15

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	.3	3.7	3.3	.3								8.
020-040	2.2	17.6	10.0	.3								30.
050-070	2.4	5.9	1.3									10.
(E) 080-100	1.7	1.2										2.
110-130	.6	1.2	.1									1.
140-160	1.1	1.1	1.2									3.
(S) 170-190	.4	4.7	3.7	1.5	.2							10.
200-220	1.4	5.5	7.4	1.8								16.
230-250	.9	2.8	3.7	.2								7.
(W) 260-280	.3	1.5	.6	.1								2.
290-310	.4	1.8	.9	.2								3.
320-340	.2	.6	1.1	.2	.2							2.

VARIABLE

CALM	////////////////////////////////////																		
TOTALS	12.4	48.6	33.3	4.6	.4														100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TC: + 5 MONTH: JUL HOURS: 15-17

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
.3								8.1	9.1	9.0
.3								30.1	8.4	8.0
								10.5	6.5	6.0
								2.9	4.1	4.0
								1.9	5.3	5.0
								3.3	7.1	7.0
1.5	.2							10.5	10.0	10.0
1.8								16.1	9.9	10.0
.2								7.5	9.1	10.0
.1								2.6	7.5	7.0
.2								3.3	8.5	8.0
.2	.2							2.4	10.7	10.0

//////////////////////////////////// .6 //////////////////////////////////////
4.6 .4 100.0 8.5 8.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JUL HOURS: 18-2

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.2	5.9	1.3	.1								11.1
020-040	8.9	14.3	1.9									25.2
050-070	4.0	5.2	.4									9.6
(E) 080-100	2.5	1.0										3.4
110-130	1.3	.8										2.0
140-160	1.3	2.7	.3									4.3
(S) 170-190	1.5	4.7	5.8	.9								12.9
200-220	1.8	5.4	5.6	.5								13.4
230-250	1.1	3.2	1.5	.2								6.0
(W) 260-280	1.0	1.5	.3									2.8
290-310	.9	1.5	1.0	.3								3.7
320-340	1.2	1.5	1.0	.4	.1							4.2
VARIABLE												
CALM	////////////////////										1.3	
TOTALS	28.6	47.8	19.6	2.4	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 928

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: JUL HOURS: 18-20

WIND SPEED IN KNOTS												
	14-15	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.3		.1								11.1	6.6	6.0
.4										25.2	5.7	5.0
.5										9.6	5.0	5.0
.6										3.4	3.7	4.0
.7										2.0	3.8	4.0
.8										4.3	6.0	6.0
.9		.9								12.9	9.0	10.0
1.0		.5								13.4	8.7	9.0
1.1		.2								6.0	7.5	7.0
1.2										2.8	5.8	6.0
1.3		.3								3.7	7.6	7.5
1.4		.4	.1							4.2	8.1	8.0
1.5										1.3		
1.6	2.4		.1							100.0	6.7	6.0

TOTAL NUMBER OF OBSERVATIONS 928

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: JUL HOURS: 21-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	7.7	4.2	1.4									13.3
020-040	2.8	1.6	.4									4.9
050-070	1.9	.1	.1									2.2
(E) 080-100	1.6	.1										1.7
110-130	1.4	.8										2.2
140-160	3.0	1.6										4.6
(S) 170-190	4.9	7.8	3.5	.2								16.3
200-220	4.6	7.9	2.0									14.6
230-250	3.2	1.7	.1									5.1
(W) 260-280	1.6	.4	.2									2.3
290-310	1.9	1.5	.4									3.9
320-340	3.0	1.2										4.2
.....												
VARIABLE												
CALM	////////////////////										24.9	
TOTALS	37.6	28.9	8.1	.2								100.0

TOTAL NUMBER OF OBSERVATIONS 927

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
D UTC: + 5 MONTH: JUL HOURS: 21-23

WIND SPEED IN KNOTS		TOTAL	MEAN	MEDIAN
15-19	20-24	%	WIND	WIND
.4		13.3	4.7	4.0
.4		4.9	4.6	4.0
.1		2.2	3.0	2.0
		1.7	2.9	3.0
		2.2	3.5	3.0
		4.6	3.9	4.0
.5	.2	16.3	6.7	6.0
.0		14.6	6.0	6.0
.1		5.1	4.1	4.0
.2		2.3	4.0	4.0
.4		3.9	5.4	4.5
		4.2	3.7	3.0
////////////////////////////////////		24.9		
.1	.2	100.0	3.9	4.0
TOTAL NUMBER OF OBSERVATIONS		927		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: JUL HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.4	4.0	2.4	.2	.0							10.1
020-040	3.4	7.0	2.8	.1								13.3
050-070	1.9	2.5	.3									4.7
(E) 080-100	1.3	.6										1.9
110-130	1.0	.6	.0									1.6
140-160	1.4	1.2	.2									2.8
(S) 170-190	3.0	4.7	3.0	.5	.0							11.3
200-220	4.6	7.0	4.0	.6	.0	.0						16.2
230-250	2.8	3.2	1.6	.1								7.8
(W) 260-280	2.0	1.8	.5	.1								4.4
290-310	1.7	1.9	.8	.1								4.5
320-340	2.4	1.8	.7	.2	.1							5.1
VARIABLE												
CALM	////////////////////////////////////										16.3	
TOTALS	28.9	36.3	16.3	1.9	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 7435

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 LOC: + 5 MONTH: JUL HOURS: ALL

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
								%	WIND	WIND
.2	.0							10.1	6.8	6.0
.1								13.3	6.9	7.0
								4.7	5.3	5.0
								1.9	3.8	4.0
								1.6	3.8	4.0
								2.8	5.2	5.0
.5	.0							11.3	7.5	7.0
.6	.0	.0						16.2	7.2	7.0
.1								7.8	6.5	6.0
.1								4.4	5.3	5.0
.1								4.5	6.1	6.0
.2	.1							5.1	5.8	5.0
////////////////////////////////////								16.3	////////////////////////////////	
1.9	.1							100.0	5.5	6.0

TOTAL NUMBER OF OBSERVATIONS 7435

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JUL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.9	7.6	10.5	1.0	.2							21.1
020-040	3.0	4.9	3.0	.3								11.3
050-070	2.7	1.1	.3									4.1
(E) 080-100	2.5	.2										2.7
110-130	2.5	.6										3.2
140-160	2.2	2.1	.2									4.5
(S) 170-190	1.7	3.5	4.5	.6								10.3
200-220	3.2	6.4	3.5	.5								13.5
230-250	2.4	3.3										5.7
(W) 260-280	2.5	1.3		.2								4.0
290-310	1.6	1.1	.3									3.0
320-340	1.9	3.7	1.9	1.0	.2							8.6
VARIABLE												
CALM	////////////////////										7.9	
TOTALS	28.1	35.8	24.2	3.6	.4							100.0

TOTAL NUMBER OF OBSERVATIONS 629

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: JUL HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 1 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

	WIND SPEED IN KNOTS							TOTAL	MEAN	MEDIAN	
	0-14	15-19	20-24	25-29	30-34	35-39	40-49				50-64
9	0.5	1.0	.2						21.1	9.3	10.0
7	0.0	.3							11.3	7.0	6.0
4	.3								4.1	4.8	4.0
2									2.7	2.7	2.0
2									3.2	2.9	2.0
4	.2								4.5	4.9	4.5
8	4.5	.6							10.3	8.8	9.0
7	3.5	.5							13.5	7.4	8.0
4									5.7	4.7	5.5
4		.2							4.0	4.5	4.0
4	.3								3.0	4.8	4.0
8	1.4	1.0	.2						8.6	8.4	8.0
									7.9	//////////	
6	4.2	3.6	.4						100.0	6.6	7.0

TOTAL NUMBER OF OBSERVATIONS 629

OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSI
 USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AU
 LST TO UTC: + 5 MONTH: AUG HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	3.7	3.0	.2								
020-040	2.3	2.2	.3								
050-070	1.0	.2	.1								
(E) 080-100	.5										
110-130	.8	.4									
140-160	1.6	1.0	.1								
(S) 170-190	4.9	4.0	1.5	.3		.1					
200-220	8.6	7.8	2.7	.3							
230-250	3.8	1.7	.9								
(W) 260-280	5.2	1.2	.1								
290-310	4.3	1.0	.2								
320-340	2.9	1.0	.1	.1							

VARIABLE

CALM

TOTALS

40.1 23.5 6.3 .7 .1

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: AUG HOURS: 00-02

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
								6.9	4.8	4.0
								4.7	5.2	5.0
								1.3	3.8	3.0
								.5	3.2	3.0
								1.2	3.8	4.0
								2.7	4.8	4.0
.3		.1						10.9	6.1	5.0
.3								19.7	5.8	5.0
								6.2	4.7	4.0
								6.5	3.6	3.0
								6.0	3.4	3.0
.1								4.1	3.8	2.0
								29.4		
.7		.1						100.0	3.5	4.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: AUG HOURS: 03

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.8	3.5	.9	.1								9.
020-040	1.6	2.3	.2									4.
050-070	1.3	.4	.1									1.
(E) 080-100	.4	.2	.1									.
110-130	.3	.2										.
140-160	.6	1.5										2.
(S) 170-190	4.2	4.4	1.5	.2								10.
200-220	8.6	6.2	2.0	.1								17.
230-250	5.6	.9	.4									6.
(W) 260-280	4.2	1.6	.1									5.
290-310	5.3	.9		.1								6.
320-340	3.7	1.6	.6									5.
VARIABLE												
CALM	////////////////////										29.	
TOTALS	40.6	23.7	5.9	.5								100.
TOTAL NUMBER OF OBSERVATIONS											930	

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: AUG HOURS: 03-05

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.1								9.4	5.0	4.0
								4.1	5.4	5.0
								1.8	4.6	4.0
								.8	4.6	4.0
								.5	3.2	2.0
								2.2	5.3	6.0
.2								10.3	6.0	5.0
.1								17.0	5.3	4.0
								6.9	3.5	3.0
								5.9	3.9	4.0
.1								6.2	3.7	4.0
								5.9	4.5	4.0
								29.0		
.5								100.0	3.4	4.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: AUG HOURS: 0

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TO	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.7	4.6	2.0		.1							10
020-040	2.9	2.6	.9									6
050-070	.9	.5										1
(E) 080-100	.6	.3										1
110-130	1.0	.4										1
140-160	1.4	1.6	.2									3
(S) 170-190	2.4	4.5	2.0	.1								9
200-220	7.6	5.3	2.7	.1								15
230-250	4.2	2.9	.5									7
(W) 260-280	4.1	2.0										6
290-310	4.1	2.6	.4									7
320-340	3.2	2.2	1.1	.2								6
VARIABLE												
CALM	////////////////////											24
TOTALS	36.1	29.5	9.8	.4	.1							100

TOTAL NUMBER OF OBSERVATIONS 930

(ND)

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: AUG HOURS: 06-08

WIND SPEED IN KNOTS												
	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
2.0			.1							10.4	6.3	6.0
.9										6.3	5.3	5.0
										1.4	3.8	4.0
										1.0	3.6	4.0
										1.4	3.8	3.0
.2										3.2	5.2	6.0
2.0		.1								9.0	6.9	7.0
.7		.1								15.7	5.7	5.0
.5										7.6	4.5	4.0
										6.1	3.9	4.0
.4										7.1	4.7	4.0
1.1		.2								6.7	6.0	5.0
////////////////////										24.0	////////////////	
.9		.4	.1							100.0	4.1	5.0
TOTAL NUMBER OF OBSERVATIONS										930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: AUG HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.6	4.2	3.3	.6	.1							10.9
020-040	4.4	6.1	2.5									13.0
050-070	2.8	.6										3.4
(E) 080-100	1.9	.8										2.7
110-130	.6	1.1	.1									1.8
140-160	1.5	1.3	.3									3.1
(S) 170-190	1.3	5.3	2.8	.8								10.1
200-220	2.4	8.7	4.8	1.1	.1							17.1
230-250	2.9	6.0	2.8									11.7
(W) 260-280	.3	3.7	1.4									5.8
290-310	1.6	5.9	1.7		.1							9.4
320-340	1.2	3.9	2.4	.6	.1							8.2
VARIABLE												
CALM	////////////////////////////////////										2.8	
TOTALS	24.0	47.6	22.1	3.1	.4							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: AUG HOURS: 09-11

WIND SPEED IN KNOTS												
	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3		.6	.1							10.9	8.0	8.0
5										13.0	6.3	6.0
3										3.4	3.3	3.0
4										2.7	3.9	4.0
5										1.8	4.9	5.0
8										3.1	5.4	5.0
8										3.1	5.4	5.0
7		.8								10.1	8.4	8.0
7		1.1	.1							17.1	8.6	8.0
7										11.7	7.0	7.0
7										5.8	7.4	6.0
8										5.8	7.4	6.0
7			.1							9.4	7.0	7.0
7		.6	.1							8.2	8.7	8.0
7										2.8		
1		3.1	.4							100.0	7.1	7.0
TOTAL NUMBER OF OBSERVATIONS 930												

OPERATING LOCATION "AW"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: AUG HOURS: 12-1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.4	3.2	3.8	.2	.2							8.8
020-040	1.8	9.4	4.2	.1								15.5
050-070	3.0	3.9	1.1									8.0
(E) 080-100	1.5	1.5	.1									3.1
110-130	1.0	1.5	.2									2.7
140-160	.8	1.7	.9	.1								3.4
(S) 170-190	1.1	4.5	4.9	1.2								11.7
200-220	2.3	5.5	6.7	2.5	.6							17.5
230-250	1.9	4.6	2.6	.4	.2							9.8
(W) 260-280	.8	3.1	2.3	.1								6.2
290-310	.5	2.6	3.0	.3								6.5
320-340	.5	1.6	3.1	.4	.2							5.9
.....												
VARIABLE												
CALM	////////////////////////////////////										.9	
TOTALS	16.6	43.1	32.9	5.3	1.2							100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: AUG HOURS: 12-14

WIND SPEED IN KNOTS											
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.8	.2	.2							8.8	8.9	9.0
4.2	.1								15.5	7.7	8.0
4.6									8.0	5.6	5.0
5.0									3.1	4.6	5.0
5.4									2.7	5.6	5.0
5.8	.1								3.4	7.4	7.0
6.2	1.2								11.7	9.7	10.0
6.6	2.5	.6							17.5	10.1	10.0
7.0	.4	.2							9.8	8.1	8.0
7.4	.1								6.2	8.5	8.0
7.8	.3								6.5	8.9	10.0
8.2	.4	.2							5.9	10.6	11.0
.....											
//////////////////////////////////// .9 //////////////////////////////////											
8.6	5.3	1.2							100.0	8.4	8.0
TOTAL NUMBER OF OBSERVATIONS 930											
.....											

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: AUG HOURS: 15-18

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	.9	3.3	3.2	.5	.1							8.1
020-040	2.3	14.8	5.8	.3								23.2
050-070	1.7	6.2	.5									8.5
(E) 080-100	1.6	1.2										2.8
110-130	.6	.5	.1									1.3
140-160	1.1	2.3	1.2	.3								4.8
(S) 170-190	1.1	2.6	5.3	2.2	.3	.1						11.5
200-220	1.4	6.7	4.1	1.6	.3							14.1
230-250	.5	4.8	2.6	1.2	.1							9.2
(W) 260-280	.4	2.6	2.7									5.7
290-310	.2	2.2	3.0	.2								5.6
320-340		1.3	2.4	.5								4.2
VARIABLE												
CALM	////////////////////										1.0	
TOTALS	11.8	48.5	30.9	6.8	.8	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: AUG HOURS: 15-17

DIRECTION	WIND SPEED IN KNOTS							TOTAL %	MEAN WIND	MEDIAN WIND
	15-19	20-24	25-29	30-34	35-39	40-49	50-64			
9.	.5	.1						8.1	9.1	9.0
7.	.3							23.2	7.8	8.0
6.								8.5	6.0	6.0
4.								2.8	4.7	4.0
5.								1.3	5.1	5.0
7.	.3							4.8	7.9	7.0
1.	2.2	.3	.1					11.5	11.0	11.0
9.	1.6	.3						14.1	9.6	9.0
9.	1.2	.1						9.2	9.2	8.0
8.								5.7	8.6	9.0
9.	.2							5.6	9.8	10.0
0.	.5							4.2	10.7	11.0

//////////////////// 1.0 //////////////////////
8. 6.8 .8 .1 100.0 8.6 8.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "AW"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: AUG HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	3.2	4.6	1.7	.2							
020-040	6.6	12.6	.9								
050-070	4.3	3.5									
(E) 080-100	1.8	1.0									
110-130	1.4	.8									
140-160	1.8	2.7	.6	.1							
(S) 170-190	1.1	6.0	7.0	1.3							
200-220	2.4	6.7	3.8	.9							
230-250	2.3	1.9	.9	.1							
(W) 260-280	.9	2.2	.9	.1	.1						
290-310	1.2	1.3	1.3	.2							
320-340	1.7	3.1	1.6	.1	.1						
.....											
VARIABLE											
CALM	////////////////////										
TOTALS	28.7	46.4	18.7	3.0	.2						
.....											
TOTAL NUMBER OF OBSERVATIONS 930											
.....											

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: AUG HOURS: 18-20

WIND SPEED IN KNOTS		TOTAL %	MEAN WIND	MEDIAN WIND				
15-19	20-24				25-29	30-34	35-39	40-49
.2		9.8	6.6	6.0				
		20.0	5.6	6.0				
		7.8	4.4	4.0				
		2.8	3.9	3.5				
		2.2	4.1	4.0				
.1		5.3	6.5	6.0				
1.3		15.4	9.7	10.0				
.9		13.7	7.9	7.0				
.1		5.2	6.0	5.5				
.1	.1	4.1	7.6	7.0				
.2		4.0	7.4	7.0				
.1	.1	6.7	7.4	8.0				
////////////////////////////////////		3.2	////////////////////////////////					
.7	3.0	.2	100.0	6.6	6.0			
TOTAL NUMBER OF OBSERVATIONS					930			

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: AUG HOURS: 21-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	6.2	2.6	.4									9.2
020-040	3.5	2.3	.3									6.1
050-070	2.5	.9										3.3
(E) 080-100	1.3											1.3
110-130	1.0	.4										1.4
140-160	3.7	1.8	.5									6.0
(S) 170-190	4.7	7.7	3.9	.8								17.1
200-220	5.1	5.9	3.3	.8								15.1
230-250	4.1	1.5	.2	.1								5.9
(W) 260-280	2.3	1.1	.1									3.4
290-310	3.4	1.0	.2									4.6
320-340	3.5	1.1				.1						4.7
VARIABLE												
CALM	////////////////////										21.7	
TOTALS	41.3	26.3	8.9	1.7	.1							100.0
TOTAL NUMBER OF OBSERVATIONS											930	

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: AUG HOURS: 21-23

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
										9.2	4.1	3.0
.4										6.1	4.4	4.0
.3										3.3	3.5	3.0
										1.3	2.3	2.0
										1.4	3.3	2.0
.5										6.0	4.9	4.0
.9	.8									17.1	7.4	7.0
.3	.8									15.1	7.0	6.0
.2	.1									5.9	3.9	3.0
.1										3.4	3.9	3.0
.2										4.6	3.6	2.0
		.1								4.7	3.7	3.0

//////////////////////////////////// 21.7 //////////////////////////////////////

.9 1.7 .1 100.0 4.2 4.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: AUG HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.3	3.6	1.9	.2	.1							9.2
020-040	3.2	6.5	1.9	.1								11.6
050-070	2.2	2.0	.2									4.4
(E) 080-100	1.2	.6	.0									1.9
110-130	.8	.7	.1									1.6
140-160	1.6	1.7	.5	.1								3.8
(S) 170-190	2.6	4.9	3.6	.8	.0	.0						12.0
200-220	4.8	6.6	3.8	.9	.1							16.2
230-250	3.2	3.1	1.3	.2	.0							7.8
(W) 260-280	2.3	2.2	.9	.0	.0							5.5
290-310	2.6	2.2	1.2	.1	.0							6.2
320-340	2.1	2.0	1.4	.3	.1							5.8
.....												
VARIABLE												
CALM	////////////////////////////////////										14.0	
TOTALS	29.9	36.1	16.8	2.7	.3							100.0

TOTAL NUMBER OF OBSERVATIONS 7440

SPE
UL

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI		PERIOD OF RECORD: AUG 78 - JUL 88						
UTC: + 5		MONTH: AUG		HOURS: ALL				
WIND SPEED IN KNOTS	WIND SPEED IN KNOTS					TOTAL	MEAN	MEDIAN
	15-19	20-24	25-29	30-34	35-39			
						%	WIND	WIND
6.6								
6.4	.2	.1				9.2	6.6	6.0
4.8	.1					11.6	6.4	6.0
4.1						4.4	4.8	5.0
4.5						1.9	4.1	4.0
6.0						1.6	4.5	4.0
9.3	.1					3.8	6.0	6.0
7.5	.8	.0	.0			12.0	8.3	8.0
6.2	.9	.1				16.2	7.5	7.0
5.9	.2	.0				7.8	6.2	6.0
6.1	.0	.0				5.5	5.9	5.0
7.1	.1	.0				6.2	6.1	5.0
4.4	.3	.1				5.8	7.1	7.0
5.7	////////////////////					14.0	////////////////	
	2.7	.3				100.0	5.7	6.0
TOTAL NUMBER OF OBSERVATIONS 7440								

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: AUG HOURS: AI

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEIL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TO	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.6	7.0	3.5	.5	.1							13.
020-040	4.6	7.8	1.8	.1								14.
050-070	2.6	1.2	.2									4.
(E) 080-100	2.0	.6	.1									2.
110-130	.9	1.2										2.
140-160	1.4	2.0	1.0	.2								4.
(S) 170-190	1.7	8.4	8.2	1.6	.1							19.
200-220	4.5	7.2	4.4	.4								16.
230-250	2.2	1.4	.7	.1								4.
(W) 260-280	1.3	1.2	.4									3.
290-310	1.3	1.5	.4									3.
320-340	1.0	1.4	.9	.2								3.
VARIABLE												
CALM	////////////////////										8.	
TOTALS	26.6	40.9	21.6	3.1	.2							100.

TOTAL NUMBER OF OBSERVATIONS 1128

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 ITC: + 5 MONTH: AUG HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 LE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS		TOTAL %	MEAN WIND	MEDIAN WIND			
15-19	20-24				25-29	30-34	35-39
.5	.1	13.7	7.8	8.0			
.1		14.3	6.2	6.0			
		4.0	4.2	4.0			
		2.7	4.1	4.0			
		2.0	4.7	5.0			
.2		4.5	7.3	7.0			
1.6	.1	19.9	9.4	9.0			
.4		16.5	7.1	7.0			
.1		4.4	5.6	4.5			
		3.3	4.9	4.0			
		3.2	5.7	6.0			
.2		3.5	7.3	7.0			
6 //		8.1	//////////				
3.1	.2	100.0	6.5	7.0			

TOTAL NUMBER OF OBSERVATIONS 1128

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: SEP HOURS: 00-01

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.7	2.6	1.7	.3								7.2
020-040	1.1	4.1	.8	.1	.1							6.2
050-070	1.9	1.2	.3									3.4
(E) 080-100	1.1	.7										1.8
110-130	.7	.2										.9
140-160	1.0	1.1	.4	.1								2.7
(S) 170-190	2.4	5.2	3.8	.8								12.2
200-220	5.9	9.0	3.7	1.3								19.9
230-250	2.9	2.1	.4	.3								5.8
(W) 260-280	3.3	1.6	.1									5.4
290-310	3.6	1.6	.1									5.2
320-340	2.7	2.2	.3	.1								5.3
.....												
VARIABLE												
CALM	////////////////////////////////////											23.9
TOTALS	29.3	31.6	11.6	3.0	.1							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: SEP HOURS: 00-02

WIND SPEED IN KNOTS

0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.7	.3								7.2	6.6	6.0
.8	.1	.1							6.2	6.9	6.0
.3									3.4	4.7	3.0
									1.8	4.5	3.5
									.9	4.1	3.0
.4	.1								2.7	6.0	5.5
1.8	.8								12.2	7.9	7.5
3.7	1.3								19.9	7.0	6.0
.4	.3								5.8	5.7	4.5
.1									5.4	4.0	4.0
.1									5.2	4.1	4.0
.3	.1								5.3	5.3	4.5

//////////////////////////////////// 23.9 //////////////////////////////////
11.6 3.0 .1 100.0 4.7 6.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: SEP HOURS: 03-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.3	4.9	1.7	.3	.1							10.3
020-040	1.9	3.0	.3									5.2
050-070	.7	.3	.6									2.0
(E) 080-100	.9	.7										1.6
110-130	.6	.8										1.4
140-160	1.1	.7	.1									1.9
(S) 170-190	3.1	5.4	2.7	.9								12.1
200-220	7.2	7.3	3.4	.6	.2							18.7
230-250	4.5	1.8	.7	.3								7.3
(W) 260-280	3.1	1.4										4.5
290-310	4.2	2.3	.2									6.7
320-340	2.1	2.0	.3									4.4
VARIABLE												
CALM	////////////////////////////////////										23.1	
TOTALS	32.8	31.1	10.5	2.1	.3							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: 03-05

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.7	.3	.1							10.3	6.9	6.0
.3									5.7	6.0	6.0
.6									2.0	6.3	6.0
									1.6	4.8	4.0
									1.3	4.6	5.0
.1									1.9	4.7	4.0
2.7	.9								12.1	7.5	6.0
3.4	.6	.2							18.8	6.6	6.0
.7	.3								7.3	5.0	4.0
									4.6	3.7	4.0
.2									6.8	4.1	4.0
.3									4.4	4.8	5.0

//////////////////////////////////// 23.2 //////////////////////////////////////
10.5 2.1 .3 100.0 4.6 5.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: SEP HOURS: 06-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.3	4.4	1.6	.6	.2							11.1
020-040	1.4	2.8	.4	.1								4.8
050-070	.9	1.3	.4									3.1
(E) 080-100	.7	.7										1.3
110-130	1.0	.4										1.4
140-160	.8	1.7	.3									2.8
(S) 170-190	3.1	4.4	1.6	.8	.2							10.1
200-220	5.3	8.6	3.6	1.3								18.8
230-250	4.9	2.0	.8									7.7
(W) 260-280	4.1	2.1	.1									6.3
290-310	4.8	2.2	.1	.1								7.2
320-340	3.1	2.2	.6									5.9
.....												
VARIABLE												
CALM	////////////////////											19.4
TOTALS	34.4	33.3	9.5	2.9	.4							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 MEAN UTC: + 5 MONTH: SEP HOURS: 06-08

WIND SPEED IN KNOTS		TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	11.1	6.6	6.0
20-24	25-29	4.8	6.2	6.0
25-29	30-34	3.1	6.3	6.0
30-34	35-39	1.3	4.7	4.5
35-39	40-49	1.4	3.6	4.0
40-49	50-64	2.8	6.4	7.0
45-49	50-64	10.1	7.2	6.0
50-64	50-64	18.8	7.3	7.0
55-64	50-64	7.7	4.4	4.0
60-64	50-64	6.3	3.8	3.0
65-69	50-64	7.2	4.0	4.0
70-74	50-64	5.9	5.0	4.0
////		19.4	////	////
75-79	50-64	2.9	4.8	5.0
TOTAL NUMBER OF OBSERVATIONS		900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: SEP HOURS: 1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	1.9	5.0	3.3	.8	.3						1
020-040	2.6	5.4	1.2	.4	.1						
050-070	1.3	2.1	.6								
(E) 080-100	.7	.9									
110-130	1.0	.7	.1								
140-160	1.2	2.6	.4								
(S) 170-190	.6	4.4	3.2	.9	.3						
200-220	1.6	7.8	5.7	2.4	.1						1
230-250	3.8	5.4	2.9	.4							1
(W) 260-280	1.7	4.1	1.6	.1							
290-310	2.0	5.0	1.6	.2							
320-340	1.7	4.0	2.6	.3							

VARIABLE

CALM //

TOTALS 20.1 47.4 23.2 5.5 .8 10

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: SEP HOURS: 09-11

WIND SPEED IN KNOTS

0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.3	.8	.3							11.3	8.8	8.0
1.2	.4	.1							9.8	6.9	6.0
.6									4.0	6.5	6.5
									1.6	5.4	5.0
.1									1.8	4.7	4.0
.4									4.2	6.1	6.0
3.2	.9	.3							9.4	9.8	9.0
5.7	2.4	.1							17.6	9.5	9.0
2.9	.4								12.6	6.9	6.0
1.6	.1								7.4	7.2	7.0
1.6	.2								8.8	6.7	6.0
2.6	.3								8.6	7.9	8.0
									3.0		
3.2	5.5	.8							100.0	7.6	7.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSU
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: SEP HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										T	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.7	5.2	3.6	1.7	.1							1
020-040	2.6	7.7	4.2	.1	.2							1
050-070	1.6	2.4	.8	.1								
(E) 080-100	1.0	.7										
110-130	.8	1.0										
140-160	1.3	2.6	.4									
(S) 170-190	1.4	4.2	4.4	3.0	.2							1
200-220	1.4	3.3	5.1	3.9	1.6	.1						1
230-250	1.7	5.0	2.4	.9	.1							1
(W) 260-280	.8	2.9	2.6									
290-310	.8	3.8	2.9	.1								
320-340	.6	2.4	2.6	.4								
VARIABLE												
CAL ^M	////////////////////////////////////											
TOTALS	15.7	41.2	29.0	10.2	2.2	.1						10

TOTAL NUMBER OF OBSERVATIONS 900

WIN

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

B -

-14

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: SEP HOURS: 12-14

AL

.....											
WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.6	1.7	.1							12.2	9.1	8.0
4.2	.1	.2							14.8	7.7	8.0
.8	.1								4.9	6.4	6.0
									1.7	4.4	4.0
									1.8	5.1	5.0
.4									4.3	6.2	7.0
4.4	3.0	.2							13.3	10.3	10.0
5.1	3.9	1.6	.1						15.4	12.0	12.0
2.4	.9	.1							10.1	8.3	8.0
2.6									6.2	8.3	8.5
2.7	.1								7.6	8.4	8.0
2.6	.4								6.0	9.2	9.5
.....											
////////////////////									1.7	////////////////	
2.0	10.2	2.2	.1						100.0	8.8	8.0

.....

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERS
 USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AL
 LST TO UTC: + 5 MONTH: SEP HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	.9	2.7	3.2	1.7							
020-040	3.3	14.1	4.9	.8							
050-070	2.7	5.8	1.0								
(E) 080-100	.9	1.1									
110-130	.2	.8									
140-160	.7	2.2	1.0								
(S) 170-190	.7	3.6	5.9	2.4	.9						
200-220	.7	4.9	4.9	3.0	1.2	.1					
230-250	.8	2.9	2.0	.8	.1						
(W) 260-280	.3	2.0	1.0	.2	.1						
290-310	1.0	2.6	2.8	.8							
320-340	.6	1.2	2.2	.4							
.....											
VARIABLE											
CALM	////////////////////////////////////										
TOTALS	13.8	43.9	28.9	10.1	2.3	.1					1

TOTAL NUMBER OF OBSERVATIONS 900

WIN

78 -

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: SEP HOURS: 15-17

WIND SPEED IN KNOTS		TOTAL %	MEAN WIND	MEDIAN WIND						
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
1.7								8.4	10.3	10.0
.8								23.6	7.7	8.0
								9.4	6.1	6.0
								2.0	4.4	5.0
								1.0	5.6	5.0
								3.9	7.6	8.0
2.4	.9							13.4	11.5	11.0
3.0	1.2	.1						14.8	11.8	11.0
.8	.1							6.6	9.6	9.0
.2	.1							4.1	7.9	8.0
.8								7.1	9.1	9.5
.4								4.4	9.5	10.0
////////////////////////////////////								1.2	////////////////////////////////////	
10.1	2.3	.1						100.0	9.0	8.0
TOTAL NUMBER OF OBSERVATIONS 900										

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: SEP HOURS: 1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.1	4.1	2.9	.8								10.9
020-040	6.3	8.4	2.1	.1								17.0
050-070	5.6	3.3	.2									9.1
(E) 080-100	2.7	.8	.3									3.8
110-130	1.8	.3										2.1
140-160	1.1	1.6	1.1									3.8
(S) 170-190	1.2	5.3	7.7	1.3	.1							15.7
200-220	1.4	5.0	4.4	1.6								12.4
230-250	1.3	2.1	.3									3.7
(W) 260-280	1.6	.9	.2									2.7
290-310	2.1	2.9	1.2	.1	.1							6.5
320-340	1.0	2.3	1.0									4.3
VARIABLE												
CALM	////////////////////////////////////										7.0	
TOTALS	29.2	37.0	21.9	3.9	.2							100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: SEP HOURS: 18-20

WIND SPEED IN KNOTS

	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
7	.9	.8								10.9	7.7	7.0
5	.1	.1								17.0	5.8	5.0
4	.2									9.1	4.1	4.0
3	.3									3.8	3.9	3.5
3										2.1	3.2	3.0
7	.1									3.8	7.2	8.0
10	.7	1.3	.1							15.7	10.0	10.0
9	.4	1.6								12.4	9.3	9.0
5	.2									4.2	6.3	6.0
4	.2									2.7	4.8	4.0
6	.2	.1	.1							6.4	6.5	5.5
6	.3									4.3	6.9	7.0
// 7.6 //												
6	.1	3.9	.2							100.0	6.5	6.0
TOTAL NUMBER OF OBSERVATIONS										900		

OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSU
 USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: SEP HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										T	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	4.2	3.7	1.8	1.1								1
020-040	3.1	2.9	.8	.1								
050-070	1.8	1.9		.1								
(E) 080-100	1.9	.3	.1									
110-130	1.4	.4	.1									
140-160	1.7	1.6	.2	.1								
(S) 170-190	3.6	5.9	6.1	.4								1
200-220	3.0	5.9	4.4	1.0	.2							1
230-250	2.0	2.4	.6	.3								
(W) 260-280	3.3	.7	.2	.2								
290-310	3.3	1.2	.3	.1								
320-340	3.7	1.9	.3									
VARIABLE												
CALM	////////////////////////////////////											1
TOTALS	33.0	28.8	14.9	3.4	.2							10

TOTAL NUMBER OF OBSERVATIONS 900

AGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: SEP HOURS: 21-23

WIND SPEED IN KNOTS										
-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.1								10.8	6.8	6.0
.1								6.9	5.6	5.0
.1								3.8	4.9	5.0
								2.3	3.4	2.0
								2.0	4.1	3.0
.1								3.6	5.5	5.0
.4								16.0	8.4	8.0
1.0	.2							14.6	8.4	8.0
.3								5.3	6.1	5.0
.2								4.4	4.2	3.0
.1								5.0	4.5	4.0
								5.9	4.3	4.0
////////////////////////////////////								19.4	////////////////////////////////	
0.4	.2							100.0	5.2	6.0
NUMBER OF OBSERVATIONS 900										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 71
 MONTH: SEP HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	2.9	4.1	2.5	.9	.1							10.0
020-040	2.8	6.1	1.9	.2	.1							11.0
050-070	2.0	2.4	.5	.0								5.0
(E) 080-100	1.2	.7	.1									2.0
110-130	.9	.6	.0									1.0
140-160	1.1	1.7	.5	.0								3.0
(S) 170-190	2.0	4.3	4.4	1.3	.2							12.0
200-220	3.3	6.5	4.4	1.9	.4	.0						16.0
230-250	2.7	3.0	1.3	.4	.0							7.0
(W) 260-280	2.4	2.0	.7	.1	.0							5.0
290-310	2.7	2.7	1.2	.2	.0							6.0
320-340	1.9	2.3	1.2	.2								5.0
VARIABLE												
CALM	////////////////////										12.0	
TOTALS	25.3	36.9	18.7	5.2	.8							100.0

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: SEP HOURS: ALL

WIND SPEED IN KNOTS

10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
2.5	.9	.1							10.3	7.9	7.0
1.9	.2	.1							11.1	6.8	6.0
.5	.0								5.0	5.5	5.0
.1									2.0	4.3	4.0
.0									1.5	4.3	4.0
.5	.0								3.4	6.3	6.0
4.4	1.3	.2							12.8	9.1	9.0
4.4	1.9	.4	.0						16.5	8.8	8.0
1.3	.4	.0							7.4	6.6	6.0
.7	.1	.0							5.2	5.6	5.0
1.2	.2	.0							6.8	6.1	6.0
1.2	.2								5.6	6.7	6.0

//////////////////////////////////// 12.4 //////////////////////////////////////
18.7 5.2 .8 100.0 6.4 7.0

TOTAL NUMBER OF OBSERVATIONS 7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: SEP HOURS: AL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS						GE 65	TOT %			
	1-4	5-9	10-14	15-19	20-24	25-29			30-34	35-39	40-49
(N) 350-010	2.2	5.7	5.9	2.3	.2						16.
020-040	3.4	9.6	3.8	.7	.2						17.
050-070	2.1	3.9	.8								6.
(E) 080-100	1.3	.6	.2								2.
110-130	1.3	1.6	.1								3.
140-160	1.9	4.2	1.4	.1							7.
(S) 170-190	1.7	7.1	6.3	2.4	.5						18.
200-220	1.5	6.5	4.4	1.0	.1						13.
230-250	1.5	1.5	.8	.1							3.
(W) 260-280	.3	.6	.3								1.
290-310	.5	.5	.5								1.
320-340	1.1	.9	.6	.1							2.
VARIABLE											
CALM	////////////////////										4.
TOTALS	19.3	42.7	25.0	6.7	1.0						100.

TOTAL NUMBER OF OBSERVATIONS 1484

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: SEP HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND DIRECTION	WIND SPEED IN KNOTS							TOTAL %	MEAN WIND	MEDIAN WIND	
	0-14	15-19	20-24	25-29	30-34	35-39	40-49				50-64
0	5.9	2.3	.2						16.2	9.7	10.0
6	3.9	.7	.2						17.7	7.6	7.0
4	.2								6.8	6.1	6.0
5	.2								2.2	4.6	4.0
7	.1								3.1	5.2	5.0
9	1.4	.1							7.6	7.0	7.0
1	6.3	2.4	.5						18.1	9.8	10.0
2	4.4	1.0	.1						13.7	8.9	8.0
3	.8	.1							3.9	6.4	6.0
6	.3								1.7	5.5	5.0
5	.5								1.5	6.8	8.0
8	.6	.1							2.8	6.6	6.0

//////////////////// 4.9 //////////////////
 25.0 6.7 1.0 100.0 7.7 8.0

TOTAL NUMBER OF OBSERVATIONS 1484

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: OCT HOURS: 00

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.7	2.5	2.3	1.0	.8	.2						8.5
020-040	2.0	1.7	.8	.3	.3							5.1
050-070	1.0	.2	.1									1.3
(E) 080-100	.5	.2	.2									0.9
110-130	1.1	.1	.2									1.4
140-160	1.3	1.2	1.5	.3			.1					4.4
(S) 170-190	3.7	4.9	3.9	1.0								13.5
200-220	4.6	8.1	1.8	.5	.3	.1						15.4
230-250	4.7	2.0	.3	.4	.1							7.6
(W) 260-280	3.0	2.2	.1									5.3
290-310	4.3	2.7	.5									7.5
320-340	3.7	2.2	1.1	.1								7.1
VARIABLE												
CALM	////////////////////										21.0	
TOTALS	31.6	28.0	13.3	3.6	1.5	.3	.1					100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: OCT HOURS: 00-02

WIND SPEED IN KNOTS

	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
2	.3	1.0	.8	.2						8.4	10.3	9.5
4	.3	.3	.3							5.2	7.5	6.0
5	.1									1.3	4.0	3.0
3	.2									1.0	5.8	4.0
5	.2									1.4	3.9	2.0
7	.5	.3			.1					4.4	8.4	7.0
6	.7	1.0								13.4	7.8	7.0
5	.4	.5	.3	.1						15.5	6.7	6.0
4	.3	.4	.1							8.1	5.5	4.0
4	.1									5.3	4.2	4.0
5	.5									7.5	4.5	4.0
1	.1	.1								7.0	5.4	4.0

5 // 21.6 //
 3.3 3.6 1.5 .3 .1 100.0 5.3 6.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: OCT HOURS: 03

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.3	3.2	2.9	1.3	1.0							9.
020-040	1.7	1.3	.4		.1							3.
050-070	.2	.3										.
(E) 080-100	.3		.1									.
110-130	.6	.4	.5									1.
140-160	.9	1.6	.3									3.
(S) 170-190	2.9	4.8	3.3	1.4	.1							12.
200-220	7.2	7.4	2.6	.2	.1	.1		.1				17.
230-250	3.8	1.3	.5									6.
(W) 260-280	3.0	2.3	.2	.2								5.
290-310	5.7	2.3	.6									8.
320-340	3.3	2.7	1.1	.1								7.
VARIABLE												
CALM	////////////////////										23.	
TOTALS	30.9	26.1	13.0	3.2	1.3	.1		.1				100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: OCT HOURS: 03-05

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
2.9	1.3	1.0							9.7	10.4	10.0
.4		.1							3.5	5.7	5.0
									.5	4.6	5.0
.1									.4	4.3	2.5
.2									1.6	6.5	6.0
.8									3.2	7.1	7.0
3.3	1.4	.1							12.6	8.5	8.0
2.6	.2	.1	.1		.1				17.7	6.3	6.0
.5									6.1	4.4	4.0
.2	.2								5.7	4.6	4.0
.6									8.6	4.4	4.0
1.1	.1								7.2	5.7	5.0
									23.0	////////////////	
13.0	3.2	1.3	.1		.1				100.0	5.1	6.0
TOTAL NUMBER OF OBSERVATIONS 930											

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: OCT HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	2.0	2.6	2.3	.9	.9	.2					
020-040	1.3	1.3	.4								
050-070	.4	.1	.1								
(E) 080-100	.3	.5									
110-130	1.0	.4	.3								
140-160	.4	1.9	.5								
(S) 170-190	2.4	4.1	3.2	1.4	.3						1
200-220	7.0	6.7	3.4	1.4							1
230-250	5.4	1.7	1.3								
(W) 260-280	4.6	1.0	.4	.1							
290-310	4.7	1.7	1.0								
320-340	3.5	3.9	1.2	.4	.1						
VARIABLE											
CALM	////////////////////										2
TOTALS	33.0	26.4	14.1	4.2	1.3	.2					10

TOTAL NUMBER OF OBSERVATIONS 930

IND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: OCT HOURS: 06-08

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
.9	.9	.2						8.8	10.0	9.0
								3.5	6.1	6.0
								.6	5.7	4.0
								.9	4.6	5.0
								1.7	5.4	4.0
								2.9	6.8	7.0
1.4	.3							11.4	9.0	8.0
1.4								18.5	6.9	6.0
								8.4	4.9	4.0
.1								6.1	4.2	3.0
								7.4	4.6	4.0
.4	.1							9.1	6.2	6.0
////////////////////////////////////								20.5	////////////////////////////////////	
4.2	1.3	.2						100.0	5.3	6.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AU
 LST TO UTC: + 5 MONTH: OCT HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	1.5	4.6	2.4	1.5	.4	.4	.1				
020-040	2.3	2.8	1.7	.2							
050-070	.5	.2									
(E) 080-100	1.0	.8									
110-130	.8	1.7	.2								
140-160	1.0	2.2	1.1	.3							
(S) 170-190	1.7	5.3	4.2	2.2	.2	.1					
200-220	2.5	6.2	5.7	1.9	1.0						
230-250	3.2	3.3	2.2								
(W) 260-280	2.5	4.3	1.0	.1							
290-310	2.2	3.3	2.2	.2	.1	.1					
320-340	2.2	3.7	3.7	.8	.1						
VARIABLE	////////////////////////////////////										
CALM	////////////////////////////////////										
TOTALS	21.4	38.4	24.4	7.2	1.8	.6	.1				10

TOTAL NUMBER OF OBSERVATIONS 930

WIND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

78 -
9-11

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: OCT HOURS: 09-11

TOTAL

WIND SPEED IN KNOTS

	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
0	.4	1.5	.4	.4	.1					11.0	10.4	8.0
.8	.7	.2								7.0	7.2	7.0
.7										.8	3.3	4.0
.7										1.7	4.3	4.0
.5	.2									2.7	5.8	6.0
.7	.1	.3								4.5	8.1	7.5
.3	.2	2.2	.2	.1						13.7	9.9	9.0
.7	.7	1.9	1.0							17.3	9.9	9.0
.8	.2									8.7	6.3	6.0
.1	.3	.1								7.8	6.2	5.0
.3	.2	.2	.1	.1						8.1	7.9	8.0
.7	.7	.8	.1							10.3	8.8	9.0
5	////////////////////										6.5	////////////////
0	.4	7.2	1.8	.5	.1					100.0	7.9	8.0
TOTAL NUMBER OF OBSERVATIONS											930	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: OCT HOURS: 12

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.0	3.8	5.2	1.2	.5	.2	.2					12.
020-040	1.5	4.5	2.7	.3	.1							9.
050-070	1.1	1.2	.2									2.
(E) 090-100	1.4	.6	.2									2.
110-130	.5	1.5	.2									2.
140-160	1.4	1.4	1.7	.6								5.
(S) 170-190	2.3	5.7	5.7	3.4	.4							17.
200-220	1.0	4.4	6.7	3.5	.5							16.
230-250	1.2	3.9	1.9	.5	.2							7.
(W) 260-280	.3	3.1	1.2	.3	.1							5.
290-310	1.2	2.5	3.7	.9	.1	.1						8.
320-340	1.3	2.7	4.3	.9	.4	.1						9.
VARIABLE	////////////////////////////////////											1.
CALM	////////////////////////////////////											1.
TOTALS	14.7	35.3	33.6	11.6	2.3	.4	.2					100.
TOTAL NUMBER OF OBSERVATIONS 930												

GE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

M K. I. SAWYER AFB MI

PERIOD OF RECORD: AUG 78 - JUL 88

W 5 MONTH: OCT HOURS: 12-14

.....										
1 WIND SPEED IN KNOTS										
20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND	
.....										
.2	.5	.2	.2				12.0	11.0	10.0	
.3	.1						9.1	7.9	8.0	
							2.5	5.3	5.0	
							2.3	4.7	4.0	
							2.3	6.0	6.0	
							5.2	8.2	7.0	
.4	.4						17.5	10.3	10.0	
.5	.5						16.1	11.4	11.0	
.7	.2						7.6	8.6	8.0	
1.3	.1						5.5	8.1	7.0	
.2	.1	.1					8.4	9.7	10.0	
.7	.4	.1					9.7	10.2	10.0	
.....										
////////////////////							1.8	////////		
.6	.3	.4	.2				100.0	9.4	9.0	
.....										
NUMBER OF OBSERVATIONS 930										
.....										

OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 1
 LST TO UTC: + 5 MONTH: OCT HOURS: 15

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	.6	4.3	5.4	1.1	.6	.3	.1					12.
020-040	2.8	7.3	2.6	.4								13.
050-070	2.0	1.6	.2									3.
(E) 080-100	1.0	.2										1.
110-130	.4	.3	.5									1.
140-160	1.4	3.2	2.2	.9								7.
(S) 170-190	.9	5.4	5.9	2.8	.3							15.
200-220	1.0	5.9	4.6	2.0	.4	.1	.1					14.
230-250	1.3	2.9	1.9	.9	.1		.1					7.
(W) 260-280	1.5	2.9	1.1	.4								5.
290-310	2.3	2.9	1.3	.6								7.
320-340	1.0	3.2	2.9	1.2	.2							8.
.....												
VARIABLE												
CALM	////////////////////											1.
TOTALS	15.2	40.6	28.5	10.3	1.6	.4	.3					100.

TOTAL NUMBER OF OBSERVATIONS 930

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: OCT HOURS: 15-17

WIND SPEED IN KNOTS										
5-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.1	.6	.3	.1					12.5	11.0	10.0
.4								13.1	7.3	7.0
								3.9	4.8	4.0
								1.2	3.5	3.0
								1.7	7.3	6.0
.9								7.6	8.3	8.0
2.6	.3							15.3	10.8	10.0
2.0	.4	.1	.1					14.2	10.4	10.0
.9	.1		.1					7.1	9.2	8.5
.4								5.9	7.1	6.0
.6								7.1	7.1	6.0
1.2	.2							8.5	10.1	10.0
////////////////////////////////////								1.9	////////////////////////////////////	
10.3	1.6	.4	.3					100.0	8.9	8.0
NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: OCT HOURS: 1

DIRECTION (DEGPFS)	WIND SPEED IN KNOTS							GE	65	TC	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34				35-39
(N) 350-010	2.7	3.0	2.6	.8	.6	.2					10
020-040	4.5	3.7	.9	.1	.1						9
050-070	2.7	1.2									3
(E) 080-100	1.7	.5	.1								2
110-130	1.3	1.2	.4								2
140-160	1.8	2.0	1.1	.2							5
(S) 170-190	3.0	9.2	6.3	1.3	.2						20
200-220	2.2	4.7	2.6	.4							9
230-250	2.0	2.5	.5	.1							5
(W) 260-280	1.2	1.3	.1								2
290-310	2.9	2.7	1.7	.1							7
320-340	2.9	4.0	2.0	.5	.2						9
.....											
VARIABLE											
CALM	////////////////////////////////////										11
TOTALS	29.1	36.0	18.3	3.5	1.1	.2					100

TOTAL NUMBER OF OBSERVATIONS 930

IND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

20 J IN NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
D UTC: + 5 MONTH: OCT HOURS: 18-20

		WIND SPEED IN KNOTS								TOTAL	MEAN	MEDIAN	
		14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
2.6			.8	.6	.2						10.1	9.0	7.0
.9			.1	.1							9.2	5.5	5.0
											3.9	3.4	3.5
.1											2.4	3.6	3.0
.4											2.9	5.7	6.0
1.1			.2								5.2	7.3	7.0
.3	1.3		.2								20.1	8.5	8.0
.5	.4										9.9	7.7	8.0
.5	.1										5.2	5.7	5.0
.1											2.6	4.9	5.0
1.7	.1										7.4	6.4	6.0
.6	.5		.2								9.7	7.4	7.0
////////////////////////////////////											11.5	////////////////////////////////////	
.2	3.5	1.1	.2								100.0	6.3	6.0
TOTAL NUMBER OF OBSERVATIONS											930		

OPERATING LOCATION "A" PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSU
 USAFETAC, ASHEVILLE NC FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: OCT HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										T	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.5	2.4	2.2	1.0	.8							
020-040	2.0	2.2	.8	.3	.2							
050-070	1.0	.5										
(E) 080-100	.5	.1	.1									
110-130	1.2	.9	.3	.1								
140-160	2.0	2.4	1.4	.2								
(S) 170-190	2.2	6.5	4.2	.9	.3							1
200-220	4.2	10.2	2.3	1.0	.1							1
230-250	2.9	1.9	.2	.1	.1							
(W) 260-280	3.2	1.5	.2									
290-310	2.4	2.8	.1									
320-340	1.7	3.9	1.7	.3								
VARIABLE												
CALM	////////////////////											2
TOTALS	25.8	35.3	13.5	3.9	1.5							10
TOTAL NUMBER OF OBSERVATIONS 930												

WIND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: OCT HOURS: 21-23

WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65				
.2	1.0	.8								8.7	9.1	8.0
.2	.3	.2								5.5	6.9	6.0
										1.5	4.2	4.0
.1										.8	4.6	4.0
.3	.1									2.5	5.8	5.0
1.4	.2									6.0	6.9	6.0
.2	.9	.3								14.0	8.5	8.0
.3	1.0	.1								17.7	7.1	7.0
.2	.1	.1								5.3	5.2	4.0
.2										4.9	4.3	4.0
.1										5.3	5.0	5.0
1.7	.3									7.6	7.3	7.0
////////////////////////////////////										20.2	////////////////////////////////////	
.5	3.9	1.5								100.0	5.6	6.0
TOTAL NUMBER OF OBSERVATIONS										930		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: OCT HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										T	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.7	3.3	3.1	1.1	.7	.2	.1					10
020-040	2.3	3.2	1.3	.2	.1							
050-070	1.1	.7	.1									
(E) 080-100	.3	.4	.1									
110-130	.9	.9	.3	.0								
140-160	1.3	2.0	1.3	.3			.0					
(S) 170-190	2.4	5.7	4.6	1.8	.2	.0						10
200-220	3.7	6.7	3.7	1.4	.3	.0	.0	.0				10
230-250	3.1	2.5	1.1	.3	.1		.0					
(W) 260-280	2.5	2.3	.5	.1	.0							
290-310	3.2	2.6	1.4	.2	.0	.0						
320-340	2.4	3.3	2.2	.5	.1	.0						
VARIABLE												
CALM	////////////////////										1	
TOTALS	25.4	33.6	19.7	5.9	1.5	.2	.1					10

TOTAL NUMBER OF OBSERVATIONS 7440

IND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
MTC: + 5 MONTH: OCT HOURS: ALL

WIND SPEED IN KNOTS											
	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
1	1.1	.7	.2	.1					10.1	10.2	10.0
2	.2	.1							7.0	6.9	6.0
3									1.9	4.3	4.0
4									1.3	4.3	4.0
5	.0								2.1	5.8	5.0
6	.3			.0					4.9	7.7	7.0
7	1.3	.2	.0						14.7	9.2	9.0
8	1.4	.3	.0	.0	.0				15.9	8.3	7.0
9	.3	.1		.0					7.1	6.3	5.0
10	.1	.0							5.5	5.5	5.0
11	.2	.0	.0						7.5	6.3	5.0
12	.5	.1	.0						8.6	7.8	7.0
////////////////////////////////////									13.4	////////////////////////////////////	
13	5.9	1.5	.2	.1					100.0	6.7	7.0
TOTAL NUMBER OF OBSERVATIONS 7440											

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: A
MONTH: OCT HOURS

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METER
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH C

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65
(N) 350-010	1.4	6.8	5.2	2.5	2.3	.5					
020-040	3.5	6.1	2.5	1.0	.5						
050-070	.9	1.3	.1								
(E) 080-100	.3	.8	.3								
110-130	.2	1.4	1.0	.1							
140-160	1.0	3.2	2.6	.7			.1				
(S) 170-190	2.5	6.0	7.5	2.6	.2						
200-220	2.0	4.0	3.0	1.0				.1			
230-250	1.0	.5	.6								
(W) 260-280	1.2	1.1	.3								
290-310	1.5	1.2	.5	.2							
320-340	1.3	3.0	2.3	.5	.3	.1					
VARIABLE											
CALM	////////////////////////////////////										
TOTALS	13.4	35.7	26.7	8.9	3.8	.6	.1	.1			

TOTAL NUMBER OF OBSERVATIONS 1550

WIND

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TC: + 5 MONTH: OCT HOURS: ALL

WIND SPEEDS LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS),
AND/OR
(0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND DIRECTION	WIND SPEED IN KNOTS							TOTAL	MEAN WIND	MEDIAN WIND
	15-19	20-24	25-29	30-34	35-39	40-49	50-64			
0										
5	2.5	2.3	.5					19.8	11.9	10.0
3	1.0	.5						13.5	7.9	7.0
8								2.3	5.3	5.0
2								1.8	5.3	5.0
5	.1							3.2	7.0	7.0
8	.7			.1				7.5	9.3	9.0
1	2.6	.2						18.8	9.9	10.0
5	1.0				.1			10.1	8.6	8.0
6								2.5	6.2	6.0
5								2.6	5.6	6.0
3	.2							3.5	6.5	5.0
8	.3	.3	.1					8.3	9.0	8.0
0										
0	////////////////////							6.0	////////////////	
	8.9	3.8	.6	.1	.1			100.0	8.6	8.0

TOTAL NUMBER OF OBSERVATIONS 1550

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: NOV HOURS: C

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TC	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.3	2.4	3.2	1.3	.1							8
020-040	1.7	1.6	2.1	.4								5
050-070	.7	.6	.2									1
(E) 080-100	.9	.3	.2									1
110-130	.3	1.0	.1									1
140-160	1.2	.9	.4	.1								2
(S) 170-190	2.1	3.7	2.8	.8	.2							5
200-220	4.0	5.0	4.7	1.1	.2							18
230-250	3.2	3.3	1.7	.4	.1							8
(W) 260-280	2.6	3.8	1.6	.4								8
290-310	2.9	3.3	1.0	.1								7
320-340	3.3	3.6	3.0	.2								10

.....
VARIABLE

CALM	////////////////////////////////////										15	
TOTALS	24.6	33.0	21.0	4.8	.6							100

.....
TOTAL NUMBER OF OBSERVATIONS 900
.....

IND SP: PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 00-02

L	WIND SPEED IN KNOTS						TOTAL %	MEAN WIND	MEDIAN WIND
	15-19	20-24	25-29	30-34	35-39	40-49			
9.	1.3	.1					8.9	9.6	10.0
7.	.4						5.8	7.8	8.0
6.							1.4	6.2	5.0
5.							1.3	5.0	3.0
6.							1.4	6.1	6.0
6.	.1						2.7	6.2	5.5
8.	.8	.2					9.6	8.7	8.0
8.	1.1	.2					18.0	8.0	7.0
6.	.4	.1					8.8	6.7	6.0
7.	.4						8.3	7.0	6.0
6.	.1						7.8	6.2	6.0
7.	.2						10.1	7.0	6.0
////////////////////////////////////							15.9	////////////////////////////////	
6.	4.8	.6					100.0	6.4	7.0

TOTAL NUMBER OF OBSERVATIONS 900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: NOV HOURS: 03-C

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.4	3.1	2.6	2.1	.1							10.3
020-040	1.3	1.9	2.0	.3	.1							5.7
050-070	.6	.6	.6	.2								1.9
(E) 080-100	.9	.4										1.3
110-130	.9	.8	.1									1.8
140-160	.7	1.6	.6									2.8
(S) 170-190	.9	5.7	1.1	.8	.1							8.6
200-220	5.6	7.1	2.8	1.7	.1							17.2
230-250	2.5	3.6	.9	.3								7.6
(W) 260-280	3.0	3.0	1.6	.7								8.2
290-310	2.3	3.8	.7	.1								7.3
320-340	3.4	5.7	2.4	.2								11.9
VARIABLE												
CALM	////////////////////////////////////										15.6	
TOTALS	25.3	37.3	15.4	6.4	.4							100.0

TOTAL NUMBER OF OBSERVATIONS 900

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: NOV HOURS: 03-05

WIND SPEED IN KNOTS		TOTAL	MEAN	MEDIAN
20-24	25-29	%	WIND	WIND
2.1	.1	10.3	9.1	9.0
.3	.1	5.7	8.6	8.0
.2		1.9	7.8	6.0
		1.3	3.8	3.0
		1.8	5.0	4.5
		2.8	7.0	7.0
.8	.1	8.6	8.4	8.0
1.7	.1	17.2	7.4	6.0
.3		7.6	6.6	6.0
.7		8.2	6.9	6.0
.1		7.3	5.8	5.5
.2		11.5	6.8	6.0
////////////////////////////////////		15.6	////////////////////////////////	
.4	.4	100.0	6.2	7.0
NUMBER OF OBSERVATIONS		900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: NOV HOURS: 06

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOT %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	1.7	2.9	3.1	1.9	.6							10.
020-040	2.4	1.3	1.0	.4								5.
050-070	1.1	1.0	.4									2.
(E) 090-100	1.0	.3										1.
110-130	.8	1.2										2.
140-160	.1	1.3	.7	.1								2.
(S) 170-190	2.3	4.4	2.8	.2	.6							10.
200-220	4.4	6.8	2.9	1.6	.2							15.
230-250	3.9	2.3	1.3	.3								8.
(W) 260-280	2.7	2.9	1.4	.4								7.
290-310	2.7	3.6	.6	.2								7.
320-340	2.9	5.3	2.2									10.
VARIABLE												
CALM	////////////////////////////////////											16.
TOTALS	26.0	33.3	16.9	5.1	1.4							100.

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: C: + 5 MONTH: NOV HOURS: 06-08

WIND SPEED IN KNOTS								TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
1.9	.6							10.1	10.5	10.0
.4								5.7	6.8	6.0
								2.6	5.5	5.0
								1.3	3.8	3.5
								2.0	5.3	6.0
.1								2.2	8.9	9.0
.2	.6							10.3	8.2	7.0
1.6	.2							15.9	7.6	7.0
.3								8.3	6.3	5.0
.4								7.4	6.7	6.0
.2								7.0	5.7	5.0
								10.4	6.8	6.5
								16.7		
5.1	1.4							100.0	6.1	7.0
TOTAL NUMBER OF OBSERVATIONS								900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 71
 LST TO UTC: + 5 MONTH: NOV HOURS: 09

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.3	3.4	2.6	2.3	.6							10.0
020-040	1.1	2.6	1.6	.4								5.0
050-070	1.3	1.6	.6	.1								3.0
(E) 080-100	.9	.8	.1									1.8
110-130	.7	1.8										2.4
140-160	.2	1.3	.7	.1								2.3
(S) 170-190	2.3	3.0	3.4	1.0	.6	.2	.1					10.0
200-220	4.1	7.4	4.7	1.9	.4							18.0
230-250	2.2	4.7	2.6	.9								10.0
(W) 260-280	1.8	3.0	1.4	.2								6.4
290-310	2.6	3.8	1.8	.3	.1							8.6
320-340	2.2	5.6	3.8	.6								12.1
VARIABLE												
CALM	////////////////////										7.3	
TOTALS	20.7	39.0	23.3	7.8	1.7	.2	.1					100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: NOV HOURS: 09-11

WIND SPEED IN KNOTS				TOTAL	MEAN	MEDIAN
15-19	20-24	25-29	30-34	%	WIND	WIND
2.3	.6			10.2	10.5	10.0
.4				5.7	8.0	8.0
.1				3.6	6.1	5.5
				1.8	4.6	4.5
				2.4	5.5	5.0
.1				2.3	8.6	8.0
1.0	.6	.2	.1	10.7	9.9	9.5
1.9	.4			18.6	8.5	8.0
.9				10.3	8.1	7.0
.2				6.4	6.8	6.0
.3	.1			8.6	7.0	7.0
.5				12.1	8.3	8.0
////////////////////////////////////				7.3	////////////////////////////////	
7.3	1.7	.2	.1	100.0	7.7	8.0
TOTAL NUMBER OF OBSERVATIONS				900		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: NOV HOURS: 12-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	1.4	4.9	3.6	1.6	.7							12.1
020-040	1.1	2.9	3.3	.3								7.7
050-070	1.6	1.1	.4									3.1
(E) 090-100	.9	1.1										2.0
110-130	.4	1.1	.1									1.7
140-160	.4	1.9	.3									2.7
(S) 170-190	1.4	4.1	5.4	2.4	.1	.3						14.9
200-220	1.0	5.0	5.8	2.3	1.0	.3						15.4
230-250	1.7	3.3	3.2	1.0	.1							9.8
(N) 260-280	1.3	2.9	2.2	.3								6.6
290-310	1.2	3.8	3.8	.6	.1							9.4
320-340	2.2	5.3	4.3	1.2								13.1
.....												
VARIABLE												
CALM	////////////////////////////////////											1.3
TOTALS	14.5	37.9	33.4	9.7	2.0	.6						100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: NOV HOURS: 12-14

WIND SPEED IN KNOTS												
	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
0-4		1.6	.7							12.1	9.7	9.0
5-9		.3								7.7	8.7	9.0
10-14										3.1	5.4	4.5
15-19										2.0	4.6	5.0
20-24										1.7	5.2	5.0
25-29										2.7	6.9	7.0
30-34		2.4	.1	.3						14.9	10.6	10.0
35-39		2.3	1.0	.3						15.4	11.5	11.0
40-49		1.0	.1							9.8	8.9	8.0
50-64		.3								6.8	7.9	8.0
65-69		.6	.1							9.4	9.1	9.0
70-74		1.2								13.1	8.7	8.0
////////////////////////////////////										1.3		
80-84		9.7	2.0	.6						100.0	9.1	9.0
TOTAL NUMBER OF OBSERVATIONS										900		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 71
 LST TO UTC: + 5 MONTH: NOV HOURS: 15

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.4	5.3	3.1	2.1	.1							13.
020-040	2.3	4.8	2.4	.2	.2							10.
050-070	1.9	1.4	.3									3.
(E) 080-100	1.0		.1									1.
110-130	.9	.7	.2									1.
140-160	1.5	1.0	.3	.1	.2							3.
(S) 170-190	1.9	4.9	6.6	1.6	.3	.2						15.
200-220	1.6	5.6	5.9	1.7	.3	.1						15.
230-250	1.0	3.8	1.0	.6	.1							7.
(W) 260-280	1.7	2.3	2.2	.2								6.
290-310	1.8	3.7	1.9	.7	.1							8.
320-340	1.9	6.3	3.2	.3	.2							12.
.....												
VARIABLE												
CALM	////////////////////											2.
TOTALS	19.9	39.5	28.2	8.0	1.5	.3						100.

TOTAL NUMBER OF OBSERVATIONS 700

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: NOV HOURS: 15-17

WIND SPEED IN KNOTS											
0-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
3.1	2.1	.1							13.1	8.9	9.0
2.4	.2	.2							10.0	7.5	7.0
.3									3.7	4.8	4.0
.1									1.1	3.6	3.0
.2									1.8	5.1	3.5
.2	.1	.2							3.2	6.9	6.0
.4	1.6	.3	.2						15.3	10.1	10.0
2.4	1.7	.3	.1						15.1	10.1	10.0
1.9	.6	.1							7.3	8.4	7.0
2.2	.2								6.6	7.7	8.0
1.9	.7	.1							8.1	8.2	8.0
3.2	.3	.2							12.4	8.3	8.0
////////////////////////////////////									2.2	////////////////////////////////	
.3	2.0	1.5	.3						100.0	6.4	8.0
TOTAL NUMBER OF OBSERVATIONS 900											

OPERATING LOCATION: WAW
 USAFETAC, ASHEVILLE, NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 74
 MONTH: NOV HOURS: 18-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	3.0	4.1	3.4	1.3	.1							12.0
020-040	2.7	3.1	2.2	.2								8.2
050-070	2.3	1.0	.2									3.5
(E) 080-100	.2	.6										1.3
110-130	1.4		.1									1.6
140-160	.7	2.0	.6	.4	.1							3.8
(S) 170-190	1.2	5.2	4.4	1.6	.7							13.1
200-220	3.0	6.9	5.0	.6	.2	.1						15.1
230-250	2.0	1.9	1.1	.4								5.4
(W) 260-280	2.6	2.3	1.5									6.7
290-310	3.1	4.2	1.1	.3	.1							8.8
320-340	3.7	4.3	2.7	.1								10.8
VARIABLE												
CALM	////////////////////////////////////										8.2	
TOTALS	27.1	35.6	22.4	4.9	1.2	.1						100.0
TOTAL NUMBER OF OBSERVATIONS 200												

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: NOV HOURS: 18-20

WIND SPEED IN KNOTS												
	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
	1.4	1.3	.1							12.0	8.6	8.0
	2.2	.2								8.2	6.9	7.0
	.2									3.6	4.1	3.0
										1.3	4.7	4.0
	.1									1.6	3.0	2.0
	.6	.4	.1							3.8	8.1	6.0
	4.4	1.6	.7							13.7	9.8	9.0
	7.0	.6	.2	.1						15.8	9.2	8.0
	1.1	.4								5.4	7.3	6.0
	1.1									6.7	6.7	5.5
	1.1	.3	.1							8.9	6.5	6.0
	3.7	.1								10.8	6.7	6.0
////////////////////////////////////										8.3	////////////////////////////////////	
	12.4	4.2	1.2	.1						100.0	6.9	7.0
TOTAL NUMBER OF OBSERVATIONS 900												

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: NOV HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.2	3.4	2.8	1.6								10.0
020-040	1.1	2.6	1.9	.2								5.8
050-070	.8	.3	.1									1.2
(E) 080-100	1.7	1.0	.1									2.8
110-130	1.7	.6	.1									2.3
140-160	.9	1.0	.7		.1							2.6
(S) 170-190	1.4	5.4	3.1	.9	.1							11.0
200-220	3.6	6.9	5.9	.9	.3	.1						17.7
230-250	2.0	2.2	1.6	.6	.1							6.4
(W) 260-280	3.3	4.0	1.7	.3								9.3
290-310	3.4	4.4	.9									8.8
320-340	2.9	3.9	2.4	.3								9.6
.....												
VARIABLE												
CALM	////////////////////											12.6 /
TOTALS	24.9	35.7	21.3	4.8	.6	.1						100.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 ZONE: + 5 MONTH: NOV HOURS: 21-23

WIND SPEED IN KNOTS										
10-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.6								10.0	8.8	8.0
.2								5.8	8.0	8.0
								1.2	5.2	4.0
								2.8	4.7	4.0
								2.3	3.8	3.0
	.1							2.6	7.7	6.0
.9	.1							11.0	8.7	8.0
.9	.3	.1						17.7	8.3	8.0
.6	.1							6.4	7.9	6.5
.3								9.3	6.7	6.0
								8.8	5.6	5.0
.3								9.6	7.3	7.0
////////////////////////////////////								12.6	////////////////////////////////	
4.8	.6	.1						100.0	6.6	7.0
TOTAL NUMBER OF OBSERVATIONS 900										

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSU
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: NOV HOURS:

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.0	3.7	3.0	1.8	.3							1
020-040	1.7	2.6	2.1	.3	.0							
050-070	1.3	.9	.4	.0								
(E) 080-100	1.0	.5	.1									
110-130	.9	.9	.1									
140-160	.7	1.4	.5	.1	.1							
(S) 170-190	1.8	4.6	3.3	1.2	.3	.1	.0					1
200-220	3.4	6.7	4.7	1.5	.4	.1						1
230-250	2.3	3.2	1.8	.6	.1							
(W) 260-280	2.4	3.0	1.8	.3								
290-310	2.5	3.9	1.5	.3	.1							
320-340	2.3	5.0	3.0	.4	.0							1
VARIABLE												
CALM	////////////////////////////////////										1	
TOTALS	22.9	36.5	22.8	6.5	1.3	.2						10

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: NOV HOURS: ALL

DIRECTION	WIND SPEED IN KNOTS					TOTAL	MEAN WIND	MEDIAN WIND
	14-19	20-24	25-29	30-34	35-39			
00	1.8	.3				10.8	9.4	9.0
01	.3	.0				6.8	7.8	7.5
04	.0					2.6	5.5	5.0
01						1.6	4.4	4.0
01						1.9	4.9	5.0
05	.1	.1				2.8	7.5	7.0
07	1.2	.3	.1	.0		11.7	9.4	9.0
07	1.5	.4	.1			16.7	8.7	8.0
08	.6	.1				8.0	7.6	7.0
09	.3					7.5	7.0	6.0
09	.3	.1				8.2	6.8	6.0
09	.4	.0				11.3	7.6	7.0
////////////////////////////////////						10.0	////////////////////////////////	
10	6.5	1.3	.2			100.0	7.2	7.0
TOTAL NUMBER OF OBSERVATIONS						7200		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: NOV HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS						TOTAL %
	1-4	5-9	10-14	15-19	20-24	25-29	
(N) 350-010	2.0	5.6	6.0	3.8	.8		18.1
020-040	3.3	5.4	4.7	.6	.1		14.0
050-070	1.9	1.9	.4				4.2
(E) 080-100	1.4	1.3	.1				2.8
110-130	1.3	1.8	.4				3.5
140-160	.7	2.5	1.8	.4	.2		5.7
(S) 170-190	1.1	4.2	4.1	1.6	.6		11.6
200-220	2.3	4.3	3.7	1.1	.2		11.6
230-250	1.4	1.5	.4				3.3
(W) 260-280	1.1	1.1	1.1				3.2
290-310	1.0	2.2	.6	.2			3.9
320-340	2.5	3.9	4.1	.6	.1		11.2
VARIABLE							
CALM	////////////////////						7.0
TOTALS	20.0	35.7	27.4	8.3	2.0		100.0

TOTAL NUMBER OF OBSERVATIONS 1808

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: NOV HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 GE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND DIRECTION	WIND SPEED IN KNOTS							TOTAL %	MEAN WIND	MEDIAN WIND	
	15-19	20-24	25-29	30-34	35-39	40-49	50-64				GE 65
800	3.8	.8						18.1	10.8	10.0	
57	.6	.1						14.0	8.0	8.0	
47								4.2	5.4	5.0	
57								2.8	4.9	5.0	
97								3.5	5.7	5.0	
07	.4	.2						5.7	9.2	8.0	
91	1.6	.6						11.6	10.4	10.0	
57	1.1	.2						11.6	9.0	9.0	
77								3.3	5.7	5.0	
61								3.2	7.0	7.0	
86	.2							3.9	6.9	6.0	
1	.6	.1						11.2	8.5	8.0	
8	////////////////////							7.0	////////////////		
4	8.3	2.0						100.0	8.0	8.0	

TOTAL NUMBER OF OBSERVATIONS 1808

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: DEC HOURS: 00-02

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	1.2	1.3	2.8	1.2	.6	.1	.1					7.3
020-040	1.7	1.1	.4	.2	.1							3.5
050-070	.3	.6										1.0
(E) 080-100	.8	.5										1.3
110-130	1.0	.5	.1									1.6
140-160	1.0	1.9	.5									3.4
(S) 170-190	1.7	3.2	2.6	1.5	.1	.1						9.2
200-220	5.5	5.9	2.9	1.4	1.2	.2						17.1
230-250	4.0	4.1	1.5									9.6
(W) 260-280	5.6	5.6	2.4									13.5
290-310	2.3	4.7	2.4	.2	.1							10.2
320-340	2.3	4.7	2.8	1.0								10.8
VARIABLE												
CALM	////////////////////////////////////										11.4	
TOTALS	27.9	34.1	18.4	5.5	2.1	.4	.1					100.0
TOTAL NUMBER OF OBSERVATIONS 930												

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC + 5 MONTH: DEC HOURS: 00-02

WIND SPEED IN KNOTS

15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.2	.6	.1	.1					7.3	12.0	12.0
.2	.1							3.5	6.7	6.0
								1.0	5.6	5.0
								1.3	3.9	4.0
								1.6	4.4	4.0
								3.4	6.8	7.0
1.5	.1	.1						9.2	9.6	9.0
1.4	1.2	.2						17.1	8.4	7.0
								9.6	5.6	5.0
								13.5	5.8	5.0
.2	.1							10.2	7.3	7.0
1.0								10.8	8.0	8.0

//////////////////// 11.4 //////////////////////
 5.5 2.1 .4 .1 100.0 6.8 7.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: DEC HOURS: 03-05

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.3	2.0	2.7	.6	.5		.2	.1				7.5
020-040	1.5	1.1	1.1									3.7
050-070	.6	.3										1.0
(E) 080-100	.9	.9										1.7
110-130	1.0	.4	.1									1.5
140-160	.8	1.5	.4									2.7
(S) 170-190	2.0	3.1	2.8	1.5	.1							9.6
200-220	4.6	4.6	3.4	1.3	1.1							15.1
230-250	6.1	3.7	.6									10.4
(W) 260-280	5.1	4.6	1.2	.2								11.1
290-310	3.9	6.5	2.3	.4								13.0
320-340	2.4	4.4	3.1	.2	.1							10.2
VARIABLE												
CALM	////////////////////////////////////										12.6	
TOTALS	30.2	33.1	17.7	4.2	1.8		.2	.1				100.0
TOTAL NUMBER OF OBSERVATIONS											930	

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: DEC HOURS: 03-05

WIND SPEED IN KNOTS												
	14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
										%	WIND	WIND
0.												
5.	2.7	.6	.5		.2	.1				7.5	10.8	10.0
3.	1.1									3.7	6.8	5.5
4.										1.0	3.9	3.0
4.										1.7	4.6	4.5
5.	.1									1.5	4.6	4.0
9.	.4									2.7	6.8	6.0
8.	2.8	1.5	.1							9.6	9.1	8.0
4.	4.4	1.3	1.1							15.1	8.5	7.0
5.	.6									10.4	4.7	4.0
6.	1.2	.2								11.1	5.5	5.0
7.	.3	.4								13.0	6.8	6.0
1.	.1	.2	.1							10.2	7.8	8.0
////////////////////////////////////										12.6	////////////////////////////////////	
7.	4.2	1.8		.2	.1					100.0	6.4	6.0
TOTAL NUMBER OF OBSERVATIONS										930		

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: DEC HOURS: 06

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOT %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.9	2.2	2.6	1.6	.6	.2	.1					9.
020-040	1.1	1.1	1.2	.3	.1							3.
050-070	1.1	.6										1.
(E) 080-100	.9	.1										1.
110-130	.4	.4										.
140-160	1.2	1.4	.3									2.
(S) 170-190	2.0	3.3	3.0	1.1	.2							9.
200-220	4.2	4.9	3.7	1.5	.9							15.
230-250	5.1	4.1	1.0	.1								10.
(W) 260-280	4.7	4.9	.9									10.
290-310	4.5	6.1	1.6	.1								12.
320-340	2.0	3.9	3.0	1.0	.1							10.
VARIABLE												
CALM	////////////////////////////////////										12.	
TOTALS	29.1	33.0	17.3	5.7	1.9	.2	.1					100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME: + 5 MONTH: DEC HOURS: 06-08

WIND SPEED IN KNOTS		TOTAL	MEAN	MEDIAN						
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	%	WIND	WIND
1.6	.6	.2	.1					9.2	10.9	10.5
.3	.1							3.8	8.5	8.0
								1.7	4.9	4.0
								1.0	3.4	4.0
								.9	4.9	4.5
								2.9	5.3	6.0
1.1	.2							9.7	8.7	8.0
1.5	.9							15.2	8.8	8.0
.1								10.2	5.2	5.0
								10.5	5.2	5.0
.1								12.4	6.0	6.0
1.0	.1							10.0	8.8	8.0
								12.6		
5.7	1.9	.2	.1					100.0	6.5	6.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: DEC HOURS: 09

DIRECTION (DEGREES)	WIND SPEED IN KNOTS							TOT %
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	
(N) 350-010	1.3	2.4	2.7	1.1	.5	.1		8.
020-040	1.2	1.3	1.4	.5				4.
050-070	.2	.3	.3					1.
(E) 080-100	.3	.5						.
110-130	.2	1.5	.1					2.
140-160	.5	.5	.5					1.
(S) 170-190	3.3	2.3	2.5	1.6	.4			10.
200-220	3.5	5.1	4.2	1.8	.3			16.
230-250	4.2	5.4	1.7	.3				11.
(W) 260-280	3.4	4.4	1.0	.2				9.
290-310	3.0	2.2	2.0	.1				13.
320-340	2.0	4.3	4.2	1.3	.1			11.
VARIABLE								
CALM	////////////////////////////////////							7.
TOTALS	24.9	36.3	22.1	5.9	1.8	.1		100.
TOTAL NUMBER OF OBSERVATIONS 930								

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 MONTH: DEC HOURS: 09-11

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.1	.5	.1						8.6	10.1	10.0
.5								4.4	8.4	8.0
								1.9	5.7	5.0
								.9	5.5	5.5
								2.4	5.8	6.0
								1.9	7.6	8.5
1.6	.4							10.1	9.0	8.0
1.8	.3							16.0	9.1	8.0
.3								11.6	6.3	6.0
.2								9.7	6.3	6.0
.1								13.3	6.7	7.0
1.3	.1							11.9	9.2	9.0
////////////////////////////////////								7.2	////////////////////////////////////	
5.9	1.8	.1						100.0	7.4	7.0
TOTAL NUMBER OF OBSERVATIONS								930		

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: DEC HOURS: 12-1

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.3	3.3	4.4	1.9	.5							11.5
020-040	1.3	2.2	1.1	.4		.1						5.6
050-070	.9	.4	.3									1.6
(E) 080-100	.5	.2	.1									.9
110-130	.5	.6	.2									1.4
140-160	.4	2.7	1.2									4.3
(S) 170-190	1.3	1.6	1.8	2.3	.2	.1						7.3
200-220	1.5	6.6	5.1	2.8	1.1							17.0
230-250	2.2	3.5	3.3	.5								9.6
(W) 260-280	1.6	4.4	2.7	.8								9.5
290-310	2.3	7.1	4.8	.8	.1							15.1
320-340	1.1	4.6	4.4	1.9	.3							12.4
.....												
VARIABLE												
CALM	////////////////////										4.0	
TOTALS	15.4	37.2	29.4	11.4	2.2	.2						100.0
TOTAL NUMBER OF OBSERVATIONS 930												
.....												

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC + 5 MONTH: DEC HOURS: 12-14

WIND SPEED IN KNOTS											
1-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
4.4	1.9	.5							11.5	10.7	10.0
1.1	.4		.1						5.6	7.7	6.0
.3									1.6	5.0	4.0
.1									.9	4.9	4.0
.2									1.4	5.8	6.0
1.2									4.3	7.8	7.5
1.4	2.3	.2	.1						7.3	11.2	11.0
2.1	2.8	1.1							17.0	10.6	10.0
1.3	.5								9.6	8.2	8.0
2.7	.8								9.5	8.4	8.5
4.3	.8	.1							15.1	8.3	8.0
2.4	1.9	.3							12.4	10.2	10.0
////////////////////////////////////									4.0	////////////////////////////////////	
1.4	11.4	2.2	.2						100.0	8.9	9.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: DEC HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	1.8	4.3	3.5	1.1	.2							11.0
020-040	1.2	2.0	.9	.4	.3							4.8
050-070	.3	.9										1.2
(E) 080-100	.9	.3										1.2
110-130	.5	.9										1.4
140-160	.5	1.7	.9									3.1
(S) 170-190	2.2	3.1	2.5	2.5	.4							10.6
200-220	1.7	6.5	5.1	2.4	.6	.2						16.5
230-250	1.4	4.3	1.5	.3								7.5
(W) 260-280	2.5	3.9	2.8	.6	.2							10.1
290-310	3.0	6.0	4.3	.5								13.9
320-340	2.0	5.6	5.1	.8	.1							13.8
.....												
VARIABLE												
CALM	////////////////////////////////////											4.9
TOTALS	19.1	39.7	26.6	8.6	1.8	.2						100.0

TOTAL NUMBER OF OBSERVATIONS 930

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: DEC HOURS: 15-17

WIND SPEED IN KNOTS										
5-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.1	.2							11.0	9.1	8.0
.4	.3							4.8	8.9	8.0
								1.2	4.7	5.0
								1.2	3.6	4.0
								1.4	5.1	5.0
								3.1	7.4	8.0
2.5	.4							10.6	10.0	10.0
2.4	.6	.2						16.5	10.1	10.0
.3								7.5	7.5	7.0
.6	.2							10.1	8.1	8.0
.5								13.9	7.8	7.0
.3	.1							13.8	8.8	9.0
								4.9	////////////////	
1.6	1.8	.2						100.0	8.2	8.0
NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: DEC HOURS: 1

WIND SPEED IN KNOTS

DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TO
(N) 350-010	2.3	1.8	2.2	1.1	.1							7
020-040	1.0	1.4	.8	.4	.2	.1						3
050-070	.4	.3	.1									1
(E) 080-100	.4	.5		.1								1
110-130	.9	.8	.1									1
140-160	1.3	1.4	.6									3
(S) 170-190	1.5	4.1	3.0	1.1	.4	.3						10.
200-220	3.7	4.9	4.0	1.3	.9	.1						14.
230-250	3.9	4.1	1.6	.1	.3							10.
(W) 260-280	3.2	3.2	2.0	.4								8.
290-310	3.7	4.8	2.0	.2								10.
320-340	3.0	4.8	4.5	.8								13.
VARIABLE												
CALM	////////////////////											13.
TOTALS	25.3	32.6	20.9	5.5	1.9	.5						100.

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME: + 5 MONTH: DEC HOURS: 18-20

WIND SPEED IN KNOTS					TOTAL %	MEAN WIND	MEDIAN WIND
15-19	20-24	25-29	30-34	35-39			
1.1	.1				7.4	8.8	8.0
.4	.2	.1			3.9	9.3	8.0
					1.3	5.1	5.0
.1					1.1	6.3	5.5
					1.7	4.3	3.5
					3.3	6.2	6.0
1.1	.4	.3			10.4	10.1	9.0
1.3	.9	.1			14.8	9.0	8.0
.1	.3				10.0	6.6	6.0
.4					8.9	6.5	6.0
.2					10.8	6.6	6.0
.8					13.1	8.1	8.0

13.2
 5.5 1.9 .5 100.0 6.8 7.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS W
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: DEC HOURS: 21-

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOTAL %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	2.3	.8	2.6	1.5	.2	.2						8.1
020-040	.1	1.0	.8	.2	.1							2.2
050-070	.5	.9	.1									1.5
(E) 080-100	.4	.4										.9
110-130	.5	1.0	.1									1.6
140-160	1.6	1.5	.4									3.5
(S) 170-190	2.3	4.2	2.4	1.4	.5							10.8
200-220	3.3	6.6	4.2	1.3	.9							16.2
230-250	4.4	4.0	1.3		.1							9.8
(W) 260-280	4.1	5.2	2.2	.2								11.6
290-310	3.3	4.2	1.9	.2								10.1
320-340	2.4	3.5	5.4	.5								11.8
VARIABLE												
CALM	////////////////////////////////////											11.9
TOTALS	26.2	33.3	21.4	5.3	1.8	.2						100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: DEC HOURS: 21-23

WIND SPEED IN KNOTS										
15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
1.5	.2	.2						8.1	9.6	10.0
.2	.1							2.2	10.0	9.5
								1.5	5.3	5.5
								.9	4.6	4.5
								1.6	5.1	6.0
								3.5	5.5	5.0
1.4	.5							10.8	9.0	8.0
1.3	.9							16.2	8.8	8.0
	.1							9.8	5.8	5.0
.2								11.6	6.4	6.0
.2								10.1	6.5	6.0
.5								11.8	8.6	9.5
								11.9		
5.3	1.8	.2						100.0	6.8	7.0
TOTAL NUMBER OF OBSERVATIONS 930										

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: DEC HOURS: A

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TO	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	1.8	2.3	2.9	1.3	.4	.1	.1	.0				8
020-040	1.2	1.4	.9	.3	.1	.0						4
050-070	.6	.7	.1									1
(E) 080-100	.6	.4	.0	.0								1
110-130	.7	.8	.1									1
140-160	.9	1.6	.6									3
(S) 170-190	2.0	3.1	2.6	1.6	.3	.1						9
200-220	3.5	5.6	4.1	1.7	.9	.1						16
230-250	3.9	4.1	1.5	.2	.1							9
(W) 260-280	3.3	4.5	2.0	.3	.0							10
290-310	3.4	5.0	2.7	.3	.0							12
320-340	2.2	4.5	4.1	.9	.1							11
VARIABLE												
CALM	////////////////////										9	
TOTALS	24.6	35.0	21.7	6.6	1.9	.3	.1					100

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: DEC HOURS: ALL

DIRECTION	WIND SPEED IN KNOTS						TOTAL	MEAN WIND	MEDIAN WIND
	15-19	20-24	25-29	30-34	35-39	40-49			
0	1.3	.4	.1	.1	.0		8.8	10.2	10.0
1	.3	.1	.0				4.0	8.2	8.0
2							1.4	5.1	5.0
3	.0						1.1	4.6	4.0
4							1.6	5.0	5.0
5							3.2	6.7	6.0
6	1.6	.3	.1				9.7	9.6	9.0
7	1.7	.9	.1				16.0	9.2	8.0
8	.2	.1					9.8	6.2	6.0
9	.3	.0					10.6	6.5	6.0
10	.3	.0					12.3	7.1	7.0
11	.9	.1					11.7	8.7	8.0
12							9.7		
13	6.6	1.9	.3	.1			100.0	7.2	7.0

TOTAL NUMBER OF OBSERVATIONS 7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: DEC HOURS: AL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING

DIRECTION (DEGREES)	WIND SPEED IN KNOTS								TOT %			
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39		40-49	50-64	GE 65
(N) 350-010	2.1	4.2	6.3	3.2	.7							16.
020-040	2.1	2.9	2.3	.5	.1							7.
050-070	1.2	1.1	.3									2.
(E) 080-100	1.0	1.2	.0	.0								2.
110-130	1.1	1.7	.2									3.
140-160	1.4	2.9	1.0									6.
(S) 170-190	1.7	3.0	4.6	3.4	.6	.0						13.
200-220	2.2	3.8	3.8	1.9	1.4	.0						13.
230-250	1.5	1.4	.5	.0	.0							3.
(W) 260-280	1.7	1.2	.3	.1								3.
290-310	2.1	3.0	1.1	.2	.0							6.
320-340	1.7	4.7	5.3	1.8	.2							13.
VARIABLE												
CALM	////////////////////////////////////										7.	
TOTALS	20.1	31.1	27.1	11.1	3.0							100.

TOTAL NUMBER OF OBSERVATIONS 2080

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: DEC HOURS: ALL

LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 MILE (0900 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS

	-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
										%	WIND	WIND
1	0.3	3.2	.7							16.5	10.8	11.0
2	0.3	.5	.1							7.9	8.2	8.0
3	.3									2.5	5.5	5.0
4	.0	.0								2.2	5.2	5.0
5	.2									3.0	5.4	5.5
6	1.7									6.2	7.4	7.0
7	0.6	3.4	.6	.0						13.3	11.4	11.0
8	2.3	1.9	1.4	.0						13.1	10.6	10.0
9	.0	.0	.0							3.9	5.7	5.0
10	.0	.1								3.8	6.1	5.0
11	0.1	.2	.0							6.4	6.6	6.0
12	.3	1.8	.2							13.8	9.9	10.0
////////////////////////////////////										7.3	////////////////////////////////////	
13	7.1	11.1	3.0							100.0	8.4	8.0

TOTAL NUMBER OF OBSERVATIONS 2080

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 73
 MONTH: ALL HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.7	4.1	3.8	1.6	.6	.1	.0	.0	.0			13.0
020-040	2.4	5.0	2.4	.4	.1	.0						10.3
050-070	1.6	1.5	.3	.0								3.5
(E) 080-100	1.0	.6	.1	.0	.0							1.7
110-130	.9	.3	.1	.0								1.3
140-160	1.2	1.9	.9	.1	.0	.0	.0					4.0
(S) 170-190	2.3	4.7	3.7	1.2	.3	.0	.0					12.3
200-220	3.4	5.3	3.4	1.0	.3	.0	.0	.0				13.5
230-250	2.4	2.5	1.2	.2	.0	.0	.0					6.4
(W) 260-280	2.2	2.2	.9	.1	.0	.0						5.5
290-310	2.4	3.0	1.4	.3	.1	.0						7.1
320-340	2.0	3.2	2.5	.7	.2	.0	.0					8.5
VARIABLE												
CALM	////////////////////										12.4	
TOTALS	24.5	34.9	20.6	5.6	1.6	.1						100.0

TOTAL NUMBER OF OBSERVATIONS: 87647

SP

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED FROM HOURLY OBSERVATIONS

JUL

STATION: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
+ 5 MONTH: ALL HOURS: ALL

MEA

WIN

9.

7.

5.

4.

5.

7.

9.

5.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

6.

WIND SPEED IN KNOTS

	10-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
									%	WIND	WIND
9.									13.0	9.6	9.0
7.	1.6	.6	.1	.0	.0	.0			10.3	7.6	7.0
5.	.4	.1	.0						3.5	5.2	5.0
4.	.0								1.7	4.5	4.0
5.	.0	.0							1.8	5.1	5.0
7.	.0								4.0	7.0	7.0
9.	.1	.0	.0	.0					12.3	8.9	8.0
5.	1.2	.3	.0	.0					13.5	8.1	8.0
6.	1.0	.3	.0	.0	.0				6.4	6.6	6.0
6.	.2	.0	.0	.0					5.5	6.2	5.0
6.	.1	.0	.0						7.1	6.9	6.0
6.	.3	.1	.0						8.6	8.4	8.0
6.	.7	.2	.0	.0					//////////////////////////////////// 12.4 //////////////////////////////////////		
6.	.6	1.6	.1						100.0	6.8	7.0

NUMBER OF OBSERVATIONS: 87667

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: ALL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
 AND/OR
 VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING C

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64		GE 65
(N) 350-010	2.2	6.4	7.8	3.9	1.3	.1						21.7
020-040	2.9	5.8	3.6	.8	.2	.0						13.4
050-070	1.7	1.6	.3	.0								3.6
(E) 080-100	1.3	1.0	.1	.0	.0							2.5
110-130	1.0	1.3	.3	.0								2.6
140-160	1.3	2.7	1.6	.2	.0	.0	.0					5.8
(S) 170-190	1.7	4.8	5.0	1.9	.5	.0						13.9
200-220	2.0	4.4	3.2	.9	.3	.0		.0				10.7
230-250	1.4	1.2	.4	.1	.0							3.1
(W) 260-280	1.1	.9	.4	.1	.0	.0						2.6
290-310	1.2	1.6	.7	.3	.0							3.9
320-340	1.4	3.5	3.7	1.3	.3	.0	.0					10.3

VARIABLE

CALM	////////////////////										6.0	
TOTALS	19.2	35.2	27.1	9.5	2.6	.1						100.0

TOTAL NUMBER OF OBSERVATIONS: 16969

STAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI + 5 PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: ALL HOURS: ALL

WIND SPEED GE 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
WIND SPEED GE 1000 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS										
19-24	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
								%	WIND	WIND
3.9	1.3	.1						21.7	11.0	10.0
.5	.2	.0						13.4	8.1	8.0
.0								3.6	5.3	5.0
.0	.0							2.5	5.0	4.0
.0								2.6	5.7	6.0
.2	.0	.0	.0					5.8	7.8	7.0
1.9	.5	.0						13.9	10.1	10.0
.9	.3	.0		.0				10.7	8.7	8.0
.1	.0							3.1	5.7	5.0
.1	.0	.0						2.6	6.0	5.0
.3	.0							3.9	7.3	6.5
1.3	.3	.0	.0					10.3	9.9	10.0
								6.0	6.0	6.0
9.5	2.6	.1						100.0	8.4	8.0

TOTAL NUMBER OF OBSERVATIONS: 16969

PPPPPPP	AAAAAA	RRRRRRR	TTTTTTTTT	DDDDDDD
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TTTTTTTTT	DDDDDDDD
PP PP	AA AA	RR RR	TT	DD DD
PP PP	AA AA	RR RR	TT	DD DD
PPPPPPPP	AA AA	RRRRRRR	TT	DD DD
PPPPPPPP	AAAAAAAAA	RRRRRRR	TT	DD DD
PP	AAAAAAAAA	RR RR	TT	DD DD
PP	AA AA	RR RR	TT	DD DD
PP	AA AA	RR RR	TT	DDDDDDDD
PP	AA AA	RR RR	TT	DDDDDDDD

PART D

CEILING VERSUS VISIBILITY AND SKY COVER SUMMARIES

CEILING VS VISIBILITY--PERCENT OCCURRENCE FREQUENCY (POF).

CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY IS A BIVARIATE DISTRIBUTION OF PERCENTAGE FREQUENCY BY CLASSES OF CEILING (FROM ZERO FEET TO 20,000 FEET-- "NO CEILING" IS A SEPARATE CLASS) VERSUS VISIBILITY CLASSES (FROM ZERO MILES (METERS) TO GREATER THAN OR EQUAL TO 7 STATUTE MILES (11,200 METERS)). THE TABLES SUMMARIZE THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

BECAUSE OF THE CUMULATIVE NATURE OF THESE SUMMARIES, IT IS POSSIBLE TO DETERMINE THE PERCENTAGE OCCURRENCE FREQUENCY (POF) FOR ANY GIVEN CEILING AND/OR VISIBILITY LIMIT(S), EITHER SEPARATELY OR IN ANY COMBINATION. TOTALS PROGRESS FROM RIGHT TO LEFT AND FROM BOTTOM TO TOP. TO DETERMINE CEILING ALONE, REFER TO THE EXTREME RIGHT-HAND COLUMN (ZERO VISIBILITY). TO DETERMINE VISIBILITY ALONE, REFER TO THE BOTTOM ROW (ZERO CEILINGS). TO DETERMINE THE POF THAT MEETS OR EXCEEDS ANY GIVEN SET OF MAXIMA BY READING THE VALUE AT THE INTERSECTION OF THE APPROPRIATE CEILING ROW AND VISIBILITY COLUMN.

NOTE 1: IN JANUARY 1968, METAR STATIONS BEGAN REPORTING VISIBILITIES TO 6 STATUTE MILES OR 9000 METERS. VALUES EXCEEDING 9000 METERS ARE REPORTED AS "9999."

NOTE 2: FOR OVERSEAS CIVILIAN STATIONS REPORTING "CAVOK", ALL CEILINGS GREATER THAN 5000 FEET APPEAR IN THE 5000 FEET CLASS.

CONVERSIONS: 1 STATUTE MILE = 1,609.344 METERS = .868391 NAUTICAL MILES.
FOR CONVENIENCE, THE CONVERSION OFTEN USED IS 1 STATUTE MILE = 1,600 METERS.

SKY COVER--PERCENT OCCURRENCE FREQUENCY.

ALSO CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY GIVES PERCENTAGE OCCURRENCE FREQUENCY (POF) OF SKY COVER IN EIGHTHS FOR SYNOPTIC STATIONS, BUT AS CLEAR, SCATTERED, BROKEN, OVERCAST, PARTIALLY OBSCURED, OR TOTALLY OBSCURED FOR AIRWAYS STATIONS. FOR AIRWAYS STATIONS, THIS SUMMARY ALSO GIVES POF FOR SKY COVER GREATER THAN ONE-HALF (I.E., 6/10). DATA IS SUMMARIZED THE SAME AS FOR PREVIOUS TABLE.

NOTE 1. THESE SUMMARIES ARE NOT AVAILABLE FOR METAR REPORTING STATIONS.

NOTE 2. AIRWAYS STATIONS THAT HAVE REPORTED IN SYNOPTIC CODE HAVE HAD THEIR
SYNOPTIC SKY COVER REPORTS CONVERTED AS FOLLOWS:

0/8.....CLEAR

1/8 THRU 4/8.....SCATTERED

5/8 THRU 7/8.....BROKEN

9/8.....OVERCAST

NOTE 3. "PARTIAL OBSCURATION" IS A SEPARATE CATEGORY NOT INCLUDED IN
COMPUTATION OF "GREATER THAN 1/2" PERCENTAGES. "TOTAL OBSCURATIONS,"
HOWEVER, ARE INCLUDED.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: 00-02

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	30.6	30.8	30.8	30.8	31.3	31.3	31.4	31.6	31.7	31.7	31.8	31.8	31.8
GE 20000	31.5	31.6	31.7	31.7	32.3	32.3	32.4	32.6	32.7	32.7	32.9	32.9	32.9
GE 18000	31.9	32.0	32.2	32.2	32.7	32.7	32.8	33.0	33.1	33.1	33.3	33.3	33.3
GE 16000	31.9	32.0	32.2	32.2	32.7	32.7	32.8	33.0	33.1	33.1	33.3	33.3	33.3
GE 14000	32.0	32.2	32.3	32.3	32.8	32.8	32.9	33.1	33.2	33.2	33.4	33.4	33.4
GE 12000	32.8	32.9	33.0	33.0	33.5	33.5	33.7	33.9	34.0	34.0	34.2	34.2	34.2
GE 10000	33.9	34.0	34.1	34.1	34.6	34.6	34.7	34.9	35.1	35.1	35.3	35.3	35.3
GE 9000	34.1	34.2	34.3	34.3	34.8	34.8	34.9	35.2	35.3	35.3	35.5	35.5	35.5
GE 8000	34.8	34.9	35.3	35.3	35.8	35.8	35.9	36.1	36.2	36.2	36.5	36.5	36.5
GE 7000	35.8	35.9	36.2	36.2	36.8	36.8	36.9	37.2	37.3	37.3	37.5	37.5	37.5
GE 6000	36.1	36.2	36.6	36.6	37.1	37.1	37.2	37.5	37.6	37.6	37.8	37.8	37.8
GE 5000	37.2	37.3	37.6	37.7	38.3	38.3	38.4	38.7	38.8	38.8	39.0	39.0	39.0
GE 4500	37.7	37.8	38.2	38.4	38.9	38.9	39.1	39.5	39.6	39.6	39.8	39.8	39.8
GE 4000	39.7	39.8	40.1	40.3	41.0	41.0	41.3	41.6	41.7	41.7	41.9	41.9	41.9
GE 3500	41.1	41.2	41.6	41.9	42.7	42.7	43.0	43.3	43.4	43.4	43.9	43.9	43.9
GE 3000	43.9	44.3	45.1	45.5	47.0	47.1	47.4	47.7	47.8	47.8	48.3	48.3	48.3
GE 2500	49.9	50.3	51.4	52.0	54.2	54.3	54.8	55.4	55.7	55.8	56.2	56.2	56.2
GE 2000	53.3	54.2	56.1	56.8	59.4	59.6	61.0	62.4	62.9	63.0	63.4	63.4	63.4
GE 1800	56.1	56.6	58.8	59.5	62.5	62.7	64.3	65.8	66.3	66.5	66.9	66.9	66.9
GE 1500	59.9	60.3	62.9	63.5	66.8	67.8	69.8	72.2	73.7	74.3	75.3	75.3	75.3
GE 1200	61.6	62.0	64.8	65.6	69.5	70.5	73.4	75.9	77.6	78.3	79.4	79.4	79.5
GE 1000	63.2	63.7	66.8	67.7	72.0	73.1	76.6	79.2	81.2	81.9	83.0	83.0	83.1
GE 900	64.0	64.7	67.8	68.8	73.2	74.3	77.8	81.1	83.3	84.2	85.3	85.3	85.4
GE 800	64.6	65.5	69.6	69.6	74.0	75.2	79.0	82.4	84.6	85.7	86.8	86.8	86.9
GE 700	65.1	65.9	69.1	70.3	75.2	76.5	80.3	83.8	86.3	87.5	89.0	89.1	89.2
GE 600	66.1	67.0	70.4	71.6	76.5	77.8	81.8	85.6	88.4	89.6	91.2	91.3	91.5
GE 500	66.3	67.3	70.8	72.0	77.0	78.4	82.4	86.1	89.6	90.9	92.7	92.8	93.0
GE 400	66.3	67.3	70.8	72.4	77.5	79.1	83.5	87.5	91.0	92.6	94.4	94.5	94.9
GE 300	66.7	67.6	71.1	72.7	78.1	79.6	84.0	88.4	92.5	94.5	96.5	96.7	97.5
GE 200	66.7	67.6	71.1	72.7	78.1	79.6	84.0	88.5	92.7	94.8	97.0	97.2	98.1
GE 100	66.7	67.6	71.1	72.7	78.1	79.6	84.0	88.5	92.7	94.8	97.1	97.3	98.2
GE 000	66.7	67.6	71.1	72.7	78.1	79.6	84.0	88.5	92.7	94.8	97.1	97.3	98.2

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 00-02

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.8	31.3	31.3	31.4	31.6	31.7	31.7	31.8	31.8	31.8	31.9	31.9	31.9
31.7	32.3	32.3	32.4	32.6	32.7	32.7	32.9	32.9	32.9	33.0	33.0	33.0
32.2	32.7	32.7	32.8	33.0	33.1	33.1	33.3	33.3	33.3	33.4	33.4	33.4
32.2	32.7	32.7	32.8	33.0	33.1	33.1	33.3	33.3	33.3	33.4	33.4	33.4
32.3	32.8	32.8	32.9	33.1	33.2	33.2	33.4	33.4	33.4	33.5	33.5	33.5
33.0	33.5	33.5	33.7	33.9	34.0	34.0	34.2	34.2	34.2	34.3	34.3	34.3
34.1	34.6	34.6	34.7	34.9	35.1	35.1	35.3	35.3	35.3	35.4	35.4	35.4
34.3	34.8	34.8	34.9	35.2	35.3	35.3	35.5	35.5	35.5	35.6	35.6	35.6
35.3	35.8	35.8	35.9	36.1	36.2	36.2	36.5	36.5	36.5	36.6	36.6	36.6
36.2	36.8	36.8	36.9	37.2	37.3	37.3	37.5	37.5	37.5	37.6	37.6	37.6
36.6	37.1	37.1	37.2	37.5	37.6	37.6	37.8	37.8	37.8	38.0	38.0	38.0
37.7	38.3	38.3	38.4	38.7	38.8	38.8	39.0	39.0	39.0	39.1	39.1	39.1
38.4	38.9	38.9	39.1	39.5	39.6	39.6	39.8	39.8	39.8	39.9	39.9	39.9
40.3	41.0	41.0	41.3	41.6	41.7	41.7	41.9	41.9	41.9	42.0	42.0	42.0
41.9	42.7	42.7	43.0	43.3	43.4	43.4	43.9	43.9	43.9	44.0	44.0	44.0
45.5	47.0	47.1	47.4	47.7	47.8	47.8	48.3	48.3	48.3	48.4	48.4	48.4
52.0	54.2	54.3	54.8	55.4	55.7	55.8	56.2	56.2	56.2	56.3	56.3	56.3
56.3	59.4	59.6	61.0	62.4	62.9	63.0	63.4	63.4	63.4	63.5	63.5	63.5
59.5	62.5	62.7	64.3	65.8	66.3	66.5	66.9	66.9	66.9	67.0	67.0	67.0
63.5	66.8	67.8	69.8	72.2	73.7	74.3	75.3	75.3	75.3	75.4	75.4	75.4
65.6	69.5	70.5	73.4	75.9	77.6	78.3	79.4	79.4	79.5	79.8	79.8	79.8
67.7	72.0	73.1	76.6	79.2	81.2	81.9	83.0	83.0	83.1	83.4	83.4	83.4
68.6	73.2	74.3	77.8	81.1	83.3	84.2	85.3	85.3	85.4	85.7	85.7	85.7
69.6	74.0	75.2	79.0	82.4	84.6	85.7	86.8	86.8	86.9	87.2	87.2	87.2
70.3	75.2	76.5	80.3	83.8	86.3	87.5	89.0	89.1	89.2	89.6	89.6	89.6
71.6	76.5	77.8	81.8	85.6	88.4	89.6	91.2	91.3	91.5	91.8	91.8	91.8
72.0	77.0	78.4	82.4	86.1	89.6	90.9	92.7	92.8	93.0	93.3	93.4	93.4
72.4	77.6	79.1	83.5	87.5	91.0	92.6	94.4	94.5	94.9	95.4	95.6	95.8
72.7	78.1	79.6	84.0	88.4	92.5	94.5	96.5	96.7	97.5	98.0	98.5	98.7
72.7	78.1	79.6	84.0	88.5	92.7	94.8	97.0	97.2	98.1	98.6	99.5	99.7
72.7	78.1	79.6	84.0	88.5	92.7	94.8	97.1	97.3	98.2	98.7	99.6	100.0
72.7	79.1	79.6	84.0	88.5	92.7	94.8	97.1	97.3	98.2	98.7	99.6	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: 03-05

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	30.1	30.3	30.3	30.3	30.9	31.3	31.3	31.6	31.7	31.8	31.8	31.8	31.8	31.8
GE 20000	30.3	31.0	31.0	31.0	31.7	32.2	32.2	32.5	32.6	32.7	32.7	32.7	32.7	32.7
GE 18000	31.3	31.5	31.5	31.5	32.3	32.7	32.7	33.0	33.1	33.2	33.2	33.2	33.2	33.2
GE 16000	31.3	31.5	31.5	31.5	32.3	32.7	32.7	33.0	33.1	33.2	33.2	33.2	33.2	33.2
GE 14000	31.3	31.5	31.5	31.5	32.3	32.7	32.7	33.0	33.1	33.2	33.2	33.2	33.2	33.2
GE 12000	32.2	32.4	32.4	32.4	33.1	33.5	33.5	33.9	34.0	34.1	34.1	34.1	34.1	34.1
GE 10000	33.4	33.7	33.7	33.7	34.4	34.8	34.8	35.2	35.3	35.4	35.4	35.4	35.4	35.4
GE 9000	33.4	33.7	33.7	33.7	34.4	34.8	34.8	35.2	35.3	35.4	35.4	35.4	35.4	35.4
GE 8000	34.3	34.5	34.7	34.7	35.5	35.9	35.9	36.2	36.3	36.5	36.5	36.5	36.5	36.5
GE 7000	35.5	35.9	36.1	36.1	37.0	37.4	37.4	37.7	37.8	38.0	38.0	38.0	38.0	38.0
GE 6000	36.2	36.7	36.9	36.9	37.7	38.2	38.2	38.5	38.6	38.7	38.7	38.7	38.7	38.7
GE 5000	37.8	38.3	38.6	38.6	39.5	39.9	39.9	40.2	40.3	40.4	40.4	40.4	40.4	40.4
GE 4500	39.4	39.8	40.1	40.1	41.1	41.5	41.5	41.8	41.9	42.0	42.0	42.0	42.0	42.0
GE 4000	41.2	41.7	42.0	42.4	43.3	44.2	44.3	44.6	44.7	44.8	44.8	44.8	44.8	44.8
GE 3500	42.9	43.4	43.8	44.1	45.5	45.9	46.0	46.3	46.5	46.6	46.6	46.6	46.6	46.6
GE 3000	45.9	46.5	46.9	47.2	48.9	49.4	49.6	50.1	50.2	50.3	50.3	50.3	50.3	50.3
GE 2500	48.9	49.6	50.4	50.3	53.0	53.7	54.2	54.8	54.9	55.1	55.2	55.2	55.2	55.2
GE 2000	54.1	54.7	56.3	56.3	59.9	61.0	62.3	63.2	63.5	63.8	63.9	63.9	63.9	63.9
GE 1800	56.2	56.9	58.8	59.2	62.5	63.7	65.3	66.3	66.7	66.9	67.0	67.0	67.0	67.0
GE 1500	59.8	60.5	62.8	63.3	67.6	69.4	72.0	74.2	75.9	76.2	76.8	76.8	76.8	76.8
GE 1200	61.4	62.2	64.4	65.1	69.7	71.4	74.6	77.0	78.8	79.2	79.8	79.8	79.8	79.8
GE 1000	62.6	63.3	65.6	66.6	71.5	73.3	77.0	79.4	81.2	81.8	82.6	82.6	82.6	82.6
GE 900	63.7	64.4	66.7	67.6	72.7	74.5	78.5	81.0	82.9	83.5	84.3	84.3	84.3	84.3
GE 800	64.8	65.6	67.8	68.8	74.0	75.8	80.0	82.7	84.7	85.4	86.1	86.1	86.1	86.1
GE 700	65.5	66.2	68.6	69.6	74.3	76.7	81.0	84.0	86.2	87.0	88.2	88.2	88.2	88.2
GE 600	66.2	67.0	69.4	70.4	76.5	78.4	82.7	86.0	88.3	89.0	90.2	90.2	90.2	90.2
GE 500	66.7	67.4	69.8	70.9	77.0	79.0	83.5	87.4	90.2	91.1	92.8	92.8	92.8	92.8
GE 400	66.7	67.7	70.2	71.3	78.0	80.0	84.9	89.2	92.3	93.4	95.2	95.2	95.2	95.2
GE 300	66.8	67.9	70.4	71.5	78.2	80.2	85.5	90.1	93.3	94.6	96.7	96.8	96.8	96.8
GE 200	66.9	68.0	70.5	71.6	78.6	80.6	85.9	90.5	94.0	95.6	97.6	97.7	97.7	97.7
GE 100	66.9	68.0	70.5	71.6	78.6	80.6	85.9	90.5	94.1	95.7	97.7	97.7	97.7	97.7
GE 000	66.9	68.0	70.5	71.6	78.6	80.6	85.9	90.5	94.1	95.7	97.7	97.7	97.7	97.7

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 03-05

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.3	30.9	31.3	31.3	31.6	31.7	31.8	31.8	31.8	31.8	31.8	31.8	31.8
31.0	31.7	32.2	32.2	32.5	32.6	32.7	32.7	32.7	32.7	32.7	32.7	32.7
31.5	32.3	32.7	32.7	33.0	33.1	33.2	33.2	33.2	33.2	33.2	33.2	33.2
31.5	32.3	32.7	32.7	33.0	33.1	33.2	33.2	33.2	33.2	33.2	33.2	33.2
32.4	33.1	33.5	33.5	33.9	34.0	34.1	34.1	34.1	34.1	34.1	34.1	34.1
33.7	34.4	34.8	34.8	35.2	35.3	35.4	35.4	35.4	35.4	35.4	35.4	35.4
33.7	34.4	34.8	34.8	35.2	35.3	35.4	35.4	35.4	35.4	35.4	35.4	35.4
34.7	35.5	35.9	35.9	36.2	36.3	36.5	36.5	36.5	36.5	36.5	36.5	36.5
36.1	37.0	37.4	37.4	37.7	37.8	38.0	38.0	38.0	38.0	38.0	38.0	38.0
36.9	37.7	38.2	38.2	38.5	38.6	38.7	38.7	38.7	38.7	38.7	38.7	38.7
38.6	39.5	39.9	39.9	40.2	40.3	40.4	40.4	40.4	40.4	40.4	40.4	40.4
40.1	41.1	41.5	41.5	41.8	41.9	42.0	42.0	42.0	42.0	42.0	42.0	42.0
42.4	43.3	44.2	44.3	44.6	44.7	44.8	44.8	44.8	44.8	44.8	44.8	44.8
44.1	45.5	45.9	46.0	46.3	46.5	46.6	46.6	46.6	46.6	46.6	46.6	46.6
47.2	48.9	49.4	49.6	50.1	50.2	50.3	50.3	50.3	50.3	50.3	50.3	50.3
50.3	53.0	53.7	54.2	54.8	54.9	55.1	55.2	55.2	55.2	55.2	55.2	55.2
56.3	59.9	61.0	62.3	63.2	63.5	63.8	63.9	63.9	63.9	63.9	64.0	64.0
59.2	62.5	63.7	65.3	66.3	66.7	66.9	67.0	67.0	67.0	67.0	67.1	67.1
63.3	67.5	69.4	72.0	74.2	75.9	76.2	76.8	76.8	76.8	76.8	76.9	76.9
65.1	69.7	71.4	74.6	77.0	78.8	79.2	79.8	79.8	79.8	79.8	79.9	79.9
66.6	71.5	73.3	77.0	79.4	81.2	81.8	82.6	82.6	82.6	82.6	82.7	82.7
67.6	72.7	74.5	78.5	81.0	82.9	83.5	84.3	84.3	84.3	84.4	84.7	84.7
68.8	74.0	75.8	80.0	82.7	84.7	85.4	86.1	86.1	86.1	86.2	86.8	86.8
69.6	74.8	76.7	81.0	84.0	86.2	87.0	88.2	88.2	88.2	88.3	88.8	88.8
70.4	76.5	78.4	82.7	86.0	88.3	89.0	90.2	90.2	90.4	90.5	91.1	91.1
70.9	77.0	79.0	83.5	87.4	90.2	91.1	92.8	92.8	93.1	93.2	93.8	93.8
71.3	78.0	80.0	84.9	89.2	92.3	93.4	95.2	95.2	95.5	95.6	96.1	96.1
71.5	78.2	80.2	85.5	90.1	93.3	94.6	96.7	96.8	97.4	97.8	98.5	98.5
71.6	78.6	80.6	85.9	90.5	94.0	95.6	97.6	97.7	98.5	98.9	99.7	99.8
71.6	78.6	80.6	85.9	90.5	94.1	95.7	97.7	97.8	98.6	99.0	99.9	100.0
71.6	78.6	80.6	85.9	90.5	94.1	95.7	97.7	97.8	98.6	99.0	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	28.2	28.2	28.2	28.3	28.7	29.0	29.2	29.2	29.4	29.4	29.4	29.4	29.4	
GE 20000	29.7	29.7	29.7	29.8	30.2	30.5	30.8	30.8	30.9	30.9	30.9	30.9	30.9	
GE 18000	29.8	29.8	29.8	29.9	30.3	30.6	30.9	30.9	31.0	31.0	31.0	31.0	31.0	
GE 16000	29.8	29.8	29.8	29.9	30.3	30.6	30.9	30.9	31.0	31.0	31.0	31.0	31.0	
GE 14000	29.8	29.8	29.8	29.9	30.4	30.8	31.0	31.0	31.1	31.1	31.1	31.1	31.1	
GE 12000	30.5	30.5	30.5	30.6	31.2	31.5	31.7	31.7	31.8	31.8	31.8	31.8	31.8	
GE 10000	31.5	31.5	31.5	31.5	32.2	32.5	32.7	32.7	32.8	32.8	32.8	32.8	32.8	
GE 9000	31.7	31.7	31.7	31.8	32.4	32.7	32.9	32.9	33.0	33.0	33.0	33.0	33.0	
GE 8000	32.5	32.5	32.8	32.9	33.4	33.8	34.0	34.0	34.1	34.1	34.1	34.1	34.1	
GE 7000	33.4	33.4	33.8	33.9	34.4	34.7	34.9	34.9	35.1	35.1	35.1	35.1	35.1	
GE 6000	34.4	34.4	34.7	34.8	35.4	35.7	35.9	35.9	36.0	36.0	36.0	36.0	36.0	
GE 5000	36.3	36.3	36.7	36.8	37.3	37.6	37.8	38.0	38.1	38.1	38.1	38.1	38.1	
GE 4500	37.7	37.7	38.2	38.3	38.8	39.1	39.4	39.5	39.6	39.6	39.6	39.6	39.6	
GE 4000	39.5	39.5	40.0	40.3	41.2	41.5	41.8	41.9	42.0	42.0	42.0	42.0	42.0	
GE 3500	40.5	40.5	41.0	41.4	42.3	42.6	42.9	43.0	43.1	43.1	43.1	43.1	43.1	
GE 3000	42.9	43.1	43.9	44.4	45.3	45.6	45.9	46.1	46.2	46.2	46.2	46.2	46.2	
GE 2500	46.2	46.7	47.3	48.5	49.7	50.0	50.6	51.1	51.3	51.3	51.3	51.3	51.3	
GE 2000	50.3	50.8	52.5	53.3	55.4	56.2	57.3	58.0	58.4	58.5	58.5	58.5	58.5	
GE 1800	53.4	53.9	55.2	57.4	59.7	60.8	61.8	62.7	63.2	63.3	63.3	63.3	63.3	
GE 1500	57.8	58.5	61.0	62.6	66.2	67.4	69.7	71.4	72.0	72.5	72.6	72.6	72.6	
GE 1200	59.9	60.5	63.2	65.1	68.3	70.1	72.6	74.6	75.6	76.0	76.3	76.3	76.3	
GE 1000	61.2	61.8	64.6	66.9	70.8	72.2	74.9	77.4	78.9	79.5	80.1	80.1	80.2	
GE 900	62.4	63.0	65.8	68.1	72.4	73.8	76.7	79.2	80.9	81.4	82.3	82.3	82.4	
GE 800	63.4	64.1	66.9	69.1	73.9	75.3	78.7	81.7	83.3	83.9	85.1	85.1	85.2	
GE 700	64.6	65.3	68.1	70.3	75.5	76.9	80.8	83.8	85.7	86.5	87.7	87.8	88.0	
GE 600	65.3	65.9	68.3	71.3	76.9	78.3	82.2	85.4	87.3	88.2	89.6	89.8	90.0	
GE 500	65.6	66.2	69.4	71.9	77.6	79.2	83.2	86.9	89.5	90.8	92.6	92.8	93.0	
GE 400	66.0	66.7	70.1	72.7	78.5	80.1	84.4	88.3	91.1	92.4	94.2	94.4	94.7	
GE 300	66.2	66.9	70.4	73.0	78.8	80.4	84.7	88.9	92.0	93.5	95.4	95.6	95.9	
GE 200	66.5	67.1	70.6	73.3	79.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.7	
GE 100	66.5	67.1	70.6	73.3	79.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.8	
GE 000	66.5	67.1	70.6	73.3	79.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.8	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

JUL 30	PERIOD OF RECORD: AUG 78 - JUL 88												
	MONTH: JAN HOURS: 06-08												
VISIBILITY IN STATUTE MILES													
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0	
29	28.3	28.7	29.0	29.2	29.2	29.4	29.4	29.4	29.4	29.4	29.4	29.4	29.4
30	29.9	30.2	30.5	30.9	30.8	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9
31	29.9	30.3	30.6	30.9	30.9	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
31	29.9	30.3	30.6	30.9	30.9	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
31	29.9	30.4	30.8	31.0	31.0	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1
31	30.6	31.2	31.5	31.7	31.7	31.8	31.8	31.8	31.8	31.8	31.8	31.8	31.8
32	31.6	32.2	32.5	32.7	32.7	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
33	31.9	32.4	32.7	32.9	32.9	33.0	33.0	33.0	33.0	33.0	33.0	33.0	33.0
34	32.9	33.4	33.8	34.0	34.0	34.1	34.1	34.1	34.1	34.1	34.1	34.1	34.1
35	33.9	34.4	34.7	34.9	34.9	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1
36	34.8	35.4	35.7	35.9	35.9	36.0	36.0	36.0	36.0	36.0	36.0	36.0	36.0
37	36.4	37.3	37.6	37.9	38.0	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1
38	36.3	37.8	39.1	39.4	39.5	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6
42	40.3	41.2	41.5	41.8	41.9	42.0	42.0	42.0	42.0	42.0	42.0	42.0	42.0
43	41.4	42.3	42.6	42.9	43.0	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
43	44.4	45.3	45.6	45.9	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
51	47.5	49.7	50.0	50.6	51.1	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3
52	53.3	55.4	56.2	57.3	58.0	58.4	58.5	58.5	58.5	58.5	58.5	58.6	58.6
62	67.4	69.7	69.8	61.8	62.7	63.2	63.3	63.3	63.3	63.3	63.3	63.5	63.5
72	62.6	65.2	67.4	69.7	71.4	72.0	72.5	72.6	72.6	72.6	72.6	72.8	72.8
75	65.1	68.3	70.1	72.6	74.6	75.6	76.0	76.3	76.3	76.3	76.3	76.6	76.6
80	66.9	70.8	72.2	74.9	77.4	78.9	79.5	80.1	80.1	80.2	80.3	80.8	80.8
82	68.1	72.4	73.8	76.7	79.2	80.9	81.4	82.3	82.3	82.4	82.5	82.9	82.9
85	69.1	73.9	75.3	78.7	81.7	83.3	83.9	85.1	85.1	85.2	85.4	85.8	85.8
88	70.3	75.5	76.9	80.8	83.8	85.7	86.5	87.7	87.8	88.0	88.3	88.8	88.8
90	71.3	76.9	78.3	82.2	85.4	87.3	88.2	89.6	89.8	90.0	90.4	91.0	91.0
93	71.9	77.6	79.2	83.2	86.9	89.5	90.8	92.6	92.8	93.0	93.5	94.1	94.1
95	72.7	78.5	80.1	84.4	88.3	91.1	92.4	94.2	94.4	94.7	95.3	95.8	95.8
96	73.0	79.8	80.4	84.7	88.9	92.0	93.5	95.4	95.6	95.9	96.5	97.3	97.6
98	73.3	79.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.7	98.3	99.2	99.7
98	73.3	77.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.8	98.4	99.5	100.0
99	73.3	77.2	80.9	85.5	90.0	93.5	95.2	97.0	97.2	97.8	98.4	99.5	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 7
 LST TO UTC: + 5 MONTH: JAN HOURS: 09-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	27.2	27.4	27.6	27.9	28.2	28.4	28.6	28.6	28.6	28.7	28.8	28.9	29
GE 20000	30.5	30.8	31.1	31.3	31.7	31.9	32.2	32.2	32.2	32.3	32.4	32.5	32
GE 18000	31.0	31.2	31.5	31.7	32.2	32.4	32.6	32.6	32.6	32.7	32.8	32.9	33
GE 16000	31.2	31.4	31.7	31.9	32.4	32.6	32.8	32.8	32.8	32.9	33.0	33.1	33
GE 14000	31.9	32.2	32.5	32.7	33.1	33.3	33.5	33.5	33.5	33.7	33.8	33.9	34
GE 12000	32.6	32.8	33.1	33.3	33.8	34.0	34.2	34.2	34.2	34.3	34.4	34.5	34
GE 10000	34.0	34.2	34.5	34.7	35.2	35.4	35.6	35.7	35.7	35.8	35.9	36.0	36
GE 9000	34.7	34.9	35.3	35.5	35.9	36.1	36.3	36.5	36.5	36.6	36.7	36.8	37
GE 8000	36.0	36.2	36.6	36.9	37.5	37.8	38.2	38.3	38.3	38.4	38.5	38.6	38
GE 7000	36.9	37.1	37.4	37.7	38.4	38.7	39.0	39.1	39.1	39.2	39.4	39.5	39
GE 6000	37.3	37.6	38.0	38.3	38.9	39.2	39.6	39.7	39.7	39.8	39.9	40.0	40
GE 5000	37.8	38.3	38.6	39.0	39.7	40.0	40.3	40.4	40.4	40.5	40.6	40.8	41
GE 4500	38.2	38.6	38.9	39.4	40.0	40.3	40.6	40.8	40.8	40.9	41.0	41.1	41
GE 4000	40.0	40.5	41.1	41.5	42.3	42.7	43.0	43.1	43.3	43.5	43.7	43.8	44
GE 3500	40.8	41.3	41.8	42.4	43.1	43.5	43.9	44.0	44.2	44.5	44.6	44.7	44
GE 3000	41.8	42.5	43.2	43.9	44.7	45.4	45.7	45.9	46.1	46.6	46.7	46.8	47
GE 2500	43.5	44.3	45.4	46.1	47.4	48.3	49.2	49.6	49.8	50.2	50.3	50.4	50
GE 2000	47.1	48.3	49.3	51.1	53.5	54.6	56.5	57.3	57.6	58.2	58.4	58.5	58
GE 1800	48.5	49.7	51.4	53.0	55.6	56.7	58.7	59.7	60.0	60.5	60.8	60.9	61
GE 1500	51.9	53.3	55.5	57.5	61.3	62.7	65.5	67.3	67.8	68.9	69.2	69.5	69
GE 1200	54.4	56.2	58.7	60.9	65.1	66.7	70.0	72.4	73.7	74.8	75.2	75.4	75
GE 1000	55.8	57.7	60.4	62.7	67.2	68.8	72.3	74.9	76.5	78.2	78.7	78.9	79
GE 900	55.1	58.1	61.0	63.3	68.2	69.8	73.2	76.2	78.0	79.9	80.6	80.9	81
GE 800	56.7	59.6	61.6	64.0	69.1	70.8	74.2	77.4	79.1	81.2	82.2	82.4	83
GE 700	57.2	59.1	62.2	64.5	70.2	71.8	75.6	79.1	80.9	83.0	84.4	84.6	85
GE 600	57.8	59.8	62.8	65.5	71.3	72.9	76.8	80.4	82.8	84.9	86.5	86.7	88
GE 500	58.4	60.4	63.4	66.2	72.4	74.2	78.2	82.4	85.3	88.1	89.8	90.0	91
GE 400	58.6	60.6	63.8	66.6	72.9	74.7	78.9	83.2	86.3	89.2	91.4	91.6	93
GE 300	58.7	60.8	64.1	66.9	73.2	75.1	79.3	84.1	87.3	90.4	92.8	93.0	94
GE 200	58.7	60.8	64.2	67.0	73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95
GE 100	59.7	60.8	64.2	67.0	73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95
GE 000	59.7	60.8	64.2	67.0	73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95

TOTAL NUMBER OF OBSERVATIONS 936

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

AF: K. I. SAWYER AFB MI
: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 09-11

VISIBILITY IN STATUTE MILES											
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
28.2	28.4	28.6	28.6	28.6	28.7	28.8	28.9	29.1	29.2	29.2	29.2
31.7	31.9	32.2	32.2	32.2	32.3	32.4	32.5	32.7	32.8	32.8	32.8
32.2	32.4	32.6	32.6	32.6	32.7	32.8	32.9	33.1	33.2	33.2	33.2
32.4	32.6	32.8	32.8	32.8	32.9	33.0	33.1	33.3	33.4	33.4	33.4
33.1	33.3	33.5	33.5	33.5	33.7	33.8	33.9	34.1	34.2	34.2	34.2
33.8	34.0	34.2	34.2	34.2	34.3	34.4	34.5	34.7	34.8	34.8	34.8
35.2	35.4	35.6	35.7	35.7	35.8	35.9	36.0	36.2	36.3	36.3	36.3
35.9	36.1	36.3	36.5	36.5	36.6	36.7	36.8	37.0	37.1	37.1	37.1
37.5	37.9	38.2	38.3	38.3	38.4	38.5	38.6	38.8	38.9	38.9	38.9
38.4	38.7	39.0	39.1	39.1	39.2	39.4	39.5	39.7	39.8	39.8	39.8
38.9	39.2	39.6	39.7	39.7	39.8	39.9	40.0	40.2	40.3	40.3	40.3
40.0	40.3	40.5	40.8	40.8	40.9	41.0	41.1	41.3	41.4	41.4	41.4
42.3	42.7	43.0	43.1	43.3	43.5	43.7	43.8	44.0	44.1	44.1	44.1
43.1	43.5	43.9	44.0	44.2	44.5	44.6	44.7	44.9	45.1	45.1	45.1
44.7	45.4	45.7	45.9	46.1	46.6	46.7	46.8	47.0	47.1	47.1	47.1
47.4	48.3	49.2	49.6	49.8	50.2	50.3	50.4	50.6	50.8	50.8	50.9
53.5	54.6	56.5	57.3	57.6	58.2	58.4	58.5	58.8	58.9	59.0	59.2
55.6	56.7	58.7	59.7	60.0	60.5	60.8	60.9	61.2	61.3	61.4	61.6
61.3	62.7	65.5	67.3	67.8	68.9	69.2	69.5	69.9	70.1	70.3	70.6
65.1	66.7	70.0	72.4	73.7	74.8	75.2	75.4	75.9	76.3	76.6	76.9
67.2	68.8	72.3	74.9	76.5	78.2	78.7	78.9	79.7	80.2	80.4	80.8
68.2	69.8	73.2	76.2	78.0	79.9	80.6	80.9	81.7	82.3	82.5	83.1
69.1	70.8	74.2	77.4	79.1	81.2	82.2	82.4	83.4	84.1	84.3	84.9
70.2	71.8	75.6	79.1	80.7	83.0	84.4	84.6	85.8	86.6	86.8	87.6
71.3	72.9	76.8	80.4	82.8	84.9	86.5	86.7	88.1	89.1	89.4	90.2
72.4	74.2	78.2	82.4	85.3	88.1	89.8	90.0	91.6	92.8	93.1	94.3
72.7	74.7	78.9	83.2	86.3	89.2	91.4	91.6	93.5	94.7	95.1	96.3
73.2	75.1	79.8	84.1	87.3	90.4	92.8	93.0	94.9	96.2	97.0	98.3
73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95.9	97.4	98.5	100.0
73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95.9	97.4	98.5	100.0
73.4	75.3	80.1	84.4	87.6	90.8	93.3	93.5	95.9	97.4	98.5	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JAN HOURS: 12-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	28.7	28.7	29.1	29.6	29.9	29.9	30.0	30.3	30.3	30.3	30.4	30.4	3
GE 20000	34.1	34.2	34.5	35.2	35.5	35.5	36.6	35.9	35.9	35.9	36.0	36.0	3
GE 18000	35.1	35.2	35.5	36.1	36.5	36.5	36.6	37.0	37.0	37.0	37.1	37.1	3
GE 16000	35.4	35.5	35.9	36.5	36.8	36.8	36.9	37.3	37.3	37.3	37.4	37.4	3
GE 14000	35.9	36.0	36.5	37.2	37.5	37.5	37.6	38.1	38.1	38.1	38.2	38.2	3
GE 12000	37.1	37.2	37.6	38.4	38.7	38.7	38.8	39.2	39.2	39.2	39.4	39.4	3
GE 10000	39.4	39.5	39.9	40.4	41.1	41.1	41.2	41.6	41.6	41.6	41.7	41.7	4
GE 9000	40.0	40.1	40.5	41.4	41.7	41.7	41.3	42.3	42.3	42.3	42.4	42.4	4
GE 8000	40.4	40.9	41.3	42.2	42.5	42.5	42.6	43.0	43.0	43.0	43.1	43.1	4
GE 7000	41.9	42.0	42.5	43.3	43.7	43.8	43.9	44.3	44.3	44.3	44.4	44.4	4
GE 6000	42.7	42.8	43.2	44.2	44.5	44.7	44.8	45.3	45.3	45.3	45.4	45.4	4
GE 5000	43.2	43.3	44.0	45.4	45.7	45.9	46.0	46.6	46.6	46.6	46.7	46.7	4
GE 4500	43.3	43.9	44.5	45.7	46.2	46.5	46.6	47.1	47.1	47.1	47.2	47.2	4
GE 4000	44.5	44.6	45.4	46.8	47.4	47.6	47.7	48.4	48.4	48.4	48.5	48.5	4
GE 3500	45.7	46.9	46.8	48.2	48.8	49.0	49.2	49.9	50.0	50.0	50.1	50.1	5
GE 3000	47.1	47.3	48.2	49.6	50.2	50.5	50.8	51.4	51.5	51.5	51.6	51.6	5
GE 2500	48.8	49.1	50.6	52.3	52.9	53.3	54.0	54.7	54.9	55.1	55.2	55.2	5
GE 2000	51.9	52.6	55.6	58.2	59.6	60.2	61.4	62.3	62.6	62.8	63.3	63.3	6
GE 1800	52.7	53.3	56.6	59.4	60.8	61.4	62.7	63.8	64.1	64.3	64.8	64.8	6
GE 1500	56.3	57.1	60.6	63.8	66.0	66.8	68.9	70.9	71.8	72.4	73.2	73.3	7
GE 1200	58.4	59.1	63.3	66.6	69.8	70.8	73.0	75.5	76.9	77.7	78.8	78.9	7
GE 1000	59.3	60.8	64.9	68.4	72.2	73.2	75.7	78.4	80.3	81.4	82.5	82.6	8
GE 700	60.6	61.6	65.3	69.2	73.4	74.5	77.0	79.9	81.9	83.1	84.2	84.3	8
GE 800	61.2	62.2	65.7	70.3	74.6	75.8	78.4	81.6	84.1	85.5	86.6	86.7	8
GE 700	61.7	62.7	67.2	71.0	75.3	76.5	79.2	82.6	85.1	86.6	87.6	87.8	8
GE 600	62.2	63.1	67.6	71.5	75.8	77.0	79.8	83.7	86.6	88.2	89.4	89.6	9
GE 500	62.5	63.5	68.1	71.9	76.2	77.5	80.4	84.5	87.7	89.9	91.3	91.6	9
GE 400	62.5	63.5	68.1	71.9	76.5	77.7	80.9	85.1	88.3	90.5	92.2	92.5	9
GE 300	62.5	63.5	68.1	71.9	76.6	77.8	81.1	85.5	88.9	91.2	93.5	93.9	9
GE 200	62.5	63.5	68.1	71.9	76.6	77.8	81.1	85.5	89.0	91.4	94.0	94.3	9
GE 100	62.5	63.5	68.1	71.9	76.6	77.8	81.1	85.5	89.0	91.4	94.0	94.3	9
GE 000	62.5	63.5	68.1	71.9	76.6	77.8	81.1	85.5	89.0	91.4	94.0	94.3	9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: JAN HOURS: 12-14

VISIBILITY IN STATUTE MILES												
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
29.9	29.9	30.0	30.3	30.3	30.3	30.4	30.4	30.4	30.4	30.4	30.4	30.4
35.5	35.5	36.6	35.9	35.9	35.9	36.0	36.0	36.0	36.0	36.0	36.0	36.0
35.5	36.5	36.6	37.0	37.0	37.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1
35.8	36.8	36.9	37.3	37.3	37.3	37.4	37.4	37.4	37.4	37.4	37.4	37.4
37.5	37.5	37.6	38.1	38.1	38.1	38.2	38.2	38.2	38.2	38.2	38.2	38.2
38.7	38.7	38.8	39.2	39.2	39.2	39.4	39.4	39.4	39.4	39.4	39.4	39.4
41.1	41.1	41.2	41.6	41.6	41.6	41.7	41.7	41.7	41.7	41.7	41.7	41.7
41.7	41.7	41.8	42.3	42.3	42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4
42.5	42.5	42.6	43.0	43.0	43.0	43.1	43.1	43.1	43.1	43.1	43.1	43.1
43.7	43.8	43.9	44.3	44.3	44.3	44.4	44.4	44.4	44.4	44.4	44.4	44.4
44.5	44.7	44.8	45.3	45.3	45.3	45.4	45.4	45.4	45.4	45.4	45.4	45.4
45.7	45.9	46.0	46.6	46.6	46.6	46.7	46.7	46.7	46.7	46.7	46.7	46.7
46.2	46.5	46.6	47.1	47.1	47.1	47.2	47.2	47.2	47.2	47.2	47.2	47.2
47.4	47.6	47.7	48.4	48.4	48.4	48.5	48.5	48.5	48.5	48.5	48.5	48.5
48.8	49.0	49.2	49.9	50.0	50.0	50.1	50.1	50.1	50.1	50.1	50.1	50.1
50.2	50.5	50.8	51.4	51.5	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6
52.9	53.3	54.0	54.7	54.9	55.1	55.2	55.2	55.2	55.3	55.3	55.3	55.3
57.6	60.2	61.4	62.3	62.6	62.8	63.3	63.3	63.5	63.7	63.7	63.7	63.7
60.8	61.4	62.7	63.8	64.1	64.3	64.8	64.8	65.1	65.2	65.2	65.2	65.2
66.0	66.8	68.9	70.9	71.8	72.4	73.2	73.3	73.7	73.8	73.8	74.0	74.0
69.8	70.8	73.0	75.5	76.9	77.7	78.8	78.9	79.2	79.5	79.5	79.8	79.8
72.2	73.2	75.7	78.4	80.3	81.4	82.5	82.6	83.1	83.4	83.4	83.8	83.8
73.4	74.5	77.0	79.9	81.0	83.1	84.2	84.3	84.9	85.3	85.3	85.9	85.9
74.5	75.8	78.4	81.6	84.1	85.5	86.6	86.7	87.3	87.7	87.7	88.4	88.4
75.3	76.5	79.2	82.6	85.1	86.6	87.6	87.8	88.7	89.2	89.2	89.9	89.9
75.3	77.0	79.8	83.7	86.6	88.2	89.4	89.6	91.0	91.5	91.5	92.2	92.2
75.2	77.5	80.4	84.5	87.7	89.9	91.3	91.6	93.3	94.0	94.1	95.1	95.1
76.5	77.7	80.9	85.1	88.3	90.5	92.2	92.5	94.5	95.3	95.4	96.7	96.7
76.6	77.8	81.1	85.5	88.9	91.2	93.5	93.9	96.3	97.3	97.6	98.9	98.9
76.6	77.8	81.1	85.5	89.0	91.4	94.0	94.3	97.0	98.1	98.7	100.0	100.0
76.6	77.8	81.1	85.5	89.0	91.4	94.0	94.3	97.0	98.1	98.7	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBIL
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	30.8	31.1	31.9	32.3	32.4	32.4	32.5	32.5	32.6	32.6	32.6	32.6	32.6
GE 20000	35.5	35.8	36.9	37.2	37.4	37.4	37.5	37.5	37.6	37.6	37.6	37.6	37.6
GE 18000	36.5	36.8	37.8	38.2	38.4	38.4	38.5	38.5	38.6	38.6	38.6	38.6	38.6
GE 16000	36.8	37.1	38.2	38.5	38.7	38.7	38.8	38.8	38.9	38.9	38.9	38.9	38.9
GE 14000	37.6	38.0	39.0	39.5	39.7	39.7	39.8	39.8	39.9	39.9	39.9	39.9	39.9
GE 12000	38.6	38.9	40.1	40.5	40.9	40.9	41.0	41.0	41.1	41.1	41.1	41.1	41.1
GE 10000	40.5	41.0	42.2	42.6	42.9	42.9	43.0	43.0	43.1	43.1	43.1	43.1	43.1
GE 9000	41.2	41.6	42.8	43.2	43.5	43.5	43.7	43.7	43.8	43.8	43.8	43.8	43.8
GE 8000	41.9	42.4	43.8	44.2	44.5	44.5	44.6	44.6	44.7	44.7	44.7	44.7	44.7
GE 7000	43.1	43.5	45.1	45.5	46.6	46.7	46.8	46.8	46.9	47.0	47.0	47.0	47.0
GE 6000	44.1	44.5	46.0	46.5	47.5	47.6	47.7	47.7	48.0	48.1	48.1	48.1	48.1
GE 5000	44.5	45.1	46.6	47.1	48.2	48.3	48.7	48.7	48.9	49.0	49.0	49.0	49.0
GE 4500	44.5	45.1	46.6	47.2	48.4	48.5	48.9	48.9	49.1	49.2	49.2	49.2	49.2
GE 4000	45.8	46.5	48.0	48.7	49.9	50.0	50.6	50.6	50.9	51.0	51.0	51.0	51.0
GE 3500	47.1	47.8	49.5	50.3	51.7	51.8	52.5	52.7	52.9	53.0	53.0	53.0	53.0
GE 3000	49.7	50.4	52.4	53.3	55.1	55.2	55.8	56.0	56.2	56.3	56.3	56.3	56.5
GE 2500	53.2	54.2	56.2	57.2	59.2	59.4	60.4	60.8	61.0	61.2	61.2	61.2	61.3
GE 2000	56.8	58.2	60.8	62.3	64.8	65.2	66.5	67.2	67.4	67.7	68.0	68.0	68.2
GE 1800	58.2	59.6	62.4	63.9	66.5	66.8	68.1	68.8	69.0	69.4	69.6	69.6	69.8
GE 1500	61.4	62.8	66.1	67.8	70.8	71.5	73.2	74.3	74.7	75.3	75.6	75.6	75.8
GE 1200	63.9	65.3	68.8	70.5	73.8	74.5	76.3	77.7	78.5	79.2	79.6	79.7	80.2
GE 1000	65.3	66.9	71.4	73.3	76.8	77.6	80.0	81.4	82.6	83.5	84.4	84.5	85.1
GE 900	65.6	67.3	71.9	74.0	77.8	78.7	81.2	82.9	84.1	85.1	85.9	86.0	86.6
GE 800	66.3	68.1	72.7	74.8	78.8	79.8	82.6	84.3	85.8	87.0	87.8	88.0	88.6
GE 700	66.6	68.3	73.1	75.4	79.5	80.4	83.5	85.5	87.0	88.2	89.0	89.1	90.0
GE 600	66.8	68.6	73.4	75.7	79.8	80.9	84.0	86.1	87.7	89.1	90.3	90.5	91.4
GE 500	67.1	68.9	73.8	76.1	80.2	81.3	84.7	87.0	89.0	90.9	92.5	92.7	93.7
GE 400	67.1	68.9	73.8	76.1	80.5	81.7	85.6	87.8	90.0	91.9	93.5	93.6	94.8
GE 300	67.1	68.9	73.8	76.1	80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.0
GE 200	67.1	68.9	73.8	76.1	80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.1
GE 100	67.1	68.9	73.8	76.1	80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.1
GE 000	67.1	68.9	73.8	76.1	80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.1

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 15-17

VISIBILITY IN STATUTE MILES

GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
32.4	32.4	32.5	32.5	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6
37.4	37.4	37.5	37.5	37.6	37.6	37.6	37.6	37.6	37.6	37.6	37.6
38.4	38.4	38.5	38.5	38.6	38.6	38.6	38.6	38.6	38.6	38.6	38.6
38.7	38.7	38.8	38.8	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
39.7	39.7	39.8	39.8	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
40.9	40.9	41.0	41.0	41.1	41.1	41.1	41.1	41.1	41.1	41.1	41.1
42.9	42.9	43.0	43.0	43.1	43.1	43.1	43.1	43.1	43.1	43.1	43.1
43.5	43.5	43.7	43.7	43.8	43.8	43.8	43.8	43.8	43.8	43.8	43.8
44.5	44.5	44.6	44.6	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7
46.5	46.7	46.8	46.8	46.9	47.0	47.0	47.0	47.0	47.0	47.0	47.0
47.5	47.6	47.7	47.7	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1
48.2	48.3	48.7	48.7	48.9	49.0	49.0	49.0	49.0	49.0	49.0	49.0
48.4	48.5	48.9	48.9	49.1	49.2	49.2	49.2	49.2	49.2	49.2	49.2
49.9	50.0	50.6	50.6	50.9	51.0	51.0	51.0	51.0	51.0	51.0	51.0
51.7	51.8	52.5	52.7	52.9	53.0	53.0	53.0	53.0	53.0	53.1	53.2
55.1	55.2	55.4	56.0	56.2	56.3	56.3	56.3	56.5	56.5	56.6	56.7
57.2	59.4	60.4	60.8	61.0	61.2	61.2	61.2	61.3	61.3	61.4	61.5
64.8	55.2	55.5	67.2	57.4	67.7	68.0	68.0	68.2	68.2	68.5	68.6
65.5	65.8	68.1	68.8	69.0	69.4	69.6	69.6	69.8	69.8	70.1	70.2
70.3	71.5	73.2	74.3	74.7	75.3	75.6	75.6	75.8	76.0	76.3	76.7
73.8	74.5	76.3	77.7	78.5	79.2	79.6	79.7	80.2	80.4	80.9	81.3
76.8	77.6	80.0	81.4	82.6	83.5	84.4	84.5	85.1	85.4	85.8	86.3
77.8	78.7	81.2	82.9	84.1	85.1	85.9	86.0	86.6	86.9	87.3	87.8
78.8	79.8	82.6	84.3	85.8	87.0	87.8	88.0	88.6	88.9	89.4	90.0
79.5	80.4	83.5	85.5	87.0	88.2	89.0	89.1	90.0	90.3	90.8	91.4
79.8	80.9	84.0	86.1	87.7	89.1	90.3	90.5	91.4	91.7	92.2	92.8
80.2	81.3	84.7	87.0	89.0	90.9	92.5	92.7	93.7	94.0	94.4	95.3
80.5	81.7	85.6	87.8	90.0	91.9	93.5	93.8	94.8	95.6	96.0	97.2
80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.0	96.8	97.8	99.1
80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.1	97.1	98.5	100.0
80.5	81.7	85.6	88.0	90.3	92.5	94.3	94.7	96.1	97.1	98.5	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBIL
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: JAN HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	31.9	31.9	32.0	32.2	32.3	32.4	32.6	32.6	32.6	32.7	32.7	32.8	32.8
GE 20000	35.1	35.4	36.0	36.3	36.6	36.7	36.9	36.9	37.0	37.1	37.1	37.2	37.2
GE 18000	35.6	35.9	36.5	36.7	37.1	37.2	37.4	37.4	37.5	37.6	37.6	37.7	37.7
GE 16000	35.8	36.1	36.8	37.1	37.3	37.4	37.6	37.6	37.7	37.8	37.8	38.0	38.0
GE 14000	36.5	36.8	37.4	37.7	38.0	38.1	38.3	38.3	38.4	38.5	38.5	38.6	38.6
GE 12000	38.1	38.4	39.0	39.4	39.6	39.7	39.9	39.9	40.0	40.1	40.1	40.2	40.2
GE 10000	39.7	40.0	40.6	41.1	41.3	41.5	41.7	41.7	41.8	41.9	41.9	42.0	42.0
GE 9000	40.3	40.6	41.3	41.7	42.0	42.3	42.5	42.5	42.6	42.7	42.7	42.8	42.8
GE 8000	42.5	42.8	43.4	44.0	44.4	44.6	44.8	44.8	44.9	45.1	45.1	45.2	45.2
GE 7000	43.7	44.0	44.7	45.3	45.8	46.0	46.2	46.2	46.3	46.5	46.5	46.6	46.6
GE 6000	44.6	44.9	45.7	46.2	46.9	47.4	47.7	47.7	48.0	48.1	48.1	48.2	48.2
GE 5000	46.0	46.3	47.1	47.6	48.4	49.1	49.5	49.5	49.7	49.8	49.8	49.9	49.9
GE 4500	46.5	46.8	47.5	48.1	49.1	49.9	50.2	50.2	50.4	50.5	50.5	50.6	50.6
GE 4000	48.3	48.7	49.5	50.1	51.3	52.0	52.6	52.6	52.9	53.0	53.0	53.1	53.1
GE 3500	49.0	49.5	50.3	50.9	52.0	52.8	53.4	53.5	53.9	54.0	54.0	54.1	54.1
GE 3000	52.3	52.7	53.5	54.2	55.9	56.7	57.4	57.5	57.8	58.0	58.0	58.1	58.1
GE 2500	54.2	54.6	55.5	56.1	58.0	58.7	59.6	59.8	60.1	60.2	60.3	60.4	60.4
GE 2000	59.5	60.0	61.4	62.2	64.8	66.0	67.2	67.8	68.2	68.3	68.6	68.8	69.0
GE 1800	61.1	61.5	62.9	63.7	65.3	67.6	68.9	69.8	70.2	70.3	70.6	70.9	71.1
GE 1500	63.5	64.1	65.7	66.6	69.7	71.1	72.6	74.2	74.7	75.3	75.6	75.9	76.1
GE 1200	66.3	66.9	68.6	69.5	72.8	74.6	76.5	78.2	78.9	79.6	80.2	80.5	81.1
GE 1000	68.1	68.7	70.5	71.4	75.1	77.2	79.1	81.4	82.5	83.2	83.9	84.2	84.9
GE 900	68.7	69.4	71.3	72.4	75.2	78.4	80.8	83.0	84.1	84.8	85.5	85.8	86.6
GE 800	69.0	69.7	71.6	72.8	76.7	78.8	81.2	83.7	84.8	85.7	86.5	86.8	87.7
GE 700	69.6	70.2	72.4	73.7	77.5	79.8	82.2	84.2	86.5	87.5	88.4	88.7	90.0
GE 600	69.7	70.3	72.5	73.9	77.8	80.5	82.9	86.0	88.0	89.1	90.3	90.6	91.9
GE 500	69.8	70.4	72.9	74.3	78.4	81.1	83.9	87.1	89.5	91.5	93.2	93.7	94.9
GE 400	69.9	70.5	73.0	74.4	78.5	81.3	84.2	87.7	90.3	92.4	94.2	94.6	95.9
GE 300	69.9	70.5	73.0	74.4	78.7	81.4	84.3	87.8	91.0	93.8	95.7	96.1	97.7
GE 200	69.9	70.5	73.0	74.4	78.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0
GE 100	69.9	70.5	73.0	74.4	78.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0
GE 000	69.9	70.5	73.0	74.4	78.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
32.3	32.4	32.6	32.6	32.6	32.7	32.7	32.8	32.8	32.8	32.9	32.9
35.6	36.7	36.9	36.9	37.0	37.1	37.1	37.2	37.2	37.2	37.3	37.3
37.1	37.2	37.4	37.4	37.5	37.6	37.6	37.7	37.7	37.7	37.8	37.8
37.3	37.4	37.6	37.6	37.7	37.8	37.8	38.0	38.0	38.0	38.1	38.1
38.0	38.1	38.3	38.3	38.4	38.5	38.5	38.6	38.6	38.6	38.7	38.7
39.6	39.7	39.9	39.9	40.0	40.1	40.1	40.2	40.2	40.2	40.3	40.3
41.3	41.5	41.7	41.7	41.8	41.9	41.9	42.0	42.0	42.0	42.2	42.2
42.0	42.3	42.5	42.5	42.6	42.7	42.7	42.8	42.8	42.8	42.9	42.9
44.4	44.6	44.8	44.8	44.9	45.1	45.1	45.2	45.2	45.2	45.3	45.3
45.8	46.0	46.2	46.2	46.3	46.5	46.5	46.6	46.6	46.6	46.7	46.7
46.9	47.4	47.7	47.7	48.0	48.1	48.1	48.2	48.2	48.2	48.3	48.3
49.4	49.1	49.5	49.5	49.7	49.8	49.8	49.9	49.9	49.9	50.0	50.0
49.1	49.9	50.2	50.2	50.4	50.5	50.5	50.6	50.6	50.6	50.8	50.8
51.3	52.0	52.6	52.6	52.9	53.0	53.0	53.1	53.1	53.1	53.2	53.2
52.0	52.8	53.4	53.5	53.9	54.0	54.0	54.1	54.1	54.1	54.2	54.2
55.9	56.7	57.4	57.5	57.8	58.0	58.0	58.1	58.1	58.1	58.2	58.2
58.7	58.7	59.6	59.8	60.1	60.2	60.3	60.4	60.4	60.4	60.5	60.5
64.8	66.0	67.2	67.8	68.2	68.3	68.6	68.8	69.0	69.0	69.2	69.2
66.3	67.6	68.9	69.8	70.2	70.3	70.6	70.9	71.1	71.1	71.3	71.3
69.7	71.1	72.6	74.2	74.7	75.3	75.6	75.9	76.1	76.1	76.3	76.3
72.8	74.6	76.5	78.2	78.9	79.6	80.2	80.5	81.1	81.1	81.3	81.3
75.1	77.2	79.1	81.4	82.5	83.2	83.9	84.2	84.9	84.9	85.2	85.2
75.2	78.4	80.8	83.0	84.1	84.8	85.5	85.8	86.6	86.6	86.8	86.8
75.7	78.8	81.2	83.7	84.8	85.7	86.5	86.8	87.7	87.7	88.0	88.3
77.5	79.8	82.2	84.2	86.5	87.5	88.4	88.7	90.0	90.0	90.3	90.8
77.8	80.5	82.9	86.0	88.0	89.1	90.3	90.6	91.9	92.0	92.4	92.8
73.4	81.1	83.9	87.1	89.5	91.5	93.2	93.7	94.9	95.2	95.5	95.9
73.6	81.3	84.2	87.7	90.3	92.4	94.2	94.6	95.9	96.5	96.8	97.3
73.7	81.4	84.3	87.8	91.0	93.8	95.7	96.1	97.7	98.3	98.8	99.8
73.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0	98.5	99.0	100.0
73.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0	98.5	99.0	100.0
73.7	81.4	84.3	87.8	91.0	93.9	95.8	96.3	98.0	98.5	99.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: JAN HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	31.0	31.0	31.3	31.4	31.6	31.7	31.9	32.0	32.2	32.2	32.2	32.2	32.2	
GE 20000	33.8	34.1	34.5	34.6	34.9	35.1	35.3	35.4	35.5	35.5	35.5	35.5	35.5	
GE 18000	34.2	34.5	34.9	35.1	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	
GE 16000	34.2	34.5	34.9	35.1	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	
GE 14000	34.2	34.5	34.9	35.1	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	
GE 12000	35.4	35.7	36.1	36.2	36.6	36.7	36.9	37.0	37.1	37.1	37.1	37.1	37.1	
GE 10000	37.0	37.3	37.8	38.0	38.3	38.4	38.6	38.7	38.8	38.8	38.8	38.8	38.8	
GF 9000	37.2	37.5	38.1	38.2	38.5	38.6	38.8	38.9	39.0	39.0	39.0	39.0	39.0	
GE 8000	38.8	39.1	39.7	39.9	40.4	40.5	40.9	41.1	41.2	41.2	41.2	41.2	41.2	
GE 7000	38.9	39.2	39.8	40.0	40.5	40.6	41.0	41.2	41.3	41.3	41.3	41.3	41.3	
GF 6000	39.8	40.1	40.6	40.9	41.4	41.5	41.8	42.0	42.2	42.2	42.2	42.2	42.2	
GE 5000	41.0	41.3	41.8	42.2	42.9	43.0	43.3	43.5	43.7	43.7	43.7	43.7	43.7	
GE 4500	41.5	41.8	42.4	42.7	43.4	43.5	43.9	44.1	44.2	44.2	44.2	44.2	44.2	
GE 4000	43.7	44.0	44.6	44.9	45.8	45.9	46.2	46.5	46.6	46.6	46.6	46.6	46.6	
GE 3500	44.5	44.8	45.5	45.8	46.9	47.0	47.3	47.6	47.7	47.7	47.7	47.7	47.7	
GE 3000	48.7	49.1	49.9	50.2	52.4	52.7	53.0	53.3	53.4	53.4	53.5	53.5	53.5	
GE 2500	53.4	54.0	55.2	55.5	58.1	58.7	59.0	59.5	59.6	59.8	59.9	59.9	59.9	
GE 2000	58.4	59.2	60.6	61.1	64.2	65.3	66.1	67.5	67.8	68.4	68.5	68.6	68.8	
GE 1800	61.1	61.9	63.3	63.8	67.0	68.1	69.1	70.6	71.0	71.6	71.7	71.8	72.0	
GE 1500	63.4	64.4	65.9	66.5	69.9	71.1	72.8	75.2	76.0	77.3	77.6	77.7	78.1	
GE 1200	65.7	66.7	68.5	69.1	72.7	73.9	76.1	78.8	79.9	81.3	81.9	82.0	82.4	
GE 1000	67.3	68.3	70.3	71.2	75.1	76.5	78.8	82.0	83.4	84.8	85.5	85.6	85.9	
GF 900	68.2	69.1	71.3	72.3	76.6	78.0	80.5	84.2	85.6	87.1	87.8	88.0	88.3	
GE 800	68.5	69.5	71.6	72.6	76.9	78.4	81.1	84.7	86.1	87.6	88.4	88.5	89.0	
GE 700	69.2	70.2	72.5	73.4	77.8	79.4	82.2	86.2	88.0	89.5	90.4	90.5	91.5	
GE 600	69.8	70.8	73.0	74.0	78.5	80.2	83.1	87.7	89.5	91.1	92.0	92.3	93.3	
GE 500	69.9	71.0	73.2	74.2	78.7	80.4	83.3	88.2	90.2	91.9	93.1	93.4	94.6	
GE 400	69.9	71.3	73.5	74.6	79.4	81.1	84.1	89.2	91.3	93.1	94.4	94.7	95.9	
GE 300	70.0	71.4	73.7	74.7	79.7	81.4	84.6	90.0	92.5	94.6	96.1	96.7	98.2	
GE 200	70.0	71.4	73.7	74.7	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.4	
GE 100	70.0	71.4	73.7	74.7	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.5	
GE 000	70.0	71.4	73.7	74.7	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.5	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: JAN HOURS: 21-23

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
4	31.6	31.7	31.9	32.0	32.2	32.2	32.2	32.2	32.2	32.2	32.2	32.2
5	34.9	35.1	35.3	35.4	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5
6	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
7	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
8	35.4	35.5	35.7	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
9	36.6	36.7	36.9	37.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
0	38.3	38.4	38.6	38.7	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8
1	38.5	38.6	38.8	38.9	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0
2	40.4	40.5	40.9	41.1	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2
3	40.5	40.6	41.0	41.2	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3
4	41.4	41.5	41.8	42.0	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
5	42.9	43.0	43.3	43.5	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
6	43.4	43.5	43.9	44.1	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2
7	45.8	45.9	46.2	46.5	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6
8	46.9	47.0	47.3	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.7	47.7
9	52.4	52.7	53.0	53.3	53.4	53.4	53.5	53.5	53.5	53.5	53.5	53.5
0	53.1	58.7	59.0	59.5	59.6	59.8	59.9	59.9	59.9	59.9	59.9	59.9
1	64.2	65.3	66.1	67.5	67.8	68.4	68.5	68.6	68.8	68.8	68.8	68.8
2	67.0	68.1	69.1	70.6	71.0	71.6	71.7	71.8	72.0	72.0	72.0	72.0
3	69.9	71.1	72.8	75.2	76.0	77.3	77.6	77.7	78.1	78.1	78.1	78.1
4	72.7	73.9	76.1	78.8	79.9	81.3	81.9	82.0	82.4	82.5	82.5	82.5
5	75.1	76.5	78.8	82.0	83.4	84.8	85.5	85.6	85.9	86.0	86.0	86.0
6	76.6	78.0	80.5	84.2	85.6	87.1	87.8	88.0	88.3	88.4	88.4	88.4
7	76.9	78.4	81.1	84.7	86.1	87.6	88.4	88.5	89.0	89.1	89.2	89.5
8	77.8	79.4	82.2	86.2	88.0	89.5	90.4	90.5	91.5	91.6	91.7	91.9
9	78.5	80.2	83.1	87.7	89.5	91.1	92.0	92.3	93.3	93.4	93.5	93.8
0	79.7	80.4	83.3	88.2	90.2	91.9	93.1	93.4	94.6	94.7	94.8	95.1
1	79.4	81.1	84.1	89.2	91.3	93.1	94.4	94.7	95.9	96.0	96.1	96.3
2	79.7	81.4	84.6	90.0	92.5	94.6	96.1	96.7	98.2	98.4	98.8	99.0
3	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.4	98.7	99.1	99.4
4	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.5	99.0	99.7	99.9
5	79.7	81.4	84.6	90.0	92.5	94.7	96.3	96.9	98.5	99.0	99.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	29.8	29.9	30.2	30.3	30.6	30.8	30.9	31.1	31.1	31.2	31.2	31.2	31.2	
GE 20000	32.6	32.8	33.2	33.4	33.8	33.9	34.1	34.2	34.3	34.3	34.4	34.4	34.4	
GE 18000	33.2	33.4	33.7	33.9	34.3	34.5	34.6	34.8	34.9	34.9	34.9	35.0	35.0	
GE 16000	33.3	33.5	33.9	34.1	34.5	34.6	34.8	34.9	35.0	35.0	35.1	35.1	35.1	
GE 14000	33.7	33.9	34.2	34.5	34.9	35.0	35.2	35.3	35.4	35.4	35.5	35.5	35.5	
GE 12000	34.7	34.9	35.2	35.5	35.9	36.1	36.2	36.3	36.4	36.5	36.5	36.5	36.5	
GE 10000	36.2	36.4	36.8	37.1	37.5	37.6	37.8	37.9	38.0	38.1	38.1	38.1	38.1	
GE 9000	36.6	36.8	37.2	37.5	37.9	38.1	38.2	38.4	38.5	38.5	38.5	38.6	38.6	
GE 8000	37.7	37.9	38.4	38.8	39.3	39.4	39.6	39.8	39.9	39.9	39.9	40.0	40.0	
GE 7000	38.7	38.9	39.4	39.8	40.4	40.6	40.8	40.9	41.0	41.1	41.1	41.2	41.2	
GE 6000	39.4	39.7	40.2	40.5	41.2	41.4	41.6	41.8	41.9	42.0	42.0	42.0	42.0	
GE 5000	40.5	40.8	41.4	41.8	42.5	42.8	43.0	43.2	43.3	43.4	43.4	43.4	43.4	
GE 4500	41.2	41.4	42.0	42.5	43.3	43.5	43.8	44.0	44.1	44.1	44.2	44.2	44.2	
GE 4000	42.8	43.2	43.8	44.4	45.3	45.6	46.0	46.2	46.3	46.4	46.4	46.5	46.5	
GE 3500	44.0	44.3	45.0	45.6	46.6	46.9	47.3	47.6	47.7	47.8	47.9	47.9	47.9	
GE 3000	46.5	47.0	47.9	48.5	49.9	50.3	50.7	51.0	51.2	51.3	51.4	51.4	51.4	
GE 2500	49.8	50.3	51.6	52.3	54.1	54.5	55.2	55.7	55.9	56.1	56.2	56.2	56.2	
GE 2000	54.0	54.7	56.7	57.7	60.2	61.0	62.3	63.2	63.6	63.8	64.1	64.1	64.1	
GE 1800	55.9	56.7	58.8	60.0	62.6	63.5	64.9	65.9	66.3	66.6	66.8	66.9	66.9	
GE 1500	59.3	60.1	62.6	64.0	67.3	68.5	70.6	72.4	73.3	74.0	74.5	74.6	74.6	
GE 1200	61.5	62.4	65.1	66.5	70.3	71.6	74.1	76.3	77.5	78.3	78.9	79.0	79.0	
GE 1000	62.9	63.9	66.9	68.5	72.6	74.0	76.8	79.3	80.8	81.8	82.6	82.7	82.7	
GE 900	63.7	64.7	67.7	69.5	73.8	75.2	78.2	80.9	82.6	83.6	84.5	84.6	84.6	
GE 800	64.3	65.4	68.4	70.3	74.7	76.2	79.4	82.3	84.1	85.2	86.2	86.3	86.3	
GE 700	64.9	66.0	69.1	71.0	75.7	77.2	80.6	83.7	85.7	87.0	88.1	88.3	88.3	
GE 600	65.5	66.6	69.7	71.7	76.6	78.3	81.7	85.1	87.3	88.7	89.9	90.1	90.1	
GE 500	65.8	66.9	70.2	72.2	77.2	78.9	82.5	86.2	88.9	90.6	92.2	92.5	92.5	
GE 400	65.9	67.1	70.4	72.5	77.7	79.5	83.3	87.3	90.1	91.9	93.7	93.9	93.9	
GE 300	66.0	67.2	70.6	72.7	78.0	79.7	83.7	87.8	91.0	93.1	95.1	95.4	95.4	
GE 200	66.0	67.2	70.6	72.7	78.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	96.0	
GE 100	66.0	67.2	70.6	72.7	78.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	96.0	
GE 000	66.0	67.2	70.6	72.7	73.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	96.0	

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: ALL

VISIBILITY IN STATUTE MILES

CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.3	30.6	30.8	30.9	31.1	31.1	31.2	31.2	31.2	31.3	31.3	31.3	31.3
33.4	33.9	33.9	34.1	34.2	34.3	34.3	34.4	34.4	34.4	34.5	34.5	34.5
33.9	34.3	34.5	34.6	34.8	34.9	34.9	34.9	35.0	35.0	35.0	35.0	35.0
34.1	34.5	34.6	34.8	34.9	35.0	35.0	35.1	35.1	35.1	35.2	35.2	35.2
34.5	34.9	35.0	35.2	35.3	35.4	35.4	35.5	35.5	35.6	35.6	35.6	35.6
35.5	35.9	36.1	36.2	36.3	36.4	36.5	36.5	36.5	36.6	36.6	36.6	36.6
37.1	37.5	37.6	37.8	37.9	38.0	38.1	38.1	38.1	38.2	38.2	38.2	38.2
37.5	37.9	38.1	38.2	38.4	38.5	38.5	38.5	38.6	38.6	38.6	38.6	38.6
38.8	39.3	39.4	39.6	39.8	39.9	39.9	39.9	40.0	40.0	40.0	40.0	40.0
39.8	40.4	40.6	40.8	40.9	41.0	41.1	41.1	41.2	41.2	41.2	41.2	41.2
39.5	41.2	41.4	41.6	41.8	41.9	42.0	42.0	42.0	42.1	42.1	42.1	42.1
41.8	42.5	42.8	43.0	43.2	43.3	43.4	43.4	43.4	43.5	43.5	43.5	43.5
42.5	43.3	43.5	43.8	44.0	44.1	44.1	44.2	44.2	44.2	44.3	44.3	44.3
44.4	45.3	45.6	46.0	46.2	46.3	46.4	46.4	46.5	46.5	46.5	46.5	46.5
45.6	46.6	46.9	47.3	47.6	47.7	47.8	47.9	47.9	47.9	48.0	48.0	48.0
49.5	49.9	50.3	50.7	51.0	51.2	51.3	51.4	51.4	51.4	51.5	51.5	51.5
52.3	54.1	54.5	55.2	55.7	55.9	56.1	56.2	56.2	56.3	56.3	56.3	56.4
57.7	60.2	61.0	62.3	63.2	63.6	63.8	64.1	64.1	64.3	64.3	64.4	64.5
60.0	62.6	63.5	64.9	65.9	66.3	66.6	66.8	66.9	67.0	67.1	67.2	67.2
64.0	67.3	68.5	70.6	72.4	73.3	74.0	74.5	74.6	74.8	74.9	75.0	75.1
65.5	70.3	71.6	74.1	76.3	77.5	78.3	78.9	79.0	79.3	79.5	79.6	79.7
68.5	72.6	74.0	76.8	79.3	80.8	81.8	82.6	82.7	83.1	83.3	83.5	83.6
68.5	73.8	75.2	78.2	80.9	82.6	83.6	84.5	84.6	85.0	85.2	85.4	85.7
68.3	74.7	76.2	79.4	82.3	84.1	85.2	86.2	86.3	86.8	87.1	87.3	87.6
71.0	75.7	77.2	80.6	83.7	85.7	87.0	88.1	88.3	88.9	89.2	89.5	89.9
71.7	76.6	78.3	81.7	85.1	87.3	88.7	89.9	90.1	91.0	91.3	91.6	91.9
72.2	77.2	78.9	82.5	86.2	88.9	90.6	92.2	92.5	93.4	93.8	94.2	94.6
72.5	77.7	79.5	83.3	87.3	90.1	91.9	93.7	93.9	95.0	95.5	95.9	96.5
72.7	78.0	79.7	83.7	87.8	91.0	93.1	95.1	95.4	96.8	97.4	98.1	98.8
72.7	78.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	97.5	98.2	99.0	99.8
72.7	78.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	97.5	98.3	99.2	100.0
72.7	78.1	79.8	83.9	88.1	91.3	93.6	95.7	96.0	97.5	98.3	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: FEB HOURS: 00-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	35.1	35.5	36.0	36.4	37.0	37.0	37.3	37.3	37.3	37.6	37.6	37.6	3
GE 20000	37.9	38.3	38.7	39.2	39.8	39.8	40.2	40.2	40.2	40.4	40.4	40.4	4
GE 18000	38.2	38.5	39.1	39.5	40.0	40.0	40.4	40.4	40.4	40.6	40.6	40.6	4
GE 16000	39.2	38.5	39.1	39.5	40.0	40.0	40.4	40.4	40.4	40.6	40.6	40.6	4
GE 14000	39.1	39.7	40.3	40.6	41.3	41.3	41.7	41.7	41.7	41.9	41.9	41.9	4
GE 12000	39.9	40.5	41.1	41.5	42.2	42.2	42.5	42.5	42.5	42.8	42.8	42.8	4
GE 10000	41.5	42.0	42.6	43.0	43.7	43.7	44.1	44.1	44.1	44.3	44.3	44.3	4
GE 9000	42.0	42.6	43.2	43.6	44.3	44.3	44.6	44.6	44.6	44.9	44.9	44.9	4
GE 8000	44.4	45.1	45.7	46.1	46.8	46.8	47.1	47.1	47.1	47.3	47.3	47.3	4
GE 7000	45.3	46.2	46.8	47.1	47.8	47.8	48.2	48.2	48.2	48.4	48.4	48.4	4
GE 6000	46.2	47.0	47.5	47.9	48.5	48.6	49.0	49.0	49.0	49.2	49.2	49.2	4
GE 5000	47.2	48.1	48.6	49.0	49.8	49.8	50.2	50.2	50.2	50.4	50.4	50.4	5
GE 4500	47.9	48.8	49.4	49.7	50.6	50.6	51.0	51.0	51.0	51.2	51.2	51.2	5
GE 4000	49.8	50.9	51.6	51.9	53.2	53.4	53.9	53.9	54.1	54.4	54.4	54.4	5
GE 3500	50.3	51.4	52.2	52.5	53.3	54.1	54.7	54.7	54.8	55.1	55.1	55.1	5
GE 3000	53.4	54.7	55.5	55.8	57.7	58.0	58.5	58.7	58.8	59.1	59.1	59.1	5
GE 2500	55.7	57.1	58.2	58.7	60.7	61.0	62.3	62.5	62.7	63.0	63.0	63.0	6
GE 2000	58.9	60.4	61.7	62.7	64.9	65.7	67.6	68.4	68.6	69.0	69.0	69.0	6
GE 1800	60.4	62.0	63.4	64.7	66.9	67.7	70.0	70.8	70.9	71.4	71.5	71.5	7
GE 1500	62.0	63.6	65.5	67.0	69.6	70.4	72.8	74.1	74.3	75.3	75.5	75.5	7
GE 1200	63.0	64.7	66.5	68.4	71.4	72.7	75.1	76.7	76.9	78.1	78.4	78.6	7
GE 1000	64.3	66.3	68.6	70.6	74.0	75.4	78.1	80.2	80.6	81.7	82.2	82.4	8
GE 900	65.1	67.1	69.5	71.5	74.9	76.3	79.9	82.1	82.4	83.7	84.2	84.5	8
GE 800	65.7	67.7	70.1	72.1	75.3	77.9	81.4	83.6	84.0	85.3	85.9	86.1	8
GE 700	66.1	68.1	70.6	72.6	76.9	78.4	82.4	84.7	85.2	86.5	87.4	87.6	8
GE 600	66.5	68.6	71.0	73.0	77.6	79.2	83.3	86.0	86.5	87.8	88.8	89.0	9
GE 500	66.9	68.9	71.5	73.5	78.6	80.1	84.5	87.5	88.2	90.1	91.4	91.6	9
GE 400	67.3	69.4	72.0	74.0	79.0	80.6	85.5	89.7	89.6	91.8	93.2	93.4	9
GE 300	67.4	69.5	72.1	74.2	79.3	80.9	86.0	89.5	90.5	92.8	94.5	94.8	9
GE 200	67.4	69.5	72.1	74.2	79.3	80.9	86.1	89.8	90.9	93.4	95.2	95.8	9
GE 100	67.4	69.5	72.1	74.2	79.3	80.9	86.1	89.8	91.0	93.8	95.5	96.1	9
GE 000	67.4	69.5	72.1	74.2	79.3	80.9	86.1	89.8	91.0	93.8	95.5	96.1	9

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 00-02

VISIBILITY IN STATUTE MILES

CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
37.4	37.0	37.0	37.3	37.3	37.3	37.6	37.6	37.6	37.7	37.7	37.7	37.7
37.2	39.8	39.8	40.2	40.2	40.2	40.4	40.4	40.4	40.5	40.5	40.5	40.5
37.5	40.0	40.0	40.4	40.4	40.4	40.6	40.6	40.6	40.8	40.8	40.8	40.8
37.5	40.0	40.0	40.4	40.4	40.4	40.6	40.6	40.6	40.8	40.8	40.8	40.8
37.5	41.3	41.3	41.7	41.7	41.7	41.9	41.9	41.9	42.0	42.0	42.0	42.0
37.5	42.2	42.2	42.5	42.5	42.5	42.8	42.8	42.8	42.9	42.9	42.9	42.9
37.0	43.7	43.7	44.1	44.1	44.1	44.3	44.3	44.3	44.4	44.4	44.4	44.4
37.5	44.3	44.3	44.6	44.6	44.6	44.9	44.9	44.9	45.0	45.0	45.0	45.0
37.1	46.8	46.8	47.1	47.1	47.1	47.3	47.3	47.3	47.5	47.5	47.5	47.5
37.1	47.8	47.8	48.2	48.2	48.2	48.4	48.4	48.4	48.5	48.5	48.5	48.5
37.0	48.5	48.6	49.0	49.0	49.0	49.2	49.2	49.2	49.4	49.4	49.4	49.4
37.0	49.0	49.3	50.2	50.2	50.2	50.4	50.4	50.4	50.5	50.5	50.5	50.5
37.7	50.6	50.6	51.0	51.0	51.0	51.2	51.2	51.2	51.4	51.4	51.4	51.4
37.9	53.2	53.4	53.9	53.9	54.1	54.4	54.4	54.4	54.5	54.5	54.5	54.5
37.8	53.3	54.1	54.7	54.7	54.8	55.1	55.1	55.1	55.2	55.2	55.2	55.2
37.3	57.7	58.0	58.5	58.7	58.8	59.1	59.1	59.1	59.2	59.2	59.2	59.2
37.7	60.7	61.0	62.3	62.5	62.7	63.0	63.0	63.0	63.1	63.1	63.1	63.1
37.7	64.9	65.7	67.6	68.4	68.6	69.0	69.0	69.0	69.1	69.1	69.1	69.1
37.7	66.9	67.7	70.0	70.8	70.9	71.4	71.5	71.5	71.6	71.6	71.6	71.6
37.0	69.6	70.4	72.8	74.1	74.3	75.3	75.5	75.5	75.6	75.6	75.6	75.6
37.4	71.4	72.7	75.1	76.7	76.9	78.1	78.4	78.6	78.9	78.9	78.9	78.9
37.5	74.0	75.4	78.1	80.2	80.6	81.7	82.2	82.4	82.9	83.0	83.2	83.2
37.5	74.9	76.3	79.9	82.1	82.4	83.7	84.2	84.5	84.9	85.0	85.2	85.2
37.1	75.3	77.9	81.4	83.6	84.0	85.3	85.9	86.1	86.7	86.8	86.9	87.0
37.6	76.9	78.4	82.4	84.7	85.2	86.5	87.4	87.6	88.5	88.6	88.7	88.8
37.0	77.6	79.2	83.3	86.0	86.5	87.8	88.8	89.0	90.2	90.3	90.5	90.6
37.5	78.6	80.1	84.5	87.5	88.2	90.1	91.4	91.6	92.8	92.9	93.1	93.2
37.0	79.0	80.6	85.5	89.7	89.6	91.8	93.2	93.4	94.7	94.8	95.2	95.3
37.2	79.3	80.9	86.0	89.5	90.5	92.8	94.5	94.8	96.5	96.6	96.9	97.1
37.2	79.3	80.9	86.1	89.8	90.9	93.4	95.2	95.8	97.6	98.0	98.6	98.8
37.2	79.3	80.9	86.1	89.8	91.0	93.8	95.5	96.1	98.0	98.4	99.3	99.5
37.2	79.3	80.9	86.1	89.8	91.0	93.8	95.5	96.1	98.0	98.4	99.5	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: FEB HOURS: 03-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	34.6	34.7	35.0	35.1	35.5	35.5	35.8	35.8	35.9	35.9	35.9	35.9	35.9
GE 20000	37.9	38.0	38.4	38.6	39.0	39.0	39.3	39.5	39.7	39.7	39.7	39.7	39.7
GE 18000	38.2	38.3	38.6	38.9	39.2	39.2	39.6	39.7	39.9	39.9	39.9	39.9	39.9
GE 16000	38.4	38.5	38.9	39.1	39.5	39.5	39.8	39.9	40.2	40.2	40.2	40.2	40.2
GE 14000	38.8	38.9	39.2	39.5	39.8	39.8	40.2	40.3	40.5	40.5	40.5	40.5	40.5
GE 12000	38.8	38.9	39.2	39.5	39.8	39.8	40.2	40.3	40.5	40.5	40.5	40.5	40.5
GE 10000	39.6	39.7	40.2	40.4	40.8	40.8	41.1	41.3	41.7	41.8	41.8	41.8	41.8
GE 9000	40.4	40.5	41.0	41.2	41.6	41.6	41.9	42.2	42.5	42.6	42.6	42.6	42.6
GE 8000	42.8	42.9	43.3	43.5	43.9	43.9	44.3	44.5	44.9	45.0	45.0	45.0	45.0
GE 7000	43.8	44.1	44.5	44.8	45.1	45.1	45.5	45.7	46.1	46.2	46.2	46.2	46.2
GE 6000	44.3	44.6	45.1	45.3	45.8	45.8	46.2	46.4	46.8	46.9	46.9	46.9	46.9
GE 5000	45.7	46.1	46.5	46.8	47.2	47.2	47.6	47.8	48.2	48.3	48.3	48.3	48.3
GE 4500	45.9	46.3	46.8	47.0	47.6	47.6	47.9	48.2	48.5	48.6	48.6	48.6	48.6
GE 4000	48.5	48.9	49.6	49.8	50.5	50.9	51.6	52.3	52.7	52.8	52.8	52.8	52.8
GE 3500	49.9	50.3	51.0	51.7	52.5	52.9	53.6	54.3	54.7	54.8	54.8	54.8	54.8
GE 3000	53.2	53.6	54.3	55.2	56.7	57.0	57.7	58.7	59.0	59.1	59.1	59.1	59.1
GE 2500	55.6	55.9	56.8	57.8	59.4	59.8	61.1	62.1	62.4	62.5	62.5	62.5	62.5
GE 2000	57.6	58.0	59.0	60.4	62.4	63.3	65.0	66.1	66.4	66.5	66.9	67.0	67.0
GE 1800	59.7	60.1	61.1	62.7	65.0	66.0	67.8	68.9	69.3	69.5	69.8	70.0	70.0
GE 1500	61.7	62.1	63.4	65.8	68.1	69.3	71.6	73.3	73.6	74.8	75.3	75.7	75.7
GE 1200	63.4	63.7	65.1	67.6	69.8	71.0	73.6	75.4	75.7	77.1	78.0	78.6	78.6
GE 1000	65.0	65.5	67.0	69.5	72.3	73.5	76.2	78.2	78.6	80.2	81.3	82.0	82.0
GE 900	65.3	65.7	67.4	69.8	73.0	74.3	77.3	79.5	79.9	81.5	82.6	83.3	83.3
GE 800	66.1	66.5	68.3	70.9	74.4	75.9	78.8	81.0	81.4	83.0	84.2	85.2	85.2
GE 700	66.7	67.1	69.0	71.7	75.4	76.8	80.1	82.7	83.3	85.2	86.5	87.4	87.4
GE 600	66.9	67.4	69.3	72.0	75.7	77.5	81.0	84.1	84.7	86.6	87.9	88.9	88.9
GE 500	66.9	67.4	69.4	72.2	76.1	78.0	82.0	85.0	85.6	88.1	89.4	90.6	90.6
GE 400	67.3	67.7	69.7	72.7	76.6	78.4	83.0	86.3	87.4	90.0	91.3	92.5	92.5
GE 300	67.4	67.8	69.8	72.3	76.7	78.8	83.9	87.4	88.9	91.9	93.2	94.6	94.6
GE 200	67.4	67.8	69.8	72.8	76.7	78.8	83.9	87.6	89.4	92.5	93.8	95.3	95.3
GE 100	67.4	67.8	69.8	72.9	76.7	78.8	83.9	87.6	89.5	92.7	94.0	95.5	95.5
GE 000	67.4	67.8	69.8	72.9	76.7	78.8	83.9	87.6	89.5	92.7	94.0	95.5	95.5

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 03-05

VISIBILITY IN STATUTE MILES												
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
35.5	35.5	35.8	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
37.0	39.0	39.3	39.5	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7
39.2	39.2	39.6	39.7	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9	39.9
39.5	39.5	39.8	39.9	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
39.8	39.8	40.2	40.3	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5
39.8	39.8	40.2	40.3	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5	40.5
40.8	40.8	41.1	41.3	41.7	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8
41.6	41.6	41.9	42.2	42.5	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6
43.9	43.9	44.3	44.5	44.9	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
45.1	45.1	45.5	45.7	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
45.8	45.8	46.2	46.4	46.8	46.9	46.9	46.9	46.9	46.9	46.9	46.9	46.9
47.2	47.2	47.6	47.8	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
47.6	47.6	47.9	48.2	48.5	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6
50.5	50.9	51.6	52.3	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8
52.5	52.9	53.6	54.3	54.7	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8
55.7	57.0	57.7	58.7	59.0	59.1	59.1	59.1	59.1	59.1	59.1	59.1	59.1
59.4	59.8	61.1	62.1	62.4	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5
62.4	63.3	65.0	66.1	66.4	66.5	66.9	67.0	67.0	67.0	67.0	67.1	67.1
65.0	66.0	67.8	68.9	69.3	69.5	69.8	70.0	70.0	70.0	70.0	70.1	70.1
68.1	69.3	71.6	73.3	73.6	74.8	75.3	75.7	75.9	75.9	75.9	76.0	76.0
69.8	71.0	73.6	75.4	75.7	77.1	78.0	78.6	78.7	78.7	78.8	78.8	78.8
72.3	73.5	76.2	78.2	78.6	80.2	81.3	82.0	82.1	82.1	82.1	82.2	82.2
73.0	74.3	77.3	79.5	79.9	81.5	82.6	83.3	83.4	83.4	83.4	83.5	83.5
74.4	75.9	78.8	81.0	81.4	83.0	84.2	85.2	85.5	85.5	85.5	85.6	85.6
75.4	76.8	80.1	82.7	83.3	85.2	86.5	87.4	87.9	87.9	87.9	88.1	88.1
75.7	77.5	81.0	84.1	84.7	86.6	87.9	88.9	89.6	89.6	89.6	90.0	90.0
76.1	78.0	82.0	85.0	85.6	88.1	89.4	90.6	91.6	91.6	91.6	92.0	92.0
76.6	78.4	83.0	86.3	87.4	90.0	91.3	92.5	93.5	93.5	93.5	94.2	94.2
76.7	78.8	83.9	87.4	88.9	91.9	93.2	94.6	95.9	95.9	95.9	96.6	96.8
76.7	78.8	83.9	87.6	89.4	92.5	93.8	95.3	96.8	97.1	97.1	97.9	98.4
76.7	78.8	83.9	87.6	89.5	92.7	94.0	95.5	97.1	97.1	97.4	98.5	99.4
76.7	78.8	83.9	87.6	89.5	92.7	94.0	95.5	97.1	97.4	98.6	100.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 71
 MONTH: FEB HOURS: 06-01

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CFIL	33.7	33.9	34.2	34.7	34.9	34.9	35.1	35.1	35.3	35.5	35.9	35.9	35.9	
GE 20000	35.3	36.5	36.9	37.7	37.9	37.9	38.2	38.4	38.6	38.8	39.2	39.2	39.2	
GE 19000	36.4	36.6	37.0	37.3	38.0	38.0	38.3	38.5	38.8	38.9	39.3	39.3	39.3	
GE 16000	36.4	35.5	37.0	37.3	38.0	38.0	38.3	38.5	38.8	38.9	39.3	39.3	39.3	
GE 14000	36.9	37.1	37.5	38.3	38.5	38.5	38.8	39.0	39.2	39.3	39.8	39.8	39.8	
GE 12000	37.6	37.8	38.2	39.0	39.2	39.2	39.5	39.7	39.9	40.0	40.5	40.5	40.5	
GE 10000	39.1	39.3	39.7	40.5	40.8	40.8	41.0	41.2	41.6	41.7	42.2	42.2	42.2	
GE 9000	37.6	39.3	40.2	41.0	41.2	41.2	41.5	41.7	42.0	42.2	42.6	42.6	42.6	
GE 8000	41.5	41.7	42.0	42.9	43.1	43.1	43.3	43.6	43.9	44.1	44.5	44.5	44.5	
GE 7000	42.5	42.8	43.1	43.9	44.2	44.2	44.4	44.6	45.0	45.1	45.6	45.6	45.6	
GE 6000	42.8	43.0	43.5	44.3	44.5	44.5	44.8	45.0	45.3	45.5	45.9	45.9	45.9	
GE 5000	43.7	43.9	44.5	45.5	45.9	46.4	46.8	47.0	47.3	47.6	48.1	48.1	48.1	
GE 4500	44.1	44.3	45.2	46.1	46.6	47.1	47.5	47.7	48.1	48.3	48.8	48.8	48.8	
GE 4000	46.4	46.6	47.6	48.4	49.0	49.5	50.4	50.9	51.2	51.6	52.1	52.1	52.1	
GE 3500	46.8	47.1	48.2	49.0	49.7	50.2	51.1	51.6	51.9	52.3	52.8	52.9	52.9	
GE 3000	50.2	50.5	51.3	52.9	53.8	54.3	55.2	55.7	56.1	56.4	56.9	57.0	57.0	
GE 2500	53.0	53.5	55.0	56.3	57.6	58.1	59.6	60.1	60.4	60.8	61.2	61.4	61.4	
GE 2000	55.5	55.9	57.3	59.3	61.6	62.1	64.0	65.0	65.4	65.8	67.0	67.1	67.1	
GE 1800	56.9	57.4	59.2	61.4	63.5	64.0	66.2	67.3	67.7	68.2	69.4	69.5	69.5	
GE 1500	59.0	59.5	61.7	64.2	66.8	67.7	70.6	72.1	72.7	73.5	74.8	74.9	74.9	
GE 1200	60.9	61.4	63.7	66.3	69.1	70.1	73.7	75.6	76.2	77.0	78.3	78.6	78.6	
GE 1000	62.5	63.0	65.4	68.0	71.1	72.1	76.1	78.1	78.7	79.6	81.0	81.3	81.3	
GE 900	63.3	63.7	66.1	68.5	72.3	73.4	77.5	79.6	80.2	81.3	82.9	83.2	83.2	
GE 800	63.5	64.0	66.7	69.8	73.6	74.7	78.8	81.0	81.6	82.7	84.3	84.6	84.6	
GE 700	64.3	64.8	67.5	70.8	74.7	75.9	80.0	82.3	83.2	84.2	86.0	86.2	86.2	
GE 600	64.4	64.9	67.7	71.0	74.9	76.1	80.2	82.7	83.6	84.7	86.5	86.8	86.8	
GE 500	64.7	65.4	68.4	72.0	76.1	77.3	81.5	84.1	85.2	86.2	88.2	88.6	88.6	
GE 400	65.4	66.1	69.1	72.7	76.9	78.2	82.9	85.6	87.0	88.3	90.5	90.8	90.8	
GE 300	65.4	66.1	69.3	72.8	77.1	78.7	84.0	86.7	88.2	90.1	92.5	92.9	92.9	
GE 200	65.4	66.1	69.3	72.8	77.1	78.7	84.0	86.7	88.5	90.6	93.1	93.5	93.5	
GE 100	65.4	66.1	69.3	72.8	77.1	78.7	84.0	86.9	88.7	90.9	93.4	93.9	93.9	
GE 000	65.4	66.1	69.3	72.8	77.1	78.7	84.0	86.9	88.7	90.9	93.4	93.9	93.9	

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
IC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 06-08

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
34.9	34.9	35.1	35.1	35.3	35.5	35.9	35.9	35.9	35.9	35.9	35.9
37.9	37.9	38.2	38.4	38.6	38.8	39.2	39.2	39.2	39.2	39.2	39.2
38.0	38.0	38.3	38.5	38.8	38.9	39.3	39.3	39.3	39.3	39.3	39.3
38.0	38.0	38.3	38.5	38.8	38.9	39.3	39.3	39.3	39.3	39.3	39.3
38.5	38.5	38.8	39.0	39.2	39.3	39.8	39.8	39.8	39.8	39.8	39.8
39.2	39.2	39.5	39.7	39.9	40.0	40.5	40.5	40.5	40.5	40.5	40.5
40.8	40.8	41.0	41.2	41.6	41.7	42.2	42.2	42.2	42.2	42.2	42.2
41.2	41.2	41.5	41.7	42.0	42.2	42.6	42.6	42.6	42.6	42.6	42.6
43.1	43.1	43.3	43.6	43.9	44.1	44.5	44.5	44.5	44.5	44.5	44.5
44.2	44.2	44.4	44.6	45.0	45.1	45.6	45.6	45.6	45.6	45.6	45.6
44.5	44.5	44.8	45.0	45.3	45.5	45.9	45.9	45.9	45.9	45.9	45.9
46.7	46.4	46.8	47.0	47.3	47.6	48.1	48.1	48.1	48.1	48.1	48.1
46.6	47.1	47.5	47.7	48.1	48.3	48.8	48.8	48.8	48.8	48.8	48.8
49.0	49.5	50.4	50.9	51.2	51.6	52.1	52.1	52.1	52.1	52.1	52.1
49.7	50.2	51.1	51.6	51.9	52.3	52.8	52.9	52.9	52.9	52.9	52.9
53.8	54.3	55.2	55.7	56.1	56.4	56.9	57.0	57.0	57.0	57.0	57.0
57.6	58.1	59.6	60.1	60.4	60.8	61.2	61.4	61.4	61.4	61.4	61.4
61.6	62.1	64.0	65.0	65.4	65.8	67.0	67.1	67.1	67.1	67.1	67.1
63.5	64.0	66.2	67.3	67.7	68.2	69.4	69.5	69.5	69.5	69.5	69.5
65.8	67.7	70.6	72.1	72.7	73.5	74.8	74.9	74.9	74.9	74.9	74.9
69.1	70.1	73.7	75.6	76.2	77.0	78.3	78.6	78.7	78.7	78.7	78.7
71.1	72.1	76.1	78.1	78.7	79.6	81.0	81.3	81.6	81.6	81.6	81.6
72.3	73.4	77.5	79.6	80.2	81.3	82.9	83.2	83.5	83.5	83.5	83.5
73.6	74.7	78.8	81.0	81.6	82.7	84.3	84.6	85.3	85.3	85.6	85.6
74.7	75.9	80.0	82.3	83.2	84.2	86.0	86.2	87.0	87.0	87.9	88.0
74.7	76.1	80.2	82.7	83.6	84.7	86.5	86.8	87.8	87.8	88.6	88.7
75.1	77.3	81.5	84.1	85.2	86.2	88.2	88.6	90.8	91.2	92.1	92.3
75.9	78.2	82.9	85.6	87.0	88.3	90.5	90.8	93.1	93.4	94.7	94.9
77.1	78.7	84.0	86.7	88.2	90.1	92.5	92.9	95.2	95.6	96.9	97.4
77.1	78.7	84.0	86.7	88.5	90.6	93.1	93.5	95.9	96.6	98.0	98.9
77.1	78.7	84.0	86.9	88.7	90.9	93.4	93.9	96.2	96.9	98.4	99.6
77.1	78.7	84.0	86.9	88.7	90.9	93.4	93.9	96.2	96.9	98.4	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: FEB HOURS: 09-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES													G 1/
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	29.3	29.6	29.9	30.0	31.3	31.4	31.9	32.2	32.2	32.2	32.4	32.4	32	
GE 20000	33.8	34.0	34.4	34.6	35.9	36.0	36.5	36.7	36.7	36.7	37.0	37.0	37	
GE 18000	33.8	34.2	34.5	34.7	36.0	36.2	36.6	36.9	36.9	36.9	37.1	37.1	37	
GE 16000	33.8	34.2	34.5	34.7	36.0	36.2	36.6	36.9	36.9	36.9	37.1	37.1	37	
GE 14000	34.7	35.1	35.5	35.7	37.0	37.1	37.6	37.8	37.8	37.8	38.0	38.0	38	
GE 12000	36.3	36.6	37.0	37.2	38.5	38.6	39.1	39.3	39.3	39.3	39.6	39.6	39	
GE 10000	38.6	39.0	39.5	39.8	41.1	41.2	41.7	41.9	41.9	41.9	42.2	42.2	42	
GE 9000	39.3	39.8	40.3	40.6	41.9	42.0	42.5	42.8	42.8	42.8	43.0	43.0	43	
GE 8000	41.6	42.0	42.5	42.9	44.2	44.3	44.8	45.0	45.1	45.1	45.3	45.3	45	
GE 7000	42.6	43.1	43.6	43.9	45.2	45.3	45.9	46.2	46.3	46.3	46.5	46.5	46	
GE 6000	43.0	43.5	44.1	44.4	45.8	45.9	46.5	46.8	46.9	46.9	47.1	47.1	47	
GE 5000	44.6	45.2	45.8	46.3	48.2	48.4	49.0	49.2	49.4	49.4	49.6	49.6	49	
GE 4500	45.1	45.7	46.3	46.8	48.8	49.0	49.6	49.8	49.9	49.9	50.2	50.2	50	
GE 4000	45.9	46.5	47.2	47.7	49.7	49.9	50.6	51.1	51.2	51.2	51.5	51.5	51	
GE 3500	46.4	47.1	47.9	48.4	50.4	50.6	51.5	51.9	52.1	52.1	52.3	52.3	52	
GE 3000	47.8	48.5	49.9	50.6	52.9	53.2	54.3	54.8	54.9	54.9	55.1	55.1	55	
GE 2500	50.4	51.4	53.0	54.1	56.7	57.1	58.4	59.0	59.1	59.2	59.5	59.5	59	
GE 2000	52.3	53.5	55.6	56.9	59.8	60.3	63.1	63.8	64.2	64.8	65.1	65.3	65	
GE 1800	53.4	54.8	56.9	58.3	61.6	62.1	65.3	65.1	66.4	67.1	67.5	67.6	68	
GE 1500	55.5	56.9	59.4	61.1	65.0	65.5	69.4	70.4	70.8	71.5	72.0	72.1	72	
GE 1200	56.5	58.0	61.1	63.4	68.0	68.4	72.4	73.5	74.4	75.4	76.3	76.4	76	
GE 1000	57.6	59.0	62.4	64.8	69.8	70.3	74.8	76.2	77.3	78.6	79.6	79.7	80	
GE 900	58.7	60.4	64.0	66.3	71.5	72.0	76.4	77.0	79.0	80.3	81.4	81.5	82	
GE 800	59.1	60.9	64.4	66.9	72.3	72.8	77.4	79.0	80.3	81.6	82.9	83.2	84	
GE 700	59.4	61.1	64.8	67.3	72.7	73.1	77.7	79.5	80.8	82.3	84.0	84.3	85	
GE 600	59.8	61.6	65.4	67.8	73.5	74.0	78.6	80.4	81.7	83.3	84.9	85.4	86	
GE 500	60.2	62.0	65.8	68.4	74.3	74.9	79.6	81.6	83.6	85.6	87.9	88.6	90	
GE 400	60.4	62.2	66.7	69.4	75.4	76.1	80.8	83.0	85.3	87.5	90.5	91.2	93	
GE 300	60.4	62.2	66.7	69.5	75.9	76.6	81.3	83.6	85.9	88.3	92.1	92.9	94	
GE 200	60.4	62.2	66.7	69.5	75.9	76.6	81.3	83.6	85.9	88.3	92.7	93.6	95	
GE 100	60.4	62.2	66.7	69.5	75.9	76.6	81.3	83.6	85.9	88.3	92.8	93.8	96	
GE 000	60.4	62.2	66.7	69.5	75.9	76.6	81.3	83.6	85.9	88.3	92.8	93.8	96	

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: UTC: + 5 MONTH: FEB HOURS: 09-11

VISIBILITY IN STATUTE MILES												
CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0.0	31.3	31.4	31.9	32.2	32.2	32.2	32.4	32.4	32.4	32.4	32.4	32.4
4.6	35.9	36.0	36.5	36.7	36.7	36.7	37.0	37.0	37.0	37.0	37.0	37.0
4.7	35.0	36.2	36.6	36.9	36.9	36.9	37.1	37.1	37.1	37.1	37.1	37.1
4.7	35.0	36.2	36.6	36.9	36.9	36.9	37.1	37.1	37.1	37.1	37.1	37.1
4.7	37.0	37.1	37.6	37.8	37.8	37.8	38.0	38.0	38.0	38.0	38.0	38.0
7.2	38.5	38.6	39.1	39.3	39.3	39.3	39.6	39.6	39.6	39.6	39.6	39.6
7.3	41.1	41.2	41.7	41.9	41.9	41.9	42.2	42.2	42.2	42.2	42.2	42.2
7.5	41.9	42.0	42.5	42.8	42.8	42.8	43.0	43.0	43.0	43.0	43.0	43.0
7.7	44.2	44.3	44.8	45.0	45.1	45.1	45.3	45.3	45.3	45.3	45.3	45.3
7.7	45.2	45.3	45.9	46.2	46.3	46.3	46.5	46.5	46.5	46.5	46.5	46.5
7.7	45.3	45.9	46.5	46.3	46.9	46.9	47.1	47.1	47.1	47.1	47.1	47.1
7.7	43.2	48.4	49.0	49.2	49.4	49.4	49.6	49.6	49.6	49.6	49.6	49.6
7.7	43.3	49.0	49.6	49.8	49.9	49.9	50.2	50.2	50.2	50.2	50.2	50.2
7.7	49.7	49.9	50.6	51.1	51.2	51.2	51.5	51.5	51.6	51.6	51.6	51.6
7.7	50.4	50.6	51.5	51.9	52.1	52.1	52.3	52.3	52.4	52.4	52.4	52.4
7.7	52.9	53.2	54.3	54.8	54.9	54.9	55.1	55.1	55.2	55.2	55.2	55.2
7.7	56.7	57.1	58.4	59.0	59.1	59.2	59.5	59.5	59.7	59.7	59.7	59.7
7.7	59.3	60.3	63.1	63.8	64.2	64.8	65.1	65.3	65.6	65.6	65.6	65.6
7.7	61.6	62.1	65.3	65.1	66.4	67.1	67.5	67.6	68.0	68.0	68.0	68.0
7.7	65.0	65.5	69.4	70.4	70.8	71.5	72.0	72.1	72.4	72.4	72.4	72.4
7.7	68.0	68.4	72.4	73.5	74.4	75.4	76.3	76.4	76.8	76.8	76.8	76.8
7.7	59.8	70.3	74.8	76.2	77.3	78.6	79.6	79.7	80.8	80.8	80.8	80.8
7.7	71.5	72.0	76.4	78.0	79.0	80.3	81.4	81.5	82.6	82.6	82.6	82.6
7.7	72.3	72.8	77.4	79.0	80.3	81.6	82.9	83.2	84.2	84.2	84.3	84.3
7.7	72.7	73.1	77.7	79.5	80.8	82.3	84.0	84.3	85.4	85.4	85.5	86.2
7.7	73.5	74.0	78.6	80.4	81.7	83.3	84.9	85.4	86.6	86.6	86.7	87.4
7.7	74.3	74.9	79.6	81.6	83.6	85.6	87.9	88.6	90.3	90.3	90.5	91.4
7.7	75.4	76.1	80.8	83.0	85.3	87.5	90.5	91.2	93.1	93.2	94.1	95.1
7.7	75.9	76.6	81.3	83.6	85.9	88.3	92.1	92.9	94.9	95.1	96.3	97.3
7.7	75.9	76.6	81.3	83.6	85.9	88.3	92.7	93.6	95.8	95.9	97.3	99.1
7.7	75.9	76.6	81.3	83.6	85.9	88.3	92.8	93.8	96.2	96.3	97.8	99.6
7.7	75.9	76.6	81.3	83.6	85.9	88.3	92.8	93.8	96.2	96.3	97.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: FEB HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	28.9	29.3	29.4	29.6	29.7	29.7	30.0	30.0	30.0	30.3	30.3	30.3	30.3	
GE 20000	34.3	34.7	34.9	35.2	35.3	35.3	35.7	35.7	35.7	35.9	35.9	35.9	35.9	
GE 18000	34.5	35.0	35.1	35.6	35.7	35.7	36.0	36.0	36.0	36.3	36.3	36.3	36.3	
GE 16000	34.7	35.2	35.3	35.8	35.9	35.9	36.3	36.3	36.3	36.5	36.5	36.5	36.5	
GE 14000	35.9	36.4	36.5	37.1	37.2	37.2	37.6	37.6	37.7	38.0	38.0	38.0	38.0	
GE 12000	37.1	37.6	37.7	38.3	38.4	38.4	38.8	38.8	38.9	39.2	39.2	39.2	39.2	
GE 10000	38.4	38.9	39.0	39.8	39.9	39.9	40.3	40.3	40.4	40.8	40.8	40.8	40.8	
GE 9000	38.6	39.1	39.2	40.0	40.2	40.2	40.5	40.5	40.6	41.0	41.0	41.0	41.0	
GE 8000	41.3	41.8	42.0	42.9	43.0	43.2	43.6	43.6	43.7	44.1	44.1	44.1	44.1	
GE 7000	43.1	43.6	43.9	44.6	44.9	45.1	45.5	45.6	45.7	46.1	46.1	46.1	46.1	
GE 6000	43.2	43.7	43.9	44.8	45.1	45.3	45.7	45.8	45.9	46.4	46.4	46.4	46.4	
GE 5000	44.4	45.2	45.7	46.8	47.3	47.6	47.9	48.2	48.5	49.0	49.0	49.0	49.0	
GE 4500	44.5	45.3	45.8	46.9	47.5	47.7	48.1	48.3	48.6	49.1	49.1	49.1	49.1	
GE 4000	46.3	47.1	47.7	48.9	49.4	49.6	49.9	50.2	50.5	51.1	51.1	51.1	51.1	
GE 3500	47.2	48.1	48.9	50.1	50.8	51.0	51.4	51.6	51.9	52.5	52.5	52.5	52.5	
GE 3000	50.3	51.2	52.4	53.5	54.8	55.0	55.4	55.6	55.9	56.5	56.5	56.5	56.5	
GE 2500	51.7	53.1	54.4	55.8	57.5	58.0	58.7	59.0	59.5	60.2	60.3	60.3	60.3	
GE 2000	55.5	57.2	59.1	60.9	63.0	63.5	65.0	65.6	66.1	66.9	67.1	67.1	67.1	
GE 1800	56.8	58.5	60.5	62.3	64.5	65.1	67.1	67.8	68.3	69.1	69.4	69.4	69.5	
GE 1500	59.2	61.0	64.0	65.8	68.9	69.7	72.4	73.6	74.3	75.4	75.7	75.7	76.0	
GE 1200	61.5	63.8	66.8	69.1	72.4	73.5	76.9	78.1	78.8	80.0	80.6	80.6	80.8	
GE 1000	63.1	65.5	68.7	71.1	74.4	75.7	79.6	81.0	81.9	83.4	84.3	84.3	85.3	
GE 900	64.0	66.5	70.2	73.0	76.6	77.9	81.9	83.5	84.5	86.1	87.0	87.0	88.0	
GE 800	64.2	66.8	70.7	73.5	77.3	78.6	82.7	84.9	85.9	88.0	88.9	88.9	89.9	
GE 700	64.5	67.3	71.1	74.1	78.0	79.4	83.5	85.9	86.9	89.0	90.0	90.1	91.0	
GE 600	64.7	67.4	71.3	74.2	78.1	79.5	83.6	86.5	87.5	89.6	90.7	90.9	91.9	
GE 500	64.7	67.4	71.3	74.2	78.3	79.7	84.3	87.5	88.7	91.0	92.5	92.8	93.9	
GE 400	64.7	67.4	71.5	74.6	78.7	80.2	84.9	88.1	89.3	91.8	93.4	94.0	95.2	
GE 300	64.7	67.4	71.5	74.6	78.7	80.2	84.9	88.2	89.4	91.9	94.0	94.7	96.2	
GE 200	64.7	67.4	71.5	74.5	78.7	80.2	84.9	88.2	89.4	91.9	94.0	94.7	96.3	
GE 100	64.7	67.4	71.5	74.6	78.7	80.2	84.9	88.2	89.4	91.9	94.2	94.9	96.6	
GE 000	64.7	67.4	71.5	74.6	78.7	80.2	84.9	88.2	89.4	91.9	94.2	94.9	96.6	

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 12-14

VISIBILITY IN STATUTE MILES											
CE 3	CE 2 1/2	CE 2	CE 1 1/2	CE 1 1/4	CE 1	CE 3/4	CE 5/8	CE 1/2	CE 3/8	CE 1/4	CE 0
29.7	29.7	30.0	30.0	30.0	30.3	30.3	30.3	30.3	30.3	30.3	30.3
35.3	35.3	35.7	35.7	35.7	35.9	35.9	35.9	35.9	35.9	35.9	35.9
35.7	35.7	36.0	36.0	36.0	36.3	36.3	36.3	36.3	36.3	36.3	36.3
35.9	35.9	36.3	36.3	36.3	36.5	36.5	36.5	36.5	36.5	36.5	36.5
37.2	37.2	37.6	37.6	37.7	38.0	38.0	38.0	38.0	38.0	38.0	38.0
38.4	38.4	38.8	38.8	38.9	39.2	39.2	39.2	39.2	39.2	39.2	39.2
39.9	39.9	40.3	40.3	40.4	40.8	40.8	40.8	40.8	40.8	40.8	40.8
40.2	40.2	40.5	40.5	40.6	41.0	41.0	41.0	41.0	41.0	41.0	41.0
43.0	43.2	43.6	43.6	43.7	44.1	44.1	44.1	44.1	44.1	44.1	44.1
44.9	45.1	45.5	45.6	45.7	46.1	46.1	46.1	46.1	46.1	46.1	46.1
45.1	45.3	45.7	45.8	45.9	46.4	46.4	46.4	46.4	46.4	46.4	46.4
47.3	47.6	47.9	48.2	48.5	49.0	49.0	49.0	49.0	49.0	49.0	49.0
47.5	47.7	48.1	48.3	48.6	49.1	49.1	49.1	49.1	49.1	49.1	49.1
49.4	49.6	49.9	50.2	50.5	51.1	51.1	51.1	51.1	51.1	51.1	51.1
50.3	51.0	51.4	51.6	51.9	52.5	52.5	52.5	52.5	52.5	52.5	52.5
54.8	55.0	55.4	55.6	55.9	56.5	56.5	56.5	56.5	56.5	56.5	56.5
57.5	58.0	58.7	59.0	59.5	60.2	60.3	60.3	60.3	60.3	60.3	60.3
63.0	63.5	65.0	65.6	66.1	66.9	67.1	67.1	67.3	67.3	67.3	67.3
64.5	65.1	67.1	67.8	68.3	69.1	69.4	69.4	69.5	69.5	69.5	69.5
68.9	69.7	72.4	73.6	74.3	75.4	75.7	75.7	76.0	76.0	76.2	76.2
72.4	73.5	76.9	78.1	78.8	80.0	80.6	80.6	80.8	80.9	81.2	81.2
74.4	75.7	79.6	81.0	81.9	83.4	84.3	84.3	85.3	85.4	85.6	85.6
75.6	77.9	81.9	83.5	84.5	86.1	87.0	87.0	88.0	88.1	88.3	88.3
77.3	78.6	82.7	84.9	85.9	88.0	88.9	88.9	89.9	90.0	90.2	90.2
78.0	79.4	83.5	85.9	86.9	89.0	90.0	90.1	91.0	91.2	91.4	91.8
79.1	79.5	83.6	86.5	87.5	89.6	90.7	90.9	91.9	92.1	92.3	92.7
79.3	79.7	84.3	87.5	88.7	91.0	92.5	92.8	93.9	94.1	94.5	94.8
79.7	80.2	84.9	88.1	89.3	91.8	93.4	94.0	95.2	95.6	96.3	96.7
79.7	80.2	84.9	88.2	89.4	91.9	94.0	94.7	96.2	96.7	97.9	98.2
79.7	80.2	84.9	88.2	89.4	91.9	94.2	94.9	96.6	97.4	98.8	99.6
79.7	80.2	84.9	88.2	89.4	91.9	94.2	94.9	96.6	97.4	98.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: FEB HOURS: 15-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8		
NO CEIL	29.8	29.9	30.0	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	3
GE 20000	35.8	35.9	36.2	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	3
GE 19000	36.6	36.9	37.2	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	3
GE 16000	37.2	37.5	37.8	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	3
GE 14000	38.6	38.9	39.2	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	3
GE 12000	40.9	41.1	41.5	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	4
GE 10000	43.3	43.6	43.9	44.4	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	4
GE 9000	43.6	43.8	44.2	44.8	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	4
GE 8000	45.3	45.6	45.9	46.5	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	4
GE 7000	46.4	46.6	47.0	47.6	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	4
GE 6000	46.6	46.9	47.2	47.8	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	4
GE 5000	47.8	48.1	48.4	49.0	49.2	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	4
GE 4500	47.8	48.1	48.4	49.0	49.2	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	4
GE 4000	49.6	49.8	50.8	51.6	51.8	51.9	51.9	52.1	52.2	52.2	52.2	52.2	52.2	5
GE 3500	51.2	51.5	52.5	53.4	53.8	53.9	53.9	54.1	54.2	54.2	54.2	54.2	54.2	5
GE 3000	55.9	56.2	57.4	58.2	58.9	59.0	59.0	59.1	59.2	59.2	59.4	59.4	59.4	5
GE 2500	58.8	59.2	61.0	62.1	62.9	63.0	63.4	63.6	63.7	63.8	64.0	64.0	64.0	6
GE 2000	62.3	63.1	66.8	68.2	69.6	69.7	70.1	70.3	70.4	70.6	70.7	70.8	70.8	7
GE 1800	63.5	64.4	68.1	69.5	71.0	71.1	71.5	72.1	72.2	72.6	72.7	72.8	72.8	7
GE 1500	65.7	67.1	71.6	73.6	76.0	76.2	77.0	78.0	78.4	79.3	79.7	79.9	79.9	8
GE 1200	67.1	68.9	74.2	76.7	79.6	79.9	80.9	82.0	82.7	83.9	84.8	85.0	85.0	8
GE 1000	68.4	70.3	75.9	78.7	81.7	82.1	83.2	84.5	85.3	86.5	87.5	87.8	87.8	8
GE 900	68.4	70.7	76.8	79.6	82.9	83.3	84.3	86.0	86.3	88.0	89.0	89.4	89.4	8
GE 800	69.3	71.1	77.6	80.7	84.1	84.5	85.5	87.5	88.9	90.1	91.3	91.6	91.6	9
GE 700	69.5	71.4	77.9	81.3	84.7	85.0	86.1	88.1	89.5	90.9	92.5	92.8	92.8	9
GE 600	69.6	71.5	78.0	81.4	84.8	85.3	86.3	88.3	89.8	91.2	92.8	93.2	93.2	9
GE 500	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.6	90.0	91.9	93.5	93.9	93.9	9
GE 400	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.8	90.3	92.5	94.5	94.9	94.9	9
GE 300	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	96.1	9
GE 200	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	96.1	9
GE 100	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	96.1	9
GE 000	69.6	71.5	78.0	81.4	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	96.1	9

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 15-17

VISIBILITY IN STATUTE MILES

CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3	30.3
35.4	35.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4	36.4
37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5
38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0	38.0
39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5	39.5
41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8
44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6
45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8
47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8	47.8
48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
51.9	51.9	51.9	51.9	52.1	52.2	52.2	52.2	52.2	52.2	52.2	52.2	52.2
53.8	53.8	53.9	53.9	54.1	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2
59.2	59.2	59.0	59.0	59.1	59.2	59.2	59.4	59.4	59.4	59.4	59.4	59.4
62.9	62.9	63.0	63.4	63.6	63.7	63.8	64.0	64.0	64.0	64.0	64.0	64.0
69.6	69.6	69.7	70.1	70.3	70.4	70.6	70.7	70.8	70.9	71.0	71.0	71.0
71.0	71.0	71.1	71.5	72.1	72.2	72.6	72.7	72.8	72.9	73.0	73.0	73.0
76.0	76.0	76.2	77.0	78.0	78.4	79.3	79.7	79.9	80.0	80.1	80.1	80.1
79.6	79.6	79.9	80.9	82.0	82.7	83.9	84.8	85.0	85.2	85.3	85.3	85.3
82.1	82.1	82.1	83.2	84.5	85.3	86.5	87.5	87.8	88.2	88.5	88.5	88.5
83.9	83.9	83.3	84.3	86.0	86.8	88.0	89.0	89.4	89.9	90.1	90.1	90.1
84.1	84.1	84.5	85.5	87.5	88.9	90.1	91.3	91.6	92.1	92.3	92.3	92.3
84.7	84.7	85.0	86.1	88.1	89.5	90.9	92.5	92.8	93.5	93.8	93.8	94.1
84.8	84.8	85.3	86.3	89.3	89.8	91.2	92.8	93.2	94.1	94.3	94.5	94.8
84.8	84.8	85.4	86.5	88.6	90.0	91.9	93.5	93.9	94.9	95.2	95.3	95.8
84.8	84.8	85.4	86.5	88.8	90.3	92.5	94.5	94.9	96.3	96.6	96.9	97.4
84.8	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	97.9	98.1	98.6	99.1
84.8	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	97.9	98.1	99.2	100.0
84.8	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	97.9	98.1	99.2	100.0
84.8	84.8	85.4	86.5	88.8	90.6	93.3	95.6	96.1	97.9	98.1	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: FEB HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	33.3	33.9	33.9	33.9	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3
GE 20000	40.0	40.6	40.8	40.8	41.5	41.5	41.5	41.6	41.6	41.6	41.6	41.6	41.6
GE 18000	40.6	41.2	41.3	41.3	42.0	42.0	42.0	42.2	42.2	42.2	42.2	42.2	42.2
GE 16000	40.6	41.2	41.3	41.3	42.0	42.0	42.0	42.2	42.2	42.2	42.2	42.2	42.2
GE 14000	42.8	43.3	43.5	43.5	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3	44.3
GE 12000	43.8	44.5	44.6	44.6	45.3	45.3	45.3	45.5	45.5	45.5	45.5	45.5	45.5
GE 10000	46.5	47.2	47.6	47.6	48.4	48.4	48.4	48.5	48.5	48.5	48.5	48.5	48.5
GE 9000	46.8	47.5	47.8	47.8	48.6	48.6	48.6	48.8	48.8	48.8	48.8	48.8	48.8
GE 8000	49.5	50.3	50.6	50.6	51.5	51.5	51.5	51.6	51.6	51.6	51.6	51.6	51.6
GE 7000	49.8	50.6	51.0	51.0	51.8	51.8	51.8	51.9	51.9	51.9	51.9	51.9	51.9
GE 6000	50.4	51.2	51.6	51.6	52.4	52.4	52.4	52.5	52.5	52.5	52.5	52.5	52.5
GE 5000	51.4	52.3	52.7	52.7	53.5	53.5	53.5	53.6	53.6	53.6	53.6	53.6	53.6
GE 4500	51.4	52.3	52.7	52.7	53.5	53.5	53.5	53.6	53.6	53.6	53.6	53.6	53.6
GE 4000	52.2	53.4	53.8	53.8	54.9	54.9	54.9	55.0	55.0	55.0	55.0	55.0	55.0
GE 3500	53.1	54.4	54.9	55.0	56.2	56.2	56.3	56.4	56.4	56.4	56.4	56.4	56.4
GE 3000	55.7	57.1	57.6	57.7	59.2	59.4	59.6	59.7	59.7	59.7	59.7	59.7	59.7
GE 2500	59.2	60.9	61.6	61.8	63.5	63.6	63.8	64.4	64.4	64.4	64.4	64.4	64.4
GE 2000	63.4	65.3	66.4	67.0	69.7	70.0	70.3	71.7	71.8	71.8	71.8	71.8	71.8
GE 1800	64.8	66.9	68.1	69.3	72.0	72.2	72.6	74.0	74.1	74.1	74.1	74.1	74.1
GE 1500	69.4	71.6	72.9	74.6	77.9	78.2	78.9	80.8	81.6	81.6	81.7	81.7	81.7
GE 1200	70.7	73.3	75.0	77.1	81.0	81.4	82.4	84.6	85.4	85.4	85.5	85.5	85.5
GE 1000	71.1	73.7	75.6	77.7	82.6	82.9	84.2	86.5	87.3	87.5	87.8	87.8	88.0
GE 900	72.0	74.7	76.6	78.8	83.6	84.0	85.3	87.8	88.6	88.8	89.0	89.0	89.0
GE 800	72.3	75.0	76.9	79.2	84.0	84.3	85.6	88.8	90.1	90.3	90.6	90.6	90.6
GE 700	72.3	75.0	76.9	79.4	84.2	84.7	86.0	89.4	91.2	91.4	91.6	91.6	92.0
GE 600	72.4	75.1	77.3	79.7	84.7	85.3	86.7	90.2	92.0	92.5	92.7	92.7	93.0
GE 500	72.6	75.4	77.7	80.2	85.4	86.0	88.1	91.9	93.8	94.2	94.9	94.9	95.0
GE 400	72.7	75.5	77.9	80.3	85.5	86.1	88.3	92.5	94.3	94.8	95.6	95.6	96.0
GE 300	72.7	75.5	77.9	80.3	85.6	86.2	88.5	92.6	94.8	95.4	96.2	96.3	96.6
GE 200	72.7	75.5	77.9	80.3	85.6	86.2	88.5	92.6	94.8	95.5	96.5	96.6	97.0
GE 100	72.7	75.5	77.9	80.3	85.6	86.2	88.5	92.6	94.8	95.5	96.5	96.6	97.0
GE 000	72.7	75.5	77.9	80.3	85.6	86.2	88.5	92.6	94.8	95.5	96.5	96.6	97.0

TOTAL NUMBER OF OBSERVATIONS 840

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 18-20

VISIBILITY IN STATUTE MILES												
CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
33.0	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3
40.8	41.5	41.5	41.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
41.3	42.0	42.0	42.0	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
41.3	42.0	42.0	42.0	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2	42.2
43.5	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
44.6	45.3	45.3	45.3	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.5
47.6	48.4	48.4	48.4	48.5	48.5	48.5	48.5	48.5	48.5	48.5	48.5	48.5
47.8	48.6	48.6	48.6	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8
50.6	51.5	51.5	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
51.0	51.8	51.8	51.8	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9	51.9
51.6	52.4	52.4	52.4	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5	52.5
52.7	53.5	53.5	53.5	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
52.7	53.5	53.5	53.5	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
53.7	54.9	54.9	54.9	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0
55.0	56.2	56.2	56.3	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
57.7	59.2	59.4	59.6	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7	59.7
61.3	63.5	63.6	63.8	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
67.0	69.7	70.0	70.3	71.7	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8
69.3	72.0	72.2	72.6	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
74.5	77.9	78.2	78.9	80.8	81.6	81.6	81.7	81.7	81.7	81.7	81.7	81.7
77.1	81.0	81.4	82.4	84.6	85.4	85.4	85.5	85.5	85.7	85.9	85.9	85.9
77.7	82.6	82.9	84.2	86.5	87.3	87.5	87.8	87.8	88.0	88.2	88.2	88.2
78.3	83.6	84.0	85.3	87.8	88.6	88.8	89.0	89.0	89.3	89.5	89.5	89.5
79.2	84.0	84.3	85.6	88.8	90.1	90.3	90.6	90.6	90.8	91.0	91.2	91.2
79.4	84.2	84.7	86.0	89.4	91.2	91.4	91.6	91.6	92.0	92.2	92.5	92.6
79.7	84.7	85.3	86.7	90.2	92.0	92.5	92.7	92.7	93.1	93.3	93.6	93.8
80.2	85.4	86.0	87.1	91.9	93.8	94.2	94.9	94.9	95.3	95.6	96.0	96.2
80.3	85.5	86.1	87.3	92.5	94.3	94.8	95.6	95.6	96.0	96.3	96.7	96.9
80.3	85.6	86.2	87.5	92.6	94.8	95.4	96.2	96.3	96.9	97.3	97.6	98.0
80.3	85.6	86.2	87.5	92.6	94.8	95.5	96.5	96.6	97.4	98.2	98.8	99.8
80.3	85.6	86.2	87.5	92.6	94.8	95.5	96.5	96.6	97.4	98.2	98.9	100.0
80.3	85.6	86.2	87.5	92.6	94.8	95.5	96.5	96.6	97.4	98.2	98.9	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: A
 LST TO UTC: + 5 MONTH: FEB HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	35.6	35.7	35.4	36.5	37.0	37.0	37.2	37.2	37.2	37.2	37.2	37.2
GE 20000	40.6	40.8	41.5	41.6	42.0	42.0	42.3	42.3	42.3	42.3	42.3	42.3
GE 18000	41.0	41.1	41.8	41.9	42.4	42.4	42.6	42.6	42.6	42.6	42.6	42.6
GE 16000	41.0	41.1	41.8	41.9	42.4	42.4	42.6	42.6	42.6	42.6	42.6	42.6
GE 14000	42.8	43.0	43.8	44.1	44.5	44.5	44.8	44.8	44.8	44.8	44.8	44.8
GE 12000	43.5	43.7	44.5	44.8	45.2	45.2	45.5	45.5	45.5	45.5	45.5	45.5
GE 10000	45.0	45.2	46.1	46.3	46.8	46.8	47.0	47.0	47.0	47.0	47.0	47.0
GE 9000	45.3	45.6	46.4	46.6	47.1	47.1	47.3	47.3	47.3	47.3	47.3	47.3
GF 8000	47.0	47.2	48.1	48.3	48.9	48.9	49.1	49.1	49.1	49.1	49.1	49.1
GE 7000	47.7	48.1	48.9	49.1	50.1	50.3	50.5	50.5	50.5	50.5	50.5	50.5
GE 6000	48.5	48.9	49.7	49.9	50.9	51.1	51.4	51.4	51.4	51.4	51.4	51.4
GE 5000	50.3	50.6	51.5	51.7	52.7	52.9	53.1	53.1	53.1	53.1	53.1	53.1
GE 4500	51.2	51.6	52.4	52.7	53.6	53.8	54.1	54.1	54.1	54.1	54.1	54.1
GE 4000	53.0	53.6	54.7	54.9	56.1	56.4	56.7	56.7	56.7	56.7	56.7	56.7
GE 3500	53.7	54.3	55.4	55.7	57.0	57.5	57.7	57.7	57.7	57.7	57.7	57.7
GE 3000	55.9	56.5	58.1	58.5	60.0	60.4	60.7	60.7	60.7	60.7	60.7	60.7
GE 2500	59.4	60.0	62.0	62.7	64.2	64.7	65.0	65.3	65.3	65.3	65.3	65.3
GE 2000	62.2	63.0	65.1	66.1	68.4	69.3	70.0	70.6	70.7	70.8	70.8	70.8
GE 1800	63.5	64.3	66.4	67.5	69.8	70.7	71.5	72.1	72.3	72.4	72.4	72.4
GE 1500	66.9	67.7	70.0	71.1	73.9	74.9	76.2	77.5	78.4	78.7	78.9	78.9
GE 1200	68.3	69.6	72.2	73.7	76.8	77.9	79.4	80.8	81.7	82.0	82.2	82.2
GE 1000	69.7	70.6	73.3	75.4	78.9	80.0	81.9	83.6	84.6	85.2	85.5	85.5
GF 900	70.0	71.0	73.7	75.9	79.7	80.8	82.7	84.8	85.7	86.3	86.7	86.7
GE 800	70.6	71.6	74.4	76.6	80.7	81.9	83.7	86.1	87.0	87.6	88.2	88.2
GE 700	70.6	71.6	74.4	76.6	80.7	81.9	83.9	86.3	87.5	88.3	89.2	89.2
GE 600	70.9	72.0	75.0	77.1	81.3	82.4	84.6	87.2	88.7	89.6	90.7	90.7
GE 500	71.3	72.4	75.6	77.9	82.0	83.2	85.6	88.3	89.9	91.0	92.2	92.2
GE 400	71.4	72.6	75.7	78.1	82.4	83.6	86.6	89.9	91.4	92.9	94.3	94.3
GE 300	71.4	72.6	75.7	78.1	82.4	83.6	86.8	90.6	92.6	94.2	95.9	96.0
GE 200	71.4	72.6	75.7	78.1	82.6	83.9	87.2	91.0	93.2	95.2	97.1	97.3
GE 100	71.4	72.6	75.7	78.1	82.6	83.9	87.2	91.0	93.2	95.2	97.1	97.3
GE 000	71.4	72.6	75.7	78.1	82.6	83.9	87.2	91.0	93.2	95.2	97.1	97.3

TOTAL NUMBER OF OBSERVATIONS 849

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

AFB: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: 21-23

VISIBILITY IN STATUTE MILES

GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
37.0	37.0	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.2	37.3
42.0	42.0	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.3	42.4
42.4	42.4	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.8
42.4	42.4	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.8
44.5	44.5	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.9
45.2	45.2	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.5	45.6
46.8	46.8	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.0	47.1
47.1	47.1	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.5
48.9	48.9	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.2
50.1	50.3	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.6
50.9	51.1	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.4	51.5
52.7	52.9	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.2
53.6	53.8	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.2
55.1	56.4	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.8
57.0	57.5	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.8
60.0	60.4	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.8
64.2	64.7	65.0	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.3	65.4
69.4	69.3	70.0	70.6	70.7	70.8	70.8	70.8	70.8	70.8	70.8	70.9
67.8	70.7	71.5	72.1	72.3	72.4	72.4	72.4	72.4	72.4	72.4	72.6
73.9	74.9	76.2	77.5	78.4	78.7	78.9	78.9	78.9	78.9	78.9	79.0
76.8	77.9	79.4	80.8	81.7	82.0	82.2	82.2	82.4	82.4	82.4	82.6
78.9	80.0	81.9	83.6	84.6	85.2	85.5	85.5	85.9	85.9	85.9	86.0
79.7	80.8	82.7	84.8	85.7	86.3	86.7	86.7	87.0	87.0	87.0	87.2
80.7	81.9	83.7	86.1	87.0	87.6	88.2	88.2	88.6	88.6	88.6	88.7
80.7	81.9	83.9	86.3	87.5	88.3	89.2	89.2	89.8	89.8	89.8	89.9
81.3	82.4	84.6	87.2	88.7	89.6	90.7	90.7	91.3	91.4	91.5	91.6
82.0	83.2	85.6	88.3	89.9	91.0	92.2	92.2	92.8	92.9	93.1	93.2
82.4	83.6	86.6	89.9	91.4	92.9	94.3	94.3	94.9	95.1	95.2	95.3
82.4	83.6	86.8	90.6	92.6	94.2	95.9	96.0	96.7	96.8	96.9	97.1
82.5	83.9	87.2	91.0	93.2	95.2	97.1	97.3	98.5	98.8	99.3	99.6
82.6	83.9	87.2	91.0	93.2	95.2	97.1	97.3	98.5	98.8	99.6	100.0
82.6	83.9	87.2	91.0	93.2	95.2	97.1	97.3	98.5	98.8	99.6	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: FEB HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	32.5	32.8	33.1	33.3	33.7	33.7	34.0	34.0	34.1	34.1	34.2	34.2	34.2	
GE 20000	37.1	37.4	37.7	38.0	38.5	38.5	38.8	38.8	38.9	39.0	39.1	39.1	39.1	
GE 18000	37.4	37.7	38.1	38.4	38.9	38.9	39.1	39.2	39.3	39.4	39.4	39.4	39.4	
GE 16000	37.5	37.9	38.2	38.5	39.0	39.0	39.3	39.4	39.4	39.5	39.6	39.6	39.6	
GE 14000	38.7	39.0	39.4	39.8	40.3	40.3	40.5	40.6	40.7	40.8	40.9	40.9	40.9	
GE 12000	39.7	40.1	40.5	40.8	41.3	41.3	41.6	41.7	41.7	41.8	41.9	41.9	41.9	
GE 10000	41.5	41.9	42.3	42.7	43.3	43.3	43.5	43.6	43.7	43.8	43.9	43.9	43.9	
GE 9000	42.0	42.3	42.8	43.2	43.7	43.8	44.0	44.1	44.2	44.3	44.4	44.4	44.4	
GE 8000	44.2	44.6	45.0	45.5	46.0	46.1	46.3	46.4	46.5	46.6	46.7	46.7	46.7	
GE 7000	45.2	45.6	46.1	46.5	47.1	47.2	47.5	47.6	47.7	47.8	47.9	47.9	47.9	
GE 6000	45.6	46.1	46.6	47.0	47.7	47.7	48.0	48.1	48.2	48.4	48.4	48.4	48.4	
GE 5000	46.9	47.4	48.0	48.5	49.2	49.4	49.7	49.8	50.0	50.1	50.2	50.2	50.2	
GE 4500	47.2	47.8	48.4	48.8	49.7	49.8	50.1	50.3	50.4	50.5	50.6	50.6	50.6	
GE 4000	49.0	49.6	50.4	50.9	51.8	52.1	52.5	52.8	52.9	53.1	53.2	53.2	53.2	
GE 3500	49.8	50.5	51.4	52.0	53.0	53.3	53.8	54.0	54.2	54.4	54.5	54.5	54.5	
GE 3000	52.8	53.5	54.6	55.3	56.7	57.0	57.6	57.9	58.0	58.2	58.3	58.3	58.3	
GE 2500	55.5	56.4	57.7	58.7	60.3	60.7	61.5	62.0	62.2	62.4	62.5	62.5	62.5	
GE 2000	58.5	59.6	61.5	62.8	64.9	65.5	66.7	67.7	67.9	68.3	68.6	68.6	68.6	
GE 1800	59.9	61.0	63.0	64.5	66.8	67.4	69.0	69.9	70.2	70.6	70.8	70.9	71.0	
GE 1500	62.4	63.7	65.0	67.9	70.8	71.5	73.6	75.0	75.5	76.3	76.7	76.8	76.8	
GE 1200	64.0	65.4	68.1	70.3	73.5	74.4	76.8	78.3	79.0	79.9	80.5	80.7	80.7	
GE 1000	65.2	66.7	69.6	72.0	75.6	76.5	79.3	81.0	81.8	82.8	83.7	83.9	84.0	
GE 900	65.9	67.5	70.5	73.0	76.8	77.7	80.7	82.7	83.4	84.5	85.4	85.6	85.6	
GE 800	66.3	67.9	71.1	73.7	77.8	78.8	81.7	84.0	84.9	86.1	87.0	87.3	87.3	
GE 700	66.7	68.3	71.5	74.2	78.4	79.4	82.5	84.9	85.9	87.2	88.4	88.7	88.7	
GE 600	66.9	68.6	71.9	74.5	78.8	79.9	83.0	85.7	86.6	88.1	89.4	89.7	89.7	
GE 500	67.1	68.8	72.2	75.0	79.4	80.6	84.0	86.8	88.1	89.8	91.3	91.7	91.7	
GE 400	67.3	69.0	72.6	75.4	79.9	81.1	84.8	87.9	89.3	91.2	92.9	93.3	93.3	
GE 300	67.4	69.1	72.6	75.5	80.1	81.3	85.2	88.4	90.1	92.2	94.2	94.8	94.8	
GE 200	67.4	69.1	72.6	75.5	80.1	81.3	85.3	88.5	90.3	92.6	94.7	95.4	95.4	
GE 100	67.4	69.1	72.6	75.5	80.1	81.3	85.3	88.6	90.4	92.7	94.9	95.5	95.5	
GE 000	67.4	69.1	72.6	75.5	80.1	81.3	85.3	88.6	90.4	92.7	94.9	95.5	95.5	

TOTAL NUMBER OF OBSERVATIONS 6792

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB HOURS: ALL

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
33.7	33.7	34.0	34.0	34.1	34.1	34.2	34.2	34.2	34.2	34.2	34.3
34.5	38.5	38.8	38.8	38.9	39.0	39.1	39.1	39.1	39.1	39.1	39.1
38.9	38.9	39.1	39.2	39.3	39.4	39.4	39.4	39.5	39.5	39.5	39.5
39.0	39.0	39.3	39.4	39.4	39.5	39.6	39.6	39.6	39.6	39.6	39.6
40.3	40.3	40.5	40.6	40.7	40.8	40.9	40.9	40.9	40.9	40.9	40.9
41.3	41.3	41.6	41.7	41.7	41.8	41.9	41.9	41.9	41.9	41.9	41.9
43.3	43.3	43.5	43.6	43.7	43.8	43.9	43.9	43.9	43.9	43.9	43.9
43.7	43.8	44.0	44.1	44.2	44.3	44.4	44.4	44.4	44.4	44.4	44.4
46.0	46.1	46.3	46.4	46.5	46.6	46.7	46.7	46.7	46.7	46.7	46.7
47.1	47.2	47.5	47.6	47.7	47.8	47.9	47.9	47.9	47.9	47.9	47.9
47.7	47.7	48.0	48.1	48.2	48.4	48.4	48.4	48.5	48.5	48.5	48.5
49.2	49.4	49.7	49.8	50.0	50.1	50.2	50.2	50.2	50.2	50.2	50.2
49.7	49.8	50.1	50.3	50.4	50.5	50.6	50.6	50.6	50.6	50.6	50.6
51.8	52.1	52.5	52.8	52.9	53.1	53.2	53.2	53.2	53.2	53.2	53.3
53.0	53.3	53.8	54.0	54.2	54.4	54.5	54.5	54.5	54.5	54.5	54.5
56.7	57.0	57.6	57.9	58.0	58.2	58.3	58.3	58.4	58.4	58.4	58.4
60.3	60.7	61.5	62.0	62.2	62.4	62.5	62.5	62.6	62.6	62.6	62.6
64.9	65.5	66.9	67.7	67.9	68.3	68.6	68.6	69.7	68.7	68.7	68.8
66.8	67.4	69.0	69.9	70.2	70.6	70.8	70.9	71.0	71.0	71.0	71.0
70.8	71.5	73.6	75.0	75.5	76.3	76.7	76.8	76.9	76.9	77.0	77.0
73.5	74.4	76.8	78.3	79.0	79.9	80.5	80.7	80.9	80.9	81.0	81.0
75.6	76.5	79.3	81.0	81.8	82.8	83.7	83.8	84.3	84.4	84.5	84.5
75.8	77.7	80.7	82.7	83.4	84.5	85.4	85.6	86.1	86.2	86.2	86.2
77.8	78.8	81.7	84.0	84.9	86.1	87.0	87.3	87.9	88.0	88.1	88.1
78.4	79.4	82.5	84.9	85.9	87.2	88.4	88.7	89.4	89.5	89.7	89.9
78.8	79.9	83.0	85.7	86.6	88.1	89.4	89.7	90.6	90.7	91.0	91.2
79.4	80.6	84.0	86.8	88.1	89.8	91.3	91.7	92.8	93.0	93.3	93.6
79.9	81.1	84.8	87.9	89.3	91.2	92.9	93.3	94.6	94.8	95.4	95.7
80.1	81.3	85.2	88.4	90.1	92.2	94.2	94.8	96.3	96.5	97.2	97.6
80.1	81.3	85.3	88.5	90.3	92.6	94.7	95.4	97.0	97.5	98.4	99.2
80.1	81.3	85.3	88.6	90.4	92.7	94.9	95.5	97.2	97.7	98.8	99.7
80.1	81.3	85.3	88.6	90.4	92.7	94.9	95.5	97.2	97.7	98.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: MAR HOURS: 00-0

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	39.0	39.2	39.5	39.6	40.0	40.0	40.1	40.2	40.2	40.2	40.2	40.2	40.2
GE 2000	42.2	42.4	42.5	42.7	43.2	43.2	43.3	43.4	43.4	43.4	43.4	43.4	43.4
GE 1800	42.5	42.7	42.9	43.0	43.5	43.5	43.7	43.8	43.8	43.8	43.8	43.8	43.8
GE 1600	42.5	42.7	42.9	43.0	43.5	43.5	43.7	43.8	43.8	43.8	43.8	43.8	43.8
GE 1400	42.5	42.7	42.9	43.0	43.5	43.5	43.7	43.8	43.8	43.9	43.9	43.9	43.9
GE 1200	42.6	42.8	43.0	43.1	43.7	43.7	43.8	43.9	43.9	43.9	43.9	43.9	44.0
GE 1000	43.3	44.0	44.2	44.4	45.2	45.2	45.3	45.4	45.4	45.4	45.4	45.4	45.4
GE 900	44.5	44.8	45.1	45.3	46.0	46.0	46.1	46.2	46.2	46.2	46.2	46.2	46.2
GE 800	46.3	46.6	46.8	47.0	48.0	48.0	48.1	48.2	48.2	48.2	48.2	48.2	48.2
GE 700	47.0	47.2	47.5	47.7	48.8	48.8	48.9	49.0	49.0	49.0	49.0	49.0	49.0
GE 600	47.1	47.3	47.6	47.8	48.9	48.9	49.0	49.1	49.1	49.1	49.1	49.1	49.1
GE 500	48.3	48.5	48.8	49.0	50.3	50.3	50.4	50.5	50.5	50.5	50.5	50.5	50.5
GE 450	49.4	49.7	50.0	50.2	51.5	51.5	51.6	51.7	51.7	51.7	51.7	51.7	51.7
GE 400	52.5	52.8	53.1	53.3	54.6	54.6	54.7	54.8	54.8	54.8	54.8	54.8	54.8
GE 3500	53.5	53.9	54.2	54.4	55.7	55.7	55.8	55.9	55.9	55.9	55.9	55.9	55.9
GE 3000	56.5	56.8	57.2	57.6	59.0	59.0	59.4	59.5	59.5	59.5	59.5	59.5	59.5
GE 2500	59.4	59.7	60.1	60.6	62.2	62.2	62.5	62.6	62.6	62.6	62.6	62.6	62.6
GE 2000	63.5	63.9	64.7	65.7	67.7	67.7	68.5	68.9	69.1	69.1	69.1	69.1	69.1
GE 1800	64.4	64.8	65.7	66.7	68.7	68.8	69.8	70.2	70.5	70.5	70.5	70.5	70.5
GE 1500	66.2	66.7	67.5	68.5	70.9	70.9	72.6	73.0	73.4	73.4	73.4	73.4	73.4
GE 1200	67.1	67.5	68.4	69.6	72.4	72.6	74.6	75.2	75.6	75.7	75.7	75.8	76.0
GE 1000	67.5	68.0	68.9	70.2	73.4	73.7	75.7	76.2	76.9	77.2	77.3	77.4	77.7
GE 900	68.1	68.5	69.6	71.1	74.6	74.8	77.0	77.5	78.4	78.7	78.8	78.9	79.1
GE 800	68.5	68.9	70.0	71.5	75.3	75.5	77.6	78.4	79.5	80.1	80.2	80.3	80.6
GE 700	68.7	69.2	70.4	72.2	76.1	76.3	78.7	79.8	81.1	81.8	82.0	82.2	82.6
GE 600	69.1	69.7	71.2	73.2	77.5	78.0	81.0	82.5	84.1	85.1	85.6	85.7	86.1
GE 500	69.7	70.3	72.0	74.3	78.9	79.5	82.5	84.9	86.6	87.8	88.5	88.6	89.1
GE 400	69.9	70.5	72.3	74.7	79.8	80.4	84.0	86.6	88.2	89.6	90.2	90.3	91.0
GE 300	70.1	70.8	72.5	75.1	80.4	81.4	85.4	88.4	90.1	92.0	93.4	93.5	94.4
GE 200	70.1	70.8	72.5	75.1	80.4	81.4	85.9	89.4	91.2	93.4	95.1	95.2	96.1
GE 100	70.1	70.8	72.5	75.1	80.4	81.4	85.9	89.4	91.2	93.4	95.1	95.2	96.1
GE 000	70.1	70.8	72.5	75.1	80.4	81.4	85.9	89.4	91.2	93.4	95.1	95.2	96.1

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
ELEVATION: + 5 MONTH: MAR HOURS: 00-02

CEILING	VISIBILITY IN STATUTE MILES												
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
40.0	40.0	40.0	40.1	40.2	40.2	40.2	40.2	40.2	40.2	40.3	40.3	40.3	40.3
40.7	43.2	43.2	43.3	43.4	43.4	43.4	43.4	43.4	43.4	43.5	43.5	43.5	43.5
41.0	43.5	43.5	43.7	43.8	43.8	43.8	43.8	43.8	43.8	43.9	43.9	43.9	43.9
41.3	43.5	43.5	43.7	43.8	43.8	43.8	43.8	43.8	43.8	43.9	43.9	43.9	43.9
41.6	43.5	43.5	43.7	43.8	43.8	43.8	43.8	43.8	43.8	43.9	43.9	43.9	43.9
41.9	43.7	43.7	43.8	43.9	43.9	43.9	43.9	43.9	43.9	44.0	44.0	44.0	44.0
42.2	45.2	45.2	45.3	45.4	45.4	45.4	45.4	45.4	45.4	45.5	45.5	45.5	45.5
42.5	46.0	46.0	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.3	46.3	46.3	46.3
42.8	48.0	48.0	48.1	48.2	48.2	48.2	48.2	48.2	48.2	48.3	48.3	48.3	48.3
43.1	48.8	48.8	48.9	49.0	49.0	49.0	49.0	49.0	49.0	49.1	49.1	49.1	49.1
43.4	48.9	48.9	49.0	49.1	49.1	49.1	49.1	49.1	49.1	49.2	49.2	49.2	49.2
43.7	50.3	50.3	50.4	50.5	50.5	50.5	50.5	50.5	50.5	50.6	50.6	50.6	50.6
44.0	51.5	51.5	51.6	51.7	51.7	51.7	51.7	51.7	51.7	51.8	51.8	51.8	51.8
44.3	54.6	54.6	54.7	54.8	54.8	54.8	54.8	54.8	54.8	54.9	54.9	54.9	54.9
44.6	55.7	55.7	55.8	55.9	55.9	55.9	55.9	55.9	55.9	56.0	56.0	56.0	56.0
44.9	59.0	59.0	59.4	59.5	59.5	59.5	59.5	59.5	59.5	59.6	59.6	59.6	59.6
45.2	62.2	62.2	62.5	62.6	62.6	62.6	62.6	62.6	62.6	62.7	62.7	62.7	62.7
45.5	67.7	67.7	68.5	68.9	69.1	69.1	69.1	69.1	69.1	69.2	69.2	69.2	69.2
45.8	68.7	68.8	69.5	70.2	70.5	70.5	70.5	70.5	70.5	70.6	70.6	70.6	70.6
46.1	70.8	70.9	72.6	73.0	73.4	73.4	73.4	73.4	73.4	73.5	73.5	73.5	73.5
46.4	72.4	72.6	74.6	75.2	75.6	75.7	75.7	75.8	76.1	76.1	76.1	76.1	76.1
46.7	73.4	73.7	75.7	76.2	76.9	77.2	77.3	77.4	77.7	77.7	77.7	77.7	77.7
47.0	74.6	74.8	77.0	77.5	78.4	78.7	78.8	78.9	79.2	79.2	79.2	79.2	79.2
47.3	75.3	75.5	77.6	78.4	79.5	80.1	80.2	80.3	80.6	80.6	80.6	80.6	80.6
47.6	76.1	76.3	78.7	79.4	81.1	81.8	82.0	82.2	82.5	82.5	82.5	82.5	82.5
47.9	77.5	78.0	81.0	82.5	84.1	85.1	85.6	85.7	86.3	86.3	86.3	87.0	87.0
48.2	78.4	79.5	82.5	84.9	86.6	87.8	88.5	88.6	89.2	89.2	89.2	89.9	89.9
48.5	79.3	80.4	84.0	86.6	88.2	89.6	90.2	90.3	91.0	91.3	91.3	91.9	91.9
48.8	80.4	81.4	85.4	88.4	90.1	92.0	93.4	93.5	94.2	94.7	94.7	95.4	95.4
49.1	80.4	81.4	85.9	89.4	91.2	93.4	95.1	95.2	96.3	97.1	97.7	98.5	98.5
49.4	80.4	81.4	85.7	89.4	91.2	93.4	95.1	95.2	96.3	97.2	97.8	99.4	99.4
49.7	80.4	81.4	85.9	89.4	91.2	93.4	95.1	95.2	96.3	97.2	97.8	100.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
 MONTH: MAR HOURS: 03-05

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 5	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	34.9	35.1	35.2	35.4	35.7	35.7	35.7	35.9	35.9	35.9	36.0	36.0	36.0
GE 20000	37.6	37.7	37.8	38.1	38.7	38.7	38.7	38.9	38.9	38.9	39.0	39.0	39.0
GE 18000	37.6	37.7	37.8	38.1	38.7	38.7	38.7	38.9	38.9	38.9	39.0	39.0	39.0
GE 16000	37.8	38.0	38.1	38.3	38.9	38.9	38.9	39.1	39.1	39.1	39.2	39.2	39.2
GE 14000	37.8	38.0	38.1	38.3	38.9	38.9	38.9	39.1	39.1	39.1	39.2	39.2	39.2
GE 12000	38.5	38.6	38.7	38.9	39.6	39.6	39.6	39.8	39.8	39.8	39.9	39.9	39.9
GE 10000	39.8	39.9	40.0	40.2	41.0	41.0	41.0	41.2	41.2	41.2	41.3	41.3	41.3
GE 9000	40.1	40.2	40.3	40.5	41.3	41.3	41.3	41.5	41.5	41.5	41.6	41.6	41.6
GE 8000	41.3	41.4	41.5	41.7	42.5	42.5	42.5	42.7	42.7	42.7	42.8	42.8	42.8
GE 7000	43.0	43.1	43.2	43.4	44.3	44.3	44.3	44.5	44.5	44.5	44.6	44.6	44.6
GE 6000	43.7	43.8	43.9	44.1	44.9	44.9	44.9	45.2	45.2	45.2	45.3	45.3	45.3
GE 5000	45.3	45.4	45.5	45.8	46.9	46.9	47.1	47.3	47.3	47.3	47.4	47.4	47.4
GE 4500	45.8	45.9	46.0	46.5	47.6	47.6	47.8	48.1	48.1	48.1	48.2	48.2	48.2
GE 4000	48.7	48.9	49.1	49.5	51.1	51.1	51.3	51.5	51.5	51.5	51.6	51.6	51.6
GE 3500	49.7	50.0	50.3	50.8	52.3	52.3	52.5	52.7	52.7	52.7	52.8	52.8	52.8
GE 3000	51.9	52.3	52.7	53.1	54.8	54.8	55.1	55.3	55.3	55.3	55.4	55.4	55.4
GE 2500	54.3	54.4	54.9	55.3	56.5	56.6	56.9	57.4	57.4	57.4	57.5	57.5	57.5
GE 2000	58.7	59.2	59.9	60.5	63.4	63.8	64.1	64.9	65.2	65.4	65.5	65.5	65.5
GE 1800	59.7	60.2	61.1	61.7	64.9	64.9	65.3	66.1	66.3	66.6	66.7	66.7	66.7
GE 1500	62.4	63.3	64.4	65.1	68.7	69.0	69.5	70.4	70.6	71.0	71.1	71.1	71.1
GE 1200	64.4	65.1	65.8	67.1	70.8	71.1	71.7	72.7	72.9	73.3	73.8	73.8	73.8
GE 1000	65.5	66.2	67.5	68.4	72.2	72.6	73.4	74.5	75.2	75.6	76.2	76.2	76.2
GE 900	65.2	67.0	68.5	69.2	73.4	73.9	75.2	76.6	77.2	77.8	78.6	78.6	78.6
GE 800	65.9	67.7	69.2	70.0	74.2	74.6	75.9	77.5	78.7	79.4	80.1	80.1	80.1
GE 700	67.3	68.2	69.8	70.9	75.3	75.8	77.2	79.0	80.2	81.2	81.9	81.9	81.9
GE 600	68.0	68.8	70.4	71.5	76.2	76.8	78.5	80.5	82.0	83.0	84.1	84.1	84.4
GE 500	68.3	69.1	70.8	71.9	76.9	77.8	79.8	82.3	83.9	84.9	86.7	86.7	87.1
GE 400	68.6	69.5	71.3	72.5	77.5	78.8	81.1	84.0	85.5	86.7	88.9	89.0	89.6
GE 300	68.9	69.9	71.8	73.1	78.2	79.2	82.9	86.6	88.6	89.9	92.4	92.5	93.0
GE 200	68.9	69.9	71.8	73.1	78.4	80.2	83.3	87.4	89.7	91.2	94.1	94.6	95.9
GE 100	69.0	70.0	72.0	73.3	78.6	80.4	83.5	87.6	89.9	91.4	94.3	94.8	96.3
GE 000	69.0	70.0	72.0	73.3	78.6	80.4	83.5	87.6	89.9	91.4	94.3	94.8	96.3

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

W. K. I. SAWYER AFB MI
5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 03-05

VISIBILITY IN STATUTE MILES												
3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
35.7	35.7	35.7	35.9	35.9	35.9	36.0	36.0	36.0	36.0	36.0	36.0	36.0
38.7	38.7	38.7	38.9	38.9	38.9	39.0	39.0	39.0	39.0	39.0	39.0	39.0
38.7	38.7	38.7	38.9	38.9	38.9	39.0	39.0	39.0	39.0	39.0	39.0	39.0
38.9	38.9	38.9	39.1	39.1	39.1	39.2	39.2	39.2	39.2	39.2	39.2	39.2
38.9	38.9	38.9	39.1	39.1	39.1	39.2	39.2	39.2	39.2	39.2	39.2	39.2
39.6	39.6	39.6	39.8	39.8	39.8	39.9	39.9	39.9	39.9	39.9	39.9	39.9
41.0	41.0	41.0	41.2	41.2	41.2	41.3	41.3	41.3	41.3	41.3	41.3	41.3
41.3	41.3	41.3	41.5	41.5	41.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6
42.5	42.5	42.5	42.7	42.7	42.7	42.8	42.8	42.8	42.8	42.8	42.8	42.8
44.3	44.3	44.3	44.5	44.5	44.5	44.6	44.6	44.6	44.6	44.6	44.6	44.6
44.9	44.9	44.9	45.2	45.2	45.2	45.3	45.3	45.3	45.3	45.3	45.3	45.3
46.9	46.9	47.1	47.3	47.3	47.3	47.4	47.4	47.4	47.4	47.4	47.4	47.4
47.6	47.6	47.8	48.1	48.1	48.1	48.2	48.2	48.2	48.2	48.2	48.2	48.2
51.1	51.1	51.3	51.5	51.5	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6
52.3	52.3	52.5	52.7	52.7	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8
54.8	54.8	55.1	55.3	55.3	55.3	55.4	55.4	55.4	55.4	55.4	55.4	55.4
58.6	58.6	58.9	59.4	59.4	59.4	59.5	59.5	59.5	59.5	59.5	59.5	59.5
63.4	63.4	64.1	64.9	65.2	65.4	65.5	65.5	65.5	65.5	65.5	65.5	65.5
64.9	64.9	65.3	66.1	66.3	66.6	66.7	66.7	66.7	66.7	66.7	66.7	66.7
69.7	69.0	69.5	70.4	70.6	71.0	71.1	71.1	71.1	71.1	71.1	71.1	71.1
73.8	71.1	71.7	72.7	72.9	73.3	73.8	73.8	73.8	74.1	74.1	74.1	74.1
77.2	77.6	73.4	74.5	75.2	75.6	76.2	76.2	76.2	76.6	76.6	76.6	76.6
73.4	73.9	75.2	76.6	77.2	77.8	78.6	78.6	78.6	78.9	78.9	78.9	78.9
74.2	74.6	75.9	77.5	78.7	79.4	80.1	80.1	80.1	80.4	80.4	80.4	80.4
75.4	75.4	77.2	79.0	80.2	81.2	81.9	81.9	81.9	82.3	82.3	82.3	82.3
76.2	76.8	73.5	80.5	82.0	83.0	84.1	84.1	84.4	84.7	84.7	84.7	85.4
76.7	77.8	73.8	82.3	83.9	84.9	86.7	86.7	87.1	87.4	87.4	87.4	89.1
77.6	78.8	81.1	84.0	85.6	86.7	88.9	89.0	89.6	89.9	89.9	89.9	90.8
73.2	80.0	82.9	86.6	88.6	89.9	92.4	92.5	93.0	93.3	93.3	93.3	94.2
78.4	80.2	83.3	87.4	89.7	91.2	94.1	94.6	95.9	96.5	96.9	96.9	97.8
78.9	80.4	83.5	87.6	89.9	91.4	94.3	94.8	96.3	97.1	97.8	97.8	99.7
78.6	80.4	83.5	87.6	89.9	91.4	94.3	94.8	96.3	97.1	98.1	98.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: MAR HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	33.5	33.8	34.1	34.3	34.5	34.6	34.7	35.3	35.4	35.4	35.5	35.5	35.6	
GE 20000	36.2	36.5	37.0	37.2	37.5	37.5	37.8	38.4	38.5	38.5	38.6	38.6	38.7	
GE 18000	36.3	36.6	37.1	37.3	37.5	37.7	38.0	38.5	38.6	38.6	38.7	38.7	38.8	
GE 16000	36.5	36.7	37.2	37.4	37.7	37.8	38.1	38.6	38.7	38.7	38.8	38.8	38.9	
GE 14000	36.9	37.1	37.6	37.8	38.2	38.3	38.5	39.0	39.1	39.1	39.2	39.2	39.4	
GE 12000	38.2	38.4	38.9	39.2	39.5	39.7	40.0	40.5	40.5	40.6	40.6	40.8	40.9	
GE 10000	39.8	40.0	40.5	40.9	41.2	41.3	41.6	42.2	42.3	42.3	42.4	42.4	42.5	
GE 9000	40.0	40.2	40.3	41.1	41.4	41.5	41.8	42.4	42.5	42.5	42.6	42.6	42.7	
GE 8000	41.3	42.0	42.5	42.9	43.2	43.3	43.7	44.2	44.3	44.3	44.4	44.4	44.5	
GE 7000	43.1	43.3	43.9	44.2	44.5	44.6	44.9	45.5	45.6	45.6	45.7	45.7	45.8	
GE 6000	44.1	44.3	45.1	45.4	45.7	45.8	46.1	46.7	46.8	46.9	46.9	46.9	47.0	
GE 5000	46.0	46.2	47.2	47.5	47.8	48.0	48.4	48.9	49.0	49.0	49.1	49.1	49.2	
GE 4500	46.2	46.8	47.5	48.0	48.5	48.6	49.1	49.7	49.8	49.8	49.9	49.9	50.0	
GE 4000	47.5	48.2	49.0	49.4	50.0	50.1	50.6	51.3	51.4	51.5	51.6	51.6	51.7	
GE 3500	48.5	49.1	50.0	50.3	51.0	51.2	51.7	52.4	52.5	52.6	52.7	52.7	52.8	
GE 3000	50.0	50.5	51.5	51.8	53.0	53.3	54.0	54.6	54.7	54.8	54.9	54.9	55.1	
GE 2500	51.4	52.2	53.2	53.7	55.1	55.4	56.1	56.8	57.0	57.1	57.2	57.2	57.3	
GE 2000	55.1	55.9	57.3	57.8	59.7	60.1	61.2	61.9	62.5	62.7	63.0	63.0	63.1	
GE 1800	56.7	57.5	58.9	59.5	61.3	61.7	62.9	63.7	64.2	64.4	64.7	64.7	64.8	
GE 1500	59.8	60.5	62.2	62.8	65.5	65.9	67.6	68.5	69.0	69.4	69.9	69.9	70.0	
GE 1200	62.0	62.9	64.6	65.3	68.3	68.8	70.6	71.6	72.4	72.7	73.4	73.4	74.0	
GE 1000	63.1	64.1	65.8	66.5	69.6	70.2	72.5	73.5	74.4	75.1	75.8	75.8	76.3	
GE 900	63.8	64.7	66.7	67.4	70.8	71.4	73.9	74.9	75.8	76.6	77.4	77.4	78.0	
GE 800	64.1	65.1	67.1	67.8	71.5	72.3	74.9	75.3	77.4	78.6	79.6	79.8	80.3	
GE 700	64.7	65.7	67.7	68.5	72.3	73.0	76.2	76.0	79.1	80.4	81.7	81.7	82.4	
GE 600	65.1	66.0	68.3	69.0	72.9	73.8	77.2	79.2	80.5	82.2	83.9	83.9	85.2	
GE 500	65.6	66.7	69.0	69.8	73.9	74.7	78.5	80.5	82.5	84.5	86.8	86.9	88.3	
GE 400	65.8	66.9	69.2	70.0	74.1	75.1	79.0	81.6	83.3	85.4	88.0	88.3	89.9	
GE 300	65.8	67.0	69.5	70.2	74.4	75.4	79.9	82.9	85.6	88.0	90.9	91.2	93.3	
GE 200	65.8	67.0	69.5	70.2	74.7	75.8	80.4	84.4	87.3	90.3	93.4	93.8	96.1	
GE 100	65.8	67.0	69.5	70.2	74.7	75.8	80.4	84.4	87.3	90.3	93.4	93.8	96.1	
GE 000	65.8	67.0	69.5	70.2	74.7	75.8	80.4	84.4	87.3	90.3	93.4	93.8	96.1	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

K. I. SAWYER AFB MI

PERIOD OF RECORD: AUG 78 - JUL 88

MONTH: MAR HOURS: 06-08

VISIBILITY IN STATUTE MILES											
	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
35.5	34.6	34.7	35.3	35.4	35.4	35.5	35.5	35.6	35.6	35.6	35.6
36.5	37.5	37.2	38.4	38.5	38.5	38.6	38.6	38.7	38.7	38.7	38.7
37.5	37.7	38.0	38.5	38.6	38.6	38.7	38.7	38.8	38.8	38.8	38.8
38.5	37.8	38.1	38.6	38.7	38.7	38.8	38.8	38.9	38.9	38.9	38.9
39.5	38.3	38.5	39.0	39.1	39.1	39.2	39.2	39.4	39.4	39.4	39.4
40.5	39.7	40.0	40.5	40.6	40.6	40.8	40.8	40.9	40.9	40.9	40.9
41.5	41.3	41.6	42.2	42.3	42.3	42.4	42.4	42.5	42.5	42.5	42.5
42.5	41.5	41.8	42.4	42.5	42.5	42.6	42.6	42.7	42.7	42.7	42.7
43.5	43.3	43.7	44.2	44.3	44.3	44.4	44.4	44.5	44.5	44.5	44.5
44.5	44.6	44.9	45.5	45.6	45.6	45.7	45.7	45.8	45.8	45.8	45.8
45.5	45.2	45.1	46.7	46.8	46.8	46.9	46.9	47.0	47.0	47.0	47.0
46.5	48.0	48.4	48.9	49.0	49.0	49.1	49.1	49.2	49.2	49.2	49.2
47.5	48.6	49.1	49.7	49.8	49.8	49.9	49.9	50.0	50.0	50.0	50.0
48.5	50.1	50.6	51.3	51.4	51.5	51.6	51.6	51.7	51.7	51.7	51.7
49.5	51.2	51.7	52.4	52.5	52.6	52.7	52.7	52.8	52.8	52.8	52.8
50.5	53.3	54.0	54.6	54.7	54.8	54.9	54.9	55.1	55.1	55.1	55.1
51.5	55.4	56.1	56.3	57.0	57.1	57.2	57.2	57.3	57.3	57.3	57.3
52.5	60.1	61.2	61.9	62.5	62.7	63.0	63.0	63.1	63.1	63.1	63.1
53.5	61.7	62.9	63.7	64.2	64.4	64.7	64.7	64.8	64.8	64.8	64.8
54.5	65.9	67.6	68.5	69.0	69.4	69.9	69.9	70.0	70.0	70.0	70.0
55.5	68.8	70.6	71.6	72.4	72.7	73.4	73.4	74.0	74.1	74.1	74.1
56.5	70.2	72.5	73.5	74.4	75.1	75.8	75.8	76.3	76.5	76.5	76.5
57.5	71.4	73.9	74.9	75.8	76.6	77.4	77.4	78.0	78.1	78.1	78.1
58.5	72.3	74.9	75.3	77.4	78.6	79.8	79.8	80.3	80.4	80.4	80.6
59.5	73.0	75.2	78.0	79.1	80.4	81.7	81.7	82.4	82.5	82.5	82.7
60.5	73.3	77.2	79.2	80.5	82.2	83.9	83.9	85.2	85.3	85.3	85.7
61.5	74.7	74.5	80.8	82.5	84.5	86.8	86.9	88.3	88.4	88.5	88.9
62.5	75.1	79.0	81.6	83.3	85.4	88.0	88.3	89.9	90.2	90.3	91.1
63.5	75.4	79.9	82.9	85.6	88.0	90.9	91.2	93.3	93.8	93.9	94.7
64.5	75.8	80.4	84.4	87.3	90.3	93.4	93.8	96.1	97.0	97.4	98.4
65.5	75.8	80.4	84.4	87.3	90.3	93.4	93.8	96.1	97.3	98.2	99.9
66.5	75.4	80.4	84.4	87.3	90.3	93.4	93.8	96.1	97.3	98.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AL
MONTH: MAR HOURS: C

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GF 1 1/2	GE 1 1/4	GE 1	GF 3/4	GE 5/8
NO CEIL	31.3	31.8	32.3	32.5	33.0	33.1	33.1	33.1	33.1	33.1	33.1	33.1
GE 20000	34.7	35.3	35.9	36.1	36.7	36.8	36.8	36.8	36.8	36.8	36.8	36.8
GE 18000	35.3	35.3	37.0	37.2	37.7	37.8	37.8	37.8	37.8	37.8	37.8	37.8
GE 16000	36.0	36.6	37.2	37.4	38.0	38.1	38.1	38.1	38.1	38.1	38.1	38.1
GE 14000	36.5	37.0	37.5	37.8	38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5
GE 12000	37.6	38.2	38.6	39.0	39.7	39.8	39.8	39.8	39.8	39.8	39.8	39.8
GE 10000	40.0	40.6	41.4	41.6	42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4
GE 9000	40.0	40.6	41.4	41.6	42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4
GE 8000	42.6	43.2	44.0	44.3	44.9	45.1	45.2	45.2	45.2	45.2	45.2	45.2
GE 7000	44.2	44.8	45.8	46.2	46.9	47.0	47.1	47.1	47.1	47.1	47.1	47.1
GE 6000	44.9	45.6	46.6	47.0	47.6	47.8	48.0	48.0	48.0	48.0	48.0	48.0
GE 5000	46.5	47.1	48.1	48.6	49.4	49.6	49.7	49.7	49.7	49.7	49.7	49.7
GF 4500	46.7	47.4	48.4	48.9	49.8	50.0	50.1	50.1	50.1	50.1	50.1	50.1
GE 4000	47.2	48.1	49.1	49.8	50.9	51.1	51.2	51.3	51.3	51.3	51.3	51.3
GE 3500	47.7	48.6	49.8	50.4	51.5	51.7	51.8	51.9	51.9	51.9	51.9	51.9
GE 3000	48.6	49.5	50.6	51.3	52.0	52.8	53.0	53.2	53.2	53.3	53.4	53.4
GE 2500	50.0	50.9	52.3	53.0	54.4	54.7	55.2	55.5	55.5	55.6	55.8	55.8
GE 2000	53.7	54.6	56.1	57.2	58.6	58.9	59.6	60.1	60.2	60.4	60.6	60.6
GE 1800	55.5	56.5	58.2	59.2	60.8	61.2	61.9	62.5	62.6	62.9	63.1	63.1
GE 1500	58.2	59.2	61.1	62.4	64.1	64.7	65.8	66.7	66.8	67.2	67.5	67.5
GE 1200	61.0	62.2	64.0	65.4	67.1	68.0	69.2	70.4	70.8	71.7	72.6	72.7
GF 1000	61.9	63.2	65.1	66.5	68.4	69.2	70.8	72.2	72.7	73.9	75.1	75.2
GE 900	62.5	64.0	65.9	67.4	69.4	70.4	71.9	73.7	74.3	75.5	77.0	77.1
GE 800	63.0	64.5	66.9	68.5	70.8	72.2	74.1	76.0	76.9	78.2	80.1	80.3
GE 700	63.4	64.9	67.3	68.9	71.3	72.7	74.6	76.6	77.5	79.2	81.4	81.8
GE 600	63.8	65.3	67.8	69.7	72.4	74.3	76.5	78.7	79.9	81.8	84.6	85.1
GE 500	64.0	65.5	68.2	70.0	72.7	74.6	77.6	80.9	82.5	85.2	88.1	88.7
GE 400	64.0	65.5	68.2	70.0	72.8	74.7	78.0	81.7	83.3	86.2	89.6	90.4
GE 300	64.0	65.5	68.3	70.1	73.0	75.1	78.4	82.3	84.4	87.7	91.4	92.4
GE 200	64.0	65.5	68.3	70.1	73.0	75.1	78.4	82.4	84.6	88.4	92.4	93.5
GE 100	64.0	65.5	68.3	70.1	73.0	75.1	78.4	82.4	84.6	88.4	92.6	93.8
GE 000	64.0	65.5	68.3	70.1	73.0	75.1	78.4	82.4	84.6	88.4	92.6	93.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 09-11

VISIBILITY IN STATUTE MILES

GC	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0	
33.0	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1
36.7	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
37.7	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8
38.0	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1
38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
39.7	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
42.3	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4	42.4
44.9	45.1	45.2	45.2	45.2	45.2	45.2	45.2	45.2	45.2	45.2	45.2	45.2
46.9	47.0	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
47.6	47.8	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0
49.4	49.6	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7
49.8	50.0	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1	50.1
50.9	51.1	51.2	51.3	51.3	51.3	51.3	51.3	51.3	51.5	51.5	51.5	51.5
51.5	51.7	51.8	51.9	51.9	51.9	51.9	51.9	51.9	52.2	52.3	52.3	52.3
52.6	52.8	53.0	53.2	53.2	53.3	53.4	53.4	53.7	53.8	53.8	53.8	53.8
54.4	54.7	55.2	55.5	55.5	55.6	55.8	55.8	56.0	56.1	56.1	56.1	56.1
58.6	58.9	59.6	60.1	60.2	60.4	60.6	60.6	61.0	61.1	61.1	61.1	61.1
60.8	61.2	61.9	62.5	62.6	62.9	63.1	63.1	63.5	63.7	63.7	63.7	63.7
64.1	64.7	65.8	66.7	66.8	67.2	67.5	67.5	68.0	68.1	68.1	68.1	68.1
67.1	68.0	69.2	70.4	70.8	71.7	72.6	72.7	73.3	73.8	74.0	74.0	74.0
63.4	69.2	70.8	72.2	72.7	73.9	75.1	75.2	75.8	76.2	76.5	76.5	76.5
69.4	70.4	71.9	73.7	74.3	75.5	77.0	77.1	77.7	78.2	78.4	78.4	78.4
70.8	72.2	74.1	76.0	76.9	78.2	80.1	80.3	81.1	81.5	81.8	82.2	82.2
71.3	72.7	74.6	76.6	77.5	79.2	81.4	81.8	82.7	83.1	83.4	83.8	83.8
72.4	74.3	76.5	78.7	79.9	81.8	84.6	85.1	85.9	86.3	87.2	87.5	87.5
72.7	74.6	77.6	80.9	82.5	85.2	88.1	88.7	89.7	90.1	91.0	91.4	91.4
72.8	74.7	79.0	81.7	83.3	86.2	89.6	90.4	91.4	92.6	93.5	94.1	94.1
73.0	75.1	78.4	82.3	84.4	87.7	91.4	92.4	93.4	94.6	96.0	96.8	96.8
73.0	75.1	78.4	82.4	84.6	88.4	92.4	93.5	94.6	96.2	97.7	98.8	98.8
73.0	75.1	78.4	82.4	84.6	88.4	92.6	93.8	95.1	96.7	98.3	99.7	99.7
73.0	75.1	78.4	82.4	84.6	88.4	92.6	93.8	95.1	96.7	98.3	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAR HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	36.1	36.5	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6
GE 20000	40.6	41.1	41.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
GE 18000	41.5	41.9	42.4	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
GE 16000	41.7	42.2	42.6	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
GE 14000	42.5	42.9	43.3	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
GE 12000	43.0	43.4	43.9	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0
GE 10000	45.1	45.5	45.9	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
GE 9000	45.3	45.7	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
GE 8000	47.5	48.0	48.4	48.5	48.8	48.8	48.8	48.8	48.9	48.9	48.9	48.9	48.9
GE 7000	48.5	48.9	49.4	49.6	49.8	49.8	49.8	49.8	49.9	49.9	49.9	49.9	49.9
GE 6000	48.7	49.1	49.6	49.3	50.1	50.1	50.1	50.1	50.2	50.2	50.2	50.2	50.2
GE 5000	48.9	49.5	49.9	50.1	50.4	50.4	50.4	50.4	50.5	50.5	50.5	50.5	50.5
GE 4500	49.5	50.0	50.4	50.6	51.0	51.0	51.0	51.0	51.1	51.1	51.1	51.1	51.1
GE 4000	49.9	50.4	50.9	51.1	51.5	51.5	51.5	51.6	51.7	51.8	51.9	51.9	52.0
GE 3500	51.1	51.6	52.0	52.3	52.9	52.9	53.1	53.1	53.2	53.3	53.4	53.4	53.5
GE 3000	52.3	52.8	53.3	53.5	54.2	54.2	54.5	54.5	54.6	54.7	54.8	54.8	54.9
GE 2500	55.1	55.6	56.2	56.6	57.3	57.3	57.8	58.1	58.2	58.4	58.5	58.5	58.6
GE 2000	58.7	59.2	60.5	61.2	62.4	62.6	63.5	63.8	64.0	64.2	64.4	64.4	64.5
GE 1800	60.0	60.6	62.0	62.7	63.9	64.1	65.4	65.6	66.0	66.2	66.6	66.6	66.7
GE 1500	63.2	64.2	65.9	66.3	68.1	68.3	69.6	69.8	70.4	70.8	71.2	71.2	71.4
GE 1200	65.1	65.3	66.7	70.1	71.5	71.8	73.2	73.4	74.3	74.7	75.4	75.6	75.8
GE 1000	65.7	67.1	69.3	71.2	72.7	73.4	75.1	75.5	76.3	76.9	78.0	78.2	78.7
GE 900	65.7	68.1	71.3	72.9	74.5	75.4	77.3	77.7	78.7	79.2	80.4	80.6	81.4
GE 800	67.0	68.4	71.8	73.4	75.3	76.1	78.4	78.8	80.0	80.5	82.3	82.6	83.3
GE 700	67.4	68.8	72.4	74.4	76.5	77.4	79.8	80.4	81.6	82.4	84.1	84.4	85.3
GE 600	67.6	69.0	72.6	74.5	76.8	78.0	80.3	81.4	82.3	83.7	85.6	85.9	87.2
GE 500	67.3	69.5	73.2	75.3	77.6	78.8	81.6	83.2	84.9	86.1	88.2	88.5	89.9
GE 400	67.8	69.7	73.4	75.5	78.1	79.2	82.3	84.1	85.8	87.2	89.9	90.4	91.9
GE 300	67.3	69.7	73.5	75.5	78.4	79.7	82.3	84.7	87.0	88.7	91.4	92.0	93.7
GE 200	67.3	69.7	73.5	75.6	78.4	79.7	82.9	85.3	87.8	89.8	92.8	93.4	95.3
GE 100	67.3	69.7	73.5	75.6	78.4	79.7	82.9	85.3	87.8	89.8	92.9	93.5	95.6

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 84
MONTH: MAR HOURS: 12-14

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6	36.6
41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0	44.0
46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
48.8	48.8	48.8	48.8	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
49.8	49.8	49.8	49.8	49.9	49.9	49.9	49.9	49.9	49.9	49.9	49.9
50.1	50.1	50.1	50.1	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
50.4	50.4	50.4	50.4	50.5	50.5	50.5	50.5	50.5	50.5	50.5	50.5
51.0	51.0	51.0	51.0	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1
51.5	51.5	51.5	51.6	51.7	51.8	51.9	51.9	52.0	52.0	52.0	52.0
52.9	52.9	53.1	53.1	53.2	53.3	53.4	53.4	53.5	53.5	53.5	53.5
54.2	54.2	54.5	54.5	54.6	54.7	54.8	54.8	54.9	54.9	54.9	54.9
57.3	57.3	57.8	58.1	58.2	58.4	58.5	58.5	58.6	58.6	58.6	58.6
52.4	62.6	63.5	63.8	64.0	64.2	64.4	64.4	64.5	64.6	64.6	64.6
53.9	54.1	65.4	65.6	66.0	66.2	66.6	66.6	66.7	66.8	66.8	66.8
59.1	68.3	69.6	69.8	70.4	70.8	71.2	71.2	71.4	71.8	71.8	71.8
71.5	71.8	73.2	73.4	74.3	74.7	75.4	75.6	75.8	76.3	76.3	76.3
72.7	73.4	75.1	75.5	76.3	76.9	78.0	78.2	78.7	79.4	79.4	79.4
74.5	75.4	77.3	77.7	78.7	79.2	80.4	80.6	81.4	82.0	82.2	82.2
75.3	76.1	78.4	78.8	80.0	80.5	82.3	82.6	83.3	84.0	84.2	84.3
76.5	77.4	79.8	80.4	81.6	82.4	84.1	84.4	85.3	86.0	86.2	86.6
76.8	78.0	80.3	81.4	82.8	83.7	85.6	85.9	87.2	88.1	88.5	88.8
77.6	78.8	81.6	83.2	84.9	86.1	88.2	88.5	89.9	90.9	91.7	92.2
79.1	79.2	82.3	84.1	85.8	87.2	89.9	90.4	91.9	93.2	94.4	94.8
79.4	79.7	82.8	84.7	87.0	88.7	91.4	92.0	93.7	95.3	96.6	97.0
79.4	79.7	82.9	85.3	87.8	89.8	92.8	93.4	95.3	97.0	98.5	99.2
79.4	79.7	82.9	85.3	87.8	89.8	92.9	93.5	95.6	97.4	98.9	99.7
79.4	79.7	82.9	85.3	87.8	89.8	92.9	93.5	95.6	97.4	98.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: MAR HOURS

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	38.5	38.5	38.7	38.8	38.9	38.8	38.8	38.9	38.9	38.9	38.9	38.9
GE 20000	43.0	43.1	43.3	43.4	43.4	43.4	43.4	43.5	43.5	43.5	43.5	43.5
GE 19000	43.8	44.0	44.4	44.5	44.5	44.5	44.5	44.6	44.6	44.6	44.6	44.6
GE 18000	44.0	44.2	44.6	44.7	44.7	44.7	44.7	44.8	44.8	44.8	44.8	44.8
GE 14000	44.5	44.7	45.2	45.3	45.3	45.3	45.3	45.4	45.4	45.4	45.4	45.4
GE 12000	45.3	45.5	45.9	46.0	46.0	46.0	46.0	46.1	46.1	46.1	46.1	46.1
GE 10000	47.2	47.4	48.0	48.1	48.1	48.1	48.1	48.2	48.2	48.2	48.2	48.2
GE 9000	47.7	48.0	48.5	48.6	48.6	48.6	48.6	48.7	48.7	48.7	48.7	48.7
GE 8000	50.0	50.2	50.8	50.9	50.9	50.9	50.9	51.0	51.1	51.2	51.2	51.2
GE 7000	51.3	51.5	52.0	52.2	52.2	52.2	52.2	52.3	52.4	52.5	52.5	52.5
GE 6000	51.8	52.0	52.6	52.7	52.9	52.9	52.9	53.0	53.1	53.2	53.2	53.2
GE 5000	52.3	52.6	53.1	53.3	53.4	53.5	53.7	53.8	53.9	54.0	54.0	54.0
GE 4500	52.9	53.2	53.8	54.0	54.1	54.2	54.3	54.4	54.6	54.7	54.7	54.7
GE 4000	54.1	54.5	55.3	55.5	55.6	55.7	55.8	56.1	56.3	56.5	56.6	56.6
GE 3500	55.7	56.1	56.9	57.1	57.3	57.4	57.5	57.8	58.2	58.3	58.4	58.4
GE 3000	57.3	57.7	58.5	58.7	58.9	59.0	59.1	59.5	59.8	59.9	60.0	60.0
GE 2500	59.7	60.2	61.3	61.7	62.2	62.3	62.4	62.7	63.1	63.2	63.3	63.3
GE 2000	63.3	63.9	65.5	65.0	65.3	67.1	67.3	67.6	68.3	68.4	68.5	68.5
GE 1800	64.1	64.7	66.6	67.1	67.3	68.2	68.5	68.9	69.6	69.7	69.8	69.8
GE 1500	67.0	67.7	69.9	70.5	71.4	71.9	72.5	73.1	73.8	74.1	74.6	74.6
GE 1200	68.9	70.0	72.5	73.7	75.4	76.0	77.2	78.2	78.9	79.5	80.1	80.1
GE 1000	69.5	70.6	73.3	74.5	76.2	76.9	78.2	79.1	79.9	80.6	81.3	81.3
GE 900	70.0	71.2	73.9	75.1	75.9	77.5	78.9	80.1	81.1	81.8	82.5	82.5
GE 800	70.2	71.4	74.5	75.8	77.7	78.5	80.1	81.5	82.3	83.9	84.6	84.6
GE 700	70.2	71.5	74.9	76.5	78.5	79.2	81.1	82.5	83.9	84.9	85.7	85.7
GE 600	70.5	71.8	75.3	77.1	79.4	80.2	82.2	83.3	85.5	86.7	87.5	87.5
GE 500	71.0	72.5	76.2	78.2	80.9	81.8	84.1	86.1	88.2	89.7	91.0	91.0
GE 400	71.0	72.6	76.5	78.4	81.1	82.3	84.6	86.8	88.3	90.4	91.9	92.0
GE 300	71.0	72.6	76.5	78.4	81.3	82.5	85.1	87.2	89.4	91.0	93.1	94.0
GE 200	71.0	72.6	76.5	78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.0
GE 100	71.0	72.6	76.5	78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.0
GE 000	71.0	72.6	76.5	78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 15-17

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
38.9	38.9	38.8	38.8	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
43.4	43.4	43.4	43.4	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5	43.5
44.5	44.5	44.5	44.5	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6	44.6
44.7	44.7	44.7	44.7	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
45.3	45.3	45.3	45.3	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.4
46.0	46.0	46.0	46.0	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1
48.1	48.1	48.1	48.1	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2	48.2
48.6	48.6	48.6	48.6	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7
50.9	50.9	50.9	50.9	51.0	51.1	51.2	51.2	51.2	51.3	51.3	51.3	51.3
52.2	52.2	52.2	52.2	52.3	52.4	52.5	52.5	52.5	52.6	52.6	52.6	52.6
52.7	52.8	52.9	52.9	53.0	53.1	53.2	53.2	53.2	53.3	53.3	53.3	53.3
53.3	53.4	53.5	53.7	53.8	53.9	54.0	54.0	54.0	54.1	54.1	54.1	54.1
54.0	54.1	54.2	54.3	54.4	54.6	54.7	54.7	54.7	54.8	54.8	54.8	54.8
55.5	55.6	55.7	55.8	56.1	56.3	56.5	56.6	56.6	56.7	56.7	56.7	56.7
57.1	57.3	57.4	57.5	57.8	58.2	58.3	58.4	58.4	58.5	58.5	58.5	58.5
58.7	58.9	59.0	59.1	59.5	59.8	59.9	60.0	60.0	60.1	60.1	60.1	60.1
61.7	62.2	62.3	62.4	62.7	63.1	63.2	63.3	63.3	63.4	63.7	63.7	63.7
65.0	65.3	67.1	67.3	67.6	68.3	68.4	68.5	68.5	68.6	68.8	68.8	68.8
67.1	67.3	68.2	68.5	68.9	69.6	69.7	69.8	69.8	69.9	70.1	70.1	70.1
70.5	71.4	71.9	72.5	73.1	73.8	74.1	74.6	74.6	74.7	75.3	75.3	75.3
73.7	75.4	76.0	77.2	78.2	78.9	79.5	80.1	80.1	80.2	80.8	80.8	80.8
74.5	76.2	76.9	78.2	79.1	79.9	80.6	81.3	81.3	81.5	82.0	82.0	82.0
75.1	75.9	77.5	78.9	80.1	81.1	81.8	82.5	82.6	82.8	83.4	83.7	83.7
75.8	77.7	78.5	80.1	81.5	82.8	83.9	84.6	84.7	85.1	85.8	86.1	86.1
76.5	78.5	79.2	81.1	82.5	83.9	84.9	85.7	85.8	86.1	86.9	87.2	87.3
77.1	79.4	80.2	82.2	83.3	85.5	86.7	87.5	87.8	88.4	89.1	89.7	89.8
78.2	80.9	81.3	84.1	86.1	88.2	89.7	91.0	91.3	91.9	92.7	93.4	93.8
78.4	81.1	82.3	84.6	86.8	88.3	90.4	91.9	92.5	93.4	94.4	95.4	95.7
78.4	81.3	82.5	85.1	87.2	89.4	91.0	93.1	94.0	95.1	96.2	97.3	97.7
78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.5	95.9	97.2	98.7	99.5
78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.5	95.9	97.3	98.8	99.7
78.4	81.3	82.5	85.1	87.2	89.4	91.3	93.7	94.5	95.9	97.3	98.8	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: A
 LST TO UTC: + 5 MONTH: MAR HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	41.0	41.0	41.0	41.0	41.0	41.1	41.2	41.2	41.2	41.2	41.2	41.2
GF 20000	46.3	46.3	46.3	46.3	46.5	46.6	46.8	46.9	46.9	46.9	46.9	46.9
GE 18000	47.4	47.4	47.4	47.5	47.6	47.7	48.0	48.1	48.1	48.1	48.1	48.1
GF 16000	47.4	47.4	47.4	47.5	47.6	47.7	48.0	48.1	48.1	48.1	48.1	48.1
GE 14000	47.6	47.6	47.6	47.7	47.8	48.0	48.2	48.3	48.3	48.3	48.3	48.3
GE 12000	48.2	48.2	48.2	48.3	48.4	48.5	48.7	48.8	48.8	48.8	48.8	48.8
GF 10000	50.0	50.0	50.2	50.6	50.8	50.9	51.1	51.2	51.2	51.2	51.2	51.2
GE 9000	50.3	50.3	50.5	51.0	51.1	51.2	51.5	51.6	51.6	51.6	51.6	51.6
GE 8000	53.4	53.4	53.8	54.3	54.4	54.5	54.8	54.9	54.9	54.9	54.9	54.9
GE 7000	54.3	54.3	54.7	55.3	55.5	55.6	55.9	56.0	56.0	56.0	56.0	56.0
GE 6000	54.9	54.9	55.4	55.9	56.1	56.2	56.6	56.7	56.7	56.7	56.7	56.7
GF 5000	56.0	56.1	56.6	57.1	57.4	57.5	57.8	58.0	58.0	58.0	58.0	58.0
GE 4500	56.7	56.8	57.2	57.7	58.1	58.3	58.6	58.7	58.7	58.7	58.7	58.7
GF 4000	57.5	57.5	58.2	58.9	59.2	59.5	59.9	60.1	60.2	60.2	60.2	60.2
GE 3500	58.2	58.3	58.8	59.5	60.0	60.2	60.6	60.9	61.1	61.1	61.1	61.1
GE 3000	59.8	59.9	60.4	61.2	61.6	61.8	62.5	62.7	62.9	62.9	62.9	62.9
GF 2500	62.9	63.0	64.3	65.2	65.7	65.9	66.6	66.8	67.1	67.1	67.1	67.1
GE 2000	65.4	65.5	67.1	68.1	68.7	68.9	70.1	70.4	70.9	71.0	71.1	71.1
GF 1800	65.9	65.1	67.7	68.7	69.7	70.0	71.2	71.5	71.9	72.0	72.2	72.2
GE 1500	68.1	68.6	70.3	71.6	72.9	73.2	74.6	74.9	75.8	76.0	76.6	76.6
GE 1200	70.1	70.6	72.6	73.9	75.6	76.0	77.6	78.3	79.1	79.4	80.0	80.0
GF 1000	71.2	71.7	73.7	75.1	75.9	77.4	79.2	80.3	81.2	81.4	82.0	82.0
GE 900	71.6	72.2	74.1	75.5	77.6	78.2	80.4	81.6	82.6	83.0	83.7	83.7
GE 800	71.7	72.3	74.3	75.7	78.0	78.5	81.1	82.3	83.3	84.0	84.6	84.6
GE 700	72.7	73.2	75.4	76.8	79.2	79.9	82.7	83.9	85.3	86.0	86.7	86.7
GF 600	73.1	73.7	75.3	77.2	79.9	80.5	83.7	85.2	86.9	87.8	88.5	88.5
GF 500	73.2	73.8	75.9	77.3	80.1	81.0	84.5	86.8	88.7	90.1	90.8	90.8
GE 400	73.2	73.6	75.9	77.4	80.3	81.4	85.3	87.7	89.9	91.5	92.6	92.6
GE 300	73.2	73.8	75.9	77.4	80.5	81.8	85.8	88.3	91.0	92.7	94.0	94.6
GE 200	73.2	73.8	75.9	77.4	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8
GE 100	73.2	73.8	75.9	77.4	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8
GE 000	73.2	73.8	75.9	77.4	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ELEVATION: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 18-20

VISIBILITY IN STATUTE MILES

	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
6.5	41.0	41.1	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2
8.0	45.5	46.6	46.8	46.9	46.7	46.9	46.9	46.9	46.9	46.9	46.9	46.9
8.3	47.6	47.7	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
8.9	47.5	47.7	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
9.7	47.7	48.0	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
1.7	48.3	48.4	48.5	48.7	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8
1.9	50.8	50.9	51.1	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
4.9	51.1	51.2	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
6.7	54.4	54.5	54.3	54.9	54.7	54.9	54.9	54.9	54.9	54.9	54.9	54.9
8.3	55.5	55.6	55.9	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
8.9	56.1	56.2	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
0.7	57.4	57.5	57.6	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
1.1	58.1	58.3	58.6	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
2.7	59.2	59.5	59.3	60.1	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2
3.5	60.0	60.2	60.6	60.9	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
7.1	61.6	61.8	62.5	62.7	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9
1.1	65.7	65.9	66.6	66.8	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
6.7	68.7	68.9	70.1	70.4	70.9	71.0	71.1	71.1	71.1	71.1	71.1	71.1
8.7	69.7	70.0	71.2	71.5	71.9	72.0	72.2	72.2	72.2	72.2	72.2	72.2
11.5	72.9	73.2	74.6	74.9	75.8	76.0	76.6	76.6	76.6	76.8	76.8	76.8
2.2	75.6	76.0	77.6	78.3	79.1	79.4	80.0	80.0	80.0	80.2	80.2	80.2
3.7	76.0	77.4	79.2	80.3	81.2	81.4	82.0	82.0	82.2	82.4	82.4	82.4
6.8	77.6	78.2	80.4	81.6	82.6	83.0	83.7	83.7	83.8	84.0	84.0	84.0
8.4	78.0	78.5	81.1	82.3	83.3	84.0	84.6	84.6	84.7	84.9	84.9	84.9
9.7	79.2	79.9	82.7	83.9	85.3	86.0	86.7	86.7	86.8	87.0	87.0	87.0
0.9	79.7	80.5	83.7	85.2	86.9	87.8	88.5	88.5	88.6	88.8	89.1	89.8
3.0	80.1	81.0	84.5	86.8	88.7	90.1	90.8	90.8	90.9	91.1	91.4	92.0
5.6	80.3	81.4	85.3	87.7	89.9	91.5	92.6	92.6	93.0	93.2	93.5	94.2
6.2	80.5	81.8	85.8	88.3	91.0	92.7	94.0	94.6	95.6	95.8	96.2	96.9
7.8	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8	96.0	96.7	97.4	98.4
6.2	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8	96.2	96.9	98.0	99.5
9.7	80.5	81.8	85.9	88.4	91.1	92.8	94.2	94.8	96.2	96.9	98.0	100.0

STAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

1. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 18-20

VISIBILITY IN STATUTE MILES										
GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
41.1	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2	41.2
46.6	46.8	46.9	46.7	46.9	46.9	46.9	46.9	46.9	46.9	46.9
47.7	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
47.7	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
48.0	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
48.5	48.7	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8	48.8
50.9	51.1	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
51.2	51.5	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
54.5	54.6	54.9	54.7	54.9	54.9	54.9	54.9	54.9	54.9	54.9
55.6	55.9	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
56.2	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
57.5	57.8	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
58.3	58.6	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
59.5	59.9	60.1	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2
60.2	60.6	60.9	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
61.8	62.5	62.7	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9
65.0	66.5	66.8	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
68.9	70.1	70.4	70.9	71.0	71.1	71.1	71.1	71.1	71.1	71.1
70.0	71.2	71.5	71.9	72.0	72.2	72.2	72.2	72.2	72.2	72.2
73.2	74.5	74.9	75.8	76.0	76.6	76.6	76.6	76.8	76.8	76.8
76.0	77.6	78.3	79.1	79.4	80.0	80.0	80.0	80.2	80.2	80.2
77.4	79.2	80.3	81.2	81.4	82.0	82.0	82.2	82.4	82.4	82.4
78.2	80.4	81.6	82.6	83.0	83.7	83.7	83.8	84.0	84.0	84.0
79.5	81.1	82.3	83.3	84.0	84.6	84.6	84.7	84.9	84.9	84.9
79.9	82.7	83.9	85.3	86.0	86.7	86.7	86.8	87.0	87.0	87.0
80.5	83.7	85.2	86.9	87.8	88.5	88.5	88.6	88.8	89.1	89.8
81.0	84.5	85.8	88.7	90.1	90.8	90.8	90.9	91.1	91.4	92.0
81.4	85.3	87.7	89.9	91.5	92.6	92.6	93.0	93.2	93.5	94.2
81.5	85.8	88.3	91.0	92.7	94.0	94.6	95.6	95.8	96.2	96.9
81.8	85.9	88.4	91.1	92.8	94.2	94.8	95.0	96.7	97.4	98.4
81.8	85.9	88.4	91.1	92.8	94.2	94.8	96.2	96.9	98.0	99.5
81.8	85.9	88.4	91.1	92.8	94.2	94.8	96.2	96.9	98.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AL
MONTH: MAR HOURS: 2

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	43.3	43.7	43.8	43.9	44.0	44.2	44.2	44.2	44.2	44.3	44.3	44.3
GE 20000	46.5	46.8	47.0	47.1	47.2	47.4	47.4	47.4	47.4	47.5	47.5	47.5
GE 18000	46.7	47.0	47.2	47.3	47.4	47.6	47.6	47.6	47.6	47.7	47.7	47.7
GE 16000	46.7	47.0	47.2	47.3	47.4	47.6	47.6	47.6	47.6	47.7	47.7	47.7
GE 14000	46.7	47.0	47.2	47.3	47.4	47.6	47.6	47.6	47.6	47.7	47.7	47.7
GE 12000	47.5	47.8	48.1	48.2	48.3	48.5	48.5	48.5	48.5	48.6	48.6	48.6
GE 10000	49.6	49.9	50.1	50.2	50.3	50.5	50.5	50.5	50.5	50.6	50.6	50.6
GE 9000	49.7	50.0	50.2	50.3	50.4	50.6	50.6	50.6	50.6	50.8	50.8	50.8
GE 8000	51.9	52.3	52.5	52.7	53.0	53.2	53.2	53.2	53.2	53.3	53.3	53.3
GE 7000	52.3	52.6	52.8	53.0	53.3	53.5	53.5	53.5	53.5	53.7	53.7	53.7
GE 6000	52.7	53.0	53.2	53.4	53.8	54.0	54.0	54.0	54.0	54.1	54.1	54.1
GE 5000	54.4	54.9	55.2	55.5	55.8	56.0	56.0	56.0	56.0	56.1	56.1	56.1
GE 4500	55.1	55.6	55.8	56.1	56.5	56.7	56.7	56.7	56.7	56.8	56.8	56.8
GE 4000	56.5	57.0	57.2	57.5	57.8	58.2	58.3	58.3	58.3	58.4	58.4	58.4
GE 3500	57.2	57.7	58.0	58.3	58.6	58.9	59.0	59.0	59.0	59.1	59.1	59.1
GE 3000	58.9	59.5	59.8	60.1	61.2	61.6	61.9	61.9	61.9	62.0	62.0	62.0
GE 2500	61.9	62.5	62.9	63.3	64.5	64.9	65.3	65.4	65.4	65.5	65.5	65.5
GE 2000	65.4	65.9	66.7	67.3	68.9	69.5	70.4	70.6	70.6	70.8	70.8	70.8
GE 1800	65.8	66.3	67.3	68.0	69.6	70.1	71.2	71.5	71.6	71.8	71.8	71.8
GE 1500	68.1	68.7	69.9	70.5	72.6	73.1	74.5	74.9	75.2	75.9	76.0	76.0
GE 1200	69.1	69.8	71.2	71.9	74.1	74.7	76.3	76.8	77.1	78.1	78.4	78.5
GE 1000	70.1	70.8	72.5	73.2	75.5	76.1	77.8	78.4	78.7	79.8	80.2	80.4
GE 900	70.2	70.9	72.6	73.5	76.0	76.7	78.5	79.0	79.6	80.8	81.2	81.4
GE 800	70.4	71.1	72.8	73.8	76.6	77.4	79.4	79.9	80.4	81.9	82.6	82.8
GE 700	71.3	71.9	73.8	74.9	77.8	78.7	81.5	82.6	83.1	84.6	85.3	85.5
GE 600	71.6	72.3	74.4	75.8	78.9	79.9	83.2	84.3	84.9	86.6	87.2	87.4
GE 500	72.2	72.8	74.9	76.7	80.1	81.1	84.6	85.8	86.7	88.4	89.1	89.4
GE 400	72.3	72.9	75.2	76.9	80.5	81.6	85.7	87.6	88.6	90.5	91.5	91.7
GE 300	72.5	73.1	75.4	77.1	81.0	82.6	86.9	89.2	90.9	93.1	94.4	94.9
GE 200	72.5	73.1	75.4	77.1	81.0	82.6	87.0	89.7	91.3	93.7	94.9	95.5
GE 100	72.5	73.1	75.4	77.1	81.0	82.6	87.0	89.7	91.3	93.8	95.1	95.6
GE 000	72.5	73.1	75.4	77.1	81.0	82.6	87.0	89.7	91.3	93.8	95.1	95.6

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: 21-23

VISIBILITY IN STATUTE MILES											
GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
44.0	44.2	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3	44.3	44.3
47.2	47.4	47.4	47.4	47.4	47.5	47.5	47.5	47.5	47.5	47.5	47.5
47.4	47.5	47.6	47.6	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.7
47.4	47.5	47.5	47.6	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.7
47.4	47.5	47.6	47.6	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.7
48.3	48.5	48.5	48.5	48.5	48.6	48.6	48.6	48.6	48.6	48.6	48.6
50.3	50.5	50.5	50.5	50.5	50.6	50.6	50.6	50.6	50.6	50.6	50.6
50.4	50.6	50.6	50.6	50.6	50.8	50.8	50.8	50.8	50.8	50.8	50.8
53.0	53.2	53.2	53.2	53.2	53.3	53.3	53.3	53.3	53.3	53.3	53.3
53.3	53.5	53.5	53.5	53.5	53.7	53.7	53.7	53.7	53.7	53.7	53.7
53.8	54.0	54.0	54.0	54.0	54.1	54.1	54.1	54.1	54.1	54.1	54.1
55.9	56.0	56.0	56.0	56.0	56.1	56.1	56.1	56.1	56.1	56.1	56.1
55.5	56.7	56.7	56.7	56.7	56.8	56.8	56.8	56.8	56.8	56.8	56.8
57.8	58.2	58.3	58.3	58.3	58.4	58.4	58.4	58.4	58.4	58.4	58.4
58.6	58.9	59.0	59.0	59.0	59.1	59.1	59.1	59.1	59.1	59.1	59.1
61.2	61.6	61.9	61.9	61.9	62.0	62.0	62.0	62.0	62.0	62.0	62.0
64.5	64.9	65.3	65.4	65.4	65.5	65.5	65.5	65.5	65.5	65.5	65.5
68.9	69.5	70.4	70.6	70.6	70.8	70.8	70.8	70.8	70.8	70.8	70.8
69.6	70.1	71.2	71.5	71.6	71.8	71.8	71.8	71.8	71.8	71.8	71.8
72.6	73.1	74.5	74.9	75.2	75.9	76.0	76.0	76.0	76.0	76.0	76.0
74.1	74.7	76.3	76.8	77.1	78.1	78.4	78.5	78.5	78.5	78.5	78.5
75.5	76.1	77.8	78.4	78.7	79.8	80.2	80.4	80.4	80.4	80.4	80.4
75.0	76.7	78.5	79.0	79.6	80.8	81.2	81.4	81.4	81.4	81.4	81.4
76.6	77.4	79.4	79.9	80.4	81.9	82.6	82.8	82.8	82.8	82.8	82.8
77.8	78.7	81.5	82.6	83.1	84.6	85.3	85.5	85.5	85.5	85.5	85.5
78.9	79.9	83.2	84.3	84.9	86.6	87.2	87.4	87.7	87.7	87.8	88.5
80.1	81.1	84.6	85.8	86.7	88.4	89.1	89.4	89.7	89.7	89.8	90.4
80.5	81.6	85.7	87.6	88.6	90.5	91.5	91.7	92.0	92.2	92.4	93.0
81.0	82.6	86.9	89.2	90.9	93.1	94.4	94.9	95.8	96.0	96.3	97.0
81.0	82.6	87.0	89.7	91.3	93.7	94.9	95.5	96.6	96.8	97.7	98.4
81.0	82.6	87.0	89.7	91.3	93.8	95.1	95.6	96.7	96.9	98.0	99.4
81.0	82.6	87.0	89.7	91.3	93.8	95.1	95.6	96.7	96.9	98.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: /
 LST TO UTC: + 5 MONTH: MAR HOURS: AI

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	37.2	37.4	37.6	37.7	37.9	38.0	38.1	38.2	38.2	38.2	38.2	38.2
GE 20000	40.9	41.1	41.4	41.5	41.9	41.9	42.0	42.1	42.1	42.2	42.2	42.2
GE 18000	41.5	41.7	42.0	42.2	42.5	42.5	42.6	42.7	42.7	42.8	42.8	42.8
GE 16000	41.6	41.8	42.2	42.3	42.6	42.6	42.7	42.8	42.9	42.9	42.9	42.9
GE 14000	41.9	42.1	42.4	42.6	42.9	42.9	43.0	43.1	43.2	43.2	43.2	43.2
GE 12000	42.6	42.9	43.2	43.3	43.6	43.7	43.8	43.9	43.9	44.0	44.0	44.0
GE 10000	44.4	44.7	45.0	45.3	45.6	45.7	45.7	45.9	45.9	45.9	45.9	45.9
GE 9000	44.7	45.0	45.4	45.6	45.9	46.0	46.1	46.2	46.2	46.2	46.3	46.3
GE 8000	46.9	47.1	47.5	47.8	48.2	48.3	48.4	48.5	48.6	48.6	48.6	48.6
GE 7000	48.0	48.2	48.7	49.0	49.4	49.5	49.6	49.7	49.8	49.8	49.8	49.8
GE 6000	48.5	48.8	49.2	49.5	50.0	50.1	50.2	50.3	50.4	50.4	50.4	50.4
GE 5000	49.7	50.1	50.5	50.9	51.4	51.5	51.7	51.8	51.9	51.9	51.9	51.9
GE 4500	50.3	50.7	51.2	51.5	52.1	52.2	52.4	52.5	52.6	52.6	52.6	52.6
GE 4000	51.7	52.2	52.7	53.1	53.8	54.0	54.2	54.4	54.4	54.5	54.6	54.6
GE 3500	52.7	53.2	53.8	54.1	54.9	55.0	55.3	55.5	55.6	55.6	55.7	55.7
GE 3000	54.4	54.9	55.5	55.9	56.9	57.1	57.4	57.6	57.7	57.8	57.9	57.9
GE 2500	56.9	57.4	58.3	58.8	60.0	60.2	60.6	60.9	61.0	61.1	61.2	61.2
GE 2000	60.5	61.0	62.2	63.0	64.5	64.8	65.6	66.0	66.3	66.5	66.6	66.6
GE 1800	61.5	62.1	63.4	64.2	65.8	66.1	67.0	67.5	67.8	68.0	68.2	68.2
GE 1500	64.2	64.9	66.4	67.3	69.2	69.6	70.8	71.4	71.9	72.2	72.5	72.5
GE 1200	66.0	66.8	68.5	69.6	71.9	72.4	73.8	74.6	75.1	75.6	76.2	76.2
GE 1000	66.8	67.7	69.6	70.7	73.1	73.7	75.3	76.2	76.9	77.6	78.2	78.3
GE 900	67.4	68.3	70.3	71.5	74.2	74.8	76.6	77.6	78.5	79.2	79.9	80.0
GE 800	67.7	68.7	70.8	72.1	74.7	75.6	77.7	79.8	79.9	80.2	81.8	81.9
GE 700	68.2	69.2	71.5	72.9	75.9	76.6	79.0	80.3	81.5	82.6	83.6	83.8
GE 600	68.6	69.6	72.0	73.5	76.7	77.7	80.3	81.9	83.3	84.6	85.9	86.0
GE 500	69.0	70.0	72.5	74.2	77.6	78.7	81.7	83.8	85.5	87.1	88.6	88.8
GE 400	69.1	70.2	72.7	74.4	78.0	79.2	82.5	85.0	86.7	88.4	90.3	90.7
GE 300	69.2	70.3	72.9	74.6	78.4	79.8	83.4	86.2	88.4	90.4	92.6	93.1
GE 200	69.2	70.3	72.9	74.6	78.5	79.9	83.6	86.8	89.0	91.4	93.8	94.4
GE 100	69.2	70.3	72.9	74.7	78.5	79.9	83.6	86.8	89.1	91.4	93.9	94.5
GE 000	69.2	70.3	72.9	74.7	78.5	79.9	83.6	86.8	89.1	91.4	93.9	94.5

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: ALL

VISIBILITY IN STATUTE MILES											
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
37.9	38.0	38.1	38.2	38.2	38.2	38.2	38.2	38.3	38.3	38.3	38.3
41.9	41.9	42.0	42.1	42.1	42.2	42.2	42.2	42.2	42.2	42.2	42.2
42.5	42.5	42.6	42.7	42.7	42.8	42.8	42.8	42.8	42.8	42.8	42.8
42.6	42.6	42.7	42.8	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
42.9	42.9	43.0	43.1	43.2	43.2	43.2	43.2	43.2	43.2	43.2	43.2
43.6	43.7	43.8	43.9	43.9	44.0	44.0	44.0	44.0	44.0	44.0	44.0
45.6	45.7	45.7	45.9	45.9	45.9	45.9	45.9	46.0	46.0	46.0	46.0
45.9	46.0	46.1	46.2	46.2	46.2	46.3	46.3	46.3	46.3	46.3	46.3
48.2	48.3	48.4	48.5	48.6	48.6	48.6	48.6	48.7	48.7	48.7	48.7
49.4	49.5	49.6	49.7	49.8	49.8	49.8	49.8	49.9	49.9	49.9	49.9
50.0	50.1	50.2	50.3	50.4	50.4	50.4	50.4	50.5	50.5	50.5	50.5
51.4	51.5	51.7	51.8	51.9	51.9	51.9	51.9	52.0	52.0	52.0	52.0
52.1	52.2	52.4	52.5	52.6	52.6	52.6	52.6	52.7	52.7	52.7	52.7
53.8	54.0	54.2	54.4	54.4	54.5	54.6	54.6	54.6	54.6	54.6	54.6
54.9	55.0	55.3	55.5	55.6	55.6	55.7	55.7	55.8	55.8	55.8	55.8
56.9	57.1	57.4	57.6	57.7	57.8	57.9	57.9	58.0	58.0	58.0	58.0
60.0	60.2	60.6	60.9	61.0	61.1	61.2	61.2	61.3	61.3	61.3	61.3
64.5	64.8	65.6	66.0	66.3	66.5	66.6	66.6	66.7	66.8	66.8	66.8
65.8	66.1	67.0	67.5	67.8	68.0	68.2	68.2	68.3	68.3	68.3	68.3
69.2	69.6	70.8	71.4	71.9	72.2	72.5	72.5	72.7	72.8	72.8	72.8
71.9	72.4	73.8	74.6	75.1	75.6	76.2	76.2	76.5	76.7	76.8	76.8
73.1	73.7	75.3	76.2	76.9	77.6	78.2	78.3	78.6	78.9	78.9	78.9
74.2	74.8	76.6	77.6	78.5	79.2	79.9	80.0	80.4	80.7	80.7	80.7
74.7	75.6	77.7	79.8	79.9	80.8	81.8	81.9	82.3	82.6	82.7	82.8
75.9	76.6	79.0	80.3	81.5	82.6	83.6	83.8	84.1	84.5	84.6	84.7
76.7	77.7	80.3	81.9	83.3	84.6	85.9	86.0	86.7	87.1	87.3	87.8
77.6	78.7	81.7	83.8	85.5	87.1	88.6	88.8	89.6	89.9	90.3	90.8
78.0	79.2	82.5	85.0	86.7	88.4	90.3	90.7	91.5	92.1	92.6	93.2
78.4	79.8	83.4	86.2	88.4	90.4	92.6	93.1	94.3	95.0	95.6	96.2
78.5	79.9	83.6	86.8	89.0	91.4	93.8	94.4	95.8	96.8	97.8	98.6
79.5	79.9	83.6	86.8	89.1	91.4	93.9	94.5	96.0	97.1	98.2	99.6
73.5	79.9	83.6	86.8	89.1	91.4	93.9	94.5	96.0	97.1	98.3	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: 00

CEILING IN FFET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	51.2	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3
GE 20000	54.9	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
GE 18000	55.4	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
GE 16000	55.6	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
GE 14000	56.8	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
GE 12000	57.6	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8
GE 10000	59.2	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
GF 9000	59.2	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
GE 8000	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
GE 7000	61.7	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9
GE 6000	62.3	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
GE 5000	65.6	65.8	66.0	66.0	66.0	66.0	66.2	66.2	66.2	66.2	66.2	66.2
GE 4500	68.1	68.3	68.6	68.7	68.8	68.8	69.0	69.0	69.0	69.0	69.0	69.0
GE 4000	70.4	70.7	71.0	71.1	71.6	71.6	71.8	71.8	71.8	71.8	71.8	71.8
GE 3500	71.4	71.8	72.2	72.3	72.8	72.8	73.0	73.0	73.0	73.0	73.0	73.0
GE 3000	73.8	74.1	74.7	74.8	75.2	75.2	75.4	75.4	75.4	75.4	75.4	75.4
GF 2500	75.7	76.0	76.6	76.7	77.1	77.1	77.3	77.3	77.3	77.3	77.3	77.3
GF 2000	77.0	77.4	78.1	78.4	79.0	79.0	79.2	79.3	79.3	79.3	79.3	79.3
GE 1800	77.8	78.2	79.1	79.4	80.0	80.0	80.2	80.3	80.3	80.3	80.3	80.3
GE 1500	79.2	79.7	80.7	81.0	81.8	81.8	82.0	82.1	82.1	82.1	82.1	82.1
GE 1200	79.9	80.3	81.4	81.8	82.7	82.7	82.9	83.0	83.0	83.0	83.1	83.1
GE 1000	80.9	81.3	82.4	82.3	83.8	83.9	84.1	84.3	84.3	84.3	84.4	84.4
GE 900	81.2	81.8	82.9	83.2	84.3	84.4	84.7	85.0	85.0	85.0	85.1	85.1
GE 800	81.9	82.6	83.9	84.3	85.6	85.7	85.9	86.3	86.6	86.6	86.8	87.0
GE 700	82.1	82.8	84.1	84.6	85.8	85.9	86.2	87.1	87.3	87.3	87.6	87.9
GE 600	82.4	83.1	84.6	85.1	86.8	86.9	87.3	88.2	88.4	88.4	88.7	89.0
GF 500	82.8	83.4	84.9	85.7	87.9	88.3	89.4	90.6	90.9	90.9	91.1	91.4
GF 400	82.8	83.4	85.0	85.8	88.1	88.6	89.8	91.2	91.9	92.0	92.2	92.6
GE 300	83.0	83.7	85.4	86.2	88.8	89.3	90.9	92.9	94.1	94.3	94.8	95.2
GE 200	83.0	83.7	85.4	86.2	88.8	89.3	90.9	93.3	94.8	95.0	95.4	95.9
GE 100	83.0	83.7	85.4	86.2	88.8	89.3	90.9	93.3	94.8	95.1	95.6	96.0
GE 000	83.0	83.7	85.4	86.2	88.8	89.3	90.9	93.3	94.8	95.1	95.6	96.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 00-02

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3	51.3
1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
4	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8
4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4	59.4
3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9
6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
2	66.0	66.0	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2
0	68.8	68.8	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
8	71.6	71.6	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8
0	72.8	72.8	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0
4	75.2	75.2	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
1	77.1	77.1	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3
3	79.0	79.0	79.2	79.3	79.3	79.3	79.3	79.3	79.3	79.3	79.3	79.3
3	80.0	80.0	80.2	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.3	80.3
2	81.8	81.8	82.0	82.1	82.1	82.1	82.1	82.1	82.2	82.2	82.2	82.2
2	82.7	82.7	82.9	83.0	83.0	83.0	83.1	83.1	83.2	83.3	83.3	83.3
6	83.8	83.9	84.1	84.3	84.3	84.3	84.4	84.4	84.6	84.7	84.7	84.7
2	84.3	84.4	84.7	85.0	85.0	85.0	85.1	85.1	85.2	85.3	85.3	85.3
0	85.6	85.7	85.9	86.3	86.6	86.6	86.8	87.0	87.1	87.3	87.3	87.3
1	85.8	85.9	86.2	87.1	87.3	87.3	87.6	87.9	88.0	88.2	88.2	88.2
1	86.8	86.9	87.3	88.2	88.4	88.4	88.7	89.0	89.1	89.3	89.3	89.3
6	87.9	88.3	89.4	90.6	90.9	90.9	91.1	91.4	91.6	91.8	91.8	91.8
6	89.1	89.6	89.8	91.2	91.9	92.0	92.2	92.6	92.8	93.0	93.0	93.0
6	89.8	89.8	90.9	92.9	94.1	94.3	94.8	95.2	95.6	95.8	95.9	96.2
4	89.8	89.3	90.9	93.3	94.8	95.0	95.4	95.9	96.4	96.9	97.4	98.3
7	89.8	89.3	90.9	93.3	94.8	95.1	95.6	96.0	96.7	97.2	98.6	99.7
7	89.8	89.3	90.9	93.3	94.8	95.1	95.6	96.0	96.7	97.2	98.6	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: APR HOURS: 03

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	49.3	49.6	49.6	49.6	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7
GE 20000	51.6	52.0	52.0	52.0	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1
GE 18000	51.9	52.3	52.3	52.3	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
GE 16000	51.9	52.3	52.3	52.3	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
GE 14000	52.6	53.0	53.0	53.0	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1
GE 12000	53.9	54.3	54.3	54.3	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4
GE 10000	55.9	56.3	56.3	56.3	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
GE 9000	56.1	56.6	56.6	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
GE 8000	58.3	58.8	58.8	58.8	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9
GE 7000	58.7	59.1	59.1	59.1	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
GE 6000	59.8	60.3	60.3	60.3	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4
GE 5000	61.8	62.3	62.3	62.3	62.4	62.4	62.6	62.8	62.8	62.8	62.8	62.8
GE 4500	62.7	63.2	63.2	63.2	63.3	63.3	63.4	63.7	63.7	63.7	63.7	63.7
GE 4000	66.9	67.4	67.4	67.7	67.8	67.8	67.9	68.1	68.1	68.1	68.1	68.1
GE 3500	67.9	68.4	68.6	68.8	68.9	68.9	69.1	69.3	69.3	69.3	69.3	69.3
GE 3000	69.3	69.9	70.1	70.3	70.3	70.8	71.1	71.3	71.3	71.3	71.3	71.3
GE 2500	70.7	71.2	71.6	72.0	72.4	72.4	72.8	73.0	73.0	73.0	73.1	73.1
GE 2000	72.7	73.2	73.7	74.1	74.8	74.8	75.2	75.4	75.4	75.4	75.6	75.6
GE 1800	73.7	74.2	74.8	75.3	75.2	75.2	76.7	76.9	76.9	76.9	77.0	77.0
GE 1500	75.1	75.7	76.6	77.2	78.2	78.2	78.7	79.2	79.3	79.3	79.4	79.4
GE 1200	76.9	77.4	78.4	79.1	80.1	80.1	80.6	81.1	81.2	81.2	81.3	81.3
GE 1000	77.9	78.4	79.8	80.4	81.6	81.6	82.0	82.6	82.7	82.7	82.8	82.8
GE 900	78.0	78.6	79.9	80.6	81.7	82.0	82.4	83.1	83.4	83.4	83.6	83.6
GE 800	78.7	79.2	80.3	81.4	82.9	83.2	83.7	84.6	85.0	85.0	85.1	85.1
GE 700	79.0	79.7	81.2	81.9	83.4	83.8	84.3	85.2	85.8	85.8	85.9	85.9
GE 600	79.1	79.8	81.3	82.0	83.8	84.1	84.9	85.9	86.4	86.4	86.6	86.6
GE 500	79.2	80.0	81.6	82.3	84.3	84.9	86.2	87.2	88.0	88.0	88.3	88.3
GE 400	79.4	80.3	82.1	82.9	85.1	85.8	87.8	89.0	90.1	90.1	90.4	90.4
GE 300	79.4	80.3	82.3	83.2	85.7	86.3	88.4	89.8	91.1	91.2	91.8	91.8
GE 200	79.4	80.3	82.4	83.3	85.8	86.4	88.7	90.1	92.0	92.6	93.2	93.3
GE 100	79.4	80.3	82.4	83.3	85.8	86.4	88.7	90.3	92.2	92.9	93.6	93.7
GE 000	79.4	80.3	82.4	83.3	85.8	86.4	88.7	90.3	92.2	92.9	93.6	93.7

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 03-05

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.7	49.9	49.9	49.9
52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.1	52.3	52.3	52.3
52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.7	52.7	52.7
52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.7	52.7	52.7
53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.1	53.3	53.3	53.3
54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.4	54.7	54.7	54.7
56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.7	56.7	56.7
56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.9	56.9	56.9
58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	59.1	59.1	59.1
59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.4	59.4	59.4
60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.7	60.7	60.7
62.4	62.4	62.6	62.8	62.8	62.8	62.8	62.8	62.8	63.0	63.0	63.0
63.3	63.3	63.4	63.7	63.7	63.7	63.7	63.7	63.7	63.9	63.9	63.9
67.8	67.8	67.9	68.1	68.1	68.1	68.1	68.1	68.1	68.3	68.3	68.3
68.9	68.9	69.1	69.3	69.3	69.3	69.3	69.3	69.3	69.6	69.7	69.7
70.8	70.8	71.1	71.3	71.3	71.3	71.3	71.3	71.4	71.7	71.8	71.8
72.4	72.4	72.8	73.0	73.0	73.0	73.1	73.1	73.2	73.4	73.6	73.6
74.8	74.8	75.2	75.4	75.4	75.4	75.6	75.6	75.7	75.9	76.0	76.0
76.2	76.2	76.7	76.9	76.9	76.9	77.0	77.0	77.1	77.3	77.4	77.4
78.2	78.2	78.7	79.2	79.3	79.3	79.4	79.4	79.9	80.2	80.3	80.3
80.1	80.1	80.6	81.1	81.2	81.2	81.3	81.3	81.8	82.1	82.2	82.2
81.6	81.6	82.0	82.6	82.7	82.7	82.8	82.8	83.2	83.6	83.7	83.7
81.7	82.0	82.4	83.1	83.4	83.4	83.6	83.6	84.0	84.3	84.4	84.4
82.9	83.2	83.7	84.6	85.0	85.0	85.1	85.1	85.8	86.3	86.4	86.4
83.4	83.8	84.3	85.2	85.8	85.8	85.9	85.9	86.7	87.2	87.3	87.3
83.8	84.1	84.9	85.9	86.4	86.4	86.6	86.6	87.3	87.9	88.0	88.0
84.3	84.9	86.2	87.2	88.0	88.0	88.3	88.3	89.1	89.7	89.9	90.0
85.1	85.8	87.8	89.0	90.1	90.1	90.4	90.4	91.2	91.8	92.0	92.1
85.7	86.3	88.4	89.8	91.1	91.2	91.8	91.8	92.6	93.1	93.3	93.4
85.8	86.4	88.7	90.1	92.0	92.6	93.2	93.3	94.4	95.4	96.2	96.7
85.8	86.4	88.7	90.3	92.2	92.9	93.6	93.7	94.9	96.0	98.1	99.7
85.8	86.4	88.7	90.3	92.2	92.9	93.6	93.7	94.9	96.0	98.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: 06-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	41.0	41.4	42.0	42.3	42.9	43.0	43.0	43.2	43.3	43.3	43.3	43.3	43.3	43.3
GE 20000	44.9	45.4	46.0	46.3	46.9	47.0	47.0	47.2	47.3	47.3	47.3	47.3	47.3	47.3
GE 18000	45.7	46.2	46.8	47.1	47.7	47.8	47.8	48.0	48.1	48.1	48.1	48.1	48.1	48.1
GE 16000	45.7	46.2	46.8	47.1	47.7	47.8	47.8	48.0	48.1	48.1	48.1	48.1	48.1	48.1
GE 14000	46.6	47.1	47.7	48.0	48.6	48.7	48.7	48.9	49.0	49.0	49.0	49.0	49.0	49.0
GE 12000	48.1	48.7	49.3	49.7	50.2	50.3	50.3	50.6	50.7	50.7	50.7	50.7	50.8	50.8
GE 10000	50.7	51.3	52.2	52.6	53.1	53.2	53.2	53.4	53.6	53.6	53.6	53.6	53.7	53.7
GE 9000	50.8	51.6	52.4	52.8	53.3	53.4	53.4	53.7	53.8	53.8	53.8	53.8	53.9	53.9
GE 8000	52.9	53.7	54.9	55.2	55.8	55.9	55.9	56.1	56.2	56.2	56.2	56.2	56.3	56.3
GE 7000	53.7	54.4	55.7	56.0	56.6	56.7	56.7	56.9	57.0	57.0	57.0	57.0	57.1	57.1
GE 6000	54.2	55.0	56.3	56.7	57.4	57.6	57.6	57.8	57.9	57.9	57.9	57.9	58.0	58.0
GE 5000	57.0	57.8	59.6	60.0	61.0	61.2	61.2	61.4	61.6	61.6	61.6	61.6	61.7	61.7
GE 4500	58.2	59.0	60.8	61.3	62.3	62.6	62.6	62.8	63.0	63.0	63.0	63.0	63.1	63.1
GE 4000	60.9	61.7	63.6	64.1	65.3	65.6	65.6	66.0	66.3	66.3	66.3	66.3	66.4	66.4
GE 3500	61.6	62.3	64.2	64.8	66.0	66.4	66.4	67.0	67.3	67.3	67.3	67.3	67.4	67.4
GE 3000	62.4	63.2	65.1	65.7	67.1	67.6	67.6	68.3	68.7	68.7	68.7	68.7	68.8	68.8
GE 2500	63.6	64.3	66.2	66.8	68.3	68.8	69.0	69.7	70.0	70.0	70.0	70.0	70.1	70.1
GE 2000	66.4	67.2	69.2	69.8	71.3	71.9	72.2	72.9	73.2	73.2	73.2	73.2	73.3	73.3
GE 1800	67.2	68.0	70.0	70.6	72.3	72.9	73.2	73.9	74.2	74.2	74.2	74.2	74.3	74.3
GE 1500	69.0	69.9	72.0	72.8	74.6	75.2	75.7	76.3	76.8	76.8	76.8	77.0	77.1	77.1
GE 1200	71.0	71.9	74.1	74.9	76.9	77.6	78.2	79.0	79.7	79.7	79.7	80.0	80.1	80.1
GE 1000	72.0	72.9	75.2	76.0	78.1	78.8	79.4	80.2	81.0	81.2	81.7	81.7	81.8	81.8
GE 900	72.1	73.0	75.3	76.2	78.3	79.0	79.7	80.6	81.3	81.6	82.0	82.1	82.1	82.1
GE 800	72.4	73.4	75.9	76.9	79.2	79.9	80.7	81.6	82.7	82.9	83.4	83.4	83.6	83.6
GE 700	72.8	73.8	76.4	77.4	79.8	80.4	81.3	82.3	83.4	83.7	84.2	84.2	84.3	84.3
GE 600	73.2	74.3	77.3	78.3	80.8	81.7	83.0	84.0	85.2	85.7	86.2	86.2	86.3	86.3
GE 500	73.3	74.4	77.7	78.7	81.8	82.8	84.4	85.6	87.0	87.6	88.3	88.3	88.4	88.4
GE 400	73.6	74.8	78.2	79.4	83.0	84.0	86.3	87.9	89.3	90.0	90.9	90.9	91.0	91.0
GE 300	73.7	74.9	78.3	79.5	83.1	84.1	86.4	88.0	89.6	90.6	91.8	91.8	91.9	91.9
GE 200	73.7	74.9	78.3	79.6	83.1	84.1	86.4	88.1	90.2	91.3	93.0	93.0	93.2	93.2
GE 100	73.7	74.9	78.3	79.6	83.1	84.1	86.4	88.1	90.2	91.3	93.1	93.1	93.3	93.3
GE 000	73.7	74.9	78.3	79.6	83.1	84.1	86.4	88.1	90.2	91.3	93.1	93.1	93.3	93.3

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI
ELEVATION: 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 06-08

VISIBILITY IN STATUTE MILES											
GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
42.9	43.0	43.0	43.2	43.3	43.3	43.3	43.3	43.4	43.4	43.6	43.6
46.9	47.0	47.0	47.2	47.3	47.3	47.3	47.3	47.4	47.4	47.6	47.6
47.7	47.8	47.8	48.0	48.1	48.1	48.1	48.1	48.2	48.2	48.3	48.3
47.7	47.8	47.8	48.0	48.1	48.1	48.1	48.1	48.2	48.2	48.3	48.3
48.6	48.7	48.7	48.9	49.0	49.0	49.0	49.0	49.1	49.1	49.2	49.2
50.2	50.3	50.3	50.6	50.7	50.7	50.7	50.8	50.9	50.9	51.0	51.0
53.1	53.2	53.2	53.4	53.6	53.6	53.6	53.7	53.8	53.8	53.9	53.9
53.3	53.4	53.4	53.7	53.8	53.8	53.8	53.9	54.0	54.0	54.1	54.1
55.8	55.9	55.9	56.1	56.2	56.2	56.2	56.3	56.4	56.4	56.6	56.6
56.6	56.7	56.7	56.9	57.0	57.0	57.0	57.1	57.2	57.2	57.3	57.3
57.4	57.6	57.6	57.8	57.9	57.9	57.9	58.0	58.1	58.1	58.2	58.2
61.0	61.2	61.2	61.4	61.6	61.6	61.6	61.7	61.8	61.9	62.0	62.0
62.3	62.6	62.6	62.8	63.0	63.0	63.0	63.1	63.2	63.3	63.4	63.4
65.3	65.6	65.6	66.0	66.3	66.3	66.3	66.4	66.6	66.7	66.8	66.8
66.0	66.4	66.4	67.0	67.3	67.3	67.3	67.4	67.6	67.7	67.8	67.8
67.1	67.6	67.8	68.3	68.7	68.7	68.7	68.8	68.9	69.0	69.1	69.1
68.3	68.8	69.0	69.7	70.0	70.0	70.0	70.1	70.2	70.3	70.4	70.4
71.3	71.7	72.2	72.9	73.2	73.2	73.2	73.3	73.4	73.6	73.7	73.7
72.3	72.9	73.2	73.9	74.2	74.2	74.2	74.3	74.4	74.6	74.7	74.7
74.6	75.2	75.7	76.3	76.8	76.8	77.0	77.1	77.3	77.4	77.6	77.6
76.9	77.6	78.2	79.0	79.7	79.8	80.0	80.1	80.3	80.4	80.6	80.6
78.1	78.8	79.4	80.2	81.0	81.2	81.7	81.8	82.0	82.1	82.2	82.2
78.3	79.0	79.7	80.6	81.3	81.6	82.0	82.1	82.3	82.4	82.6	82.6
79.2	79.9	80.7	81.6	82.7	82.9	83.4	83.6	83.8	83.9	84.3	84.3
79.6	80.4	81.3	82.3	83.4	83.7	84.2	84.3	84.6	84.7	85.1	85.1
80.8	81.7	83.0	84.0	85.2	85.7	86.2	86.3	86.6	86.7	87.1	87.1
81.8	82.8	84.4	85.6	87.0	87.6	88.3	88.4	89.0	89.1	89.6	89.6
83.0	84.0	86.3	87.9	89.3	90.0	90.9	91.0	91.9	92.0	92.4	92.4
83.1	84.1	86.4	88.0	89.6	90.6	91.8	91.9	92.9	93.0	93.4	93.8
83.1	84.1	86.4	88.1	90.2	91.3	93.0	93.2	94.3	94.6	96.3	97.1
83.1	84.1	86.4	88.1	90.2	91.3	93.1	93.3	94.6	95.1	97.8	99.9
83.1	84.1	86.4	88.1	90.2	91.3	93.1	93.3	94.6	95.1	97.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: 09

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GF 7	GE 5	GF 5	GE 4	GF 3	GF 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GF 1	GE 3/4	GE 5/8
NO CEIL	40.4	40.9	41.3	41.4	41.4	41.4	41.6	41.6	41.6	41.6	41.6	41.6
GE 20000	45.2	45.7	45.1	45.2	45.2	46.2	45.3	45.3	45.3	45.3	46.3	45.3
GE 18000	45.7	46.1	46.5	46.7	45.7	46.7	46.3	46.8	46.8	46.8	46.8	46.8
GE 16000	46.0	46.4	46.9	47.0	47.0	47.0	47.1	47.1	47.1	47.1	47.1	47.1
GE 14000	47.0	47.4	47.9	48.0	48.0	48.0	48.1	48.1	48.1	48.1	48.1	48.1
GE 12000	48.4	48.9	49.3	49.4	49.4	49.4	49.6	49.6	49.6	49.6	49.6	49.6
GE 10000	51.6	52.0	52.4	52.5	52.5	52.6	52.7	52.7	52.7	52.7	52.7	52.7
GE 9000	51.7	52.1	52.5	52.7	52.7	52.7	52.8	52.8	52.8	52.8	52.8	52.8
GE 8000	54.5	55.0	55.4	55.5	55.5	55.5	55.7	55.7	55.7	55.7	55.7	55.7
GE 7000	55.6	56.2	56.7	56.8	56.8	56.8	56.9	56.9	56.9	56.9	56.9	56.9
GE 6000	56.5	57.2	57.7	57.8	57.8	57.8	57.9	57.9	57.9	57.9	57.9	57.9
GE 5000	58.5	59.4	59.3	60.4	60.6	60.6	60.7	60.7	60.7	60.7	60.7	60.7
GE 4500	59.2	60.1	61.0	61.1	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3
GE 4000	60.2	61.1	62.3	62.5	62.7	62.7	62.8	62.9	62.9	62.9	62.9	62.9
GE 3500	61.9	62.8	64.1	64.3	64.4	64.4	64.5	64.7	64.7	64.7	64.7	64.7
GE 3000	63.8	64.8	65.2	65.7	65.8	65.8	66.0	67.0	67.1	67.1	67.1	67.1
GE 2500	65.2	66.2	68.1	68.7	68.8	68.8	68.9	69.0	69.1	69.1	69.1	69.1
GE 2000	67.4	68.5	70.4	71.1	71.6	71.6	71.7	72.0	72.1	72.1	72.1	72.1
GE 1800	69.1	70.2	72.2	72.9	73.4	73.6	74.1	74.7	74.8	74.8	74.8	74.8
GE 1500	71.3	72.4	74.7	75.4	75.1	76.2	77.2	77.8	77.9	78.1	78.1	78.1
GE 1200	73.9	75.0	77.2	78.1	78.7	78.8	79.8	80.3	80.6	81.1	81.1	81.2
GE 1000	74.4	75.7	77.9	78.3	77.3	79.4	80.4	81.4	81.3	82.3	82.3	82.6
GE 900	74.8	76.0	78.2	79.1	79.3	79.9	80.9	81.9	82.2	82.8	82.8	83.0
GE 800	75.7	77.0	79.3	80.3	81.2	81.3	82.4	83.4	83.9	84.4	84.6	84.8
GE 700	76.0	77.3	79.7	80.7	81.9	82.1	83.5	84.6	85.1	85.7	85.9	86.1
GE 600	76.3	77.8	80.3	81.7	83.1	83.6	85.0	86.0	86.6	87.2	87.7	87.9
GE 500	76.7	78.3	81.6	82.9	84.7	85.2	87.2	88.4	89.0	89.8	90.6	90.8
GE 400	76.8	78.4	81.9	83.2	85.3	86.0	88.7	90.2	91.0	92.1	93.1	93.3
GE 300	76.3	78.4	82.0	83.3	85.7	86.4	89.1	91.1	92.2	93.6	94.7	95.0
GE 200	76.8	78.4	82.0	83.3	85.7	86.4	89.3	91.5	93.0	94.3	95.9	96.2
GE 100	76.8	78.4	82.0	83.3	85.7	86.4	89.3	91.7	93.1	94.4	96.1	96.4
GE 000	76.8	78.4	82.0	83.3	85.7	86.4	89.3	91.7	93.1	94.4	96.1	96.4

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ELEVATION: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 09-11

VISIBILITY IN STATUTE MILES													
CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
41.4	41.4	41.4	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.6
45.2	45.2	46.2	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3	46.3
45.7	45.7	46.7	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8
47.0	47.0	47.0	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
48.0	48.0	48.0	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1	48.1
49.4	49.4	49.4	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
52.6	52.6	52.6	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
52.7	52.7	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8
55.6	55.6	55.6	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7	55.7
56.3	56.3	56.3	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9
57.3	57.3	57.3	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
60.6	60.6	60.6	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7	60.7
61.1	61.1	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9	62.9
64.4	64.4	64.4	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
65.3	65.3	65.3	66.9	67.0	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
68.8	68.8	68.8	68.9	69.0	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1
71.6	71.6	71.6	71.7	72.0	72.1	72.1	72.1	72.1	72.1	72.1	72.1	72.1	72.1
73.4	73.4	73.6	74.1	74.7	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
76.1	76.1	76.2	77.2	77.8	77.9	78.1	78.1	78.1	78.3	78.3	78.3	78.3	78.3
78.7	78.7	78.8	79.8	80.3	80.6	81.1	81.1	81.2	81.4	81.4	81.4	81.4	81.4
79.3	79.3	79.4	80.4	81.4	81.8	82.3	82.3	82.6	82.8	83.1	83.1	83.1	83.1
79.8	79.8	79.9	80.9	81.9	82.2	82.8	82.8	83.0	83.2	83.6	83.6	83.6	83.6
81.2	81.2	81.3	82.4	83.4	83.9	84.4	84.6	84.8	85.0	85.3	85.3	85.3	85.3
81.9	81.9	82.1	83.6	84.6	85.1	85.7	85.9	86.1	86.3	86.8	86.9	86.9	86.9
83.1	83.1	83.6	85.0	86.0	86.6	87.2	87.7	87.9	88.2	88.7	88.8	88.8	88.8
84.7	84.7	85.2	87.2	88.4	89.0	89.8	90.6	90.8	91.1	91.7	91.8	91.8	91.8
85.3	85.3	86.0	88.7	90.2	91.0	92.1	93.1	93.3	93.8	94.3	94.4	94.4	94.4
85.7	85.7	86.4	89.1	91.1	92.2	93.6	94.7	95.0	95.6	96.2	96.4	96.6	96.6
85.7	85.7	86.4	89.3	91.6	93.0	94.3	95.9	96.2	96.8	97.4	98.1	98.2	98.2
85.7	85.7	86.4	89.3	91.7	93.1	94.4	96.1	96.4	97.3	98.2	99.1	99.9	99.9
85.7	85.7	86.4	89.3	91.7	93.1	94.4	96.1	96.4	97.3	98.2	99.2	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: APR HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 5	GF 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GF 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	42.1	42.6	42.6	42.6	42.5	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6
GE 20000	49.2	49.8	49.8	49.8	49.3	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8
GE 18000	50.4	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
GE 16000	50.7	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
GE 14000	51.4	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0
GE 12000	52.1	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
GE 10000	54.7	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
GE 9000	55.2	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
GE 8000	58.1	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
GE 7000	58.7	59.4	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
GE 6000	60.2	60.8	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
GE 5000	61.8	62.5	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2
GF 4500	62.9	63.8	64.4	64.4	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
GE 4000	64.8	65.7	66.4	66.4	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
GE 3500	66.3	67.2	68.0	68.0	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7
GE 3000	67.8	68.7	69.4	69.4	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
GE 2500	69.4	70.4	71.4	71.4	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
GE 2000	72.2	73.2	74.3	74.3	75.7	75.8	75.9	76.0	76.1	76.6	76.6	76.6	76.6
GE 1800	73.7	74.7	75.8	75.9	77.2	77.3	77.4	77.6	77.7	78.1	78.1	78.1	78.1
GE 1500	77.1	78.1	79.8	80.1	81.7	81.8	82.2	82.3	82.4	83.0	83.1	83.1	83.1
GE 1200	78.4	79.6	81.4	81.8	83.3	83.4	83.9	84.1	84.2	84.9	85.0	85.0	85.0
GE 1000	79.8	81.1	83.1	83.4	85.0	85.1	85.6	85.8	86.0	86.9	87.1	87.1	87.1
GF 900	80.7	82.0	84.4	84.8	86.6	86.7	87.1	87.3	87.6	88.6	88.8	88.8	88.8
GE 800	81.7	83.0	85.4	85.8	87.8	88.1	88.6	88.9	89.1	90.3	90.6	90.6	90.6
GE 700	82.0	83.3	85.8	86.2	88.2	88.7	89.2	89.8	90.2	91.4	91.7	91.7	91.7
GE 600	82.7	84.0	86.4	86.9	89.1	89.6	90.1	90.7	91.2	92.4	92.9	92.9	93.0
GE 500	82.7	84.1	86.8	87.7	90.1	90.6	91.6	92.1	92.8	94.0	94.6	94.6	94.7
GE 400	82.7	84.1	86.8	87.7	90.1	90.6	91.9	92.8	93.6	94.8	95.7	95.7	95.8
GE 300	82.8	84.2	87.0	88.0	90.4	90.9	92.3	93.7	94.6	96.2	97.1	97.1	97.3
GE 200	82.8	84.2	87.0	88.0	90.4	90.9	92.4	94.0	95.4	97.2	98.3	98.7	99.0
GE 100	82.8	84.2	87.0	88.0	90.4	90.9	92.4	94.0	95.4	97.2	98.3	98.7	99.2

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 12-14

VISIBILITY IN STATUTE MILES

CE	GE	GE	GE	GE	GE	GF	GE	GE	GE	GE	GE	GE
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6	42.6
49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8	49.8
51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2	51.2
52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0
52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8	55.8
58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2	63.2
64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7
70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3	74.3
75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9
77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2	77.2
77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3
77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4	77.4
77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6
77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7	77.7
78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1
81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4
85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: 15-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	46.8	47.2	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
GE 20000	54.6	55.0	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
GE 18000	55.3	56.2	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
GE 16000	56.3	56.8	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9
GE 14000	57.1	57.6	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7
GE 12000	57.4	57.9	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
GE 10000	59.9	60.2	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3
GE 9000	60.3	60.8	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
GE 8000	63.3	63.8	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9
GE 7000	64.9	65.3	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
GE 6000	65.9	66.3	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
GE 5000	68.2	69.0	69.4	69.4	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
GE 4500	68.8	69.6	70.0	70.0	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2
GE 4000	71.9	72.7	73.3	73.3	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
GE 3500	72.9	73.7	74.3	74.3	74.8	74.9	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
GE 3000	73.6	74.3	75.0	75.0	75.6	75.7	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8
GE 2500	76.2	77.1	77.9	77.9	78.7	78.8	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0
GE 2000	75.1	79.2	80.4	80.4	81.4	81.7	82.2	82.3	82.4	82.4	82.4	82.4	82.4	82.4
GE 1800	79.6	80.7	82.0	82.0	83.0	83.2	83.8	83.9	84.0	84.0	84.0	84.0	84.0	84.0
GE 1500	81.9	83.1	84.9	84.9	85.9	86.2	87.0	87.4	87.6	87.7	87.7	87.7	87.7	87.7
GE 1200	83.0	84.2	86.0	86.1	87.3	87.7	88.4	89.0	89.1	89.2	89.2	89.2	89.2	89.2
GE 1000	83.4	84.7	86.6	86.7	88.1	88.4	89.2	90.1	90.4	90.6	90.6	90.6	90.6	90.6
GE 900	83.8	85.0	87.2	87.3	89.1	89.4	90.2	91.2	91.6	91.7	91.8	91.8	91.8	91.8
GE 800	84.0	85.2	87.6	87.8	89.6	89.9	90.8	91.9	92.3	92.7	92.8	92.8	92.8	92.8
GE 700	84.2	85.4	87.9	88.2	90.0	90.3	91.3	92.4	92.9	93.2	93.3	93.3	93.3	93.3
GE 600	84.2	85.4	88.1	88.4	90.2	90.6	91.7	93.1	93.8	94.1	94.2	94.4	94.4	94.4
GE 500	84.4	85.7	88.3	88.3	91.0	91.3	92.6	94.1	95.0	95.3	95.6	95.8	95.8	95.8
GE 400	84.4	85.7	88.4	89.0	91.3	91.7	92.9	94.4	95.7	96.0	96.2	96.4	96.4	96.4
GE 300	84.4	85.7	88.4	89.0	91.4	91.8	93.4	95.1	97.0	97.3	97.8	98.0	98.0	98.0
GE 200	84.4	85.7	88.4	89.0	91.4	91.8	93.4	95.1	97.2	97.7	98.2	98.4	98.4	98.4
GE 100	84.4	85.7	88.4	89.0	91.4	91.8	93.4	95.1	97.2	97.8	98.3	98.6	98.6	98.6
GE 000	84.4	85.7	88.4	89.0	91.4	91.8	93.4	95.1	97.2	97.8	98.3	98.6	98.6	98.6

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 15-17

VISIBILITY IN STATUTE MILES

CE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9
57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7
58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3
60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9
65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.4
66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8
69.4	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
70.0	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2	70.2
73.3	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
74.3	74.8	74.9	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
75.0	75.6	75.7	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8	75.8
77.9	78.7	78.8	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
80.4	81.4	81.7	82.2	82.3	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
82.0	83.0	83.2	83.8	83.9	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0
84.9	85.9	86.2	87.0	87.4	87.6	87.7	87.7	87.7	87.7	87.7	87.7	87.7
86.1	87.3	87.7	88.4	89.0	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2
86.7	88.1	88.4	89.2	90.1	90.4	90.6	90.6	90.6	90.6	90.6	90.6	90.6
87.3	89.1	89.4	90.2	91.2	91.6	91.7	91.8	91.8	91.9	91.9	91.9	91.9
87.8	89.6	89.9	90.8	91.9	92.3	92.7	92.8	92.8	92.9	92.9	93.0	93.0
88.2	90.0	90.3	91.3	92.4	92.9	93.2	93.3	93.3	93.4	93.4	93.6	93.6
88.4	90.2	90.6	91.7	93.1	93.8	94.1	94.2	94.4	94.6	94.6	94.7	94.7
89.3	91.0	91.3	92.6	94.1	95.0	95.3	95.6	95.8	96.0	96.0	96.1	96.1
89.8	91.3	91.7	92.9	94.4	95.7	96.0	96.2	96.4	96.8	96.8	96.9	96.9
89.8	91.4	91.8	93.4	95.1	97.0	97.3	97.8	98.0	98.3	98.6	98.8	98.8
89.8	91.4	91.8	93.4	95.1	97.2	97.7	98.2	98.4	98.9	99.1	99.7	99.7
89.8	91.4	91.8	93.4	95.1	97.2	97.8	98.3	98.6	99.0	99.2	99.8	100.0
89.8	91.4	91.8	93.4	95.1	97.2	97.8	98.3	98.6	99.0	99.2	99.8	100.0

900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: 19

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	48.8	49.4	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
GE 20000	55.7	56.3	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
GE 18000	56.2	56.9	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
GE 16000	56.3	57.0	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
GE 14000	57.9	58.6	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
GE 12000	58.6	59.2	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3
GE 10000	60.9	61.6	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
GE 9000	61.4	62.1	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3
GE 8000	64.1	64.9	65.1	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
GE 7000	65.1	65.9	66.1	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2
GE 6000	65.7	66.4	66.7	66.8	66.9	67.1	67.1	67.1	67.1	67.1	67.1	67.1
GE 5000	68.6	69.6	69.9	70.1	70.2	70.4	70.4	70.4	70.4	70.4	70.4	70.4
GE 4500	69.8	70.8	71.1	71.3	71.4	71.8	71.8	71.8	71.8	71.8	71.8	71.8
GE 4000	71.3	72.3	72.7	72.9	73.0	73.3	73.4	73.4	73.4	73.4	73.4	73.4
GE 3500	73.1	74.2	74.6	74.8	75.0	75.3	75.4	75.4	75.4	75.4	75.4	75.4
GE 3000	74.1	75.2	75.6	75.8	76.0	76.3	76.4	76.4	76.4	76.4	76.4	76.4
GE 2500	77.1	78.2	78.8	79.0	79.7	80.3	80.6	80.6	80.6	80.6	80.6	80.6
GE 2000	78.4	79.6	80.2	80.4	81.4	82.1	82.9	82.9	82.9	82.9	83.0	83.0
GE 1800	79.6	80.7	81.3	81.7	82.7	83.3	84.1	84.1	84.1	84.1	84.2	84.2
GE 1500	81.8	83.0	84.0	84.3	85.7	86.3	87.2	87.3	87.3	87.3	87.4	87.4
GE 1200	82.9	84.1	85.2	85.6	87.0	87.7	88.6	88.8	88.8	88.9	89.1	89.1
GE 1000	83.3	84.6	85.7	86.0	87.8	88.6	89.6	90.0	90.0	90.1	90.4	90.4
GE 900	83.4	84.7	85.8	86.1	88.1	88.9	89.9	90.3	90.3	90.4	90.9	90.9
GE 800	83.8	85.1	86.3	86.8	89.0	89.8	91.1	91.6	91.8	91.9	92.3	92.3
GE 700	84.1	85.4	86.7	87.1	89.3	90.1	91.9	92.3	92.6	92.7	93.2	93.2
GE 600	84.3	85.8	87.1	87.6	89.9	90.7	92.6	93.1	93.4	93.6	94.1	94.1
GE 500	84.6	86.0	87.3	89.0	90.6	91.3	93.3	93.9	94.6	94.9	95.4	95.4
GE 400	84.7	86.1	87.4	88.1	90.8	91.6	93.6	94.2	95.0	95.3	95.9	95.9
GE 300	84.7	86.1	87.4	88.1	90.9	91.7	93.9	94.6	95.7	96.2	96.9	96.9
GE 200	84.7	86.1	87.4	88.1	90.9	91.7	94.1	94.8	96.0	96.6	97.3	97.3
GE 100	84.7	86.1	87.4	88.1	90.9	91.7	94.1	94.9	96.1	96.8	97.7	97.7
GE 000	84.7	86.1	87.4	88.1	90.9	91.7	94.1	94.9	96.1	96.8	97.7	97.7

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
D UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4	56.4
57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3	59.3
61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3
65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2
66.8	66.9	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1
70.1	70.2	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.4
71.3	71.4	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8	71.8
72.9	73.0	73.3	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4
74.8	75.0	75.3	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
75.8	76.0	76.3	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4
79.0	79.7	80.3	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
80.4	81.4	82.1	82.9	82.9	82.9	82.9	83.0	83.0	83.1	83.1	83.1	83.1
81.7	82.7	83.3	84.1	84.1	84.1	84.1	84.2	84.2	84.3	84.3	84.3	84.3
84.3	85.7	86.3	87.2	87.3	87.3	87.3	87.4	87.4	87.6	87.6	87.6	87.6
85.6	87.0	87.7	88.6	88.8	88.8	88.9	89.1	89.1	89.2	89.2	89.2	89.2
86.0	87.5	88.6	89.6	90.0	90.0	90.1	90.4	90.4	90.7	90.7	90.7	90.7
86.1	88.1	88.9	89.9	90.3	90.3	90.4	90.9	90.9	91.1	91.1	91.1	91.1
86.8	89.0	89.8	91.1	91.6	91.8	91.9	92.3	92.3	92.6	92.7	92.7	92.7
87.1	89.3	90.1	91.9	92.3	92.6	92.7	93.2	93.2	93.4	93.6	93.6	93.6
87.6	89.9	90.7	92.6	93.1	93.4	93.6	94.1	94.1	94.3	94.4	94.4	94.4
89.0	90.6	91.3	93.3	93.9	94.6	94.9	95.4	95.4	95.7	95.9	95.9	95.9
88.1	90.8	91.6	93.6	94.2	95.0	95.3	95.9	95.9	96.1	96.3	96.4	96.4
88.1	90.9	91.7	93.9	94.6	95.7	96.2	96.9	96.9	97.1	97.6	97.7	97.8
89.1	90.9	91.7	94.1	94.8	96.0	96.6	97.3	97.3	98.2	98.8	99.0	99.2
89.1	90.9	91.7	94.1	94.9	96.1	96.8	97.7	97.7	98.6	99.1	99.3	100.0
86.1	90.9	91.7	94.1	94.9	96.1	96.8	97.7	97.7	98.6	99.1	99.3	100.0

900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AU
MONTH: APR HOURS: 2

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CFIL	51.3	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
GE 20000	56.3	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6
GE 18000	56.8	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
GE 16000	57.0	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
GE 14000	58.2	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4
GE 12000	59.0	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
GE 10000	60.7	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
GE 9000	61.0	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
GE 8000	62.2	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
GE 7000	63.8	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
GE 6000	64.8	65.0	65.1	65.1	65.1	65.1	65.2	65.2	65.2	65.2	65.2	65.2
GE 5000	67.3	68.0	68.2	68.2	68.3	68.3	68.4	68.4	68.4	68.4	68.4	68.4
GE 4500	70.3	71.0	71.2	71.2	71.6	71.6	71.7	71.7	71.7	71.7	71.7	71.7
GE 4000	73.1	73.3	73.8	73.8	74.3	74.6	74.8	74.9	74.9	75.0	75.0	75.0
GE 3500	74.2	74.4	75.0	75.0	75.6	75.8	76.0	76.1	76.1	76.2	76.2	76.2
GE 3000	75.6	75.8	76.3	76.3	76.9	77.1	77.3	77.4	77.4	77.6	77.6	77.6
GE 2500	78.6	78.8	79.3	79.4	80.2	80.6	80.9	81.0	81.0	81.1	81.1	81.1
GE 2000	79.4	79.7	80.2	80.3	81.7	82.0	82.3	82.4	82.4	82.6	82.7	82.7
GE 1800	79.8	80.0	80.6	80.7	82.0	82.3	82.7	82.8	82.8	82.9	83.0	83.0
GE 1500	80.4	80.7	81.4	81.6	83.0	83.4	84.0	84.1	84.2	84.3	84.4	84.4
GE 1200	81.9	82.1	82.9	83.0	84.6	85.0	85.7	85.8	85.9	86.0	86.1	86.1
GE 1000	82.7	82.9	83.7	83.8	85.3	85.8	86.6	86.7	86.8	86.9	87.0	87.0
GE 900	82.9	83.1	83.9	84.0	85.7	86.2	87.0	87.1	87.2	87.3	87.6	87.6
GE 800	82.9	83.3	84.2	84.3	86.1	86.8	87.7	88.0	88.1	88.2	88.4	88.4
GE 700	83.3	83.8	84.7	84.8	86.8	87.4	88.3	89.0	89.1	89.2	89.4	89.4
GE 600	83.7	84.1	85.2	85.3	87.6	88.2	89.1	89.8	89.9	90.1	90.6	90.6
GE 500	84.0	84.4	85.6	85.7	88.1	88.8	90.4	91.1	91.8	92.0	92.4	92.4
GE 400	84.2	84.7	85.8	85.9	88.3	89.2	91.3	92.0	92.8	93.3	93.8	93.8
GE 300	84.3	84.8	85.9	86.0	88.8	89.7	92.0	93.0	94.2	94.9	95.6	95.6
GE 200	84.3	84.8	85.9	86.0	88.9	89.8	92.1	93.3	94.8	95.9	96.7	96.8
GE 100	84.3	84.8	85.9	86.0	88.9	89.8	92.1	93.3	94.9	96.1	96.9	97.0
GE 000	84.3	84.8	85.9	86.0	88.9	89.8	92.1	93.3	94.9	96.1	96.9	97.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: 21-23

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6
57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2	57.2
58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4	58.4
59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
65.1	65.1	65.1	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.2
68.2	68.3	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
71.2	71.6	71.6	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7	71.7
73.9	74.3	74.6	74.8	74.9	74.9	75.0	75.0	75.0	75.0	75.0	75.0	75.0
75.0	75.6	75.8	76.0	76.1	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2
76.3	76.9	77.1	77.3	77.4	77.4	77.6	77.6	77.6	77.6	77.6	77.6	77.6
79.4	80.2	80.6	80.9	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.1	81.1
80.3	81.7	82.0	82.3	82.4	82.4	82.6	82.7	82.7	82.7	82.7	82.7	82.7
80.7	82.0	82.3	82.7	82.8	82.8	82.9	83.0	83.0	83.0	83.0	83.0	83.0
81.6	83.0	83.4	84.0	84.1	84.2	84.3	84.4	84.4	84.4	84.4	84.4	84.4
83.0	84.6	85.0	85.7	85.8	85.9	86.0	86.1	86.1	86.2	86.2	86.2	86.2
83.8	85.3	85.8	86.6	86.7	86.8	86.9	87.0	87.0	87.3	87.3	87.3	87.3
84.0	85.7	86.2	87.0	87.1	87.2	87.3	87.6	87.6	87.9	87.9	87.9	87.9
84.3	86.1	86.8	87.7	88.0	88.1	88.2	88.4	88.4	88.9	88.9	88.9	88.9
84.9	86.8	87.4	88.3	89.0	89.1	89.2	89.4	89.4	90.0	90.0	90.0	90.0
85.3	87.6	88.2	89.1	89.8	89.9	90.1	90.6	90.6	91.1	91.1	91.1	91.1
85.7	88.1	88.8	90.4	91.1	91.8	92.0	92.4	92.4	93.0	93.0	93.0	93.0
85.9	88.3	89.2	91.3	92.0	92.8	93.3	93.8	93.8	94.3	94.4	94.4	94.4
86.0	88.8	89.7	92.0	93.0	94.2	94.9	95.6	95.6	96.1	96.2	96.4	96.7
86.0	88.9	89.8	92.1	93.3	94.8	95.9	96.7	96.8	97.6	97.7	98.2	98.8
86.0	88.9	89.8	92.1	93.3	94.9	96.1	96.9	97.0	98.1	98.2	99.2	100.0
86.0	88.9	89.8	92.1	93.3	94.9	96.1	96.9	97.0	98.1	98.2	99.2	100.0

900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: APR HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 1/4
NO CEIL	46.4	46.8	46.9	47.0	47.0	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1
GE 20000	51.5	52.0	52.1	52.2	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3
GE 18000	52.2	52.7	52.8	52.9	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
GE 16000	52.4	52.9	53.0	53.1	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
GE 14000	53.4	53.9	54.0	54.1	54.2	54.2	54.2	54.2	54.3	54.3	54.3	54.3	54.3	54.3
GE 12000	54.4	54.8	55.0	55.1	55.1	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2
GE 10000	56.7	57.1	57.3	57.4	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5
GE 9000	57.0	57.4	57.6	57.7	57.8	57.8	57.8	57.8	57.9	57.9	57.9	57.9	57.9	57.9
GE 8000	59.3	59.8	60.1	60.1	60.2	60.2	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3
GE 7000	60.3	60.8	61.1	61.1	61.2	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3	61.3
GE 6000	61.2	61.7	62.1	62.1	62.3	62.3	62.3	62.4	62.4	62.4	62.4	62.4	62.4	62.4
GE 5000	63.7	64.3	64.9	65.0	65.2	65.2	65.3	65.4	65.4	65.4	65.4	65.4	65.4	65.4
GE 4500	65.1	65.7	66.3	66.4	66.7	66.8	66.8	66.9	66.9	66.9	66.9	66.9	66.9	66.9
GE 4000	67.4	68.1	68.8	69.0	69.4	69.5	69.6	69.7	69.8	69.8	69.8	69.8	69.8	69.8
GE 3500	68.7	69.4	70.1	70.3	70.8	70.9	71.0	71.2	71.2	71.2	71.2	71.2	71.2	71.2
GE 3000	70.0	70.8	71.6	71.8	72.3	72.5	72.6	72.8	72.8	72.8	72.8	72.8	72.8	72.8
GE 2500	72.1	72.8	73.7	74.0	74.7	74.9	75.1	75.3	75.3	75.3	75.3	75.3	75.4	75.4
GE 2000	74.0	74.8	75.8	76.1	77.1	77.3	77.7	77.9	79.0	78.1	78.1	78.1	78.1	78.1
GE 1800	75.0	75.8	77.0	77.3	78.4	78.6	79.0	79.3	79.3	79.4	79.5	79.5	79.5	79.5
GE 1500	77.0	77.8	79.3	79.7	80.9	81.2	81.8	82.1	82.2	82.3	82.4	82.4	82.4	82.4
GE 1200	78.5	79.3	80.8	81.3	82.6	82.9	83.5	83.9	84.1	84.3	84.4	84.4	84.4	84.4
GF 1000	79.3	80.2	81.3	82.2	83.5	83.9	84.6	85.1	85.4	85.6	85.8	85.8	85.8	85.8
GE 900	79.6	80.5	82.2	82.7	84.2	84.6	85.2	85.8	86.1	86.3	86.6	86.6	86.6	86.6
GE 800	80.1	81.1	82.9	83.5	85.2	85.6	86.3	87.0	87.4	87.8	88.0	88.1	88.1	88.1
GE 700	80.4	81.4	83.3	83.9	85.7	86.1	87.0	87.8	88.3	88.6	88.9	89.0	89.0	89.0
GE 600	80.8	81.8	83.8	84.4	86.4	86.9	88.0	88.8	89.4	89.8	90.1	90.2	90.2	90.2
GE 500	81.0	82.1	84.2	85.0	87.3	87.9	89.4	90.4	91.1	91.6	92.0	92.2	92.2	92.2
GE 400	81.1	82.2	84.5	85.3	87.8	88.4	90.3	91.5	92.4	93.0	93.5	93.6	93.6	93.6
GE 300	81.1	82.3	84.6	85.4	88.1	88.8	90.8	92.3	93.6	94.3	95.0	95.2	95.2	95.2
GE 200	81.1	82.3	84.6	85.4	88.1	88.8	90.9	92.5	94.2	95.1	96.0	96.2	96.2	96.2
GE 100	81.1	82.3	84.6	85.4	88.1	88.8	90.9	92.6	94.3	95.2	96.2	96.4	96.4	96.4
GE 000	81.1	82.3	84.6	85.4	88.1	88.8	90.9	92.6	94.3	95.2	96.2	96.4	96.4	96.4

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR HOURS: ALL

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
47.0	47.0	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.1	47.2	47.2	47.2
52.2	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.3	52.4	52.4	52.4	52.4
52.9	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.1	53.1	53.1	53.1
53.1	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.3	53.3	53.3	53.3
54.1	54.2	54.2	54.2	54.2	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3
55.1	55.1	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.2	55.3	55.3	55.3
57.4	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.5	57.6	57.6	57.6	57.6
57.7	57.8	57.8	57.8	57.8	57.9	57.9	57.9	57.9	57.9	57.9	57.9	57.9
60.1	60.2	60.2	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.3	60.4	60.4
61.1	61.2	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
62.1	62.3	62.3	62.3	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
65.0	65.2	65.2	65.3	65.4	65.4	65.4	65.4	65.4	65.4	65.4	65.5	65.5
66.4	66.7	66.8	66.8	66.9	66.9	66.9	66.9	66.9	66.9	67.0	67.0	67.0
69.0	69.4	69.5	69.6	69.7	69.8	69.8	69.8	69.8	69.8	69.8	69.9	69.9
70.3	70.8	70.9	71.0	71.2	71.2	71.2	71.2	71.2	71.2	71.3	71.3	71.3
71.8	72.3	72.5	72.6	72.8	72.8	72.8	72.8	72.8	72.9	72.9	72.9	72.9
74.0	74.7	74.9	75.1	75.3	75.3	75.3	75.3	75.4	75.4	75.4	75.5	75.5
76.1	77.1	77.3	77.7	77.9	78.0	78.1	78.1	78.1	78.2	78.2	78.2	78.2
77.3	78.4	78.6	79.0	79.3	79.3	79.4	79.5	79.5	79.5	79.6	79.6	79.6
79.7	80.9	81.2	81.8	82.1	82.2	82.3	82.4	82.4	82.6	82.6	82.7	82.7
81.3	82.6	82.9	83.5	83.9	84.1	84.3	84.4	84.4	84.6	84.6	84.7	84.7
82.2	83.6	83.9	84.6	85.1	85.4	85.6	85.8	85.8	86.0	86.1	86.2	86.2
82.7	84.2	84.6	85.2	85.8	86.1	86.3	86.6	86.6	86.8	86.9	86.9	86.9
83.5	85.2	85.6	86.3	87.0	87.4	87.8	88.0	88.1	88.3	88.5	88.6	88.6
83.9	85.7	86.1	87.0	87.8	88.3	88.6	88.9	89.0	89.3	89.4	89.5	89.5
84.4	86.4	86.9	88.0	88.8	89.4	89.8	90.1	90.2	90.5	90.7	90.8	90.8
85.0	87.3	87.9	89.4	90.4	91.1	91.6	92.0	92.2	92.5	92.7	92.8	92.8
85.3	87.8	88.4	90.3	91.5	92.4	93.0	93.5	93.6	94.1	94.3	94.4	94.4
85.4	88.1	88.8	90.8	92.3	93.6	94.3	95.0	95.2	95.7	96.0	96.2	96.3
85.4	88.1	88.8	90.9	92.5	94.2	95.1	96.0	96.2	97.0	97.4	98.0	98.4
85.4	88.1	88.8	90.9	92.6	94.3	95.2	96.2	96.4	97.3	97.8	98.9	99.9
85.4	88.1	88.8	90.9	92.6	94.3	95.2	96.2	96.4	97.3	97.8	98.9	100.0

7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: MAY HOURS: 00

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	55.2	55.6	56.1	56.2	56.5	56.6	56.8	57.0	57.0	57.0	57.0	57.0
GE 20000	59.4	59.8	60.3	60.4	60.6	60.8	61.0	61.2	61.2	61.2	61.2	61.2
GE 18000	59.5	59.9	60.4	60.5	60.8	60.9	61.1	61.3	61.3	61.3	61.3	61.3
GF 16000	59.5	59.9	60.4	60.5	60.8	60.9	61.1	61.3	61.3	61.3	61.3	61.3
GE 14000	59.6	60.0	60.5	60.6	60.9	61.0	61.2	61.4	61.4	61.4	61.4	61.4
GE 12000	60.9	61.3	61.9	62.0	62.3	62.4	62.6	62.8	62.8	62.8	62.8	62.8
GE 10000	64.0	64.4	65.3	65.5	65.7	65.8	66.0	66.2	66.2	66.2	66.2	66.2
GE 9000	64.5	64.9	65.8	66.0	66.2	66.3	66.6	66.8	66.8	66.8	66.8	66.8
GE 8000	67.3	67.7	68.6	68.8	69.0	69.1	69.4	69.6	69.6	69.6	69.6	69.6
GE 7000	68.7	69.1	70.0	70.3	70.5	70.6	70.9	71.1	71.1	71.1	71.1	71.1
GE 6000	70.4	70.9	71.7	72.2	72.4	72.5	72.7	72.9	72.9	72.9	72.9	72.9
GE 5000	71.8	72.4	73.2	73.7	73.9	74.0	74.2	74.4	74.4	74.4	74.4	74.4
GE 4500	73.4	74.0	74.9	75.4	75.6	75.7	75.9	76.1	76.1	76.1	76.1	76.1
GE 4000	75.5	76.1	77.2	77.7	78.4	78.7	78.9	79.2	79.2	79.2	79.2	79.2
GE 3500	76.3	77.0	78.1	78.6	79.2	79.6	79.8	80.1	80.1	80.1	80.1	80.1
GE 3000	76.8	77.4	78.6	79.1	80.1	80.4	80.6	81.0	81.0	81.0	81.0	81.0
GE 2500	77.3	78.0	79.1	79.7	80.6	81.1	81.3	81.6	81.6	81.6	81.6	81.6
GE 2000	78.6	79.2	80.4	81.0	81.9	82.5	82.7	83.0	83.0	83.0	83.0	83.0
GE 1800	79.1	79.8	81.0	81.5	82.6	83.1	83.3	83.7	83.7	83.7	83.7	83.7
GE 1500	80.2	80.9	82.0	82.6	83.7	84.2	84.4	84.7	84.7	84.7	84.7	84.7
GE 1200	81.0	81.6	82.9	83.4	84.5	85.1	85.4	85.7	85.7	85.7	85.7	85.7
GE 1000	81.4	82.0	83.4	84.0	85.3	85.8	86.2	86.6	86.6	86.6	86.6	86.6
GE 900	81.8	82.6	84.1	84.6	85.1	86.7	87.1	87.4	87.4	87.4	87.4	87.4
GE 800	82.2	82.9	84.4	84.9	85.5	87.0	87.4	87.7	87.7	87.7	87.7	87.7
GE 700	82.5	83.2	84.8	85.4	86.9	87.4	88.0	88.3	88.3	88.3	88.3	88.3
GE 600	82.7	83.4	85.1	85.6	87.2	87.8	88.4	88.7	88.7	88.7	88.7	88.7
GE 500	82.7	83.5	85.5	86.2	88.4	89.1	90.0	90.6	90.6	90.6	90.6	90.6
GE 400	82.8	83.7	86.0	86.8	89.0	89.8	91.0	91.9	92.2	92.2	92.2	92.2
GE 300	82.9	83.9	86.2	87.1	89.7	90.5	91.9	93.5	93.9	94.4	94.4	94.4
GE 200	82.9	84.0	86.3	87.2	90.0	90.9	92.5	94.8	95.6	96.7	97.0	97.1
GF 100	82.9	84.0	86.3	87.3	90.1	91.0	92.6	94.9	95.7	97.0	97.5	97.6
GE 000	82.9	84.0	86.3	87.3	90.1	91.0	92.6	94.9	95.7	97.0	97.5	97.6

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 00-02

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0	56.2	56.5	56.6	56.8	57.0	57.0	57.0	57.0	57.0	57.0	57.1	57.1	57.1
2	60.4	60.6	60.8	61.0	61.2	61.2	61.2	61.2	61.2	61.2	61.3	61.3	61.3
3	60.5	60.8	60.9	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.4	61.4	61.4
4	60.5	60.8	60.9	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.4	61.4	61.4
8	60.6	60.9	61.0	61.2	61.4	61.4	61.4	61.4	61.4	61.4	61.5	61.5	61.5
9	62.0	62.3	62.4	62.6	62.8	62.8	62.8	62.8	62.8	62.8	62.9	62.9	62.9
2	65.5	65.7	65.8	66.0	66.2	66.2	66.2	66.2	66.2	66.2	66.3	66.3	66.3
8	66.0	66.2	66.3	66.6	66.8	66.8	66.8	66.8	66.8	66.8	66.9	66.9	66.9
6	68.8	69.0	69.1	69.4	69.6	69.6	69.6	69.6	69.6	69.6	69.7	69.7	69.7
1	70.3	70.5	70.6	70.9	71.1	71.1	71.1	71.1	71.1	71.1	71.2	71.2	71.2
9	72.2	72.4	72.5	72.7	72.9	72.9	72.9	72.9	72.9	72.9	73.0	73.0	73.0
4	73.7	73.9	74.0	74.2	74.4	74.4	74.4	74.4	74.4	74.4	74.5	74.5	74.5
2	75.4	75.6	75.7	75.9	76.1	76.1	76.1	76.1	76.1	76.1	76.2	76.2	76.2
1	77.7	78.4	78.7	78.9	79.2	79.2	79.2	79.2	79.2	79.2	79.4	79.4	79.4
0	78.6	79.2	79.6	79.8	80.1	80.1	80.1	80.1	80.1	80.1	80.2	80.2	80.2
5	79.1	80.1	80.4	80.6	81.0	81.0	81.0	81.0	81.0	81.0	81.1	81.1	81.1
6	81.7	81.6	81.1	81.3	81.6	81.6	81.6	81.6	81.6	81.6	81.7	81.7	81.7
2	81.0	81.9	82.5	82.7	83.0	83.0	83.0	83.0	83.0	83.0	83.1	83.1	83.1
7	81.5	82.6	83.1	83.3	83.7	83.7	83.7	83.7	83.7	83.7	83.8	83.8	83.8
7	82.6	83.7	84.2	84.4	84.7	84.7	84.7	84.7	84.7	84.7	84.8	84.8	84.8
7	83.4	84.5	85.1	85.4	85.7	85.7	85.7	85.7	85.7	85.7	85.8	85.8	85.8
5	84.0	85.3	85.8	86.2	86.6	86.6	86.6	86.6	86.6	86.6	86.7	86.7	86.7
1	84.6	85.1	86.7	87.1	87.4	87.4	87.4	87.4	87.4	87.4	87.5	87.5	87.5
4	84.9	85.5	87.0	87.4	87.7	87.7	87.7	87.7	87.7	87.7	87.8	87.8	87.8
7	85.4	86.7	87.4	88.0	88.3	88.3	88.3	88.3	88.3	88.3	88.4	88.4	88.4
1	85.6	87.2	87.8	88.4	88.7	88.7	88.7	88.7	88.7	88.7	88.8	88.8	88.8
5	86.2	88.4	89.1	90.0	90.6	90.6	90.6	90.6	90.6	90.6	90.8	90.8	90.8
0	86.8	89.0	89.8	91.0	91.9	92.2	92.2	92.2	92.2	92.2	92.3	92.3	92.3
2	87.1	89.7	90.5	91.9	93.5	93.9	94.4	94.4	94.4	94.4	94.5	94.5	94.5
3	87.2	90.0	90.9	92.5	94.8	95.6	96.7	97.0	97.1	97.4	97.6	98.4	98.7
3	87.3	90.1	91.0	92.6	94.9	95.7	97.0	97.5	97.6	98.4	98.6	99.5	100.0
3	87.3	90.1	91.0	92.6	94.9	95.7	97.0	97.5	97.6	98.4	98.6	99.5	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: MAY HOURS: 03

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	52.4	52.6	53.5	54.0	54.3	54.4	54.5	54.7	54.7	54.8	54.8	54.8
GE 20000	56.8	57.1	58.1	58.5	58.8	58.9	59.0	59.2	59.2	59.4	59.4	59.4
GE 18000	56.8	57.1	58.1	58.5	58.8	58.9	59.0	59.2	59.2	59.4	59.4	59.4
GE 15000	56.9	57.2	58.2	58.6	58.9	59.0	59.1	59.4	59.4	59.5	59.5	59.5
GE 14000	57.3	57.5	58.6	59.0	59.4	59.5	59.6	59.8	59.8	59.9	59.9	59.9
GE 12000	57.6	58.0	58.9	59.4	59.7	59.8	59.9	60.1	60.1	60.2	60.2	60.2
GE 10000	61.0	61.4	62.5	63.0	63.5	63.7	63.8	64.2	64.2	64.3	64.3	64.3
GE 9000	61.4	61.8	62.9	63.4	64.1	64.2	64.3	64.7	64.7	64.8	64.8	64.8
GE 8000	62.7	63.1	64.2	64.7	65.4	65.5	65.6	66.0	66.1	66.2	66.2	66.2
GE 7000	64.1	64.5	65.7	66.3	67.0	67.1	67.2	67.6	67.7	67.8	67.8	67.8
GE 6000	64.5	64.9	66.1	66.8	67.4	67.5	67.5	68.1	68.2	68.3	68.3	68.3
GE 5000	66.1	66.6	67.8	68.5	69.2	69.4	69.6	70.1	70.3	70.4	70.4	70.4
GE 4500	67.4	68.0	69.2	69.9	70.6	70.8	71.0	71.5	71.7	71.8	71.8	71.8
GE 4000	70.4	71.0	72.4	73.0	73.8	73.9	74.2	74.8	75.1	75.2	75.2	75.2
GE 3500	71.5	72.0	73.4	74.2	75.1	75.2	75.6	76.2	76.5	76.6	76.6	76.6
GE 3000	72.6	73.2	74.9	75.9	76.8	76.9	77.3	78.0	78.2	78.3	78.3	78.3
GE 2500	73.3	74.0	75.7	76.8	77.6	77.7	78.2	78.8	79.0	79.1	79.1	79.1
GE 2000	75.3	75.9	77.6	78.5	79.7	79.8	80.2	80.9	81.1	81.2	81.2	81.2
GE 1800	76.2	76.9	78.6	79.5	80.6	80.8	81.2	81.8	82.0	82.2	82.2	82.2
GE 1500	77.7	78.4	80.2	81.6	82.6	82.7	83.3	84.0	84.2	84.3	84.3	84.3
GE 1200	78.1	78.7	80.5	81.9	82.9	83.0	83.7	84.3	84.5	84.6	84.6	84.6
GE 1000	78.8	79.5	81.3	82.7	83.9	84.1	84.8	85.6	85.8	85.9	85.9	85.9
GE 900	79.1	79.5	81.5	83.1	84.4	84.7	85.5	86.2	86.5	86.6	86.6	86.6
GE 800	79.5	80.1	81.9	83.4	84.7	85.1	85.9	86.6	86.8	86.9	86.9	86.9
GE 700	79.9	80.5	82.4	84.1	85.4	85.7	86.6	87.3	87.5	87.6	87.6	87.6
GE 600	80.5	81.3	83.2	85.1	86.3	86.7	87.5	88.4	88.6	88.7	88.7	88.7
GE 500	81.5	82.5	84.5	86.7	88.3	88.7	90.0	90.9	91.1	91.2	91.2	91.2
GE 400	81.7	82.5	84.6	86.9	88.7	89.1	91.0	92.2	92.7	92.8	92.8	92.8
GE 300	81.7	82.5	84.6	86.9	88.9	89.4	91.4	93.2	94.1	94.5	94.6	94.6
GE 200	81.7	82.6	84.6	86.9	89.2	89.7	92.0	94.2	95.2	95.9	96.5	96.6
GE 100	81.7	82.5	84.6	86.9	89.2	89.7	92.2	94.4	95.4	96.2	96.9	97.0
GE 000	81.7	82.6	84.6	86.9	89.2	89.7	92.2	94.4	95.4	96.2	96.9	97.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 03-05

VISIBILITY IN STATUTE MILES

4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
54.0	54.3	54.4	54.5	54.7	54.7	54.8	54.8	54.8	55.1	55.1	55.2	55.2
54.5	54.8	54.9	55.0	55.2	55.2	55.4	55.4	55.4	55.6	55.6	55.7	55.7
54.6	54.9	55.0	55.1	55.4	55.4	55.5	55.5	55.5	55.7	55.7	55.8	55.8
54.7	55.4	55.5	55.6	55.8	55.8	55.9	55.9	55.9	60.1	60.1	60.2	60.2
54.8	55.7	55.8	55.9	60.1	60.1	60.2	60.2	60.2	60.4	60.4	60.5	60.5
63.0	63.5	63.7	63.8	64.2	64.2	64.3	64.3	64.3	64.5	64.5	64.6	64.6
63.4	64.1	64.2	64.3	64.7	64.7	64.8	64.8	64.8	65.1	65.1	65.2	65.2
64.7	65.4	65.5	65.6	66.0	66.1	66.2	66.2	66.2	66.5	66.5	66.6	66.6
65.3	67.0	67.1	67.2	67.6	67.7	67.8	67.8	67.8	68.1	68.1	68.2	68.2
65.4	67.4	67.5	67.6	68.1	68.2	68.3	68.3	68.3	68.5	68.5	68.6	68.6
69.5	69.2	69.4	69.6	70.1	70.3	70.4	70.4	70.4	70.6	70.6	70.8	70.8
70.7	70.6	70.8	71.0	71.5	71.7	71.8	71.8	71.8	72.0	72.0	72.2	72.2
73.0	73.3	73.9	74.2	74.8	75.1	75.2	75.2	75.2	75.4	75.4	75.5	75.5
74.2	75.1	75.2	75.6	76.2	76.5	76.6	76.6	76.6	76.8	76.8	76.9	76.9
75.7	76.3	76.9	77.3	78.0	78.2	78.3	78.3	78.3	78.5	78.5	78.6	78.6
76.5	77.6	77.7	78.2	78.8	79.0	79.1	79.1	79.1	79.4	79.4	79.5	79.5
79.5	79.7	79.8	80.2	80.9	81.1	81.2	81.2	81.2	81.4	81.4	81.5	81.5
80.0	80.6	80.8	81.2	81.8	82.0	82.2	82.2	82.2	82.4	82.4	82.5	82.5
81.6	82.6	82.7	83.3	84.0	84.2	84.3	84.3	84.3	84.5	84.5	84.6	84.6
81.9	82.9	83.0	83.7	84.3	84.5	84.6	84.6	84.6	84.8	84.8	84.9	84.9
85.7	83.9	84.1	84.8	85.6	85.8	85.9	85.9	85.9	86.1	86.1	86.2	86.2
86.1	84.4	84.7	85.5	86.2	86.5	86.6	86.6	86.6	86.8	86.8	86.9	86.9
86.4	84.7	85.1	85.8	86.6	86.8	86.9	86.9	86.9	87.1	87.1	87.2	87.2
86.1	85.4	85.7	86.6	87.3	87.5	87.6	87.6	87.6	87.8	87.8	88.0	88.0
86.1	86.3	86.7	87.6	88.4	88.6	88.7	88.7	88.7	88.9	88.9	89.0	89.0
86.7	83.3	88.7	90.0	90.9	91.1	91.2	91.2	91.2	91.4	91.4	91.5	91.5
86.9	83.7	89.1	91.0	92.2	92.7	92.8	92.8	92.8	93.0	93.0	93.1	93.1
86.9	89.9	89.4	91.4	93.2	94.1	94.5	94.6	94.6	95.1	95.1	95.2	95.2
86.7	89.2	89.7	92.0	94.2	95.2	95.9	96.5	96.6	97.3	97.4	97.7	98.2
86.9	89.2	89.7	92.2	94.4	95.4	96.2	96.9	97.0	98.1	98.2	99.1	100.0
86.9	89.2	89.7	92.2	94.4	95.4	96.2	96.9	97.0	98.1	98.2	99.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AL
MONTH: MAY HOURS: C

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	45.8	46.5	46.8	47.0	47.4	47.6	47.7	47.7	47.7	47.8	48.0	48.0
GE 20000	52.6	53.2	53.8	54.0	54.6	54.8	54.9	54.9	54.9	55.1	55.2	55.2
GE 18000	52.9	53.7	54.2	54.4	55.1	55.3	55.5	55.5	55.5	55.6	55.7	55.7
GE 16000	53.1	53.9	54.4	54.6	55.3	55.5	55.7	55.7	55.7	55.8	55.9	55.9
GE 14000	53.3	54.1	54.6	54.8	55.5	55.7	55.9	55.9	55.9	56.0	56.1	56.1
GE 12000	54.1	54.9	55.5	55.8	56.5	56.7	56.9	56.9	56.9	57.0	57.1	57.1
GE 10000	56.7	57.5	58.1	58.7	59.5	59.7	59.9	59.9	60.0	60.1	60.2	60.2
GE 9000	57.4	58.3	58.3	59.5	60.2	60.4	60.8	60.8	60.9	61.0	61.1	61.1
GE 8000	59.3	60.6	61.2	62.0	62.8	63.0	63.4	63.4	63.5	63.7	63.8	63.8
GE 7000	62.3	63.1	64.0	64.8	65.7	66.0	66.6	66.6	66.7	66.8	66.9	66.9
GE 6000	63.0	63.9	64.7	66.0	67.0	67.3	67.8	67.8	68.0	68.1	68.2	68.2
GE 5000	64.9	65.9	66.9	68.2	69.7	70.1	70.6	70.8	71.0	71.1	71.2	71.2
GE 4500	65.8	66.8	67.8	69.1	70.6	71.1	71.8	71.9	72.2	72.3	72.4	72.4
GE 4000	68.3	69.2	70.4	71.7	73.2	73.7	74.4	74.7	75.1	75.2	75.3	75.3
GE 3500	68.8	70.0	71.2	72.5	74.0	74.4	75.2	75.6	75.9	76.0	76.1	76.1
GE 3000	70.4	71.7	72.9	74.2	75.7	76.3	77.1	77.5	77.8	78.0	78.1	78.1
GE 2500	71.2	72.5	73.3	75.1	76.8	77.5	78.3	78.7	79.0	79.1	79.2	79.2
GE 2000	73.1	74.5	75.3	77.1	78.9	79.7	80.4	80.9	81.2	81.3	81.4	81.4
GE 1800	73.4	74.8	76.1	77.5	79.4	80.1	80.9	81.3	81.6	81.7	81.8	81.8
GE 1500	74.9	76.5	77.8	79.7	81.7	82.5	83.2	83.7	84.0	84.1	84.2	84.2
GE 1200	76.5	78.0	79.7	81.5	83.7	84.4	85.3	85.7	86.0	86.1	86.2	86.2
GE 1000	77.7	79.2	81.2	83.0	85.5	86.3	87.3	87.7	88.1	88.2	88.3	88.3
GE 900	78.3	79.8	81.7	83.7	86.3	87.2	88.2	88.6	88.9	89.0	89.1	89.1
GE 800	78.5	80.0	82.2	84.1	86.8	87.6	88.7	89.1	89.5	89.6	89.7	89.7
GE 700	78.8	80.3	82.5	84.6	87.7	88.7	89.9	90.3	90.6	90.8	90.9	90.9
GE 600	79.0	80.5	82.7	84.9	88.3	89.2	90.4	90.9	91.2	91.3	91.4	91.4
GE 500	79.1	80.6	82.8	85.1	88.5	89.6	91.4	91.8	92.3	92.4	92.5	92.5
GE 400	79.4	80.9	83.0	85.3	88.8	90.0	92.4	93.1	93.5	93.8	93.9	93.9
GE 300	79.5	81.0	83.1	85.4	89.5	90.6	93.3	94.2	95.4	95.8	96.0	96.1
GE 200	79.5	81.0	83.1	85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.0	97.1
GE 100	79.5	81.0	83.1	85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.1	97.3
GE 000	79.5	81.0	83.1	85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.1	97.3

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAY HOURS: 06-08

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
47.0	47.4	47.6	47.7	47.7	47.7	47.8	48.0	48.0	48.1	48.1	48.2	48.2
54.0	54.6	54.8	54.9	54.9	54.9	55.1	55.2	55.2	55.3	55.3	55.5	55.5
54.4	55.1	55.3	55.5	55.5	55.5	55.6	55.7	55.7	55.8	55.8	56.0	56.0
54.6	55.3	55.5	55.7	55.7	55.7	55.8	55.9	55.9	56.0	56.0	56.2	56.2
54.8	55.5	55.7	55.9	55.9	55.9	56.0	56.1	56.1	56.2	56.2	56.5	56.5
55.8	56.5	56.7	56.9	56.9	56.9	57.0	57.1	57.1	57.2	57.2	57.4	57.4
58.7	59.5	59.7	59.9	59.9	60.0	60.1	60.2	60.2	60.3	60.3	60.5	60.6
59.5	60.2	60.4	60.8	60.8	60.9	61.0	61.1	61.1	61.2	61.2	61.4	61.5
62.0	62.8	63.0	63.4	63.4	63.5	63.7	63.8	63.8	63.9	63.9	64.1	64.2
64.8	65.7	66.0	66.6	66.6	66.7	66.8	66.9	66.9	67.0	67.0	67.2	67.3
66.0	67.0	67.3	67.8	67.8	68.0	68.1	68.2	68.2	68.3	68.3	68.5	68.6
68.2	69.7	70.1	70.6	70.8	71.0	71.1	71.2	71.2	71.3	71.3	71.5	71.6
69.1	70.6	71.1	71.8	71.9	72.2	72.3	72.4	72.4	72.5	72.5	72.7	72.8
71.7	73.2	73.7	74.4	74.7	75.1	75.2	75.3	75.3	75.4	75.4	75.6	75.7
72.5	74.0	74.4	75.2	75.6	75.9	76.0	76.1	76.1	76.2	76.2	76.5	76.6
74.2	75.7	76.3	77.1	77.5	77.8	78.0	78.1	78.1	78.2	78.2	78.4	78.6
75.1	76.8	77.5	78.3	78.7	79.0	79.1	79.2	79.2	79.4	79.4	79.6	79.8
77.1	78.9	79.7	80.4	80.9	81.2	81.3	81.4	81.4	81.5	81.5	81.7	81.9
77.5	79.4	80.1	80.9	81.3	81.6	81.7	81.8	81.8	81.9	81.9	82.2	82.4
79.7	81.7	82.5	83.2	83.7	84.0	84.1	84.2	84.2	84.3	84.3	84.5	84.7
81.5	83.7	84.4	85.3	85.7	86.0	86.1	86.2	86.2	86.3	86.3	86.6	86.8
83.0	85.5	86.3	87.3	87.7	88.1	88.2	88.3	88.3	88.4	88.4	88.6	88.8
83.7	85.3	87.2	88.2	88.6	88.9	89.0	89.1	89.1	89.2	89.2	89.5	89.7
84.1	86.8	87.6	88.7	89.1	89.5	89.6	89.7	89.7	89.8	89.8	90.0	90.2
84.6	87.7	88.7	89.9	90.3	90.6	90.8	90.9	90.9	91.0	91.0	91.2	91.4
84.9	88.3	89.2	90.4	90.9	91.2	91.3	91.4	91.4	91.5	91.5	91.7	91.9
85.1	88.5	89.6	91.4	91.8	92.3	92.4	92.5	92.5	92.6	92.6	92.8	93.0
85.3	88.8	90.0	92.4	93.1	93.5	93.8	93.9	93.9	94.1	94.1	94.3	94.5
85.4	89.5	90.6	93.3	94.2	95.4	95.8	96.0	96.1	96.5	96.6	96.8	97.0
85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.0	97.1	97.7	98.0	98.3	98.8
85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.1	97.3	98.0	98.2	99.1	100.0
85.4	89.5	90.6	93.7	94.6	96.0	96.7	97.1	97.3	98.0	98.2	99.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: A
MONTH: MAY HOURS: C

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	44.1	45.4	45.7	46.0	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
GE 20000	53.1	54.4	54.7	55.2	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4
GE 18000	53.3	54.6	54.9	55.4	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6
GE 16000	53.8	55.1	55.4	55.8	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
GE 14000	53.9	55.2	55.5	55.9	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1
GE 12000	54.6	56.1	56.5	56.9	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
GE 10000	57.2	58.7	59.1	59.8	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0
GE 9000	57.8	59.4	59.8	60.4	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6
GE 8000	59.8	61.3	61.7	62.4	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
GE 7000	61.1	62.7	63.3	64.0	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
GE 6000	63.4	65.2	66.0	66.9	67.2	67.2	67.3	67.3	67.3	67.3	67.3	67.3
GE 5000	64.9	66.8	67.6	68.5	68.9	68.9	69.5	69.5	69.5	69.5	69.5	69.5
GE 4500	65.6	67.4	68.5	69.4	69.8	69.8	70.5	70.5	70.5	70.5	70.5	70.5
GE 4000	67.3	69.1	70.2	71.1	71.7	71.7	72.5	72.5	72.5	72.5	72.5	72.5
GE 3500	68.3	70.1	71.2	72.2	72.9	72.9	73.7	73.7	73.7	73.7	73.7	73.7
GE 3000	70.5	72.4	73.5	74.5	75.3	75.3	76.0	76.1	76.1	76.1	76.1	76.1
GE 2500	72.6	74.4	75.6	76.6	77.4	77.4	78.2	78.3	78.3	78.3	78.3	78.3
GE 2000	74.5	76.5	78.0	78.9	79.9	79.9	80.8	80.9	81.0	81.1	81.2	81.2
GE 1800	74.7	76.7	78.2	79.1	80.1	80.1	81.0	81.2	81.3	81.4	81.5	81.5
GE 1500	77.7	79.9	81.5	82.6	83.8	83.9	84.8	85.2	85.3	85.4	85.5	85.5
GE 1200	78.9	81.2	83.0	84.1	85.4	85.5	86.5	86.8	86.9	87.0	87.1	87.1
GE 1000	79.8	82.0	84.0	85.2	86.6	86.8	87.7	88.1	88.2	88.3	88.4	88.4
GE 900	80.4	82.7	84.6	86.0	87.4	87.7	88.7	89.0	89.1	89.2	89.4	89.4
GE 800	81.2	83.4	85.7	87.2	88.7	89.1	90.2	90.5	90.6	90.8	90.9	90.9
GE 700	81.4	83.7	86.0	87.5	89.1	89.9	91.3	91.7	91.8	91.9	92.0	92.0
GE 600	81.7	84.0	86.5	88.0	89.8	90.5	92.0	92.5	92.6	92.7	92.8	92.8
GE 500	81.9	84.3	86.8	88.4	90.5	91.7	93.4	94.2	94.6	94.7	94.9	94.9
GE 400	81.9	84.3	87.0	88.6	91.0	92.6	94.7	95.8	96.5	96.7	96.9	96.9
GE 300	81.9	84.3	87.0	88.9	91.4	93.1	95.3	96.8	97.7	98.1	98.4	98.5
GE 200	81.9	84.3	87.0	88.9	91.4	93.1	95.3	96.9	98.1	98.4	98.8	98.9
GE 100	81.9	84.3	87.0	88.9	91.4	93.1	95.3	96.9	98.3	98.6	99.0	99.2
GE 000	81.9	84.3	87.0	88.9	91.4	93.1	95.3	96.9	98.3	98.6	99.0	99.2

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 09-11

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
46.0	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
55.2	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4
55.4	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6
55.8	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
55.9	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1
56.9	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
59.8	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0
60.4	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6
62.4	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
64.0	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
66.9	67.2	67.2	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3
68.5	68.9	68.9	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5
69.4	69.8	69.8	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5	70.5
71.1	71.7	71.7	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5
72.2	72.9	72.9	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
74.5	75.3	75.3	76.0	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1
76.6	77.4	77.4	78.2	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3
78.9	79.9	79.9	80.3	80.9	81.0	81.1	81.2	81.2	81.2	81.2	81.2	81.2
79.1	80.1	80.1	81.0	81.2	81.3	81.4	81.5	81.5	81.5	81.5	81.5	81.5
82.6	83.8	83.9	84.8	85.2	85.3	85.4	85.5	85.5	85.5	85.5	85.5	85.5
84.1	85.4	85.5	86.5	86.8	86.9	87.0	87.1	87.1	87.1	87.1	87.1	87.1
85.2	86.6	86.8	87.7	88.1	88.2	88.3	88.4	88.4	88.4	88.4	88.4	88.4
86.0	87.4	87.7	88.7	89.0	89.1	89.2	89.4	89.4	89.4	89.4	89.4	89.4
87.2	88.7	89.1	90.2	90.5	90.6	90.8	90.9	90.9	90.9	90.9	90.9	90.9
87.5	89.1	89.9	91.3	91.7	91.8	91.9	92.0	92.0	92.0	92.0	92.0	92.0
88.0	89.8	90.5	92.0	92.5	92.6	92.7	92.8	92.8	92.8	92.8	92.8	92.8
88.4	90.5	91.7	93.4	94.2	94.6	94.7	94.9	94.9	94.9	94.9	94.9	94.9
88.6	91.0	92.6	94.7	95.8	96.5	96.7	96.9	96.9	96.9	96.9	96.9	96.9
88.9	91.4	93.1	95.3	96.8	97.7	98.1	98.4	98.5	98.5	98.6	98.6	98.6
88.9	91.4	93.1	95.3	96.9	98.1	98.4	98.8	98.9	99.0	99.2	99.4	99.4
88.9	91.4	93.1	95.3	96.9	98.3	98.6	99.0	99.2	99.4	99.7	100.0	100.0
88.9	91.4	93.1	95.3	96.9	98.3	98.6	99.0	99.2	99.4	99.7	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: MAY HOURS: 12-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	1	
NO CEIL	45.3	45.8	45.8	45.9	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	4
GE 20000	55.3	55.8	56.1	56.2	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	5
GE 18000	55.3	55.8	56.3	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	5
GE 16000	55.3	55.8	56.3	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	5
GE 14000	55.9	56.5	57.0	57.2	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	5
GE 12000	56.9	57.5	58.1	58.3	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	5
GE 10000	58.6	59.2	60.0	60.2	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	6
GE 9000	59.4	60.0	60.8	61.0	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	6
GE 8000	61.2	61.8	62.7	62.9	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	6
GE 7000	62.8	63.5	64.4	64.5	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	6
GE 6000	64.4	65.3	66.1	66.6	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	6
GE 5000	66.5	67.3	68.2	68.6	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	6
GE 4500	67.5	68.6	69.5	69.9	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	7
GE 4000	71.2	72.2	73.4	73.9	74.3	74.3	74.3	74.4	74.4	74.4	74.4	74.4	74.4	7
GE 3500	73.2	74.2	75.6	76.1	76.8	76.8	76.8	76.9	76.9	76.9	76.9	76.9	76.9	7
GE 3000	76.5	77.4	78.8	79.4	80.0	80.0	80.0	80.1	80.1	80.1	80.1	80.1	80.1	8
GE 2500	77.3	78.4	79.9	80.4	81.1	81.1	81.1	81.3	81.3	81.3	81.3	81.3	81.3	8
GE 2000	79.9	81.0	82.5	83.0	83.9	83.9	83.9	84.1	84.3	84.3	84.3	84.3	84.3	8
GE 1800	80.4	81.5	83.1	83.7	84.5	84.5	84.5	84.7	84.9	84.9	84.9	84.9	84.9	8
GE 1500	82.7	83.8	86.0	86.6	87.6	87.6	87.6	87.8	88.1	88.1	88.1	88.1	88.1	8
GE 1200	84.0	85.1	87.4	88.0	89.1	89.4	89.4	89.6	89.8	89.8	89.8	89.8	89.8	9
GE 1000	84.4	85.5	87.8	88.4	89.8	90.0	90.1	90.3	90.5	90.5	90.5	90.5	90.5	9
GE 900	84.9	86.0	88.4	88.9	90.3	90.5	90.6	91.0	91.2	91.2	91.2	91.2	91.2	9
GE 800	85.2	86.2	88.6	89.2	90.6	90.9	91.1	91.4	91.6	91.6	91.6	91.6	91.6	9
GE 700	85.5	86.6	89.0	89.9	91.3	91.6	92.0	92.4	92.6	92.6	92.6	92.6	92.6	9
GE 600	85.8	86.9	89.5	90.5	92.2	92.6	93.0	93.4	93.7	93.7	93.7	93.7	93.7	9
GE 500	86.0	87.2	90.1	91.7	93.3	94.1	94.7	95.8	96.5	96.5	96.7	96.7	96.7	9
GE 400	86.0	87.3	90.2	91.9	94.0	94.8	95.6	97.0	97.7	97.7	98.1	98.1	98.1	9
GE 300	86.0	87.3	90.2	92.0	94.1	94.9	95.7	97.3	98.3	98.3	98.6	98.6	98.6	9
GE 200	86.0	87.3	90.2	92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.5	9
GE 100	86.0	87.3	90.2	92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.5	9
GE 000	86.0	87.3	90.2	92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.5	9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAY HOURS: 12-14

VISIBILITY IN STATUTE MILES												
GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
45.9	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
56.2	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
57.2	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
58.3	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5
60.2	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4
61.0	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
62.9	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
64.5	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9
66.6	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9
68.6	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
69.9	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
73.7	74.3	74.3	74.3	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
76.1	76.8	76.8	76.8	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
79.4	80.0	80.0	80.0	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
80.4	81.1	81.1	81.1	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3
83.0	83.9	83.9	83.9	84.1	84.3	84.3	84.3	84.3	84.6	84.6	84.6	84.6
83.7	84.5	84.5	84.5	84.7	84.9	84.9	84.9	84.9	85.3	85.3	85.3	85.3
86.6	87.6	87.6	87.6	87.8	88.1	88.1	88.1	88.1	88.4	88.4	88.4	88.4
88.0	89.1	89.4	89.4	89.6	89.8	89.8	89.8	89.8	90.1	90.1	90.1	90.1
88.4	89.8	90.0	90.1	90.3	90.5	90.5	90.5	90.5	90.9	90.9	90.9	90.9
90.9	90.3	90.5	90.6	91.0	91.2	91.2	91.2	91.2	91.5	91.5	91.5	91.5
90.2	90.6	90.9	91.1	91.4	91.6	91.6	91.6	91.6	91.9	91.9	91.9	91.9
89.9	91.3	91.6	92.0	92.4	92.6	92.6	92.6	92.6	92.9	92.9	92.9	92.9
90.5	92.2	92.6	93.0	93.4	93.7	93.7	93.7	93.7	94.0	94.0	94.0	94.0
91.7	93.3	94.1	94.7	95.8	96.5	96.5	96.7	96.7	97.0	97.0	97.0	97.0
91.9	94.0	94.8	95.6	97.0	97.7	97.7	98.1	98.1	98.4	98.4	98.4	98.4
92.0	94.1	94.9	95.7	97.3	98.3	98.3	98.6	98.6	99.0	99.0	99.0	99.0
92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.9	99.9	99.9	99.9
92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.9	99.9	99.9	100.0
92.0	94.1	95.1	95.9	97.8	98.9	99.0	99.5	99.5	99.9	99.9	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: MAY HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GF 7	GE 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	45.3	45.6	45.9	46.0	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5
GE 20000	56.2	56.7	57.3	57.4	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8
GE 18000	56.7	57.1	57.7	57.8	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
GE 16000	57.1	57.5	58.2	58.3	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
GE 14000	58.2	58.6	59.2	59.4	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8
GE 12000	59.5	59.9	60.8	60.9	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
GE 10000	61.8	62.3	63.1	63.2	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
GE 9000	62.6	63.0	63.9	64.0	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
GE 8000	65.7	66.1	67.0	67.1	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5
GE 7000	67.2	67.6	68.5	68.6	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
GE 6000	68.2	68.7	69.7	69.9	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
GF 5000	71.4	72.0	73.0	73.2	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
GE 4500	73.7	74.4	75.4	75.6	75.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1
GE 4000	76.2	77.0	78.3	78.5	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
GE 3500	78.2	78.9	80.5	80.8	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3
GE 3000	80.1	80.9	82.6	82.8	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
GE 2500	81.4	82.3	84.2	84.6	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
GE 2000	83.7	84.5	85.6	87.1	87.6	87.7	87.7	87.7	88.1	88.1	88.1	88.1	88.1
GE 1800	84.3	85.2	87.2	87.9	88.4	88.5	88.7	88.7	89.0	89.0	89.0	89.0	89.0
GE 1500	85.7	86.6	88.8	89.8	90.5	90.8	91.0	91.0	91.3	91.3	91.3	91.3	91.3
GE 1200	86.3	87.2	89.6	90.5	91.3	91.5	91.7	91.7	92.0	92.0	92.0	92.0	92.0
GE 1000	86.9	87.7	90.1	91.2	92.3	92.5	92.7	92.7	93.0	93.0	93.0	93.0	93.0
GE 900	86.9	87.7	90.1	91.2	92.3	92.5	92.7	92.8	93.1	93.1	93.1	93.1	93.1
GE 800	87.0	87.8	90.3	91.5	92.6	92.8	93.0	93.1	93.4	93.4	93.4	93.4	93.4
GE 700	87.6	88.5	91.3	92.5	93.8	94.0	94.2	94.3	94.6	94.6	94.6	94.6	94.6
GE 600	87.7	88.6	91.4	92.6	93.9	94.1	94.3	94.4	94.7	94.7	94.7	94.7	94.7
GE 500	87.8	88.7	91.6	92.9	94.4	94.6	95.3	96.0	96.3	96.5	96.6	96.6	96.6
GE 400	88.0	88.8	92.0	93.4	94.9	95.3	96.0	97.1	97.4	97.6	97.8	97.8	97.8
GE 300	88.0	88.8	92.0	93.7	95.4	95.7	96.7	98.0	98.5	98.7	98.9	98.9	98.9
GE 200	88.0	88.8	92.0	93.7	95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	99.7
GE 100	88.0	88.8	92.0	93.7	95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	99.7
GE 000	88.0	88.8	92.0	93.7	95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	99.7

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
C: + 5 MONTH: MAY HOURS: 15-17

VISIBILITY IN STATUTE MILES

GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5	46.5
57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8	57.8
58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3	58.3
58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7	58.7
59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8	59.8
61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5	67.5
69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3	70.3
73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
75.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1	76.1
79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3	81.3
83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
87.6	87.7	87.7	87.7	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
88.4	88.5	88.7	88.7	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0
90.5	90.8	91.0	91.0	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
91.3	91.5	91.7	91.7	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
92.3	92.5	92.7	92.7	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
92.3	92.5	92.7	92.8	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
92.6	92.8	93.0	93.1	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4
93.8	94.0	94.2	94.3	94.6	94.6	94.6	94.6	94.7	94.7	94.7	94.7
93.9	94.1	94.3	94.4	94.7	94.7	94.7	94.7	94.8	94.8	94.8	94.8
94.4	94.6	95.3	96.0	96.3	96.5	96.6	96.6	96.8	96.8	96.8	96.8
94.9	95.3	96.0	97.1	97.4	97.6	97.8	97.8	98.1	98.1	98.1	98.1
95.4	95.7	96.7	98.0	98.5	98.7	98.9	98.9	99.1	99.1	99.1	99.1
95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	100.0	100.0	100.0	100.0
95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	100.0	100.0	100.0	100.0
95.5	95.8	96.9	98.3	98.9	99.1	99.6	99.7	100.0	100.0	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: MAY HOURS: 18-21

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	50.6	51.2	51.9	52.0	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
GE 20000	57.7	58.3	59.2	59.6	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9
GE 18000	58.5	59.0	60.0	60.3	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6
GE 16000	58.9	59.5	60.4	60.8	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
GE 14000	60.0	60.6	61.6	61.9	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3
GE 12000	62.0	62.7	63.9	64.3	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
GE 10000	66.1	66.8	68.1	68.5	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8
GE 9000	66.9	67.5	68.8	69.2	69.6	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7
GE 8000	70.2	70.9	72.4	72.9	73.2	73.2	73.3	73.3	73.3	73.3	73.3	73.3	73.3
GE 7000	73.1	73.8	75.4	75.9	76.5	76.5	76.6	76.6	76.6	76.6	76.6	76.6	76.6
GE 6000	74.5	75.2	76.9	77.5	78.2	78.2	78.3	78.3	78.3	78.3	78.3	78.3	78.3
GE 5000	76.5	77.3	79.2	80.3	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.1	81.1
GE 4500	77.3	78.3	80.2	81.3	81.9	81.9	82.0	82.0	82.0	82.0	82.0	82.0	82.0
GE 4000	78.8	79.8	81.8	83.1	83.8	84.2	84.3	84.3	84.3	84.3	84.3	84.3	84.3
GE 3500	79.4	80.3	82.4	83.7	84.3	84.7	84.8	84.8	84.8	84.8	84.8	84.8	84.8
GE 3000	80.2	81.2	83.3	84.6	85.4	85.8	85.9	85.9	85.9	85.9	85.9	85.9	85.9
GE 2500	81.1	82.0	84.2	85.6	86.3	86.9	87.1	87.1	87.1	87.1	87.1	87.1	87.1
GE 2000	82.6	83.5	85.8	87.2	88.2	88.7	88.9	88.9	89.1	89.1	89.1	89.1	89.1
GE 1800	83.0	84.0	86.2	87.6	88.6	89.1	89.4	89.4	89.6	89.6	89.6	89.6	89.6
GE 1500	84.2	85.2	87.4	88.8	89.9	90.4	90.6	90.6	90.9	90.9	90.9	90.9	90.9
GE 1200	85.3	86.3	88.7	90.2	91.3	91.8	92.0	92.0	92.3	92.3	92.3	92.3	92.3
GE 1000	85.4	86.5	88.8	90.3	91.4	91.9	92.3	92.3	92.5	92.5	92.5	92.5	92.5
GE 900	85.8	86.9	89.2	90.8	91.9	92.5	92.8	92.8	93.0	93.0	93.0	93.0	93.0
GE 800	85.9	87.0	89.4	90.9	92.0	92.6	93.0	93.0	93.2	93.2	93.2	93.2	93.2
GE 700	86.3	87.4	89.9	91.5	92.9	93.4	94.0	94.0	94.2	94.2	94.2	94.2	94.2
GE 600	86.5	87.5	90.0	91.7	93.1	93.7	94.3	94.3	94.5	94.5	94.5	94.5	94.5
GE 500	86.5	87.5	90.0	91.7	93.2	93.8	94.7	94.9	95.2	95.2	95.2	95.2	95.2
GE 400	86.6	87.7	90.4	92.2	94.1	94.6	96.0	96.3	96.6	96.7	96.7	96.7	96.7
GE 300	86.6	87.7	90.5	92.5	94.4	94.9	96.6	97.2	98.0	98.4	98.5	98.5	98.5
GE 200	86.6	87.7	90.5	92.5	94.4	94.9	96.7	97.3	98.2	98.8	99.0	99.0	99.0
GE 100	86.6	87.7	90.5	92.5	94.4	94.9	96.7	97.4	98.3	98.9	99.1	99.1	99.1
GE 000	86.6	87.7	90.5	92.5	94.4	94.9	96.7	97.4	98.3	98.9	99.1	99.1	99.1

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
52.0	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
59.6	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9
60.3	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6	60.6
60.3	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
61.9	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3	62.3
64.3	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
68.5	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8
69.2	69.6	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
72.9	73.2	73.2	73.3	73.3	73.3	73.3	73.3	73.3	73.3	73.3	73.3	73.3
75.9	76.5	76.5	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6
77.5	78.2	78.2	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3	78.3
80.3	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1
81.3	81.9	81.9	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0
83.1	83.8	84.2	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3
83.7	84.3	84.7	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
84.4	85.4	85.8	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9
85.6	86.3	86.9	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
87.2	88.2	88.7	88.9	88.9	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
87.5	88.6	89.1	89.4	89.4	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
88.8	89.9	90.4	90.6	90.6	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
90.2	91.3	91.8	92.0	92.0	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
90.3	91.4	91.9	92.3	92.3	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
90.8	91.9	92.5	92.8	92.8	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
90.9	92.0	92.6	93.0	93.0	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
91.5	92.9	93.4	94.0	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
91.7	93.1	93.7	94.3	94.3	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
91.7	93.2	93.8	94.7	94.9	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
92.2	94.1	94.6	96.0	96.3	96.6	96.7	96.7	96.7	96.7	96.7	96.7	96.7
92.5	94.4	94.9	96.6	97.2	98.0	98.4	98.5	98.5	98.5	98.5	98.5	98.6
92.5	94.4	94.9	96.7	97.3	98.2	98.8	99.0	99.0	99.6	99.6	99.8	99.9
92.5	94.4	94.9	96.7	97.4	98.3	98.9	99.1	99.1	99.7	99.7	99.9	100.0
92.5	94.4	94.9	96.7	97.4	98.3	98.9	99.1	99.1	99.7	99.7	99.9	100.0

930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: MAY HOURS: 21-

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	55.8	55.9	56.5	56.6	56.9	56.9	57.0	57.0	57.0	57.0	57.0	57.0
GE 20000	58.8	58.9	59.3	60.0	60.4	60.4	60.5	60.5	60.5	60.5	60.5	60.5
GE 18000	59.4	59.6	60.4	60.5	61.1	61.1	61.2	61.2	61.2	61.2	61.2	61.2
GE 16000	59.4	59.6	60.4	60.8	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3
GE 14000	60.1	60.3	61.2	61.5	61.9	61.9	62.0	62.0	62.0	62.0	62.0	62.0
GE 12000	61.8	62.4	63.2	63.7	64.1	64.1	64.2	64.2	64.2	64.2	64.2	64.2
GE 10000	66.0	66.6	67.5	68.1	68.6	68.6	68.7	68.7	68.7	68.7	68.7	68.7
GE 9000	66.2	66.8	67.7	68.3	68.8	68.8	68.9	68.9	68.9	68.9	68.9	68.9
GE 8000	68.0	68.6	69.7	70.3	70.9	70.9	71.0	71.0	71.0	71.0	71.0	71.0
GE 7000	70.6	71.3	72.4	73.0	73.5	73.5	73.7	73.7	73.7	73.7	73.7	73.7
GE 6000	72.4	73.0	74.1	74.9	75.5	75.5	75.6	75.6	75.6	75.6	75.6	75.6
GE 5000	74.0	74.9	76.3	77.2	77.8	77.8	78.0	78.0	78.0	78.0	78.0	78.0
GE 4500	75.3	77.3	78.8	79.7	80.3	80.3	80.4	80.4	80.4	80.4	80.4	80.4
GE 4000	78.6	79.6	81.1	82.0	82.7	83.1	83.2	83.2	83.2	83.2	83.2	83.2
GE 3500	79.0	80.0	81.5	82.6	83.5	84.0	84.1	84.1	84.1	84.1	84.1	84.1
GE 3000	80.2	81.2	82.7	84.0	85.1	85.6	85.8	85.8	85.8	85.8	85.8	85.8
GE 2500	80.5	81.5	83.1	84.4	85.5	86.3	86.6	86.6	86.6	86.6	86.6	86.6
GE 2000	81.5	82.5	84.1	85.5	86.6	87.5	87.7	87.7	87.7	87.7	87.7	87.7
GE 1800	82.2	83.1	84.8	86.2	87.3	88.3	88.5	88.5	88.5	88.5	88.5	88.5
GE 1500	83.4	84.4	86.1	87.5	88.6	89.6	89.9	89.9	89.9	89.9	89.9	89.9
GE 1200	84.0	84.9	86.7	88.1	89.2	90.2	90.6	90.6	90.6	90.6	90.6	90.6
GE 1000	84.3	85.3	87.0	88.4	89.6	90.5	91.0	91.0	91.0	91.0	91.0	91.0
GE 900	84.5	85.5	87.2	88.6	89.8	90.8	91.2	91.2	91.2	91.2	91.2	91.2
GE 800	84.7	85.7	87.4	89.0	90.2	91.2	91.8	91.8	91.8	91.8	91.8	91.8
GE 700	85.1	86.0	87.7	89.4	90.9	91.9	92.7	92.7	92.7	92.7	92.7	92.7
GE 600	85.2	86.1	88.0	89.6	91.2	92.3	93.0	93.0	93.0	93.0	93.0	93.0
GE 500	85.3	86.2	88.2	89.8	91.5	92.6	93.5	93.9	93.9	93.9	93.9	93.9
GE 400	85.5	86.5	88.4	90.1	91.9	93.1	94.5	94.8	94.8	94.8	94.8	94.8
GE 300	85.6	86.6	88.5	90.3	92.2	93.3	94.8	95.8	96.0	96.1	96.1	96.1
GE 200	85.6	86.6	88.5	90.3	92.2	93.3	94.9	95.9	96.2	96.8	97.4	97.4
GE 100	85.6	86.6	88.5	90.3	92.2	93.3	94.9	95.9	96.5	97.3	98.0	98.0
GE 000	85.6	86.6	88.5	90.3	92.2	93.3	94.9	95.9	96.5	97.3	98.0	98.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. J. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: 21-23

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
5	56.6	56.9	56.9	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0	57.0
5	60.0	60.4	60.4	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
3	60.5	61.1	61.1	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2	61.2
3	60.8	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
0	61.5	61.9	61.9	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
2	63.7	64.1	64.1	64.2	64.2	64.2	64.2	64.2	64.2	64.2	64.2	64.2	64.2
7	68.1	68.6	68.6	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7	68.7
9	68.3	68.8	68.8	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9
0	70.3	70.9	70.9	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0	71.0
7	73.0	73.5	73.5	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7	73.7
5	74.9	75.5	75.5	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6
0	77.2	77.8	77.8	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0
4	79.7	80.3	80.3	80.4	80.4	80.4	80.4	80.4	80.4	80.4	80.4	80.4	80.4
2	82.0	82.7	83.1	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
1	82.6	83.5	84.0	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1
8	84.0	85.1	85.6	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8
5	84.4	85.5	86.3	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6
7	85.5	86.6	87.5	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7
5	86.2	87.3	88.3	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
9	87.5	88.6	89.6	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9
8	88.1	89.2	90.2	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
0	88.4	89.6	90.5	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
2	88.6	89.3	90.8	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
4	89.0	90.2	91.2	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
7	89.4	90.9	91.9	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7
0	89.6	91.2	92.3	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
2	89.8	91.5	92.6	93.5	93.9	93.9	93.9	93.9	93.9	94.0	94.0	94.0	94.0
4	90.1	91.9	93.1	94.5	94.8	94.8	94.8	94.8	94.8	94.9	94.9	94.9	94.9
5	90.3	92.2	93.3	94.8	95.8	96.0	96.1	96.1	96.1	96.2	96.2	96.3	96.3
5	90.3	92.2	93.3	94.9	95.9	96.2	96.8	97.4	97.4	98.2	98.4	98.8	99.2
5	90.3	92.2	93.3	94.9	95.9	96.5	97.3	98.0	98.0	98.8	99.0	99.6	100.0
5	90.3	92.2	93.3	94.9	95.9	96.5	97.3	98.0	98.0	98.8	99.0	99.6	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSU
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD:
 LST TO UTC: + 5 MONTH: MAY HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CFIL	49.3	49.8	50.3	50.5	50.8	50.8	50.9	50.9	50.9	51.0	51.0	51
GE 20000	56.2	56.8	57.4	57.7	58.0	58.1	58.1	58.2	58.2	58.2	58.2	58
GE 18000	56.5	57.1	57.8	58.0	58.4	58.4	58.5	58.5	58.5	58.6	58.6	58
GE 16000	56.7	57.3	58.0	58.2	58.6	58.6	58.7	58.8	58.8	58.8	58.8	58
GE 14000	57.3	57.9	58.5	58.8	59.2	59.2	59.3	59.3	59.3	59.4	59.4	59
GE 12000	58.4	59.1	59.8	60.1	60.5	60.6	60.6	60.7	60.7	60.7	60.7	60
GE 10000	61.4	62.1	63.0	63.4	63.8	63.8	63.9	64.0	64.0	64.0	64.0	64
GE 9000	62.0	62.7	63.6	64.0	64.4	64.4	64.6	64.6	64.7	64.7	64.7	64
GE 8000	64.3	65.0	65.9	66.4	65.8	66.9	67.0	67.1	67.1	67.1	67.2	67
GE 7000	66.2	67.0	68.0	68.5	68.9	69.0	69.1	69.2	69.2	69.3	69.3	69
GE 6000	67.5	68.4	69.4	70.1	70.5	70.7	70.8	70.9	70.9	71.0	71.0	71
GE 5000	69.5	70.4	71.5	72.3	72.9	73.0	73.2	73.3	73.4	73.4	73.4	73
GE 4500	70.9	71.8	73.1	73.5	74.4	74.5	74.8	74.9	74.9	75.0	75.0	75
GE 4000	73.3	74.2	75.5	75.4	77.1	77.3	77.6	77.6	77.8	77.9	77.9	77
GE 3500	74.3	75.3	76.7	77.6	78.4	78.6	78.9	79.1	79.2	79.2	79.2	79
GE 3000	75.9	76.9	78.4	79.3	80.2	80.5	80.8	81.0	81.0	81.1	81.1	81
GE 2500	76.8	77.9	79.4	80.4	81.3	81.7	82.0	82.2	82.3	82.3	82.3	82
GE 2000	78.6	79.7	81.3	82.3	83.3	83.7	84.0	84.3	84.4	84.5	84.5	84
GE 1800	79.2	80.2	81.7	82.9	83.9	84.3	84.7	84.9	85.1	85.1	85.1	85
GE 1500	80.8	81.9	83.5	84.9	86.0	86.5	86.9	87.1	87.3	87.3	87.4	87
GE 1200	81.7	82.9	84.6	86.0	87.2	87.6	88.1	88.3	88.5	88.5	88.5	88
GE 1000	82.3	83.5	85.5	86.6	88.0	88.5	89.0	89.3	89.4	89.5	89.5	89
GE 900	82.7	83.9	85.9	87.1	88.5	89.1	89.6	89.9	90.1	90.1	90.1	90
GE 800	83.0	84.2	86.2	87.5	89.0	89.5	90.1	90.4	90.6	90.6	90.7	90
GE 700	83.4	84.5	86.7	88.1	89.7	90.3	91.1	91.4	91.5	91.6	91.6	91
GE 600	83.5	84.8	87.0	88.5	90.2	90.9	91.5	91.9	92.1	92.2	92.2	92
GE 500	83.9	85.1	87.4	89.1	91.0	91.8	92.9	93.5	93.8	93.9	93.9	93
GE 400	84.0	85.2	87.7	89.4	91.6	92.4	93.9	94.8	95.2	95.3	95.4	95
GE 300	84.0	85.3	87.8	89.5	91.9	92.8	94.5	95.8	96.5	96.8	96.9	97
GE 200	84.0	85.3	87.8	89.6	92.0	92.9	94.7	96.2	97.1	97.7	98.1	98
GE 100	84.0	85.3	87.8	89.6	92.0	92.9	94.8	96.3	97.2	97.9	98.3	98
GE 000	84.0	85.3	87.8	89.6	92.0	92.9	94.8	96.3	97.2	97.9	98.3	98

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 89
MONTH: MAY HOURS: ALL

VISIBILITY IN STATUTE MILES													
GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
50.5	50.8	50.8	50.9	50.9	50.9	51.0	51.0	51.0	51.0	51.0	51.1	51.1	
57.7	58.0	58.1	58.1	58.2	58.2	58.2	58.2	58.2	58.3	58.3	58.3	58.3	
58.0	58.4	58.4	58.5	58.5	58.5	58.6	58.6	58.6	58.6	58.6	58.7	58.7	
58.2	58.6	58.6	58.7	58.8	58.8	58.8	58.8	58.8	58.8	58.9	58.9	58.9	
58.8	59.2	59.2	59.3	59.3	59.3	59.4	59.4	59.4	59.4	59.4	59.5	59.5	
60.1	60.5	60.6	60.6	60.7	60.7	60.7	60.7	60.7	60.8	60.8	60.8	60.8	
63.4	63.3	63.3	63.9	64.0	64.0	64.0	64.0	64.0	64.1	64.1	64.1	64.2	
64.0	64.4	64.4	64.6	64.6	64.7	64.7	64.7	64.7	64.7	64.7	64.8	64.8	
66.4	65.8	66.9	67.0	67.1	67.1	67.1	67.2	67.2	67.2	67.2	67.2	67.3	
68.5	68.9	69.0	69.1	69.2	69.2	69.3	69.3	69.3	69.3	69.3	69.4	69.4	
70.1	70.5	70.7	70.8	70.9	70.9	71.0	71.0	71.0	71.0	71.0	71.1	71.1	
72.3	72.9	73.0	73.2	73.3	73.4	73.4	73.4	73.4	73.4	73.5	73.5	73.5	
73.5	74.4	74.5	74.8	74.9	74.9	75.0	75.0	75.0	75.0	75.0	75.1	75.1	
75.4	77.1	77.3	77.5	77.8	77.8	77.9	77.9	77.9	77.9	77.9	78.0	78.0	
77.4	78.4	78.6	78.9	79.1	79.2	79.2	79.2	79.2	79.2	79.2	79.3	79.3	
79.3	80.2	80.5	80.8	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.2	81.2	
80.4	81.3	81.7	82.0	82.2	82.3	82.3	82.3	82.3	82.3	82.4	82.4	82.4	
82.3	83.3	83.7	84.0	84.3	84.4	84.5	84.5	84.5	84.6	84.6	84.6	84.7	
82.9	83.9	84.3	84.7	84.9	85.1	85.1	85.1	85.1	85.2	85.2	85.3	85.3	
84.9	86.0	86.5	86.9	87.1	87.3	87.3	87.4	87.4	87.4	87.4	87.5	87.5	
86.0	87.2	87.6	88.1	88.3	88.5	88.5	88.5	88.5	88.6	88.6	88.7	88.7	
86.5	88.0	88.5	89.0	89.3	89.4	89.5	89.5	89.5	89.6	89.6	89.7	89.7	
87.1	88.6	89.1	89.6	89.9	90.1	90.1	90.1	90.1	90.2	90.2	90.3	90.3	
87.5	89.0	89.5	90.1	90.4	90.6	90.6	90.7	90.7	90.7	90.8	90.8	90.8	
88.1	89.7	90.3	91.1	91.4	91.5	91.6	91.6	91.6	91.7	91.7	91.8	91.8	
88.5	90.2	90.9	91.5	91.9	92.1	92.2	92.2	92.2	92.3	92.3	92.3	92.4	
89.1	91.0	91.8	92.9	93.5	93.8	93.9	93.9	93.9	94.1	94.1	94.1	94.1	
89.4	91.6	92.4	93.9	94.8	95.2	95.3	95.4	95.4	95.5	95.5	95.6	95.6	
89.5	91.9	92.8	94.5	95.8	96.5	96.8	96.9	97.0	97.2	97.2	97.3	97.3	
89.6	92.0	92.9	94.7	96.2	97.1	97.7	98.1	98.2	98.6	98.8	99.0	99.3	
89.6	92.0	92.9	94.8	96.3	97.2	97.9	98.3	98.4	99.0	99.2	99.6	100.0	
89.6	92.0	92.9	94.8	96.3	97.2	97.9	98.3	98.4	99.0	99.2	99.6	100.0	

7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: JUN HOURS: 00-0

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	56.4	56.7	57.7	58.0	58.2	58.3	58.6	58.9	58.9	59.0	59.0	59.0	59
GE 20000	60.2	60.7	61.7	62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63
GE 18000	60.2	60.7	61.7	62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63
GE 16000	60.2	60.7	61.7	62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63
GE 14000	61.2	61.7	62.7	63.1	63.3	63.4	63.7	64.1	64.1	64.2	64.2	64.2	64
GE 12000	62.4	62.9	63.9	64.3	64.6	64.7	64.9	65.3	65.3	65.4	65.4	65.4	65
GE 10000	66.7	67.1	68.1	68.6	68.9	69.0	69.2	69.7	69.7	69.8	69.8	69.8	70
GE 9000	67.3	67.8	68.8	69.2	69.6	69.7	69.9	70.3	70.3	70.4	70.4	70.4	70
GE 8000	70.3	70.9	71.9	72.3	72.7	72.9	73.1	73.6	73.6	73.7	73.8	73.8	74
GE 7000	72.6	73.1	74.1	74.6	74.9	75.1	75.3	75.8	75.8	75.9	76.0	76.0	76
GE 6000	74.6	75.1	76.1	76.6	76.9	77.1	77.3	77.8	77.8	77.9	78.0	78.0	78
GE 5000	77.9	78.6	79.6	80.0	80.3	80.6	80.9	81.3	81.3	81.4	81.6	81.6	81
GE 4500	78.6	79.2	80.2	80.7	81.0	81.2	81.6	82.0	82.0	82.1	82.2	82.2	82
GE 4000	79.4	80.1	81.1	81.7	82.2	82.4	82.8	83.2	83.2	83.3	83.4	83.4	83
GE 3500	80.8	81.4	82.7	83.2	83.8	84.0	84.3	84.8	84.8	84.9	85.0	85.0	85
GE 3000	81.3	82.0	83.2	83.8	84.7	84.9	85.2	85.7	85.7	85.8	85.9	85.9	86
GE 2500	82.7	83.3	84.6	85.1	86.0	86.2	86.6	87.0	87.0	87.1	87.2	87.2	87
GE 2000	83.6	84.2	85.4	86.0	87.0	87.2	87.6	88.0	88.0	88.1	88.2	88.2	88
GE 1800	83.8	84.4	85.7	86.2	87.2	87.4	87.8	88.2	88.2	88.3	88.4	88.4	88
GE 1500	84.3	85.1	86.3	87.0	88.0	88.2	88.6	89.0	89.0	89.1	89.2	89.2	89
GE 1200	84.7	85.4	86.7	87.3	88.3	88.6	88.9	89.3	89.3	89.4	89.6	89.6	89
GE 1000	85.4	86.2	87.4	88.1	89.2	89.4	89.9	90.3	90.3	90.4	90.6	90.6	90
GE 900	85.6	86.3	87.6	88.2	89.3	89.6	90.0	90.4	90.4	90.6	90.7	90.7	90
GE 800	86.1	86.9	88.1	88.8	90.0	90.2	90.7	91.1	91.1	91.2	91.3	91.3	91
GE 700	86.9	87.7	89.0	89.7	90.9	91.2	91.7	92.1	92.1	92.2	92.3	92.3	92
GE 600	87.0	87.9	89.2	90.3	91.8	92.1	92.7	93.1	93.1	93.2	93.3	93.3	93
GE 500	87.5	88.4	89.8	90.9	92.4	92.8	93.3	94.2	94.3	94.4	94.6	94.6	94
GE 400	87.6	88.4	89.8	90.9	92.3	93.3	94.0	95.6	95.7	95.9	96.1	96.1	96
GE 300	87.6	88.4	89.8	90.9	92.8	93.3	94.1	96.1	96.2	96.6	97.0	97.0	97
GE 200	87.6	88.4	89.8	90.9	92.9	93.4	94.3	96.6	96.9	97.4	98.0	98.0	98
GE 100	87.6	88.4	89.8	90.9	92.9	93.4	94.3	96.6	97.0	97.6	98.1	98.3	99
GE 000	87.6	88.4	89.8	90.9	92.9	93.4	94.3	96.6	97.0	97.6	98.1	98.3	99

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 86
MONTH: JUN HOURS: 00-02

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
58.0	58.2	58.3	58.6	58.9	58.9	59.0	59.0	59.0	59.2	59.2	59.2	59.2
62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63.3	63.3	63.3	63.3
62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63.3	63.3	63.3	63.3
62.0	62.2	62.3	62.6	63.0	63.0	63.1	63.1	63.1	63.3	63.3	63.3	63.3
63.1	63.3	63.4	63.7	64.1	64.1	64.2	64.2	64.2	64.4	64.4	64.4	64.4
64.3	64.6	64.7	64.9	65.3	65.3	65.4	65.4	65.4	65.7	65.7	65.7	65.7
68.6	68.9	69.0	69.2	69.7	69.7	69.8	69.8	69.8	70.0	70.0	70.0	70.0
69.2	69.6	69.7	69.9	70.3	70.3	70.4	70.4	70.4	70.7	70.7	70.7	70.7
72.3	72.7	72.9	73.1	73.6	73.6	73.7	73.8	73.8	74.0	74.0	74.0	74.0
74.6	74.9	75.1	75.3	75.8	75.8	75.9	76.0	76.0	76.2	76.2	76.2	76.2
76.6	76.9	77.1	77.3	77.8	77.8	77.9	78.0	78.0	78.2	78.2	78.2	78.2
80.0	80.3	80.6	80.9	81.3	81.3	81.4	81.6	81.6	81.8	81.8	81.8	81.8
80.7	81.0	81.2	81.6	82.0	82.0	82.1	82.2	82.2	82.4	82.4	82.4	82.4
81.7	82.2	82.4	82.8	83.2	83.2	83.3	83.4	83.4	83.7	83.7	83.7	83.7
83.2	83.8	84.0	84.3	84.8	84.8	84.9	85.0	85.0	85.2	85.2	85.2	85.2
83.3	84.7	84.9	85.2	85.7	85.7	85.8	85.9	85.9	86.1	86.1	86.1	86.1
85.1	86.0	86.2	86.6	87.0	87.0	87.1	87.2	87.2	87.4	87.4	87.4	87.4
86.0	87.0	87.2	87.6	88.0	88.0	88.1	88.2	88.2	88.4	88.4	88.4	88.4
86.2	87.2	87.4	87.8	88.2	88.2	88.3	88.4	88.4	88.7	88.7	88.7	88.7
87.0	88.0	88.2	88.6	89.0	89.0	89.1	89.2	89.2	89.4	89.4	89.4	89.4
87.3	88.3	88.6	88.9	89.3	89.3	89.4	89.6	89.6	89.8	89.8	89.8	89.8
88.1	89.2	89.4	89.9	90.3	90.3	90.4	90.6	90.6	90.8	90.8	90.8	90.8
88.2	89.3	89.6	90.0	90.4	90.4	90.6	90.7	90.7	90.9	90.9	90.9	90.9
88.8	90.0	90.2	90.7	91.1	91.1	91.2	91.3	91.3	91.6	91.6	91.6	91.6
89.7	90.9	91.2	91.7	92.1	92.1	92.2	92.3	92.3	92.6	92.6	92.6	92.6
90.3	91.8	92.1	92.7	93.1	93.1	93.2	93.3	93.3	93.6	93.6	93.6	93.6
90.9	92.4	92.6	93.3	94.2	94.3	94.4	94.6	94.6	94.8	94.8	94.8	94.8
90.9	92.3	93.3	94.0	95.6	95.7	95.9	96.1	96.1	96.4	96.4	96.4	96.6
90.9	92.8	93.3	94.1	96.1	96.2	96.6	97.0	97.0	97.3	97.3	97.3	97.4
90.9	92.9	93.4	94.3	96.6	96.9	97.4	98.0	98.0	98.7	98.8	98.8	99.2
90.9	92.9	93.4	94.3	96.6	97.0	97.6	98.1	98.3	99.0	99.1	99.2	100.0
90.9	92.9	93.4	94.3	96.6	97.0	97.6	98.1	98.3	99.0	99.1	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: A
MONTH: JUN HOURS:

CEILING TN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	52.4	53.2	54.0	54.6	55.4	55.4	55.6	55.7	55.8	55.8	55.8	55.8
GE 20000	57.2	58.0	58.8	59.3	60.2	60.2	60.3	60.6	60.7	60.7	60.7	60.7
GE 18000	57.6	58.3	59.1	59.7	60.6	60.6	60.7	60.9	61.0	61.0	61.0	61.0
GE 16000	57.7	58.4	59.2	59.8	60.7	60.7	60.8	61.0	61.1	61.1	61.1	61.1
GE 14000	58.9	59.7	60.6	61.1	62.0	62.0	62.1	62.3	62.4	62.4	62.4	62.4
GE 12000	60.0	60.8	61.7	62.2	63.1	63.1	63.2	63.4	63.6	63.6	63.6	63.6
GE 10000	63.9	64.8	65.7	66.2	67.2	67.2	67.3	67.6	67.7	67.7	67.7	67.7
GE 9000	64.3	65.2	66.1	66.7	67.7	67.7	67.8	68.0	68.1	68.1	68.1	68.1
GE 8000	67.4	68.6	69.4	70.1	71.1	71.1	71.2	71.6	71.7	71.7	71.7	71.7
GE 7000	68.9	70.0	70.9	71.6	72.6	72.6	72.7	73.0	73.1	73.1	73.1	73.1
GE 6000	69.8	71.0	71.9	72.6	73.6	73.6	73.7	74.0	74.1	74.1	74.1	74.1
GE 5000	72.9	74.2	75.2	75.9	76.9	76.9	77.0	77.3	77.4	77.4	77.4	77.4
GE 4500	74.3	75.7	76.7	77.4	78.4	78.4	78.6	78.9	79.0	79.0	79.0	79.0
GE 4000	76.3	77.7	78.7	79.4	80.8	80.8	80.9	81.2	81.3	81.3	81.3	81.3
GE 3500	77.6	79.0	80.0	80.9	82.2	82.2	82.3	82.7	82.8	82.8	82.8	82.8
GE 3000	79.0	80.4	81.4	82.3	83.8	83.8	83.9	84.2	84.3	84.3	84.3	84.3
GE 2500	80.1	81.6	82.6	83.4	84.9	84.9	85.0	85.3	85.4	85.4	85.4	85.4
GE 2000	81.2	82.7	83.7	84.6	85.0	85.0	85.1	85.4	85.6	85.6	85.6	85.6
GE 1800	81.7	83.1	84.2	85.1	85.6	85.6	85.7	86.0	86.1	86.1	86.1	86.1
GE 1500	83.3	84.8	85.9	86.8	88.3	88.3	88.4	88.8	88.9	88.9	88.9	88.9
GE 1200	84.2	85.7	86.8	87.7	89.2	89.2	89.3	89.7	89.8	89.8	89.8	89.8
GE 1000	85.2	86.7	87.9	88.9	90.3	90.3	90.4	90.8	90.9	90.9	90.9	90.9
GE 900	85.6	87.0	88.2	89.1	90.7	90.7	90.8	91.1	91.2	91.2	91.2	91.2
GE 800	85.9	87.3	88.6	89.4	91.0	91.0	91.2	91.6	91.7	91.7	91.7	91.7
GE 700	86.1	87.6	88.8	89.7	91.2	91.2	91.4	91.8	91.9	91.9	91.9	91.9
GE 600	86.2	87.7	88.9	89.9	91.5	91.5	91.8	92.1	92.2	92.2	92.2	92.2
GE 500	87.0	88.4	89.7	90.8	92.4	92.4	92.8	93.2	93.6	93.6	93.6	93.6
GE 400	87.0	88.4	89.9	91.1	93.1	93.1	93.6	94.7	95.0	95.1	95.1	95.1
GE 300	87.1	88.6	90.0	91.2	93.4	93.4	94.1	95.3	95.8	95.9	96.3	96.3
GE 200	87.1	88.6	90.0	91.2	93.8	93.9	94.7	95.9	96.7	97.0	97.7	97.8
GE 100	87.1	88.6	90.0	91.2	93.8	94.0	94.8	96.0	96.8	97.1	97.9	98.0
GE 000	87.1	88.6	90.0	91.2	93.8	94.0	94.8	96.0	96.8	97.1	97.9	98.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 03-05

VISIBILITY IN STATUTE MILES												
GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
54.6	55.4	55.4	55.6	55.7	55.8	55.8	55.8	55.8	55.8	55.9	55.9	55.9
59.3	60.2	60.2	60.3	60.6	60.7	60.7	60.7	60.7	60.7	60.8	60.8	60.8
59.7	60.6	60.6	60.7	60.9	61.0	61.0	61.0	61.0	61.0	61.1	61.1	61.1
59.8	60.7	60.7	60.8	61.0	61.1	61.1	61.1	61.1	61.1	61.2	61.2	61.2
61.1	62.0	62.0	62.1	62.3	62.4	62.4	62.4	62.4	62.4	62.6	62.6	62.6
62.2	63.1	63.1	63.2	63.4	63.6	63.6	63.6	63.6	63.6	63.7	63.7	63.7
66.2	67.2	67.2	67.3	67.6	67.7	67.7	67.7	67.7	67.7	67.8	67.8	67.8
66.7	67.7	67.7	67.8	68.0	68.1	68.1	68.1	68.1	68.1	68.2	68.2	68.2
70.1	71.1	71.1	71.2	71.6	71.7	71.7	71.7	71.7	71.7	71.8	71.8	71.8
71.6	72.6	72.6	72.7	73.0	73.1	73.1	73.1	73.1	73.1	73.2	73.2	73.2
72.6	73.6	73.6	73.7	74.0	74.1	74.1	74.1	74.1	74.1	74.2	74.2	74.2
75.9	76.9	76.9	77.0	77.3	77.4	77.4	77.4	77.4	77.4	77.6	77.6	77.6
77.4	78.4	78.4	78.6	78.9	79.0	79.0	79.0	79.0	79.1	79.2	79.2	79.2
79.4	80.8	80.8	80.9	81.2	81.3	81.3	81.3	81.3	81.4	81.6	81.6	81.6
80.9	82.2	82.2	82.3	82.7	82.8	82.8	82.8	82.8	82.9	83.0	83.0	83.0
82.3	83.8	83.8	83.9	84.2	84.3	84.3	84.3	84.3	84.4	84.6	84.6	84.6
83.4	84.9	84.9	85.0	85.3	85.4	85.4	85.4	85.4	85.6	85.7	85.7	85.7
84.6	85.0	86.0	86.1	86.4	86.6	86.6	86.6	86.6	86.7	86.8	86.8	86.8
85.1	86.6	86.6	86.7	87.0	87.1	87.1	87.1	87.1	87.2	87.3	87.3	87.3
86.2	88.3	88.3	88.4	88.8	88.9	88.9	88.9	88.9	89.0	89.1	89.1	89.1
87.7	89.2	89.2	89.3	89.7	89.8	89.8	89.8	89.8	89.9	90.0	90.0	90.0
89.3	90.3	90.3	90.4	90.8	90.9	90.9	90.9	90.9	91.0	91.1	91.1	91.1
89.1	90.7	90.7	90.8	91.1	91.2	91.2	91.2	91.2	91.3	91.4	91.4	91.4
89.4	91.0	91.0	91.2	91.6	91.7	91.7	91.7	91.7	91.8	91.9	91.9	91.9
89.7	91.2	91.2	91.4	91.8	91.9	91.9	91.9	91.9	92.0	92.1	92.1	92.1
89.9	91.5	91.5	91.8	92.1	92.2	92.2	92.2	92.2	92.3	92.4	92.4	92.4
90.3	92.4	92.4	92.8	93.2	93.6	93.6	93.6	93.6	93.7	93.8	93.8	93.8
91.1	93.1	93.1	93.6	94.7	95.0	95.1	95.1	95.1	95.2	95.3	95.3	95.3
91.2	93.4	93.4	94.1	95.3	95.8	95.9	96.3	96.3	96.4	96.6	96.7	96.7
91.2	93.8	93.9	94.7	95.9	96.7	97.0	97.7	97.8	98.0	98.1	98.7	99.2
91.2	93.8	94.0	94.8	96.0	96.8	97.1	97.9	98.0	98.2	98.5	98.9	99.8
91.2	93.8	94.0	94.8	96.0	96.8	97.1	97.9	98.0	98.2	98.3	93.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: A
MONTH: JUN HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	52.7	53.3	54.4	55.3	55.8	56.1	56.3	56.6	56.6	56.6	56.6	56.6
GE 20000	58.2	58.9	60.4	61.4	61.9	62.3	62.7	63.1	63.1	63.1	63.1	63.1
GE 18000	58.4	59.1	60.7	61.7	62.1	62.6	62.9	63.3	63.3	63.3	63.3	63.3
GE 16000	58.4	59.1	60.7	61.7	62.1	62.6	62.9	63.3	63.3	63.3	63.3	63.3
GE 14000	59.2	60.0	61.8	62.8	63.2	63.7	64.0	64.4	64.4	64.4	64.4	64.4
GE 12000	60.3	61.1	62.9	63.9	64.3	64.8	65.1	65.6	65.6	65.6	65.6	65.6
GE 10000	63.3	64.1	65.9	67.0	67.7	68.1	68.4	68.9	68.9	68.9	68.9	68.9
GE 9000	64.0	64.8	66.6	67.3	68.6	69.0	69.3	69.8	69.8	69.8	69.8	69.8
GE 8000	67.8	68.6	70.4	71.8	72.9	73.3	73.7	74.1	74.1	74.1	74.1	74.1
GE 7000	68.6	69.3	71.2	72.6	73.8	74.2	74.6	75.0	75.0	75.0	75.0	75.0
GE 6000	69.2	70.1	72.6	73.9	75.2	75.7	76.1	76.6	76.6	76.6	76.6	76.6
GE 5000	70.6	71.6	74.0	75.3	76.7	77.1	77.6	78.0	78.0	78.0	78.0	78.0
GE 4500	71.3	72.3	74.8	76.3	77.7	78.1	78.6	79.0	79.0	79.1	79.1	79.1
GE 4000	72.4	73.6	76.0	77.6	79.0	79.4	80.0	80.4	80.4	80.5	80.6	80.6
GE 3500	73.6	74.7	77.3	78.9	80.6	81.0	81.6	82.0	82.0	82.1	82.1	82.1
GE 3000	74.3	75.4	78.1	79.7	81.6	82.0	82.7	83.1	83.1	83.2	83.2	83.2
GE 2500	74.9	76.0	78.8	80.3	82.2	82.7	83.3	83.8	83.8	83.9	83.9	83.9
GE 2000	76.2	77.3	80.2	81.8	83.8	84.2	85.1	85.6	85.6	85.7	85.7	85.7
GE 1800	76.6	77.7	80.6	82.1	84.1	84.6	85.4	85.9	85.9	86.0	86.0	86.0
GE 1500	79.0	80.1	83.2	84.8	87.0	87.4	88.3	88.8	88.8	88.9	88.9	88.9
GE 1200	80.0	81.2	84.3	85.9	88.2	88.7	89.6	90.0	90.0	90.1	90.1	90.1
GE 1000	81.0	82.2	85.3	86.7	89.2	89.7	90.6	91.1	91.1	91.2	91.2	91.2
GE 900	81.2	82.4	85.6	87.1	89.4	89.9	90.3	91.3	91.3	91.4	91.4	91.4
GE 800	81.6	82.8	85.9	87.7	90.0	90.7	91.7	92.2	92.2	92.3	92.3	92.3
GE 700	82.0	83.3	86.6	88.4	90.8	91.4	92.4	93.0	93.0	93.1	93.1	93.1
GE 600	82.2	83.6	86.9	88.9	91.4	92.1	93.1	93.7	93.7	93.8	93.8	93.8
GE 500	82.6	83.9	87.2	89.2	91.8	92.6	93.8	94.7	94.7	95.0	95.0	95.0
GE 400	82.8	84.1	87.4	89.4	92.1	93.1	94.4	95.4	96.0	96.1	96.1	96.1
GE 300	82.8	84.1	87.4	89.6	92.6	93.6	95.1	96.1	97.0	97.1	97.1	97.1
GE 200	82.8	84.1	87.4	89.6	92.6	93.6	95.1	96.1	97.1	97.3	97.6	97.7
GE 100	82.8	84.1	87.4	89.6	92.6	93.6	95.1	96.1	97.1	97.4	97.7	97.8
GE 000	82.8	84.1	87.4	89.6	92.6	93.6	95.1	96.1	97.1	97.4	97.7	97.8

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 06-08

VISIBILITY IN STATUTE MILES

CEILING	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
50	55.3	55.8	56.1	56.3	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6
53	61.4	61.9	62.3	62.7	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
63	61.7	62.1	62.6	62.9	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
63	61.7	62.1	62.6	62.9	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
63	62.4	63.2	63.7	64.0	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
64	63.9	64.3	64.8	65.1	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
65	67.0	67.7	68.1	68.4	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9
65	67.3	67.6	68.0	68.3	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8
69	71.8	72.9	73.3	73.7	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
74	72.5	73.3	74.2	74.6	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
75	73.9	75.2	75.7	76.1	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6	76.6
76	76.3	76.7	77.1	77.6	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0
78	76.3	77.7	78.1	78.6	79.0	79.0	79.1	79.1	79.1	79.1	79.1	79.1	79.1
79	77.6	79.0	79.4	80.0	80.4	80.4	80.6	80.6	80.6	80.6	80.6	80.6	80.6
80	78.9	80.6	81.0	81.6	82.0	82.0	82.1	82.1	82.1	82.1	82.1	82.1	82.1
82	79.7	81.6	82.0	82.7	83.1	83.1	83.2	83.2	83.2	83.2	83.2	83.2	83.2
83	80.3	82.2	82.7	83.3	83.8	83.8	83.9	83.9	83.9	83.9	83.9	83.9	83.9
85	81.5	83.8	84.2	85.1	85.6	85.6	85.7	85.7	85.7	85.7	85.7	85.7	85.7
86	82.1	84.1	84.6	85.4	85.9	85.9	86.0	86.0	86.0	86.0	86.0	86.0	86.0
86	84.8	87.0	87.4	88.3	88.8	88.8	88.9	88.9	88.9	88.9	88.9	88.9	88.9
88	85.9	88.2	88.7	89.6	90.0	90.0	90.1	90.1	90.1	90.1	90.1	90.1	90.1
91	86.0	89.2	89.7	90.6	91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2
91	87.1	89.4	89.9	90.3	91.3	91.3	91.4	91.4	91.4	91.4	91.4	91.4	91.4
92	87.7	90.0	90.7	91.7	92.2	92.2	92.3	92.3	92.3	92.3	92.3	92.3	92.3
92	88.4	90.8	91.4	92.4	93.0	93.0	93.1	93.1	93.1	93.1	93.1	93.1	93.1
93	88.9	91.4	92.1	93.1	93.7	93.7	93.8	93.8	93.8	93.9	93.9	93.9	93.9
95	89.2	91.8	92.6	93.8	94.7	94.7	95.0	95.0	95.0	95.1	95.1	95.1	95.1
96	89.4	92.1	93.1	94.4	95.4	96.0	96.1	96.1	96.1	96.2	96.2	96.2	96.2
97	89.6	93.6	93.6	95.1	96.1	97.0	97.1	97.1	97.1	97.6	97.8	98.1	98.1
97	89.6	92.6	93.6	95.1	96.1	97.1	97.3	97.6	97.7	98.3	98.7	99.2	99.4
98	89.6	92.6	93.6	95.1	96.1	97.1	97.4	97.7	97.8	98.4	98.9	99.4	99.9
99	89.6	92.6	93.6	95.1	96.1	97.1	97.4	97.7	97.8	98.4	98.9	99.4	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AU
MONTH: JUN HOURS: 0

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	51.8	53.1	54.2	54.7	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0
GE 20000	58.6	60.1	61.7	62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
GE 18000	58.6	60.1	61.7	62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
GE 16000	58.6	60.1	61.7	62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
GE 14000	58.9	60.7	62.2	62.7	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0
GE 12000	60.7	62.4	64.1	64.6	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9
GE 10000	64.2	66.0	67.9	68.4	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8
GE 9000	65.3	67.1	69.0	69.6	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9
GE 8000	67.7	69.4	71.4	72.0	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4
GE 7000	68.8	70.6	72.7	73.2	73.7	73.7	73.8	73.8	73.8	73.8	73.8	73.8
GE 6000	69.2	71.2	73.4	74.0	74.6	74.6	74.7	74.7	74.7	74.7	74.7	74.7
GE 5000	70.8	72.8	75.0	75.6	76.1	76.1	76.2	76.2	76.2	76.2	76.2	76.2
GE 4500	71.6	73.6	75.8	76.3	76.9	76.9	77.0	77.0	77.0	77.0	77.0	77.0
GE 4000	73.1	75.1	77.4	78.0	78.6	78.6	78.7	78.7	78.7	78.7	78.7	78.7
GE 3500	74.2	76.2	78.8	79.3	79.9	79.9	80.1	80.1	80.1	80.1	80.1	80.1
GE 3000	76.1	78.1	80.8	81.4	82.0	82.0	82.2	82.2	82.2	82.2	82.2	82.2
GE 2500	78.2	80.2	83.1	83.9	84.4	84.4	84.7	84.7	84.7	84.7	84.7	84.7
GE 2000	80.2	82.3	85.2	86.0	86.6	86.6	86.8	86.8	86.8	86.8	86.8	86.8
GE 1900	81.0	83.1	86.0	86.3	87.3	87.3	87.6	87.6	87.6	87.6	87.6	87.6
GE 1500	82.4	84.6	87.6	88.3	88.9	88.9	89.1	89.1	89.1	89.1	89.1	89.1
GE 1200	84.4	86.6	89.6	90.3	90.9	90.9	91.1	91.1	91.1	91.1	91.1	91.1
GE 1000	85.7	87.8	90.9	91.7	92.2	92.2	92.4	92.4	92.4	92.4	92.4	92.4
GE 900	86.4	88.6	91.7	92.4	93.0	93.0	93.2	93.2	93.2	93.2	93.2	93.2
GE 800	87.4	89.7	93.0	93.9	94.4	94.4	94.7	94.7	94.7	94.7	94.7	94.7
GE 700	87.9	90.1	93.6	94.4	95.0	95.0	95.2	95.2	95.2	95.2	95.2	95.2
GE 600	88.1	90.4	94.0	94.9	95.7	95.7	96.1	96.3	96.3	96.3	96.3	96.3
GE 500	88.4	90.8	94.4	95.3	95.1	96.1	96.6	96.9	97.0	97.0	97.0	97.0
GE 400	88.4	90.3	94.5	95.4	95.3	96.4	96.9	97.4	97.6	97.6	97.7	97.7
GE 300	88.4	90.8	94.6	95.4	96.3	96.4	97.0	97.6	98.2	98.7	98.9	98.9
GE 200	88.4	90.8	94.6	95.4	96.3	96.4	97.0	97.6	98.4	98.9	99.3	99.4
GE 100	88.4	90.8	94.6	95.4	96.3	96.4	97.0	97.6	98.4	98.9	99.4	99.6
GE 000	88.4	90.8	94.6	95.4	96.3	96.4	97.0	97.6	98.4	98.9	99.4	99.6

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 09-11

VISIBILITY IN STATUTE MILES

4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
54.7	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0
62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
62.1	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4
62.7	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0
64.5	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9
68.4	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8	68.8
69.5	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9	69.9
72.5	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4
73.2	73.7	73.7	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8
74.0	74.6	74.6	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7	74.7
75.5	76.1	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2
76.3	76.9	76.9	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0
78.0	78.6	78.6	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
79.3	79.9	79.9	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
81.4	82.0	82.0	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
83.9	84.4	84.4	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
86.0	86.6	86.6	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
87.3	87.3	87.3	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
88.3	88.9	88.9	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
90.3	90.9	90.9	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
91.7	92.2	92.2	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
92.4	93.0	93.0	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
93.9	94.4	94.4	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
94.4	95.0	95.0	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
94.9	95.7	95.7	96.1	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
95.3	95.1	96.1	96.6	96.9	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
95.4	95.3	96.4	96.9	97.4	97.6	97.6	97.7	97.7	97.7	97.7	97.8	97.8
95.4	96.3	96.4	97.0	97.6	98.2	98.7	98.9	98.9	98.9	98.9	99.0	99.0
95.4	96.3	95.4	97.0	97.6	98.4	98.9	99.3	99.4	99.6	99.6	99.8	99.9
95.4	96.3	96.4	97.0	97.6	98.4	98.9	99.4	99.6	99.7	99.7	99.9	100.0
95.4	95.3	96.4	97.0	97.6	98.4	98.9	99.4	99.6	99.7	99.7	99.9	100.0

900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUN HOURS: 12-

CEILING IN FEET	VISIBILITY IN STATUTE MILES														
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	1		
NO CEIL	44.3	45.3	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	4
GE 20000	54.8	56.0	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	5
GE 18000	55.1	56.3	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	5
GE 16000	55.2	56.4	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	5
GE 14000	56.4	57.9	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	5
GE 12000	58.3	59.8	60.0	60.0	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	6
GE 10000	60.9	62.3	62.6	62.6	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	6
GE 9000	61.8	63.2	63.4	63.4	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	6
GE 8000	64.5	66.0	66.2	66.2	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	6
GE 7000	66.1	67.6	67.9	68.0	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	6
GE 6000	66.8	68.6	68.9	69.0	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	6
GE 5000	69.9	71.9	72.4	72.6	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	6
GE 4500	71.7	73.7	74.2	74.3	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	7
GE 4000	75.6	77.7	78.2	78.3	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	7
GE 3500	78.3	80.6	81.2	81.3	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	8
GE 3000	82.4	84.8	85.4	85.6	86.0	86.0	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	8
GE 2500	84.8	87.1	87.8	88.0	88.4	88.4	88.6	88.7	88.7	88.7	88.7	88.7	88.7	88.7	8
GE 2000	86.2	88.7	89.3	89.6	90.0	90.1	90.2	90.3	90.3	90.3	90.3	90.3	90.3	90.3	9
GE 1800	86.9	89.3	90.0	90.2	90.7	90.8	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	9
GE 1500	88.6	91.0	91.8	92.0	92.4	92.6	92.7	92.9	93.0	93.0	93.0	93.0	93.0	93.0	9
GE 1200	89.8	92.3	93.2	93.6	94.0	94.2	94.3	94.7	94.8	94.8	94.8	94.8	94.8	94.8	9
GE 1000	90.3	92.9	93.8	94.1	94.7	95.0	95.2	95.6	95.7	95.7	95.7	95.7	95.7	95.7	9
GE 900	90.4	93.0	94.1	94.4	95.0	95.3	95.7	96.0	96.2	96.3	96.3	96.3	96.3	96.3	9
GE 800	90.7	93.2	94.3	94.9	95.4	95.8	96.1	96.4	96.7	96.8	96.8	96.8	96.8	96.8	9
GE 700	90.9	93.4	94.6	95.1	95.7	96.0	96.3	96.7	96.9	97.0	97.0	97.0	97.0	97.0	9
GE 600	91.2	93.9	95.0	95.5	96.1	96.4	97.0	97.3	97.6	97.7	97.7	97.7	97.7	97.7	9
GE 500	91.3	94.0	95.2	96.0	96.6	96.9	97.6	97.9	98.1	98.2	98.2	98.2	98.2	98.2	9
GE 400	91.3	94.0	95.2	96.0	96.7	97.0	97.8	98.2	98.6	98.7	98.8	98.8	98.8	98.8	9
GE 300	91.4	94.1	95.3	96.1	97.0	97.3	98.1	98.6	99.1	99.2	99.3	99.3	99.3	99.3	9
GE 200	91.4	94.1	95.3	96.1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.4	99.4	9
GE 100	91.4	94.1	95.3	96.1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.4	99.4	9
GE 000	91.4	94.1	95.3	96.1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.4	99.4	9

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 12-14

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6	45.6
2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2	56.2
5	55.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6	56.6
7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
1	53.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1
7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7	62.7
5	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6	63.6
2	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3
2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2	68.2
3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3	69.3
5	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0
3	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
3	73.6	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8
3	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8	81.8
5	86.0	86.0	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1
0	88.4	88.4	88.6	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7
6	90.0	90.1	90.2	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
2	90.7	90.8	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
0	92.4	92.6	92.7	92.9	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
5	94.0	94.2	94.3	94.7	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
1	94.7	95.0	95.2	95.6	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
4	95.0	95.3	95.7	96.0	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3
2	95.4	95.8	96.1	96.4	96.7	96.8	96.8	96.8	96.8	96.8	96.8	96.8
1	95.7	96.0	96.3	96.7	96.9	97.0	97.0	97.0	97.0	97.2	97.2	97.2
5	96.1	96.4	97.0	97.3	97.6	97.7	97.7	97.7	97.7	97.9	97.9	97.9
0	96.6	96.9	97.6	97.9	98.1	98.2	98.2	98.2	98.2	98.4	98.4	98.4
0	96.7	97.0	97.8	98.2	98.6	98.7	98.8	98.8	98.8	99.0	99.0	99.0
1	97.0	97.3	98.1	98.6	99.1	99.2	99.3	99.3	99.3	99.6	99.6	99.6
1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.6	99.8	99.8	99.8
1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.6	99.9	100.0	100.0
1	97.0	97.3	98.1	98.6	99.2	99.3	99.4	99.4	99.6	99.9	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: JUN HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	43.3	43.8	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
GE 20000	55.9	56.4	57.0	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
GE 18000	56.7	57.2	57.9	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
GE 16000	56.7	57.2	57.9	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
GE 14000	57.9	58.4	59.1	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
GE 12000	59.6	60.1	60.8	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
GE 10000	63.2	63.8	64.4	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
GE 9000	64.3	64.9	65.5	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
GE 8000	67.2	67.8	68.4	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6
GE 7000	68.4	69.0	69.7	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8
GE 6000	69.7	70.6	71.4	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6
GE 5000	73.6	74.6	75.7	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9
GE 4500	75.4	76.6	77.8	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0
GE 4000	78.8	80.0	81.3	82.0	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 3500	81.9	83.1	84.9	85.1	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
GE 3000	84.6	85.8	87.6	87.8	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2
GE 2500	87.0	88.2	90.0	90.2	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
GE 2000	88.8	90.0	92.0	92.4	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
GE 1800	89.2	90.4	92.4	92.9	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6
GE 1500	89.7	91.1	93.1	93.6	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 1200	90.8	92.2	94.2	94.7	95.4	95.6	95.7	95.8	95.8	95.8	95.8	95.8
GE 1000	91.4	93.0	95.0	95.4	95.2	96.3	96.7	96.8	96.8	96.8	96.8	96.8
GE 900	91.7	93.2	95.2	95.7	95.4	96.6	96.9	97.0	97.0	97.0	97.0	97.0
GE 800	91.9	93.4	95.4	95.9	95.9	96.9	97.0	97.3	97.4	97.4	97.4	97.4
GE 700	92.1	93.7	95.7	96.1	97.2	97.3	97.8	97.9	97.9	97.9	97.9	97.9
GE 600	92.3	93.9	95.9	96.3	97.4	97.6	98.0	98.1	98.1	98.1	98.1	98.1
GE 500	92.4	94.0	96.0	96.4	97.6	97.7	98.1	98.4	98.4	98.4	98.4	98.4
GE 400	92.4	94.0	96.0	96.4	97.7	97.8	98.3	98.9	99.0	99.0	99.0	99.0
GE 300	92.4	94.0	96.1	96.6	97.8	97.9	98.4	99.0	99.1	99.3	99.3	99.3
GE 200	92.4	94.0	96.1	96.6	97.8	98.0	98.6	99.1	99.2	99.4	99.6	99.6
GE 100	92.4	94.0	96.1	96.6	97.8	98.0	98.6	99.1	99.2	99.4	99.7	99.7
GE 000	92.4	94.0	96.1	96.6	97.8	98.0	98.6	99.1	99.2	99.4	99.7	99.7

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME: + 5 MONTH: JUN HOURS: 15-17

CEILING	VISIBILITY IN STATUTE MILES											
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0	58.0
59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2	59.2
60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7	65.7
68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6	68.6
69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8	69.8
71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6	71.6
75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9	75.9
78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0	78.0
82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7
88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.2	99.2
99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.6	99.6
99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.8	99.8
99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	100.0	100.0
99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: JUN HOURS: 18-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	50.4	51.2	51.6	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
GE 20000	62.7	63.4	63.8	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
GE 18000	63.1	64.0	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
GE 16000	63.3	64.7	64.6	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0	65.0
GE 14000	64.7	65.6	65.9	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3
GE 12000	65.9	66.8	67.1	67.5	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6	67.6
GE 10000	69.6	70.4	70.9	71.3	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4
GE 9000	70.3	71.2	71.7	72.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
GE 8000	73.4	74.4	74.9	75.3	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
GE 7000	75.8	76.8	77.2	77.7	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8	77.8
GE 6000	78.0	79.4	80.1	80.6	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
GE 5000	80.6	82.0	83.0	83.4	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7
GE 4500	81.1	82.5	83.6	84.1	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3
GE 4000	84.1	85.6	86.9	87.4	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
GE 3500	85.7	87.1	88.4	89.0	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
GE 3000	86.8	88.2	89.6	90.1	90.4	90.6	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
GE 2500	88.1	89.6	90.9	91.4	91.8	91.9	92.1	92.2	92.2	92.2	92.2	92.3	92.3	92.3
GE 2000	89.1	90.6	92.1	92.7	93.0	93.2	93.3	93.3	93.3	93.3	93.3	93.9	94.0	94.0
GE 1800	89.1	90.6	92.1	92.7	93.0	93.2	93.3	93.3	93.3	93.3	93.3	93.9	94.0	94.0
GE 1500	89.6	91.0	92.6	93.1	93.4	93.7	94.4	94.6	94.6	94.6	94.6	94.6	94.7	94.7
GE 1200	90.8	92.2	93.8	94.3	94.7	94.9	95.8	95.9	95.9	95.9	95.9	96.0	96.0	96.0
GE 1000	90.9	92.3	93.9	94.4	94.8	95.0	95.9	96.0	96.1	96.1	96.1	96.2	96.2	96.2
GE 900	91.1	92.6	94.1	94.7	95.0	95.2	96.1	96.2	96.3	96.3	96.3	96.4	96.4	96.4
GE 800	91.1	92.7	94.2	94.8	95.2	95.4	96.3	96.4	96.4	96.4	96.4	96.7	96.7	96.7
GE 700	91.6	93.1	94.7	95.3	95.8	96.0	96.9	97.1	97.3	97.3	97.3	97.4	97.4	97.4
GE 600	91.8	93.3	94.9	95.5	95.1	96.3	97.2	97.4	97.7	97.7	97.7	97.8	97.8	97.8
GE 500	92.0	93.6	95.2	95.9	96.6	96.8	97.7	98.1	98.3	98.3	98.3	98.4	98.4	98.4
GE 400	92.0	93.6	95.2	95.9	96.6	96.9	97.8	98.6	98.8	98.9	98.9	99.1	99.1	99.1
GE 300	92.0	93.6	95.2	95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.0	99.3	99.3	99.3
GE 200	92.0	93.6	95.2	95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.0	99.3	99.3	99.3
GE 100	92.0	93.6	95.2	95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.0	99.3	99.3	99.3
GE 000	92.0	93.6	95.2	95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.0	99.3	99.3	99.3

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 18-20

VISIBILITY IN STATUTE MILES

GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GF 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0	54.0
54.3	54.8	54.8	54.9	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8
55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0	55.0
56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
57.5	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6	57.6
71.3	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4
72.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
75.3	75.4	75.4	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6	75.6
77.7	77.8	77.8	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9
80.6	80.7	80.7	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8	80.8
83.4	83.7	83.7	83.8	83.8	83.8	83.8	83.8	83.8	83.8	83.8	83.8	83.8
84.1	84.3	84.3	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6
87.4	87.9	87.9	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
89.0	89.3	89.4	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7
90.1	90.4	90.6	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
91.4	91.8	91.9	92.1	92.2	92.2	92.2	92.3	92.3	92.3	92.3	92.3	92.3
92.7	93.0	93.2	93.3	93.9	93.9	93.9	94.0	94.0	94.0	94.0	94.0	94.0
92.7	93.0	93.2	93.3	93.9	93.9	93.9	94.0	94.0	94.0	94.0	94.0	94.0
93.1	93.4	93.7	94.4	94.6	94.6	94.6	94.7	94.7	94.7	94.7	94.7	94.7
94.3	94.7	94.9	95.8	95.9	95.9	95.9	96.0	96.0	96.0	96.0	96.0	96.0
94.4	94.8	95.0	95.9	96.0	96.1	96.1	96.2	96.2	96.2	96.2	96.2	96.2
94.7	95.0	95.2	95.1	96.2	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4
94.8	95.2	95.4	96.3	96.4	96.7	96.7	96.8	96.8	96.8	96.8	96.8	96.8
95.3	95.8	96.0	96.9	97.1	97.3	97.3	97.4	97.4	97.4	97.4	97.4	97.4
95.5	95.1	96.3	97.2	97.4	97.7	97.7	97.8	97.8	97.8	97.8	97.8	97.8
95.9	96.5	96.8	97.7	98.1	98.3	98.3	98.4	98.4	98.4	98.4	98.4	98.4
95.7	96.5	96.9	97.8	98.6	98.8	98.9	99.1	99.1	99.2	99.2	99.2	99.2
95.9	95.5	96.9	97.9	98.7	98.9	99.0	99.3	99.3	99.7	99.7	99.7	99.9
95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.3	99.3	99.7	99.7	99.7	100.0
95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.3	99.3	99.7	99.7	99.7	100.0
95.9	96.6	96.9	97.9	98.7	98.9	99.0	99.3	99.3	99.7	99.7	99.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AU
MONTH: JUN HOURS: 2

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	54.4	55.0	55.6	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
GE 20000	61.6	62.4	63.1	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
GE 18000	61.2	62.7	63.3	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
GE 16000	62.0	62.9	63.6	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9
GE 14000	63.6	64.4	65.1	65.5	65.5	65.5	65.5	65.5	65.5	65.5	65.5	65.5
GE 12000	65.2	66.1	66.8	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2
GE 10000	68.3	69.2	69.9	70.3	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7
GE 9000	69.1	70.0	70.7	71.1	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4
GE 8000	72.4	73.4	74.1	74.5	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
GE 7000	75.1	76.3	77.0	77.4	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9
GE 6000	76.8	78.1	79.1	79.6	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
GE 5000	79.3	81.2	82.3	82.9	83.4	83.4	83.7	83.7	83.7	83.7	83.7	83.7
GE 4500	81.0	82.4	83.6	84.1	84.7	84.7	84.9	84.9	84.9	84.9	84.9	84.9
GE 4000	83.1	84.6	85.7	86.2	86.9	86.9	87.2	87.2	87.2	87.2	87.2	87.2
GE 3500	83.9	85.3	86.7	87.2	87.9	87.9	88.2	88.2	88.2	88.2	88.2	88.2
GE 3000	84.2	85.7	87.0	87.6	88.3	88.3	88.7	88.8	88.8	88.8	88.9	88.9
GE 2500	85.0	86.4	87.8	88.3	89.2	89.2	89.6	89.7	89.7	89.7	89.8	89.8
GE 2000	85.9	87.3	88.7	89.4	90.3	90.3	91.0	91.1	91.1	91.1	91.2	91.2
GE 1800	86.1	87.6	88.9	89.7	90.6	90.6	91.2	91.3	91.3	91.3	91.4	91.4
GE 1500	86.7	88.1	89.4	90.2	91.1	91.1	91.8	91.9	91.9	91.9	92.0	92.0
GE 1200	87.4	88.9	90.2	91.0	92.0	92.1	92.8	92.9	92.9	92.9	93.0	93.0
GE 1000	87.9	89.3	90.8	91.6	92.6	92.8	93.6	93.7	93.7	93.7	93.8	93.8
GE 900	87.9	89.3	90.8	91.6	92.6	92.8	93.6	93.7	93.7	93.7	93.8	93.8
GE 800	88.6	90.0	91.4	92.3	93.3	93.6	94.3	94.4	94.4	94.4	94.6	94.6
GE 700	88.6	90.0	91.6	92.4	93.4	93.9	94.7	94.8	94.8	94.8	94.9	94.9
GE 600	88.9	90.3	92.0	92.9	93.9	94.3	95.1	95.2	95.2	95.2	95.3	95.3
GE 500	89.0	90.4	92.1	93.1	94.2	94.7	95.6	95.8	95.8	96.0	96.1	96.1
GE 400	89.0	90.4	92.1	93.4	95.1	95.6	96.6	96.8	96.8	97.1	97.2	97.2
GE 300	89.0	90.4	92.2	93.6	95.2	95.7	96.7	97.1	97.6	98.1	98.4	98.4
GE 200	89.0	90.4	92.2	93.6	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2
GE 100	89.0	90.4	92.2	93.6	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2
GE 000	89.0	90.4	92.2	93.6	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: 21-23

VISIBILITY IN STATUTE MILES												
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9	55.9
63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9
65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2
70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7	70.7
71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4	71.4
75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9
80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
83.7	83.4	83.4	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7
84.9	84.7	84.7	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9
87.2	85.9	86.9	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2
88.2	87.9	87.9	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2
88.9	88.3	88.3	88.7	88.8	88.8	88.8	88.9	88.9	88.9	88.9	88.9	88.9
89.8	89.2	89.2	89.6	89.7	89.7	89.7	89.8	89.8	89.8	89.8	89.8	89.8
91.2	90.3	90.3	91.0	91.1	91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2
91.4	90.6	90.6	91.2	91.3	91.3	91.3	91.4	91.4	91.4	91.4	91.4	91.4
92.0	91.1	91.1	91.8	91.9	91.9	91.9	92.0	92.0	92.0	92.0	92.0	92.0
93.0	92.0	92.1	92.8	92.9	92.9	92.9	93.0	93.0	93.0	93.0	93.0	93.0
93.8	92.6	92.8	93.6	93.7	93.7	93.7	93.8	93.8	93.8	93.8	93.8	93.8
93.8	92.6	92.8	93.6	93.7	93.7	93.7	93.8	93.8	93.8	93.8	93.8	93.8
94.6	93.3	93.6	94.3	94.4	94.4	94.4	94.6	94.6	94.6	94.6	94.6	94.6
94.9	93.4	93.9	94.7	94.8	94.8	94.8	94.9	94.9	94.9	94.9	94.9	94.9
95.3	93.9	94.3	95.1	95.2	95.2	95.2	95.3	95.3	95.3	95.3	95.3	95.3
96.1	94.2	94.7	95.6	95.8	95.8	96.0	96.1	96.1	96.1	96.1	96.1	96.1
97.2	95.1	95.6	96.6	96.8	96.8	97.1	97.2	97.2	97.2	97.2	97.2	97.2
98.6	95.2	95.7	96.7	97.1	97.6	98.1	98.4	98.4	98.4	98.4	98.4	98.6
100.0	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2	99.3	99.7	99.7	100.0
100.0	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2	99.3	99.7	99.7	100.0
100.0	95.2	95.7	96.7	97.2	97.9	98.4	99.2	99.2	99.3	99.7	99.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUN HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILFS												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	50.7	51.5	52.2	52.5	52.8	52.8	52.9	53.0	53.0	53.0	53.0	53.0	53.0
GE 20000	58.5	59.5	60.3	60.7	60.9	61.0	61.1	61.2	61.3	61.3	61.3	61.3	61.3
GE 18000	58.9	59.8	60.7	61.1	61.3	61.4	61.4	61.6	61.6	61.6	61.6	61.6	61.6
GE 16000	59.0	59.9	60.7	61.1	61.4	61.4	61.5	61.7	61.7	61.7	61.7	61.7	61.7
GE 14000	60.1	61.0	61.9	62.4	62.6	62.7	62.8	62.9	62.9	62.9	62.9	62.9	62.9
GE 12000	61.6	62.5	63.4	63.8	64.1	64.2	64.2	64.4	64.4	64.4	64.4	64.4	64.4
GE 10000	65.0	66.0	66.9	67.4	67.7	67.8	67.9	68.0	68.0	68.1	68.1	68.1	68.1
GE 9000	65.5	66.8	67.7	68.2	68.6	68.6	68.7	68.9	68.9	68.9	68.9	68.9	68.9
GE 8000	68.9	69.9	70.9	71.4	71.8	71.9	72.0	72.1	72.2	72.2	72.2	72.2	72.2
GE 7000	70.5	71.6	72.6	73.1	73.6	73.7	73.8	73.9	73.9	73.9	74.0	74.0	74.0
GE 6000	71.8	73.0	74.2	74.7	75.2	75.3	75.4	75.6	75.6	75.6	75.6	75.6	75.6
GE 5000	74.5	75.8	77.2	77.7	78.3	78.3	78.5	78.7	78.7	78.7	78.7	78.7	78.7
GE 4500	75.5	77.0	78.3	78.9	79.5	79.6	79.7	79.9	79.9	79.9	79.9	79.9	79.9
GE 4000	77.9	79.3	80.7	81.3	82.1	82.2	82.4	82.5	82.5	82.6	82.6	82.6	82.6
GE 3500	79.5	80.9	82.5	83.1	83.9	84.0	84.2	84.4	84.4	84.4	84.4	84.4	84.4
GE 3000	81.1	82.6	84.1	84.8	85.6	85.7	86.0	86.2	86.2	86.2	86.2	86.2	86.2
GE 2500	82.6	84.1	85.7	86.3	87.2	87.3	87.6	87.8	87.8	87.8	87.9	87.9	87.9
GE 2000	83.9	85.4	87.1	87.3	88.7	88.8	89.2	89.4	89.4	89.5	89.5	89.5	89.5
GE 1800	84.3	85.8	87.5	88.2	89.1	89.3	89.6	89.8	89.8	89.9	89.9	89.9	89.9
GE 1500	85.4	87.0	88.7	89.5	90.4	90.6	91.0	91.2	91.2	91.3	91.3	91.3	91.3
GE 1200	86.5	88.1	89.8	90.6	91.6	91.8	92.2	92.4	92.4	92.5	92.5	92.5	92.5
GE 1000	87.2	88.8	90.6	91.4	92.4	92.6	93.1	93.3	93.4	93.4	93.4	93.4	93.4
GE 900	87.5	89.1	90.9	91.7	92.7	92.9	93.4	93.6	93.7	93.7	93.8	93.8	93.8
GE 800	87.9	89.5	91.4	92.2	93.3	93.5	94.0	94.3	94.4	94.4	94.4	94.4	94.4
GE 700	38.3	39.9	91.8	92.7	93.8	94.0	94.6	94.8	94.9	94.9	95.0	95.0	95.0
GE 600	88.5	90.1	92.1	93.0	94.3	94.5	95.1	95.4	95.5	95.5	95.6	95.6	95.6
GE 500	88.8	90.4	92.5	93.5	94.7	95.0	95.7	96.2	96.3	96.4	96.4	96.4	96.4
GE 400	88.8	90.5	92.5	93.5	95.0	95.4	96.2	96.9	97.2	97.3	97.4	97.4	97.4
GE 300	88.8	90.5	92.6	93.7	95.2	95.6	96.4	97.3	97.7	98.0	98.2	98.2	98.2
GE 200	88.8	90.5	92.6	93.7	95.3	95.7	96.5	97.5	98.0	98.4	98.8	98.8	98.8
GE 100	88.8	90.5	92.6	93.7	95.3	95.7	95.6	97.5	98.1	98.4	98.8	98.9	98.9

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN HOURS: ALL

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
52.5	52.8	52.8	52.9	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0	53.0
60.7	60.9	61.0	61.1	61.2	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
61.1	61.3	61.4	61.4	61.6	61.6	61.6	61.6	61.6	61.6	61.7	61.7	61.7
61.1	61.4	61.4	61.5	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
62.4	62.6	62.7	62.8	62.9	62.9	62.9	62.9	62.9	62.9	63.0	63.0	63.0
63.3	64.1	64.2	64.2	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
67.4	67.7	67.8	67.9	68.0	68.0	68.1	68.1	68.1	68.1	68.1	68.1	68.1
68.2	63.6	68.6	68.7	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9
71.4	71.8	71.9	72.0	72.1	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
73.1	73.6	73.7	73.8	73.9	73.9	73.9	74.0	74.0	74.0	74.0	74.0	74.0
74.7	75.2	75.3	75.4	75.6	75.6	75.6	75.6	75.6	75.7	75.7	75.7	75.7
77.7	73.3	78.3	78.5	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
78.9	79.5	79.6	79.7	79.9	79.9	79.9	79.9	79.9	80.0	80.0	80.0	80.0
81.3	82.1	82.2	82.4	82.5	82.5	82.6	82.6	82.6	82.6	82.6	82.6	82.6
83.1	83.9	84.0	84.2	84.4	84.4	84.4	84.4	84.4	84.5	84.5	84.5	84.5
84.8	85.6	85.7	86.0	86.2	86.2	86.2	86.2	86.2	86.3	86.3	86.3	86.3
86.3	87.2	87.3	87.6	87.8	87.8	87.8	87.9	87.9	87.9	87.9	87.9	87.9
87.3	83.7	88.8	89.2	89.4	89.4	89.5	89.5	89.5	89.6	89.6	89.6	89.6
89.2	89.1	89.3	89.6	89.8	89.8	89.9	89.9	89.9	90.0	90.0	90.0	90.0
89.5	90.4	90.6	91.0	91.2	91.2	91.3	91.3	91.3	91.3	91.3	91.3	91.3
90.6	91.6	91.8	92.2	92.4	92.4	92.5	92.5	92.5	92.6	92.6	92.6	92.6
91.4	92.4	92.6	93.1	93.3	93.4	93.4	93.4	93.4	93.5	93.5	93.5	93.5
91.7	92.7	92.9	93.4	93.6	93.7	93.7	93.8	93.8	93.8	93.8	93.8	93.8
92.2	93.3	93.5	94.0	94.3	94.4	94.4	94.4	94.4	94.5	94.5	94.5	94.5
92.7	93.8	94.0	94.6	94.8	94.9	94.9	95.0	95.0	95.0	95.1	95.1	95.1
93.0	94.3	94.5	95.1	95.4	95.5	95.5	95.6	95.6	95.6	95.7	95.7	95.7
93.5	94.7	95.0	95.7	96.2	96.3	96.4	96.4	96.4	96.5	96.5	96.5	96.5
93.5	95.0	95.4	96.2	96.9	97.2	97.3	97.4	97.4	97.5	97.5	97.6	97.6
93.7	95.2	95.6	96.4	97.3	97.7	98.0	98.2	98.2	98.4	98.4	98.5	98.6
93.7	95.3	95.7	96.5	97.5	98.0	98.4	98.8	98.8	99.1	99.2	99.4	99.7
93.7	95.3	95.7	96.6	97.5	98.1	98.4	98.8	98.9	99.2	99.4	99.6	100.0
93.7	95.3	95.7	96.6	97.5	98.1	98.4	98.8	98.9	99.2	99.4	99.6	100.0

7200

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: JUL HOURS: 00-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	61.3	62.7	64.0	65.3	66.3	66.3	66.6	66.9	67.1	67.3	67.4	67.4	67.4
GE 20000	66.6	67.6	68.9	70.2	71.4	71.5	71.8	72.2	72.4	72.6	72.7	72.7	72.7
GE 18000	66.7	67.7	69.0	70.3	71.5	71.6	71.9	72.3	72.5	72.7	72.8	72.8	72.8
GE 16000	66.9	68.0	69.2	70.5	71.7	71.8	72.2	72.5	72.7	72.9	73.0	73.0	73.0
GE 14000	68.2	69.2	70.5	71.8	73.0	73.1	73.4	73.8	74.0	74.2	74.3	74.3	74.3
GE 12000	69.7	70.8	72.0	73.4	74.7	74.8	75.2	75.5	75.7	75.9	76.0	76.0	76.0
GE 10000	72.3	73.4	74.8	76.2	77.6	77.7	78.1	78.4	78.6	78.8	78.9	78.9	78.9
GE 9000	72.8	74.0	75.4	76.8	78.2	78.3	78.9	79.2	79.5	79.7	79.8	79.8	79.8
GE 8000	74.4	75.6	77.0	78.4	79.8	79.9	80.5	80.9	81.1	81.3	81.4	81.4	81.4
GE 7000	76.2	77.4	78.8	80.2	81.6	81.7	82.4	82.7	82.9	83.1	83.2	83.2	83.2
GE 6000	77.0	78.2	79.6	81.0	82.4	82.5	83.1	83.4	83.7	83.9	84.0	84.0	84.0
GE 5000	79.0	80.2	81.6	83.2	84.6	84.7	85.5	85.8	86.0	86.2	86.3	86.3	86.3
GE 4500	79.6	80.8	82.2	83.9	85.3	85.4	86.1	86.5	86.7	86.9	87.0	87.0	87.0
GE 4000	81.1	82.3	83.7	85.3	87.3	87.4	88.2	88.5	88.7	88.9	89.0	89.0	89.0
GE 3500	81.9	83.1	84.5	86.7	88.2	88.3	89.1	89.5	89.7	89.9	90.0	90.0	90.0
GE 3000	82.3	83.4	84.8	87.0	88.6	88.7	89.6	89.9	90.1	90.3	90.4	90.4	90.4
GE 2500	82.8	84.0	85.4	87.5	89.2	89.4	90.2	90.5	90.8	91.0	91.1	91.1	91.1
GE 2000	82.9	84.1	85.6	87.7	89.5	89.7	90.5	90.9	91.1	91.3	91.4	91.4	91.4
GE 1800	83.0	84.2	85.7	87.3	89.6	89.8	90.6	91.0	91.3	91.5	91.6	91.6	91.6
GE 1500	83.2	84.4	85.9	88.1	89.8	90.0	91.0	91.4	91.7	91.9	92.0	92.0	92.0
GE 1200	83.7	84.8	86.3	88.5	90.2	90.4	91.6	92.0	92.4	92.6	92.7	92.7	92.7
GE 1000	84.0	85.2	86.7	88.8	90.5	90.8	92.0	92.5	92.8	93.0	93.1	93.1	93.1
GE 900	84.1	85.3	86.8	88.9	90.6	90.9	92.2	92.6	92.9	93.1	93.2	93.2	93.2
GE 800	84.3	85.5	87.0	89.1	90.9	91.1	92.5	92.9	93.2	93.4	93.5	93.5	93.5
GE 700	84.4	85.6	87.1	89.2	91.0	91.2	92.6	93.0	93.3	93.5	93.7	93.7	93.7
GE 600	84.5	85.7	87.2	89.4	91.1	91.3	92.7	93.1	93.4	93.8	93.9	93.9	93.9
GE 500	84.6	85.8	87.3	89.5	91.3	91.5	93.1	93.5	94.1	94.5	94.6	94.6	94.6
GE 400	84.8	86.0	87.5	89.7	91.5	91.7	93.3	93.8	94.7	95.2	95.3	95.3	95.3
GE 300	84.8	86.0	87.5	89.8	91.8	92.2	94.0	94.7	95.7	96.2	96.5	96.5	96.5
GE 200	84.9	86.1	87.6	89.9	92.2	92.7	94.9	95.7	96.7	97.2	97.4	97.4	97.4
GE 100	84.9	86.1	87.6	89.9	92.2	92.7	94.9	95.7	96.9	97.4	97.8	97.8	97.8
GE 000	84.9	86.1	87.6	89.9	92.2	92.7	94.9	95.7	96.9	97.4	97.8	97.8	97.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: 00-02

VISIBILITY IN STATUTE MILES

CE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
65.3	66.3	66.3	66.6	66.9	67.1	67.3	67.4	67.4	67.4	67.4	67.4	67.4
70.2	71.4	71.5	71.8	72.2	72.4	72.6	72.7	72.7	72.7	72.7	72.7	72.7
70.3	71.5	71.6	71.9	72.3	72.5	72.7	72.8	72.8	72.8	72.8	72.8	72.8
70.5	71.7	71.8	72.2	72.5	72.7	72.9	73.0	73.0	73.0	73.0	73.0	73.0
71.8	73.0	73.1	73.4	73.8	74.0	74.2	74.3	74.3	74.3	74.3	74.3	74.3
73.4	74.7	74.8	75.2	75.5	75.7	75.9	76.0	76.0	76.0	76.0	76.0	76.0
76.2	77.6	77.7	78.1	78.4	78.6	78.8	78.9	78.9	78.9	78.9	78.9	78.9
76.8	73.2	78.3	78.9	79.2	79.5	79.7	79.8	79.8	79.8	79.8	79.8	79.8
78.4	79.4	79.9	80.5	80.9	81.1	81.3	81.4	81.4	81.4	81.4	81.4	81.4
80.2	81.6	81.7	82.4	82.7	82.9	83.1	83.2	83.2	83.2	83.2	83.2	83.2
81.0	82.4	82.5	83.1	83.4	83.7	83.9	84.0	84.0	84.0	84.0	84.0	84.0
83.2	84.6	84.7	85.5	85.8	86.0	86.2	86.3	86.3	86.3	86.3	86.3	86.3
83.9	85.3	85.4	86.1	86.5	86.7	86.9	87.0	87.0	87.0	87.0	87.0	87.0
85.3	87.3	87.4	88.2	88.5	88.7	88.9	89.0	89.0	89.0	89.0	89.0	89.0
86.7	88.2	88.3	89.1	89.5	89.7	89.9	90.0	90.0	90.0	90.0	90.0	90.0
87.0	88.6	88.7	89.6	89.9	90.1	90.3	90.4	90.4	90.4	90.4	90.4	90.4
87.5	89.2	89.4	90.2	90.5	90.8	91.0	91.1	91.1	91.1	91.1	91.1	91.1
87.7	89.5	89.7	90.5	90.9	91.1	91.3	91.4	91.4	91.4	91.4	91.4	91.4
87.7	89.6	89.8	90.6	91.0	91.3	91.5	91.6	91.6	91.7	91.7	91.8	91.8
88.1	89.8	90.0	91.0	91.4	91.7	91.9	92.0	92.0	92.2	92.2	92.3	92.3
88.5	90.2	90.4	91.6	92.0	92.4	92.6	92.7	92.7	92.8	92.8	92.9	92.9
88.8	90.5	90.8	92.0	92.5	92.8	93.0	93.1	93.1	93.2	93.2	93.3	93.3
88.9	90.6	90.9	92.2	92.6	92.9	93.1	93.2	93.2	93.3	93.3	93.4	93.4
89.1	90.9	91.1	92.5	92.9	93.2	93.4	93.5	93.5	93.7	93.7	93.8	93.8
89.2	91.0	91.2	92.6	93.0	93.3	93.5	93.7	93.7	93.8	93.8	93.9	93.9
89.4	91.1	91.3	92.7	93.1	93.4	93.8	93.9	93.9	94.0	94.0	94.1	94.1
89.5	91.3	91.5	93.1	93.5	94.1	94.5	94.6	94.6	94.8	94.8	94.9	94.9
89.7	91.5	91.7	93.3	93.8	94.7	95.2	95.3	95.3	95.6	95.6	95.7	95.7
89.8	91.8	92.2	94.0	94.7	95.7	96.2	96.5	96.5	96.8	96.8	96.9	96.9
89.9	92.2	92.7	94.9	95.7	96.7	97.2	97.4	97.4	97.8	98.1	98.5	98.6
89.9	92.2	92.7	94.9	95.7	96.9	97.4	97.8	97.8	98.4	98.7	99.2	100.0
89.9	92.2	92.7	94.9	95.7	96.9	97.4	97.8	97.8	98.4	98.7	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUL HOURS: 03

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	54.5	54.9	56.7	57.7	59.8	60.3	60.9	61.2	61.2	61.6	62.3	62.4
GE 20000	58.3	58.6	60.6	61.7	63.8	64.4	64.9	65.3	65.3	65.7	66.3	66.5
GE 18000	58.4	58.7	60.8	61.8	63.9	64.5	65.1	65.4	65.4	65.8	66.5	66.6
GE 16000	58.7	59.0	61.1	62.2	64.2	64.8	65.4	65.7	65.7	66.1	66.8	66.9
GE 14000	60.4	60.8	62.8	63.9	65.9	66.6	67.1	67.4	67.4	67.8	68.5	68.6
GE 12000	62.6	62.9	64.9	66.0	68.2	68.9	69.6	69.9	69.9	70.3	71.0	71.1
GE 10000	65.3	65.6	67.7	68.8	71.0	71.7	72.4	72.7	72.7	73.1	73.8	73.9
GE 9000	66.1	66.5	68.6	69.7	71.8	72.6	73.5	73.9	73.9	74.3	74.9	75.1
GE 8000	68.2	68.6	71.0	72.0	74.2	74.9	75.9	76.3	76.3	76.9	77.5	77.6
GE 7000	69.4	69.8	72.2	73.2	75.4	76.1	77.1	77.5	77.5	78.1	78.7	78.8
GE 6000	70.2	70.6	73.0	74.2	76.3	77.1	78.1	78.5	78.5	79.0	79.7	79.8
GE 5000	71.9	72.5	74.8	76.0	78.2	78.9	79.9	80.3	80.3	80.9	81.5	81.6
GE 4500	72.4	72.9	75.3	76.5	78.6	79.4	80.3	80.8	80.8	81.3	81.9	82.0
GE 4000	74.0	74.5	77.0	78.3	80.5	81.4	82.4	82.8	82.8	83.3	84.0	84.1
GE 3500	74.8	75.4	77.8	79.1	81.4	82.4	83.3	83.8	83.8	84.3	84.9	85.1
GE 3000	74.9	75.5	78.0	79.2	81.5	82.5	83.4	83.9	83.9	84.4	85.1	85.2
GE 2500	75.6	76.1	78.6	79.9	82.3	83.2	84.2	84.6	84.6	85.2	85.8	85.9
GE 2000	76.3	76.9	79.4	80.6	83.0	84.0	85.4	85.8	85.8	86.3	87.0	87.1
GE 1800	76.3	76.9	79.4	80.6	83.0	84.0	85.4	85.8	85.8	86.3	87.0	87.1
GE 1500	77.1	77.6	80.2	81.5	83.9	84.8	86.2	86.9	86.9	87.4	88.1	88.2
GE 1200	77.3	77.8	80.6	81.9	84.3	85.3	86.7	87.4	87.4	88.0	88.6	88.7
GE 1000	77.4	78.1	80.9	82.2	84.6	85.6	87.2	88.0	88.0	88.5	89.1	89.2
GE 900	77.7	78.5	81.3	82.6	85.1	86.0	87.6	88.4	88.4	88.9	89.6	89.7
GE 800	78.1	78.8	81.7	83.0	85.5	86.6	88.3	89.0	89.0	89.6	90.2	90.3
GE 700	78.2	78.9	81.9	83.2	85.8	86.9	88.6	89.4	89.4	89.9	90.5	90.6
GE 600	78.6	79.4	82.4	83.7	86.3	87.4	89.2	90.0	90.0	90.5	91.2	91.3
GE 500	79.0	79.8	82.9	84.2	86.9	88.0	90.2	91.1	91.1	91.6	92.3	92.4
GE 400	79.1	79.9	83.1	84.5	87.4	88.5	90.9	92.0	92.3	92.8	93.4	93.5
GE 300	79.8	80.6	83.9	85.4	88.5	89.6	92.2	93.5	93.8	94.4	95.1	95.2
GE 200	79.8	80.8	84.0	85.6	88.7	89.8	92.7	94.1	94.3	94.9	95.7	95.8
GE 100	79.8	80.8	84.0	85.6	88.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8
GE 000	79.8	80.8	84.0	85.6	88.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MT
ELEVATION: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: 03-05

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
7	59.8	60.3	60.9	61.2	61.2	61.6	62.3	62.4	62.8	62.8	63.3	63.3
7	63.8	64.4	64.9	65.3	65.3	65.7	66.3	66.5	66.9	66.9	67.4	67.4
6	63.9	64.5	65.1	65.4	65.4	65.8	66.5	66.6	67.0	67.0	67.5	67.5
2	64.2	64.8	65.4	65.7	65.7	66.1	66.8	66.9	67.3	67.3	67.8	67.8
3	65.9	66.6	67.1	67.4	67.4	67.8	68.5	68.6	69.0	69.0	69.6	69.6
0	68.2	68.9	69.6	69.9	69.9	70.3	71.0	71.1	71.5	71.5	72.0	72.0
5	71.0	71.7	72.4	72.7	72.7	73.1	73.8	73.9	74.3	74.3	74.8	74.8
3	71.8	72.6	73.5	73.9	73.9	74.3	74.9	75.1	75.5	75.5	76.0	76.0
5	74.2	74.9	75.9	76.3	76.3	76.9	77.5	77.6	78.1	78.1	78.6	78.6
1	75.4	76.1	77.1	77.5	77.5	78.1	78.7	78.8	79.2	79.2	79.8	79.8
2	76.3	77.1	78.1	78.5	78.5	79.0	79.7	79.8	80.2	80.2	80.8	80.8
0	73.2	78.9	79.9	80.3	80.3	80.9	81.5	81.6	82.0	82.0	82.6	82.6
0	79.6	79.4	80.3	80.8	80.8	81.3	81.9	82.0	82.5	82.5	83.0	83.0
5	80.5	81.4	82.4	82.8	82.8	83.3	84.0	84.1	84.5	84.5	85.1	85.1
5	81.4	82.4	83.3	83.8	83.8	84.3	84.9	85.1	85.5	85.5	86.0	86.0
5	81.5	82.5	83.4	83.9	83.9	84.4	85.1	85.2	85.6	85.6	86.1	86.1
6	82.3	83.2	84.2	84.6	84.6	85.2	85.8	85.9	86.3	86.3	86.9	86.9
5	83.0	84.0	85.4	85.8	85.8	86.3	87.0	87.1	87.5	87.5	88.1	88.1
6	83.0	84.0	85.4	85.8	85.8	86.3	87.0	87.1	87.5	87.5	88.1	88.1
5	83.9	84.9	86.2	86.9	86.9	87.4	88.1	88.2	88.6	88.6	89.1	89.1
6	84.3	85.3	86.7	87.4	87.4	88.0	88.6	88.7	89.1	89.1	89.7	89.7
1	84.6	85.6	87.2	88.0	88.0	88.5	89.1	89.2	89.7	89.7	90.2	90.2
7	85.1	86.0	87.6	88.4	88.4	88.9	89.6	89.7	90.1	90.1	90.6	90.6
1	85.5	86.6	88.3	89.0	89.0	89.6	90.2	90.3	90.8	90.8	91.3	91.3
3	85.3	86.9	88.6	89.4	89.4	89.9	90.5	90.6	91.1	91.1	91.6	91.6
1	86.3	87.4	89.2	90.0	90.0	90.5	91.2	91.3	91.7	91.7	92.3	92.3
7	86.9	88.0	90.2	91.1	91.1	91.6	92.3	92.4	92.8	92.8	93.3	93.3
8	87.4	88.5	90.9	92.0	92.3	92.8	93.4	93.5	94.0	94.0	94.5	94.5
0	88.5	89.6	92.2	93.5	93.8	94.4	95.1	95.2	95.6	95.8	96.5	96.5
6	88.7	89.8	92.7	94.1	94.3	94.9	95.7	95.8	96.7	96.9	98.3	98.4
7	89.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8	97.6	97.8	99.5	99.9
6	89.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8	97.6	97.8	99.5	99.9
5	89.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8	97.6	97.8	99.5	99.9
5	89.7	89.8	92.9	94.4	94.8	95.8	96.7	96.8	97.6	97.8	99.5	99.9

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUL HOURS: 06

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	48.2	48.8	49.6	50.5	51.9	52.5	53.1	53.8	53.9	54.1	54.4	54.5
GE 20000	54.7	55.4	56.5	58.0	59.9	60.4	61.2	61.8	62.0	62.4	62.8	62.9
GE 19000	54.7	55.4	56.5	58.0	59.9	60.4	61.2	61.8	62.0	62.4	62.8	62.9
GE 16000	55.1	55.7	56.8	58.3	60.2	60.8	61.5	62.2	62.4	62.7	63.1	63.2
GE 14000	56.3	57.0	58.1	59.6	61.8	62.4	63.1	64.1	64.3	64.6	65.1	65.2
GE 12000	58.9	59.7	60.8	62.4	64.9	65.6	66.5	67.5	67.7	68.1	68.5	68.6
GE 10000	60.6	61.6	62.8	64.4	67.1	67.7	68.6	69.8	70.0	70.4	70.9	71.0
GE 9000	61.2	62.2	63.5	65.2	67.8	68.5	69.4	70.5	70.8	71.2	71.6	71.7
GE 8000	64.6	65.6	67.2	68.8	71.6	72.3	73.1	74.4	74.6	75.1	75.5	75.6
GE 7000	65.7	66.7	68.4	70.0	72.9	73.5	74.4	75.8	76.0	76.5	76.9	77.0
GE 6000	66.7	67.6	69.4	71.0	73.9	74.5	75.4	76.8	77.0	77.4	77.8	78.0
GE 5000	68.8	69.8	71.5	73.4	76.7	77.3	78.2	79.6	79.8	80.3	80.8	80.9
GE 4500	69.0	70.1	71.8	73.9	77.2	78.0	78.9	80.3	80.5	81.1	81.5	81.6
GE 4000	70.1	71.2	73.0	75.3	78.7	79.5	80.4	81.8	82.2	82.7	83.1	83.2
GE 3500	70.4	71.5	73.3	75.6	79.0	79.8	80.8	82.2	82.5	83.0	83.4	83.5
GE 3000	71.0	72.0	73.9	76.1	79.9	80.6	81.6	83.1	83.4	84.0	84.4	84.5
GE 2500	71.4	72.5	74.3	76.6	80.3	81.1	82.2	83.7	84.0	84.5	84.9	85.1
GE 2000	72.0	73.1	74.9	77.4	81.4	82.2	83.3	84.8	85.2	85.7	86.1	86.2
GE 1900	72.0	73.1	74.9	77.4	81.4	82.2	83.3	84.9	85.2	85.7	86.1	86.2
GE 1500	72.5	73.5	75.5	78.0	81.9	82.7	83.9	85.5	85.8	86.3	86.8	86.9
GE 1200	73.5	74.8	77.0	79.5	83.8	84.5	85.8	87.4	87.7	88.3	88.7	88.8
GE 1000	73.7	74.9	77.2	79.7	84.1	84.8	86.2	87.8	88.2	88.7	89.1	89.2
GE 900	74.3	75.6	77.8	80.3	84.7	85.5	86.9	88.5	88.8	89.4	89.8	89.9
GE 800	74.7	76.0	78.4	81.1	85.5	86.2	87.6	89.2	89.6	90.1	90.5	90.6
GE 700	74.8	76.1	78.5	81.2	85.7	86.5	87.8	89.5	89.8	90.3	90.8	90.9
GE 600	74.9	76.3	79.1	82.2	86.7	87.6	89.0	90.6	91.0	91.5	91.9	92.0
GE 500	74.9	76.3	79.5	82.6	87.3	88.3	89.7	91.6	92.0	92.6	93.0	93.1
GE 400	74.9	76.3	79.6	82.8	87.5	88.5	89.9	92.0	93.0	93.7	94.2	94.3
GE 300	74.9	76.3	79.6	82.9	87.6	88.6	90.4	92.7	94.0	94.8	95.6	95.7
GE 200	74.9	76.3	79.6	82.9	87.6	88.6	90.6	93.0	94.3	95.3	96.3	96.5
GE 100	74.9	76.3	79.6	82.9	87.6	88.6	90.6	93.1	94.4	95.4	96.6	96.7

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: 06-08

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
50.5	51.9	52.5	53.1	53.8	53.9	54.1	54.4	54.5	54.8	54.9	55.1	55.4
58.0	59.9	60.4	61.2	61.8	62.0	62.4	62.8	62.9	63.2	63.3	63.5	63.9
58.0	59.9	60.4	61.2	61.8	62.0	62.4	62.8	62.9	63.2	63.3	63.5	63.9
58.3	60.2	60.8	61.5	62.2	62.4	62.7	63.1	63.2	63.5	63.7	63.9	64.2
59.6	61.8	62.4	63.1	64.1	64.3	64.6	65.1	65.2	65.5	65.6	65.8	66.1
62.4	64.9	65.6	66.5	67.5	67.7	68.1	68.5	68.6	68.9	69.0	69.2	69.6
64.4	67.1	67.7	68.6	69.8	70.0	70.4	70.9	71.0	71.4	71.5	71.7	72.0
65.2	67.8	68.5	69.4	70.5	70.8	71.2	71.6	71.7	72.2	72.3	72.5	72.8
68.3	71.6	72.3	73.1	74.4	74.6	75.1	75.5	75.6	76.0	76.1	76.3	76.7
70.0	72.9	73.5	74.4	75.8	76.0	76.5	76.9	77.0	77.4	77.5	77.7	78.1
71.0	73.9	74.5	75.4	76.8	77.0	77.4	77.8	78.0	78.4	78.5	78.7	79.0
73.4	76.7	77.3	78.2	79.6	79.8	80.3	80.8	80.9	81.3	81.4	81.6	81.9
73.9	77.2	78.0	78.9	80.3	80.5	81.1	81.5	81.6	82.2	82.6	82.8	83.1
75.3	78.7	79.5	80.4	81.8	82.2	82.7	83.1	83.2	83.8	84.2	84.4	84.7
75.6	79.0	79.8	80.8	82.2	82.5	83.0	83.4	83.5	84.1	84.5	84.7	85.1
76.1	79.9	80.6	81.6	83.1	83.4	84.0	84.4	84.5	85.1	85.5	85.7	86.0
76.6	80.3	81.1	82.2	83.7	84.0	84.5	84.9	85.1	85.6	86.0	86.2	86.6
77.4	81.4	82.2	83.3	84.8	85.2	85.7	86.1	86.2	86.8	87.2	87.4	87.7
77.4	81.4	82.2	83.3	84.9	85.2	85.7	86.1	86.2	86.8	87.2	87.4	87.7
78.0	81.9	82.7	83.9	85.5	85.8	86.3	86.8	86.9	87.4	87.8	88.1	88.4
79.5	83.3	84.5	85.8	87.4	87.7	88.3	88.7	88.8	89.4	89.8	90.0	90.3
79.7	84.1	84.8	86.2	87.8	88.2	88.7	89.1	89.2	89.8	90.2	90.4	90.8
80.3	84.7	85.5	86.9	88.5	88.8	89.4	89.8	89.9	90.4	90.9	91.1	91.4
81.1	85.5	86.2	87.6	89.2	89.6	90.1	90.5	90.6	91.2	91.6	91.8	92.2
81.2	85.7	86.5	87.8	89.5	89.8	90.3	90.8	90.9	91.4	91.8	92.0	92.4
82.2	86.7	87.6	89.0	90.6	91.0	91.5	91.9	92.0	92.6	93.0	93.2	93.5
82.6	87.3	88.3	89.7	91.6	92.0	92.6	93.0	93.1	93.7	94.1	94.3	94.6
82.8	87.5	88.5	89.9	92.0	93.0	93.7	94.2	94.3	94.8	95.3	95.5	95.8
82.9	87.6	88.6	90.4	92.7	94.0	94.8	95.6	95.7	96.2	96.7	96.9	97.3
82.4	87.6	88.6	90.6	93.0	94.3	95.3	96.3	96.5	97.1	97.8	98.3	99.1
82.9	87.6	88.6	90.6	93.1	94.4	95.4	96.6	96.7	97.4	98.3	98.7	100.0
82.9	87.6	88.6	90.6	93.1	94.4	95.4	96.6	96.7	97.4	98.3	98.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSU
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: JUL HOUR

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	49.8	51.8	52.0	52.3	52.8	53.2	53.5	53.9	53.9	53.9	53.9	53
GE 20000	57.5	59.7	60.2	60.5	61.5	61.9	62.3	62.6	62.6	62.6	62.6	62
GE 18000	59.0	60.1	60.6	61.0	61.9	62.4	62.7	63.0	63.0	63.0	63.0	63
GE 16000	58.1	60.2	60.8	61.1	62.0	62.5	62.8	63.1	63.1	63.1	63.1	63
GE 14000	60.3	62.5	63.0	63.3	64.4	64.9	65.3	65.6	65.6	65.6	65.6	65
GE 12000	63.3	65.6	66.1	66.6	67.8	68.4	68.8	69.1	69.1	69.1	69.1	69
GE 10000	66.0	68.4	69.0	69.6	71.0	71.5	71.9	72.3	72.3	72.3	72.3	72
GE 9000	67.1	69.5	70.2	70.8	72.2	72.7	73.1	73.4	73.4	73.4	73.4	73
GE 8000	70.4	73.0	73.9	74.5	76.0	76.6	77.0	77.3	77.3	77.3	77.3	77
GE 7000	71.3	73.9	74.7	75.4	76.9	77.4	77.8	78.2	78.2	78.2	78.2	78
GE 6000	72.0	74.7	75.7	76.3	77.8	78.4	78.8	79.1	79.1	79.1	79.1	79
GE 5000	73.5	76.5	78.3	78.9	80.6	81.2	81.7	82.0	82.0	82.0	82.0	82
GE 4500	73.8	76.8	78.6	79.2	81.1	81.6	82.2	82.5	82.6	82.6	82.6	82
GE 4000	73.9	76.9	79.0	79.7	81.6	82.2	82.8	83.1	83.2	83.2	83.2	83
GE 3500	74.5	77.5	79.7	80.3	82.3	82.8	83.4	83.8	83.9	83.9	83.9	83
GE 3000	75.6	78.7	80.9	81.5	83.5	84.2	84.9	85.4	85.5	85.5	85.5	85
GE 2500	77.2	80.4	82.8	83.5	85.7	86.3	87.1	87.5	87.6	87.6	87.6	87
GE 2000	79.1	82.4	84.7	85.5	87.7	88.5	89.2	89.7	89.8	89.8	89.8	89
GE 1800	79.5	82.7	85.1	85.8	88.1	88.8	89.6	90.0	90.1	90.1	90.1	90
GE 1500	80.3	83.5	86.1	87.0	89.2	90.0	91.0	91.4	91.5	91.5	91.5	91
GE 1200	81.1	84.3	87.0	87.8	90.1	90.9	92.0	92.5	92.6	92.6	92.6	92
GE 1000	81.9	85.3	88.6	89.5	91.8	92.6	94.0	94.4	94.5	94.5	94.5	94
GE 900	82.2	85.6	89.0	89.9	92.3	93.0	94.4	94.8	94.9	94.9	94.9	94
GE 800	82.4	85.9	89.5	90.3	92.8	93.5	94.9	95.4	95.5	95.5	95.5	95
GE 700	83.0	86.6	90.1	91.0	93.5	94.3	95.7	96.1	96.2	96.2	96.2	96
GE 600	83.1	86.7	90.3	91.2	93.8	94.8	96.6	97.0	97.1	97.2	97.2	97
GE 500	83.3	86.9	90.6	91.5	94.1	95.2	97.0	97.4	97.5	97.6	97.6	97
GE 400	83.3	86.9	90.9	91.7	94.3	95.4	97.3	97.8	98.1	98.5	98.5	98
GE 300	83.3	86.9	90.9	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99
GE 200	83.3	86.9	90.9	91.7	94.3	95.4	97.4	98.3	98.3	99.4	99.5	99
GE 100	83.3	86.9	90.9	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99
GE 000	83.3	86.9	90.9	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 MONTH: JUL HOURS: 09-11
 UTC: + 5

VISIBILITY IN STATUTE MILES

CEILING	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
50	52.3	52.8	53.2	53.5	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9	53.9
55	60.5	61.5	61.9	62.3	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6
60	61.0	61.9	62.4	62.7	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0
65	61.1	62.0	62.5	62.8	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
70	63.3	64.4	64.9	65.3	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
75	66.6	67.8	68.4	68.8	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1	69.1
80	70.6	71.0	71.5	71.9	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3
85	70.8	72.2	72.7	73.1	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4	73.4
90	74.5	76.0	76.6	77.0	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3	77.3
95	75.4	76.9	77.4	77.8	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2	78.2
100	76.3	77.8	78.4	78.8	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1
110	80.9	80.6	81.2	81.7	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0
120	79.2	81.1	81.6	82.2	82.5	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
130	77.7	81.6	82.2	82.8	83.1	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
140	80.3	82.3	82.8	83.4	83.8	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9
150	81.5	83.5	84.2	84.9	85.4	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5
160	83.5	85.7	86.3	87.1	87.5	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
170	85.5	87.7	88.5	89.2	89.7	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
180	86.8	88.1	88.8	89.6	90.0	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
190	87.0	89.2	90.0	91.0	91.4	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
200	87.8	90.1	90.9	92.0	92.5	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
220	91.5	91.8	92.6	94.0	94.4	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
240	91.9	92.3	93.0	94.4	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
260	90.3	92.8	93.5	94.9	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
280	91.0	93.5	94.3	95.7	96.1	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
300	91.2	93.8	94.8	96.6	97.0	97.1	97.2	97.2	97.2	97.2	97.2	97.2	97.2
320	91.5	94.1	95.2	97.0	97.4	97.5	97.6	97.6	97.6	97.6	97.6	97.6	97.6
340	91.7	94.3	95.4	97.3	97.8	98.1	98.5	98.5	98.5	98.5	98.5	98.5	98.5
360	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99.5	99.5	99.5	99.5	99.5
380	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99.6	99.8	99.8	99.9	100.0
400	91.7	94.3	95.4	97.4	98.3	98.8	99.4	99.5	99.6	99.8	99.8	99.9	100.0

430

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: JUL HOURS: 12

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	44.9	46.1	46.8	47.0	47.0	47.0	47.3	47.3	47.3	47.3	47.3	47.3
GE 20000	57.4	59.1	60.1	60.5	60.8	60.8	61.1	61.1	61.1	61.1	61.1	61.1
GE 18000	57.6	59.4	60.3	60.8	61.0	61.0	61.3	61.3	61.3	61.3	61.3	61.3
GE 16000	57.7	59.5	60.4	60.9	61.1	61.1	61.4	61.4	61.4	61.4	61.4	61.4
GE 14000	58.3	60.5	61.5	61.9	62.2	62.2	62.5	62.5	62.5	62.5	62.5	62.5
GE 12000	61.0	62.7	63.7	64.1	64.3	64.3	64.6	64.6	64.6	64.6	64.6	64.6
GE 10000	64.3	66.0	67.0	67.5	67.7	67.7	68.1	68.1	68.1	68.1	68.1	68.1
GE 9000	65.3	67.0	68.0	68.5	68.7	68.7	69.0	69.0	69.0	69.0	69.0	69.0
GE 8000	68.4	70.1	71.3	71.9	72.2	72.2	72.5	72.5	72.5	72.5	72.5	72.5
GE 7000	69.5	71.2	72.5	73.2	73.4	73.4	73.8	73.8	73.8	73.8	73.8	73.8
GE 6000	70.9	72.6	74.0	74.7	74.9	74.9	75.3	75.3	75.3	75.3	75.3	75.3
GE 5000	73.7	75.8	77.5	78.4	79.1	79.1	79.5	79.5	79.5	79.5	79.5	79.5
GE 4500	74.2	76.3	78.1	78.9	79.7	79.7	80.0	80.0	80.0	80.0	80.0	80.0
GE 4000	76.0	78.2	80.0	81.1	81.8	81.9	82.3	82.3	82.3	82.3	82.3	82.3
GE 3500	78.5	80.5	82.9	84.0	84.8	84.9	85.3	85.3	85.3	85.3	85.3	85.3
GE 3000	81.8	84.2	86.6	87.7	88.8	88.9	89.2	89.2	89.2	89.2	89.2	89.2
GE 2500	83.4	85.9	88.3	89.5	90.6	90.9	91.2	91.2	91.2	91.2	91.2	91.2
GE 2000	84.9	87.6	90.2	91.4	92.6	92.8	93.4	93.4	93.4	93.4	93.4	93.4
GE 1800	85.2	87.8	90.4	91.6	92.9	93.1	93.8	93.8	93.8	93.8	93.8	93.8
GE 1500	85.6	88.5	91.1	92.4	93.7	93.9	94.5	94.5	94.5	94.5	94.5	94.5
GE 1200	86.3	89.4	92.4	93.7	94.9	95.2	95.8	95.9	95.9	95.9	95.9	95.9
GE 1000	86.7	89.8	92.5	94.2	95.6	95.8	96.6	96.7	96.7	96.7	96.7	96.7
GE 900	87.1	90.2	93.2	94.5	96.0	96.2	97.0	97.1	97.1	97.1	97.1	97.1
GE 800	87.2	90.3	93.4	94.9	96.3	96.6	97.3	97.4	97.4	97.4	97.4	97.4
GE 700	87.5	90.6	93.8	95.3	96.7	96.9	97.7	98.0	98.0	98.0	98.0	98.0
GE 600	87.6	90.8	93.9	95.4	96.8	97.0	97.8	98.3	98.3	98.3	98.3	98.3
GE 500	87.6	90.8	93.9	95.4	96.8	97.0	97.8	98.4	98.4	98.4	98.4	98.4
GE 400	87.8	91.1	94.3	95.9	97.5	97.7	98.8	99.4	99.4	99.4	99.4	99.4
GE 300	87.3	91.1	94.3	95.9	97.5	97.7	98.8	99.5	99.6	99.6	99.6	99.6
GE 200	87.8	91.1	94.3	95.9	97.5	97.7	98.8	99.6	99.7	99.7	99.7	99.8 1
GE 100	87.3	91.1	94.3	95.9	97.5	97.7	98.8	99.5	99.7	99.7	99.7	99.8 1
GE 000	87.3	91.1	94.3	95.9	97.5	97.7	98.8	99.6	99.7	99.7	99.7	99.8 1

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME: + 5 MONTH: JUL HOURS: 12-14

E 2	VISIBILITY IN STATUTE MILES												
	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0.3	47.0	47.0	47.0	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
0.1	60.5	60.8	60.8	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1	61.1
0.3	60.8	61.0	61.0	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
0.4	60.9	61.1	61.1	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4
0.5	61.9	62.2	62.2	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5	62.5
0.6	64.1	64.3	64.3	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6	64.6
0.1	67.5	67.7	67.7	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1	68.1
0.0	68.5	68.7	68.7	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
0.5	71.9	72.2	72.2	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5	72.5
0.8	73.2	73.4	73.4	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8
0.3	74.7	74.9	74.9	75.3	75.3	75.3	75.3	75.3	75.3	75.3	75.3	75.3	75.3
0.5	78.4	79.1	79.1	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5
0.0	79.9	79.7	79.7	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
0.3	81.1	81.8	81.9	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3
0.3	84.0	84.8	84.9	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
0.2	87.7	88.8	88.9	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
0.2	90.5	90.6	90.9	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
0.4	91.4	92.6	92.8	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4	93.4
0.8	91.9	92.9	93.1	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
0.5	92.4	93.7	93.9	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
0.9	93.7	94.9	95.2	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
0.7	94.2	95.6	95.8	96.6	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
0.1	95.5	96.0	96.2	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
0.4	95.9	96.3	96.6	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
0.0	96.3	96.7	96.9	97.7	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
0.3	96.4	96.8	97.0	97.8	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
0.4	96.4	96.8	97.0	97.8	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
0.4	96.9	97.5	97.7	98.8	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
0.6	96.9	97.5	97.7	98.8	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
0.0	97.5	97.5	97.7	98.8	99.6	99.7	99.7	99.7	99.7	99.8	100.0	100.0	100.0
0.0	97.5	97.5	97.7	98.8	99.6	99.7	99.7	99.7	99.7	99.8	100.0	100.0	100.0
0.0	97.5	97.5	97.7	98.8	99.6	99.7	99.7	99.7	99.7	99.8	100.0	100.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: JUL HOURS: 15-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	42.9	43.9	44.4	44.6	44.6	44.6	44.7	44.7	44.7	44.7	44.7	44.7	44.7
GE 20000	57.1	58.7	59.8	60.0	60.0	60.0	60.1	60.1	60.1	60.1	60.1	60.1	60.1
GE 18000	57.3	59.0	60.1	60.3	60.3	60.3	60.4	60.4	60.4	60.4	60.4	60.4	60.4
GE 16000	57.4	59.1	60.2	60.4	60.4	60.4	60.5	60.5	60.5	60.5	60.5	60.5	60.5
GE 14000	58.3	60.5	61.6	61.8	61.8	61.8	61.9	61.9	61.9	61.9	61.9	61.9	61.9
GE 12000	61.2	63.0	64.1	64.3	64.3	64.3	64.4	64.4	64.4	64.4	64.4	64.4	64.4
GE 10000	66.0	63.2	69.4	69.6	69.6	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7
GE 9000	66.3	68.5	69.7	69.9	69.9	69.9	70.0	70.0	70.0	70.0	70.0	70.0	70.0
GE 8000	70.0	72.2	73.4	73.8	74.0	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1
GE 7000	71.1	73.2	74.5	74.8	75.1	75.1	75.2	75.2	75.2	75.2	75.2	75.2	75.2
GE 6000	72.7	74.8	76.1	76.5	76.7	76.7	76.8	76.8	76.8	76.8	76.8	76.8	76.8
GE 5000	74.5	77.0	78.4	78.7	78.9	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0
GE 4500	76.6	79.0	80.3	80.3	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.1	81.1
GE 4000	79.4	81.8	83.8	84.3	84.5	84.5	84.8	84.8	84.8	84.8	84.8	84.8	84.8
GE 3500	82.4	84.8	86.9	87.7	88.0	88.0	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 3000	84.7	87.4	90.1	91.0	91.2	91.2	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 2500	85.6	88.3	91.2	92.2	92.4	92.4	92.7	92.8	92.8	92.8	92.8	92.8	92.8
GE 2000	86.3	89.1	92.0	93.1	93.3	93.3	93.7	93.9	93.9	94.0	94.1	94.1	94.1
GE 1800	86.5	89.2	92.2	93.2	93.5	93.5	93.9	94.1	94.1	94.2	94.3	94.3	94.3
GE 1500	86.8	89.6	92.8	93.9	94.2	94.2	94.6	94.8	94.8	94.9	95.1	95.1	95.1
GE 1200	87.3	90.2	93.7	94.9	95.4	95.4	96.0	96.2	96.2	96.3	96.5	96.5	96.5
GE 1000	87.5	90.4	93.9	95.2	95.8	95.8	96.5	96.7	96.7	96.8	96.9	96.9	96.9
GE 900	88.1	91.0	94.4	95.7	96.5	96.5	97.1	97.3	97.3	97.4	97.5	97.5	97.5
GE 800	88.6	91.5	94.9	96.2	97.0	97.0	97.5	98.0	98.0	98.1	98.2	98.2	98.2
GE 700	88.7	91.6	95.1	96.3	97.2	97.2	97.8	98.2	98.2	98.3	98.4	98.4	98.4
GE 600	88.8	91.7	95.2	96.6	97.5	97.5	98.2	98.5	98.5	98.6	98.7	98.7	98.7
GE 500	88.8	91.7	95.2	96.6	97.5	97.5	98.2	98.6	98.6	98.7	98.8	98.8	98.8
GE 400	88.8	91.7	95.3	96.7	97.8	97.8	98.5	98.9	98.9	99.0	99.1	99.1	99.1
GE 300	88.9	91.8	95.4	96.8	98.1	98.1	98.7	99.1	99.1	99.2	99.4	99.4	99.4
GE 200	88.9	91.8	95.4	96.8	98.1	98.1	98.7	99.1	99.2	99.5	99.8	99.8	100.0
GE 100	88.9	91.8	95.4	96.8	98.1	98.1	98.7	99.1	99.2	99.5	99.8	99.8	100.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
EST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: 15-17

	VISIBILITY IN STATUTE MILES												
	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
.4	44.6	44.6	44.6	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7
.6	60.0	60.0	60.0	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1	60.1
.1	60.3	60.3	60.3	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4	60.4
.2	60.4	60.4	60.4	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
.5	61.5	61.3	61.8	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9	61.9
.1	64.3	64.3	64.3	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
.4	69.6	69.6	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7	69.7
.7	69.9	69.9	69.9	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0
.4	73.9	74.0	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
.3	74.3	75.1	75.1	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2	75.2
.1	76.5	76.7	76.7	76.8	76.8	76.8	76.8	76.8	76.8	76.8	76.8	76.8	76.8
.4	78.7	78.9	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
.4	80.3	81.0	81.0	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1	81.1
.3	84.3	84.5	84.5	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
.4	87.7	88.0	88.0	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
.1	91.0	91.2	91.2	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
.2	92.2	92.4	92.4	92.7	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8
.2	93.1	93.3	93.3	93.7	93.9	93.9	94.0	94.1	94.1	94.1	94.1	94.1	94.1
.2	93.2	93.5	93.5	93.9	94.1	94.1	94.2	94.3	94.3	94.3	94.3	94.3	94.3
.1	93.9	94.2	94.2	94.5	94.8	94.8	94.9	95.1	95.1	95.1	95.1	95.1	95.1
.7	94.7	95.4	95.4	96.0	96.2	96.2	96.3	96.5	96.5	96.5	96.5	96.5	96.5
.7	95.2	95.8	95.8	96.5	96.7	96.7	96.8	96.9	96.9	96.9	96.9	96.9	96.9
.4	95.7	96.5	96.5	97.1	97.3	97.3	97.4	97.5	97.5	97.5	97.5	97.5	97.5
.3	96.2	97.0	97.0	97.5	98.0	98.0	98.1	98.2	98.2	98.2	98.2	98.2	98.2
.1	96.3	97.2	97.2	97.3	98.2	98.2	98.3	98.4	98.4	98.4	98.4	98.4	98.4
.2	96.6	97.5	97.5	98.2	98.5	98.5	98.6	98.7	98.7	98.7	98.7	98.7	98.7
.2	96.6	97.5	97.5	98.2	98.6	98.6	98.7	98.8	98.8	98.8	98.8	98.8	98.8
.3	96.7	97.8	97.8	98.5	98.9	98.9	99.0	99.1	99.1	99.1	99.1	99.1	99.1
.4	96.8	98.1	98.1	98.7	99.1	99.1	99.2	99.4	99.4	99.4	99.4	99.4	99.4
.4	96.8	98.1	98.1	98.7	99.1	99.2	99.5	99.8	99.8	100.0	100.0	100.0	100.0
.4	96.8	98.1	98.1	98.7	99.1	99.2	99.5	99.8	99.8	100.0	100.0	100.0	100.0
.4	96.8	98.1	98.1	98.7	99.1	99.2	99.5	99.8	99.8	100.0	100.0	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JUL HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	50.6	51.8	53.4	54.0	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3
GE 20000	59.4	61.0	63.0	63.6	63.9	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
GE 18000	59.8	61.4	63.5	64.0	64.3	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
GE 16000	60.0	61.6	63.7	64.2	64.5	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7
GE 14000	61.1	62.7	64.9	65.4	65.7	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8
GE 12000	63.5	65.1	67.3	68.0	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
GE 10000	68.3	70.2	72.8	73.6	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
GE 9000	69.0	70.8	73.5	74.2	74.7	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
GE 8000	72.6	74.7	77.5	78.2	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
GE 7000	74.0	76.1	78.9	79.6	80.4	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
GE 6000	75.0	77.0	79.8	80.6	81.4	81.6	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
GE 5000	76.9	79.0	82.2	83.0	83.7	83.9	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
GE 4500	78.1	80.2	83.4	84.2	84.9	85.1	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
GE 4000	80.3	82.5	85.8	86.5	87.6	87.8	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4
GE 3500	82.1	84.5	87.8	88.7	89.9	90.1	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 3000	83.3	85.8	89.2	90.2	91.4	91.6	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 2500	84.1	86.5	90.0	90.9	92.1	92.5	93.0	93.0	93.0	93.0	93.2	93.2	93.2	93.2
GE 2000	84.8	87.3	90.8	91.3	93.3	93.6	94.2	94.2	94.2	94.2	94.4	94.4	94.4	94.4
GE 1800	84.7	87.4	91.2	92.1	93.6	94.0	94.5	94.5	94.5	94.6	94.6	94.8	94.8	94.8
GE 1500	85.7	88.1	92.0	93.0	94.6	94.9	95.7	95.7	95.7	95.8	95.8	96.0	96.1	96.1
GE 1200	85.7	88.1	92.0	93.0	94.6	94.9	95.8	95.8	95.8	95.9	95.9	96.1	96.2	96.2
GE 1000	86.3	88.8	92.7	93.5	95.3	95.6	96.4	96.6	96.6	96.7	96.7	96.9	97.0	97.0
GE 900	86.5	89.0	92.9	93.9	95.5	95.8	96.7	96.8	96.8	96.9	96.9	97.1	97.2	97.2
GE 800	86.7	89.2	93.2	94.2	95.8	96.1	97.0	97.1	97.1	97.2	97.2	97.4	97.5	97.5
GE 700	87.0	89.4	93.4	94.4	96.0	96.3	97.2	97.4	97.4	97.5	97.6	97.8	98.0	98.0
GE 600	87.0	89.4	93.4	94.4	96.1	96.6	97.4	97.6	97.6	97.7	98.0	98.3	98.4	98.4
GE 500	87.3	89.8	93.8	94.7	96.7	97.2	98.1	98.3	98.4	98.6	98.9	99.0	99.1	99.1
GE 400	87.3	89.8	93.8	94.7	96.7	97.2	98.1	98.3	98.5	98.7	99.0	99.1	99.2	99.2
GE 300	87.3	89.8	93.8	94.7	96.7	97.2	98.1	98.3	98.5	98.7	99.1	99.2	99.3	99.3
GE 200	87.3	89.8	93.8	94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.8
GE 100	87.3	89.8	93.8	94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.8
GE 000	87.3	89.8	93.8	94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.8

TOTAL NUMBER OF OBSERVATIONS 928

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
T.O. UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
54.0	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3	54.3
53.6	53.9	64.0	64.0	64.0	54.0	64.0	64.0	64.0	64.0	64.0	64.0	64.0
54.0	54.3	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4	64.4
64.2	64.5	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7	64.7
65.4	65.7	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.8
68.0	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
73.6	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
74.2	74.7	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
78.2	78.9	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0	79.0
79.4	80.4	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
80.6	81.4	81.6	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
83.0	83.7	83.9	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
84.2	84.9	85.1	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
86.5	87.6	87.8	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4
88.7	89.9	90.1	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
92.2	91.4	91.6	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
93.0	92.1	92.5	93.0	93.0	93.0	93.0	93.2	93.2	93.2	93.2	93.2	93.2
91.3	93.3	93.6	94.2	94.2	94.2	94.2	94.4	94.5	94.5	94.5	94.5	94.5
92.1	93.6	94.0	94.5	94.5	94.6	94.6	94.8	94.9	94.9	94.9	94.9	94.9
93.0	94.6	94.9	95.7	95.7	95.8	95.8	96.0	96.1	96.1	96.1	96.1	96.1
93.0	94.6	94.9	95.8	95.8	95.9	95.9	96.1	96.2	96.2	96.2	96.2	96.2
93.5	95.3	95.6	96.4	96.6	96.7	96.7	96.9	97.0	97.0	97.0	97.0	97.0
93.9	95.5	95.8	96.7	96.8	96.9	96.9	97.1	97.2	97.2	97.2	97.2	97.2
94.2	95.8	96.1	97.0	97.1	97.2	97.2	97.4	97.5	97.5	97.5	97.5	97.5
94.4	96.0	96.3	97.2	97.4	97.5	97.6	97.8	98.0	98.0	98.0	98.0	98.0
94.4	96.1	96.6	97.4	97.6	97.7	98.0	98.3	98.4	98.4	98.4	98.4	98.4
94.7	96.7	97.2	98.1	98.3	98.4	98.6	98.9	99.0	99.0	99.0	99.0	99.0
94.7	96.7	97.2	98.1	98.3	98.5	98.7	99.0	99.1	99.1	99.1	99.1	99.1
94.7	96.7	97.2	98.1	98.3	98.5	98.7	99.1	99.2	99.2	99.2	99.2	99.4
94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.9	99.9	100.0
94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.9	99.9	100.0
94.7	96.9	97.4	98.3	98.6	98.9	99.1	99.7	99.8	99.8	99.9	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: JUL HOURS: 21-2

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	57.3	57.8	58.8	59.1	59.8	59.9	60.0	60.0	60.0	60.0	60.1	60.1	60
GE 20000	64.2	64.8	65.0	66.9	67.5	67.6	67.7	67.7	67.7	67.7	67.9	67.9	67
GE 18000	64.3	64.9	66.1	67.0	67.6	67.7	67.9	67.9	67.9	67.9	68.0	68.0	68
GE 16000	64.3	64.9	66.1	67.0	67.6	67.7	67.9	67.9	67.9	67.9	68.0	68.0	68
GE 14000	65.9	66.6	67.7	68.6	69.3	69.4	69.5	69.5	69.5	69.5	69.6	69.6	69
GE 12000	68.6	69.3	70.4	71.4	72.3	72.5	72.7	72.7	72.7	72.7	72.8	72.8	72
GE 10000	71.0	71.6	73.0	74.3	75.2	75.5	75.7	75.7	75.7	75.7	75.8	75.8	75
GE 9000	71.6	72.3	73.8	75.1	75.9	76.3	76.5	76.5	76.5	76.5	76.6	76.6	76
GE 8000	74.5	75.2	76.7	78.0	78.9	79.2	79.5	79.5	79.6	79.6	79.7	79.7	79
GE 7000	76.4	77.0	78.6	79.9	80.8	81.1	81.4	81.4	81.6	81.6	81.7	81.7	81
GE 6000	77.0	77.7	79.3	80.6	81.4	81.8	82.1	82.1	82.2	82.2	82.3	82.3	82
GE 5000	79.5	80.3	82.0	83.5	84.5	84.8	85.1	85.2	85.3	85.3	85.4	85.4	85
GE 4500	80.6	81.3	83.2	84.8	85.8	86.1	86.4	86.5	86.6	86.6	86.7	86.7	86
GE 4000	82.0	82.7	84.8	86.5	88.1	88.5	88.8	88.9	89.0	89.0	89.1	89.1	89
GE 3500	82.7	83.5	85.7	87.5	89.1	89.4	89.8	90.0	90.1	90.1	90.2	90.2	90
GE 3000	83.9	84.7	86.8	88.8	90.5	91.0	91.4	91.6	91.8	91.8	91.9	91.9	92
GE 2500	84.3	85.0	87.3	89.3	91.2	91.6	91.9	92.1	92.4	92.4	92.7	92.7	92
GE 2000	84.7	85.4	87.7	89.3	91.6	92.0	92.3	92.7	93.0	93.0	93.2	93.2	93
GE 1800	85.0	85.8	88.1	90.2	92.0	92.4	92.8	93.2	93.5	93.5	93.7	93.7	93
GE 1500	85.5	86.3	88.8	90.8	92.7	93.1	93.4	93.9	94.2	94.2	94.4	94.4	94
GE 1200	85.9	86.6	89.2	91.3	93.1	93.5	94.0	94.4	94.7	94.7	94.9	94.9	95
GE 1000	86.2	86.9	89.5	91.6	93.4	93.9	94.4	94.8	95.1	95.1	95.4	95.4	95
GE 900	86.3	87.1	89.8	91.8	93.6	94.1	94.6	95.0	95.4	95.4	95.6	95.6	95
GE 800	86.4	87.2	90.0	92.0	94.0	94.4	94.9	95.4	95.7	95.7	95.9	95.9	96
GE 700	86.4	87.2	90.0	92.0	94.0	94.4	94.9	95.4	95.8	95.9	96.1	96.1	96
GE 600	86.6	87.4	90.2	92.2	94.2	94.6	95.3	95.7	96.1	96.2	96.4	96.4	96
GE 500	86.6	87.4	90.2	92.2	94.2	94.6	95.5	95.9	96.3	96.5	96.8	96.8	96
GE 400	86.6	87.4	90.2	92.2	94.2	94.6	95.7	96.2	97.1	97.3	97.5	97.5	97
GE 300	85.7	87.6	90.4	92.4	94.7	95.1	96.5	97.2	98.2	98.4	98.6	98.6	98
GE 200	86.7	87.6	90.4	92.4	94.8	95.4	96.8	97.4	98.5	98.7	99.0	99.0	99
GE 100	86.7	87.6	90.4	92.4	94.8	95.4	96.8	97.4	98.5	98.7	99.0	99.0	99
GE 000	86.7	87.6	90.4	92.4	94.8	95.4	96.8	97.4	98.5	98.7	99.0	99.0	99

TOTAL NUMBER OF OBSERVATIONS 927

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JUL HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	51.3	52.2	53.2	53.8	54.6	54.8	55.1	55.3	55.3	55.4	55.5	55.6	55.7	
GE 20000	59.4	60.6	61.9	62.7	63.6	63.8	64.1	64.3	64.4	64.5	64.7	64.7	64.8	
GE 18000	59.6	60.8	62.1	62.7	63.8	64.0	64.4	64.6	64.6	64.7	64.9	64.9	65.0	
GE 16000	59.8	61.0	62.3	63.1	64.0	64.2	64.5	64.7	64.8	64.9	65.1	65.1	65.2	
GE 14000	61.2	62.5	63.8	64.5	65.5	65.8	66.1	66.3	66.4	66.5	66.7	66.7	66.8	
GE 12000	63.6	64.9	66.2	67.0	68.1	68.4	68.8	69.0	69.1	69.2	69.4	69.4	69.5	
GE 10000	66.7	68.1	69.5	70.5	71.6	72.0	72.3	72.6	72.6	72.8	72.9	73.0	73.1	
GE 9000	67.4	68.8	70.3	71.3	72.4	72.7	73.2	73.4	73.5	73.6	73.8	73.8	73.9	
GE 8000	70.4	71.9	73.5	74.5	75.7	76.0	76.4	76.7	76.8	77.0	77.1	77.1	77.2	
GE 7000	71.7	73.2	74.8	75.8	77.1	77.4	77.8	78.1	78.2	78.4	78.5	78.5	78.6	
GE 6000	72.7	74.2	75.9	76.9	78.1	78.4	78.9	79.2	79.3	79.4	79.6	79.6	79.7	
GE 5000	74.7	76.4	78.3	79.4	80.8	81.1	81.7	82.0	82.0	82.2	82.4	82.4	82.5	
GE 4500	75.5	77.2	79.1	80.3	81.7	82.0	82.6	82.9	83.0	83.1	83.3	83.3	83.4	
GE 4000	77.1	78.9	80.9	82.2	83.8	84.1	84.7	85.1	85.2	85.3	85.5	85.5	85.6	
GE 3500	78.4	80.1	82.3	83.7	85.3	85.7	86.3	86.7	86.8	86.9	87.1	87.1	87.2	
GE 3000	79.7	81.5	83.8	85.2	86.9	87.3	88.0	88.3	88.4	88.6	88.8	88.8	88.9	
GE 2500	80.5	82.3	84.7	86.2	88.0	88.4	89.1	89.4	89.5	89.7	89.9	89.9	90.0	
GE 2000	81.4	83.2	85.7	87.2	89.1	89.5	90.3	90.7	90.8	91.0	91.2	91.2	91.3	
GE 1800	81.5	83.4	85.9	87.4	89.3	89.7	90.5	90.9	91.0	91.2	91.4	91.5	91.6	
GE 1500	82.1	84.0	86.6	88.1	90.0	90.5	91.3	91.8	91.9	92.1	92.3	92.3	92.4	
GE 1200	82.6	84.5	87.3	88.8	90.8	91.3	92.2	92.7	92.9	93.0	93.2	93.3	93.4	
GE 1000	83.0	84.9	87.8	89.3	91.4	91.8	92.9	93.4	93.6	93.7	94.0	94.0	94.1	
GE 900	83.3	85.3	88.2	89.7	91.8	92.2	93.3	93.8	94.0	94.1	94.4	94.4	94.5	
GE 800	83.6	85.6	88.5	90.1	92.2	92.7	93.8	94.3	94.4	94.6	94.8	94.9	95.0	
GE 700	83.8	85.8	88.7	90.3	92.5	93.0	94.1	94.6	94.8	95.0	95.2	95.2	95.3	
GE 600	83.9	85.9	89.0	90.6	92.8	93.4	94.5	95.1	95.3	95.5	95.7	95.8	95.9	
GE 500	84.0	86.1	89.2	90.8	93.1	93.7	94.9	95.6	95.8	96.1	96.3	96.3	96.4	
GE 400	84.1	86.1	89.3	91.0	93.4	93.9	95.3	96.1	96.5	96.8	97.1	97.1	97.2	
GE 300	84.2	86.3	89.5	91.2	93.7	94.2	95.8	96.7	97.2	97.6	97.9	97.9	98.0	
GE 200	84.2	86.3	89.5	91.2	93.8	94.4	96.0	97.0	97.6	98.0	98.4	98.5	98.6	
GE 100	84.2	86.3	89.5	91.2	93.8	94.4	96.1	97.0	97.7	98.1	98.6	98.7	98.8	
GE 000	84.2	86.3	89.5	91.2	93.8	94.4	96.1	97.0	97.7	98.1	98.6	98.7	98.8	

TOTAL NUMBER OF OBSERVATIONS 7435

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: ALL

VISIBILITY IN STATUTE MILES

5	4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
53.2	53.8	54.6	54.8	55.1	55.3	55.3	55.4	55.5	55.6	55.7	55.7	55.8	55.8
61.9	62.7	63.6	63.8	64.1	64.3	64.4	64.5	64.7	64.7	64.8	64.8	64.9	64.9
62.1	62.7	63.8	64.0	64.4	64.6	64.6	64.7	64.9	64.9	65.0	65.0	65.1	65.2
62.3	63.1	64.0	64.2	64.5	64.7	64.8	64.9	65.1	65.1	65.2	65.2	65.3	65.3
63.4	64.5	65.5	65.8	66.1	66.3	66.4	66.5	66.7	66.7	66.8	66.8	66.9	66.9
64.2	67.0	68.1	68.4	68.8	69.0	69.1	69.2	69.4	69.4	69.5	69.5	69.6	69.6
70.5	70.5	71.6	72.0	72.3	72.6	72.6	72.8	72.9	73.0	73.1	73.1	73.2	73.2
70.3	71.3	72.4	72.7	73.2	73.4	73.5	73.6	73.8	73.8	73.9	73.9	74.0	74.1
73.5	74.5	75.7	76.0	76.4	76.7	76.8	77.0	77.1	77.1	77.3	77.3	77.4	77.4
74.8	75.8	77.1	77.4	77.8	78.1	78.2	78.4	78.5	78.5	78.7	78.7	78.8	78.8
74.9	76.9	78.1	78.4	78.9	79.2	79.3	79.4	79.6	79.6	79.7	79.7	79.8	79.9
77.3	79.4	80.8	81.1	81.7	82.0	82.0	82.2	82.4	82.4	82.5	82.5	82.6	82.7
79.1	80.3	81.7	82.0	82.6	82.9	83.0	83.1	83.3	83.3	83.5	83.5	83.6	83.6
80.9	82.2	83.8	84.1	84.7	85.1	85.2	85.3	85.5	85.5	85.6	85.7	85.8	85.8
82.3	83.7	85.3	85.7	86.3	86.7	86.8	86.9	87.1	87.1	87.2	87.3	87.4	87.4
83.3	85.2	86.9	87.3	88.0	88.3	88.4	88.6	88.8	88.8	88.9	89.0	89.1	89.1
84.7	86.2	88.0	88.4	89.1	89.4	89.5	89.7	89.9	89.9	90.1	90.1	90.2	90.3
85.7	87.2	89.1	89.5	90.3	90.7	90.8	91.0	91.2	91.2	91.4	91.4	91.5	91.5
85.9	87.4	89.3	89.7	90.5	90.9	91.0	91.2	91.4	91.5	91.6	91.7	91.8	91.8
86.6	88.1	90.0	90.5	91.3	91.8	91.9	92.1	92.3	92.3	92.5	92.6	92.7	92.7
87.3	88.8	90.8	91.3	92.2	92.7	92.9	93.0	93.2	93.3	93.4	93.5	93.6	93.7
87.5	89.3	91.4	91.8	92.9	93.4	93.6	93.7	94.0	94.0	94.1	94.2	94.3	94.4
88.2	89.7	91.8	92.2	93.3	93.8	94.0	94.1	94.4	94.4	94.5	94.6	94.7	94.8
88.5	90.1	92.2	92.7	93.8	94.3	94.4	94.6	94.8	94.9	95.0	95.1	95.2	95.3
88.7	90.3	92.5	93.0	94.1	94.6	94.8	95.0	95.2	95.2	95.4	95.5	95.6	95.6
88.8	90.6	92.8	93.4	94.5	95.1	95.3	95.5	95.7	95.8	95.9	96.0	96.1	96.2
89.2	90.3	93.1	93.7	94.9	95.6	95.8	96.1	96.3	96.3	96.5	96.6	96.7	96.7
89.3	91.0	93.4	93.9	95.3	96.1	96.5	96.8	97.1	97.1	97.3	97.4	97.5	97.5
89.5	91.2	93.7	94.2	95.8	96.7	97.2	97.6	97.9	97.9	98.1	98.2	98.4	98.4
89.5	91.2	93.8	94.4	96.0	97.0	97.6	98.0	98.4	98.5	98.8	99.0	99.3	99.5
89.5	91.2	93.8	94.4	96.1	97.0	97.7	98.1	98.6	98.7	99.1	99.3	99.7	100.0
89.5	91.2	93.8	94.4	96.1	97.0	97.7	98.1	98.6	98.7	99.1	99.3	99.7	100.0

INS 7435

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: AUG HOURS: 00

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	50.5	50.6	51.4	51.9	53.4	53.8	54.2	54.5	54.5	54.7	55.1	55.2
GE 20000	54.4	54.6	55.5	56.0	57.6	58.0	58.4	58.9	58.9	59.1	59.5	59.6
GE 18000	54.4	54.6	55.5	56.0	57.6	58.0	58.4	58.9	58.9	59.1	59.5	59.6
GE 16000	54.5	54.7	55.6	56.1	57.7	58.1	58.5	59.0	59.0	59.2	59.6	59.7
GE 14000	55.5	55.7	56.6	57.1	58.7	59.0	59.5	60.0	60.0	60.2	60.5	60.6
GE 12000	57.8	58.1	58.9	59.5	61.1	61.4	61.8	62.4	62.4	62.6	62.9	63.0
GE 10000	60.3	60.5	61.4	61.9	63.5	63.9	64.3	64.8	64.8	65.1	65.4	65.5
GE 9000	60.6	60.9	61.7	62.3	63.9	64.2	64.6	65.2	65.2	65.4	65.7	65.8
GE 8000	61.3	61.5	62.5	63.0	64.8	65.2	65.6	66.1	66.1	66.3	66.7	66.8
GE 7000	62.4	62.6	63.5	64.2	66.0	66.3	67.0	67.6	67.6	67.8	68.2	68.3
GE 6000	64.0	64.2	65.2	65.8	67.7	68.1	68.7	69.4	69.4	69.6	69.9	70.0
GE 5000	65.9	66.3	67.5	68.3	70.4	70.8	71.4	72.0	72.0	72.3	72.6	72.7
GE 4500	68.0	68.6	69.8	70.6	72.8	73.1	73.8	74.4	74.4	74.6	74.9	75.1
GE 4000	69.5	70.1	71.4	72.5	75.1	75.7	76.3	77.0	77.1	77.3	77.6	77.7
GE 3500	70.4	71.1	72.6	73.9	76.3	77.0	77.6	78.3	78.5	78.7	79.0	79.1
GE 3000	70.9	71.6	73.3	74.6	77.3	78.0	78.7	79.5	79.7	79.9	80.2	80.3
GE 2500	71.6	72.4	74.1	75.5	78.2	78.8	79.6	80.3	80.5	80.8	81.1	81.2
GE 2000	73.4	74.3	75.1	77.5	80.4	81.1	81.8	82.6	82.8	83.0	83.3	83.4
GE 1800	73.5	74.4	76.2	77.7	80.5	81.2	81.9	82.7	82.9	83.1	83.4	83.5
GE 1500	74.0	74.8	76.7	78.2	81.2	81.8	82.7	83.4	83.7	83.9	84.2	84.3
GE 1200	74.2	75.1	76.9	78.4	81.4	82.0	82.9	83.7	83.9	84.1	84.4	84.5
GE 1000	74.2	75.1	76.9	78.4	81.4	82.0	82.9	83.7	83.9	84.1	84.4	84.5
GE 900	74.3	75.2	77.0	78.5	81.5	82.2	83.0	83.8	84.0	84.2	84.5	84.6
GE 800	74.4	75.3	77.1	78.6	81.6	82.3	83.4	84.2	84.4	84.6	84.9	85.1
GE 700	74.6	75.5	77.4	78.9	82.3	82.9	84.1	84.8	85.1	85.3	85.6	85.7
GE 600	74.7	75.6	77.7	79.2	82.8	83.5	84.8	85.6	85.8	86.1	86.5	86.6
GE 500	75.3	76.1	78.2	79.7	83.5	84.3	85.8	86.8	87.0	87.3	87.6	87.7
GE 400	75.5	76.3	78.4	80.0	84.0	84.7	86.5	87.7	88.1	88.5	88.9	89.0
GE 300	75.6	76.5	78.5	80.3	84.4	85.2	87.2	89.5	90.0	90.6	91.4	91.6
GE 200	75.6	76.5	78.5	80.3	84.4	85.2	87.3	90.3	91.5	92.4	93.4	93.8
GE 100	75.7	76.6	78.6	80.4	84.5	85.3	87.5	90.5	91.8	92.9	94.2	94.5
GE 000	75.7	76.6	78.6	80.4	84.5	85.3	87.5	90.5	91.8	92.9	94.2	94.5

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: AUG HOURS: 00-02

VISIBILITY IN STATUTE MILES												
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
53.4	53.8	54.2	54.5	54.5	54.7	55.1	55.2	55.3	55.3	55.5	55.5	
57.6	58.0	58.4	58.9	58.9	59.1	59.5	59.6	59.7	59.7	59.9	59.9	
57.6	58.0	58.4	58.9	58.9	59.1	59.5	59.6	59.7	59.7	59.9	59.9	
57.7	58.1	58.5	59.0	59.0	59.2	59.6	59.7	59.8	59.8	60.0	60.0	
59.7	59.0	59.5	60.0	60.0	60.2	60.5	60.6	60.8	60.8	61.0	61.0	
61.1	61.4	61.8	62.4	62.4	62.6	62.9	63.0	63.1	63.1	63.3	63.3	
63.5	63.9	64.3	64.8	64.8	65.1	65.4	65.5	65.6	65.6	65.8	65.8	
63.9	64.2	64.5	65.2	65.2	65.4	65.7	65.8	65.9	65.9	66.1	66.1	
64.8	65.2	65.6	66.1	66.1	66.3	66.7	66.8	66.9	66.9	67.1	67.1	
66.0	66.3	67.0	67.6	67.6	67.8	68.2	68.3	68.4	68.4	68.6	68.6	
67.7	68.1	68.7	69.4	69.4	69.6	69.9	70.0	70.1	70.1	70.3	70.3	
70.4	70.8	71.4	72.0	72.0	72.3	72.6	72.7	72.8	72.8	73.0	73.0	
72.8	73.1	73.8	74.4	74.4	74.6	74.9	75.1	75.2	75.2	75.4	75.4	
75.1	75.7	76.3	77.0	77.1	77.3	77.6	77.7	77.8	77.8	78.1	78.1	
75.3	77.0	77.6	78.3	78.5	78.7	79.0	79.1	79.2	79.2	79.5	79.5	
77.3	78.0	78.7	79.5	79.7	79.9	80.2	80.3	80.4	80.4	80.5	80.6	
78.2	78.8	79.6	80.3	80.5	80.8	81.1	81.2	81.3	81.3	81.5	81.5	
80.4	81.1	81.8	82.6	82.8	83.0	83.3	83.4	83.5	83.5	83.8	83.8	
80.5	81.2	81.9	82.7	82.9	83.1	83.4	83.5	83.7	83.7	83.9	83.9	
81.2	81.8	82.7	83.4	83.7	83.9	84.2	84.3	84.4	84.4	84.6	84.6	
81.4	82.0	82.9	83.7	83.9	84.1	84.4	84.5	84.6	84.6	84.8	84.8	
81.4	82.0	82.9	83.7	83.9	84.1	84.4	84.5	84.6	84.6	84.8	84.8	
81.5	82.2	83.0	83.8	84.0	84.2	84.5	84.6	84.7	84.7	84.9	84.9	
81.6	82.3	83.4	84.2	84.4	84.6	84.9	85.1	85.2	85.2	85.4	85.4	
82.3	82.9	84.1	84.8	85.1	85.3	85.6	85.7	85.8	85.8	86.0	86.0	
82.8	83.5	84.8	85.6	85.8	86.1	86.5	86.6	86.7	86.7	86.9	86.9	
83.5	84.3	85.8	86.8	87.0	87.3	87.6	87.7	87.8	87.8	88.1	88.1	
84.0	84.7	86.5	87.7	88.1	88.5	88.9	89.0	89.1	89.1	89.4	89.4	
84.4	85.2	87.2	89.5	90.0	90.6	91.4	91.6	92.0	92.3	92.5	92.5	
84.4	85.2	87.3	90.3	91.5	92.4	93.4	93.8	95.4	95.8	97.1	97.2	
84.5	85.3	87.5	90.5	91.8	92.9	94.2	94.5	96.1	96.7	98.7	99.8	
84.5	85.3	87.5	90.5	91.8	92.9	94.2	94.5	96.1	96.7	98.7	100.0	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: AUG HOURS: 03-05

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	44.8	44.9	46.5	46.9	48.6	49.4	49.8	50.5	50.6	51.1	51.2	51.3	51.4	
GE 20000	48.1	48.2	49.9	50.3	52.0	52.8	53.2	54.3	54.4	54.8	54.9	55.1	55.2	
GE 18000	48.3	48.4	50.1	50.5	52.3	53.0	53.4	54.5	54.6	55.1	55.2	55.3	55.4	
GE 16000	48.4	48.5	50.2	50.6	52.4	53.1	53.5	54.6	54.7	55.2	55.3	55.4	55.5	
GE 14000	49.6	49.7	51.4	51.8	53.5	54.3	54.7	55.8	55.9	56.3	56.5	56.6	56.7	
GE 12000	51.0	51.1	52.8	53.2	55.1	55.9	56.2	57.3	57.4	57.8	58.0	58.1	58.2	
GE 10000	53.1	53.2	54.9	55.4	57.2	58.0	58.4	59.5	59.6	60.0	60.1	60.2	60.3	
GE 9000	53.5	53.7	55.4	55.8	57.6	58.4	58.8	59.9	60.0	60.4	60.5	60.6	60.8	
GE 8000	54.3	54.9	56.7	57.1	59.0	59.8	60.2	61.3	61.4	61.9	62.0	62.2	62.3	
GE 7000	55.5	55.6	57.3	57.7	59.7	60.4	60.9	61.9	62.0	62.6	62.7	62.8	62.9	
GE 6000	56.7	56.8	58.5	59.1	61.2	61.9	62.4	63.4	63.5	64.1	64.2	64.3	64.4	
GE 5000	58.5	58.6	60.6	61.3	63.3	64.1	64.5	65.6	65.7	66.2	66.3	66.5	66.6	
GE 4500	60.4	60.5	62.5	63.2	65.3	66.0	66.6	67.6	67.7	68.3	68.4	68.5	68.6	
GE 4000	61.9	62.0	64.3	65.1	67.2	68.1	68.6	69.7	69.8	70.3	70.4	70.5	70.6	
GE 3500	63.1	63.2	65.6	66.5	68.6	69.6	70.2	71.3	71.4	71.9	72.0	72.2	72.3	
GE 3000	63.7	63.8	66.2	67.2	69.4	70.3	71.1	72.2	72.3	72.8	72.9	73.0	73.1	
GE 2500	64.3	64.5	67.2	68.3	70.5	71.5	72.3	73.4	73.5	74.1	74.2	74.3	74.4	
GE 2000	65.4	65.7	68.4	70.0	72.3	73.2	74.0	75.3	75.4	75.9	76.0	76.1	76.2	
GE 1800	65.9	66.2	68.9	70.5	72.8	73.8	74.5	75.8	75.9	76.5	76.6	76.7	76.8	
GE 1500	66.3	66.7	69.4	71.0	73.2	74.2	74.9	76.3	76.5	77.0	77.1	77.2	77.3	
GE 1200	66.9	67.2	69.9	71.5	73.8	74.7	75.5	76.9	77.0	77.5	77.6	77.7	77.8	
GE 1000	67.5	67.8	70.8	72.6	74.8	75.8	76.7	78.3	78.4	78.9	79.0	79.1	79.2	
GE 900	67.6	68.0	70.9	72.8	75.1	76.0	76.9	78.5	78.6	79.1	79.2	79.4	79.5	
GE 800	68.0	68.3	71.2	73.1	75.4	76.3	77.3	78.9	79.0	79.6	79.7	79.8	79.9	
GE 700	68.4	68.7	71.6	73.5	76.0	77.0	78.0	79.6	79.7	80.2	80.3	80.4	80.5	
GE 600	68.4	68.7	71.7	73.7	76.2	77.2	78.4	80.1	80.3	80.9	81.0	81.1	81.2	
GE 500	69.7	69.9	72.5	74.7	77.6	78.7	80.4	82.4	82.7	83.2	83.3	83.4	83.5	
GE 400	69.7	70.2	73.8	75.1	79.6	80.8	83.0	85.3	85.6	86.2	86.3	86.5	86.6	
GE 300	69.9	70.4	74.0	76.3	79.9	81.1	83.5	86.1	86.5	87.5	88.2	88.4	89.0	
GE 200	69.9	70.4	74.0	76.3	79.9	81.2	83.9	87.3	88.0	89.4	90.4	90.6	92.7	
GE 100	69.9	70.4	74.0	76.5	80.1	81.4	84.3	87.8	88.5	90.0	91.6	91.9	94.0	
GE 000	69.9	70.4	74.0	76.5	80.1	81.4	84.3	87.8	88.5	90.0	91.6	91.9	94.0	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: AUG HOURS: 03-05

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
55.	46.9	48.6	49.4	49.8	50.5	50.6	51.1	51.2	51.3	51.4	51.5	51.8	51.8
55.	50.3	52.0	52.8	53.2	54.3	54.4	54.8	54.9	55.1	55.2	55.3	55.7	55.7
56.	50.5	52.3	53.0	53.4	54.5	54.6	55.1	55.2	55.3	55.4	55.5	55.9	55.9
58.	50.6	52.4	53.1	53.5	54.6	54.7	55.2	55.3	55.4	55.5	55.6	56.0	56.0
51.	51.2	53.5	54.3	54.7	55.8	55.9	56.3	56.5	56.6	56.7	56.8	57.2	57.2
60.	53.2	55.1	55.8	56.2	57.3	57.4	57.8	58.0	58.1	58.2	58.3	58.7	58.7
62.	55.4	57.2	58.0	58.4	59.5	59.6	60.0	60.1	60.2	60.3	60.4	60.9	60.9
63.	55.8	57.6	58.4	58.8	59.9	60.0	60.4	60.5	60.6	60.8	60.9	61.3	61.3
64.	57.1	59.0	59.8	60.2	61.3	61.4	61.9	62.0	62.2	62.3	62.4	62.8	62.8
65.	57.7	59.7	60.4	60.9	61.9	62.0	62.6	62.7	62.8	62.9	63.0	63.4	63.4
66.	59.1	61.2	61.9	62.4	63.4	63.5	64.1	64.2	64.3	64.4	64.5	64.9	64.9
70.	61.3	63.3	64.1	64.5	65.6	65.7	66.2	66.3	66.5	66.6	66.7	67.1	67.1
72.	63.2	65.3	66.0	66.6	67.6	67.7	68.3	68.4	68.5	68.6	68.7	69.1	69.1
73.	65.1	67.2	68.1	68.6	69.7	69.8	70.3	70.4	70.5	70.6	70.8	71.2	71.2
74.	66.5	68.6	69.6	70.2	71.3	71.4	71.9	72.0	72.2	72.3	72.4	72.8	72.8
76.	67.2	69.4	70.3	71.1	72.2	72.3	72.8	72.9	73.0	73.1	73.2	73.7	73.7
76.	68.3	70.5	71.5	72.3	73.4	73.5	74.1	74.2	74.3	74.4	74.5	74.9	74.9
77.	70.0	72.3	73.2	74.0	75.3	75.4	75.9	76.0	76.1	76.2	76.3	76.8	76.8
78.	70.6	72.8	73.8	74.5	75.8	75.9	76.5	76.6	76.7	76.8	76.9	77.3	77.3
79.	71.0	73.2	74.2	74.9	76.3	76.5	77.0	77.1	77.2	77.3	77.4	77.8	77.8
79.	71.5	73.8	74.7	75.5	76.9	77.0	77.5	77.6	77.7	77.8	78.0	78.4	78.4
80.	72.6	74.8	75.8	76.7	78.3	78.4	78.9	79.0	79.1	79.2	79.4	79.8	79.8
80.	72.8	75.1	76.0	76.9	78.5	78.6	79.1	79.2	79.4	79.5	79.6	80.0	80.0
81.	73.1	75.4	76.3	77.3	78.9	79.0	79.6	79.7	79.8	79.9	80.0	80.4	80.4
83.	73.5	76.0	77.0	78.0	79.6	79.7	80.2	80.3	80.4	80.5	80.6	81.1	81.1
83.	73.7	76.2	77.2	78.4	80.1	80.3	80.9	81.0	81.1	81.2	81.3	81.7	81.7
86.	74.7	77.6	78.7	80.4	82.4	82.7	83.2	83.3	83.4	83.5	83.7	84.4	84.4
89.	75.1	79.6	80.8	83.0	85.3	85.6	86.2	86.3	86.5	86.6	86.7	87.4	87.4
93.	76.3	79.9	81.1	83.5	86.1	86.5	87.5	88.2	88.4	89.0	89.1	89.9	89.9
94.	75.3	79.9	81.2	83.9	87.3	88.0	89.4	90.4	90.6	92.7	93.2	94.7	95.3
94.	75.5	80.1	81.4	84.3	87.8	88.5	90.0	91.6	91.9	94.0	94.7	96.9	99.4
...	76.5	80.1	81.4	84.3	87.8	88.5	90.0	91.6	91.9	94.0	94.7	96.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: ALL
MONTH: AUG HOURS: 24

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	40.2	40.5	42.2	43.1	45.1	45.7	46.5	46.6	47.0	47.3	47.3	47.3
GE 20000	43.9	44.2	46.2	47.2	49.2	49.9	50.6	50.9	51.4	51.8	51.8	51.8
GE 18000	43.9	44.2	46.2	47.2	49.2	49.9	50.6	50.9	51.4	51.8	51.8	51.8
GE 16000	44.2	44.5	46.6	47.5	49.6	50.2	51.0	51.2	51.7	52.2	52.2	52.2
GE 14000	44.5	44.8	46.9	47.8	50.1	50.8	51.5	51.7	52.3	52.7	52.7	52.7
GE 12000	45.9	46.2	48.3	49.2	51.6	52.3	53.0	53.3	53.9	54.3	54.3	54.3
GE 10000	48.5	48.9	51.0	52.0	54.4	55.1	55.8	56.2	56.8	57.2	57.2	57.2
GE 9000	49.5	49.9	51.9	53.0	55.4	56.0	56.3	57.2	57.7	58.2	58.2	58.2
GE 8000	51.6	52.0	54.1	55.2	57.8	58.5	59.2	59.7	60.4	60.9	61.0	61.0
GE 7000	52.6	53.0	55.1	56.1	59.1	59.8	60.8	61.2	61.9	62.4	62.5	62.5
GE 6000	53.0	53.4	55.6	56.7	59.8	60.4	61.4	61.8	62.6	63.0	63.1	63.1
GE 5000	54.5	55.1	57.3	58.4	61.5	62.4	63.4	64.0	64.7	65.2	65.3	65.3
GE 4500	55.1	55.7	58.1	59.1	62.4	63.2	64.3	64.9	65.7	66.1	66.2	66.2
GE 4000	56.7	57.4	60.4	61.7	65.5	66.3	67.5	68.2	68.9	69.4	69.5	69.5
GE 3500	57.2	58.0	61.0	62.3	66.1	67.0	68.2	68.8	69.6	70.0	70.1	70.1
GE 3000	57.7	58.5	61.6	63.0	67.0	67.8	69.0	69.9	71.0	71.4	71.5	71.5
GE 2500	58.1	58.8	61.9	63.4	67.4	68.3	69.5	70.3	71.4	71.9	72.0	72.0
GE 2000	59.6	60.3	63.5	65.1	69.1	70.0	71.4	72.5	73.7	74.2	74.3	74.3
GE 1800	59.8	60.5	63.3	65.3	69.6	70.4	71.8	72.9	74.1	74.6	74.7	74.7
GE 1500	60.8	61.5	64.8	66.3	71.0	71.9	73.5	74.6	75.8	76.5	76.6	76.6
GE 1200	61.6	62.4	65.7	67.2	71.8	72.9	74.6	75.8	77.0	77.6	77.7	77.7
GE 1000	62.7	63.4	66.8	68.4	73.1	74.3	76.2	77.4	78.6	79.2	79.4	79.4
GE 900	63.4	64.2	67.7	69.4	74.1	75.5	77.5	78.8	80.0	80.6	80.8	80.8
GE 800	64.3	65.1	68.7	70.3	75.3	76.3	78.3	80.2	81.4	82.0	82.2	82.2
GE 700	64.5	65.3	69.2	70.9	76.0	77.7	79.8	81.3	82.5	83.1	83.2	83.2
GE 600	64.8	65.6	69.7	71.5	77.0	79.7	81.1	82.6	83.8	84.4	84.5	84.5
GE 500	64.9	65.8	70.3	72.5	73.0	79.8	82.6	84.2	85.5	86.2	86.3	86.5
GE 400	65.2	66.0	70.6	73.0	73.6	80.8	83.8	86.2	87.6	88.5	88.7	88.8
GE 300	65.5	66.3	71.1	73.5	73.1	81.4	84.6	89.3	90.3	91.5	92.3	92.4
GE 200	65.5	66.3	71.1	73.5	79.1	81.5	84.7	88.6	90.9	92.2	93.3	93.4
GE 100	65.5	66.3	71.2	73.7	79.2	81.6	84.8	88.9	91.2	92.5	93.7	93.6
GE 000	65.5	66.3	71.2	73.7	79.2	81.6	84.8	88.9	91.2	92.5	93.7	93.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TIME ZONE: + 5 MONTH: AUG HOURS: 06-08

VISIBILITY IN STATUTE MILES

CEILING	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
7.6	45.1	45.1	45.7	46.5	46.6	47.0	47.3	47.3	47.3	47.6	47.7	47.8	48.0	
2.2	47.2	47.2	49.2	49.9	50.6	50.9	51.4	51.8	51.8	51.8	52.2	52.4	52.5	52.6
2.2	47.2	49.2	49.9	50.6	50.9	51.4	51.8	51.8	51.8	52.2	52.4	52.5	52.6	
2.5	47.5	49.6	50.2	51.0	51.7	51.7	52.2	52.2	52.2	52.5	52.7	52.8	52.9	
3.0	47.8	50.1	50.8	51.5	51.7	52.3	52.7	52.7	52.7	53.0	53.2	53.3	53.4	
4.6	49.2	51.6	52.3	53.0	53.3	53.9	54.3	54.3	54.3	54.6	54.8	54.9	55.1	
7.5	54.4	54.4	55.1	55.8	56.2	56.8	57.2	57.2	57.2	57.5	57.7	57.8	58.0	
8.5	55.4	55.4	56.0	56.3	57.2	57.7	58.2	58.2	58.2	58.5	58.7	58.8	58.9	
1.3	57.3	57.3	58.5	59.2	59.7	60.4	60.9	61.0	61.0	61.3	61.5	61.6	61.7	
2.8	59.1	59.1	59.8	60.3	61.2	61.9	62.4	62.5	62.5	62.8	63.0	63.1	63.2	
3.4	59.8	59.8	60.4	61.4	61.8	62.6	63.0	63.1	63.1	63.4	63.7	63.8	63.9	
5.6	61.6	61.6	62.4	63.4	64.0	64.7	65.2	65.3	65.3	65.6	65.8	65.9	66.0	
6.5	62.4	62.4	63.2	64.3	64.9	65.7	66.1	66.2	66.2	66.6	66.8	66.9	67.0	
9.4	65.5	65.5	66.3	67.5	68.2	68.9	69.4	69.5	69.5	69.8	70.0	70.1	70.2	
10.4	66.1	66.1	67.0	68.2	68.8	69.6	70.0	70.1	70.1	70.4	70.6	70.8	70.9	
1.8	67.0	67.0	67.8	69.0	69.9	71.0	71.4	71.5	71.5	71.8	72.0	72.2	72.3	
2.4	67.4	67.4	68.3	69.5	70.3	71.4	71.9	72.0	72.0	72.4	72.6	72.7	72.8	
4.7	69.1	69.1	70.0	71.4	72.5	73.7	74.2	74.3	74.3	74.7	74.9	75.1	75.2	
5.2	69.6	69.6	70.4	71.8	72.9	74.1	74.6	74.7	74.7	75.2	75.4	75.5	75.6	
7.0	71.0	71.0	71.9	73.5	74.6	75.8	76.5	76.6	76.6	77.0	77.2	77.3	77.4	
8.2	71.3	71.3	72.9	74.6	75.8	77.0	77.6	77.7	77.7	78.2	78.4	78.5	78.6	
9.8	73.1	73.1	74.3	76.2	77.4	78.6	79.2	79.4	79.4	79.8	80.0	80.1	80.2	
1.2	74.1	74.1	75.5	77.5	78.8	80.0	80.6	80.8	80.8	81.2	81.4	81.5	81.6	
2.6	75.3	75.3	76.3	78.3	80.2	81.4	82.0	82.2	82.2	82.6	82.8	82.9	83.0	
3.7	76.0	76.0	77.7	79.8	81.3	82.5	83.1	83.2	83.2	83.7	83.9	84.0	84.1	
4.9	77.0	77.0	78.7	81.1	82.6	83.8	84.4	84.5	84.5	84.9	85.2	85.3	85.4	
7.0	79.8	79.8	82.6	84.2	85.5	86.2	86.3	86.5	86.5	87.0	87.2	87.3	87.4	
10.6	80.6	80.6	83.8	86.2	87.6	88.5	88.7	88.8	88.8	89.6	89.8	89.9	90.0	
10.4	81.4	81.4	84.6	87.3	89.3	90.3	91.5	92.3	92.4	93.4	93.7	93.9	94.6	
10.2	81.5	81.5	84.7	88.6	90.9	92.2	93.3	93.4	93.4	95.2	95.5	96.5	97.8	
10.6	81.6	81.6	84.8	88.9	91.2	92.5	93.7	93.8	93.8	95.6	96.3	97.8	100.0	
10.6	81.6	81.6	84.8	88.9	91.2	92.5	93.7	93.8	93.8	95.6	96.3	97.8	100.0	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: A
MONTH: AUG HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	40.1	40.9	41.7	42.0	42.0	42.3	42.5	42.6	42.7	42.7	42.7	42.7
GE 20000	45.9	47.0	48.3	48.7	48.8	49.0	49.4	49.5	49.6	49.6	49.6	49.6
GE 18000	46.3	47.4	48.7	49.1	49.2	49.5	49.8	49.9	50.0	50.0	50.0	50.0
GE 16000	46.3	47.4	48.7	49.1	49.2	49.5	49.8	49.9	50.0	50.0	50.0	50.0
GE 14000	47.3	48.4	49.7	50.1	50.2	50.4	50.8	50.9	51.0	51.0	51.0	51.0
GE 12000	48.7	49.8	51.1	51.5	51.6	51.8	52.2	52.3	52.4	52.4	52.4	52.4
GE 10000	51.1	52.2	53.7	54.5	54.6	54.8	55.2	55.3	55.4	55.4	55.4	55.4
GE 9000	51.3	52.9	54.4	55.3	55.4	55.5	55.9	56.0	56.1	56.1	56.1	56.1
GE 8000	54.4	55.6	57.1	58.3	58.5	58.7	59.0	59.4	59.6	59.6	59.6	59.6
GE 7000	55.9	57.2	58.8	60.0	60.2	60.4	60.8	61.1	61.3	61.3	61.3	61.3
GE 6000	56.2	57.5	59.1	60.3	60.6	60.9	61.2	61.5	61.7	61.7	61.7	61.7
GE 5000	57.4	58.7	60.3	61.5	62.3	62.5	62.8	63.1	63.3	63.3	63.3	63.3
GE 4500	58.2	59.5	61.2	62.5	63.2	63.4	63.8	64.1	64.3	64.3	64.3	64.3
GE 4000	59.8	61.2	63.5	64.9	65.8	66.0	66.3	66.7	66.9	66.9	66.9	66.9
GE 3500	60.5	62.0	64.4	65.8	66.8	67.0	67.3	67.6	67.8	67.8	67.8	67.8
GE 3000	63.0	64.5	67.0	68.5	69.6	69.9	70.2	70.5	70.8	70.8	70.8	70.8
GE 2500	64.3	65.8	68.4	69.9	71.1	71.4	71.7	72.0	72.3	72.3	72.3	72.3
GE 2000	65.9	67.5	71.2	72.9	74.2	74.5	74.8	75.2	75.4	75.4	75.4	75.4
GE 1800	69.1	69.7	72.4	74.1	75.5	75.8	76.1	76.5	76.7	76.7	76.7	76.7
GE 1500	70.5	72.2	74.9	76.7	78.1	78.4	78.9	79.2	79.5	79.5	79.5	79.5
GE 1200	72.5	74.2	77.1	78.8	80.2	80.5	81.1	81.4	81.6	81.6	81.6	81.6
GE 1000	74.2	75.8	78.9	80.6	82.0	82.4	83.0	83.3	83.5	83.5	83.5	83.5
GE 900	75.1	76.9	80.3	82.5	83.9	84.2	84.8	85.2	85.4	85.4	85.4	85.4
GE 800	76.1	78.1	81.7	84.0	85.5	85.8	86.7	87.0	87.2	87.2	87.2	87.2
GE 700	76.7	78.6	82.6	84.9	86.7	87.2	88.2	88.7	88.9	88.9	88.9	88.9
GE 600	77.2	79.2	83.3	86.2	88.2	88.7	90.2	90.8	91.0	91.0	91.0	91.0
GE 500	77.4	79.8	84.1	87.1	89.2	89.9	91.9	92.9	93.2	93.2	93.2	93.2
GE 400	77.7	80.1	84.4	87.4	89.7	90.3	92.3	94.3	95.1	95.1	95.1	95.1
GE 300	77.7	80.1	84.4	87.4	89.8	90.6	93.5	95.5	96.5	96.8	97.4	97.5
GE 200	77.7	80.1	84.4	87.4	90.0	90.9	93.5	95.7	96.9	97.3	98.5	98.8
GE 100	77.7	80.1	84.4	87.4	90.0	90.9	93.6	95.7	96.9	97.3	98.5	98.8
GE 000	77.7	80.1	84.4	87.4	90.0	90.9	93.5	95.7	96.9	97.3	98.5	98.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
IC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG HOURS: 09-11

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
42.0	42.3	42.5	42.6	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
48.8	49.0	49.4	49.5	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
49.2	49.5	49.5	49.9	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
49.2	49.5	49.8	49.9	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
50.2	50.4	50.3	50.9	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
51.6	51.8	52.2	52.3	52.4	52.4	52.4	52.4	52.4	52.4	52.4	52.4
54.6	54.4	55.2	55.3	55.4	55.4	55.4	55.4	55.4	55.4	55.4	55.4
55.4	55.5	55.9	56.0	56.1	56.1	56.1	56.1	56.1	56.1	56.1	56.1
53.5	58.7	59.0	59.4	59.6	59.6	59.6	59.6	59.6	59.6	59.6	59.6
59.2	59.4	60.8	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
60.6	60.9	61.2	61.5	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
62.3	62.5	62.8	63.1	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
63.2	63.4	63.8	64.1	64.3	64.3	64.3	64.3	64.3	64.3	64.3	64.3
65.8	66.0	66.3	66.7	66.9	66.9	66.9	66.9	66.9	66.9	66.9	66.9
66.8	67.0	67.3	67.6	67.8	67.8	67.8	67.8	67.8	67.8	67.8	67.8
69.5	69.9	70.2	70.5	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8
71.1	71.4	71.7	72.0	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3
74.2	74.5	74.8	75.2	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4
75.5	75.4	76.1	76.5	76.7	76.7	76.7	76.7	76.7	76.7	76.7	76.7
73.1	73.4	74.9	79.2	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5
80.2	80.5	81.1	81.4	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
82.0	82.4	83.0	83.3	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5
83.9	84.2	84.3	85.2	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4
85.5	85.8	86.7	87.0	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2
86.7	87.2	88.2	88.7	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9
88.2	88.7	90.2	90.8	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
89.2	89.9	91.9	92.9	93.2	93.2	93.3	93.3	93.3	93.3	93.3	93.3
90.7	90.3	92.3	94.3	95.1	95.1	95.3	95.3	95.3	95.4	95.4	95.4
90.8	90.6	93.5	95.5	96.5	96.8	97.4	97.5	97.5	97.6	97.6	97.6
90.0	90.9	93.8	95.7	96.9	97.3	98.5	98.8	99.4	99.9	99.9	99.9
90.0	90.9	93.8	95.7	96.9	97.3	98.5	98.8	99.4	99.9	99.9	100.0
90.0	90.9	93.5	95.7	96.9	97.3	98.5	98.8	99.4	99.9	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: AUG HOURS: 12-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	1	
NO CEIL	39.6	39.8	40.1	40.2	40.2	40.3	40.4	40.4	40.4	40.4	40.4	40.4	40.4	4
GE 20000	49.9	50.2	50.5	50.8	50.9	51.0	51.1	51.1	51.1	51.1	51.1	51.1	51.1	5
GE 18000	50.5	50.9	51.3	51.5	51.6	51.7	51.8	51.8	51.8	51.8	51.8	51.8	51.8	5
GE 16000	50.5	50.9	51.3	51.5	51.6	51.7	51.8	51.8	51.8	51.8	51.8	51.8	51.8	5
GE 14000	51.5	51.8	52.3	52.5	52.6	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8	5
GE 12000	53.2	53.5	54.2	54.5	54.6	54.7	54.8	54.8	54.8	54.8	54.8	54.8	54.8	5
GE 10000	56.8	57.2	58.0	58.3	58.4	58.5	58.6	58.6	58.6	58.6	58.6	58.6	58.6	5
GE 9000	57.0	57.4	58.2	58.5	58.6	58.7	58.8	58.8	58.8	58.8	58.8	58.8	58.8	5
GE 8000	58.8	59.2	60.0	60.5	60.5	60.8	60.9	60.9	60.9	60.9	60.9	60.9	60.9	6
GE 7000	60.1	60.5	61.3	61.8	62.0	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.3	6
GE 6000	61.0	61.4	62.2	62.7	62.9	63.0	63.1	63.1	63.1	63.1	63.1	63.1	63.1	6
GE 5000	62.6	63.1	64.1	64.6	64.8	64.9	65.1	65.1	65.1	65.1	65.1	65.1	65.1	6
GE 4500	63.2	63.8	64.8	65.5	65.7	65.8	65.9	65.9	65.9	65.9	65.9	65.9	65.9	6
GE 4000	65.8	66.7	68.1	68.9	69.1	69.2	69.4	69.5	69.5	69.5	69.5	69.5	69.5	6
GE 3500	69.9	70.8	72.3	73.1	73.4	73.7	73.8	73.9	73.9	73.9	73.9	73.9	73.9	7
GE 3000	72.5	73.5	75.3	76.2	76.6	76.8	77.0	77.1	77.1	77.1	77.1	77.1	77.1	7
GE 2500	75.5	76.4	78.3	79.2	79.6	79.8	80.0	80.1	80.1	80.1	80.1	80.1	80.1	8
GE 2000	78.7	80.0	81.9	82.9	83.3	83.5	83.8	83.9	83.9	83.9	83.9	83.9	83.9	8
GE 1800	79.8	81.1	83.1	84.1	84.5	84.7	84.9	85.1	85.1	85.1	85.1	85.1	85.1	8
GE 1500	81.8	83.2	85.4	86.3	86.8	87.1	87.3	87.4	87.4	87.4	87.4	87.4	87.4	8
GE 1200	84.3	85.7	88.0	89.0	89.5	89.8	90.1	90.2	90.2	90.2	90.2	90.2	90.2	9
GE 1000	85.1	86.6	89.1	90.3	90.9	91.3	91.6	91.7	91.7	91.7	91.7	91.7	91.7	9
GE 900	85.5	87.1	90.0	91.2	91.9	92.4	92.7	92.9	92.9	92.9	92.9	92.9	92.9	9
GE 800	85.7	87.4	90.3	91.5	92.7	93.1	93.5	93.8	93.8	93.8	93.8	93.8	93.8	9
GE 700	86.1	88.0	91.2	92.3	94.3	94.7	95.3	95.5	95.5	95.5	95.5	95.5	95.5	9
GE 600	86.7	88.5	91.8	93.7	95.4	96.0	96.9	97.3	97.3	97.3	97.3	97.3	97.3	9
GE 500	86.9	88.7	92.2	94.0	95.9	96.6	97.4	98.3	98.3	98.3	98.3	98.3	98.3	9
GE 400	86.9	88.7	92.2	94.0	95.9	96.7	97.6	98.8	99.0	99.0	99.0	99.0	99.0	9
GE 300	86.9	88.7	92.2	94.1	96.2	97.1	98.2	99.4	99.6	99.6	99.7	99.7	99.7	9
GE 200	86.9	88.7	92.2	94.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	9
GE 100	86.9	88.7	92.2	94.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	9
GE 000	86.9	88.7	92.2	94.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG HOURS: 12-14

VISIBILITY IN STATUTE MILES												
CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
40.2	40.2	40.3	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
50.9	50.9	51.0	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1
51.6	51.6	51.7	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
52.5	52.6	52.7	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8	52.8
54.5	54.6	54.7	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8	54.8
58.3	58.4	58.5	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6
58.5	58.6	58.7	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8	58.8
60.5	60.6	60.8	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
62.5	62.6	62.7	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8
62.7	62.9	63.0	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1	63.1
64.5	64.6	64.7	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8
65.5	65.7	65.8	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9
69.0	69.1	69.2	69.4	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5	69.5
73.1	73.4	73.7	73.8	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
75.2	75.6	76.8	77.0	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1	77.1
79.2	79.6	79.8	80.0	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
83.2	83.3	83.5	83.8	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9
84.1	84.5	84.7	84.9	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1	85.1
87.3	87.6	87.1	87.3	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
89.2	89.5	89.8	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
91.3	91.9	91.3	91.6	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
92.2	91.9	92.4	92.7	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
93.5	92.7	93.1	93.5	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
95.7	94.3	94.7	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
97.7	95.4	96.0	96.9	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
98.2	95.9	96.6	97.4	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
99.0	95.9	96.7	97.6	98.8	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
99.1	95.2	97.1	98.2	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7
99.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.9
99.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	99.8	99.8	100.0
99.1	96.2	97.1	98.2	99.4	99.7	99.7	99.8	99.8	99.8	99.8	99.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: AUG HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	45.1	45.1	45.6	46.0	46.5	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8
GE 20000	54.7	55.8	56.3	56.3	56.3	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
GE 18000	54.9	56.0	56.5	56.6	56.6	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9
GE 16000	54.9	56.0	56.5	56.6	56.6	56.9	56.9	56.9	56.9	56.9	56.9	56.9	56.9
GE 14000	56.1	57.2	57.7	57.7	57.7	58.1	58.1	58.1	58.1	58.1	58.1	58.1	58.1
GE 12000	58.5	59.6	60.2	60.2	60.2	60.5	60.5	60.5	60.5	60.5	60.5	60.5	60.5
GE 10000	60.8	61.8	62.5	62.5	62.5	62.8	62.8	62.8	62.8	62.8	62.8	62.8	62.8
GE 9000	61.8	62.9	63.5	63.5	63.5	63.9	63.9	63.9	63.9	63.9	63.9	63.9	63.9
GE 8000	63.4	64.6	65.3	65.3	65.3	65.6	65.6	65.6	65.6	65.6	65.6	65.6	65.6
GE 7000	64.1	65.4	66.1	66.1	66.2	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6
GE 6000	64.9	66.2	67.0	67.0	67.1	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.4
GE 5000	66.3	67.6	68.5	68.5	68.6	68.9	68.9	68.9	68.9	68.9	68.9	68.9	68.9
GE 4500	67.4	68.7	69.7	69.7	70.0	70.4	70.4	70.4	70.4	70.4	70.4	70.4	70.4
GE 4000	70.1	71.4	72.6	72.9	73.1	73.5	73.7	73.7	73.7	73.7	73.7	73.7	73.7
GE 3500	73.0	74.4	75.8	76.1	76.5	76.9	77.0	77.0	77.0	77.0	77.0	77.0	77.0
GE 3000	75.4	77.0	78.7	79.1	79.5	79.9	80.0	80.0	80.0	80.0	80.0	80.0	80.0
GE 2500	78.2	79.8	81.5	81.9	82.5	83.0	83.1	83.1	83.1	83.1	83.1	83.1	83.1
GE 2000	80.6	82.6	84.6	85.4	85.9	86.7	86.8	86.8	86.8	86.8	86.8	87.0	87.0
GE 1800	81.3	83.2	85.3	86.0	87.0	87.6	87.7	87.7	87.7	87.7	87.7	88.0	88.0
GE 1500	82.0	84.3	86.5	87.3	88.3	88.9	89.0	89.0	89.0	89.0	89.0	89.2	89.2
GE 1200	84.0	86.5	88.8	89.4	90.9	91.5	91.6	91.6	91.6	91.6	91.6	91.8	91.8
GE 1000	84.8	87.4	90.0	91.2	92.7	93.3	93.4	93.4	93.4	93.4	93.4	93.7	93.7
GE 900	85.3	87.8	90.4	91.6	93.5	94.2	94.3	94.3	94.3	94.3	94.3	94.5	94.5
GE 800	85.6	88.3	90.9	92.0	94.0	94.7	94.8	94.8	94.8	94.8	94.8	95.1	95.1
GE 700	86.0	88.9	91.5	92.7	95.2	96.0	96.2	96.2	96.2	96.2	96.2	96.5	96.5
GE 600	86.0	88.9	91.7	93.0	95.6	96.5	97.2	97.2	97.3	97.4	97.4	97.6	97.6
GE 500	86.0	88.9	92.0	93.3	95.7	96.8	97.9	98.1	98.2	98.4	98.4	98.6	98.6
GE 400	86.0	88.9	92.0	93.4	96.2	97.2	98.3	98.6	98.8	99.0	99.0	99.2	99.2
GE 300	86.0	88.9	92.0	93.4	96.2	97.2	98.3	98.8	99.4	99.6	99.7	99.9	99.9
GE 200	86.0	88.9	92.0	93.4	96.2	97.2	98.3	98.8	99.4	99.7	99.8	100.0	100.0
GE 100	86.0	88.9	92.0	93.4	96.2	97.2	98.3	98.8	99.4	99.7	99.8	100.0	100.0
GE 000	86.0	88.9	92.0	93.4	96.2	97.2	98.3	98.8	99.4	99.7	99.8	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 930

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: AUG HOURS: 18-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	50.6	51.8	52.6	53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	5
GE 20000	58.0	59.2	60.6	61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	6
GE 18000	58.2	59.5	60.9	61.3	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	6
GE 16000	58.3	59.6	61.0	61.4	61.6	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	6
GE 14000	60.0	61.4	62.9	63.3	63.5	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	6
GE 12000	62.8	64.2	65.7	66.1	66.3	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	6
GE 10000	64.1	65.6	67.3	67.3	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	6
GE 9000	65.2	66.8	68.5	69.0	69.5	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	6
GE 8000	67.3	68.9	70.9	71.7	72.2	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	7
GE 7000	68.3	69.9	72.0	73.0	73.4	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	7
GE 6000	69.4	71.0	73.1	74.1	74.5	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	7
GE 5000	70.8	72.5	74.7	75.7	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	7
GE 4500	71.4	73.1	75.4	76.3	76.8	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	7
GE 4000	72.8	74.7	77.2	78.3	78.7	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	7
GE 3500	74.0	75.9	78.6	79.7	80.1	80.4	80.4	80.6	80.8	80.9	80.9	80.9	80.9	8
GE 3000	75.7	77.7	80.5	81.9	82.5	82.8	82.8	83.0	83.1	83.2	83.2	83.2	83.2	8
GE 2500	76.8	78.8	81.8	83.7	84.2	84.5	84.5	84.7	84.8	84.9	84.9	84.9	84.9	8
GE 2000	78.8	81.2	84.4	86.6	87.3	88.0	88.1	88.3	88.4	88.5	88.5	88.5	88.5	8
GE 1800	79.1	81.5	84.7	87.0	87.8	88.5	88.6	88.8	88.9	89.0	89.0	89.0	89.0	8
GE 1500	79.2	81.8	85.1	87.3	88.3	88.9	89.1	89.4	89.5	89.6	89.6	89.6	89.6	8
GE 1200	79.5	82.2	85.6	88.3	89.5	90.1	90.3	90.5	90.6	90.8	90.8	90.8	90.8	9
GE 1000	80.2	83.0	86.8	89.6	90.9	91.6	91.9	92.3	92.4	92.5	92.5	92.5	92.5	9
GE 900	80.8	83.5	87.4	90.2	91.6	92.4	92.7	93.0	93.1	93.2	93.2	93.2	93.2	9
GE 800	81.4	84.3	88.5	91.3	92.9	93.7	94.1	94.4	94.5	94.6	94.6	94.6	94.6	9
GE 700	81.6	84.6	89.0	91.8	93.5	94.6	95.2	95.7	95.8	95.9	95.9	95.9	95.9	9
GE 600	81.7	84.7	89.1	92.0	93.9	95.2	95.7	96.3	96.5	96.6	96.6	96.6	96.6	9
GE 500	81.8	84.8	89.4	92.3	94.4	95.9	96.5	97.2	97.3	97.4	97.6	97.6	97.6	9
GE 400	81.8	84.8	89.4	92.3	94.6	96.1	97.0	97.7	98.1	98.5	98.7	98.7	98.7	9
GE 300	81.8	84.8	89.4	92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.2	99.2	99.2	9
GE 200	81.8	84.8	89.4	92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.5	99.6	99.6	9
GE 100	81.8	84.8	89.4	92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.6	99.7	99.7	9
GE 000	81.8	84.8	89.4	92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.6	99.7	99.7	9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG HOURS: 18-20

VISIBILITY IN STATUTE MILES

4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
53.0	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
61.1	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
61.3	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6	61.6
61.4	61.6	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7	61.7
63.3	63.5	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7	63.7
66.1	66.3	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5
67.3	68.3	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4	68.4
69.0	69.5	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6
71.7	72.2	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3	72.3
73.0	73.4	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5
74.1	74.5	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6
75.7	75.1	76.2	75.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2
76.3	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9	76.9
78.3	78.7	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8
79.7	80.1	80.4	80.4	80.6	80.8	80.9	80.9	80.9	80.9	80.9	80.9	80.9
81.9	82.5	82.8	82.8	83.0	83.1	83.2	83.2	83.2	83.2	83.2	83.2	83.2
83.7	84.2	84.5	84.5	84.7	84.8	84.9	84.9	84.9	84.9	84.9	84.9	84.9
86.6	87.3	88.0	88.1	88.3	88.4	88.5	88.5	88.5	88.5	88.5	88.5	88.5
87.0	87.5	88.5	88.6	88.8	88.9	89.0	89.0	89.0	89.0	89.0	89.0	89.0
87.3	88.3	88.9	89.1	89.4	89.5	89.6	89.6	89.6	89.6	89.6	89.6	89.6
88.3	89.5	90.1	90.3	90.5	90.6	90.8	90.8	90.8	90.8	90.8	90.8	90.8
90.6	90.9	91.6	91.9	92.3	92.4	92.5	92.5	92.5	92.5	92.5	92.5	92.5
90.7	91.6	92.4	92.7	93.0	93.1	93.2	93.2	93.2	93.2	93.2	93.2	93.2
91.3	92.9	93.7	94.1	94.4	94.5	94.6	94.6	94.6	94.6	94.6	94.6	94.6
91.4	93.5	94.6	95.2	95.7	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9
92.0	93.9	95.2	95.7	96.3	96.5	96.6	96.6	96.6	96.6	96.6	96.6	96.6
92.3	94.4	95.9	96.5	97.2	97.3	97.4	97.6	97.6	97.6	97.6	97.6	97.6
92.3	94.5	96.1	97.0	97.7	98.1	98.5	98.7	98.7	98.7	98.7	98.7	98.7
92.3	94.7	95.2	97.2	98.1	98.6	99.0	99.2	99.2	99.4	99.4	99.4	99.4
92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.5	99.6	99.7	99.8	99.9	99.9
92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.6	99.7	99.8	99.9	100.0	100.0
92.3	94.7	96.2	97.2	98.1	98.6	99.0	99.6	99.7	99.8	99.9	100.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: AUG HOURS: 21-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GF 1	GE 3/4	GE 5/8	
NO CEIL	53.8	54.1	55.2	55.5	56.9	57.0	57.1	57.3	57.3	57.4	57.4	57.4	5
GE 20000	57.1	57.4	58.6	59.2	60.6	60.8	60.9	61.1	61.1	61.2	61.2	61.2	6
GF 18000	57.3	57.6	58.8	59.5	60.9	61.0	61.1	61.3	61.3	61.4	61.4	61.4	6
GE 16000	57.5	57.8	59.0	59.7	61.1	61.2	61.3	61.5	61.5	61.6	61.6	61.6	6
GE 14000	59.0	59.4	60.6	61.3	62.7	62.8	62.9	63.1	63.1	63.2	63.2	63.2	6
GE 12000	60.5	61.0	62.4	63.0	64.4	64.5	64.6	64.8	64.8	64.9	64.9	64.9	6
GE 10000	61.6	62.0	63.4	64.1	65.5	65.6	65.7	66.1	66.1	66.2	66.2	66.2	6
GF 9000	61.7	62.2	63.5	64.3	65.7	65.8	65.9	66.3	66.3	66.5	66.5	66.5	6
GE 8000	63.3	63.9	65.5	66.5	68.0	68.1	68.2	68.6	68.6	68.7	68.7	68.7	6
GE 7000	64.2	64.7	66.5	67.5	68.9	69.0	69.1	69.6	69.6	69.7	69.7	69.7	6
GE 6000	66.0	66.6	68.3	69.4	70.8	70.9	71.0	71.4	71.4	71.5	71.5	71.5	7
GF 5000	68.4	68.9	70.6	71.3	73.3	73.4	73.5	74.0	74.0	74.1	74.1	74.1	7
GF 4500	69.8	70.3	72.0	73.3	74.9	75.1	75.2	75.6	75.6	75.7	75.7	75.7	7
GE 4000	71.0	71.5	73.4	74.7	76.3	76.5	76.7	77.1	77.1	77.2	77.2	77.2	7
GE 3500	72.3	72.8	74.9	76.2	78.0	78.2	78.6	79.4	79.4	79.5	79.5	79.5	7
GE 3000	73.8	74.8	77.1	78.7	80.6	80.9	81.4	82.2	82.2	82.3	82.3	82.3	8
GE 2500	75.2	76.2	78.5	80.4	82.4	82.6	83.1	83.9	83.9	84.0	84.0	84.0	8
GE 2000	78.2	79.4	81.6	83.5	85.6	85.9	86.5	87.2	87.2	87.3	87.3	87.3	8
GE 1800	78.2	79.4	81.6	83.7	85.7	86.0	86.7	87.4	87.4	87.5	87.5	87.5	8
GE 1500	78.5	79.7	82.2	84.3	86.5	86.8	87.4	88.2	88.2	88.3	88.3	88.3	8
GE 1200	78.8	80.0	82.5	84.6	86.9	87.2	87.8	88.6	88.6	88.7	88.7	88.7	8
GE 1000	78.9	80.1	82.6	84.7	87.0	87.3	88.1	88.8	88.8	88.9	88.9	88.9	8
GF 900	79.8	81.0	83.4	85.8	88.2	88.5	89.2	90.0	90.0	90.1	90.1	90.1	9
GF 800	80.2	81.4	84.0	86.3	88.7	89.0	89.9	90.6	90.6	90.8	90.8	90.8	9
GE 700	80.3	81.5	84.2	86.9	89.6	90.0	91.0	91.7	91.7	91.8	91.8	91.8	9
GE 600	80.3	81.5	84.4	87.1	90.0	90.4	91.6	92.6	92.7	92.8	92.8	92.8	9
GE 500	80.3	81.5	84.4	87.1	90.3	90.8	92.4	93.5	93.7	93.9	93.9	93.9	9
GF 400	80.3	81.5	84.4	87.1	90.4	91.4	93.0	94.4	94.5	94.7	94.7	94.7	9
GF 300	80.4	81.6	84.5	87.3	90.8	91.9	93.8	95.9	96.3	96.7	96.9	97.0	9
GE 200	80.4	81.6	84.5	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.5	9
GE 100	80.4	81.6	84.5	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.6	9
GE 000	80.4	81.6	84.5	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.6	9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG HOURS: 21-23

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
4	55.5	56.9	57.0	57.1	57.3	57.3	57.4	57.4	57.4	57.4	57.4	57.4	57.4
2	54.2	60.6	60.8	60.9	61.1	61.1	61.2	61.2	61.2	61.2	61.2	61.2	61.2
4	59.5	60.9	61.0	61.1	61.3	61.3	61.4	61.4	61.4	61.4	61.4	61.4	61.4
6	59.7	61.1	61.2	61.3	61.5	61.5	61.6	61.6	61.6	61.6	61.6	61.6	61.6
2	61.3	62.7	62.8	62.9	63.1	63.1	63.2	63.2	63.2	63.2	63.2	63.2	63.2
9	63.0	64.4	64.5	64.6	64.8	64.8	64.9	64.9	64.9	64.9	64.9	64.9	64.9
2	64.1	65.5	65.6	65.7	65.1	66.1	66.2	66.2	66.2	66.2	66.2	66.2	66.2
5	64.3	65.7	65.8	65.9	66.3	66.3	66.5	66.5	66.5	66.5	66.5	66.5	66.5
7	65.5	68.0	68.1	68.2	68.6	68.6	68.7	68.7	68.7	68.7	68.7	68.7	68.7
7	67.5	68.9	69.0	69.1	69.6	69.6	69.7	69.7	69.7	69.7	69.7	69.7	69.7
5	69.4	70.8	70.9	71.0	71.4	71.4	71.5	71.5	71.5	71.5	71.5	71.5	71.5
1	71.3	73.3	73.4	73.5	74.0	74.0	74.1	74.1	74.1	74.1	74.1	74.1	74.1
7	73.3	74.9	75.1	75.2	75.6	75.6	75.7	75.7	75.7	75.7	75.7	75.7	75.7
2	74.7	76.3	76.6	76.7	77.1	77.1	77.2	77.2	77.2	77.2	77.2	77.2	77.2
5	76.2	78.0	78.2	78.6	79.4	79.4	79.5	79.5	79.5	79.5	79.5	79.5	79.5
3	78.7	80.6	80.9	81.4	82.2	82.2	82.3	82.3	82.3	82.3	82.3	82.3	82.3
7	80.4	82.4	82.6	83.1	83.9	83.9	84.0	84.0	84.0	84.0	84.0	84.0	84.0
3	83.5	85.6	85.9	86.5	87.2	87.2	87.3	87.3	87.3	87.3	87.3	87.3	87.3
5	83.7	85.7	86.0	86.7	87.4	87.4	87.5	87.5	87.5	87.5	87.5	87.5	87.5
3	84.3	86.5	86.8	87.4	88.2	88.2	88.3	88.3	88.3	88.3	88.3	88.3	88.3
7	84.8	86.9	87.2	87.8	88.6	88.6	88.7	88.7	88.7	88.7	88.7	88.7	88.7
9	84.7	87.0	87.3	88.1	88.8	88.8	88.9	88.9	88.9	88.9	88.9	88.9	88.9
1	85.8	88.2	88.5	89.2	90.0	90.0	90.1	90.1	90.1	90.1	90.1	90.1	90.1
8	86.3	88.7	89.0	89.9	90.6	90.6	90.8	90.8	90.8	90.8	90.8	90.8	90.8
8	86.9	89.6	90.0	91.0	91.7	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8
8	87.1	90.0	90.4	91.6	92.6	92.7	92.8	92.8	92.8	92.8	92.8	92.8	92.8
9	87.1	90.3	90.3	92.4	93.5	93.7	93.9	93.9	93.9	93.9	93.9	93.9	93.9
9	87.1	90.4	91.4	93.0	94.4	94.5	94.7	94.7	94.7	94.9	94.9	94.9	94.9
4	87.3	90.8	91.9	93.8	95.9	96.3	96.7	96.9	97.0	97.4	97.4	97.4	97.4
1	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.5	99.1	99.1	99.6	99.6
1	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.6	99.4	99.4	99.9	100.0
1	87.3	90.8	91.9	93.8	96.0	96.8	97.8	98.3	98.6	99.4	99.4	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: AUG HOURS: 1

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	45.6	46.1	47.0	47.4	48.3	48.5	48.8	49.0	49.1	49.2	49.3	49.4
GE 20000	51.5	52.1	53.3	53.7	54.6	54.9	55.2	55.5	55.6	55.7	55.8	55.9
GE 18000	51.7	52.3	53.5	54.0	54.9	55.2	55.5	55.7	55.8	56.0	56.0	56.1
GE 16000	51.8	52.4	53.6	54.1	55.0	55.3	55.6	55.8	55.9	56.1	56.1	56.2
GE 14000	52.9	53.5	54.6	55.2	55.1	56.5	56.7	57.0	57.1	57.2	57.3	57.4
GE 12000	54.8	55.4	56.7	57.2	58.1	58.4	58.7	59.0	59.1	59.2	59.3	59.4
GE 10000	57.0	57.7	59.0	59.6	60.6	60.9	61.1	61.5	61.6	61.7	61.8	61.9
GE 9000	57.6	58.3	59.7	60.2	61.2	61.5	61.8	62.1	62.2	62.4	62.4	62.5
GE 8000	59.4	60.1	61.5	62.2	63.3	63.6	63.9	64.2	64.4	64.5	64.6	64.7
GE 7000	60.4	61.1	62.6	63.3	64.5	64.8	65.1	65.5	65.6	65.8	65.8	65.9
GE 6000	61.4	62.1	63.6	64.4	65.6	65.9	66.2	66.6	66.7	66.9	66.9	67.0
GE 5000	63.1	63.9	65.5	66.3	67.6	67.9	68.2	68.6	68.8	68.9	69.0	69.1
GE 4500	64.2	65.0	66.7	67.6	68.9	69.2	69.5	70.0	70.1	70.3	70.3	70.4
GE 4000	65.9	66.9	68.9	69.7	71.4	71.8	72.2	72.6	72.7	72.9	72.9	73.0
GE 3500	67.6	68.5	70.6	71.7	73.2	73.7	74.1	74.6	74.8	75.0	75.0	75.1
GE 3000	69.1	70.2	72.5	73.7	75.3	75.8	76.3	76.8	77.0	77.2	77.2	77.3
GE 2500	70.5	71.6	74.0	75.3	77.0	77.5	78.0	78.5	78.7	78.9	79.0	79.1
GE 2000	72.7	74.0	76.5	78.0	79.8	80.4	80.9	81.5	81.7	81.9	81.9	82.0
GE 1800	73.2	74.5	77.0	78.5	80.4	81.0	81.5	82.1	82.3	82.5	82.6	82.7
GE 1500	74.2	75.5	78.1	79.7	81.7	82.3	82.9	83.5	83.7	83.9	84.0	84.1
GE 1200	75.2	76.6	79.3	81.0	83.0	83.6	84.2	84.8	85.1	85.3	85.3	85.4
GE 1000	76.0	77.4	80.2	82.0	84.1	84.8	85.5	86.1	86.3	86.5	86.6	86.7
GE 900	76.5	78.0	80.9	82.7	85.0	85.7	86.4	87.1	87.3	87.5	87.6	87.7
GE 800	77.0	78.5	81.5	83.4	85.8	86.5	87.3	88.0	88.2	88.4	88.5	88.6
GE 700	77.3	78.9	82.1	84.1	86.7	87.5	88.5	89.2	89.4	89.6	89.7	89.8
GE 600	77.5	79.1	82.4	84.5	87.4	88.3	89.5	90.3	90.6	90.8	90.9	91.0
GE 500	77.7	79.3	82.9	85.1	88.1	89.1	90.6	91.7	92.0	92.2	92.4	92.5
GE 400	77.9	79.6	83.1	85.4	88.6	89.7	91.5	92.9	93.3	93.7	93.8	93.9
GE 300	78.0	79.7	83.3	85.5	88.9	90.1	92.0	93.9	94.6	95.2	95.6	95.9
GE 200	78.0	79.7	83.3	85.6	89.9	90.1	92.1	94.3	95.2	95.9	96.6	96.8
GE 100	78.0	79.7	83.3	85.6	89.0	90.2	92.2	94.4	95.3	96.1	96.9	97.0
GE 000	78.0	79.7	83.3	85.6	89.0	90.2	92.2	94.4	95.3	96.1	96.9	97.0

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
JTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG HOURS: ALL

VISIBILITY IN STATUTE MILES

1/4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
47	43.3	48.5	48.8	49.0	49.1	49.2	49.3	49.3	49.4	49.4	49.5	49.5
55	54.6	54.9	55.2	55.5	55.6	55.7	55.8	55.8	55.8	55.9	56.0	56.0
56	54.9	55.2	55.5	55.7	55.8	56.0	56.0	56.0	56.1	56.2	56.3	56.3
56	55.0	55.3	55.6	55.8	55.9	56.1	56.1	56.2	56.2	56.3	56.4	56.4
57	55.1	55.5	56.7	57.0	57.1	57.2	57.3	57.3	57.4	57.4	57.5	57.5
59	58.1	58.4	58.7	59.0	59.1	59.2	59.3	59.3	59.4	59.4	59.5	59.5
61	60.6	60.9	61.1	61.5	61.6	61.7	61.8	61.8	61.9	61.9	62.0	62.0
62	61.2	61.5	61.3	62.1	62.2	62.4	62.4	62.4	62.5	62.5	62.6	62.6
63	63.3	63.6	63.9	64.2	64.4	64.5	64.6	64.6	64.7	64.7	64.8	64.8
65	64.5	64.8	65.1	65.5	65.6	65.8	65.8	65.9	65.9	66.0	66.1	66.1
67	65.5	65.9	66.2	66.6	66.7	66.9	66.9	67.0	67.0	67.1	67.2	67.2
68	67.6	67.9	68.2	68.6	68.8	68.9	69.0	69.0	69.1	69.1	69.2	69.2
70	68.9	69.2	69.6	70.0	70.1	70.3	70.3	70.4	70.4	70.5	70.6	70.6
72	71.4	71.9	72.2	72.6	72.7	72.9	72.9	73.0	73.0	73.1	73.2	73.2
75	73.2	73.7	74.1	74.6	74.8	75.0	75.0	75.1	75.1	75.2	75.3	75.3
77	75.3	75.8	76.3	76.8	77.0	77.2	77.2	77.3	77.3	77.4	77.5	77.5
79	77.0	77.5	78.0	78.5	78.7	78.9	79.0	79.0	79.1	79.1	79.2	79.2
80	77.9	80.4	80.9	81.5	81.7	81.9	81.9	82.0	82.1	82.1	82.2	82.2
82	80.4	81.0	81.5	82.1	82.3	82.5	82.6	82.6	82.7	82.8	82.9	82.9
84	81.7	82.3	82.9	83.5	83.7	83.9	84.0	84.0	84.1	84.1	84.2	84.2
85	83.0	83.6	84.2	84.8	85.1	85.3	85.3	85.4	85.5	85.5	85.6	85.6
86	84.1	84.8	85.5	86.1	86.3	86.5	86.6	86.7	86.7	86.8	86.9	86.9
87	85.0	85.7	86.4	87.1	87.3	87.5	87.6	87.6	87.7	87.7	87.8	87.8
88	85.5	86.5	87.3	88.0	88.2	88.4	88.5	88.5	88.6	88.7	88.8	88.8
89	86.1	87.5	88.5	89.2	89.4	89.6	89.7	89.7	89.8	89.9	90.0	90.0
91	87.4	88.3	89.5	90.3	90.6	90.8	90.9	90.9	91.0	91.0	91.1	91.2
92	88.1	89.1	90.6	91.7	92.0	92.2	92.4	92.4	92.5	92.6	92.7	92.7
94	88.6	89.7	91.5	92.9	93.3	93.7	93.8	93.9	94.1	94.1	94.2	94.3
95	89.3	90.1	92.0	93.9	94.6	95.2	95.6	95.7	96.0	96.1	96.3	96.4
97	88.9	90.1	92.1	94.3	95.2	95.9	96.6	96.8	97.6	97.9	98.4	98.7
98	89.0	90.2	92.2	94.4	95.3	96.1	96.9	97.1	98.0	98.3	99.1	99.9
99	89.0	90.2	92.2	94.4	95.3	96.1	96.9	97.1	98.0	98.3	99.1	100.0

OPERATING LOCATION NAME
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. T. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: SEP HOURS

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	46.7	47.1	47.3	47.9	48.7	49.0	49.9	50.0	50.0	50.1	50.3	50.0
GE 20000	48.7	49.1	49.3	49.9	50.8	51.1	52.0	52.1	52.1	52.2	52.4	52.0
GE 18000	48.7	49.1	49.3	49.9	50.8	51.1	52.0	52.1	52.1	52.2	52.4	52.0
GE 16000	48.7	49.1	49.3	49.9	50.8	51.1	52.0	52.1	52.1	52.2	52.4	52.0
GE 14000	49.1	49.6	49.8	50.3	51.2	51.6	52.4	52.6	52.6	52.7	52.9	52.0
GE 12000	49.6	50.0	50.2	50.8	51.7	52.0	52.9	53.0	53.0	53.1	53.3	53.0
GE 10000	51.0	51.4	51.7	52.4	53.3	53.7	54.6	54.7	54.7	54.8	55.0	55.0
GE 9000	52.0	52.4	52.7	53.6	54.4	54.8	55.7	55.8	55.9	55.9	56.1	55.0
GE 8000	53.4	53.9	54.1	55.0	55.9	56.2	57.1	57.2	57.2	57.3	57.6	57.0
GE 7000	55.0	55.4	55.7	56.6	57.4	57.8	58.7	58.8	58.8	58.9	59.1	59.0
GE 6000	55.9	56.3	56.6	57.4	58.3	58.7	59.6	60.0	60.0	60.1	60.3	60.0
GE 5000	57.7	58.2	58.7	59.6	60.4	60.8	62.0	62.8	62.8	62.9	63.1	63.0
GE 4500	58.8	59.3	59.9	60.8	61.8	62.2	63.4	64.2	64.2	64.3	64.6	64.0
GE 4000	62.0	62.6	63.1	64.0	65.3	65.8	67.0	67.8	67.9	67.9	68.1	68.0
GE 3500	62.9	63.4	64.0	64.9	66.2	66.7	67.9	68.7	68.7	68.8	69.0	69.0
GE 3000	63.9	64.4	65.2	66.1	67.4	67.9	69.1	70.0	70.0	70.1	70.3	70.0
GE 2500	65.2	65.9	66.8	67.7	69.1	69.6	70.8	71.7	71.7	71.8	72.0	72.0
GE 2000	67.2	68.0	69.1	70.3	71.8	72.3	73.7	74.6	74.6	74.7	74.9	74.0
GE 1800	67.7	68.4	69.6	70.9	72.4	73.0	74.3	75.2	75.2	75.3	75.6	75.0
GE 1500	69.2	70.2	71.4	72.9	74.7	75.2	76.6	77.6	77.6	77.7	78.0	78.0
GE 1200	70.3	71.3	72.7	74.1	75.9	76.4	77.8	78.8	78.8	78.9	79.2	79.0
GE 1000	70.4	71.4	72.8	74.6	76.3	76.9	78.2	79.2	79.2	79.3	79.7	79.0
GE 900	70.9	71.9	73.2	75.1	76.9	77.4	78.8	80.0	80.0	80.1	80.4	80.0
GE 800	71.0	72.0	73.3	75.3	77.1	78.0	79.4	80.7	80.7	80.8	81.1	81.0
GE 700	71.3	72.3	73.7	75.9	77.7	78.6	80.0	81.2	81.2	81.3	81.7	81.0
GE 600	72.1	73.3	75.2	77.3	79.1	80.0	81.4	82.7	82.7	82.8	83.1	83.0
GE 500	72.7	73.9	75.9	78.3	80.9	81.8	83.9	85.1	85.1	85.2	85.6	85.0
GE 400	73.3	74.6	76.7	79.3	82.1	83.4	86.0	87.7	87.9	88.0	88.3	88.0
GE 300	73.4	74.7	77.0	79.9	83.1	85.0	88.4	90.2	90.9	91.0	91.4	91.0
GE 200	73.4	74.7	77.2	80.2	83.4	85.3	89.2	91.6	92.9	93.6	94.6	94.0
GE 100	73.4	74.7	77.2	80.2	83.4	85.3	89.2	91.6	92.9	93.7	94.9	95.0
GE 000	73.4	74.7	77.2	80.2	83.4	85.3	89.2	91.6	92.9	93.7	94.9	95.0

TOTAL NUMBER OF OBSERVATIONS 900

ISI

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

JG
10-0

NAME: K. T. SAWYER AFB MI
LOC: + 5

PERIOD OF RECORD: AUG 78 - JUL 86
MONTH: SEP HOURS: 00-02

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GF 5/8	GF 1/2	GE 3/8	GE 1/4	GE 0
50	47.7	49.0	49.9	50.0	50.0	50.1	50.3	50.3	50.6	50.6	50.6	50.6
51	50.8	51.1	52.0	52.1	52.1	52.2	52.4	52.4	52.7	52.7	52.7	52.7
52	50.8	51.1	52.0	52.1	52.1	52.2	52.4	52.4	52.7	52.7	52.7	52.7
53	51.2	51.6	52.4	52.6	52.6	52.7	52.9	52.9	53.1	53.1	53.1	53.1
54	51.7	52.0	52.9	53.0	53.0	53.1	53.3	53.3	53.6	53.6	53.6	53.6
55	53.3	53.7	54.5	54.7	54.7	54.8	55.0	55.0	55.2	55.3	55.4	55.4
56	54.4	54.3	55.7	55.8	55.9	55.9	56.1	56.1	56.3	56.4	56.6	56.6
57	55.9	56.2	57.1	57.2	57.2	57.3	57.6	57.6	57.8	57.9	58.0	58.0
58	57.4	57.8	58.7	58.8	58.8	58.9	59.1	59.1	59.3	59.4	59.6	59.6
59	58.3	58.7	59.6	60.0	60.0	60.1	60.3	60.3	60.6	60.7	60.8	60.8
60	60.4	60.8	62.0	62.8	62.8	62.9	63.1	63.1	63.3	63.4	63.6	63.6
61	61.8	62.2	63.4	64.2	64.2	64.3	64.5	64.6	64.8	64.9	65.0	65.0
62	65.3	65.8	67.0	67.8	67.8	67.9	68.1	68.1	68.3	68.4	68.6	68.6
63	66.2	66.7	67.9	68.7	68.7	68.8	69.0	69.0	69.2	69.3	69.4	69.4
64	67.4	67.9	69.1	70.0	70.0	70.1	70.3	70.3	70.6	70.7	70.8	70.8
65	69.1	69.6	70.8	71.7	71.7	71.8	72.0	72.0	72.2	72.3	72.4	72.4
66	71.8	72.3	73.7	74.5	74.5	74.7	74.9	74.9	75.1	75.2	75.3	75.3
67	72.4	73.0	74.3	75.2	75.2	75.3	75.6	75.6	75.8	75.9	76.0	76.0
68	74.7	75.2	76.5	77.6	77.6	77.7	78.0	78.0	78.2	78.3	78.4	78.4
69	75.9	76.4	77.8	78.8	78.8	78.9	79.2	79.2	79.4	79.6	79.7	79.7
70	76.3	76.9	78.2	79.2	79.2	79.3	79.7	79.7	79.9	80.0	80.1	80.1
71	79.9	77.4	78.8	80.0	80.0	80.1	80.4	80.4	80.7	80.8	80.9	80.9
72	77.1	78.0	79.4	80.7	80.7	80.8	81.1	81.1	81.3	81.4	81.6	81.6
73	77.7	78.6	80.0	81.2	81.2	81.3	81.7	81.7	81.9	82.0	82.1	82.1
74	79.1	80.0	81.4	82.7	82.7	82.8	83.1	83.1	83.3	83.4	83.6	83.6
75	80.7	81.8	83.9	85.1	85.1	85.2	85.6	85.6	85.9	86.0	86.1	86.1
76	82.1	83.4	86.0	87.7	87.9	88.0	88.3	88.3	88.8	88.9	89.0	89.0
77	83.1	85.0	86.4	90.2	90.4	91.0	91.4	91.6	92.1	92.8	93.1	93.2
78	83.4	85.3	89.2	91.6	92.9	93.6	94.6	94.8	95.8	96.6	97.3	97.8
79	83.4	85.3	89.2	91.6	92.9	93.7	94.9	95.1	96.3	97.1	98.0	99.2
80	83.4	85.3	89.2	91.6	92.9	93.7	94.9	95.1	96.3	97.1	98.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: SEP HOURS: 03-0

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	42.0	42.2	42.7	43.0	44.3	44.7	45.1	45.4	45.8	46.1	46.3	46.3	46	
GE 20000	43.6	43.8	44.2	44.7	46.1	46.4	46.9	47.2	47.6	47.9	48.1	48.1	48	
GE 18000	43.8	44.0	44.4	44.7	46.3	46.7	47.1	47.4	47.8	48.1	48.3	48.3	48	
GE 16000	43.9	44.2	44.7	45.2	46.7	47.0	47.4	47.8	48.1	48.4	48.7	48.7	49	
GE 14000	44.2	44.6	45.0	45.6	47.0	47.3	47.8	48.4	48.8	49.1	49.3	49.3	49	
GE 12000	45.1	45.4	46.2	46.8	48.2	48.6	49.1	49.8	50.1	50.4	50.7	50.7	51	
GE 10000	46.6	47.0	47.8	48.3	49.8	50.1	50.7	51.3	51.7	52.0	52.2	52.2	52	
GE 9000	47.1	47.6	48.4	49.1	50.8	51.1	51.7	52.3	52.7	53.0	53.2	53.2	53	
GE 8000	49.2	49.7	50.6	51.3	53.1	53.4	54.0	54.7	55.0	55.3	55.6	55.6	55	
GE 7000	50.1	50.7	51.6	52.3	54.1	54.4	55.0	55.7	56.0	56.3	56.6	56.6	56	
GE 6000	50.9	51.4	52.4	53.2	55.0	55.3	55.9	56.6	56.9	57.2	57.4	57.4	57	
GE 5000	52.2	53.0	54.4	55.3	57.1	57.4	58.0	58.7	59.0	59.3	59.6	59.6	59	
GE 4500	53.6	54.3	55.8	56.7	58.6	58.9	59.4	60.1	60.4	60.8	61.0	61.0	61	
GE 4000	56.2	57.0	58.6	59.4	61.3	61.7	62.2	62.9	63.2	63.6	63.8	63.8	64	
GE 3500	57.1	57.9	59.4	60.4	62.3	62.7	63.2	63.9	64.2	64.6	64.8	64.8	65	
GE 3000	58.6	59.3	61.1	62.1	64.0	64.3	64.9	65.6	65.9	66.2	66.4	66.4	66	
GE 2500	60.8	61.7	63.7	64.9	67.0	67.3	68.0	68.7	69.0	69.3	69.6	69.6	69	
GE 2000	63.3	64.2	66.3	67.7	70.1	70.4	71.1	71.9	72.2	72.6	72.8	72.8	73	
GE 1800	63.6	64.4	66.5	67.9	70.4	70.8	71.4	72.2	72.6	72.9	73.1	73.1	73	
GE 1500	65.2	66.1	68.2	69.6	72.4	72.8	73.4	74.2	74.6	74.9	75.1	75.1	75	
GE 1200	65.3	66.3	68.6	69.9	72.9	73.2	73.9	74.8	75.1	75.4	75.7	75.7	76	
GE 1000	66.2	67.2	69.4	70.9	73.9	74.2	75.2	76.1	76.4	76.8	77.0	77.0	77	
GE 900	66.4	67.4	69.7	71.2	74.2	74.6	75.7	76.6	76.9	77.2	77.4	77.4	77	
GE 800	66.8	67.8	70.2	71.8	75.0	75.6	77.0	77.9	78.2	78.6	78.8	78.8	79	
GE 700	67.1	68.1	70.7	72.4	75.7	76.2	77.7	78.6	78.9	79.2	79.4	79.4	79	
GE 600	68.2	69.2	72.2	74.6	78.1	78.7	80.2	81.2	81.6	81.9	82.1	82.1	82	
GE 500	68.8	69.8	73.3	75.7	79.8	80.4	82.3	83.6	83.9	84.2	84.4	84.4	84	
GE 400	68.8	69.8	73.8	76.2	81.1	81.8	84.4	86.1	86.6	87.1	87.3	87.3	87	
GE 300	69.2	70.2	74.4	77.0	82.3	83.1	87.0	89.1	89.9	90.6	90.8	90.8	91	
GE 200	69.2	70.2	74.4	77.1	82.6	83.8	88.2	91.1	92.7	93.4	94.4	94.4	95	
GE 100	69.2	70.2	74.4	77.1	82.6	83.8	88.2	91.1	92.7	93.6	94.8	94.8	95	
GE 000	69.2	70.2	74.4	77.1	82.6	83.8	88.2	91.1	92.7	93.6	94.8	94.8	95	

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: SEP HOURS: 03-05

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
43.0	44.3	44.7	45.1	45.4	45.8	46.1	46.3	46.3	46.7	46.9	47.0	47.0
44.7	46.1	46.4	46.9	47.2	47.6	47.9	48.1	48.1	48.4	48.7	48.8	48.8
44.9	46.3	46.7	47.1	47.4	47.8	48.1	48.3	48.3	48.7	48.9	49.0	49.0
45.2	46.7	47.0	47.4	47.8	48.1	48.4	48.7	48.7	49.0	49.2	49.3	49.3
45.6	47.0	47.3	47.8	48.4	48.8	49.1	49.3	49.3	49.7	49.9	50.0	50.0
46.8	48.2	48.6	49.1	49.8	50.1	50.4	50.7	50.7	51.0	51.2	51.3	51.3
48.3	49.8	50.1	50.7	51.3	51.7	52.0	52.2	52.2	52.6	52.8	52.9	52.9
49.1	50.8	51.1	51.7	52.3	52.7	53.0	53.2	53.2	53.6	53.8	53.9	53.9
51.3	53.1	53.4	54.0	54.7	55.0	55.3	55.6	55.6	55.9	56.1	56.2	56.2
52.3	54.1	54.4	55.0	55.7	56.0	56.3	56.6	56.6	56.9	57.1	57.2	57.2
53.2	55.0	55.3	55.9	56.6	56.9	57.2	57.4	57.4	57.8	58.0	58.1	58.1
55.3	57.1	57.4	58.0	58.7	59.0	59.3	59.6	59.6	59.9	60.1	60.2	60.2
56.7	58.6	58.9	59.4	60.1	60.4	60.8	61.0	61.0	61.3	61.6	61.7	61.7
59.4	61.3	61.7	62.2	62.9	63.2	63.6	63.8	63.8	64.1	64.3	64.4	64.4
60.4	62.3	62.7	63.2	63.9	64.2	64.6	64.8	64.8	65.1	65.3	65.4	65.4
62.1	64.0	64.3	64.9	65.6	65.9	66.2	66.4	66.4	66.8	67.0	67.1	67.1
64.1	67.0	67.3	68.0	68.7	69.0	69.3	69.6	69.6	69.9	70.1	70.2	70.2
67.7	70.1	70.4	71.1	71.9	72.2	72.6	72.8	72.8	73.1	73.3	73.4	73.4
67.9	70.4	70.8	71.4	72.2	72.6	72.9	73.1	73.1	73.4	73.7	73.8	73.8
69.6	72.4	72.8	73.4	74.2	74.6	74.9	75.1	75.1	75.4	75.7	75.8	75.8
69.9	72.9	73.2	73.9	74.8	75.1	75.4	75.7	75.7	76.0	76.2	76.3	76.3
70.9	73.9	74.2	75.2	76.1	76.4	76.8	77.0	77.0	77.3	77.6	77.7	77.7
71.2	74.2	74.6	75.7	76.6	76.9	77.2	77.4	77.4	77.8	78.0	78.1	78.1
71.3	75.0	75.5	77.0	77.9	78.2	78.6	78.8	78.8	79.1	79.3	79.4	79.4
72.4	75.7	76.2	77.7	78.6	78.9	79.2	79.4	79.4	79.8	80.0	80.1	80.1
74.6	78.1	78.7	80.2	81.2	81.6	81.9	82.1	82.1	82.4	82.7	82.8	82.8
75.7	79.9	80.4	82.3	83.6	83.9	84.2	84.4	84.4	84.8	85.0	85.1	85.2
76.2	81.1	81.8	84.4	86.1	86.6	87.1	87.3	87.3	87.7	87.9	88.2	88.3
77.0	82.3	83.1	87.0	89.1	89.9	90.6	90.8	90.8	91.2	91.8	92.1	92.8
77.1	82.6	83.8	88.2	91.1	92.7	93.4	94.4	94.4	95.3	96.0	96.4	98.0
77.1	82.6	83.8	88.2	91.1	92.7	93.6	94.8	94.8	95.8	96.7	97.2	99.3
77.1	82.6	83.8	88.2	91.1	92.7	93.6	94.8	94.8	95.8	96.7	97.2	100.0

999

1

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: SEP HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	34.3	34.8	35.7	36.1	37.0	37.0	37.3	38.0	38.8	38.8	39.1	39.2	39.6	
GE 20000	37.1	37.7	38.6	39.6	40.7	40.7	41.0	41.8	42.8	42.8	43.1	43.2	43.6	
GE 18000	37.6	38.1	39.0	40.0	41.1	41.1	41.4	42.2	43.2	43.2	43.6	43.7	43.9	
GE 16000	37.9	38.4	39.4	40.4	41.6	41.6	41.9	42.7	43.7	43.7	44.0	44.1	44.3	
GE 14000	38.1	38.7	39.7	40.7	41.8	41.8	42.1	43.2	44.2	44.2	44.6	44.7	44.9	
GE 12000	38.7	39.2	40.4	41.4	42.6	42.6	42.9	44.0	45.1	45.1	45.6	45.7	46.0	
GE 10000	41.3	42.1	43.4	44.4	45.6	45.6	45.9	47.0	48.1	48.1	48.6	48.7	49.1	
GE 9000	42.3	43.1	44.4	45.4	46.6	46.6	46.9	48.0	49.1	49.1	49.6	49.7	50.1	
GE 8000	45.2	46.2	47.6	48.6	50.0	50.0	50.4	51.6	52.8	52.9	53.3	53.4	53.9	
GE 7000	45.8	46.8	48.2	49.3	50.9	50.9	51.3	52.4	53.7	53.8	54.3	54.4	54.9	
GE 6000	46.4	47.4	49.1	50.4	52.0	52.0	52.4	53.6	54.9	54.9	55.4	55.6	56.1	
GE 5000	49.3	50.6	52.4	54.2	56.0	56.0	56.4	57.6	58.8	58.9	59.4	59.6	59.9	
GE 4500	50.4	51.7	53.9	55.7	57.6	57.6	58.1	59.2	60.4	60.6	61.1	61.2	61.6	
GE 4000	52.6	54.0	56.1	58.1	60.1	60.1	60.7	61.8	63.0	63.1	63.8	63.9	64.3	
GE 3500	53.1	54.6	56.7	58.7	60.8	60.9	61.4	62.6	63.8	63.9	64.6	64.7	65.1	
GE 3000	55.2	56.7	58.8	60.8	62.9	63.0	63.6	64.7	65.9	66.0	66.7	66.8	67.2	
GE 2500	57.9	59.4	61.6	63.6	65.7	65.8	66.3	67.4	68.7	68.8	69.4	69.6	69.9	
GE 2000	60.0	61.7	63.9	65.9	68.2	68.3	68.9	70.0	71.3	71.4	72.1	72.2	72.5	
GE 1800	60.3	62.0	64.2	66.2	68.6	68.7	69.2	70.3	71.7	71.8	72.4	72.6	72.9	
GE 1500	61.4	63.1	65.3	67.7	70.1	70.2	70.9	72.1	73.4	73.6	74.2	74.3	74.6	
GE 1200	62.9	64.7	67.0	69.3	72.0	72.1	72.8	74.1	75.4	75.6	76.2	76.3	76.6	
GE 1000	64.2	66.1	68.4	70.8	73.9	74.1	74.9	76.4	77.8	77.9	78.6	78.7	79.0	
GE 900	64.7	66.6	68.9	71.2	74.4	74.7	75.4	77.1	78.4	78.6	79.2	79.3	79.6	
GE 800	65.0	66.9	69.2	71.6	74.9	75.2	76.1	77.9	79.3	79.4	80.1	80.2	80.5	
GE 700	65.3	67.2	69.6	72.3	76.0	76.3	77.3	79.2	80.7	80.8	81.4	81.6	81.9	
GE 600	65.7	67.7	70.2	73.3	77.8	78.2	79.2	81.1	82.6	82.7	83.3	83.4	83.7	
GE 500	66.1	68.1	71.0	74.2	79.1	79.7	81.0	83.3	85.0	85.1	85.8	85.9	86.2	
GE 400	66.6	68.7	71.9	75.1	80.0	80.7	82.2	84.8	86.7	87.1	87.8	87.9	88.2	
GE 300	66.8	69.0	72.7	76.0	81.6	82.7	84.9	88.0	90.7	91.4	92.1	92.2	92.5	
GE 200	66.9	69.1	72.9	76.2	81.8	83.0	85.4	89.1	91.9	92.9	93.9	94.4	94.9	
GE 100	66.9	69.1	72.9	76.2	81.8	83.0	85.6	89.3	92.1	93.1	94.1	94.8	95.3	
GE 000	66.9	69.1	72.9	76.2	81.8	83.0	85.6	89.3	92.1	93.1	94.1	94.8	95.3	

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: 06-08

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
36.1	37.0	37.0	37.3	38.0	39.8	38.8	39.1	39.2	39.4	39.4	39.4	39.6
39.5	40.7	40.7	41.0	41.8	42.8	42.8	43.1	43.2	43.4	43.4	43.6	43.7
40.0	41.1	41.1	41.4	42.2	43.2	43.2	43.6	43.7	43.9	43.9	44.0	44.1
40.4	41.6	41.6	41.9	42.7	43.7	43.7	44.0	44.1	44.3	44.3	44.4	44.6
40.7	41.8	41.8	42.1	43.2	44.2	44.2	44.6	44.7	44.9	44.9	45.0	45.1
41.4	42.6	42.6	42.9	44.0	45.1	45.1	45.6	45.7	46.0	46.0	46.2	46.3
44.4	45.6	45.6	45.9	47.0	48.1	48.1	48.6	48.7	49.0	49.0	49.2	49.3
45.4	46.6	46.6	46.9	48.0	49.1	49.1	49.6	49.7	50.0	50.0	50.2	50.3
48.5	50.0	50.0	50.4	51.6	52.8	52.9	53.3	53.4	53.8	53.8	54.0	54.1
49.3	50.9	50.9	51.3	52.4	53.7	53.8	54.3	54.4	54.8	54.8	55.0	55.1
50.4	52.0	52.0	52.4	53.6	54.8	54.9	55.4	55.6	55.9	55.9	56.1	56.2
54.2	56.0	56.0	56.4	57.6	58.8	58.9	59.4	59.6	59.9	60.0	60.2	60.3
55.7	57.6	57.6	58.1	59.2	60.4	60.6	61.1	61.2	61.6	61.7	61.9	62.0
54.1	60.1	60.1	60.7	61.8	63.0	63.1	63.8	63.9	64.2	64.3	64.6	64.7
53.7	60.8	60.9	61.4	62.6	63.8	63.9	64.6	64.7	65.0	65.1	65.3	65.4
50.3	62.9	63.0	63.6	64.7	65.9	66.0	66.7	66.8	67.1	67.2	67.4	67.6
53.6	65.7	65.8	66.3	67.4	68.7	68.8	69.4	69.6	69.9	70.0	70.2	70.3
55.9	63.2	68.3	68.9	70.0	71.3	71.4	72.1	72.2	72.6	72.7	72.9	73.0
56.2	68.6	68.7	69.2	70.3	71.7	71.8	72.4	72.6	72.9	73.0	73.2	73.3
67.7	70.1	70.2	70.9	72.1	73.4	73.6	74.2	74.3	74.7	74.8	75.0	75.1
69.3	72.0	72.1	72.8	74.1	75.4	75.6	76.2	76.3	76.7	76.8	77.0	77.1
70.3	73.9	74.1	74.9	76.4	77.8	77.9	78.6	78.7	79.0	79.1	79.3	79.4
71.2	74.4	74.7	75.4	77.1	78.4	78.6	79.2	79.3	79.7	79.8	80.0	80.1
71.6	74.9	75.2	76.1	77.9	79.3	79.4	80.1	80.2	80.6	80.7	80.9	81.0
72.3	76.0	76.3	77.3	79.2	80.7	80.8	81.4	81.6	81.9	82.0	82.3	82.4
73.2	77.8	78.2	79.2	81.1	82.6	82.7	83.3	83.4	83.8	83.9	84.2	84.3
74.2	79.1	79.7	81.0	83.3	85.0	85.1	85.8	85.9	86.2	86.3	86.7	86.8
75.1	80.0	80.7	82.2	84.8	86.7	87.1	87.8	87.9	88.3	88.4	88.8	88.9
76.0	81.6	82.7	84.9	88.0	90.7	91.4	92.1	92.2	92.8	92.9	93.2	93.8
76.2	81.8	83.0	85.4	89.1	91.9	92.9	93.9	94.4	95.6	95.8	96.4	98.0
76.2	81.8	83.0	85.6	89.3	92.1	93.1	94.1	94.8	95.9	96.3	97.3	99.7
76.2	81.8	83.0	85.6	89.3	92.1	93.1	94.1	94.8	95.9	96.3	97.3	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 1
MONTH: SEP HOURS: 09-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	35.0	35.9	36.6	36.6	36.9	37.2	37.2	37.3	37.3	37.3	37.3	37.3	37.3
GE 20000	38.7	39.6	40.3	40.7	41.2	41.6	41.6	41.8	41.8	41.8	41.9	41.9	41.9
GE 19000	38.9	39.8	40.6	40.9	41.6	41.9	42.0	42.3	42.3	42.3	42.4	42.4	42.4
GE 16000	39.1	40.0	40.8	41.2	41.9	42.2	42.3	42.7	42.7	42.7	42.8	42.8	42.8
GE 14000	39.9	40.8	41.6	42.1	42.8	43.1	43.4	43.8	43.8	43.8	43.9	43.9	43.9
GE 12000	41.0	41.9	42.7	43.3	44.0	44.3	44.7	45.0	45.0	45.0	45.1	45.1	45.1
GE 10000	42.9	43.9	44.8	45.4	46.2	46.6	46.9	47.2	47.2	47.2	47.3	47.3	47.3
GE 9000	43.2	44.2	45.1	45.8	46.6	46.9	47.2	47.6	47.6	47.6	47.7	47.7	47.7
GE 8000	46.1	47.2	48.7	49.4	50.2	50.6	51.1	51.4	51.6	51.6	51.7	51.7	51.7
GE 7000	47.9	49.0	50.6	51.3	52.4	52.8	53.3	53.8	53.9	54.0	54.1	54.1	54.1
GE 6000	48.6	49.7	51.3	52.1	53.2	53.6	54.1	54.6	54.7	54.8	54.9	54.9	54.9
GE 5000	49.7	50.8	53.1	53.9	55.3	55.8	56.3	56.8	56.9	57.0	57.1	57.1	57.1
GE 4500	50.3	51.6	53.9	54.7	56.1	56.6	57.1	57.6	57.7	57.8	57.9	57.9	57.9
GE 4000	51.9	53.2	55.8	56.7	58.2	58.7	59.2	60.0	60.1	60.2	60.3	60.3	60.3
GE 3500	53.1	54.4	57.0	57.9	59.4	59.9	60.4	61.2	61.3	61.4	61.6	61.6	61.6
GE 3000	55.8	57.2	59.9	60.9	62.6	63.1	63.7	64.4	64.6	64.7	64.8	64.8	64.8
GE 2500	57.6	59.0	61.9	62.9	64.6	65.1	65.7	66.4	66.6	66.7	66.8	66.8	66.8
GE 2000	61.2	62.7	65.3	66.8	69.6	69.2	69.9	70.7	70.8	70.9	71.0	71.0	71.0
GE 1800	62.1	63.6	66.8	67.9	69.7	70.3	71.0	71.8	71.9	72.0	72.1	72.1	72.1
GE 1500	64.4	65.9	69.4	70.6	72.4	73.2	73.9	74.7	74.8	74.9	75.0	75.0	75.0
GE 1200	66.8	68.2	71.8	72.9	74.9	75.7	76.3	77.1	77.2	77.3	77.4	77.4	77.4
GE 1000	68.3	69.8	73.6	74.9	77.1	78.0	78.7	79.4	79.6	79.7	79.8	79.8	79.8
GE 900	69.2	70.8	74.5	76.0	78.4	79.3	80.0	80.8	80.9	81.0	81.1	81.1	81.1
GE 800	70.4	72.0	76.0	77.8	80.2	81.2	82.2	83.0	83.1	83.2	83.3	83.3	83.3
GE 700	71.1	72.7	76.7	78.4	81.3	82.4	83.7	84.7	84.8	84.9	85.0	85.0	85.0
GE 600	71.7	73.2	77.8	80.2	83.7	84.8	86.1	87.2	87.3	87.4	87.6	87.6	87.6
GE 500	72.1	74.1	79.1	81.9	85.4	86.9	88.7	90.2	90.6	90.7	90.8	90.8	90.8
GE 400	72.4	74.4	79.7	82.8	86.7	88.3	90.1	92.2	92.7	92.9	93.0	93.0	93.0
GE 300	72.6	74.6	79.9	83.1	87.2	88.9	91.2	94.1	95.2	95.6	95.7	95.7	95.7
GE 200	72.6	74.6	80.0	83.2	87.6	89.3	91.8	94.8	96.6	97.2	97.6	97.9	98.0
GE 100	72.6	74.6	80.0	83.2	87.6	89.3	91.8	94.8	96.6	97.3	97.7	98.0	98.0
GE 000	72.6	74.6	80.0	83.2	87.6	89.3	91.8	94.8	96.6	97.3	97.7	98.0	98.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: 09-11

VISIBILITY IN STATUTE MILES

GF	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
36.6	36.9	37.2	37.2	37.3	37.3	37.3	37.3	37.3	37.4	37.4	37.4	37.4
40.7	41.2	41.6	41.6	41.8	41.8	41.8	41.9	41.9	42.0	42.0	42.0	42.0
40.9	41.6	41.9	42.0	42.3	42.3	42.3	42.4	42.4	42.6	42.6	42.6	42.6
41.2	41.9	42.2	42.3	42.7	42.7	42.7	42.8	42.8	42.9	42.9	42.9	42.9
42.1	42.8	43.1	43.4	43.8	43.8	43.8	43.9	43.9	44.0	44.0	44.0	44.0
43.3	44.0	44.3	44.7	45.0	45.0	45.0	45.1	45.1	45.2	45.2	45.2	45.2
45.4	46.2	46.6	46.9	47.2	47.2	47.2	47.3	47.3	47.4	47.4	47.4	47.4
45.3	46.6	46.9	47.2	47.6	47.6	47.6	47.7	47.7	47.8	47.8	47.8	47.8
49.4	50.2	50.6	51.1	51.4	51.6	51.6	51.7	51.7	51.8	51.8	51.8	51.8
51.3	52.4	52.8	53.3	53.8	53.9	54.0	54.1	54.1	54.2	54.2	54.2	54.2
52.1	53.2	53.6	54.1	54.6	54.7	54.8	54.9	54.9	55.0	55.0	55.0	55.0
53.9	55.3	55.8	56.3	56.8	56.9	57.0	57.1	57.1	57.2	57.2	57.2	57.2
54.7	56.1	56.6	57.1	57.6	57.7	57.8	57.9	57.9	58.0	58.0	58.0	58.0
56.7	58.2	58.7	59.2	60.0	60.1	60.2	60.3	60.3	60.4	60.4	60.4	60.4
57.9	59.4	59.9	60.4	61.2	61.3	61.4	61.6	61.6	61.7	61.7	61.7	61.7
60.9	62.6	63.1	63.7	64.4	64.6	64.7	64.8	64.8	64.9	64.9	64.9	64.9
62.9	64.6	65.1	65.7	66.4	66.6	66.7	66.8	66.8	66.9	66.9	66.9	66.9
66.3	68.6	69.2	69.9	70.7	70.8	70.9	71.0	71.0	71.1	71.1	71.1	71.1
67.9	69.7	70.3	71.0	71.8	71.9	72.0	72.1	72.1	72.2	72.2	72.2	72.2
70.6	72.4	73.2	73.9	74.7	74.8	74.9	75.0	75.0	75.1	75.1	75.1	75.1
72.9	74.9	75.7	76.3	77.1	77.2	77.3	77.4	77.4	77.6	77.6	77.6	77.6
74.9	77.1	78.0	78.7	79.4	79.6	79.7	79.8	79.8	79.9	79.9	79.9	79.9
76.0	78.4	79.3	80.0	80.8	80.9	81.0	81.1	81.1	81.2	81.2	81.2	81.2
77.3	80.2	81.2	82.2	83.0	83.1	83.2	83.3	83.3	83.4	83.4	83.4	83.4
78.4	81.3	82.4	83.7	84.7	84.8	84.9	85.0	85.0	85.1	85.1	85.1	85.1
80.2	83.7	84.8	86.1	87.2	87.3	87.4	87.6	87.6	87.7	87.7	87.7	87.7
81.9	85.4	86.9	88.7	90.2	90.6	90.7	90.8	90.8	90.9	90.9	90.9	90.9
82.3	86.7	88.3	90.1	92.2	92.7	92.9	93.0	93.0	93.2	93.2	93.2	93.2
83.1	87.2	88.9	91.2	94.1	95.2	95.6	95.7	95.7	95.9	95.9	96.0	96.0
83.2	87.6	89.3	91.8	94.8	96.6	97.2	97.6	97.9	98.4	98.7	99.0	99.1
83.2	87.6	89.3	91.8	94.8	96.6	97.3	97.7	98.0	98.6	98.9	99.2	100.0
83.2	87.6	89.3	91.3	94.8	96.6	97.3	97.7	98.0	98.6	98.9	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: SEP HOURS: 12-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	31.7	32.7	33.4	33.6	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
GE 20000	36.6	36.0	39.0	39.1	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3
GE 18000	36.8	36.2	39.2	39.3	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7
GE 16000	36.2	38.2	39.3	39.4	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
GE 14000	37.3	38.8	40.0	40.1	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
GE 12000	38.1	39.6	40.9	41.0	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3
GE 10000	40.1	41.6	43.1	43.2	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
GE 9000	40.7	42.1	43.7	43.8	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2
GE 8000	42.8	44.6	46.5	46.7	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
GE 7000	44.3	46.1	48.1	48.2	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
GE 6000	45.0	46.8	48.8	48.9	49.7	49.9	49.9	50.0	50.0	50.0	50.0	50.0	50.0
GE 5000	46.6	48.8	51.0	51.2	52.3	52.6	52.6	52.7	52.7	52.7	52.7	52.7	52.7
GE 4500	49.0	51.2	53.4	53.7	54.8	55.0	55.0	55.1	55.1	55.1	55.1	55.1	55.1
GE 4000	52.1	54.4	57.0	57.4	58.6	58.8	58.8	58.9	58.9	58.9	58.9	58.9	58.9
GE 3500	54.4	56.9	59.4	59.9	61.0	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3
GE 3000	58.9	61.3	64.1	64.6	65.7	65.9	65.9	66.0	66.0	66.0	66.0	66.0	66.0
GE 2500	63.4	66.1	68.9	69.4	70.6	70.8	70.8	70.9	70.9	70.9	70.9	70.9	70.9
GE 2000	68.3	71.0	74.0	74.6	75.7	75.9	75.9	76.0	76.0	76.0	76.0	76.0	76.0
GE 1800	69.3	72.0	75.0	75.6	76.7	76.9	76.9	77.0	77.0	77.0	77.0	77.0	77.0
GE 1500	71.9	74.8	77.9	78.4	79.7	79.9	79.9	80.0	80.0	80.0	80.0	80.0	80.0
GE 1200	74.1	77.0	80.3	81.0	82.4	82.7	82.8	82.9	82.9	82.9	82.9	82.9	82.9
GE 1000	75.2	78.2	81.8	82.6	84.2	84.4	84.6	84.7	84.7	84.7	84.7	84.7	84.7
GE 900	76.6	79.6	83.3	84.6	86.6	86.8	86.9	87.0	87.0	87.0	87.0	87.0	87.0
GE 800	77.0	80.0	83.3	85.2	87.2	87.6	87.8	87.9	88.1	88.1	88.1	88.1	88.1
GE 700	77.8	80.9	84.8	86.4	88.6	89.1	89.4	89.6	89.8	89.8	89.9	89.9	89.9
GE 600	78.4	81.6	85.8	87.9	90.3	91.2	91.7	92.2	92.7	92.8	92.9	92.9	92.9
GE 500	78.8	81.9	86.4	89.0	91.8	93.1	93.6	94.1	94.8	94.9	95.0	95.0	95.0
GE 400	78.9	82.0	86.6	89.1	92.1	93.6	94.2	94.9	95.8	96.1	96.2	96.2	96.2
GE 300	78.9	82.1	86.7	89.3	92.6	94.1	95.1	95.9	97.6	97.9	98.0	98.0	98.0
GE 200	78.9	82.1	86.7	89.3	92.6	94.2	95.2	96.1	98.6	98.9	99.2	99.2	99.2
GE 100	78.9	82.1	86.7	89.3	92.6	94.2	95.2	96.1	98.6	98.9	99.3	99.3	99.3
GE 000	78.9	82.1	86.7	89.3	92.6	94.2	95.2	96.1	98.6	98.9	99.3	99.3	99.3

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: 12-14

VISIBILITY IN STATUTE MILES

CEILING	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8	33.8
39.1	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3	39.3
39.3	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7	39.7
39.4	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
40.1	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
41.0	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3	41.3
43.2	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
43.3	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2	44.2
47.7	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3	47.3
48.2	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9	48.9
49.9	49.7	49.9	49.9	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
51.2	52.3	52.6	52.6	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7	52.7
53.7	54.8	55.0	55.0	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
57.4	58.6	58.8	58.8	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9
61.0	61.2	61.2	61.2	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3	61.3
64.9	65.7	65.9	65.9	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.0
70.4	70.6	70.8	70.8	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9	70.9
74.6	75.7	75.9	75.9	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0	76.0
78.6	76.7	76.9	76.9	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0
79.4	79.7	79.9	79.9	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
81.0	82.4	82.7	82.8	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9
84.6	84.2	84.4	84.6	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
86.6	86.6	86.8	86.9	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0
87.2	87.2	87.5	87.8	87.9	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
88.6	88.6	89.1	89.4	89.6	89.8	89.8	89.9	89.9	89.9	89.9	89.9	89.9	89.9
90.3	90.3	91.2	91.7	92.2	92.7	92.8	92.9	92.9	92.9	92.9	92.9	92.9	92.9
91.8	91.8	93.1	93.6	94.1	94.8	94.9	95.0	95.0	95.0	95.0	95.0	95.0	95.0
92.1	92.1	93.6	94.2	94.9	95.8	96.1	96.2	96.2	96.2	96.2	96.2	96.2	96.2
92.5	92.5	94.1	95.1	95.9	97.6	97.9	98.0	98.0	98.0	98.0	98.0	98.0	98.0
92.6	92.6	94.2	95.2	96.1	98.6	98.9	99.2	99.2	99.2	99.2	99.2	99.3	99.3
92.6	92.6	94.2	95.2	96.1	98.6	98.9	99.3	99.3	99.3	99.3	99.4	99.8	100.0
92.6	92.6	94.2	95.2	96.1	98.6	98.9	99.3	99.3	99.3	99.3	99.4	99.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: SEP HOURS: 15

CEILING

VISIBILITY IN STATUTE MILFS

IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	36.2	36.7	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
GE 20000	41.2	42.0	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
GE 18000	41.2	42.1	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
GE 16000	41.2	42.1	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
GE 14000	42.0	43.0	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
GE 12000	43.2	44.3	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8
GE 10000	45.2	46.3	48.1	48.1	48.1	48.1	48.1	48.1	48.2	48.3	48.3	48.3
GE 9000	46.2	47.3	49.1	49.1	49.1	49.1	49.1	49.1	49.2	49.3	49.3	49.3
GE 8000	48.4	49.8	51.7	51.7	51.7	51.7	51.7	51.8	51.9	52.0	52.0	52.0
GE 7000	50.2	51.6	53.4	53.4	53.4	53.4	53.4	53.6	53.7	53.9	53.9	53.9
GE 6000	51.2	52.6	54.4	54.7	54.9	54.9	54.9	55.0	55.1	55.3	55.3	55.3
GE 5000	53.1	54.6	56.4	56.7	56.9	56.9	56.9	57.0	57.1	57.3	57.3	57.3
GE 4500	55.9	57.2	59.1	59.3	59.6	59.6	59.6	59.7	59.8	60.0	60.0	60.0
GE 4000	60.0	61.6	63.7	63.9	64.2	64.2	64.2	64.3	64.4	64.7	64.7	64.7
GE 3500	62.9	64.4	66.6	66.8	67.1	67.1	67.1	67.2	67.3	67.6	67.6	67.6
GE 3000	65.9	67.4	69.9	70.1	70.4	70.4	70.4	70.6	70.7	70.9	70.9	70.9
GE 2500	70.6	72.3	75.0	75.2	75.6	75.6	75.6	75.7	75.8	76.0	76.0	76.0
GE 2000	73.9	75.7	78.4	78.5	79.1	79.1	79.1	79.2	79.3	79.6	79.6	79.6
GE 1800	74.2	76.0	78.8	79.1	79.4	79.4	79.4	79.6	79.7	79.9	79.9	79.9
GE 1500	76.3	78.1	81.3	81.7	82.0	82.1	82.1	82.2	82.3	82.6	82.6	82.6
GE 1200	77.9	79.7	83.0	83.3	83.7	83.8	83.9	84.0	84.1	84.3	84.3	84.3
GE 1000	79.4	81.2	84.9	85.2	85.8	85.9	86.2	86.3	86.4	86.7	86.7	86.7
GE 900	79.9	81.9	85.7	86.1	86.8	86.9	87.2	87.3	87.4	87.7	87.7	87.7
GE 800	80.9	83.0	86.9	87.4	88.3	88.4	88.9	89.1	89.4	89.7	89.8	89.8
GE 700	81.1	83.3	87.2	88.1	89.1	89.3	89.8	90.2	90.7	90.9	91.0	91.0
GE 600	81.2	83.4	87.6	89.0	90.4	90.8	91.3	92.2	92.8	93.0	93.1	93.1
GE 500	81.7	83.9	88.3	89.9	91.5	92.2	93.0	94.0	95.2	95.4	95.6	95.6
GE 400	81.7	84.0	88.6	90.2	92.3	92.9	93.9	95.3	96.7	96.9	97.2	97.2
GE 300	81.7	84.0	88.7	90.3	92.5	93.2	94.4	96.0	97.7	98.3	98.7	98.7
GE 200	81.7	84.0	88.7	90.3	92.6	93.2	94.4	96.1	98.2	98.9	99.3	99.3
GE 100	81.7	84.0	88.7	90.3	92.6	93.2	94.4	96.1	98.2	98.9	99.4	99.4
GE 000	81.7	84.0	88.7	90.3	92.6	93.2	94.4	96.1	98.2	98.9	99.4	99.4

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 76 - JUL 88
MONTH: SEP HOURS: 15-17

CEILING	VISIBILITY IN STATUTE MILES											
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9	37.9
43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8
48.1	48.1	48.1	48.1	48.1	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3
49.1	49.1	49.1	49.1	49.1	49.2	49.3	49.3	49.3	49.3	49.3	49.3	49.3
51.7	51.7	51.7	51.7	51.8	51.9	52.0	52.0	52.0	52.0	52.0	52.0	52.0
53.4	53.4	53.4	53.4	53.6	53.7	53.9	53.9	53.9	53.9	53.9	53.9	53.9
54.9	54.9	54.9	54.9	55.0	55.1	55.3	55.3	55.3	55.3	55.3	55.3	55.3
56.9	56.9	56.9	56.9	57.0	57.1	57.3	57.3	57.3	57.3	57.3	57.3	57.3
59.6	59.6	59.6	59.6	59.7	59.8	60.0	60.0	60.0	60.0	60.0	60.0	60.0
64.2	64.2	64.2	64.2	64.3	64.4	64.7	64.7	64.7	64.7	64.7	64.7	64.7
67.1	67.1	67.1	67.1	67.2	67.3	67.6	67.6	67.6	67.6	67.6	67.6	67.6
70.4	70.4	70.4	70.4	70.6	70.7	70.9	70.9	70.9	70.9	70.9	70.9	70.9
75.6	75.6	75.6	75.6	75.7	75.8	76.0	76.0	76.0	76.0	76.0	76.0	76.0
79.1	79.1	79.1	79.1	79.2	79.3	79.6	79.6	79.6	79.6	79.6	79.6	79.6
79.4	79.4	79.4	79.4	79.6	79.7	79.9	79.9	79.9	79.9	79.9	79.9	79.9
82.0	82.0	82.1	82.1	82.2	82.3	82.6	82.6	82.6	82.6	82.6	82.6	82.6
83.7	83.7	83.8	83.9	84.0	84.1	84.3	84.3	84.3	84.3	84.3	84.3	84.3
86.2	86.2	86.2	86.2	86.3	86.4	86.7	86.7	86.7	86.7	86.7	86.7	86.7
86.9	86.9	87.2	87.2	87.3	87.4	87.7	87.7	87.7	87.7	87.7	87.7	87.7
88.3	88.3	88.4	88.7	89.1	89.4	89.7	89.8	89.8	89.8	89.8	89.8	89.8
89.3	89.3	89.3	89.8	90.2	90.7	90.9	91.0	91.0	91.0	91.0	91.0	91.0
90.4	90.4	90.8	91.3	92.2	92.8	93.0	93.1	93.1	93.1	93.1	93.1	93.1
91.5	91.5	92.2	93.0	94.0	95.2	95.4	95.6	95.6	95.6	95.6	95.6	95.6
92.3	92.3	92.9	93.9	95.3	96.7	96.9	97.2	97.2	97.2	97.2	97.2	97.2
92.5	92.5	93.2	94.4	96.0	97.7	98.3	98.7	98.7	98.7	98.7	98.7	98.7
92.6	92.6	93.2	94.4	96.1	98.2	98.9	99.3	99.3	99.4	99.4	99.6	99.6
92.6	92.6	93.2	94.4	96.1	98.2	98.9	99.4	99.4	99.7	99.7	99.9	100.0
92.6	92.6	93.2	94.4	96.1	98.2	98.9	99.4	99.4	99.7	99.7	99.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: SEP HOURS: 18-21

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	42.8	43.1	44.1	44.3	44.8	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44
GE 20000	47.1	47.6	48.8	49.1	49.7	50.1	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50
GE 18000	47.5	48.2	49.2	49.5	50.3	50.6	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50
GE 16000	47.7	48.3	49.3	49.7	50.4	50.8	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50
GE 14000	48.2	49.0	50.0	50.3	51.1	51.4	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51
GE 12000	50.5	51.7	52.9	53.2	54.1	54.4	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54
GE 10000	52.0	53.1	54.0	55.2	55.1	56.4	56.6	56.6	56.7	56.7	56.7	56.7	56.7	56
GE 9000	52.4	53.6	55.3	55.7	55.6	56.9	57.0	57.0	57.1	57.1	57.1	57.1	57.1	57
GE 8000	55.0	55.1	57.0	58.2	59.1	59.4	59.6	59.7	59.9	59.9	59.9	59.9	59.9	59
GE 7000	56.0	57.1	58.9	59.2	59.1	60.4	60.6	60.7	60.9	60.9	60.9	60.9	60.9	60
GE 6000	57.2	58.3	60.1	60.4	61.4	61.8	61.9	62.0	62.2	62.6	62.6	62.6	62.6	62
GE 5000	60.2	61.3	63.1	63.5	64.6	64.9	65.0	65.1	65.3	65.7	65.7	65.7	65.7	65
GE 4500	61.9	63.1	65.0	65.4	65.4	66.8	66.9	67.0	67.2	67.6	67.6	67.6	67.6	67
GE 4000	63.6	65.0	67.2	67.7	68.3	69.1	69.4	69.6	69.8	70.1	70.1	70.1	70.1	70
GE 3500	66.0	67.6	69.8	70.2	71.3	71.7	72.0	72.1	72.3	72.7	72.7	72.7	72.7	72
GE 3000	67.3	68.9	71.1	71.5	72.7	73.0	73.3	73.4	73.7	74.0	74.0	74.0	74.0	74
GE 2500	68.8	70.3	72.6	73.0	74.1	74.4	74.5	74.9	75.1	75.4	75.4	75.4	75.4	75
GE 2000	71.7	73.2	75.5	76.2	77.3	77.7	78.1	78.2	78.4	78.8	78.8	78.8	78.8	78
GE 1800	72.0	73.6	76.1	76.5	77.8	78.1	78.5	78.7	78.9	79.2	79.2	79.2	79.2	79
GE 1500	73.6	75.1	77.8	78.2	79.8	80.1	80.6	80.7	80.9	81.2	81.2	81.2	81.2	81
GE 1200	75.2	75.6	79.6	80.0	81.7	82.0	82.4	82.6	82.8	83.1	83.1	83.1	83.1	83
GE 1000	75.8	77.3	80.4	81.0	82.8	83.1	83.9	84.2	84.4	84.9	84.9	84.9	84.9	84
GE 900	76.1	77.8	80.7	81.7	83.4	83.8	84.5	84.9	85.1	85.6	85.6	85.6	85.6	85
GE 800	76.8	78.4	81.5	82.3	84.3	84.7	85.4	85.8	86.0	86.6	86.6	86.6	86.6	86
GE 700	77.3	79.0	82.5	83.6	85.8	86.1	87.0	87.4	87.7	88.2	88.2	88.2	88.2	88
GE 600	77.7	79.3	82.9	84.0	86.9	87.4	88.3	89.0	89.3	89.9	90.0	90.0	90.0	90
GE 500	78.5	80.2	83.7	85.3	88.4	89.3	90.3	91.6	92.1	92.9	93.2	93.2	93.2	93
GE 400	79.0	80.9	84.9	86.3	89.6	90.6	91.7	93.3	93.9	95.0	95.3	95.3	95.3	95
GE 300	79.1	81.0	85.0	86.4	89.9	91.1	92.4	94.2	94.9	96.7	97.0	97.0	97.0	97
GE 200	79.1	81.0	85.0	86.4	89.9	91.1	92.4	94.2	95.0	96.9	97.4	97.4	97.4	98
GE 100	79.1	81.0	85.0	86.4	89.9	91.1	92.4	94.2	95.1	97.0	97.7	97.7	97.8	98
GE 000	79.1	81.0	85.0	86.4	89.9	91.1	92.4	94.2	95.1	97.0	97.7	97.8	97.8	98

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LT TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: 18-20

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
44.1	44.3	44.8	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9	44.9
49.1	49.1	49.7	50.1	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2	50.2
49.6	49.6	50.3	50.6	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7	50.7
49.7	49.7	50.4	50.3	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
50.3	50.3	51.1	51.4	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6	51.6
53.2	53.2	54.1	54.4	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6	54.6
55.2	55.2	55.1	56.4	56.6	56.6	56.7	56.7	56.7	56.7	56.7	56.7	56.7	56.7
55.7	55.7	55.6	56.9	57.0	57.0	57.1	57.1	57.1	57.1	57.1	57.1	57.1	57.1
58.2	58.2	59.1	59.4	59.6	59.7	59.9	59.9	59.9	59.9	59.9	59.9	59.9	59.9
59.2	59.2	59.1	59.4	59.6	60.7	60.9	60.9	60.9	60.9	60.9	60.9	60.9	60.9
60.4	60.4	61.4	61.8	61.9	62.0	62.2	62.6	62.6	62.6	62.6	62.6	62.6	62.6
63.5	63.5	64.6	64.9	65.0	65.1	65.3	65.7	65.7	65.7	65.7	65.7	65.7	65.7
65.4	65.4	65.4	66.3	66.9	67.0	67.2	67.6	67.6	67.6	67.6	67.6	67.6	67.6
67.7	67.7	68.3	69.1	69.4	69.6	69.8	70.1	70.1	70.1	70.1	70.1	70.1	70.1
70.2	70.2	71.3	71.7	72.0	72.1	72.3	72.7	72.7	72.7	72.7	72.7	72.7	72.7
71.5	71.5	72.7	73.0	73.3	73.4	73.7	74.0	74.0	74.0	74.0	74.0	74.0	74.0
73.0	73.0	74.1	74.4	74.6	74.9	75.1	75.4	75.4	75.4	75.4	75.4	75.4	75.4
76.2	76.2	77.3	77.7	78.1	78.2	78.4	78.8	78.8	78.8	78.8	78.8	78.8	78.8
76.5	76.5	77.3	78.1	78.5	78.7	79.0	79.2	79.2	79.2	79.2	79.2	79.2	79.2
78.2	78.2	79.5	80.1	80.6	80.7	80.9	81.2	81.2	81.2	81.2	81.2	81.2	81.2
80.0	80.0	81.7	82.0	82.4	82.6	82.8	83.1	83.1	83.1	83.1	83.1	83.1	83.1
81.0	81.0	82.8	83.1	83.9	84.2	84.4	84.9	84.9	84.9	84.9	84.9	84.9	84.9
81.7	81.7	83.4	83.8	84.5	84.9	85.1	85.6	85.6	85.6	85.6	85.6	85.6	85.6
82.3	82.3	84.3	84.7	85.4	85.8	86.0	86.6	86.6	86.6	86.6	86.6	86.6	86.6
83.6	83.6	85.3	85.1	87.0	87.4	87.7	88.2	88.2	88.2	88.2	88.2	88.2	88.2
84.0	84.0	86.9	87.4	88.3	89.0	89.3	89.9	90.0	90.0	90.0	90.0	90.0	90.0
85.3	85.3	88.4	89.3	90.3	91.6	92.1	92.9	93.2	93.2	93.2	93.2	93.2	93.2
86.3	86.3	89.6	90.6	91.7	93.3	93.9	95.0	95.3	95.3	95.3	95.4	95.4	95.6
86.4	86.4	89.9	91.1	92.4	94.2	94.9	96.7	97.0	97.0	97.0	97.1	97.1	97.2
86.4	86.4	89.9	91.1	92.4	94.2	95.0	96.9	97.4	97.6	98.0	98.1	98.1	98.6
86.4	86.4	89.9	91.1	92.4	94.2	95.1	97.0	97.7	97.8	98.4	98.7	98.9	100.0
86.4	86.4	89.9	91.1	92.4	94.2	95.1	97.0	97.7	97.8	98.4	98.7	98.9	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: SEP HOURS: 21

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	46.3	46.8	47.3	48.1	49.2	49.4	49.7	50.0	50.0	50.1	50.1	50.1
GE 20000	49.0	49.4	50.0	51.0	52.2	52.4	52.7	53.0	53.0	53.1	53.1	53.1
GE 18000	49.0	49.4	50.0	51.0	52.2	52.4	52.7	53.0	53.0	53.1	53.1	53.1
GE 16000	49.1	49.6	50.1	51.1	52.3	52.6	52.8	53.1	53.1	53.2	53.2	53.2
GE 14000	49.4	49.9	50.4	51.4	52.7	52.9	53.1	53.4	53.4	53.6	53.6	53.6
GE 12000	50.6	51.1	51.8	52.3	54.3	54.6	54.8	55.1	55.1	55.2	55.2	55.2
GE 10000	52.0	52.6	53.2	54.4	56.0	56.2	56.4	57.0	57.0	57.1	57.1	57.1
GE 9000	52.3	53.3	54.0	55.2	56.8	57.0	57.2	57.8	57.8	57.9	57.9	57.9
GE 8000	54.0	54.7	55.3	56.6	58.1	58.3	58.6	59.1	59.1	59.2	59.2	59.2
GE 7000	55.4	56.1	56.8	58.0	59.6	59.8	60.0	60.6	60.6	60.7	60.7	60.7
GE 6000	56.6	57.2	57.9	59.1	60.7	60.9	61.1	62.0	62.0	62.1	62.1	62.1
GE 5000	58.9	59.6	60.2	61.4	63.0	63.2	63.6	64.4	64.4	64.6	64.6	64.6
GE 4500	60.4	61.1	61.8	63.1	64.7	64.9	65.2	66.1	66.1	66.2	66.2	66.2
GE 4000	63.1	63.8	64.4	65.8	67.3	67.6	68.1	69.0	69.0	69.1	69.1	69.1
GE 3500	64.3	65.0	65.7	67.0	68.6	68.8	69.3	70.2	70.2	70.3	70.3	70.3
GE 3000	65.8	66.4	67.2	68.6	70.2	70.4	71.1	72.0	72.0	72.1	72.1	72.1
GE 2500	67.2	67.9	68.7	70.4	72.1	72.3	73.1	74.2	74.2	74.3	74.3	74.3
GE 2000	69.7	70.4	71.3	73.3	75.0	75.3	76.1	77.3	77.3	77.4	77.4	77.4
GE 1800	69.9	70.7	72.0	73.6	75.3	75.7	76.4	77.7	77.7	77.8	77.8	77.8
GE 1500	71.6	72.3	74.0	75.7	77.6	78.0	78.8	80.0	80.0	80.1	80.1	80.1
GE 1200	72.7	73.6	75.3	77.0	79.0	79.4	80.3	81.6	81.6	81.7	81.7	81.7
GE 1000	72.9	73.8	75.6	77.3	79.6	80.0	80.9	82.1	82.1	82.2	82.2	82.2
GE 900	73.2	74.1	76.1	78.0	80.3	80.8	81.7	82.9	82.9	83.0	83.0	83.0
GE 800	73.6	74.4	76.6	78.5	81.2	81.8	82.7	83.9	83.9	84.0	84.0	84.0
GE 700	73.7	74.6	76.8	78.9	81.9	82.4	83.3	84.8	84.8	84.9	84.9	84.9
GE 600	74.4	75.3	77.7	80.1	83.6	84.1	85.0	86.7	86.7	86.8	86.8	86.8
GE 500	75.6	76.4	79.6	82.4	86.4	87.2	88.7	90.4	90.4	90.9	90.9	90.9
GE 400	75.7	76.6	79.7	82.7	86.8	87.6	89.3	91.2	91.3	91.8	91.8	91.8
GE 300	75.7	76.6	79.9	83.0	87.6	88.8	90.8	92.8	93.1	93.7	93.9	94.0
GE 200	75.9	76.8	80.2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9
GE 100	75.9	76.8	80.2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9
GE 000	75.9	76.8	80.2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
LST TO UTC: + 5 MONTH: SEP HOURS: 21-23

VISIBILITY IN STATUTE MILES													
	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GF 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
3	48.1	49.2	49.4	49.7	50.0	50.0	50.1	50.1	50.1	50.1	50.1	50.2	50.2
0	51.0	52.2	52.4	52.7	53.0	53.0	53.1	53.1	53.1	53.1	53.1	53.2	53.2
0	51.0	52.2	52.4	52.7	53.0	53.0	53.1	53.1	53.1	53.1	53.1	53.2	53.2
1	51.1	52.3	52.6	52.8	53.1	53.1	53.2	53.2	53.2	53.2	53.2	53.3	53.3
4	51.4	52.7	52.9	53.1	53.4	53.4	53.6	53.6	53.6	53.6	53.6	53.7	53.7
5	52.8	54.3	54.6	54.8	55.1	55.1	55.2	55.2	55.2	55.2	55.2	55.3	55.3
2	54.4	56.0	56.2	56.4	57.0	57.0	57.1	57.1	57.1	57.1	57.1	57.2	57.2
0	55.2	56.8	57.0	57.2	57.8	57.8	57.9	57.9	57.9	57.9	57.9	58.0	58.0
3	56.5	59.1	58.3	59.6	59.1	59.1	59.2	59.2	59.2	59.2	59.2	59.3	59.3
8	58.0	59.6	59.8	60.0	60.6	60.6	60.7	60.7	60.7	60.7	60.7	60.8	60.8
9	59.1	60.7	60.9	61.1	62.0	62.0	62.1	62.1	62.1	62.1	62.1	62.2	62.2
2	61.4	63.0	63.2	63.6	64.4	64.4	64.6	64.6	64.6	64.6	64.6	64.7	64.7
3	63.1	64.7	64.9	65.2	66.1	66.1	66.2	66.2	66.2	66.2	66.2	66.3	66.3
4	65.8	67.3	67.6	68.1	69.0	69.0	69.1	69.1	69.1	69.1	69.1	69.2	69.2
7	67.0	68.6	68.8	69.3	70.2	70.2	70.3	70.3	70.3	70.3	70.3	70.4	70.4
4	68.5	70.2	70.4	71.1	72.0	72.0	72.1	72.1	72.1	72.1	72.1	72.2	72.2
7	70.4	72.1	72.3	73.1	74.2	74.2	74.3	74.3	74.3	74.3	74.3	74.4	74.4
8	73.3	75.0	75.3	76.1	77.3	77.3	77.4	77.4	77.4	77.4	77.4	77.6	77.6
0	73.5	75.3	75.7	76.4	77.7	77.7	77.8	77.8	77.8	77.8	77.8	77.9	77.9
0	75.7	77.6	78.0	78.8	80.0	80.0	80.1	80.1	80.1	80.1	80.1	80.2	80.2
3	77.0	79.0	79.4	80.3	81.6	81.6	81.7	81.7	81.7	81.7	81.7	81.8	81.8
5	77.3	79.6	80.0	80.9	82.1	82.1	82.2	82.2	82.2	82.2	82.2	82.3	82.3
1	78.0	80.3	80.8	81.7	82.9	82.9	83.0	83.0	83.0	83.0	83.0	83.1	83.1
5	78.5	81.2	81.8	82.7	83.9	83.9	84.0	84.0	84.0	84.0	84.0	84.1	84.1
7	78.9	81.9	82.4	83.3	84.8	84.8	84.9	84.9	84.9	84.9	84.9	85.0	85.0
7	80.1	83.6	84.1	85.0	86.7	86.7	86.8	86.8	86.8	86.8	86.8	86.9	86.9
6	82.4	86.4	87.2	88.7	90.4	90.4	90.9	90.9	90.9	90.9	91.0	91.1	91.1
7	82.7	86.8	87.5	89.3	91.2	91.3	91.8	91.8	91.8	91.8	92.0	92.1	92.1
9	83.5	87.6	88.8	90.8	92.8	93.1	93.7	93.9	94.0	94.0	94.2	94.3	94.3
2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9	96.8	97.1	97.6	97.7
2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9	96.9	97.4	98.6	99.6
2	83.3	88.0	89.7	91.8	93.8	94.3	95.1	95.7	95.9	96.9	97.6	98.8	100.0

900

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: SEP HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	39.4	39.9	40.6	40.9	41.6	41.7	42.0	42.2	42.3	42.4	42.5	42.5	42.6	
GE 20000	42.7	43.4	44.2	44.7	45.4	45.6	45.9	46.1	46.3	46.3	46.4	46.5	46.6	
GE 18000	42.9	43.6	44.4	44.9	45.7	45.9	46.1	46.4	46.5	46.6	46.7	46.7	46.8	
GE 16000	43.0	43.8	44.6	45.1	45.9	46.1	46.3	46.6	46.7	46.8	46.9	46.9	47.0	
GE 14000	43.5	44.3	45.1	45.6	46.4	46.6	46.9	47.2	47.4	47.5	47.6	47.6	47.7	
GE 12000	44.6	45.4	46.4	46.9	47.8	47.9	48.3	48.6	48.8	48.8	48.9	49.0	49.1	
GE 10000	46.4	47.3	48.4	49.0	49.8	50.0	50.3	50.7	50.9	51.0	51.1	51.1	51.3	
GE 9000	47.1	48.0	49.1	49.7	50.6	50.8	51.1	51.5	51.7	51.8	51.9	51.9	52.0	
GE 8000	49.3	50.3	51.5	52.2	53.2	53.4	53.7	54.1	54.3	54.4	54.6	54.6	54.7	
GE 7000	50.6	51.6	52.9	53.6	54.6	54.8	55.2	55.5	55.8	55.9	56.1	56.1	56.2	
GE 6000	51.5	52.5	53.8	54.5	55.7	55.9	56.2	56.7	57.0	57.1	57.3	57.3	57.4	
GE 5000	53.5	54.6	56.2	57.0	58.2	58.4	58.8	59.4	59.6	59.8	59.9	59.9	60.1	
GE 4500	55.0	56.2	57.9	58.7	59.9	60.2	60.6	61.1	61.4	61.5	61.7	61.7	61.8	
GE 4000	57.7	58.9	60.7	61.6	63.0	63.2	63.7	64.3	64.5	64.7	64.8	64.9	65.0	
GE 3500	59.2	60.5	62.3	63.2	64.6	64.9	65.3	65.9	66.2	66.3	66.5	66.5	66.6	
GE 3000	61.4	62.7	64.7	65.6	67.0	67.3	67.8	68.3	68.6	68.8	68.9	68.9	69.0	
GE 2500	63.9	65.3	67.4	68.4	69.8	70.1	70.6	71.2	71.5	71.7	71.8	71.8	71.9	
GE 2000	65.9	68.4	70.6	71.7	73.2	73.5	74.1	74.7	75.0	75.2	75.3	75.3	75.5	
GE 1800	67.4	68.8	71.1	72.2	73.8	74.1	74.7	75.3	75.6	75.7	75.9	75.9	76.0	
GE 1500	69.2	70.7	73.2	74.3	76.1	76.4	77.0	77.7	77.9	78.1	78.3	78.3	78.4	
GE 1200	70.7	72.2	74.5	75.9	77.8	78.2	78.8	79.5	79.7	79.9	80.1	80.1	80.2	
GE 1000	71.6	73.1	75.9	77.2	79.2	79.6	80.3	81.1	81.3	81.5	81.7	81.7	81.8	
GE 900	72.1	73.8	76.5	78.0	80.1	80.5	81.3	82.1	82.3	82.5	82.7	82.7	82.6	
GE 800	72.7	74.3	77.2	78.6	81.0	81.6	82.4	83.3	83.6	83.8	84.0	84.0	84.1	
GE 700	73.1	74.8	77.8	79.5	82.0	82.6	83.5	84.5	84.8	85.0	85.2	85.2	85.3	
GE 600	73.7	75.4	78.7	80.8	83.7	84.4	85.4	86.5	86.9	87.2	87.4	87.4	87.5	
GE 500	74.3	76.0	79.7	82.1	85.5	86.3	87.7	89.0	89.6	89.9	90.2	90.2	90.3	
GE 400	74.5	76.4	80.2	82.7	86.3	87.3	89.0	90.7	91.4	91.9	92.1	92.1	92.3	
GE 300	74.7	76.5	80.5	83.1	87.1	88.4	90.5	92.5	93.7	94.4	94.7	94.7	95.0	
GE 200	74.7	76.6	80.6	83.3	87.3	88.7	91.1	93.3	95.0	95.9	96.5	96.7	97.3	
GE 100	74.7	76.6	80.6	83.3	87.3	88.7	91.1	93.4	95.1	95.9	96.7	96.9	97.6	
GE 000	74.7	76.6	80.6	83.3	87.3	88.7	91.1	93.4	95.1	95.9	96.7	96.9	97.6	

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: ALL

CEILING	VISIBILITY IN STATUTE MILES											
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0.9	41.6	41.7	42.0	42.2	42.3	42.4	42.5	42.5	42.6	42.6	42.7	42.7
4.7	45.4	45.6	45.9	46.1	46.3	46.3	46.4	46.5	46.6	46.6	46.6	46.7
4.9	45.7	45.9	46.1	46.4	46.5	46.6	46.7	46.7	46.8	46.9	46.9	46.9
5.1	45.9	46.1	46.3	46.6	46.7	46.8	46.9	46.9	47.0	47.1	47.1	47.1
5.6	46.4	46.6	46.9	47.2	47.4	47.5	47.6	47.6	47.7	47.7	47.8	47.8
5.9	47.8	47.9	48.3	48.6	48.8	48.8	48.9	49.0	49.1	49.1	49.2	49.2
7.0	49.8	50.0	50.3	50.7	50.9	51.0	51.1	51.1	51.3	51.3	51.4	51.4
7.7	50.6	50.8	51.1	51.5	51.7	51.8	51.9	51.9	52.0	52.1	52.1	52.2
8.2	53.2	53.4	53.7	54.1	54.3	54.4	54.6	54.6	54.7	54.8	54.8	54.8
8.5	54.6	54.8	55.2	55.5	55.8	55.9	56.1	56.1	56.2	56.2	56.3	56.3
8.5	55.7	55.9	56.2	56.7	57.0	57.1	57.3	57.3	57.4	57.4	57.5	57.5
7.0	59.2	58.4	58.8	59.4	59.6	59.8	59.9	59.9	60.1	60.1	60.2	60.2
5.7	59.9	60.2	60.6	61.1	61.4	61.5	61.7	61.7	61.8	61.9	61.9	62.0
1.5	63.0	63.2	63.7	64.3	64.5	64.7	64.8	64.9	65.0	65.0	65.1	65.1
3.2	64.6	64.9	65.3	65.9	66.2	66.3	66.5	66.5	66.6	66.7	66.7	66.8
5.5	67.0	67.3	67.8	68.3	68.6	68.8	68.9	68.9	69.0	69.1	69.2	69.2
4	69.8	70.1	70.6	71.2	71.5	71.7	71.8	71.8	71.9	72.0	72.1	72.1
1.7	73.2	73.5	74.1	74.7	75.0	75.2	75.3	75.3	75.5	75.5	75.6	75.6
3.2	73.8	74.1	74.7	75.3	75.6	75.7	75.9	75.9	76.0	76.1	76.2	76.2
4.3	76.1	76.4	77.0	77.7	77.9	78.1	78.3	78.3	78.4	78.5	78.5	78.6
5.9	77.8	78.2	78.8	79.5	79.7	79.9	80.1	80.1	80.2	80.3	80.3	80.3
7.2	79.2	79.6	80.3	81.1	81.3	81.5	81.7	81.7	81.8	81.9	81.9	82.0
7.0	80.1	80.5	81.3	82.1	82.3	82.5	82.7	82.7	82.8	82.9	82.9	83.0
7.5	81.0	81.6	82.4	83.3	83.6	83.8	84.0	84.0	84.1	84.2	84.2	84.3
7.5	82.0	82.6	83.5	84.5	84.8	85.0	85.2	85.2	85.3	85.4	85.5	85.5
7.8	83.7	84.4	85.4	86.5	86.9	87.2	87.4	87.4	87.5	87.6	87.6	87.7
7.1	85.5	86.3	87.7	89.0	89.6	89.9	90.2	90.2	90.3	90.4	90.5	90.5
7.7	85.3	87.3	89.0	90.7	91.4	91.9	92.1	92.1	92.3	92.4	92.5	92.6
7.1	87.1	88.4	90.5	92.5	93.7	94.4	94.7	94.7	95.0	95.2	95.3	95.5
7.3	87.3	88.7	91.1	93.3	95.0	95.9	96.5	96.7	97.3	97.6	98.0	98.5
7.3	87.3	88.7	91.1	93.4	95.1	95.9	96.7	96.9	97.6	98.0	98.6	99.7
7.3	87.3	88.7	91.1	93.4	95.1	95.9	96.7	96.9	97.6	98.0	98.6	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: OCT HOURS: 00-02

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	32.8	33.0	33.8	33.9	35.1	35.2	35.5	35.8	36.0	36.1	36.2	36.2	36.5	
GE 20000	35.5	35.7	36.5	36.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	
GE 18000	35.5	35.7	36.5	36.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	
GE 16000	35.5	35.7	36.5	36.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	
GE 14000	36.6	36.8	37.5	37.6	38.3	38.9	39.2	39.6	39.8	39.9	40.0	40.0	40.2	
GE 12000	37.3	38.1	38.8	38.9	40.1	40.3	40.6	41.1	41.3	41.4	41.5	41.5	41.7	
GE 10000	39.6	39.8	40.5	40.6	41.8	42.0	42.4	42.8	43.0	43.1	43.2	43.2	43.4	
GF 9000	40.0	40.2	41.0	41.1	42.3	42.5	42.8	43.2	43.4	43.5	43.7	43.7	43.9	
GE 8000	42.2	42.4	43.1	43.2	44.4	44.6	44.9	45.4	45.6	45.7	45.8	45.8	46.0	
GE 7000	43.8	44.0	44.7	44.8	46.0	46.2	46.6	47.0	47.2	47.3	47.4	47.4	47.6	
GE 6000	45.1	45.3	46.0	46.1	47.3	47.5	47.8	48.3	48.5	48.6	48.7	48.7	48.9	
GE 5000	47.1	47.3	48.1	48.3	49.5	49.7	50.2	50.6	50.9	51.0	51.1	51.1	51.3	
GF 4500	50.4	50.6	51.5	51.8	53.1	53.3	53.9	54.3	54.5	54.6	54.7	54.7	54.9	
GE 4000	55.6	55.8	56.7	57.0	58.4	58.6	59.1	59.6	59.8	59.9	60.0	60.0	60.2	
GE 3500	58.8	59.0	59.9	60.2	61.6	61.8	62.4	62.8	63.0	63.1	63.2	63.2	63.4	
GE 3000	61.6	61.8	62.8	63.2	64.8	65.1	65.6	66.0	66.2	66.3	66.5	66.5	66.7	
GE 2500	63.8	64.0	64.9	65.4	67.1	67.5	68.3	68.7	68.9	69.0	69.1	69.1	69.4	
GE 2000	67.5	67.8	68.9	69.4	71.2	71.7	72.5	72.9	73.1	73.2	73.3	73.3	73.5	
GE 1800	68.9	69.2	70.5	71.0	72.8	73.3	74.1	74.5	74.7	74.8	74.9	74.9	75.2	
GE 1500	71.1	71.4	73.1	73.7	75.6	76.1	76.9	77.3	77.5	77.6	77.7	77.7	78.0	
GE 1200	72.3	72.8	74.9	75.9	78.0	78.5	79.2	79.7	80.0	80.2	80.3	80.3	80.5	
GE 1000	73.7	74.3	76.9	78.1	80.3	81.0	81.8	82.3	82.7	82.9	83.0	83.0	83.2	
GE 900	74.4	75.1	77.6	78.8	81.6	82.3	83.1	83.5	84.0	84.3	84.5	84.5	84.7	
GF 800	75.6	76.2	79.0	80.3	83.4	84.1	84.9	85.4	85.8	86.5	86.8	86.8	87.1	
GE 700	75.9	76.6	80.1	81.4	84.6	85.5	86.6	87.0	87.4	88.1	88.4	88.4	88.7	
GE 600	77.0	77.6	81.2	82.5	85.8	86.9	88.1	88.5	88.9	89.6	90.0	90.0	90.3	
GF 500	77.3	78.0	81.6	83.3	86.8	88.2	89.4	90.0	90.4	91.1	91.5	91.5	91.8	
GE 400	77.3	78.0	81.6	83.3	86.9	88.7	90.6	91.8	92.5	93.3	93.8	93.8	94.1	
GE 300	77.4	78.1	81.7	83.4	87.1	89.0	91.1	92.6	93.8	94.7	95.2	95.2	95.5	
GE 200	77.5	78.2	81.8	83.5	87.2	89.1	92.0	93.8	95.1	96.3	96.9	96.9	97.5	
GE 100	77.5	78.2	81.8	83.5	87.2	89.1	92.0	93.8	95.2	96.5	97.0	97.1	97.7	
GE 000	77.5	78.2	81.8	83.5	87.2	89.1	92.0	93.8	95.2	96.5	97.0	97.1	97.7	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT HOURS: 00-02

VISIBILITY IN STATUTE MILES

4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
33.9	35.1	35.2	35.5	35.8	36.0	36.1	36.2	36.2	36.5	36.5	36.6	36.8
36.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	39.1	39.2	39.5
35.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	39.1	39.2	39.5
36.6	37.7	37.8	38.2	38.5	38.7	38.8	38.9	38.9	39.1	39.1	39.2	39.5
37.6	38.3	38.9	39.2	39.6	39.8	39.9	40.0	40.0	40.2	40.2	40.3	40.5
38.9	40.1	40.3	40.6	41.1	41.3	41.4	41.5	41.5	41.7	41.7	41.8	42.0
40.6	41.8	42.0	42.4	42.8	43.0	43.1	43.2	43.2	43.4	43.4	43.5	43.8
41.1	42.3	42.5	42.9	43.2	43.4	43.5	43.7	43.7	43.9	43.9	44.0	44.2
43.2	44.4	44.6	44.9	45.4	45.6	45.7	45.8	45.8	46.0	46.0	46.1	46.3
44.3	46.0	46.2	46.6	47.0	47.2	47.3	47.4	47.4	47.6	47.6	47.7	48.0
46.1	47.3	47.5	47.8	48.3	48.5	48.6	48.7	48.7	48.9	48.9	49.0	49.2
48.3	49.5	49.7	50.2	50.6	50.9	51.0	51.1	51.1	51.3	51.3	51.4	51.6
51.8	53.1	53.3	53.9	54.3	54.5	54.6	54.7	54.7	54.9	54.9	55.1	55.3
57.0	58.4	58.6	59.1	59.6	59.8	59.9	60.0	60.0	60.2	60.2	60.3	60.5
60.2	61.6	61.8	62.4	62.8	63.0	63.1	63.2	63.2	63.4	63.4	63.5	63.8
63.2	64.8	65.1	65.6	66.0	66.2	66.3	66.5	66.5	66.7	66.7	66.8	67.0
69.4	71.2	71.7	72.5	72.9	73.1	73.2	73.3	73.3	73.5	73.5	73.7	73.9
71.0	72.8	73.3	74.1	74.5	74.7	74.8	74.9	74.9	75.2	75.2	75.3	75.5
73.7	75.6	76.1	76.9	77.3	77.5	77.6	77.7	77.7	78.0	78.0	78.1	78.3
75.9	78.0	78.5	79.2	79.7	80.0	80.2	80.3	80.3	80.5	80.5	80.6	80.9
83.1	80.3	81.0	81.8	82.3	82.7	82.9	83.0	83.0	83.2	83.2	83.3	83.5
84.8	81.6	82.3	83.1	83.5	84.0	84.3	84.5	84.5	84.7	84.7	84.8	85.1
80.3	83.4	84.1	84.9	85.4	85.8	86.5	86.8	86.8	87.1	87.1	87.2	87.4
81.4	84.6	85.5	86.6	87.0	87.4	88.1	88.4	88.4	88.7	88.7	88.8	89.0
82.5	85.8	86.9	88.1	88.5	88.9	89.6	90.0	90.0	90.3	90.3	90.4	90.6
93.3	86.8	88.2	89.4	90.0	90.4	91.1	91.5	91.5	91.8	91.8	91.9	92.2
93.3	85.9	88.7	90.6	91.8	92.5	93.3	93.8	93.8	94.1	94.1	94.4	94.6
93.4	87.1	89.0	91.1	92.6	93.8	94.7	95.2	95.2	95.5	95.6	96.0	96.2
93.5	87.2	89.1	92.0	93.8	95.1	96.3	96.9	96.9	97.5	97.7	98.2	98.7
93.5	87.2	89.1	92.0	93.8	95.2	96.5	97.0	97.1	97.7	98.0	98.6	99.9
93.5	87.2	89.1	92.0	93.8	95.2	96.5	97.0	97.1	97.7	98.0	98.6	100.0

930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: ALL
MONTH: OCT HOURS: 0

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	29.7	30.0	30.4	31.1	32.0	32.0	32.8	33.1	33.2	33.7	33.9	34.0
GE 20000	31.3	31.6	32.0	32.7	33.8	33.8	34.5	34.8	34.9	35.4	35.6	35.7
GE 18000	31.5	31.8	32.3	32.9	34.0	34.0	34.7	35.1	35.2	35.6	35.8	35.9
GE 16000	31.6	31.9	32.4	33.0	34.1	34.1	34.8	35.2	35.3	35.7	35.9	36.0
GE 14000	32.7	33.0	33.4	34.1	35.2	35.2	35.9	36.2	36.3	36.8	37.0	37.1
GE 12000	34.6	34.9	35.4	36.0	37.1	37.1	37.8	38.2	38.3	38.7	38.9	39.0
GE 10000	37.0	37.3	37.8	38.5	39.7	39.7	40.4	40.8	40.9	41.3	41.5	41.6
GE 9000	37.3	37.6	38.2	38.9	40.0	40.0	40.8	41.1	41.2	41.6	41.8	41.9
GE 8000	38.9	39.4	39.9	40.8	41.8	41.8	42.5	42.9	43.0	43.4	43.7	43.8
GE 7000	39.8	40.2	40.8	41.6	42.7	42.7	43.4	43.8	43.9	44.3	44.5	44.6
GE 6000	40.6	41.1	41.6	42.5	43.5	43.5	44.3	44.6	44.7	45.2	45.4	45.5
GE 5000	43.9	44.3	44.8	45.7	46.8	46.8	47.5	47.8	48.0	48.4	48.6	48.7
GE 4500	45.9	46.3	46.9	47.7	48.9	48.9	49.8	50.2	50.3	50.8	51.0	51.1
GE 4000	50.9	51.3	51.9	52.9	54.2	54.2	55.1	55.5	55.6	56.0	56.2	56.3
GE 3500	53.7	54.1	54.7	55.7	57.0	57.0	57.8	58.3	58.4	58.8	59.0	59.1
GE 3000	56.6	57.1	57.8	58.9	60.2	60.2	61.1	61.5	61.6	62.0	62.3	62.4
GE 2500	59.4	59.9	60.6	61.8	63.1	63.3	64.2	64.6	64.7	65.2	65.4	65.5
GE 2000	64.2	64.7	65.6	67.0	68.3	68.5	69.5	69.9	70.0	70.4	70.6	70.8
GE 1900	65.1	65.6	66.5	67.8	69.1	69.7	70.6	71.2	71.3	71.7	71.9	72.0
GE 1500	67.5	68.1	69.2	70.6	72.3	72.9	73.9	74.5	74.6	75.1	75.3	75.4
GE 1200	68.6	69.1	70.5	72.4	74.1	74.7	75.7	76.3	76.5	76.9	77.1	77.2
GE 1000	69.8	70.3	72.0	74.2	76.3	77.0	78.2	78.9	78.9	79.4	79.6	79.7
GE 900	70.9	71.4	73.1	75.5	77.7	78.5	79.7	80.3	80.4	80.9	81.3	81.4
GE 800	71.7	72.4	74.4	77.0	79.7	80.4	81.7	82.4	82.6	83.2	83.7	83.8
GE 700	72.6	73.2	75.4	78.3	81.4	82.4	83.8	84.5	84.7	85.4	85.6	85.9
GE 600	73.1	73.8	75.9	78.9	82.4	83.4	85.2	85.9	86.1	86.8	87.2	87.3
GE 500	73.7	74.3	76.5	79.6	84.0	85.4	87.3	88.4	88.6	89.4	89.8	89.9
GE 400	73.9	74.5	76.7	80.0	84.9	86.3	88.6	90.1	90.9	91.7	92.2	92.3
GE 300	74.1	74.7	77.1	80.4	85.9	87.3	89.8	91.6	92.6	93.8	94.2	94.3
GE 200	74.2	74.8	77.2	80.6	86.2	87.6	90.4	92.4	93.7	95.3	95.8	96.0
GE 100	74.2	74.8	77.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2
GE 000	74.2	74.8	77.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 89
MONTH: OCT HOURS: 03-05

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0.4	31.1	32.0	32.0	32.8	33.1	33.2	33.7	33.9	34.0	34.3	34.4	34.6	34.7
0.0	32.7	33.8	33.8	34.5	34.8	34.9	35.4	35.6	35.7	36.0	36.1	36.3	36.5
0.3	32.9	34.0	34.0	34.7	35.1	35.2	35.6	35.8	35.9	36.2	36.3	36.6	36.7
0.4	33.0	34.1	34.1	34.8	35.2	35.3	35.7	35.9	36.0	36.3	36.5	36.7	36.8
0.4	34.1	35.2	35.2	35.9	36.2	36.3	36.8	37.0	37.1	37.4	37.5	37.7	37.8
0.4	36.0	37.1	37.1	37.8	38.2	38.3	38.7	38.9	39.0	39.4	39.5	39.7	39.8
0.3	38.6	39.7	39.7	40.4	40.8	40.9	41.3	41.5	41.6	41.9	42.0	42.3	42.4
0.2	38.9	40.0	40.0	40.8	41.1	41.2	41.6	41.8	41.9	42.3	42.4	42.6	42.7
0.3	40.8	41.8	41.8	42.5	42.9	43.0	43.4	43.7	43.8	44.1	44.2	44.4	44.5
0.3	41.6	42.7	42.7	43.4	43.8	43.9	44.3	44.5	44.6	44.9	45.1	45.3	45.4
0.0	42.5	43.5	43.5	44.3	44.6	44.7	45.2	45.4	45.5	45.8	45.9	46.1	46.2
0.3	45.7	46.8	46.8	47.5	47.8	48.0	48.4	48.6	48.7	49.0	49.1	49.4	49.5
0.2	47.7	48.9	48.9	49.8	50.2	50.3	50.8	51.0	51.1	51.4	51.5	51.7	51.8
0.7	52.9	54.2	54.2	55.1	55.5	55.6	56.0	56.2	56.3	56.7	56.9	57.0	57.1
0.7	55.7	57.0	57.0	57.8	58.3	58.4	58.8	59.0	59.1	59.5	59.6	59.8	59.9
0.2	58.9	60.2	60.2	61.1	61.5	61.6	62.0	62.3	62.4	62.7	62.8	63.0	63.1
0.6	61.3	63.1	63.3	64.2	64.6	64.7	65.2	65.4	65.5	65.8	65.9	66.1	66.2
0.6	67.0	68.3	68.5	69.5	69.9	70.0	70.4	70.6	70.8	71.1	71.2	71.4	71.5
0.5	67.8	69.1	69.7	70.6	71.2	71.3	71.7	71.9	72.0	72.4	72.5	72.7	72.8
0.2	70.6	72.3	72.9	73.9	74.7	74.6	75.1	75.3	75.4	75.7	75.8	76.0	76.1
0.5	72.4	74.1	74.7	75.7	76.3	76.5	76.9	77.1	77.2	77.5	77.6	77.8	78.0
0.0	74.2	76.3	77.0	78.2	78.8	78.9	79.4	79.6	79.7	80.0	80.1	80.3	80.4
0.1	75.5	77.7	78.5	79.7	80.3	80.4	80.9	81.3	81.4	81.7	81.8	82.2	82.3
0.4	77.0	79.7	80.4	81.7	82.4	82.6	83.2	83.7	83.8	84.2	84.3	84.6	84.7
0.4	78.3	81.4	82.4	83.8	84.5	84.7	85.4	85.8	85.9	86.3	86.5	86.8	86.9
0.9	78.9	82.4	83.4	85.2	85.9	86.1	86.8	87.2	87.3	87.7	87.8	88.2	88.3
0.5	79.6	84.0	85.4	87.3	88.4	88.6	89.4	89.8	89.9	90.3	90.4	90.8	90.9
0.7	80.0	84.9	86.3	88.6	90.1	90.9	91.7	92.2	92.3	92.9	93.0	93.3	93.4
0.1	80.4	85.9	87.3	89.8	91.6	92.6	93.8	94.2	94.3	95.1	95.2	95.6	95.7
0.2	80.6	86.2	87.6	90.4	92.4	93.7	95.3	95.8	96.0	97.7	97.8	98.7	99.1
0.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2	98.0	98.1	99.1	100.0
0.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2	98.0	98.1	99.1	100.0
0.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2	98.0	98.1	99.1	100.0
0.2	80.6	86.2	87.6	90.4	92.4	93.7	95.4	96.0	96.2	98.0	98.1	99.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VIS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: OCT HOURS: 06

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	27.8	28.0	28.8	29.5	30.6	30.8	31.1	31.9	32.3	32.5	32.6	32.7
GE 20000	30.5	30.6	31.5	32.2	33.3	33.4	33.8	34.6	34.9	35.2	35.3	35.4
GE 18000	30.9	30.9	31.7	32.4	33.7	33.8	34.1	34.9	35.3	35.5	35.6	35.7
GE 16000	30.9	31.0	31.8	32.5	33.8	33.9	34.2	35.1	35.4	35.6	35.7	35.8
GE 14000	31.4	31.5	32.4	33.0	34.3	34.4	34.7	35.6	35.9	36.1	36.2	36.3
GE 12000	32.3	32.4	33.2	33.9	35.2	35.3	35.6	36.5	36.8	37.0	37.1	37.2
GE 10000	34.7	34.8	35.7	36.3	37.6	37.7	38.1	38.9	39.2	39.5	39.6	39.7
GE 9000	35.1	35.2	36.0	36.8	38.1	38.2	38.7	39.6	39.9	40.1	40.2	40.3
GE 8000	36.7	36.8	37.7	38.5	39.8	40.1	40.6	41.5	41.8	42.0	42.2	42.3
GE 7000	37.5	37.6	38.7	39.5	40.9	41.2	41.7	42.6	42.9	43.1	43.2	43.3
GE 6000	38.4	38.5	39.6	40.3	41.7	42.0	42.6	43.4	43.8	44.0	44.1	44.2
GE 5000	41.1	41.2	42.3	43.0	44.6	44.9	45.5	46.6	47.0	47.3	47.4	47.5
GF 4500	43.1	43.2	44.3	45.1	46.7	47.0	47.5	48.7	49.1	49.5	49.7	49.8
GF 4000	46.5	46.7	47.8	48.6	50.4	50.8	51.3	52.5	53.0	53.3	53.5	53.7
GE 3500	48.6	48.7	49.9	50.6	52.5	52.8	53.4	54.7	55.3	55.6	55.8	55.9
GE 3000	53.2	53.3	54.6	55.4	57.3	57.6	58.3	59.6	60.1	60.4	60.6	60.8
GE 2500	56.2	56.3	57.6	58.6	60.5	60.9	61.7	63.0	63.5	63.9	64.1	64.2
GE 2000	60.0	60.1	61.7	62.7	64.8	65.2	66.1	67.4	68.0	68.3	68.5	68.6
GE 1800	61.4	61.5	63.1	64.1	66.2	66.6	67.5	68.8	69.4	69.7	69.9	70.0
GE 1500	64.4	64.6	66.5	67.6	70.0	70.3	71.3	72.6	73.1	73.4	73.7	73.8
GE 1200	66.1	66.3	68.6	70.2	72.7	73.0	74.1	75.4	75.9	76.2	76.5	76.6
GE 1000	67.3	67.7	70.0	71.7	74.5	74.8	76.0	77.3	78.0	78.3	78.5	78.6
GF 900	67.8	68.3	71.2	73.1	75.9	76.5	77.7	79.0	79.7	80.0	80.2	80.3
GE 800	69.1	69.6	72.7	74.7	78.3	78.8	80.2	81.5	82.2	82.6	82.9	83.0
GE 700	69.5	69.9	73.3	75.5	79.2	79.8	81.3	82.9	83.8	84.4	84.7	84.8
GE 600	69.5	69.9	73.3	75.6	80.0	80.6	82.4	84.3	85.4	86.0	86.3	86.5
GE 500	69.7	70.1	73.7	75.9	81.4	82.2	84.2	86.5	88.2	88.8	89.1	89.2
GE 400	70.0	70.5	74.1	76.3	81.9	82.8	85.1	87.5	89.8	90.4	90.8	90.9
GE 300	70.0	70.8	74.5	77.1	83.1	84.0	86.7	89.7	92.2	92.9	93.3	93.4
GE 200	70.0	70.8	74.5	77.1	83.1	84.1	87.0	90.1	92.8	93.7	94.2	94.4
GE 100	70.0	70.8	74.5	77.1	83.2	84.2	87.2	90.3	93.0	93.9	94.4	94.6
GE 000	70.0	70.8	74.5	77.1	83.2	84.2	87.2	90.3	93.0	93.9	94.4	94.6

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT HOURS: 06-08

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
29.5	30.6	30.8	31.1	31.9	32.3	32.5	32.6	32.7	32.8	32.9	33.3	33.9	
32.2	33.3	33.4	33.8	34.6	34.9	35.2	35.3	35.4	35.5	35.6	36.1	36.8	
32.4	33.7	33.8	34.1	34.9	35.3	35.5	35.6	35.7	35.8	35.9	36.5	37.1	
32.5	33.8	33.9	34.2	35.1	35.4	35.6	35.7	35.8	35.9	36.0	36.6	37.2	
33.0	34.3	34.4	34.7	35.6	35.9	36.1	36.2	36.3	36.5	36.6	37.1	37.7	
33.9	35.2	35.3	35.6	36.5	36.8	37.0	37.1	37.2	37.3	37.4	38.0	38.6	
36.3	37.6	37.7	38.1	38.9	39.2	39.5	39.6	39.7	39.8	39.9	40.5	41.2	
36.8	38.1	38.2	38.7	39.6	39.9	40.1	40.2	40.3	40.4	40.5	41.2	41.8	
38.5	39.8	40.1	40.6	41.5	41.8	42.0	42.2	42.3	42.4	42.5	43.1	43.8	
39.5	40.9	41.2	41.7	42.6	42.9	43.1	43.2	43.3	43.4	43.5	44.2	44.8	
40.3	41.7	42.0	42.6	43.4	43.8	44.0	44.1	44.2	44.3	44.4	45.1	45.7	
43.0	44.6	44.9	45.5	46.6	47.0	47.3	47.4	47.5	47.6	47.7	48.4	49.0	
45.1	46.7	47.0	47.5	48.7	49.1	49.5	49.7	49.8	49.9	50.0	50.6	51.3	
48.6	50.4	50.8	51.3	52.5	53.0	53.3	53.5	53.7	53.8	53.9	54.5	55.2	
50.6	52.5	52.8	53.4	54.7	55.3	55.6	55.8	55.9	56.0	56.1	56.8	57.4	
55.4	57.3	57.6	58.3	59.6	60.1	60.4	60.6	60.8	61.0	61.1	61.7	62.4	
53.6	60.5	60.9	61.7	63.0	63.5	63.9	64.1	64.2	64.4	64.5	65.2	65.8	
62.7	64.8	65.2	66.1	67.4	68.0	68.3	68.5	68.6	68.8	68.9	69.6	70.2	
64.1	66.2	66.6	67.5	68.8	69.4	69.7	69.9	70.0	70.2	70.3	71.0	71.6	
67.6	70.0	70.3	71.3	72.6	73.1	73.4	73.7	73.8	74.0	74.1	74.7	75.4	
70.2	72.7	73.0	74.1	75.4	75.9	76.2	76.5	76.6	76.8	76.9	77.5	78.2	
71.7	74.5	74.8	76.0	77.3	78.0	78.3	78.5	78.6	78.8	78.9	79.6	80.2	
73.1	75.9	76.5	77.7	79.0	79.7	80.0	80.2	80.3	80.5	80.6	81.3	81.9	
74.7	73.3	78.8	80.2	81.5	82.7	82.6	82.9	83.0	83.2	83.3	84.0	84.6	
75.5	79.2	79.8	81.3	82.9	83.8	84.4	84.7	84.8	85.1	85.2	85.8	86.5	
75.6	80.0	80.6	82.4	84.3	85.4	86.0	86.3	86.5	86.7	86.8	87.4	88.1	
75.9	81.4	82.2	84.2	86.5	88.2	88.8	89.1	89.2	89.5	89.6	90.2	90.9	
76.3	81.9	82.8	85.1	87.5	89.8	90.4	90.8	90.9	91.3	91.4	92.0	92.7	
77.1	83.1	84.0	86.7	89.7	92.2	92.9	93.3	93.4	94.1	94.4	95.4	96.5	
77.1	83.1	84.1	87.0	90.1	92.8	93.7	94.2	94.4	95.7	96.1	97.3	98.7	
77.1	83.2	84.2	87.2	90.3	93.0	93.9	94.4	94.6	96.0	96.5	97.6	99.7	
77.1	83.2	84.2	87.2	90.3	93.0	93.9	94.4	94.6	96.0	96.5	97.6	100.0	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: OCT HOURS

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	28.8	28.9	29.5	30.4	30.5	31.0	31.1	31.2	31.2	31.2	31.2	31.0
GF 20000	31.9	32.2	32.7	33.7	33.8	34.2	34.3	34.4	34.4	34.4	34.4	34.0
GE 18000	32.3	32.5	33.1	34.1	34.2	34.6	34.7	34.8	34.8	34.8	34.8	34.0
GE 16000	32.6	32.8	33.4	34.4	34.5	34.9	35.1	35.2	35.2	35.2	35.2	35.0
GE 14000	32.7	32.9	33.5	34.5	34.6	35.1	35.2	35.2	35.3	35.3	35.3	35.0
GE 12000	34.3	34.5	35.2	36.1	36.2	36.7	36.8	36.9	36.9	36.9	36.9	36.0
GE 10000	37.7	38.1	38.8	39.9	40.0	40.4	40.5	40.6	40.6	40.6	40.6	40.0
GE 9000	38.6	38.9	39.7	40.8	40.9	41.3	41.5	41.6	41.6	41.6	41.6	41.0
GE 8000	39.7	40.1	40.9	41.9	42.0	42.5	42.7	43.0	43.0	43.0	43.0	43.0
GE 7000	40.8	41.2	41.9	43.0	43.1	43.5	43.8	44.1	44.1	44.1	44.1	44.0
GE 6000	41.8	42.3	43.1	44.3	44.4	44.8	45.1	45.4	45.4	45.4	45.4	45.0
GF 5000	45.6	46.0	46.9	48.1	48.2	48.6	48.8	49.1	49.2	49.5	49.5	49.0
GE 4500	46.3	46.8	47.6	48.8	48.9	49.4	49.6	49.9	50.0	50.2	50.2	50.0
GE 4000	48.4	48.9	50.2	51.5	51.6	52.2	52.4	52.7	52.8	53.1	53.1	53.0
GE 3500	49.6	50.1	51.4	52.7	52.8	53.3	53.8	54.1	54.2	54.5	54.5	54.0
GE 3000	54.4	54.9	56.3	57.6	57.8	58.4	58.8	59.1	59.2	59.6	59.6	59.0
GE 2500	57.6	58.3	59.7	61.0	61.2	61.8	62.3	62.6	62.7	63.0	63.0	63.0
GE 2000	61.9	62.7	64.2	65.5	65.8	66.5	66.9	67.3	67.4	67.7	67.7	67.0
GE 1800	64.0	64.7	66.3	67.6	68.0	68.6	69.0	69.5	69.6	69.9	69.9	69.0
GE 1500	66.9	68.0	70.0	71.5	71.9	72.7	73.1	73.5	73.8	74.1	74.1	74.0
GE 1200	69.6	70.6	73.0	74.6	75.2	76.1	76.7	77.1	77.3	77.6	77.6	77.0
GE 1000	70.9	72.0	74.7	76.5	77.2	78.3	78.8	79.2	79.6	79.9	79.9	79.0
GE 900	71.7	73.0	76.1	78.1	78.9	80.0	80.6	81.1	81.5	81.8	81.8	81.0
GE 800	72.5	73.8	76.9	78.8	79.7	81.0	81.7	82.5	82.9	83.2	83.2	83.0
GE 700	73.0	74.3	77.4	79.5	80.3	81.9	82.8	84.0	84.4	84.7	84.7	84.0
GE 600	73.3	74.7	78.1	80.1	82.2	83.8	84.9	86.6	87.0	87.3	87.3	87.0
GF 500	73.9	75.4	79.0	81.2	83.7	85.4	86.9	89.6	90.3	90.9	90.9	90.0
GE 400	74.1	75.6	79.4	81.7	84.4	86.2	88.2	91.2	92.2	92.8	92.9	93.0
GE 300	74.2	75.8	79.8	82.3	85.5	87.4	89.9	93.1	94.6	95.4	95.9	96.0
GE 200	74.2	75.8	79.8	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.3	96.0
GE 100	74.2	75.8	79.8	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.5	96.0
GE 000	74.2	75.8	79.8	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.5	96.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC: + 5 MONTH: OCT HOURS: 09-11

CEILING FEET	VISIBILITY IN STATUTE MILES													
	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
1	30.4	30.5	31.0	31.1	31.2	31.2	31.2	31.2	31.2	31.2	31.2	31.3	31.5	31.7
2	33.7	33.8	34.2	34.3	34.4	34.4	34.4	34.4	34.4	34.4	34.4	34.5	34.7	34.9
3	34.1	34.2	34.6	34.7	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.9	35.2	35.4
4	34.4	34.5	34.9	35.1	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.3	35.5	35.7
5	34.5	34.6	35.1	35.2	35.3	35.3	35.3	35.3	35.3	35.3	35.3	35.4	35.6	35.8
6	36.1	36.2	36.7	36.8	36.9	36.9	36.9	36.9	36.9	36.9	36.9	37.0	37.2	37.4
7	39.9	40.0	40.4	40.5	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.8	41.0	41.2
8	40.5	40.9	41.3	41.5	41.6	41.6	41.6	41.6	41.6	41.6	41.6	41.7	41.9	42.2
9	41.9	42.0	42.5	42.7	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.1	43.3	43.5
10	43.0	43.1	43.5	43.8	44.1	44.1	44.1	44.1	44.1	44.1	44.1	44.2	44.4	44.6
12	44.3	44.4	44.8	45.1	45.4	45.4	45.4	45.4	45.4	45.4	45.4	45.5	45.7	45.9
14	48.1	48.2	48.6	48.8	49.1	49.2	49.5	49.5	49.5	49.5	49.5	49.6	49.8	50.0
16	48.3	48.9	49.4	49.6	49.9	50.0	50.2	50.2	50.2	50.2	50.2	50.3	50.5	50.8
18	51.5	51.6	52.2	52.4	52.7	52.8	53.1	53.1	53.1	53.1	53.1	53.2	53.4	53.7
20	52.7	52.8	53.3	53.8	54.1	54.2	54.5	54.5	54.5	54.5	54.5	54.6	54.8	55.1
22	57.6	57.8	58.4	58.8	59.1	59.2	59.6	59.6	59.6	59.6	59.6	59.7	59.9	60.1
24	61.0	61.2	61.8	62.3	62.6	62.7	63.0	63.0	63.0	63.0	63.0	63.1	63.3	63.5
26	65.5	65.8	66.5	66.9	67.3	67.4	67.7	67.7	67.7	67.7	67.7	67.8	68.1	68.3
28	67.5	68.0	68.6	69.0	69.5	69.6	69.9	69.9	69.9	69.9	69.9	70.0	70.2	70.4
30	71.5	71.9	72.7	73.1	73.5	73.8	74.1	74.1	74.1	74.1	74.1	74.2	74.4	74.6
32	74.6	75.2	76.1	76.7	77.1	77.3	77.6	77.6	77.6	77.6	77.6	77.7	78.0	78.2
34	76.5	77.2	78.3	78.8	79.2	79.6	79.9	79.9	79.9	79.9	79.9	80.0	80.2	80.4
36	78.1	78.9	80.0	80.6	81.1	81.5	81.8	81.8	81.8	81.8	81.8	81.9	82.2	82.4
38	78.8	79.7	81.0	81.7	82.5	82.9	83.2	83.2	83.2	83.2	83.2	83.3	83.5	83.8
40	79.5	80.3	81.9	82.8	84.0	84.4	84.7	84.7	84.7	84.7	84.7	84.8	85.1	85.3
42	80.1	82.2	83.8	84.9	86.6	87.0	87.3	87.3	87.3	87.3	87.3	87.4	87.6	87.8
44	81.2	83.7	85.4	86.9	89.6	90.3	90.9	90.9	90.9	90.9	90.9	91.0	91.2	91.4
46	81.7	84.4	86.2	88.2	91.2	92.2	92.8	92.8	92.8	93.0	93.1	93.3	93.7	93.9
48	82.3	85.5	87.4	89.9	93.1	94.6	95.4	95.4	95.4	96.1	96.5	96.8	97.1	97.6
50	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.3	96.8	97.2	97.7	98.6	99.4	99.6
52	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.5	96.9	97.3	97.8	98.7	99.7	99.9
54	82.3	85.5	87.5	90.1	93.3	95.1	95.8	96.5	96.9	97.3	97.8	98.8	100.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD:
MONTH: OCT HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GF 2 1/2	GE 2	GF 1 1/2	GE 1 1/4	GF 1	GE 3/4	GF 5/8
NO CEIL	31.3	31.3	31.4	31.4	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
GE 20000	33.2	33.2	33.4	33.4	33.5	33.5	33.5	33.5	33.5	33.5	33.5	33.5
GF 14000	33.4	33.4	33.5	33.5	33.7	33.7	33.7	33.7	33.7	33.7	33.7	33.7
GF 16000	33.7	33.7	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9	33.9
GE 14000	39.0	39.0	39.5	39.5	39.5	39.6	39.5	39.6	39.6	39.6	39.6	39.6
GE 12000	40.2	40.2	40.6	40.6	40.3	40.8	40.8	40.8	40.8	40.8	40.8	40.8
GE 10000	41.9	41.9	42.4	42.4	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
GF 9000	42.3	42.5	43.2	43.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
GF 9000	43.4	43.6	44.3	44.3	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4
GE 7000	44.5	44.5	45.2	45.2	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
GE 5000	45.4	45.4	46.0	46.0	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1
GE 5000	47.5	47.5	48.2	48.3	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6
GF 4500	48.3	48.3	49.5	49.5	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
GF 4000	51.6	51.6	52.3	52.3	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9
GE 3500	53.0	53.2	54.0	54.2	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7
GE 3000	58.5	58.7	59.5	59.7	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2
GE 2500	62.3	63.0	63.3	64.0	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5
GF 2000	68.9	69.1	69.9	70.3	71.1	71.3	71.3	71.3	71.3	71.3	71.3	71.3
GF 1800	70.4	70.6	71.4	71.8	72.8	73.0	73.0	73.0	73.0	73.0	73.0	73.0
GE 1500	75.2	75.9	77.1	77.5	78.6	78.8	78.9	78.9	78.9	78.9	78.9	78.9
GE 1200	75.5	79.1	81.4	81.8	83.2	83.5	83.9	83.9	83.9	83.9	83.9	83.9
GE 1000	80.1	80.8	83.2	83.9	85.4	85.7	86.2	86.3	86.3	86.3	86.3	86.3
GF 900	81.1	81.8	84.5	85.3	86.9	87.3	87.8	88.0	88.0	88.0	88.0	88.0
GE 800	81.8	82.7	85.5	86.2	87.8	88.5	89.0	89.4	89.4	89.4	89.4	89.4
GE 700	82.2	83.1	86.0	86.9	88.5	89.1	89.7	90.0	90.1	90.1	90.1	90.1
GE 600	82.6	83.7	86.6	87.4	89.7	90.4	91.3	91.9	92.3	92.3	92.3	92.3
GF 500	82.9	83.9	87.1	88.2	90.6	91.5	92.6	93.2	94.3	94.5	94.6	94.6
GE 400	82.8	84.0	87.2	88.3	90.9	91.9	93.5	94.6	96.2	96.6	96.8	96.8
GF 350	82.3	84.0	87.2	88.5	90.9	91.9	93.5	94.7	96.9	97.3	97.8	98.1
GE 200	82.8	84.0	87.2	88.4	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5
GE 100	82.8	84.0	87.2	88.4	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5
GE 000	82.8	84.0	87.2	88.4	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT HOURS: 12-14

VISIBILITY IN STATUTE MILES

CE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0	
31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5	31.5
33.5	38.5	34.5	34.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
33.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7
39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0
39.5	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6	39.6
40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8	40.8
42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5	42.5
43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4
45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1
48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6	48.6
50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9
54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7	54.7
60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2	60.2
64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5	64.5
71.1	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3	71.3
73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0
78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	79.0	79.0	79.0
83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	84.0	84.0	84.0
86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.5	86.6	86.6	86.6
88.0	87.3	87.8	88.0	88.0	88.0	88.0	88.0	88.0	88.1	88.2	88.2	88.2
89.4	88.5	89.0	89.4	89.4	89.4	89.4	89.4	89.4	89.5	89.6	89.6	89.6
90.1	89.5	89.7	90.0	90.1	90.1	90.1	90.1	90.1	90.2	90.3	90.3	90.3
92.3	90.7	90.4	91.3	91.9	92.3	92.3	92.3	92.3	92.4	92.5	92.5	92.5
94.6	91.5	92.5	93.2	94.3	94.5	94.6	94.6	94.6	94.7	94.8	94.8	94.8
96.8	91.9	93.5	94.6	96.2	96.6	96.8	96.8	96.8	96.9	97.0	97.0	97.0
97.8	91.9	93.5	94.7	96.9	97.3	97.8	97.8	98.1	98.2	98.3	98.3	98.3
98.3	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5	99.0	99.4	99.8	99.9
98.5	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5	99.0	99.4	99.8	100.0
99.8	91.0	92.0	93.7	94.9	97.3	97.7	98.3	98.5	99.0	99.4	99.8	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: OCT HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	33.1	33.1	33.1	33.2	33.3	33.3	33.4	33.4	33.4	33.4	33.4	33.4	33.4
GE 20000	39.6	39.6	39.7	39.3	39.9	39.9	40.0	40.0	40.0	40.0	40.0	40.0	40.0
GE 18000	39.9	39.9	40.0	40.1	40.2	40.2	40.3	40.3	40.3	40.3	40.3	40.3	40.3
GE 16000	40.0	40.0	40.1	40.2	40.3	40.3	40.4	40.4	40.4	40.4	40.4	40.4	40.4
GE 14000	41.1	41.1	41.4	41.5	41.6	41.6	41.7	41.7	41.7	41.7	41.7	41.7	41.7
GE 12000	42.5	42.6	42.9	43.0	43.2	43.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3
GE 10000	45.1	45.3	45.7	45.8	46.0	46.0	46.1	46.1	46.1	46.1	46.1	46.1	46.1
GE 9000	45.5	45.7	46.1	46.2	46.5	46.5	46.5	46.6	46.6	46.6	46.6	46.6	46.6
GE 8000	46.3	47.0	47.5	47.6	47.8	47.8	48.0	48.0	48.0	48.0	48.0	48.0	48.0
GE 7000	47.1	47.3	47.8	48.0	48.2	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3
GE 6000	47.6	48.0	48.6	48.7	48.9	48.9	49.0	49.0	49.0	49.0	49.0	49.0	49.0
GE 5000	49.6	50.0	50.6	50.3	51.0	51.0	51.1	51.1	51.1	51.1	51.1	51.1	51.1
GE 4500	51.1	51.5	52.2	52.3	52.5	52.5	52.6	52.6	52.6	52.6	52.6	52.6	52.6
GE 4000	54.9	55.4	56.0	56.1	56.3	56.3	56.5	56.5	56.5	56.5	56.5	56.5	56.5
GE 3500	57.2	57.6	58.4	58.6	58.8	58.8	58.9	58.9	58.9	58.9	58.9	58.9	58.9
GE 3000	61.5	61.9	62.8	63.0	63.2	63.2	63.3	63.3	63.3	63.3	63.3	63.3	63.3
GE 2500	68.2	68.8	69.9	70.3	70.6	70.6	70.8	70.8	70.8	70.8	70.8	70.8	70.8
GE 2000	73.1	73.8	74.9	75.7	76.1	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2
GE 1800	74.7	75.7	77.1	78.0	78.4	78.4	78.6	78.8	78.8	78.8	78.8	78.8	78.8
GE 1500	79.0	80.4	82.2	83.0	83.4	83.5	83.9	84.1	84.1	84.1	84.1	84.1	84.1
GE 1200	80.6	82.5	84.7	85.7	86.3	86.5	86.8	87.2	87.2	87.2	87.2	87.2	87.2
GE 1000	81.7	83.5	86.1	87.3	88.1	88.2	89.1	89.6	89.8	89.8	89.8	89.8	89.8
GE 900	82.4	84.2	86.9	88.1	88.9	89.0	90.0	90.6	90.6	90.6	90.6	90.6	90.6
GE 800	82.5	84.3	87.0	88.3	89.1	89.2	90.2	90.9	91.0	91.1	91.1	91.1	91.1
GE 700	82.5	84.3	87.2	88.9	90.0	90.2	91.3	92.0	92.2	92.3	92.3	92.3	92.3
GE 600	82.5	84.4	87.4	89.1	90.3	90.5	91.8	92.9	93.1	93.2	93.2	93.2	93.2
GE 500	82.5	84.4	87.4	89.4	90.8	91.4	92.8	94.1	94.6	95.3	95.6	95.6	95.6
GE 400	82.5	84.4	87.4	89.4	90.9	91.6	93.2	94.6	95.7	96.3	96.8	96.8	96.8
GE 300	82.5	84.4	87.5	89.5	91.3	92.0	93.9	95.5	97.2	98.0	98.4	98.4	98.4
GE 200	82.5	84.4	87.5	89.5	91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	98.7
GE 100	82.5	84.4	87.5	89.5	91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	98.7
GE 000	82.5	84.4	87.5	89.5	91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	98.7

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT HOURS: 15-17

VISIBILITY IN STATUTE MILES											
GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
33.3	33.3	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4
39.9	39.9	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0
40.2	40.2	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3	40.3
40.3	40.3	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
41.6	41.6	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7
43.2	43.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
46.0	46.0	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1
46.5	46.5	46.5	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6	46.6
47.8	47.8	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0	48.0
48.2	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
48.9	48.9	49.0	49.0	49.0	49.0	49.0	49.0	49.0	49.0	49.0	49.0
51.0	51.0	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1	51.1
52.5	52.5	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6	52.6
56.3	56.3	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5	56.5
58.8	58.8	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9	58.9
63.2	63.2	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3	63.3
70.6	70.6	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8	70.8
76.1	76.1	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2	76.2
78.4	78.4	78.6	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8	78.8
83.4	83.5	83.9	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1
86.3	86.5	86.8	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2
89.1	89.2	89.1	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
89.9	89.0	90.0	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
89.1	89.2	90.2	90.9	91.0	91.1	91.1	91.1	91.1	91.1	91.1	91.1
90.0	90.2	91.3	92.0	92.2	92.3	92.3	92.3	92.3	92.3	92.3	92.3
90.3	90.5	91.8	92.9	93.1	93.2	93.2	93.2	93.2	93.2	93.2	93.2
90.8	91.4	92.8	94.1	94.6	95.3	95.6	95.6	95.6	95.6	95.6	95.7
90.9	91.6	93.2	94.6	95.7	96.3	96.8	96.8	96.8	96.8	96.8	96.9
91.3	92.0	93.9	95.5	97.2	98.0	98.4	98.4	98.7	98.7	98.7	98.8
91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	99.4	99.6	99.7	100.0
91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	99.4	99.5	99.7	100.0
91.3	92.0	94.1	95.7	97.4	98.3	98.7	98.7	99.4	99.6	99.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBR: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - J
MONTH: OCT HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GF 6	GE 5	GF 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	36.8	36.8	37.3	37.4	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5
GE 20000	41.3	41.3	42.4	42.6	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
GE 18000	41.4	41.4	42.5	42.7	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8
GE 16000	41.4	41.4	42.6	42.8	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
GE 14000	42.7	42.7	43.9	44.1	44.2	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3
GE 12000	44.3	44.3	45.5	45.7	45.8	46.0	46.1	46.1	46.2	46.2	46.2	46.2	46.2
GE 10000	46.6	46.7	47.8	48.2	48.3	48.5	48.6	48.6	48.7	48.7	48.7	48.7	48.7
GE 9000	47.0	47.1	48.3	48.6	48.7	48.9	49.0	49.0	49.1	49.1	49.1	49.1	49.1
GE 8000	49.6	49.7	51.2	51.5	51.6	51.8	51.9	51.9	52.0	52.0	52.0	52.0	52.0
GE 7000	50.8	50.9	52.4	52.7	52.8	53.0	53.1	53.1	53.2	53.2	53.2	53.2	53.2
GE 6000	51.6	51.7	53.2	53.5	53.7	53.9	54.0	54.0	54.1	54.1	54.1	54.1	54.1
GE 5000	53.9	54.0	55.5	55.8	55.9	56.1	56.2	56.2	56.3	56.3	56.3	56.3	56.3
GE 4500	54.9	55.1	56.6	56.9	57.0	57.2	57.3	57.3	57.4	57.4	57.4	57.4	57.4
GF 4000	59.1	59.2	60.9	61.4	61.6	61.8	61.9	61.9	62.0	62.0	62.0	62.0	62.0
GE 3500	61.9	62.0	63.7	64.2	64.5	64.7	64.8	64.8	64.9	64.9	64.9	64.9	64.9
GE 3000	65.6	65.8	67.4	68.2	68.5	68.7	68.8	68.8	69.0	69.0	69.0	69.0	69.0
GE 2500	71.4	71.6	73.2	74.0	74.3	74.5	74.6	74.6	74.8	74.8	74.8	74.8	74.8
GE 2000	73.9	74.2	75.9	76.7	77.6	77.8	78.2	78.2	78.4	78.4	78.4	78.4	78.4
GE 1800	74.9	75.3	77.0	77.7	78.9	79.1	79.5	79.6	79.8	79.8	79.8	79.8	79.8
GE 1500	77.5	77.8	79.9	80.9	82.4	82.6	83.0	83.1	83.3	83.3	83.3	83.3	83.3
GE 1200	78.6	79.0	81.2	82.4	84.1	84.3	84.8	85.1	85.3	85.3	85.3	85.3	85.3
GE 1000	79.9	80.3	82.6	83.8	85.8	86.0	86.7	86.9	87.1	87.1	87.1	87.1	87.1
GE 900	80.2	80.6	83.0	84.2	86.2	86.5	87.1	87.3	87.5	87.5	87.5	87.5	87.5
GE 800	80.4	80.9	83.3	84.5	86.8	87.0	87.6	87.8	88.1	88.1	88.1	88.1	88.1
GE 700	81.0	81.4	84.0	85.2	87.7	88.0	89.2	89.7	89.9	89.9	90.0	90.0	90.0
GE 600	81.2	81.6	84.5	85.8	88.6	88.8	90.5	91.1	91.3	91.4	91.5	91.5	91.5
GE 500	81.3	81.7	84.7	86.1	89.6	90.0	92.6	93.8	94.1	94.4	94.7	94.7	94.7
GE 400	81.4	81.8	85.1	86.5	90.0	90.6	93.9	95.3	95.6	96.2	96.8	96.9	96.9
GE 300	81.4	81.8	85.1	86.6	90.3	91.1	94.4	96.6	97.1	98.1	98.6	99.1	99.1
GE 200	81.4	81.8	85.1	86.6	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.7
GE 100	81.4	81.8	85.1	86.6	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.8
GE 000	81.4	81.8	85.1	86.6	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.8

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 76 - JUL 88
 ITC: + 5 MONTH: OCT HOURS: 18-20

	VISIBILITY IN STATUTE MILES											
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
4	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5	37.5
5	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
6	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8	42.8
7	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
8	44.2	44.2	44.2	44.2	44.3	44.3	44.3	44.3	44.3	44.3	44.3	44.3
9	45.8	46.0	46.1	46.1	46.2	46.2	46.2	46.2	46.2	46.2	46.2	46.2
0	48.3	48.5	48.6	48.6	48.7	48.7	48.7	48.7	48.7	48.7	48.7	48.7
1	48.7	48.9	49.0	49.0	49.1	49.1	49.1	49.1	49.1	49.1	49.1	49.1
2	51.6	51.8	51.9	51.9	52.0	52.0	52.0	52.0	52.0	52.0	52.0	52.0
3	52.8	53.0	53.1	53.1	53.2	53.2	53.2	53.2	53.2	53.2	53.2	53.2
4	53.7	53.9	54.0	54.0	54.1	54.1	54.1	54.1	54.1	54.1	54.1	54.1
5	55.9	56.1	56.2	56.2	56.3	56.3	56.3	56.3	56.3	56.3	56.3	56.3
6	57.0	57.2	57.3	57.3	57.4	57.4	57.4	57.4	57.4	57.4	57.4	57.4
7	61.6	61.8	61.9	61.9	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0
8	64.5	64.7	64.8	64.8	64.9	64.9	64.9	64.9	64.9	64.9	64.9	64.9
9	68.5	68.7	68.8	68.8	69.0	69.0	69.0	69.0	69.0	69.0	69.0	69.0
0	74.3	74.5	74.6	74.6	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
1	77.6	77.8	78.2	78.2	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4
2	79.9	79.1	79.5	79.6	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8
3	82.4	82.6	83.0	83.1	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
4	84.1	84.3	84.8	85.1	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
5	85.8	86.0	86.7	86.9	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
6	86.2	86.5	87.1	87.3	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
7	86.8	87.0	87.6	87.8	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
8	87.7	88.0	89.2	89.7	89.9	89.9	90.0	90.0	90.0	90.0	90.0	90.0
9	88.6	88.8	90.5	91.1	91.3	91.4	91.5	91.5	91.5	91.5	91.5	91.5
0	89.6	90.0	92.6	93.8	94.1	94.4	94.7	94.7	94.7	94.7	94.7	94.7
1	90.0	90.6	93.9	95.3	95.6	96.2	96.8	96.9	96.9	96.9	96.9	96.9
2	90.3	91.1	94.4	96.6	97.1	98.1	98.6	99.1	99.1	99.1	99.1	99.1
3	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.7	99.7	99.8	99.8
4	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.8	99.8	100.0	100.0
5	90.3	91.1	94.4	96.6	97.2	98.2	98.9	99.6	99.8	99.8	100.0	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: OCT HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	36.5	36.8	37.0	37.0	37.4	37.4	37.6	37.8	38.0	38.2	38.2	38.2	38.4
GE 20000	40.5	40.9	41.2	41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7
GE 18000	40.5	40.9	41.2	41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7
GE 16000	40.5	40.9	41.2	41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7
GE 14000	41.8	42.2	42.5	42.5	43.0	43.0	43.2	43.4	43.5	43.8	43.8	43.8	44.0
GE 12000	42.6	42.9	43.4	43.4	44.0	44.3	44.5	44.7	44.8	45.1	45.1	45.1	45.3
GE 10000	44.8	45.2	45.9	45.9	46.5	46.8	47.0	47.2	47.3	47.5	47.5	47.5	47.7
GE 9000	45.4	45.7	46.5	46.5	47.0	47.3	47.5	47.7	47.8	48.1	48.1	48.1	48.3
GE 8000	47.5	47.8	48.7	48.7	49.2	49.6	49.8	50.0	50.1	50.3	50.3	50.3	50.5
GE 7000	48.9	49.2	50.1	50.1	50.6	51.0	51.2	51.4	51.5	51.7	51.7	51.7	51.9
GE 6000	51.1	51.4	52.3	52.3	52.8	53.1	53.3	53.5	53.7	53.9	53.9	53.9	54.1
GE 5000	52.9	53.2	54.1	54.1	54.8	55.2	55.4	55.6	55.7	55.9	55.9	55.9	56.1
GE 4500	54.8	55.2	56.1	56.1	56.9	57.2	57.4	57.6	57.7	58.0	58.0	58.0	58.2
GE 4000	58.5	58.9	59.9	60.0	60.9	61.2	61.4	61.6	61.7	61.9	61.9	61.9	62.2
GE 3500	61.4	61.7	62.8	62.9	64.0	64.4	64.6	64.8	64.9	65.2	65.2	65.2	65.4
GE 3000	64.5	64.8	65.9	66.0	67.2	67.6	67.8	68.2	68.3	68.5	68.5	68.5	68.7
GE 2500	68.8	69.2	70.4	70.3	72.0	72.5	72.7	73.0	73.1	73.3	73.3	73.3	73.5
GE 2000	71.9	72.4	73.9	74.2	75.5	76.1	76.5	76.8	76.9	77.1	77.1	77.1	77.3
GE 1800	73.0	73.4	75.1	75.4	76.8	77.4	77.8	78.2	78.3	78.5	78.5	78.5	78.7
GE 1500	74.3	74.8	76.5	77.0	78.4	79.0	79.6	79.9	80.0	80.2	80.2	80.2	80.4
GE 1200	75.8	76.3	78.2	78.8	80.2	80.9	81.4	81.7	81.8	82.2	82.2	82.2	82.4
GE 1000	78.0	78.6	80.6	81.5	83.7	84.5	85.1	85.5	85.6	86.1	86.1	86.1	86.3
GE 900	78.6	79.4	81.5	82.4	84.7	85.6	86.1	86.6	86.7	87.2	87.2	87.2	87.4
GE 800	78.9	79.7	81.8	82.7	85.7	86.6	87.3	87.7	87.8	88.6	88.6	88.6	88.8
GE 700	79.1	79.9	82.7	83.5	86.7	87.7	88.9	89.4	89.6	90.3	90.4	90.4	90.6
GE 600	79.7	80.4	83.3	84.2	87.4	88.6	90.0	90.4	90.6	91.4	91.5	91.5	91.7
GE 500	79.9	80.6	83.8	84.6	88.0	89.1	90.8	91.5	92.2	92.9	93.2	93.2	93.4
GE 400	80.0	80.8	83.9	84.7	88.4	89.7	91.6	92.7	93.5	94.3	94.7	94.7	95.1
GE 300	80.0	80.8	84.2	85.2	89.1	90.6	92.7	94.4	95.5	96.2	96.7	96.7	97.0
GE 200	80.0	80.8	84.3	85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.1	98.4	98.6
GE 100	80.0	80.8	84.3	85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.2	98.5	98.9
GE 000	80.0	80.8	84.3	85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.2	98.5	98.9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT HOURS: 21-23

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
37.0	37.4	37.4	37.5	37.8	38.0	38.2	38.2	38.2	38.4	38.5	38.5	38.5
41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7	42.8	42.8	42.8
41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7	42.8	42.8	42.8
41.2	41.7	41.7	41.9	42.2	42.3	42.5	42.5	42.5	42.7	42.8	42.8	42.8
42.5	43.0	43.0	43.2	43.4	43.5	43.8	43.8	43.8	44.0	44.1	44.1	44.1
43.4	44.0	44.3	44.5	44.7	44.8	45.1	45.1	45.1	45.3	45.4	45.4	45.4
45.9	46.5	46.8	47.0	47.2	47.3	47.5	47.5	47.5	47.7	47.8	47.8	47.8
46.5	47.0	47.3	47.5	47.7	47.8	48.1	48.1	48.1	48.3	48.4	48.4	48.4
48.7	49.2	49.5	49.8	50.0	50.1	50.3	50.3	50.3	50.5	50.6	50.6	50.6
50.1	50.6	51.0	51.2	51.4	51.5	51.7	51.7	51.7	51.9	52.0	52.0	52.0
52.3	52.8	53.1	53.3	53.5	53.7	53.9	53.9	53.9	54.1	54.2	54.2	54.2
54.1	54.8	55.2	55.4	55.6	55.7	55.9	55.9	55.9	56.1	56.2	56.2	56.2
56.1	56.9	57.2	57.4	57.6	57.7	58.0	58.0	58.0	58.2	58.3	58.3	58.3
60.0	60.9	61.2	61.4	61.6	61.7	61.9	61.9	61.9	62.2	62.3	62.3	62.3
62.9	64.0	64.4	64.6	64.8	64.9	65.2	65.2	65.2	65.4	65.5	65.5	65.5
66.0	67.2	67.6	67.8	68.2	68.3	68.5	68.5	68.5	68.7	68.8	68.8	68.8
70.3	72.0	72.5	72.7	73.0	73.1	73.3	73.3	73.3	73.5	73.7	73.7	73.7
74.2	75.5	76.1	76.5	76.8	76.9	77.1	77.1	77.1	77.3	77.4	77.4	77.4
75.4	76.8	77.4	77.8	78.2	78.3	78.5	78.5	78.5	78.7	78.8	78.8	78.8
77.0	78.4	79.0	79.6	79.9	80.0	80.2	80.2	80.2	80.4	80.5	80.5	80.5
78.8	80.2	80.9	81.4	81.7	81.8	82.2	82.2	82.2	82.4	82.5	82.5	82.5
81.5	83.7	84.5	85.1	85.5	85.6	86.1	86.1	86.1	86.3	86.5	86.5	86.5
82.4	84.7	85.6	86.1	86.6	86.7	87.2	87.2	87.2	87.4	87.5	87.5	87.5
82.7	85.7	86.6	87.3	87.7	87.8	88.6	88.6	88.6	88.8	88.9	88.9	88.9
83.5	86.7	87.7	88.9	89.4	89.6	90.3	90.4	90.4	90.6	90.8	90.8	90.8
84.2	87.4	88.6	90.0	90.4	90.6	91.4	91.5	91.5	91.7	91.8	91.8	91.8
84.6	88.0	89.1	90.8	91.5	92.2	92.9	93.2	93.2	93.4	93.5	93.5	93.5
84.7	88.4	89.7	91.6	92.7	93.5	94.3	94.7	94.7	95.1	95.2	95.7	95.7
85.2	89.1	90.6	92.7	94.4	95.5	96.2	96.7	96.7	97.0	97.1	97.6	97.6
85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.1	98.4	98.8	98.9	99.5	99.7
85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.2	98.5	98.9	99.0	99.6	100.0
85.3	89.4	90.9	93.3	95.4	96.9	97.6	98.2	98.5	98.9	99.0	99.6	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBIL
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: OCT HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	32.1	32.2	32.7	33.0	33.5	33.6	33.8	34.0	34.1	34.3	34.3	34.3	34.4
GE 20000	36.1	36.3	36.8	37.1	37.7	37.8	38.0	38.2	38.3	38.4	38.5	38.5	38.6
GE 18000	36.3	36.4	37.0	37.3	37.9	38.0	38.2	38.4	38.5	38.6	38.7	38.7	38.8
GE 16000	36.4	36.5	37.1	37.4	38.0	38.1	38.3	38.5	38.6	38.8	38.8	38.8	39.0
GE 14000	37.2	37.4	38.0	38.3	38.9	39.0	39.2	39.4	39.6	39.7	39.7	39.8	39.9
GE 12000	38.6	38.7	39.4	39.7	40.3	40.5	40.7	40.9	41.0	41.2	41.2	41.3	41.4
GE 10000	40.9	41.1	41.8	42.2	42.8	43.0	43.2	43.4	43.5	43.7	43.7	43.8	43.9
GE 9000	41.5	41.7	42.4	42.8	43.3	43.5	43.8	44.0	44.1	44.2	44.3	44.3	44.4
GE 8000	43.1	43.4	44.2	44.6	45.1	45.3	45.6	45.9	46.0	46.1	46.2	46.2	46.3
GE 7000	44.1	44.4	45.2	45.6	46.2	46.4	46.7	46.9	47.0	47.2	47.2	47.2	47.4
GE 6000	45.2	45.4	46.3	46.7	47.3	47.5	47.8	48.1	48.2	48.3	48.3	48.4	48.5
GE 5000	47.7	47.9	48.8	49.2	49.9	50.1	50.4	50.7	50.8	51.0	51.1	51.1	51.2
GE 4500	49.4	49.7	50.6	51.0	51.7	51.9	52.3	52.6	52.7	52.9	52.9	53.0	53.1
GE 4000	53.2	53.5	54.5	55.0	55.8	56.0	56.3	56.6	56.8	57.0	57.0	57.1	57.2
GE 3500	55.5	55.8	56.8	57.4	58.2	58.5	58.8	59.2	59.3	59.5	59.5	59.6	59.7
GE 3000	59.5	59.8	60.9	61.5	62.4	62.6	63.0	63.3	63.5	63.7	63.8	63.8	63.9
GE 2500	63.5	63.9	65.0	65.7	66.7	67.0	67.4	67.7	67.9	68.1	68.1	68.2	68.3
GE 2000	67.7	68.1	69.4	70.2	71.3	71.7	72.1	72.5	72.7	72.8	72.9	72.9	73.1
GE 1800	69.1	69.5	70.9	71.7	72.9	73.3	73.8	74.2	74.4	74.5	74.6	74.6	74.7
GE 1500	72.0	72.6	74.3	75.2	76.6	77.0	77.6	78.0	78.2	78.3	78.4	78.4	78.6
GE 1200	73.8	74.5	76.6	77.7	79.2	79.7	80.3	80.8	81.0	81.2	81.3	81.3	81.4
GE 1000	75.2	76.0	78.3	79.6	81.4	81.9	82.7	83.3	83.5	83.7	83.8	83.8	84.0
GE 900	75.9	76.7	79.2	80.7	82.6	83.2	84.0	84.6	84.8	85.0	85.1	85.2	85.3
GE 800	76.6	77.4	80.1	81.6	83.8	84.4	85.3	85.9	86.2	86.6	86.7	86.7	86.9
GE 700	77.0	77.8	80.8	82.4	84.8	85.6	86.7	87.4	87.8	88.1	88.3	88.3	88.5
GE 600	77.4	78.3	81.3	83.0	85.8	86.6	88.0	89.0	89.3	89.7	89.9	89.9	90.1
GE 500	77.6	78.5	81.7	83.5	86.8	87.9	89.6	90.9	91.6	92.2	92.4	92.5	92.6
GE 400	77.7	78.7	81.9	83.8	87.3	88.5	90.6	92.2	93.3	94.0	94.3	94.4	94.6
GE 300	77.8	78.8	82.1	84.1	87.9	89.2	91.5	93.5	95.0	95.8	96.3	96.4	96.8
GE 200	77.8	78.8	82.2	84.2	88.0	89.3	91.9	94.0	95.7	96.6	97.2	97.4	98.1
GE 100	77.8	78.8	82.2	84.2	88.0	89.3	91.9	94.0	95.7	96.7	97.2	97.5	98.3
GE 000	77.8	78.8	82.2	84.2	88.0	89.3	91.9	94.0	95.7	96.7	97.2	97.5	98.3

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: OCT HOURS: ALL

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.0	33.5	33.6	33.8	34.0	34.1	34.3	34.3	34.3	34.4	34.5	34.6	34.8
30.1	37.7	37.8	38.0	38.2	38.3	38.4	38.5	38.5	38.6	38.7	38.8	39.0
30.2	37.9	38.0	38.2	38.4	38.5	38.6	38.7	38.7	38.8	38.9	39.0	39.2
30.3	38.0	38.1	38.3	38.5	38.6	38.8	38.8	38.8	39.0	39.0	39.1	39.3
30.4	38.9	39.0	39.2	39.4	39.6	39.7	39.7	39.8	39.9	39.9	40.1	40.2
30.5	40.3	40.5	40.7	40.9	41.0	41.2	41.2	41.3	41.4	41.4	41.5	41.7
30.6	42.8	43.0	43.2	43.4	43.5	43.7	43.7	43.8	43.9	43.9	44.1	44.2
30.7	43.3	43.5	43.8	44.0	44.1	44.2	44.3	44.3	44.4	44.5	44.6	44.8
30.8	45.1	45.3	45.5	45.9	46.0	46.1	46.2	46.2	46.3	46.4	46.5	46.7
30.9	46.2	46.4	46.7	46.9	47.0	47.2	47.2	47.2	47.4	47.4	47.6	47.7
31.0	47.3	47.5	47.8	48.1	48.2	48.3	48.3	48.4	48.5	48.5	48.7	48.8
31.1	49.9	50.1	50.4	50.7	50.8	51.0	51.1	51.1	51.2	51.3	51.4	51.5
31.2	51.7	51.9	52.3	52.6	52.7	52.9	52.9	53.0	53.1	53.1	53.3	53.4
31.3	55.8	56.0	56.3	56.6	56.8	57.0	57.0	57.1	57.2	57.2	57.4	57.5
31.4	53.2	58.5	58.8	59.2	59.3	59.5	59.5	59.6	59.7	59.7	59.9	60.0
31.5	52.4	62.6	63.0	63.3	63.5	63.7	63.8	63.8	63.9	64.0	64.1	64.2
31.6	66.7	67.0	67.4	67.7	67.9	68.1	68.1	68.2	68.3	68.3	68.5	68.6
31.7	71.3	71.7	72.1	72.5	72.7	72.8	72.9	72.9	73.1	73.1	73.3	73.4
31.8	72.9	73.3	73.8	74.2	74.4	74.5	74.6	74.6	74.7	74.8	74.9	75.1
31.9	76.6	77.0	77.6	78.0	78.2	78.3	78.4	78.4	78.6	78.6	78.8	78.9
32.0	79.2	79.7	80.3	80.8	81.0	81.2	81.3	81.3	81.4	81.5	81.6	81.8
32.1	81.4	81.9	82.7	83.3	83.5	83.7	83.8	83.8	84.0	84.0	84.2	84.3
32.2	82.6	83.2	84.0	84.6	84.8	85.0	85.1	85.2	85.3	85.4	85.5	85.7
32.3	83.8	84.4	85.3	85.9	86.2	86.6	86.7	86.7	86.9	87.0	87.1	87.3
32.4	84.8	85.6	86.7	87.4	87.8	88.1	88.3	88.3	88.5	88.6	88.7	88.9
32.5	85.8	86.6	88.0	89.0	89.3	89.7	89.9	89.9	90.1	90.2	90.3	90.5
32.6	86.8	87.9	89.5	90.9	91.6	92.2	92.4	92.5	92.6	92.7	92.8	93.0
32.7	87.3	88.5	90.6	92.2	93.3	94.0	94.3	94.4	94.6	94.7	95.0	95.1
32.8	87.9	89.2	91.5	93.5	95.0	95.8	96.3	96.4	96.8	96.9	97.2	97.5
32.9	89.0	89.3	91.9	94.0	95.7	96.6	97.2	97.4	98.1	98.4	98.9	99.4
33.0	88.0	89.3	91.9	94.0	95.7	96.7	97.2	97.5	98.3	98.5	99.1	99.9
33.1	88.0	89.3	91.9	94.0	95.7	96.7	97.2	97.5	98.3	98.5	99.2	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: NOV HOURS: 00-0

.....
CEILING

.....
VISIBILITY IN STATUTE MILES

IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	26.7	26.8	27.6	27.9	28.4	28.4	28.4	28.8	28.8	28.9	29.0	29.0	29
GE 20000	30.2	30.3	31.1	31.4	32.0	32.0	32.0	32.3	32.3	32.4	32.6	32.6	32
GE 18000	30.4	30.6	31.3	31.7	32.2	32.2	32.2	32.6	32.6	32.7	32.8	32.8	32
GE 16000	30.6	30.7	31.4	31.8	32.3	32.3	32.3	32.7	32.7	32.8	32.9	32.9	32
GE 14000	30.7	30.8	31.6	31.9	32.4	32.4	32.4	32.8	32.8	32.9	33.0	33.0	33
GE 12000	31.8	31.9	32.7	33.0	33.6	33.6	33.6	33.9	33.9	34.0	34.1	34.1	34
GE 10000	33.8	33.9	34.7	35.0	35.6	35.6	35.6	35.9	35.9	36.0	36.1	36.1	36
GE 9000	34.1	34.2	35.0	35.3	35.9	35.9	35.9	36.2	36.2	36.3	36.4	36.4	36
GE 8000	35.7	35.8	36.6	37.1	37.8	37.8	37.8	38.1	38.1	38.2	38.3	38.3	38
GE 7000	36.9	37.0	37.8	38.3	39.0	39.0	39.0	39.3	39.3	39.4	39.6	39.6	39
GE 6000	36.9	37.0	37.8	38.3	39.0	39.0	39.0	39.3	39.3	39.4	39.6	39.6	39
GE 5000	37.9	38.0	38.8	39.3	40.0	40.3	40.3	40.7	40.7	40.8	40.9	40.9	40
GE 4500	40.0	40.1	41.0	41.6	42.2	42.6	42.6	42.9	42.9	43.0	43.1	43.1	43
GE 4000	42.0	42.1	43.0	43.6	44.2	44.6	44.6	44.9	44.9	45.0	45.1	45.1	45
GE 3500	43.1	43.2	44.2	44.9	45.7	46.0	46.0	46.3	46.3	46.4	46.6	46.6	46
GE 3000	46.7	46.9	48.1	49.0	50.1	50.4	50.6	50.9	50.9	51.0	51.1	51.1	51
GE 2500	52.8	53.1	54.6	55.6	56.9	57.4	57.6	57.9	57.9	58.0	58.1	58.1	58
GE 2000	60.6	61.0	62.7	63.9	65.4	66.1	66.3	66.9	66.9	67.0	67.1	67.1	67
GE 1800	63.8	64.3	66.0	67.2	68.8	69.4	69.7	70.2	70.2	70.3	70.4	70.4	70
GE 1500	67.0	67.8	69.7	71.0	72.7	73.3	74.0	74.7	74.7	74.9	75.0	75.0	75
GE 1200	69.1	69.9	72.0	73.6	75.4	76.1	76.9	77.6	77.6	77.9	78.0	78.0	78
GE 1000	70.6	71.3	73.4	75.0	77.2	78.0	79.2	80.2	80.8	81.1	81.2	81.2	81
GE 900	72.0	72.8	75.0	76.9	79.6	80.4	81.8	82.9	83.4	84.0	84.1	84.1	84
GE 800	72.8	73.6	75.9	77.3	80.8	81.8	83.1	84.8	85.3	86.0	86.2	86.2	86
GE 700	73.0	73.9	76.2	78.2	81.3	82.4	84.0	85.7	86.2	87.0	87.3	87.3	87
GE 600	73.0	73.9	76.6	78.6	82.1	83.2	85.2	87.1	87.7	88.4	88.9	88.9	89
GE 500	73.7	74.6	77.9	80.3	84.1	85.7	88.1	90.7	91.3	92.4	93.1	93.1	93
GE 400	73.7	74.6	77.9	80.3	84.2	85.8	88.4	91.0	91.7	93.1	93.8	93.8	94
GE 300	73.8	74.7	78.0	80.4	84.5	86.1	89.2	92.0	93.0	94.8	95.4	95.4	95
GE 200	73.8	74.7	78.0	80.4	84.9	86.4	89.6	92.4	94.1	96.0	97.0	97.0	97
GE 100	73.8	74.7	78.0	80.4	84.9	86.4	89.6	92.4	94.2	96.6	97.6	97.6	98
GE 000	73.8	74.7	78.0	80.4	84.9	86.4	89.6	92.4	94.2	96.6	97.6	97.6	98

.....
TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 00-02

VISIBILITY IN STATUTE MILES											
GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
28.4	28.4	28.4	28.8	28.8	28.9	29.0	29.0	29.0	29.2	29.2	29.4
32.0	32.0	32.0	32.3	32.3	32.4	32.6	32.6	32.6	32.8	32.8	33.0
32.2	32.2	32.2	32.6	32.6	32.7	32.8	32.8	32.8	33.0	33.0	33.2
32.3	32.3	32.3	32.7	32.7	32.8	32.9	32.9	32.9	33.1	33.1	33.3
32.4	32.4	32.4	32.8	32.8	32.9	33.0	33.0	33.0	33.2	33.2	33.4
33.6	33.6	33.6	33.9	33.9	34.0	34.1	34.1	34.1	34.3	34.3	34.6
35.6	35.6	35.6	35.9	35.9	36.0	36.1	36.1	36.1	36.3	36.3	36.6
35.9	35.9	35.9	36.2	36.2	36.3	36.4	36.4	36.4	36.7	36.7	36.9
37.8	37.8	37.8	38.1	38.1	38.2	38.3	38.3	38.3	38.6	38.6	38.8
39.0	39.0	39.0	39.3	39.3	39.4	39.6	39.6	39.6	39.8	39.8	40.0
39.0	39.0	39.0	39.3	39.3	39.4	39.6	39.6	39.6	39.8	39.8	40.0
40.0	40.3	40.3	40.7	40.7	40.8	40.9	40.9	40.9	41.1	41.1	41.3
42.2	42.6	42.6	42.9	42.9	43.0	43.1	43.1	43.1	43.3	43.3	43.6
44.2	44.6	44.6	44.9	44.9	45.0	45.1	45.1	45.1	45.3	45.3	45.6
45.7	46.0	46.0	46.3	46.3	46.4	46.6	46.6	46.6	46.8	46.8	47.0
50.1	50.4	50.6	50.9	50.9	51.0	51.1	51.1	51.1	51.3	51.3	51.6
55.9	57.4	57.6	57.9	57.9	58.0	58.1	58.1	58.1	58.3	58.3	58.6
65.4	66.1	66.3	66.9	66.9	67.0	67.1	67.1	67.1	67.3	67.3	67.6
63.8	69.4	69.7	70.2	70.2	70.3	70.4	70.4	70.4	70.7	70.7	70.9
72.7	73.3	74.0	74.7	74.7	74.9	75.0	75.0	75.0	75.2	75.2	75.4
75.4	76.1	76.9	77.6	77.6	77.9	78.0	78.0	78.0	78.2	78.2	78.4
77.2	78.0	79.2	80.2	80.8	81.1	81.2	81.2	81.2	81.4	81.4	81.7
77.6	80.4	81.8	82.9	83.4	84.0	84.1	84.1	84.1	84.3	84.3	84.6
80.8	81.8	83.1	84.8	85.3	86.0	86.2	86.2	86.2	86.4	86.4	86.7
81.3	82.4	84.0	85.7	86.2	87.0	87.3	87.3	87.4	87.7	87.7	87.9
82.1	83.2	85.2	87.1	87.7	88.4	88.9	88.9	89.0	89.2	89.2	89.4
84.1	85.7	88.1	90.7	91.3	92.4	93.1	93.1	93.2	93.4	93.4	93.7
84.2	85.6	88.4	91.0	91.7	93.1	93.8	93.8	94.0	94.2	94.2	94.4
84.5	86.1	89.2	92.0	93.0	94.8	95.4	95.4	95.7	95.9	96.0	96.2
84.9	86.4	89.6	92.4	94.1	96.0	97.0	97.0	97.7	98.1	98.6	98.8
84.9	86.4	89.6	92.4	94.2	96.6	97.6	97.6	98.2	98.7	99.3	100.0
84.9	86.4	89.6	92.4	94.2	96.6	97.6	97.6	98.2	98.7	99.3	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: NOV HOURS: 03-

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	26.1	26.3	27.0	27.4	28.1	28.1	28.1	28.1	28.1	28.1	28.2	28.2	2
GE 20000	28.2	28.4	29.2	29.8	30.4	30.4	30.4	30.6	30.6	30.6	30.7	30.7	3
GE 18000	28.3	28.6	29.3	29.9	30.6	30.6	30.6	30.7	30.7	30.7	30.8	30.8	3
GE 16000	28.3	28.6	29.3	29.9	30.6	30.6	30.6	30.7	30.7	30.7	30.8	30.8	3
GE 14000	29.1	29.3	30.1	30.7	31.3	31.3	31.3	31.4	31.4	31.4	31.6	31.6	3
GE 12000	29.7	29.9	30.7	31.2	31.9	31.9	31.9	32.0	32.0	32.0	32.1	32.1	3
GE 10000	32.2	32.4	33.2	33.8	34.7	34.7	34.7	34.8	34.8	34.8	34.9	34.9	3
GE 9000	33.0	33.2	34.0	34.6	35.4	35.4	35.4	35.6	35.6	35.6	35.7	35.7	3
GE 8000	34.0	34.3	35.2	35.8	36.8	36.8	36.8	36.9	36.9	36.9	37.0	37.0	3
GE 7000	34.6	34.9	35.8	36.3	37.3	37.3	37.3	37.4	37.4	37.4	37.6	37.6	3
GE 6000	34.7	35.0	35.9	36.4	37.4	37.4	37.4	37.6	37.6	37.6	37.7	37.7	3
GE 5000	36.7	37.0	37.9	38.4	39.4	39.4	39.4	39.7	39.7	39.7	39.8	39.8	3
GE 4500	37.8	38.1	39.0	39.6	40.6	40.6	40.6	40.8	40.8	40.8	40.9	40.9	4
GE 4000	40.4	40.8	41.7	42.2	43.3	43.3	43.3	43.6	43.6	43.6	43.7	43.7	4
GE 3500	42.1	42.4	43.3	43.9	45.0	45.0	45.0	45.2	45.2	45.2	45.3	45.3	4
GE 3000	46.4	46.9	47.8	48.7	49.9	49.9	49.9	50.1	50.1	50.1	50.2	50.2	5
GE 2500	54.4	55.0	56.0	56.7	58.3	58.3	58.4	59.0	59.1	59.1	59.2	59.2	5
GE 2000	59.7	60.2	61.3	62.3	63.9	64.0	64.1	64.8	64.9	64.9	65.0	65.0	5
GE 1800	62.8	63.3	64.7	65.8	67.7	67.8	67.9	68.7	68.9	68.9	69.0	69.0	5
GE 1500	67.7	68.2	69.6	70.7	72.6	73.0	73.3	74.2	74.6	74.6	74.7	74.7	7
GE 1200	70.8	71.3	72.7	73.9	75.8	76.3	76.8	78.0	78.3	78.3	78.4	78.4	7
GE 1000	72.1	72.8	74.2	75.6	77.9	78.6	79.4	81.0	81.3	81.3	81.7	81.7	8
GE 900	73.6	74.2	76.0	77.3	79.8	80.4	81.3	83.3	83.8	83.8	84.1	84.1	8
GE 800	73.9	74.6	76.3	77.8	80.3	81.0	82.0	84.2	84.8	84.8	85.1	85.1	8
GE 700	74.3	75.0	76.8	78.4	81.0	81.9	83.3	85.8	86.3	86.3	86.7	86.7	8
GE 600	74.8	75.8	77.6	79.4	82.2	83.4	85.0	87.9	88.4	88.6	89.0	89.0	8
GE 500	75.1	76.1	77.9	80.2	83.3	84.6	86.3	89.4	90.3	90.8	91.2	91.2	9
GE 400	75.3	76.3	78.1	80.6	83.7	84.9	86.8	90.2	91.2	91.8	92.2	92.2	9
GE 300	75.3	76.3	78.1	80.6	83.7	84.9	86.8	91.0	92.0	92.7	93.6	93.6	9
GE 200	75.3	76.3	78.1	80.7	84.1	85.4	87.3	92.0	93.8	95.0	96.4	96.6	9
GE 100	75.3	76.3	78.1	80.7	84.1	85.4	87.3	92.0	94.0	95.3	96.9	97.0	9
GE 000	75.3	76.3	78.1	80.7	84.1	85.4	87.3	92.0	94.0	95.3	96.9	97.0	9

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 03-05

VISIBILITY IN STATUTE MILES

CE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE	GE
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
27.4	28.1	28.1	28.1	28.1	28.1	28.1	28.2	28.2	28.2	28.2	28.2	28.3
29.4	30.4	30.4	30.4	30.6	30.6	30.6	30.7	30.7	30.7	30.7	30.7	30.8
29.9	30.6	30.6	30.6	30.7	30.7	30.7	30.8	30.8	30.8	30.8	30.8	30.9
29.7	30.6	30.6	30.6	30.7	30.7	30.7	30.8	30.8	30.8	30.8	30.8	30.9
31.7	31.3	31.3	31.3	31.4	31.4	31.4	31.6	31.6	31.6	31.6	31.6	31.7
31.2	31.9	31.9	31.9	32.0	32.0	32.0	32.1	32.1	32.1	32.1	32.1	32.2
33.3	34.7	34.7	34.7	34.8	34.8	34.8	34.9	34.9	34.9	34.9	34.9	35.0
34.5	35.4	35.4	35.4	35.6	35.6	35.6	35.7	35.7	35.7	35.7	35.7	35.8
35.3	35.8	36.8	36.8	36.9	36.9	36.9	37.0	37.0	37.0	37.0	37.0	37.1
35.3	37.3	37.3	37.3	37.4	37.4	37.4	37.6	37.6	37.6	37.6	37.6	37.7
36.4	37.4	37.4	37.4	37.6	37.6	37.6	37.7	37.7	37.7	37.7	37.7	37.8
37.4	37.4	39.4	39.4	39.7	39.7	39.7	39.8	39.8	39.8	39.8	39.8	39.9
37.5	40.6	40.6	40.6	40.8	40.8	40.8	40.9	40.9	40.9	40.9	40.9	41.0
38.2	43.3	43.3	43.3	43.6	43.6	43.6	43.7	43.7	43.7	43.7	43.7	43.8
38.0	45.0	45.0	45.0	45.2	45.2	45.2	45.3	45.3	45.3	45.3	45.3	45.4
37.7	49.9	49.9	49.9	50.1	50.1	50.1	50.2	50.2	50.2	50.2	50.2	50.3
38.7	58.3	58.3	58.4	59.0	59.1	59.1	59.2	59.2	59.2	59.2	59.2	59.3
38.3	63.9	64.0	64.1	64.8	64.9	64.9	65.0	65.0	65.0	65.0	65.0	65.1
38.5	67.7	67.8	67.9	68.7	68.9	68.9	69.0	69.0	69.0	69.0	69.0	69.1
38.7	72.6	73.0	73.3	74.2	74.6	74.6	74.7	74.7	74.7	74.7	74.7	74.8
38.9	75.8	76.3	76.8	78.0	78.3	78.3	78.4	78.4	78.4	78.4	78.4	78.6
38.5	77.9	78.6	79.4	81.0	81.3	81.3	81.7	81.7	81.7	81.7	81.7	81.8
37.3	79.8	80.4	81.3	83.3	83.8	83.8	84.1	84.1	84.1	84.1	84.1	84.2
37.3	80.3	81.0	82.0	84.2	84.8	84.8	85.1	85.1	85.2	85.2	85.2	85.3
37.4	81.0	81.9	83.3	85.8	86.3	86.3	86.7	86.7	86.8	86.8	86.8	86.9
37.4	82.2	83.4	85.0	87.9	88.4	88.6	89.0	89.0	89.2	89.2	89.2	89.3
38.2	83.3	84.6	86.3	89.4	90.3	90.8	91.2	91.2	91.4	91.4	91.6	91.7
38.6	83.7	84.9	86.8	90.2	91.2	91.8	92.2	92.2	92.4	92.4	92.7	92.8
38.6	83.7	84.9	86.8	91.0	92.0	92.7	93.6	93.6	93.8	93.8	94.2	94.3
38.7	84.1	85.4	87.3	92.0	93.8	95.0	96.4	96.6	96.9	97.2	97.8	97.9
38.7	84.1	85.4	87.3	92.0	94.0	95.3	96.9	97.0	97.3	97.9	99.1	100.0
38.7	84.1	85.4	87.3	92.0	94.0	95.3	96.9	97.0	97.3	97.9	99.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 7
LST TO UTC: + 5 MONTH: NOV HOURS: 06-0

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 1/4
NO CEIL	25.3	25.9	26.0	26.2	26.9	26.9	27.3	27.4	27.6	27.6	27.6	27.7	27	
GE 20000	27.4	28.0	28.2	28.4	29.3	29.4	29.9	30.0	30.2	30.3	30.3	30.4	30	
GE 18000	27.4	28.0	28.2	28.4	29.3	29.4	29.9	30.0	30.2	30.3	30.3	30.4	30	
GE 16000	27.4	28.0	28.2	28.4	29.3	29.4	29.9	30.0	30.2	30.3	30.3	30.4	30	
GE 14000	28.1	28.7	28.9	29.1	30.0	30.1	30.6	30.7	30.9	31.0	31.0	31.1	31	
GE 12000	28.3	28.9	29.1	29.3	30.2	30.3	30.8	30.9	31.1	31.2	31.2	31.3	31	
GE 10000	29.9	30.4	30.7	30.9	32.0	32.1	32.7	32.8	33.0	33.1	33.1	33.2	33	
GE 9000	30.4	31.0	31.2	31.4	32.7	32.8	33.3	33.4	33.7	33.8	33.8	33.9	33	
GE 8000	31.7	32.2	32.4	32.9	34.2	34.4	35.0	35.2	35.4	35.6	35.6	35.7	35	
GE 7000	32.1	32.7	32.9	33.3	34.7	34.9	35.4	35.7	35.9	36.0	36.0	36.1	36	
GE 6000	33.0	33.7	33.9	34.3	35.8	36.0	36.6	36.9	37.0	37.1	37.1	37.2	37	
GE 5000	34.3	35.0	35.2	35.8	37.3	37.6	38.1	38.3	38.6	38.7	38.7	38.8	38	
GE 4500	35.1	35.8	36.0	36.8	38.4	38.7	39.2	39.4	39.7	39.8	39.8	39.9	39	
GE 4000	38.2	38.9	39.1	39.9	41.7	41.9	42.4	42.7	43.0	43.1	43.1	43.2	43	
GE 3500	40.1	40.8	41.0	41.8	43.6	43.8	44.3	44.6	44.9	45.0	45.0	45.1	45	
GE 3000	42.4	43.1	43.3	44.1	45.9	46.1	46.8	47.0	47.3	47.4	47.4	47.6	47	
GE 2500	48.1	48.8	49.0	49.8	52.0	52.3	53.0	53.2	53.8	53.9	53.9	54.0	54	
GE 2000	56.1	57.0	57.4	58.3	60.8	61.1	62.0	62.2	62.8	62.9	62.9	63.0	63	
GE 1800	59.4	60.3	60.3	61.7	64.2	64.6	65.6	65.9	66.4	66.6	66.6	66.7	66	
GE 1500	63.2	64.1	65.2	66.2	69.1	69.6	71.1	71.8	72.4	72.6	72.6	72.7	72	
GE 1200	65.8	66.7	67.8	69.0	72.0	72.8	74.1	74.9	75.6	75.8	75.8	75.9	75	
GE 1000	67.9	68.8	70.2	71.8	75.0	75.8	77.7	78.4	79.3	79.6	79.6	79.7	79	
GE 900	69.0	69.9	71.4	73.0	76.3	77.1	79.0	79.8	80.8	81.1	81.2	81.3	81	
GE 800	69.2	70.1	71.8	73.3	76.9	77.8	79.9	80.8	81.9	82.7	82.8	83.0	83	
GE 700	69.7	70.6	72.2	73.8	77.4	78.4	80.7	81.8	82.9	83.9	84.0	84.2	84	
GE 600	70.0	71.0	72.7	74.6	78.4	79.4	81.9	83.8	84.9	86.1	86.2	86.4	86	
GE 500	70.0	71.0	73.0	75.2	79.3	80.9	83.8	86.3	87.4	89.0	89.4	89.7	89	
GE 400	70.1	71.2	73.2	75.6	80.1	81.7	84.9	88.3	90.0	91.7	92.3	92.6	92	
GE 300	70.1	71.2	73.2	75.7	80.4	82.0	85.6	89.6	91.9	93.8	94.6	94.9	95	
GE 200	70.1	71.2	73.2	75.8	80.6	82.4	86.0	90.2	92.7	94.7	95.9	96.3	96	
GE 100	70.1	71.2	73.2	75.8	80.6	82.4	86.0	90.2	92.7	94.8	96.1	96.6	97	
GE 000	70.1	71.2	73.2	75.8	80.6	82.4	86.0	90.2	92.7	94.8	96.1	96.6	97	

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 06-08

VISIBILITY IN STATUTE MILES

CEILING	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
26.2	26.9	26.9	27.3	27.4	27.6	27.6	27.6	27.7	27.7	27.7	27.8	27.8	27.8
28.4	29.3	29.4	29.9	30.0	30.2	30.3	30.3	30.4	30.4	30.4	30.6	30.6	30.6
28.4	29.3	29.4	29.9	30.0	30.2	30.3	30.3	30.4	30.4	30.4	30.6	30.6	30.6
29.1	30.0	30.1	30.6	30.7	30.9	31.0	31.0	31.1	31.1	31.1	31.2	31.2	31.2
29.3	30.2	30.3	30.8	30.9	31.1	31.2	31.2	31.3	31.3	31.3	31.4	31.4	31.4
30.9	32.0	32.1	32.7	32.8	33.0	33.1	33.1	33.2	33.2	33.2	33.3	33.3	33.3
31.4	32.7	32.8	33.3	33.4	33.7	33.8	33.8	33.9	33.9	33.9	34.0	34.0	34.0
32.7	34.2	34.4	35.0	35.2	35.4	35.6	35.6	35.7	35.7	35.7	35.8	35.8	35.8
33.3	34.7	34.9	35.4	35.7	35.9	36.0	36.0	36.1	36.1	36.1	36.2	36.2	36.2
34.3	35.8	36.0	36.6	36.8	37.0	37.1	37.1	37.2	37.2	37.2	37.3	37.3	37.3
35.3	37.3	37.6	38.1	38.3	38.6	38.7	38.7	38.8	38.8	38.8	38.9	38.9	38.9
36.3	38.4	38.7	39.2	39.4	39.7	39.8	39.8	39.9	39.9	39.9	40.0	40.0	40.0
39.7	41.7	41.9	42.4	42.7	43.0	43.1	43.1	43.2	43.2	43.2	43.3	43.3	43.3
41.8	43.6	43.8	44.3	44.6	44.9	45.0	45.0	45.1	45.1	45.1	45.2	45.2	45.2
44.1	45.9	46.1	46.8	47.0	47.3	47.4	47.4	47.6	47.6	47.6	47.7	47.7	47.7
49.8	52.0	52.3	53.0	53.2	53.8	53.9	53.9	54.0	54.0	54.0	54.1	54.1	54.1
50.3	52.8	53.1	53.7	53.9	54.5	54.6	54.6	54.7	54.7	54.7	54.8	54.8	54.8
51.7	54.2	54.6	55.6	55.9	56.4	56.6	56.6	56.7	56.7	56.7	56.8	56.8	56.8
56.2	59.1	59.8	61.1	61.8	62.4	62.6	62.6	62.7	62.7	62.7	62.8	62.8	62.8
59.0	62.0	62.8	64.1	64.9	65.6	65.8	65.8	65.9	65.9	65.9	66.0	66.0	66.0
71.3	75.0	75.8	77.7	78.4	79.3	79.6	79.6	79.7	79.7	79.7	79.8	79.8	79.8
73.0	76.3	77.1	79.0	79.8	80.8	81.1	81.2	81.3	81.3	81.3	81.4	81.4	81.4
73.3	76.9	77.8	79.9	80.8	81.9	82.7	82.8	83.0	83.0	83.0	83.1	83.1	83.1
73.8	77.4	78.4	80.7	81.8	82.9	83.9	84.0	84.2	84.2	84.2	84.3	84.3	84.3
74.6	78.4	79.4	81.9	83.8	84.9	86.1	86.2	86.4	86.6	86.6	86.7	86.7	86.7
75.2	79.3	80.9	83.8	86.3	87.4	89.0	89.4	89.7	89.8	89.8	90.2	90.2	90.2
75.5	80.1	81.7	84.9	88.3	90.0	91.7	92.3	92.6	92.7	92.7	93.2	93.2	93.2
75.7	80.4	82.0	85.6	89.6	91.9	93.8	94.6	94.9	95.2	95.2	95.9	96.1	96.1
75.8	80.6	82.4	86.0	90.2	92.7	94.7	95.9	96.3	96.8	96.9	97.9	98.1	98.1
75.8	80.6	82.4	86.0	90.2	92.7	94.8	96.1	96.6	97.1	97.7	99.0	100.0	100.0
75.8	80.6	82.4	86.0	90.2	92.7	94.8	96.1	96.6	97.1	97.7	99.0	100.0	100.0

900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
 LST TO UTC: + 5 MONTH: NOV HOURS: 09

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	22.0	22.6	22.8	22.9	23.7	23.7	23.9	23.9	24.0	24.1	24.1	24.1
GE 20000	26.7	27.3	27.7	27.9	28.7	28.7	28.9	29.1	29.2	29.3	29.3	29.3
GE 18000	26.7	27.6	27.9	28.1	28.9	28.9	29.1	29.3	29.4	29.6	29.6	29.6
GE 16000	26.9	27.8	28.1	28.3	29.1	29.1	29.4	29.7	29.8	29.9	29.9	29.9
GE 14000	27.3	28.2	28.7	29.0	29.9	29.9	30.2	30.4	30.6	30.7	30.7	30.7
GE 12000	28.0	28.9	29.3	29.8	30.7	30.7	31.0	31.2	31.3	31.4	31.4	31.4
GE 10000	29.8	30.8	31.2	31.9	33.0	33.0	33.4	33.7	33.8	33.9	33.9	33.9
GE 9000	29.9	30.9	31.3	32.0	33.1	33.1	33.6	33.8	33.9	34.0	34.0	34.0
GE 8000	31.4	32.4	32.9	33.7	35.1	35.1	35.1	35.3	36.4	36.6	36.6	36.6
GE 7000	32.7	33.7	34.1	34.9	36.4	36.6	37.7	37.9	38.0	38.1	38.1	38.1
GE 6000	33.2	34.4	34.9	35.7	37.2	37.3	38.6	38.8	38.9	39.0	39.0	39.0
GE 5000	34.3	36.0	36.6	37.4	39.1	39.2	40.6	40.8	40.9	41.0	41.0	41.0
GE 4500	35.4	35.7	37.4	38.3	40.0	40.1	41.4	41.7	41.8	41.9	41.9	41.9
GE 4000	36.3	38.1	39.9	39.8	41.6	41.7	43.0	43.2	43.3	43.4	43.4	43.4
GE 3500	37.7	38.9	39.9	40.8	42.6	42.7	44.0	44.2	44.3	44.4	44.4	44.4
GE 3000	40.3	42.0	43.0	43.9	45.7	45.8	47.1	47.3	47.4	47.6	47.6	47.6
GE 2500	45.7	47.0	49.2	49.2	51.3	51.4	52.8	53.2	53.4	53.6	53.6	53.6
GE 2000	54.6	55.9	57.4	58.7	61.1	61.2	63.1	63.6	63.8	64.0	64.0	64.0
GE 1800	57.4	58.8	60.4	61.9	64.6	64.7	66.6	67.1	67.3	67.6	67.6	67.6
GE 1500	60.6	62.1	64.3	66.0	68.3	68.9	71.0	71.6	72.3	72.6	72.7	72.7
GE 1200	63.0	64.8	67.1	68.8	71.7	71.9	74.1	74.7	75.4	75.7	75.8	75.8
GE 1000	64.4	66.4	69.3	71.3	74.3	74.6	77.0	77.7	78.6	79.8	79.1	79.1
GE 900	64.7	66.8	69.8	71.9	75.0	75.4	77.9	78.6	79.6	79.8	80.1	80.1
GE 800	65.0	67.1	70.2	72.4	75.8	76.3	78.9	79.9	81.2	81.7	82.1	82.1
GE 700	65.0	67.1	70.6	73.1	77.2	78.0	80.6	82.0	83.4	84.1	85.0	85.0
GE 600	65.6	67.8	71.3	73.9	78.1	78.9	81.9	83.7	85.3	86.1	87.3	87.4
GE 500	65.6	67.8	71.4	74.2	78.8	79.6	82.7	85.0	86.9	87.7	89.2	89.3
GE 400	65.9	68.1	71.9	74.5	79.3	80.2	83.4	85.5	88.9	89.8	91.7	91.9
GE 300	65.9	68.1	71.9	74.3	79.3	80.2	83.7	85.0	90.8	92.0	94.2	94.4
GE 200	65.9	68.1	71.9	74.3	79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.9
GE 100	65.9	68.1	71.9	74.8	79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.9
GE 000	65.9	68.1	71.9	74.3	79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.9

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 09-11

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
23.7	23.7	23.9	23.9	24.0	24.1	24.1	24.1	24.1	24.2	24.4	24.6
23.7	28.7	28.9	29.1	29.2	29.3	29.3	29.3	29.3	29.4	29.7	29.9
28.9	28.9	29.1	29.3	29.4	29.6	29.6	29.6	29.6	29.7	29.9	30.1
29.1	29.1	29.4	29.7	29.8	29.9	29.9	29.9	29.9	30.0	30.2	30.4
29.9	29.9	30.2	30.4	30.6	30.7	30.7	30.7	30.7	30.8	31.0	31.2
30.7	30.7	31.0	31.2	31.3	31.4	31.4	31.4	31.4	31.6	31.8	32.0
33.0	33.0	33.4	33.7	33.8	33.9	33.9	33.9	33.9	34.0	34.2	34.4
33.1	33.1	33.6	33.8	33.9	34.0	34.0	34.0	34.0	34.1	34.3	34.6
35.1	35.1	36.1	36.3	36.4	36.6	36.6	36.6	36.6	36.7	36.9	37.1
36.4	36.6	37.7	37.9	38.0	38.1	38.1	38.1	38.1	38.2	38.4	38.7
37.2	37.3	38.6	38.8	38.9	39.0	39.0	39.0	39.0	39.1	39.3	39.6
39.1	39.2	40.6	40.8	40.9	41.0	41.0	41.0	41.0	41.1	41.3	41.6
40.0	40.1	41.4	41.7	41.8	41.9	41.9	41.9	41.9	42.0	42.2	42.4
41.6	41.7	43.0	43.2	43.3	43.4	43.4	43.4	43.4	43.6	43.8	44.0
42.6	42.7	44.0	44.2	44.3	44.4	44.4	44.4	44.4	44.6	44.8	45.0
45.7	45.8	47.1	47.3	47.4	47.6	47.6	47.6	47.6	47.7	47.9	48.1
51.3	51.4	52.8	53.2	53.4	53.6	53.6	53.6	53.6	53.7	53.9	54.1
61.1	61.2	63.1	63.6	63.8	64.0	64.0	64.0	64.0	64.1	64.3	64.6
64.6	64.7	66.6	67.1	67.3	67.6	67.6	67.6	67.7	67.8	68.0	68.2
68.3	68.9	71.0	71.6	72.3	72.6	72.7	72.7	72.8	72.9	73.1	73.3
71.7	71.9	74.1	74.7	75.4	75.7	75.8	75.8	75.9	76.0	76.2	76.4
74.3	74.6	77.0	77.7	78.6	78.8	79.1	79.1	79.2	79.3	79.6	79.8
75.0	75.4	77.9	78.6	79.6	79.8	80.1	80.1	80.2	80.3	80.6	80.8
75.8	76.3	78.9	79.9	81.2	81.7	82.1	82.1	82.3	82.4	82.7	82.9
77.2	78.0	80.6	82.0	83.4	84.1	85.0	85.0	85.3	85.4	85.7	85.9
78.1	78.9	81.9	83.7	85.3	86.1	87.3	87.4	87.8	87.9	88.1	88.3
78.3	79.6	82.7	85.0	86.9	87.7	89.2	89.3	89.7	90.0	90.3	90.6
79.3	80.2	83.4	86.6	88.9	89.8	91.7	91.9	92.3	92.7	93.0	93.2
79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.4	95.0	95.6	95.9	96.4
79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.9	95.7	96.7	97.4	98.2
79.3	80.2	83.7	86.0	90.8	92.0	94.2	94.9	95.8	97.2	98.8	100.0
79.3	80.2	83.7	88.0	90.8	92.0	94.2	94.9	95.8	97.2	98.8	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBIL
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
 LST TO UTC: + 5 MONTH: NOV HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	25.0	25.3	25.6	25.6	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.8
GE 20000	29.5	30.3	30.3	31.1	31.9	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0
GE 18000	29.9	30.7	31.1	31.4	32.2	32.3	32.3	32.3	32.3	32.3	32.3	32.3	32.3	32.3
GE 16000	29.9	30.8	31.3	31.7	32.4	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6
GE 14000	30.8	31.7	32.2	32.6	33.3	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4
GE 12000	32.0	32.9	33.4	33.8	34.6	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.7
GE 10000	35.4	36.4	37.0	37.4	38.2	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3
GE 9000	35.9	36.9	37.4	37.9	38.7	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8
GE 8000	37.5	38.6	39.2	39.7	40.4	40.6	40.6	40.7	40.7	40.7	40.7	40.7	40.7	40.7
GE 7000	38.9	39.9	40.6	41.0	42.1	42.2	42.2	42.3	42.3	42.3	42.3	42.3	42.3	42.3
GE 6000	39.4	40.4	41.2	41.7	42.8	42.9	43.0	43.1	43.1	43.1	43.1	43.1	43.1	43.1
GE 5000	41.3	42.6	43.3	43.8	45.2	45.3	45.4	45.6	45.6	45.6	45.6	45.6	45.6	45.6
GE 4500	42.0	43.2	44.1	44.6	46.0	46.1	46.2	46.3	46.3	46.3	46.3	46.3	46.3	46.3
GE 4000	43.0	44.2	45.3	45.8	47.2	47.3	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.7
GE 3500	43.9	45.1	46.2	46.7	48.2	48.3	48.6	48.7	48.7	48.7	48.7	48.7	48.7	48.7
GE 3000	46.2	47.4	48.7	49.1	50.7	50.8	51.0	51.1	51.2	51.2	51.2	51.2	51.2	51.2
GE 2500	52.2	53.4	54.8	55.2	55.9	57.0	57.3	57.4	57.7	57.7	57.7	57.7	57.7	57.7
GE 2000	59.8	61.1	62.8	63.3	65.4	65.7	66.3	66.4	66.8	66.8	66.9	66.9	66.9	66.9
GE 1900	61.9	63.2	65.1	65.8	68.3	68.6	69.2	69.3	69.7	69.7	69.8	69.8	69.8	69.8
GE 1500	64.3	66.0	68.3	69.0	71.8	72.1	73.0	73.2	74.1	74.2	74.4	74.4	74.4	74.4
GE 1200	66.6	68.6	70.9	71.7	74.8	75.2	76.3	76.9	77.9	78.0	78.2	78.2	78.2	78.2
GE 1000	67.4	69.4	72.3	73.1	76.4	76.9	78.2	78.9	80.0	80.3	80.8	80.8	80.8	80.9
GE 900	67.9	70.0	73.0	74.1	77.6	78.1	79.4	80.1	81.2	81.7	82.1	82.1	82.1	82.2
GE 800	68.3	70.6	73.6	74.8	78.9	79.6	81.6	82.3	83.4	83.9	84.4	84.6	84.6	84.7
GE 700	68.7	70.9	74.1	75.6	80.0	81.2	83.6	84.4	85.6	86.0	86.7	86.8	86.8	86.9
GE 600	68.7	71.3	74.9	76.3	81.1	82.7	85.4	86.4	87.9	88.3	89.2	89.4	89.4	89.6
GE 500	69.1	71.8	75.4	76.9	81.8	83.6	86.7	88.1	89.7	90.6	91.8	92.0	92.0	92.1
GE 400	69.1	71.8	75.6	77.0	82.0	84.0	87.2	89.1	90.9	92.0	93.4	93.7	94.0	94.0
GE 300	69.2	72.0	75.9	77.3	82.3	84.3	87.7	89.7	90.0	92.3	94.0	95.7	96.1	96.4
GE 200	69.2	72.0	75.9	77.3	82.3	84.3	87.7	90.2	92.6	94.2	96.1	97.0	97.4	97.4
GE 100	69.2	72.0	75.9	77.3	82.3	84.3	87.7	90.2	92.6	94.2	96.1	97.0	97.6	97.6

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

IDN NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 12-14

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
25.5	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.8	25.9	25.9	25.9
31.1	31.9	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.1	32.1	32.1
31.4	32.2	32.3	32.3	32.3	32.3	32.3	32.3	32.3	32.3	32.4	32.4	32.4
31.7	32.4	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.7	32.7	32.7
32.5	33.3	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.4	33.6	33.6	33.6
33.8	34.6	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.7	34.8	34.8	34.8
37.4	38.2	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.4	38.4	38.4
37.9	38.7	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.8	38.9	38.9	38.9
39.7	40.4	40.6	40.6	40.7	40.7	40.7	40.7	40.7	40.7	40.8	40.8	40.8
41.0	42.1	42.2	42.2	42.3	42.3	42.3	42.3	42.3	42.3	42.4	42.4	42.4
41.7	42.8	42.9	43.0	43.1	43.1	43.1	43.1	43.1	43.1	43.2	43.2	43.2
43.3	45.2	45.3	45.4	45.6	45.6	45.6	45.6	45.6	45.6	45.7	45.7	45.7
44.5	46.0	46.1	46.2	46.3	46.3	46.3	46.3	46.3	46.3	46.4	46.4	46.4
45.3	47.2	47.3	47.6	47.7	47.7	47.7	47.7	47.7	47.7	47.8	47.8	47.8
46.7	48.2	48.3	48.6	48.7	48.7	48.7	48.7	48.7	48.7	48.8	48.8	48.8
49.1	50.7	50.8	51.0	51.1	51.2	51.2	51.2	51.2	51.2	51.3	51.3	51.3
55.2	55.9	57.0	57.3	57.4	57.7	57.7	57.7	57.7	57.7	57.8	57.8	57.8
63.3	65.4	65.7	66.3	66.4	66.8	66.8	66.9	66.9	66.9	67.0	67.0	67.0
65.9	68.3	68.6	69.2	69.3	69.7	69.7	69.8	69.8	69.8	69.9	69.9	69.9
69.0	71.8	72.1	73.0	73.2	74.1	74.2	74.4	74.4	74.4	74.6	74.6	74.6
71.7	74.3	75.2	76.3	76.9	77.9	78.0	78.2	78.2	78.2	78.3	78.3	78.3
73.1	76.4	76.9	78.2	78.9	80.0	80.3	80.8	80.8	80.9	81.0	81.0	81.0
74.1	77.6	78.1	79.4	80.1	81.2	81.7	82.1	82.1	82.2	82.3	82.3	82.3
74.8	78.9	79.6	81.5	82.3	83.4	83.9	84.4	84.6	84.7	84.8	84.8	84.8
75.6	80.0	81.2	83.6	84.4	85.6	86.0	86.7	86.8	86.9	87.0	87.0	87.0
76.3	81.1	82.7	85.4	86.4	87.9	88.3	89.2	89.4	89.6	89.7	89.7	89.7
76.9	81.8	83.6	86.7	88.1	89.7	90.6	91.8	92.0	92.1	92.2	92.2	92.2
77.0	82.0	84.0	87.2	89.1	90.9	92.0	93.4	93.7	94.0	94.1	94.2	94.2
77.3	82.3	84.3	87.7	90.0	92.3	94.0	95.7	96.1	96.4	96.6	97.0	97.1
77.3	82.3	84.3	87.7	90.2	92.6	94.2	96.1	97.0	97.4	98.0	98.8	99.0
77.3	82.3	84.3	87.7	90.2	92.6	94.2	96.1	97.0	97.6	98.4	99.4	100.0
77.3	82.3	84.3	87.7	90.2	92.6	94.2	96.1	97.0	97.6	98.4	99.4	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: NOV HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	26.7	26.9	26.9	27.0	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1
GE 20000	31.7	32.0	32.4	32.5	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
GE 18000	32.2	32.6	33.0	33.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
GE 16000	32.2	32.6	33.0	33.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
GE 14000	33.1	33.4	33.9	34.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
GE 12000	34.1	34.4	34.9	35.0	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
GE 10000	37.7	38.0	38.6	38.7	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
GE 9000	38.4	38.9	39.4	39.6	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
GE 8000	40.3	40.8	41.4	41.6	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8
GE 7000	41.2	41.7	42.3	42.4	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
GE 6000	42.2	42.7	43.3	43.4	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9
GE 5000	45.1	45.6	46.2	46.3	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8
GE 4500	45.8	46.2	46.9	47.0	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4
GE 4000	47.8	48.2	48.9	49.0	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
GE 3500	49.2	49.7	50.3	50.4	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9	50.9
GE 3000	51.6	52.1	52.8	52.9	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4
GE 2500	57.2	57.9	58.9	59.1	59.9	59.9	60.2	60.3	60.6	60.7	60.7	60.7	60.7	60.7
GE 2000	63.0	63.8	65.3	66.2	67.3	67.3	67.8	68.6	69.0	69.2	69.4	69.4	69.4	69.4
GE 1800	65.6	66.3	68.6	69.0	70.1	70.1	70.6	71.3	71.8	72.0	72.2	72.2	72.2	72.2
GE 1500	67.9	68.8	71.9	72.4	73.6	73.6	74.2	75.6	76.2	76.4	76.7	76.7	76.7	76.7
GE 1200	70.1	71.0	74.1	74.8	76.1	76.2	77.0	78.4	79.2	79.4	79.7	79.7	79.7	79.7
GE 1000	71.3	72.8	75.9	76.6	77.9	78.0	79.0	80.7	81.4	81.9	82.0	82.0	82.0	82.0
GE 900	72.1	73.3	76.4	77.3	78.7	78.8	79.9	81.6	82.3	82.8	83.0	83.0	83.0	83.0
GE 800	72.4	73.8	77.1	78.1	79.7	80.0	81.2	83.0	84.0	84.6	84.9	84.9	84.9	84.9
GE 700	73.0	74.3	77.9	79.8	81.7	82.1	83.4	85.4	86.8	87.6	88.1	88.1	88.1	88.1
GE 600	73.2	74.7	78.2	80.1	82.2	82.7	84.1	86.1	87.6	88.4	89.2	89.2	89.2	89.2
GE 500	73.4	74.9	78.6	80.7	82.9	83.4	85.0	87.6	89.1	90.4	91.4	91.4	91.4	91.4
GE 400	73.6	75.0	79.1	81.3	83.8	84.6	86.7	90.0	92.3	94.0	95.3	95.4	95.4	95.4
GE 300	73.7	75.1	79.3	81.6	84.1	84.9	87.3	90.7	93.7	95.6	97.0	97.1	97.1	97.1
GE 200	73.7	75.1	79.4	81.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.1	98.1
GE 100	73.7	75.1	79.4	81.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.1	98.1
GE 000	73.7	75.1	79.4	81.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.1	98.1

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 15-17

VISIBILITY IN STATUTE MILES

CEILING	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
7.0	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1	27.1
6.5	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
6.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
5.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
4.0	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
3.0	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
2.7	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9	38.9
2.5	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8	39.8
1.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8	41.8
1.4	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9	42.9
1.4	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9	43.9
1.3	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8	46.8
1.0	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4	47.4
1.0	49.4	49.4	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6	49.6
1.4	50.9	50.9	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
2.0	53.4	53.4	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
1.1	59.9	59.9	60.2	60.3	60.6	60.7	60.7	60.7	60.7	60.7	60.7	60.7
1.2	57.3	67.3	67.8	68.6	69.0	69.2	69.4	69.4	69.4	69.4	69.4	69.4
1.0	70.1	70.1	70.6	71.3	71.8	72.0	72.2	72.2	72.2	72.2	72.2	72.2
1.4	73.6	73.6	74.2	75.6	76.2	76.4	76.7	76.7	76.7	76.7	76.7	76.7
1.5	76.1	75.2	77.0	78.4	79.2	79.4	79.7	79.7	79.7	79.7	79.7	79.7
1.5	77.9	78.0	79.0	80.7	81.4	81.8	82.0	82.0	82.0	82.0	82.0	82.0
1.3	78.7	78.8	79.9	81.6	82.3	82.8	83.0	83.0	83.0	83.0	83.0	83.0
1.1	77.7	80.0	81.2	83.0	84.0	84.6	84.9	84.9	85.1	85.1	85.1	85.1
1.5	81.7	82.1	83.4	85.4	86.8	87.6	88.1	88.1	88.3	88.3	88.3	88.3
1.1	82.2	82.7	84.1	86.1	87.6	88.4	89.2	89.2	89.4	89.4	89.4	89.4
1.7	82.9	83.4	85.0	87.6	89.1	90.4	91.4	91.4	91.9	91.9	91.9	91.9
1.3	83.8	84.6	86.7	90.0	92.3	94.0	95.3	95.4	95.9	95.9	95.9	95.9
1.6	84.1	84.9	87.3	90.7	93.7	95.6	97.0	97.1	97.8	97.8	97.9	97.9
1.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.8	99.0	99.1	99.1
1.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.8	99.0	99.3	100.0
1.7	84.2	85.0	87.6	91.0	94.1	96.1	97.9	98.1	98.8	99.0	99.3	100.0

OPERATING LOCATION *A*
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: NOV HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	29.6	29.8	30.0	30.2	30.6	30.6	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
GE 20000	33.8	34.2	34.4	35.0	35.3	35.3	35.8	35.8	35.9	35.9	35.9	35.9	35.9	35.9
GE 18000	34.1	34.6	34.8	35.3	35.7	35.7	36.1	36.1	36.2	36.2	36.2	36.2	36.2	36.2
GE 16000	34.1	34.6	34.8	35.3	35.7	35.7	36.1	36.1	36.2	36.2	36.2	36.2	36.2	36.2
GE 14000	35.0	35.4	35.7	36.2	36.6	36.6	37.0	37.0	37.1	37.1	37.1	37.1	37.1	37.1
GE 12000	36.0	36.4	36.7	37.2	37.6	37.6	38.0	38.0	38.1	38.1	38.1	38.1	38.1	38.1
GE 10000	38.0	38.4	38.7	39.2	39.7	39.7	40.1	40.1	40.2	40.2	40.2	40.2	40.2	40.2
GE 9000	38.3	38.8	39.0	39.6	40.0	40.0	40.4	40.4	40.6	40.6	40.6	40.6	40.6	40.6
GE 8000	40.7	41.2	41.5	42.2	42.8	42.8	43.2	43.3	43.4	43.4	43.4	43.4	43.4	43.4
GE 7000	41.9	42.4	42.6	43.4	44.0	44.0	44.4	44.6	44.7	44.7	44.7	44.7	44.7	44.7
GE 6000	42.9	43.4	43.8	44.6	45.1	45.1	45.6	45.7	45.8	45.8	45.8	45.8	45.8	45.8
GE 5000	44.3	44.9	45.2	46.0	46.6	46.6	47.0	47.1	47.2	47.2	47.2	47.2	47.2	47.2
GE 4500	45.4	46.0	46.3	47.1	47.7	47.7	48.1	48.2	48.3	48.3	48.3	48.3	48.3	48.3
GE 4000	47.3	47.9	48.3	49.3	49.9	49.9	50.3	50.4	50.6	50.6	50.6	50.6	50.6	50.6
GE 3500	48.6	49.1	49.6	50.6	51.1	51.1	51.6	51.7	51.8	51.8	51.8	51.8	51.8	51.8
GE 3000	52.2	52.8	53.2	54.4	55.2	55.2	55.8	55.9	56.0	56.0	56.0	56.0	56.0	56.0
GE 2500	57.1	57.7	58.1	59.5	60.6	60.6	61.1	61.3	61.4	61.4	61.4	61.4	61.4	61.4
GE 2000	62.6	63.2	64.0	65.7	66.9	67.0	67.9	68.2	68.3	68.3	68.3	68.3	68.3	68.3
GE 1800	64.9	65.6	66.6	68.2	69.4	69.6	70.6	71.0	71.1	71.1	71.1	71.1	71.1	71.1
GE 1500	68.0	68.7	69.7	71.3	72.9	73.1	74.3	74.9	75.0	75.1	75.1	75.1	75.1	75.1
GE 1200	70.4	71.3	72.9	74.9	77.0	77.2	78.8	79.6	79.7	79.8	79.8	79.8	79.8	79.8
GE 1000	72.1	73.1	74.9	77.2	79.3	79.6	81.6	82.4	82.7	82.8	82.8	82.8	82.8	82.8
GE 900	72.8	74.0	76.0	78.3	80.7	80.9	82.9	83.9	84.1	84.3	84.3	84.3	84.3	84.3
GE 800	73.2	74.6	76.3	79.3	82.2	82.4	84.4	85.7	85.9	86.2	86.2	86.2	86.2	86.2
GE 700	73.4	74.8	77.0	79.9	83.1	83.3	85.4	86.8	87.1	87.8	87.8	87.8	87.8	87.8
GE 600	73.6	74.9	77.2	80.1	83.7	83.9	86.6	88.2	88.7	89.7	89.7	89.7	89.7	89.7
GE 500	73.7	75.1	77.9	81.2	85.0	85.3	88.2	90.4	91.0	92.0	92.2	92.2	92.2	92.2
GE 400	73.9	75.2	78.1	81.7	85.4	85.8	88.8	91.1	92.2	93.6	93.8	93.8	93.8	93.8
GE 300	73.8	75.2	78.1	81.7	85.6	85.9	89.4	92.3	94.3	96.4	97.1	97.2	97.2	97.2
GE 200	73.8	75.2	78.1	81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.0	99.0
GE 100	73.8	75.2	78.1	81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.0	99.0
GE 000	73.8	75.2	78.1	81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.0	99.0

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.2	30.6	30.6	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0	31.0
35.0	35.3	35.3	35.3	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
35.3	35.7	35.7	36.1	36.1	36.2	36.2	36.2	36.2	36.2	36.2	36.2	36.2
35.3	35.7	35.7	36.1	36.1	36.2	36.2	36.2	36.2	36.2	36.2	36.2	36.2
36.2	36.6	36.6	37.0	37.0	37.1	37.1	37.1	37.1	37.1	37.1	37.1	37.1
37.2	37.6	37.6	38.0	38.0	38.1	38.1	38.1	38.1	38.1	38.1	38.1	38.1
39.2	39.7	39.7	40.1	40.1	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
39.6	40.0	40.0	40.4	40.4	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
42.2	42.8	42.8	43.2	43.3	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
43.4	44.0	44.0	44.4	44.6	44.7	44.7	44.7	44.7	44.7	44.7	44.7	44.7
44.6	45.1	45.1	45.6	45.7	45.8	45.8	45.8	45.8	45.8	45.8	45.8	45.8
46.0	46.6	46.6	47.0	47.1	47.2	47.2	47.2	47.2	47.2	47.2	47.2	47.2
47.1	47.7	47.7	48.1	48.2	48.3	48.3	48.3	48.3	48.3	48.3	48.3	48.3
49.3	49.9	49.9	50.3	50.4	50.6	50.6	50.6	50.6	50.6	50.6	50.6	50.6
50.6	51.1	51.1	51.6	51.7	51.8	51.8	51.8	51.8	51.8	51.8	51.8	51.8
54.4	55.2	55.2	55.8	55.9	56.0	56.0	56.0	56.0	56.0	56.0	56.0	56.0
59.5	60.6	60.6	61.1	61.3	61.4	61.4	61.4	61.4	61.4	61.4	61.4	61.4
65.7	66.9	67.0	67.9	68.2	68.3	68.3	68.3	68.3	68.3	68.3	68.3	68.3
68.2	69.4	69.6	70.6	71.0	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1
71.3	72.9	73.1	74.3	74.9	75.0	75.1	75.1	75.1	75.1	75.1	75.1	75.1
74.9	77.0	77.2	78.8	79.6	79.7	79.8	79.8	79.8	79.8	79.8	79.8	79.8
77.2	79.3	79.6	81.6	82.4	82.7	82.8	82.8	82.8	82.8	82.8	82.8	82.8
78.3	80.7	80.9	82.9	83.9	84.1	84.3	84.3	84.3	84.3	84.3	84.3	84.3
79.3	82.2	82.4	84.4	85.7	85.9	86.2	86.2	86.2	86.2	86.2	86.2	86.2
79.9	83.1	83.3	85.4	86.8	87.1	87.8	87.8	87.8	87.9	87.9	87.9	87.9
80.1	83.7	83.9	86.6	88.2	88.7	89.7	89.7	89.7	89.8	89.8	89.8	89.8
81.2	85.0	85.3	88.2	90.4	91.0	92.0	92.2	92.2	92.3	92.3	92.3	92.3
81.7	85.4	85.8	88.8	91.1	92.2	93.6	93.8	93.8	93.9	93.9	93.9	93.9
81.7	85.6	85.9	89.4	92.3	94.3	96.4	97.1	97.2	97.4	97.4	97.4	97.4
81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.3	99.3	99.3	99.3
81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.4	99.4	99.8	100.0
81.7	85.6	85.9	89.6	92.4	95.0	97.9	98.8	99.0	99.4	99.4	99.8	100.0

900

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: NOV HOURS: 21-

CEILING

VISIBILITY IN STATUTE MILES

IN FEET GE 7 GE 6 GE 5 GE 4 GE 3 GE 2 1/2 GE 2 GE 1 1/2 GE 1 1/4 GE 1 GE 3/4 GE 5/8

NO CEIL	29.1	29.2	29.8	30.2	30.9	30.9	31.2	31.3	31.3	31.6	31.6	31.6	3
GE 20000	33.2	33.3	34.0	34.6	35.2	35.2	35.6	35.9	35.9	36.1	36.1	36.1	36
GE 18000	33.6	33.7	34.3	34.9	35.6	35.6	35.9	36.2	36.2	36.4	36.4	36.4	36
GE 16000	33.6	33.7	34.3	34.9	35.6	35.6	35.9	36.2	36.2	36.4	36.4	36.4	36
GE 14000	33.8	33.9	34.6	35.1	35.8	35.8	36.1	36.4	36.4	36.7	36.7	36.7	36
GE 12000	34.8	34.9	35.6	36.1	36.8	36.8	37.1	37.4	37.4	37.7	37.7	37.7	37
GE 10000	36.0	36.1	36.8	37.3	38.2	38.2	38.7	39.0	39.0	39.2	39.2	39.2	39
GE 9000	36.2	36.3	37.0	37.6	38.4	38.4	38.9	39.2	39.2	39.4	39.4	39.4	39
GE 8000	37.8	37.9	38.9	39.4	40.3	40.3	40.8	41.1	41.1	41.3	41.3	41.3	41
GE 7000	38.4	38.6	39.6	40.1	41.0	41.0	41.4	41.8	41.8	42.0	42.0	42.0	42
GE 6000	38.9	39.0	40.0	40.6	41.4	41.4	41.9	42.2	42.2	42.4	42.4	42.4	42
GE 5000	40.7	40.9	41.9	42.4	43.3	43.3	43.8	44.1	44.1	44.3	44.3	44.3	44
GE 4500	42.0	42.2	43.3	43.9	44.9	44.9	45.3	45.7	45.7	45.9	45.9	45.9	45
GE 4000	44.6	44.9	46.0	46.6	47.7	47.7	48.1	48.4	48.4	48.7	48.7	48.7	48
GE 3500	46.2	46.6	47.7	48.2	49.3	49.3	49.8	50.1	50.1	50.3	50.3	50.3	50
GE 3000	50.2	50.7	51.8	52.6	53.7	53.7	54.2	54.6	54.6	54.8	54.8	54.8	54
GE 2500	54.7	55.1	56.6	57.3	58.8	58.8	59.4	59.8	59.8	60.0	60.0	60.0	60
GE 2000	62.1	62.9	64.6	65.6	67.4	67.4	68.1	68.4	68.4	68.7	68.7	68.7	68
GE 1800	64.7	65.6	67.2	68.2	70.1	70.1	71.0	71.3	71.4	71.7	71.7	71.7	71
GE 1500	69.2	70.1	72.0	73.0	75.0	75.2	76.1	76.6	76.8	77.0	77.0	77.0	77
GE 1200	70.8	71.7	73.6	74.9	76.9	77.1	78.2	78.7	78.9	79.1	79.1	79.1	79
GE 1000	73.3	74.2	76.4	77.9	80.0	80.2	81.7	82.3	82.7	83.0	83.0	83.0	83
GE 900	73.4	74.3	76.7	78.1	80.6	80.8	82.3	83.2	83.7	84.1	84.1	84.1	84
GE 800	74.2	75.3	77.7	79.1	81.8	82.0	84.1	85.4	85.9	86.4	86.4	86.4	86
GE 700	74.8	75.9	78.3	79.8	83.4	83.7	86.4	87.9	88.3	89.0	89.0	89.0	89
GE 600	75.0	76.2	78.8	80.8	84.6	85.0	88.2	89.7	90.1	90.8	90.8	90.8	90
GE 500	75.1	76.3	78.9	81.3	85.3	85.8	89.4	90.9	91.4	92.4	92.6	92.6	92
GE 400	75.2	76.4	79.2	82.1	86.3	86.8	90.8	92.6	93.3	94.4	94.7	94.7	94
GE 300	75.2	76.4	79.2	82.1	86.6	87.0	91.3	93.3	94.7	96.2	96.6	96.6	96
GE 200	75.2	76.4	79.2	82.1	86.8	87.2	91.6	93.8	95.7	97.6	98.2	98.3	98
GE 100	75.2	76.4	79.2	82.1	86.8	87.2	91.6	93.8	95.8	97.9	98.6	98.7	98
GE 000	75.2	76.4	79.2	82.1	86.8	87.2	91.6	93.8	95.8	97.9	98.6	98.7	98

TOTAL NUMBER OF OBSERVATIONS 900

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
D UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: 21-23

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.2	30.9	30.9	31.2	31.3	31.3	31.6	31.6	31.6	31.6	31.6	31.6	31.6
34.6	35.2	35.2	35.6	35.9	35.9	36.1	36.1	36.1	36.1	36.1	36.1	36.1
34.9	35.6	35.6	35.9	36.2	36.2	36.4	36.4	36.4	36.4	36.4	36.4	36.4
34.9	35.6	35.6	35.9	36.2	36.2	36.4	36.4	36.4	36.4	36.4	36.4	36.4
35.1	35.8	35.8	36.1	36.4	36.4	36.7	36.7	36.7	36.7	36.7	36.7	36.7
36.1	36.8	36.8	37.1	37.4	37.4	37.7	37.7	37.7	37.7	37.7	37.7	37.7
37.3	38.2	38.2	38.7	39.0	39.0	39.2	39.2	39.2	39.2	39.2	39.2	39.2
37.6	38.4	38.4	38.9	39.2	39.2	39.4	39.4	39.4	39.4	39.4	39.4	39.4
37.4	40.3	40.3	40.8	41.1	41.1	41.3	41.3	41.3	41.3	41.3	41.3	41.3
40.1	41.0	41.0	41.4	41.8	41.8	42.0	42.0	42.0	42.0	42.0	42.0	42.0
40.6	41.4	41.4	41.9	42.2	42.2	42.4	42.4	42.4	42.4	42.4	42.4	42.4
42.4	43.3	43.3	43.8	44.1	44.1	44.3	44.3	44.3	44.3	44.3	44.3	44.3
43.9	44.9	44.9	45.3	45.7	45.7	45.9	45.9	45.9	45.9	45.9	45.9	45.9
45.6	47.7	47.7	48.1	48.4	48.4	48.7	48.7	48.7	48.7	48.7	48.7	48.7
45.2	49.3	49.3	49.8	50.1	50.1	50.3	50.3	50.3	50.3	50.3	50.3	50.3
52.6	53.7	53.7	54.2	54.6	54.6	54.8	54.8	54.8	54.8	54.8	54.8	54.8
57.3	58.8	58.8	59.4	59.8	59.8	60.0	60.0	60.0	60.0	60.0	60.0	60.0
55.5	67.4	67.4	68.1	68.4	68.4	68.7	68.7	68.7	68.7	68.7	68.7	68.7
65.2	70.1	70.2	71.0	71.3	71.4	71.7	71.7	71.7	71.7	71.7	71.7	71.7
73.0	75.0	75.2	76.1	76.6	76.8	77.0	77.0	77.0	77.0	77.0	77.0	77.0
74.9	76.9	77.1	78.2	78.7	78.9	79.1	79.1	79.1	79.1	79.1	79.1	79.1
77.9	80.0	80.2	81.7	82.3	82.7	83.0	83.0	83.0	83.0	83.0	83.0	83.0
75.1	80.6	80.8	82.3	83.2	83.7	84.1	84.1	84.1	84.1	84.1	84.1	84.1
74.1	81.3	82.0	84.1	85.4	85.9	86.4	86.4	86.4	86.4	86.4	86.4	86.4
77.3	83.4	83.7	86.4	87.9	88.3	89.0	89.0	89.0	89.0	89.0	89.0	89.0
80.8	84.6	85.0	88.2	89.7	90.1	90.8	90.8	90.8	90.8	90.8	90.8	90.8
81.3	85.3	85.8	89.4	90.9	91.4	92.4	92.6	92.6	92.6	92.6	92.6	92.6
82.1	86.3	86.8	90.8	92.6	93.3	94.4	94.7	94.7	94.8	94.8	94.8	94.8
82.1	86.6	87.0	91.3	93.3	94.7	96.2	96.6	96.6	96.7	96.7	96.8	96.9
82.1	86.8	87.2	91.6	93.8	95.7	97.6	98.2	98.3	98.4	98.4	98.9	99.0
82.1	86.8	87.2	91.6	93.8	95.8	97.9	98.6	98.7	98.9	98.9	99.7	100.0
82.1	86.8	87.2	91.6	93.8	95.8	97.9	98.6	98.7	98.9	98.9	99.7	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: NOV HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	26.3	26.6	26.9	27.2	27.7	27.7	27.9	27.9	28.0	28.0	28.0	28.1	28.1
GE 20000	30.1	30.5	31.0	31.3	32.0	32.0	32.2	32.3	32.4	32.4	32.5	32.5	32.5
GE 18000	30.3	30.8	31.3	31.6	32.2	32.3	32.4	32.6	32.6	32.7	32.7	32.7	32.7
GE 16000	30.4	30.8	31.3	31.7	32.3	32.3	32.5	32.7	32.7	32.8	32.8	32.8	32.8
GE 14000	31.0	31.4	31.9	32.3	32.9	33.0	33.2	33.3	33.4	33.4	33.5	33.5	33.5
GE 12000	31.8	32.3	32.8	33.2	33.8	33.8	34.0	34.2	34.2	34.3	34.3	34.3	34.3
GE 10000	34.1	34.6	35.1	35.5	36.3	36.3	36.5	36.7	36.7	36.8	36.8	36.8	36.8
GE 9000	34.5	35.0	35.6	36.0	36.8	36.8	37.0	37.2	37.2	37.3	37.3	37.3	37.3
GE 8000	36.1	36.7	37.3	37.8	38.7	38.7	39.0	39.2	39.2	39.3	39.3	39.3	39.3
GE 7000	37.1	37.5	38.2	38.7	39.7	39.7	40.1	40.2	40.3	40.4	40.4	40.4	40.4
GE 6000	37.7	38.2	38.8	39.4	40.3	40.4	40.7	40.9	41.0	41.0	41.1	41.1	41.1
GE 5000	39.4	40.0	40.6	41.2	42.2	42.3	42.7	42.9	42.9	43.0	43.0	43.0	43.0
GE 4500	40.4	41.0	41.8	42.3	43.4	43.5	43.9	44.1	44.1	44.2	44.2	44.2	44.2
GE 4000	42.5	43.1	43.9	44.5	45.6	45.7	46.1	46.3	46.4	46.4	46.5	46.5	46.5
GE 3500	43.9	44.5	45.3	45.9	47.0	47.1	47.5	47.7	47.8	47.9	47.9	47.9	47.9
GE 3000	47.1	47.7	48.6	49.3	50.6	50.7	51.1	51.3	51.4	51.5	51.5	51.5	51.5
GE 2500	52.8	53.5	54.5	55.3	56.8	57.0	57.5	57.8	58.0	58.0	58.1	58.1	58.1
GE 2000	59.8	60.6	62.0	63.0	64.8	65.0	65.7	66.1	66.4	66.5	66.5	66.6	66.6
GE 1800	62.5	63.4	64.9	66.0	67.9	68.1	68.9	69.4	69.6	69.7	69.8	69.8	69.8
GE 1500	66.0	67.0	68.8	70.0	72.0	72.4	73.4	74.1	74.5	74.7	74.8	74.8	74.8
GE 1200	68.3	69.4	71.4	72.7	75.0	75.4	76.5	77.3	77.8	78.0	78.1	78.1	78.1
GE 1000	70.0	71.1	73.3	74.8	77.3	77.7	79.2	80.2	80.8	81.1	81.3	81.3	81.3
GE 900	70.7	71.9	74.3	75.9	78.5	79.0	80.6	81.7	82.4	82.7	82.9	82.9	82.9
GE 800	71.1	72.4	74.9	76.6	79.5	80.1	81.9	83.3	84.1	84.5	84.8	84.8	84.9
GE 700	71.5	72.8	75.4	77.3	80.7	81.4	83.4	85.0	85.8	86.5	86.8	86.9	87.0
GE 600	71.7	73.2	75.9	79.0	81.6	82.4	84.8	86.6	87.6	88.3	88.8	88.9	89.0
GE 500	72.0	73.4	76.4	78.8	82.6	83.6	86.3	88.6	89.7	90.7	91.4	91.4	91.6
GE 400	72.1	73.6	76.6	79.2	83.1	84.2	87.1	89.9	91.3	92.5	93.4	93.5	93.8
GE 300	72.1	73.6	76.7	79.3	83.3	84.4	87.6	90.9	92.3	94.4	95.5	95.7	96.0
GE 200	72.1	73.6	76.7	79.3	83.5	84.6	87.9	91.3	93.6	95.4	96.8	97.2	97.6
GE 100	72.1	73.6	76.7	79.3	83.5	84.6	87.9	91.3	93.6	95.6	97.0	97.3	97.9
GE 000	72.1	73.6	76.7	79.3	83.5	84.6	87.9	91.3	93.6	95.6	97.0	97.3	97.9

TOTAL NUMBER OF OBSERVATIONS 7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 ITC: + 5 MONTH: NOV HOURS: ALL

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
27.7	27.7	27.9	27.9	28.0	28.0	28.0	28.1	28.1	28.1	28.2	28.2	
32.0	32.0	32.2	32.3	32.4	32.4	32.4	32.5	32.5	32.5	32.5	32.6	32.6
32.2	32.3	32.4	32.6	32.7	32.7	32.7	32.8	32.8	32.8	32.8	32.9	32.9
32.3	32.3	32.5	32.7	32.7	32.8	32.8	32.8	32.8	32.8	32.9	32.9	33.0
32.9	33.0	33.2	33.3	33.4	33.4	33.4	33.5	33.5	33.5	33.5	33.6	33.6
33.8	33.8	34.0	34.2	34.2	34.3	34.3	34.3	34.3	34.3	34.4	34.4	34.5
36.3	36.3	36.5	36.7	36.7	36.8	36.8	36.8	36.8	36.8	36.9	36.9	37.0
36.8	36.8	37.0	37.2	37.2	37.3	37.3	37.3	37.3	37.3	37.4	37.4	37.5
38.7	38.7	39.0	39.2	39.2	39.3	39.3	39.3	39.3	39.3	39.4	39.4	39.5
39.7	39.7	40.1	40.2	40.3	40.4	40.4	40.4	40.4	40.4	40.5	40.5	40.6
40.3	40.4	40.7	40.9	41.0	41.0	41.1	41.1	41.1	41.1	41.1	41.2	41.3
42.2	42.3	42.7	42.9	42.9	43.0	43.0	43.0	43.0	43.0	43.1	43.1	43.2
43.4	43.5	43.9	44.1	44.1	44.2	44.2	44.2	44.2	44.2	44.3	44.3	44.4
45.5	45.7	46.1	46.3	46.4	46.4	46.5	46.5	46.5	46.5	46.5	46.6	46.7
47.0	47.1	47.5	47.7	47.8	47.9	47.9	47.9	47.9	47.9	48.0	48.0	48.1
50.6	50.7	51.1	51.3	51.4	51.5	51.5	51.5	51.5	51.5	51.6	51.6	51.7
56.3	57.0	57.5	57.8	58.0	58.0	58.1	58.1	58.1	58.1	58.1	58.2	58.3
54.8	65.0	65.7	66.1	66.4	66.5	66.5	66.5	66.6	66.6	66.6	66.7	66.7
67.9	68.1	68.9	69.4	69.6	69.7	69.8	69.8	69.8	69.8	69.9	69.9	70.0
72.0	72.4	73.4	74.1	74.5	74.7	74.8	74.8	74.8	74.8	74.8	74.9	75.0
75.0	75.4	76.5	77.3	77.8	78.0	78.1	78.1	78.1	78.1	78.2	78.2	78.3
77.3	77.7	79.2	80.2	80.8	81.1	81.3	81.3	81.3	81.3	81.4	81.4	81.5
73.5	79.0	80.6	81.7	82.4	82.7	82.9	82.9	82.9	82.9	83.0	83.0	83.1
79.5	80.1	81.9	83.3	84.1	84.5	84.8	84.8	84.8	84.9	85.0	85.0	85.1
80.7	81.4	83.4	85.0	85.8	86.5	86.8	86.9	87.0	87.0	87.0	87.1	87.2
81.6	82.4	84.8	86.6	87.6	88.3	88.8	88.9	89.0	89.1	89.1	89.1	89.2
82.6	83.6	86.3	83.6	89.7	90.7	91.4	91.4	91.6	91.7	91.8	91.8	91.9
83.1	84.2	87.1	89.9	91.3	92.5	93.4	93.5	93.8	93.8	94.0	94.0	94.1
83.3	84.4	87.6	90.9	92.3	94.4	95.5	95.7	96.0	96.1	96.4	96.4	96.6
83.5	84.6	87.9	91.3	93.6	95.4	96.8	97.2	97.6	98.0	98.5	98.5	98.7
83.5	84.6	87.9	91.3	93.6	95.6	97.0	97.3	97.9	98.4	99.3	99.3	100.0
83.5	84.6	87.9	91.3	93.6	95.6	97.0	97.3	97.9	98.4	99.3	99.3	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: DEC HOURS: 00-02

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	24.6	24.6	24.6	24.7	24.7	24.7	25.4	25.5	25.6	25.8	25.8	25.8	25.	
GE 20000	27.1	27.1	27.1	27.2	27.2	27.2	27.8	28.0	28.1	28.3	28.3	28.3	28.	
GE 18000	28.1	28.1	28.1	28.2	28.2	28.2	28.8	28.9	29.0	29.2	29.2	29.2	29.	
GE 16000	28.3	28.3	28.3	28.4	28.4	28.4	29.0	29.1	29.2	29.5	29.5	29.5	29.	
GE 14000	28.7	28.7	28.7	28.8	28.8	28.8	29.5	29.6	29.7	29.9	29.9	29.9	29.	
GE 12000	29.6	29.6	29.6	29.7	29.7	29.7	30.3	30.4	30.5	30.8	30.8	30.8	30.	
GE 10000	30.5	30.5	30.5	30.6	30.6	30.6	31.3	31.4	31.5	31.7	31.7	31.7	31.	
GE 9000	30.8	30.8	30.8	30.9	30.9	30.9	31.5	31.6	31.7	31.9	31.9	31.9	31.	
GE 8000	32.0	32.0	32.0	32.2	32.2	32.2	32.9	32.9	33.0	33.2	33.2	33.2	33.	
GE 7000	32.8	32.8	32.8	33.0	33.0	33.1	34.1	34.2	34.4	34.6	34.6	34.6	34.	
GE 6000	32.8	32.8	32.8	33.0	33.0	33.1	34.1	34.2	34.4	34.6	34.6	34.6	34.	
GE 5000	34.6	34.6	34.6	34.8	34.8	34.9	35.9	36.0	36.2	36.5	36.5	36.5	36.	
GE 4500	35.9	35.9	35.9	36.1	36.1	36.2	37.2	37.3	37.5	37.7	37.7	37.7	37.	
GE 4000	38.1	38.1	38.1	38.5	38.5	38.6	39.6	39.7	39.9	40.1	40.1	40.1	40.	
GE 3500	40.2	40.2	40.4	40.9	40.9	41.0	42.0	42.2	42.4	42.6	42.6	42.6	42.	
GE 3000	43.0	43.0	43.3	43.8	44.1	44.2	45.5	45.6	45.8	46.0	46.0	46.0	46.	
GE 2500	47.3	47.8	49.5	49.0	49.8	49.9	51.4	51.5	51.7	51.9	51.9	51.9	51.	
GE 2000	52.8	52.8	54.0	54.6	55.9	56.0	58.5	58.9	59.2	59.5	59.5	59.5	59.	
GE 1800	56.5	56.5	57.7	58.4	60.0	60.1	63.1	63.4	63.8	64.0	64.0	64.0	64.	
GE 1500	63.3	63.5	65.5	66.1	68.1	68.3	71.5	72.2	72.7	73.1	73.3	73.3	73.	
GE 1200	64.5	64.7	67.0	67.7	69.7	69.9	73.3	74.0	74.5	74.9	75.2	75.2	75.	
GE 1000	65.9	66.1	68.4	69.1	71.2	71.4	74.9	76.0	76.6	77.0	77.3	77.3	77.	
GE 900	66.9	67.4	69.8	70.6	72.7	72.9	77.1	78.3	79.0	79.7	80.1	80.1	80.	
GE 800	67.4	68.0	70.4	71.4	73.4	73.7	78.3	79.5	81.2	81.8	82.3	82.3	82.	
GE 700	68.2	68.9	71.5	72.5	74.8	75.1	80.2	81.6	84.0	84.9	85.4	85.4	85.	
GE 600	68.5	69.2	72.4	73.7	76.2	76.7	82.3	83.8	86.7	87.7	88.4	88.4	89.	
GE 500	68.6	69.4	72.5	73.9	77.0	77.5	83.2	84.8	87.8	89.6	90.4	90.4	91.	
GE 400	69.0	69.8	73.0	74.4	77.6	78.4	84.4	85.2	89.2	91.1	92.0	92.2	93.	
GE 300	69.0	69.8	73.0	74.5	77.7	78.5	84.6	85.5	89.7	91.9	93.2	93.3	94.	
GE 200	69.0	69.8	73.1	74.6	78.2	78.9	85.1	87.2	90.5	93.2	95.3	95.8	97.	
GE 100	69.0	69.8	73.1	74.6	78.2	78.9	85.1	87.2	90.5	93.3	95.4	95.9	97.	
GE 000	69.0	69.8	73.1	74.6	78.2	78.9	85.1	87.2	90.5	93.3	95.4	95.9	97.	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME UTC: + 5 MONTH: DEC HOURS: 00-02

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
27	24.7	24.7	24.7	25.4	25.5	25.6	25.8	25.8	25.8	25.8	25.8	25.8	25.8
28	27.2	27.2	27.2	27.8	28.0	28.1	28.3	28.3	28.3	28.3	28.3	28.3	28.3
29	28.2	28.2	28.2	28.8	28.9	29.0	29.2	29.2	29.2	29.2	29.2	29.2	29.2
29	28.4	28.4	28.4	29.0	29.1	29.2	29.5	29.5	29.5	29.5	29.5	29.5	29.5
29	28.8	28.8	28.8	29.5	29.6	29.7	29.9	29.9	29.9	29.9	29.9	29.9	29.9
30	29.7	29.7	29.7	30.3	30.4	30.5	30.8	30.8	30.8	30.8	30.8	30.8	30.8
31	30.6	30.6	30.6	31.3	31.4	31.5	31.7	31.7	31.7	31.7	31.7	31.7	31.7
31	30.9	30.9	30.9	31.5	31.6	31.7	31.9	31.9	31.9	31.9	31.9	31.9	31.9
32	32.2	32.2	32.2	32.3	32.9	33.0	33.2	33.2	33.2	33.2	33.2	33.2	33.2
34	33.0	33.0	33.1	34.1	34.2	34.4	34.6	34.6	34.6	34.6	34.6	34.6	34.6
34	33.0	33.0	33.1	34.1	34.2	34.4	34.6	34.6	34.6	34.6	34.6	34.6	34.6
35	34.3	34.3	34.9	35.9	36.0	36.2	36.5	36.5	36.5	36.5	36.5	36.5	36.5
37	36.1	36.1	36.2	37.2	37.3	37.5	37.7	37.7	37.7	37.7	37.7	37.7	37.7
40	38.5	38.5	38.6	39.6	39.7	39.9	40.1	40.1	40.1	40.1	40.1	40.1	40.1
42	40.9	40.9	41.0	42.0	42.2	42.4	42.6	42.6	42.6	42.6	42.6	42.6	42.6
46	43.1	44.1	44.2	45.5	45.6	45.8	46.0	46.0	46.0	46.0	46.0	46.0	46.0
51	49.0	49.3	49.9	51.4	51.5	51.7	51.9	51.9	51.9	51.9	51.9	51.9	51.9
53	54.6	55.9	56.0	58.6	58.9	59.2	59.5	59.5	59.5	59.5	59.5	59.5	59.5
64	64.4	65.0	65.1	67.1	67.4	67.8	68.1	68.1	68.1	68.1	68.1	68.1	68.1
73	68.1	68.1	68.3	71.6	72.2	72.7	73.1	73.3	73.3	73.3	73.3	73.3	73.3
75	67.7	69.7	69.9	73.3	74.0	74.5	74.9	75.2	75.2	75.2	75.2	75.2	75.2
77	69.1	71.2	71.4	74.9	76.0	76.6	77.0	77.3	77.3	77.3	77.3	77.3	77.3
80	70.5	72.7	72.9	77.1	78.3	79.0	79.7	80.1	80.1	80.2	80.2	80.2	80.2
82	71.4	73.4	73.7	78.3	79.5	81.2	81.8	82.3	82.3	82.4	82.4	82.4	82.4
85	72.5	74.8	75.1	80.2	81.6	84.0	84.9	85.4	85.4	85.9	85.9	85.9	85.9
89	73.7	76.2	76.7	82.3	83.8	86.7	87.7	88.4	88.4	89.1	89.1	89.1	89.1
91	73.1	77.0	77.5	83.2	84.8	87.8	89.6	90.4	90.4	91.4	91.4	91.4	91.4
93	74.4	77.6	78.4	84.4	85.2	89.2	91.1	92.0	92.2	93.1	93.1	93.1	93.1
95	74.8	77.7	78.5	84.5	85.5	89.7	91.9	93.2	93.3	94.6	95.1	95.1	95.4
97	74.8	78.2	78.9	85.1	87.2	90.5	93.2	95.3	95.8	97.4	97.8	98.2	98.6
98	74.6	73.2	73.9	85.1	87.2	90.5	93.3	95.4	95.9	97.5	98.1	98.9	100.0
98	74.5	73.2	73.9	85.1	87.2	90.5	93.3	95.4	95.9	97.5	98.1	98.9	100.0

930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: DEC HOURS: 03-05

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 5	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CELL	27.6	27.7	28.3	28.3	28.6	28.8	28.8	28.9	29.1	29.4	29.5	29.5	29.6
GE 20000	30.3	30.4	31.0	31.0	31.3	31.5	31.5	31.6	31.8	32.0	32.2	32.2	32.3
GE 18000	30.4	30.5	31.1	31.1	31.4	31.6	31.6	31.7	31.9	32.2	32.3	32.3	32.4
GE 16000	30.8	30.9	31.4	31.4	31.7	31.9	31.9	32.0	32.3	32.5	32.6	32.6	32.7
GE 14000	30.9	31.0	31.5	31.5	31.8	32.0	32.0	32.2	32.4	32.6	32.7	32.7	32.8
GE 12000	31.3	31.4	31.9	31.9	32.3	32.5	32.5	32.6	32.8	33.0	33.1	33.1	33.2
GE 10000	32.3	32.4	32.9	32.9	33.2	33.4	33.4	33.5	33.8	34.0	34.1	34.1	34.2
GE 9000	32.4	32.5	33.0	33.0	33.3	33.5	33.5	33.7	33.9	34.1	34.2	34.2	34.3
GE 8000	33.0	33.1	33.3	33.3	34.2	34.4	34.4	34.5	34.7	34.9	35.1	35.1	35.2
GE 7000	33.8	33.9	34.5	34.6	34.9	35.2	35.2	35.3	35.5	35.7	35.8	35.8	35.9
GE 6000	33.8	33.9	34.5	34.6	34.9	35.5	35.5	35.6	35.8	36.0	36.1	36.1	36.2
GE 5000	35.2	35.3	35.9	36.0	36.3	36.9	36.9	37.0	37.2	37.4	37.5	37.5	37.6
GE 4500	35.3	35.9	36.6	36.7	37.0	37.5	37.5	37.6	37.9	38.1	38.2	38.2	38.3
GE 4000	38.3	38.6	39.4	39.5	39.9	40.4	40.4	41.0	41.2	41.4	41.5	41.5	41.6
GE 3500	39.2	39.6	40.3	40.4	41.0	41.5	41.8	42.0	42.3	42.5	42.6	42.6	42.7
GE 3000	41.3	41.6	42.5	42.6	43.5	44.3	44.6	44.8	45.1	45.3	45.4	45.4	45.5
GE 2500	46.3	46.3	47.8	48.0	49.5	50.0	50.3	50.5	50.8	51.0	51.1	51.1	51.2
GE 2000	52.9	53.4	55.4	55.9	57.7	58.4	59.1	59.7	60.2	60.4	60.5	60.5	60.6
GE 1800	56.6	57.2	59.2	59.3	61.9	62.6	63.4	64.0	64.5	64.7	64.8	64.8	64.9
GE 1500	62.2	62.9	65.0	65.8	69.1	69.8	70.9	71.8	72.5	72.7	72.8	72.8	72.9
GE 1200	64.4	65.2	68.6	69.5	72.4	73.1	74.9	76.1	76.8	77.1	77.2	77.2	77.3
GE 1000	65.6	66.3	69.9	71.0	74.0	74.7	76.7	79.1	78.7	79.4	79.5	79.5	79.6
GE 900	66.1	67.0	70.5	71.6	74.6	75.4	77.7	79.1	79.8	80.4	80.5	80.5	80.6
GE 800	66.7	67.6	71.2	72.3	75.5	76.3	79.0	80.6	82.0	82.8	82.9	82.9	83.0
GE 700	67.1	68.1	71.7	73.0	77.1	78.0	81.2	83.1	85.1	85.9	86.3	86.3	86.5
GE 600	67.5	68.5	72.2	73.7	77.8	78.9	82.4	84.4	86.5	87.3	87.7	88.1	88.2
GE 500	67.8	68.3	72.3	74.3	73.7	79.8	83.4	86.0	88.4	89.5	90.5	90.9	91.4
GE 400	68.0	68.9	72.9	74.4	79.2	80.5	84.5	87.3	89.7	91.0	92.3	92.6	93.1
GE 300	68.0	68.9	72.9	74.4	79.6	80.9	85.4	88.1	91.1	92.6	94.2	94.5	95.1
GE 200	68.0	68.9	72.9	74.4	79.7	81.0	85.6	88.4	91.4	93.3	95.4	95.7	96.8
GE 100	68.0	68.9	72.9	74.4	79.7	81.0	85.6	88.4	91.5	93.4	95.5	95.8	96.9
GE 000	68.0	68.9	72.9	74.4	79.7	81.0	85.6	88.4	91.5	93.4	95.5	95.8	96.9

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 03-05

VISIBILITY IN STATUTE MILES												
4	3	2 1/2	2	1 1/2	1 1/4	1	3/4	5/8	1/2	3/8	1/4	0
28.3	28.6	28.8	28.8	28.9	29.1	29.4	29.5	29.5	29.6	29.6	29.7	29.7
31.0	31.3	31.5	31.5	31.6	31.8	32.0	32.2	32.2	32.3	32.3	32.4	32.4
31.1	31.4	31.6	31.6	31.7	31.9	32.2	32.3	32.3	32.4	32.4	32.5	32.5
31.4	31.7	31.9	31.9	32.0	32.3	32.5	32.6	32.6	32.7	32.7	32.8	32.8
31.5	31.8	32.0	32.0	32.2	32.4	32.6	32.7	32.7	32.8	32.8	32.9	32.9
31.9	32.3	32.5	32.5	32.6	32.8	33.0	33.1	33.1	33.2	33.2	33.3	33.3
32.0	33.2	33.4	33.4	33.5	33.8	34.0	34.1	34.1	34.2	34.2	34.3	34.3
33.0	33.3	33.5	33.5	33.7	33.9	34.1	34.2	34.2	34.3	34.3	34.4	34.4
33.9	34.2	34.4	34.4	34.5	34.7	34.9	35.1	35.1	35.2	35.2	35.3	35.3
34.5	34.9	35.2	35.2	35.3	35.5	35.7	35.8	35.8	35.9	35.9	36.0	36.0
34.6	34.9	35.5	35.5	35.6	35.8	36.0	36.1	36.1	36.2	36.2	36.3	36.3
36.0	36.3	36.9	36.9	37.0	37.2	37.4	37.5	37.5	37.6	37.6	37.7	37.7
36.7	37.0	37.5	37.5	37.6	37.8	38.1	38.2	38.2	38.3	38.3	38.4	38.4
39.5	39.9	40.4	40.8	41.0	41.2	41.4	41.5	41.5	41.6	41.6	41.7	41.7
40.4	41.0	41.5	41.8	42.0	42.3	42.5	42.6	42.6	42.7	42.7	42.8	42.8
42.6	43.5	44.3	44.6	44.8	45.1	45.3	45.4	45.4	45.5	45.5	45.6	45.6
48.0	49.5	50.0	50.3	50.5	50.8	51.0	51.1	51.1	51.2	51.2	51.3	51.3
53.0	57.7	58.4	59.1	59.7	60.2	60.4	60.5	60.5	60.6	60.6	60.8	60.8
65.8	61.9	62.5	63.4	64.0	64.5	64.7	64.8	64.8	64.9	64.9	65.1	65.1
69.8	69.1	69.8	70.9	71.8	72.5	72.7	72.8	72.8	72.9	72.9	73.0	73.0
69.5	72.4	73.1	74.9	76.1	76.8	77.1	77.2	77.2	77.3	77.3	77.4	77.4
71.0	74.0	74.7	76.7	78.1	78.7	79.4	79.5	79.5	79.6	79.6	79.7	79.7
71.5	74.5	75.4	77.7	79.1	79.8	80.4	80.5	80.5	80.6	80.6	80.8	80.8
72.3	75.5	76.3	79.0	80.6	82.0	82.8	82.9	82.9	83.0	83.0	83.1	83.1
73.0	77.1	78.0	81.2	83.1	85.1	85.9	86.3	86.3	86.5	86.5	86.8	86.8
73.7	77.8	78.9	82.4	84.4	86.5	87.3	87.7	88.1	88.2	88.2	88.5	88.5
74.3	78.7	79.8	83.4	86.0	88.4	89.5	90.5	90.9	91.4	91.4	91.7	91.7
74.4	79.2	80.5	84.5	87.3	89.7	91.0	92.3	92.6	93.1	93.1	93.4	93.5
74.4	79.6	80.9	85.4	88.1	91.1	92.6	94.2	94.5	95.1	95.1	95.5	95.6
74.4	79.7	81.0	85.6	88.4	91.4	93.3	95.4	95.7	96.8	97.0	97.8	98.3
74.4	79.7	81.0	85.6	88.4	91.5	93.4	95.5	95.8	96.9	97.3	99.0	100.0
74.4	79.7	81.0	85.6	88.4	91.5	93.4	95.5	95.8	96.9	97.3	99.0	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: DEC HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	28.2	28.3	28.6	28.7	28.7	28.7	28.7	28.8	28.9	28.9	28.9	28.9	28.9	
GE 20000	29.0	29.1	29.5	29.6	29.6	29.6	29.6	29.7	29.8	29.8	29.8	29.8	29.8	
GE 18000	29.0	29.1	29.5	29.6	29.6	29.6	29.6	29.7	29.8	29.8	29.8	29.8	29.8	
GE 16000	29.1	29.2	29.5	29.7	29.7	29.7	29.7	29.8	29.9	29.9	29.9	29.9	29.9	
GE 14000	29.6	29.7	30.0	30.1	30.1	30.1	30.1	30.2	30.3	30.3	30.3	30.3	30.3	
GE 12000	29.7	29.8	30.1	30.2	30.2	30.2	30.2	30.3	30.4	30.4	30.4	30.4	30.4	
GE 10000	30.9	31.1	31.4	31.5	31.5	31.5	31.5	31.6	31.7	31.7	31.7	31.7	31.7	
GE 9000	31.3	31.5	31.8	31.9	31.9	31.9	31.9	32.0	32.2	32.2	32.2	32.2	32.2	
GE 8000	32.3	32.5	32.8	32.9	32.9	32.9	32.9	33.0	33.1	33.1	33.1	33.1	33.1	
GE 7000	33.0	33.2	33.5	33.8	33.8	33.8	33.8	33.9	34.0	34.0	34.0	34.0	34.0	
GE 6000	33.1	33.3	33.7	33.9	33.9	34.0	34.0	34.1	34.2	34.2	34.2	34.2	34.2	
GE 5000	35.3	35.5	35.8	36.0	36.0	36.1	36.1	36.2	36.3	36.3	36.3	36.3	36.3	
GE 4500	36.0	36.2	36.5	36.8	36.8	36.9	36.9	37.0	37.1	37.1	37.1	37.1	37.1	
GE 4000	37.5	37.7	38.1	38.3	38.3	38.4	38.4	38.7	38.8	38.8	38.8	38.8	38.8	
GE 3500	38.0	38.2	38.5	38.7	38.8	38.9	39.0	39.4	39.5	39.5	39.5	39.5	39.5	
GE 3000	40.6	41.0	41.4	41.6	41.8	41.9	42.0	42.4	42.5	42.5	42.5	42.5	42.5	
GE 2500	45.1	45.5	46.0	46.2	46.8	47.1	47.3	47.7	48.0	48.0	48.0	48.0	48.0	
GE 2000	52.2	52.6	53.3	54.0	55.1	55.6	57.0	57.6	58.2	58.3	58.3	58.3	58.3	
GE 1800	55.4	55.9	56.9	57.5	58.9	59.5	61.0	61.6	62.2	62.5	62.5	62.5	62.5	
GE 1500	61.0	61.5	63.0	63.8	65.4	65.9	68.0	68.8	69.4	69.7	69.7	69.7	69.7	
GE 1200	63.8	64.3	66.0	66.8	69.7	69.4	71.7	72.8	73.3	74.0	74.0	74.0	74.0	
GE 1000	65.2	65.7	67.5	68.7	70.9	71.5	74.4	75.9	76.6	77.2	77.4	77.4	77.4	
GE 900	66.0	66.6	68.4	69.6	71.8	72.6	75.5	77.2	78.1	78.8	79.1	79.1	79.1	
GE 800	66.7	67.2	69.1	70.4	72.9	73.7	76.9	79.2	80.5	81.4	81.7	81.7	81.7	
GE 700	67.0	67.5	69.5	70.9	73.5	74.6	78.3	81.4	82.8	84.1	84.7	84.7	84.9	
GE 600	67.8	68.4	70.3	71.8	75.1	76.2	80.4	83.8	85.3	86.7	87.3	87.3	87.5	
GE 500	68.3	68.8	71.2	72.7	76.2	77.6	81.8	85.8	87.5	89.2	90.3	90.3	90.8	
GE 400	68.4	68.9	71.9	73.0	76.7	78.1	82.6	87.2	89.1	90.9	91.9	91.9	92.5	
GE 300	68.4	68.9	71.5	73.0	77.0	78.4	83.5	88.6	91.4	93.3	94.5	94.6	95.3	
GE 200	68.4	68.9	71.5	73.0	77.0	78.4	83.9	88.9	91.8	93.9	95.5	95.6	96.6	
GE 100	68.4	68.9	71.5	73.0	77.0	78.4	83.9	88.9	92.2	94.2	95.8	95.9	96.9	
GE 000	69.4	68.9	71.5	73.0	77.0	78.4	83.9	88.9	92.2	94.2	95.8	95.9	97.0	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
C: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 06-08

VISIBILITY IN STATUTE MILES

GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
28.7	29.7	28.7	28.8	28.9	28.9	28.9	28.9	28.9	28.9	29.0	29.0
29.6	29.6	29.6	29.7	29.8	29.8	29.8	29.8	29.8	29.8	29.9	29.9
29.6	29.6	29.6	29.7	29.8	29.8	29.8	29.8	29.8	29.8	29.9	29.9
29.7	29.7	29.7	29.8	29.9	29.9	29.9	29.9	29.9	29.9	30.0	30.0
30.1	30.1	30.1	30.2	30.3	30.3	30.3	30.3	30.3	30.3	30.4	30.4
30.2	30.2	30.2	30.3	30.4	30.4	30.4	30.4	30.4	30.4	30.5	30.5
31.5	31.5	31.5	31.6	31.7	31.7	31.7	31.7	31.7	31.7	31.8	31.8
31.9	31.9	31.9	32.0	32.2	32.2	32.2	32.2	32.2	32.2	32.3	32.3
32.9	32.9	32.9	33.0	33.1	33.1	33.1	33.1	33.1	33.1	33.2	33.2
33.8	33.8	33.8	33.9	34.0	34.0	34.0	34.0	34.0	34.0	34.1	34.1
33.9	34.0	34.0	34.1	34.2	34.2	34.2	34.2	34.2	34.2	34.3	34.3
36.0	36.1	36.1	36.2	36.3	36.3	36.3	36.3	36.3	36.3	36.5	36.5
36.8	36.9	36.9	37.0	37.1	37.1	37.1	37.1	37.1	37.1	37.2	37.2
38.3	38.4	38.4	38.7	38.8	38.8	38.8	38.8	38.8	38.8	38.9	38.9
38.8	38.9	39.0	39.4	39.5	39.5	39.5	39.5	39.5	39.5	39.6	39.6
41.8	41.9	42.0	42.4	42.5	42.5	42.5	42.5	42.5	42.5	42.6	42.6
46.8	47.1	47.3	47.7	48.0	48.0	48.0	48.0	48.0	48.0	48.1	48.1
55.1	55.6	57.0	57.6	58.2	58.3	58.3	58.3	58.3	58.3	58.4	58.4
59.9	59.5	61.0	61.6	62.2	62.5	62.5	62.5	62.5	62.5	62.6	62.6
65.4	65.9	68.0	68.8	69.4	69.7	69.7	69.7	69.7	69.7	69.8	69.8
69.7	69.4	71.7	72.8	73.3	74.0	74.0	74.0	74.0	74.1	74.2	74.2
70.8	71.5	74.4	75.9	76.6	77.2	77.4	77.4	77.4	77.5	77.6	77.6
71.8	72.6	75.5	77.2	78.1	78.8	79.1	79.1	79.1	79.2	79.5	79.5
72.9	73.7	76.9	79.2	80.5	81.4	81.7	81.7	81.7	81.8	82.0	82.0
73.5	74.5	78.3	81.4	82.8	84.1	84.7	84.7	84.9	85.1	85.3	85.3
75.1	76.2	80.4	83.8	85.3	86.7	87.3	87.3	87.5	87.6	87.8	87.8
76.2	77.6	81.8	85.8	87.5	89.2	90.3	90.3	90.8	90.9	91.1	91.1
76.7	78.1	82.6	87.2	89.1	90.9	91.9	91.9	92.5	92.8	93.1	93.1
77.0	78.4	83.5	88.6	91.4	93.3	94.5	94.6	95.3	95.6	95.9	95.9
77.0	78.4	83.9	88.9	91.8	93.9	95.5	95.6	96.6	97.0	97.4	98.0
77.0	78.4	83.9	88.9	92.2	94.2	95.8	95.9	96.9	97.3	98.2	99.9
77.0	78.4	83.9	88.9	92.2	94.2	95.8	95.9	97.0	97.4	98.3	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIB
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: DEC HOURS: 09-1

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GF 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GF 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	24.3	24.4	24.7	25.1	25.7	25.7	25.8	25.9	25.9	25.9	25.9	25.9	25.9	25.9
GE 20000	28.8	28.9	29.4	29.7	30.3	30.3	30.4	30.5	30.5	30.5	30.5	30.5	30.5	30.5
GE 18000	29.1	29.2	29.7	30.0	30.6	30.6	30.8	30.9	30.9	30.9	30.9	30.9	30.9	30.9
GE 16000	29.4	29.5	29.9	30.2	30.9	30.9	31.0	31.1	31.1	31.1	31.1	31.1	31.1	31.1
GE 14000	30.2	30.3	30.8	31.1	31.7	31.7	31.8	31.9	31.9	31.9	31.9	31.9	31.9	31.9
GE 12000	31.3	31.4	31.8	32.2	32.8	32.8	32.9	33.0	33.0	33.0	33.0	33.0	33.0	33.0
GE 10000	33.2	33.4	33.9	34.2	34.8	34.8	34.9	35.1	35.1	35.1	35.1	35.1	35.1	35.1
GF 9000	34.0	34.2	34.6	34.9	35.6	35.6	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9
GE 8000	35.8	36.0	36.6	36.9	37.5	37.5	37.7	37.8	37.8	37.8	37.8	37.8	37.8	37.8
GE 7000	36.5	36.7	37.2	37.5	38.2	38.2	38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5
GE 6000	37.0	37.3	37.8	38.2	38.8	38.8	39.0	39.1	39.1	39.1	39.1	39.1	39.1	39.1
GE 5000	38.5	38.8	39.4	39.7	40.3	40.3	40.5	40.6	40.6	40.6	40.6	40.6	40.6	40.6
GE 4500	39.0	39.4	40.0	40.4	41.3	41.3	41.6	41.7	41.7	41.7	41.7	41.7	41.7	41.7
GE 4000	39.7	40.0	40.9	41.3	42.2	42.3	42.6	42.7	42.7	42.7	42.7	42.7	42.7	42.7
GE 3500	40.1	40.4	41.4	41.9	42.9	43.0	43.4	43.7	43.7	43.7	43.7	43.7	43.7	43.7
GE 3000	40.9	41.2	42.2	42.7	43.9	44.1	44.5	44.7	44.8	44.8	44.8	44.8	44.8	44.8
GE 2500	44.2	44.5	45.7	46.3	47.8	48.4	49.0	49.2	49.6	49.7	49.7	49.7	49.7	49.7
GE 2000	50.9	51.5	53.1	54.0	55.7	56.3	57.5	57.8	58.5	58.9	58.9	58.9	58.9	59.0
GF 1800	52.9	53.5	55.5	56.7	58.7	59.4	60.8	61.3	62.0	62.6	62.6	62.6	62.6	62.6
GE 1500	57.1	57.8	60.2	61.5	63.9	64.6	66.6	67.4	68.6	69.5	69.5	69.5	69.5	69.5
GE 1200	59.4	60.1	63.0	64.6	67.4	68.3	70.2	71.5	72.8	73.7	74.0	74.1	74.1	74.1
GE 1000	60.4	61.3	64.2	66.1	69.1	70.0	72.2	73.7	75.2	76.1	76.8	76.9	76.9	77.0
GE 900	61.2	62.3	65.3	67.2	70.2	71.2	73.5	75.3	76.9	78.1	78.7	78.8	78.8	79.0
GE 900	61.4	62.8	66.0	68.1	71.1	72.2	75.1	76.9	78.7	80.1	81.0	81.1	81.1	81.1
GE 700	61.5	63.1	66.5	68.5	71.8	72.9	76.6	78.9	81.3	83.2	84.3	84.5	84.5	85.0
GE 600	61.5	63.1	66.6	68.7	72.5	73.5	78.0	80.6	83.4	85.6	86.8	87.1	87.1	87.1
GF 500	61.5	63.1	66.7	68.8	72.7	73.8	78.3	81.3	84.4	86.9	88.5	89.0	89.0	90.0
GE 400	61.6	63.2	66.9	69.0	73.1	74.3	78.8	81.8	85.4	88.1	90.0	90.8	90.8	92.0
GF 300	61.5	63.2	66.9	69.0	73.1	74.4	78.9	82.6	86.5	89.4	91.4	92.3	92.3	94.0
GE 200	61.6	63.2	66.9	69.0	73.1	74.4	78.9	82.8	86.8	89.9	92.8	93.7	93.7	95.0
GE 100	61.6	63.2	66.9	69.0	73.1	74.4	78.9	82.8	86.9	90.0	93.0	93.9	93.9	96.0
GF 000	61.6	63.2	66.9	69.0	73.1	74.4	78.9	82.8	86.9	90.0	93.0	93.9	93.9	96.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 09-11

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
25.1	25.7	25.7	25.8	25.9	25.9	25.9	25.9	25.9	25.9	25.9	25.9	25.9
29.7	30.3	30.3	30.4	30.5	30.5	30.5	30.5	30.5	30.5	30.5	30.5	30.5
30.0	30.6	30.6	30.8	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9	30.9
30.2	30.9	30.9	31.0	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1
31.1	31.7	31.7	31.8	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9
32.2	32.8	32.8	32.9	33.0	33.0	33.0	33.0	33.0	33.0	33.0	33.0	33.0
34.2	34.8	34.8	34.9	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1	35.1
34.9	35.6	35.6	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
35.9	37.5	37.5	37.7	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8
37.5	38.2	38.2	38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5	38.5
38.2	38.8	38.8	39.0	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
39.7	40.3	40.3	40.5	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6	40.6
40.4	41.3	41.3	41.6	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7	41.7
41.3	42.2	42.3	42.6	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
41.9	42.9	43.0	43.4	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7	43.7
42.7	43.9	44.1	44.5	44.7	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
46.3	47.8	48.4	49.0	49.2	49.6	49.7	49.7	49.7	49.7	49.7	49.7	49.7
54.0	55.7	56.3	57.5	57.8	58.5	58.9	58.9	58.9	59.0	59.0	59.0	59.0
56.7	58.7	59.4	60.3	61.3	62.0	62.6	62.6	62.6	62.7	62.7	62.7	62.7
61.5	63.9	64.6	66.6	67.4	68.6	69.5	69.5	69.5	69.6	69.6	69.6	69.6
64.6	67.4	68.3	70.2	71.5	72.8	73.7	74.0	74.1	74.2	74.2	74.2	74.2
66.1	69.1	70.0	72.2	73.7	75.2	76.1	76.8	76.9	77.2	77.3	77.3	77.3
67.2	70.2	71.2	73.5	75.3	76.9	78.1	78.7	78.8	79.2	79.5	79.5	79.5
68.1	71.1	72.2	75.1	76.9	78.7	80.1	81.0	81.1	81.5	81.7	81.9	81.9
69.5	71.8	72.9	76.6	78.9	81.3	83.2	84.3	84.5	85.2	85.6	85.9	85.9
68.7	72.5	73.5	78.0	80.6	83.4	85.6	86.8	87.1	87.7	88.2	88.5	88.5
68.3	72.7	73.8	78.3	81.3	84.4	86.9	88.5	89.0	90.1	90.5	91.1	91.2
69.0	73.1	74.3	78.3	81.8	85.4	88.1	90.0	90.8	92.0	92.8	93.4	93.8
69.0	73.1	74.4	78.9	82.6	86.5	89.4	91.4	92.3	94.0	94.7	95.4	96.0
69.0	73.1	74.4	78.9	82.8	86.8	89.9	92.8	93.7	95.7	96.6	97.4	98.5
69.0	73.1	74.4	78.9	82.8	86.9	90.0	93.0	93.9	96.0	97.0	98.1	100.0
69.0	73.1	74.4	78.9	82.8	86.9	90.0	93.0	93.9	96.0	97.0	98.1	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS V
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: A
LST TO UTC: + 5 MONTH: DEC HOURS:

CEILING IN FEET	VISIBILITY IN STATUTE MILES											
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8
NO CEIL	25.1	25.2	25.8	26.1	26.3	26.3	26.5	26.5	26.6	26.6	26.6	26.6
GE 20000	28.4	28.5	29.1	29.5	29.7	29.7	29.8	29.8	29.9	29.9	29.9	29.9
GE 18000	29.1	29.2	29.9	30.2	30.4	30.4	30.5	30.5	30.6	30.6	30.6	30.6
GE 16000	29.1	29.2	29.9	30.2	30.4	30.4	30.5	30.5	30.6	30.6	30.6	30.6
GE 14000	30.4	30.5	31.2	31.5	31.7	31.7	31.8	31.8	31.9	31.9	31.9	31.9
GE 12000	31.2	31.3	32.0	32.4	32.6	32.6	32.7	32.7	32.8	32.8	32.8	32.8
GE 10000	33.5	33.8	34.5	34.8	35.1	35.1	35.2	35.3	35.5	35.5	35.5	35.5
GE 9000	33.9	34.1	34.3	35.2	35.4	35.4	35.5	35.6	35.8	35.8	35.8	35.8
GE 8000	35.9	35.1	36.9	37.2	37.4	37.4	37.5	37.6	37.8	37.8	37.8	37.8
GE 7000	36.8	37.0	37.7	38.1	38.3	38.3	38.4	38.5	38.7	38.7	38.7	38.7
GE 6000	37.4	37.6	38.4	38.7	38.9	38.9	39.0	39.1	39.4	39.4	39.4	39.4
GE 5000	38.3	38.5	39.4	39.3	40.0	40.0	40.1	40.2	40.4	40.4	40.4	40.4
GE 4500	38.6	38.8	39.7	40.1	40.3	40.3	40.5	40.6	41.0	41.0	41.0	41.0
GE 4000	40.1	40.3	41.3	41.8	42.0	42.0	42.3	42.4	42.7	42.7	42.7	42.7
GE 3500	40.6	40.9	41.9	42.5	42.7	42.7	42.9	43.0	43.3	43.3	43.3	43.3
GE 3000	42.6	42.8	43.9	44.6	45.2	45.2	45.4	45.6	45.9	45.9	45.9	45.9
GE 2500	46.7	47.1	48.6	49.6	50.3	50.6	51.0	51.2	51.7	51.8	51.8	51.8
GE 2000	51.4	52.0	54.0	54.9	55.9	56.2	57.1	57.6	58.5	58.6	58.6	58.6
GE 1800	52.9	53.5	55.9	57.0	58.1	58.4	59.5	60.0	61.0	61.1	61.1	61.1
GE 1500	58.3	58.9	62.2	63.7	65.4	65.8	67.6	68.7	69.8	70.0	70.0	70.0
GE 1200	60.3	61.0	65.2	66.8	68.8	69.4	71.4	72.6	73.7	74.0	74.0	74.0
GE 1000	61.8	62.7	67.5	69.1	71.3	71.8	74.3	75.8	77.5	78.0	78.5	78.5
GE 900	62.5	63.3	68.3	70.1	72.5	73.0	75.6	77.2	79.0	79.5	80.0	80.0
GE 800	62.8	63.7	68.6	71.1	73.8	74.4	77.5	79.1	81.0	81.5	82.6	82.6
GE 700	63.0	63.9	69.1	71.7	74.7	75.6	79.1	81.2	83.3	83.9	85.3	85.3
GE 600	63.0	64.0	69.4	71.9	74.9	75.8	79.8	82.3	84.9	86.0	87.6	87.6
GE 500	63.0	64.4	69.8	72.4	75.8	76.7	81.1	83.8	86.9	88.1	90.1	90.4
GE 400	63.3	64.7	70.1	72.7	76.1	77.0	81.5	84.3	87.7	89.2	91.4	91.7
GE 300	63.3	64.7	70.1	72.7	76.1	77.0	81.5	85.1	88.8	91.0	93.2	93.5
GE 200	63.3	64.7	70.1	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0
GE 100	63.3	64.7	70.1	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0
GE 000	63.3	64.7	70.1	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 12-14

VISIBILITY IN STATUTE MILES

	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
64.8	26.1	26.3	26.3	26.5	26.5	26.6	26.6	26.6	26.6	26.6	26.6	26.6	26.6
64.9	29.5	29.7	29.7	29.8	29.8	29.9	29.9	29.9	29.9	29.9	29.9	29.9	29.9
65.0	30.2	30.4	30.4	30.5	30.5	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
65.1	30.9	30.4	30.4	30.5	30.5	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
65.2	31.5	31.7	31.7	31.8	31.8	31.9	31.9	31.9	31.9	31.9	31.9	31.9	31.9
65.3	32.4	32.6	32.6	32.7	32.7	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8
65.4	34.8	35.1	35.1	35.2	35.3	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5
65.5	35.2	35.4	35.4	35.5	35.6	35.8	35.8	35.8	35.8	35.8	35.8	35.8	35.8
65.6	37.2	37.4	37.4	37.5	37.6	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8
65.7	38.1	38.3	38.3	38.4	38.5	38.7	38.7	38.7	38.7	38.7	38.7	38.7	38.7
65.8	38.7	38.9	38.9	39.0	39.1	39.4	39.4	39.4	39.4	39.4	39.4	39.4	39.4
65.9	39.3	40.0	40.0	40.1	40.2	40.4	40.4	40.4	40.4	40.4	40.4	40.4	40.4
66.0	40.1	40.3	40.3	40.5	40.6	41.0	41.0	41.0	41.0	41.0	41.0	41.0	41.0
66.1	41.3	42.0	42.0	42.3	42.4	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
66.2	42.5	42.7	42.7	42.9	43.0	43.3	43.3	43.3	43.3	43.3	43.3	43.3	43.3
66.3	44.6	45.2	45.2	45.4	45.6	45.9	45.9	45.9	45.9	45.9	45.9	45.9	45.9
66.4	49.6	50.3	50.6	51.0	51.2	51.7	51.8	51.8	51.8	52.0	52.0	52.0	52.0
66.5	54.9	55.9	56.2	57.1	57.6	58.5	58.6	58.6	58.6	58.8	58.8	58.8	58.8
66.6	57.0	58.1	58.4	59.5	60.0	61.0	61.1	61.1	61.1	61.3	61.3	61.4	61.4
66.7	53.7	65.4	65.8	67.6	68.7	69.8	70.0	70.0	70.0	70.3	70.3	70.4	70.4
66.8	66.8	68.8	69.4	71.4	72.6	73.7	74.0	74.0	74.0	74.3	74.3	74.4	74.4
66.9	69.1	71.3	71.8	74.3	75.8	77.5	78.0	78.5	78.5	78.8	78.8	78.9	78.9
67.0	70.1	72.5	73.0	75.6	77.2	79.0	79.5	80.0	80.0	80.3	80.3	80.4	80.4
67.1	71.1	73.8	74.4	77.5	79.1	81.0	81.5	82.6	82.6	83.1	83.3	83.4	83.4
67.2	71.7	74.7	75.6	79.1	81.2	83.3	83.9	85.3	85.3	85.9	86.2	86.7	86.8
67.3	71.9	74.9	75.8	79.8	82.3	84.9	86.0	87.6	87.6	88.5	88.8	89.4	89.5
67.4	72.4	75.8	76.7	81.1	83.8	86.9	88.1	90.1	90.4	91.8	92.2	92.8	93.2
67.5	72.7	76.1	77.0	81.5	84.3	87.7	89.2	91.4	91.7	93.3	93.9	94.6	95.2
67.6	72.7	76.1	77.0	81.5	85.1	88.8	91.0	93.2	93.5	95.6	96.2	97.1	97.7
67.7	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0	95.2	97.0	98.2	99.0
67.8	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0	96.2	97.3	98.8	100.0
67.9	72.7	76.1	77.0	81.5	85.1	89.0	91.2	93.7	94.0	96.2	97.3	98.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISI
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: DEC HOURS: 15-

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	25.6	25.9	26.0	26.3	26.3	26.5	26.6	26.8	26.8	26.8	26.8	26.8	26.8	26.8
GE 20000	30.1	30.4	30.6	31.3	31.3	31.4	31.5	31.7	31.7	31.8	31.8	31.8	31.8	31.8
GE 18000	31.1	31.4	31.6	32.3	32.3	32.4	32.5	32.7	32.7	32.8	32.8	32.8	32.8	32.8
GE 16000	31.2	31.5	31.7	32.4	32.4	32.5	32.6	32.8	32.8	32.9	32.9	32.9	32.9	32.9
GE 14000	32.0	32.4	32.6	33.2	33.2	33.3	33.4	33.7	33.7	33.8	33.8	33.8	33.8	33.8
GE 12000	34.2	34.5	34.8	35.5	35.5	35.6	35.7	35.9	35.9	36.0	36.0	36.0	36.0	36.0
GE 10000	36.7	37.0	37.3	38.0	38.0	38.1	38.2	38.4	38.4	38.5	38.5	38.5	38.5	38.5
GE 9000	36.8	37.1	37.4	38.1	38.1	38.2	38.3	38.5	38.5	38.6	38.6	38.6	38.6	38.6
GE 8000	38.9	39.2	39.6	40.2	40.3	40.4	40.5	40.8	40.8	40.9	40.9	40.9	40.9	40.9
GE 7000	39.9	40.2	40.5	41.3	41.5	41.6	41.7	41.9	41.9	42.0	42.0	42.0	42.0	42.0
GE 6000	40.9	41.2	41.8	42.6	42.8	42.9	43.0	43.2	43.2	43.3	43.3	43.3	43.3	43.3
GE 5000	41.2	41.5	42.2	42.9	43.3	43.4	43.5	43.8	43.8	44.0	44.0	44.0	44.0	44.0
GE 4500	41.4	41.7	42.4	43.1	43.7	43.8	43.9	44.1	44.1	44.3	44.3	44.3	44.3	44.3
GE 4000	42.7	43.0	43.7	44.4	45.1	45.2	45.4	45.8	45.8	46.0	46.0	46.0	46.0	46.0
GE 3500	44.0	44.4	45.1	45.8	45.5	46.6	46.8	47.2	47.2	47.4	47.4	47.4	47.4	47.4
GE 3000	45.8	45.2	47.0	47.7	48.5	48.6	48.8	49.2	49.2	49.5	49.5	49.5	49.5	49.5
GE 2500	50.3	50.9	51.9	52.7	53.4	53.5	54.0	54.4	54.4	54.6	54.7	54.7	54.7	54.7
GE 2000	55.3	56.0	57.8	58.7	59.9	60.1	61.1	61.6	61.6	62.2	62.5	62.5	62.5	62.5
GE 1800	58.7	59.5	61.7	62.6	64.0	64.2	65.2	65.7	65.7	66.2	66.6	66.6	66.6	66.6
GE 1500	62.8	63.8	66.3	67.2	69.0	69.5	70.8	71.6	71.9	72.5	73.1	73.1	73.1	73.1
GE 1200	66.0	67.4	70.8	71.6	73.9	74.4	76.2	77.2	77.5	78.1	78.8	78.8	78.8	78.8
GE 1000	67.3	69.2	72.8	73.9	76.2	76.8	78.8	79.8	80.2	80.9	81.6	81.6	81.6	81.6
GE 900	68.3	69.8	73.4	74.5	77.0	77.6	79.8	80.8	81.4	82.3	83.0	83.1	83.1	83.1
GE 800	68.7	70.3	74.0	75.1	77.5	78.3	80.5	81.6	82.6	83.7	84.7	84.8	84.8	84.8
GE 700	68.9	70.8	74.4	75.5	78.2	79.2	81.8	83.5	84.6	85.9	87.1	87.3	87.3	87.3
GE 600	69.0	70.9	74.7	75.9	78.9	80.0	82.7	84.5	86.3	87.7	89.0	89.2	89.2	89.2
GE 500	69.0	70.9	74.7	76.0	79.4	80.4	83.5	85.4	88.0	89.6	91.4	91.7	91.7	91.7
GE 400	69.0	70.9	74.3	76.1	79.5	80.5	83.8	86.5	89.4	91.4	93.2	93.7	93.7	93.7
GE 300	69.0	70.9	74.8	76.1	79.5	80.5	83.9	87.3	90.9	92.9	95.4	95.8	95.8	95.8
GE 200	69.0	70.9	74.8	76.1	79.5	80.5	83.9	87.3	91.0	93.1	95.7	96.1	96.1	96.1
GE 100	69.0	70.9	74.8	76.1	79.5	80.5	83.9	87.3	91.3	93.4	96.0	96.5	96.5	96.5
GE 000	69.0	70.9	74.8	76.1	79.5	80.5	83.9	87.3	91.3	93.4	96.0	96.5	96.5	96.5

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 15-17

	VISIBILITY IN STATUTE MILES												
	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
0	26.3	26.3	26.5	26.6	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8
5	31.3	31.3	31.4	31.5	31.7	31.7	31.8	31.8	31.8	31.8	31.8	31.8	31.8
6	32.3	32.3	32.4	32.5	32.7	32.7	32.8	32.8	32.8	32.8	32.8	32.8	32.8
7	32.4	32.4	32.5	32.6	32.8	32.8	32.9	32.9	32.9	32.9	32.9	32.9	32.9
8	33.2	33.2	33.3	33.4	33.7	33.7	33.8	33.8	33.8	33.8	33.8	33.8	33.8
9	35.5	35.5	35.6	35.7	35.9	35.9	36.0	36.0	36.0	36.0	36.0	36.0	36.0
1	38.0	38.0	38.1	38.2	38.4	38.4	38.5	38.5	38.5	38.5	38.5	38.5	38.5
4	38.1	38.1	38.2	38.3	38.5	38.5	38.6	38.6	38.6	38.6	38.6	38.6	38.6
5	40.2	40.3	40.4	40.5	40.8	40.8	40.9	40.9	40.9	40.9	40.9	40.9	40.9
6	41.3	41.5	41.6	41.7	41.9	41.9	42.0	42.0	42.0	42.0	42.0	42.0	42.0
8	42.6	42.8	42.9	43.0	43.2	43.2	43.3	43.3	43.3	43.3	43.3	43.3	43.3
2	42.9	43.3	43.4	43.5	43.8	43.8	44.0	44.0	44.0	44.0	44.0	44.0	44.0
4	43.1	43.7	43.8	43.9	44.1	44.1	44.3	44.3	44.3	44.3	44.3	44.3	44.3
7	44.4	45.1	45.2	45.4	45.8	45.8	46.0	46.0	46.0	46.0	46.0	46.0	46.0
1	45.8	45.5	46.6	46.8	47.2	47.2	47.4	47.4	47.4	47.4	47.4	47.4	47.4
0	47.7	48.5	48.6	48.8	49.2	49.2	49.5	49.5	49.5	49.5	49.5	49.5	49.5
9	52.7	53.4	53.5	54.0	54.4	54.4	54.6	54.7	54.7	54.7	54.7	54.7	54.7
4	58.7	59.9	60.1	61.1	61.6	61.6	62.2	62.5	62.5	62.5	62.5	62.6	62.6
7	62.6	64.0	64.2	65.2	65.7	65.7	66.2	66.6	66.6	66.6	66.6	66.7	66.7
2	67.2	69.0	69.5	70.8	71.6	71.9	72.5	73.1	73.1	73.2	73.2	73.3	73.3
4	71.6	73.9	74.4	76.2	77.2	77.5	78.1	78.8	78.8	78.9	78.9	79.0	79.0
1	73.9	76.2	76.8	78.3	79.8	80.2	80.9	81.6	81.6	81.7	81.7	81.8	81.8
4	74.5	77.0	77.6	79.3	80.8	81.4	82.3	83.0	83.1	83.2	83.2	83.4	83.4
0	75.1	77.5	78.3	80.5	81.6	82.6	83.7	84.7	84.8	84.9	84.9	85.2	85.2
4	75.5	78.2	79.2	81.8	83.5	84.6	85.9	87.1	87.3	87.6	87.7	88.0	88.1
7	75.9	78.9	80.0	82.7	84.5	86.3	87.7	89.0	89.2	89.6	89.7	89.9	90.1
7	76.0	79.4	80.4	83.5	85.4	88.0	89.6	91.4	91.7	92.8	92.9	93.1	93.3
1	76.1	79.5	80.5	83.8	86.5	89.4	91.4	93.2	93.7	94.7	94.8	95.1	95.3
2	76.1	79.5	80.5	83.9	87.3	90.9	92.9	95.4	95.8	96.9	97.2	97.5	98.0
4	76.1	79.5	80.5	83.9	87.3	91.0	93.1	95.7	96.1	97.2	97.5	98.2	99.0
4	76.1	79.5	80.5	83.9	87.3	91.3	93.4	96.0	96.5	97.5	97.8	98.9	100.0
4	76.1	79.5	80.5	83.9	87.3	91.3	93.4	96.0	96.5	97.5	97.8	98.9	100.0

930

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: DEC HOURS: 18

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	
NO CEIL	27.6	27.6	27.6	27.8	27.8	27.8	27.8	29.1	28.1	28.1	28.1	28.1	
GE 20000	32.0	32.0	32.0	32.3	32.4	32.4	32.4	32.6	32.6	32.6	32.6	32.6	
GE 18000	32.6	32.6	32.6	32.8	33.1	33.1	33.1	33.3	33.3	33.3	33.3	33.3	
GE 16000	32.6	32.6	32.6	32.8	33.1	33.1	33.1	33.3	33.3	33.3	33.3	33.3	
GE 14000	33.5	33.5	33.5	33.8	34.1	34.1	34.1	34.3	34.3	34.3	34.3	34.3	
GE 12000	34.5	34.6	34.7	34.9	35.3	35.3	35.3	35.5	35.5	35.5	35.5	35.5	
GE 10000	36.3	36.5	36.6	36.8	37.1	37.1	37.1	37.3	37.3	37.3	37.3	37.3	
GE 9000	36.9	37.0	37.1	37.3	37.6	37.6	37.6	37.8	37.8	37.8	37.8	37.8	
GE 8000	38.1	38.2	38.3	38.5	38.8	38.8	38.8	39.0	39.0	39.0	39.0	39.0	
GE 7000	38.8	38.9	39.1	39.6	40.0	40.0	40.0	40.2	40.2	40.2	40.2	40.2	
GE 6000	39.6	39.7	39.9	40.4	40.9	40.9	40.9	41.1	41.1	41.1	41.1	41.1	
GE 5000	41.0	41.1	41.4	41.9	42.5	42.5	42.5	42.7	42.7	42.7	42.7	42.7	
GE 4500	41.5	41.8	42.2	42.7	43.2	43.2	43.2	43.4	43.4	43.4	43.4	43.4	
GE 4000	43.0	43.3	43.7	44.2	44.7	44.7	44.9	45.2	45.3	45.3	45.3	45.3	
GE 3500	43.9	44.2	44.5	45.1	45.6	45.6	45.8	46.0	46.1	46.1	46.1	46.1	
GE 3000	46.8	47.1	47.4	48.1	48.6	48.6	48.9	49.2	49.4	49.4	49.4	49.4	
GE 2500	51.6	51.9	52.3	52.9	53.7	53.7	54.0	54.3	54.8	54.9	54.9	54.9	
GE 2000	58.3	58.7	59.4	60.2	61.3	61.3	62.0	62.5	63.0	63.3	63.3	63.3	
GE 1800	61.2	61.5	62.4	63.3	64.5	64.5	65.5	66.0	66.6	66.9	66.9	66.9	
GE 1500	65.6	66.0	66.9	68.0	69.2	69.6	71.0	71.9	72.6	72.9	73.0	73.0	
GE 1200	68.8	69.2	70.4	71.6	73.2	73.5	75.2	76.1	76.9	77.2	77.4	77.4	
GE 1000	70.5	71.1	72.3	73.7	75.9	76.1	78.1	79.1	80.1	80.6	80.9	80.9	
GE 900	71.2	71.9	73.2	74.7	77.1	77.4	79.4	81.0	81.9	82.5	82.7	82.7	
GE 800	71.6	72.5	73.8	75.5	78.0	78.3	80.4	82.3	83.5	84.3	84.9	84.9	
GE 700	72.2	73.0	74.3	76.0	78.6	78.9	81.4	83.9	85.4	86.1	87.1	87.2	
GE 600	72.3	73.1	74.4	76.2	79.1	79.5	82.3	85.1	86.8	87.7	89.0	89.1	
GE 500	72.3	73.1	74.5	76.5	79.6	80.1	83.1	86.2	88.3	89.8	91.1	91.2	
GE 400	72.4	73.2	74.7	76.7	79.8	80.5	83.9	87.4	90.1	91.8	93.4	93.8	
GE 300	72.4	73.2	74.7	76.7	79.8	80.5	84.2	88.0	90.9	93.0	94.9	95.3	
GE 200	72.4	73.2	74.7	76.7	79.8	80.5	84.2	88.2	91.3	93.8	95.9	96.2	
GE 100	72.4	73.2	74.7	76.7	79.8	80.5	84.2	88.2	91.3	94.0	96.3	96.7	
GE 000	72.4	73.2	74.7	76.7	79.8	80.5	84.2	88.2	91.3	94.0	96.3	96.7	

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 18-20

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
27.8	27.8	27.8	27.8	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1
32.3	32.4	32.4	32.4	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6	32.6
32.8	33.1	33.1	33.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
32.3	33.1	33.1	33.1	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3	33.3
33.8	34.1	34.1	34.1	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3	34.3
34.9	35.3	35.3	35.3	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5	35.5
36.8	37.1	37.1	37.1	37.3	37.3	37.3	37.3	37.3	37.3	37.3	37.3	37.3
37.3	37.6	37.6	37.6	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8	37.8
38.5	39.8	39.8	39.8	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0	39.0
39.6	40.0	40.0	40.0	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2	40.2
40.4	40.9	40.9	40.9	41.1	41.1	41.1	41.1	41.1	41.1	41.1	41.1	41.1
41.9	42.5	42.5	42.5	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7	42.7
42.7	43.2	43.2	43.2	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4	43.4
44.2	44.7	44.7	44.9	45.2	45.3	45.3	45.3	45.3	45.3	45.3	45.3	45.3
45.1	45.6	45.6	45.8	46.0	46.1	46.1	46.1	46.1	46.1	46.1	46.1	46.1
45.1	48.5	48.5	48.9	49.2	49.4	49.4	49.4	49.4	49.4	49.4	49.4	49.4
52.7	53.7	53.7	54.0	54.3	54.8	54.9	54.9	54.9	54.9	54.9	54.9	54.9
60.2	61.3	61.3	62.0	62.5	63.0	63.3	63.3	63.3	63.3	63.3	63.3	63.3
63.3	64.5	64.5	65.5	66.0	66.6	66.9	66.9	66.9	66.9	66.9	66.9	66.9
68.0	69.2	69.6	71.0	71.9	72.6	72.9	73.0	73.0	73.0	73.0	73.0	73.0
71.5	73.2	73.5	75.2	76.1	76.9	77.2	77.4	77.4	77.4	77.4	77.4	77.4
73.7	75.8	76.1	78.1	79.1	80.1	80.6	80.9	80.9	80.9	80.9	80.9	80.9
74.7	77.1	77.4	79.4	81.0	81.9	82.5	82.7	82.7	82.8	82.8	82.8	82.8
75.5	78.0	78.3	80.4	82.3	83.5	84.3	84.9	84.9	85.1	85.1	85.1	85.1
75.0	78.6	78.9	81.4	83.9	85.4	86.1	87.1	87.2	87.3	87.4	87.4	87.4
76.2	79.1	79.5	82.3	85.1	86.8	87.7	89.0	89.1	89.4	89.5	89.5	89.5
76.5	79.6	80.1	83.1	86.2	88.3	89.8	91.1	91.2	91.4	91.6	91.6	91.6
76.7	79.8	80.5	83.9	87.4	90.1	91.8	93.4	93.8	94.2	94.4	94.4	94.4
75.7	79.8	80.5	84.2	88.0	90.9	93.0	94.9	95.3	96.1	96.3	96.3	96.9
76.7	79.8	80.5	84.2	88.2	91.3	93.8	95.9	96.2	97.3	97.6	98.0	98.9
76.7	79.8	80.5	84.2	88.2	91.3	94.0	96.3	96.7	97.8	98.2	98.8	100.0
76.7	79.8	80.5	84.2	88.2	91.3	94.0	96.3	96.7	97.8	98.2	98.8	100.0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: DEC HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	26.1	26.2	26.3	26.3	26.6	26.6	26.7	26.8	26.8	26.8	26.8	26.8	26.8
GE 20000	29.5	29.6	29.7	29.7	29.9	29.9	30.0	30.1	30.1	30.1	30.1	30.1	30.1
GE 18000	29.9	30.0	30.1	30.1	30.3	30.3	30.4	30.5	30.5	30.5	30.5	30.5	30.5
GE 16000	30.0	30.1	30.2	30.2	30.4	30.4	30.5	30.6	30.6	30.6	30.6	30.6	30.6
GE 14000	30.4	30.5	30.6	30.6	30.9	30.9	31.0	31.1	31.1	31.1	31.1	31.1	31.1
GE 12000	31.2	31.3	31.4	31.4	31.6	31.6	31.7	31.8	31.8	31.8	31.8	31.8	31.8
GE 10000	33.9	34.0	34.1	34.1	34.4	34.4	34.5	34.6	34.6	34.6	34.6	34.6	34.6
GE 9000	34.1	34.2	34.3	34.3	34.6	34.6	34.7	34.8	34.8	34.8	34.8	34.8	34.8
GE 8000	34.8	34.9	35.1	35.1	35.6	35.6	35.8	35.9	35.9	35.9	35.9	35.9	35.9
GE 7000	35.6	35.7	35.8	35.9	36.5	36.5	36.7	36.8	36.8	36.8	36.8	36.8	36.8
GE 6000	35.7	35.8	35.9	36.0	36.6	36.6	36.9	37.0	37.0	37.0	37.0	37.0	37.0
GE 5000	37.7	37.8	38.1	38.2	38.7	38.7	39.0	39.1	39.1	39.1	39.1	39.1	39.1
GE 4500	38.3	38.4	38.6	38.7	39.6	39.6	39.9	40.0	40.0	40.0	40.1	40.1	40.1
GE 4000	40.4	40.5	40.8	40.9	41.7	41.7	42.0	42.2	42.2	42.2	42.3	42.3	42.3
GE 3500	42.2	42.3	42.6	42.8	43.7	43.7	44.3	44.4	44.4	44.4	44.5	44.5	44.5
GE 3000	44.1	44.2	44.6	45.1	46.2	46.3	47.1	47.2	47.2	47.2	47.3	47.3	47.3
GE 2500	49.7	49.9	50.9	51.4	53.0	53.4	54.2	54.5	54.5	54.6	54.7	54.7	54.7
GE 2000	56.7	56.9	58.3	58.8	60.9	61.3	62.7	63.2	63.3	63.5	63.7	63.7	63.7
GE 1800	59.4	59.6	61.1	61.6	63.8	64.2	65.9	66.6	66.7	66.9	67.0	67.0	67.0
GE 1500	63.9	64.3	66.0	66.6	69.1	69.6	71.7	72.6	72.7	73.0	73.3	73.3	73.3
GE 1200	65.9	66.3	68.1	68.7	71.7	72.4	74.5	75.4	75.5	75.9	76.2	76.2	76.2
GE 1000	66.9	67.3	69.4	70.4	73.4	74.1	76.5	77.3	77.4	77.8	78.2	78.2	78.2
GE 900	67.5	68.0	70.1	71.2	74.7	75.4	78.0	78.9	79.0	79.5	79.8	79.8	79.8
GE 800	67.4	68.3	70.6	71.3	75.5	76.1	78.9	80.0	80.6	81.2	81.9	81.9	82.0
GE 700	68.2	68.7	71.1	72.4	76.1	76.8	80.1	81.7	82.9	84.1	84.8	84.8	84.8
GE 600	68.7	69.4	71.7	73.1	77.4	78.1	81.6	83.5	84.9	86.5	87.7	87.7	87.7
GE 500	68.8	69.5	72.2	73.7	78.1	78.8	82.3	84.9	87.0	88.9	90.3	90.4	90.4
GE 400	68.9	69.6	72.5	74.0	78.4	79.5	83.4	85.6	87.7	89.7	91.3	91.4	91.4
GE 300	68.9	69.6	72.5	74.0	78.7	79.9	84.6	87.1	89.8	92.0	94.0	94.1	94.1
GE 200	68.9	69.6	72.5	74.0	78.7	79.9	84.6	87.1	90.2	93.3	95.6	95.8	96.0
GE 100	68.9	69.6	72.5	74.0	78.7	79.9	84.6	87.1	90.2	93.5	96.0	96.2	97.0
GE 000	68.9	69.6	72.5	74.0	78.7	79.9	84.6	87.1	90.2	93.5	96.0	96.2	97.0

TOTAL NUMBER OF OBSERVATIONS 930

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: 21-23

VISIBILITY IN STATUTE MILES

	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
30.3	26.6	26.6	26.7	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8	26.8
30.7	29.9	29.9	30.0	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1	30.1
30.1	30.3	30.3	30.4	30.5	30.5	30.5	30.5	30.5	30.5	30.5	30.5	30.5
30.2	30.4	30.4	30.5	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6	30.6
30.9	30.9	30.9	31.0	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1
30.4	31.6	31.6	31.7	31.8	31.8	31.8	31.8	31.8	31.8	31.8	31.8	31.8
30.1	34.4	34.4	34.5	34.6	34.6	34.6	34.6	34.6	34.6	34.6	34.6	34.6
30.3	34.6	34.6	34.7	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8	34.8
30.1	35.6	35.6	35.8	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9	35.9
30.9	36.5	36.5	36.7	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8	36.8
30.0	36.6	36.6	36.9	37.0	37.0	37.0	37.0	37.0	37.0	37.0	37.0	37.0
30.2	38.7	38.7	39.0	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1	39.1
30.7	37.6	39.6	39.9	40.0	40.0	40.0	40.1	40.1	40.1	40.1	40.1	40.1
30.9	41.7	41.7	42.0	42.2	42.2	42.2	42.3	42.3	42.3	42.3	42.3	42.3
40.7	43.7	43.7	44.3	44.4	44.4	44.4	44.5	44.5	44.5	44.5	44.5	44.5
40.1	46.2	46.3	47.1	47.2	47.2	47.2	47.3	47.3	47.3	47.3	47.3	47.3
40.4	53.0	53.4	54.2	54.5	54.5	54.6	54.7	54.7	54.7	54.7	54.7	54.7
40.3	60.9	61.3	62.7	63.2	63.3	63.5	63.7	63.7	63.7	63.7	63.7	63.7
40.5	63.8	64.2	65.9	66.6	66.7	66.9	67.0	67.0	67.0	67.0	67.0	67.0
60.0	69.1	69.6	71.7	72.6	72.7	73.0	73.3	73.3	73.4	73.4	73.4	73.4
60.7	71.7	72.4	74.5	75.4	75.5	75.9	76.2	76.2	76.3	76.3	76.5	76.5
70.4	73.4	74.1	76.5	77.3	77.4	77.8	78.2	78.2	78.3	78.3	78.4	78.4
70.2	74.7	75.4	78.0	78.9	79.0	79.5	79.8	79.8	79.9	79.9	80.0	80.0
70.1	75.5	76.1	78.9	80.0	80.6	81.2	81.9	81.9	82.0	82.0	82.2	82.2
70.4	76.1	75.8	80.1	81.7	82.9	84.1	84.8	84.8	84.9	84.9	85.1	85.1
80.1	77.4	78.1	81.6	83.5	84.9	86.5	87.7	87.7	87.8	87.8	88.0	88.0
80.7	78.1	78.8	82.8	84.9	87.0	88.9	90.3	90.4	90.6	90.6	90.8	90.8
80.0	78.4	79.5	83.4	85.6	87.7	89.7	91.3	91.4	91.7	91.7	91.8	91.8
90.1	78.7	79.9	84.6	87.1	89.8	92.0	94.0	94.1	94.8	94.9	95.2	95.6
91.0	78.7	79.9	84.6	87.1	90.2	93.3	95.6	95.8	96.8	97.0	97.5	98.7
90.0	78.7	79.9	84.6	87.1	90.2	93.5	96.0	96.2	97.2	97.4	98.4	100.0
97.0	78.7	79.9	84.6	87.1	90.2	93.5	96.0	96.2	97.2	97.4	98.4	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
 LST TO UTC: + 5 MONTH: DEC HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES													
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	
NO CEIL	26.1	26.3	26.5	26.7	26.9	26.9	27.0	27.2	27.2	27.3	27.3	27.3	27.3	
GE 20000	29.4	29.5	29.8	30.0	30.2	30.2	30.4	30.5	30.6	30.6	30.6	30.6	30.7	
GE 18000	29.9	30.0	30.3	30.5	30.7	30.8	30.9	31.0	31.1	31.2	31.2	31.2	31.2	
GE 16000	30.1	30.2	30.4	30.7	30.9	30.9	31.0	31.2	31.2	31.2	31.3	31.3	31.3	
GE 14000	30.7	30.3	31.1	31.3	31.5	31.6	31.7	31.8	31.9	32.0	32.0	32.0	32.0	
GE 12000	31.6	31.7	32.1	32.3	32.5	32.5	32.7	32.8	32.8	32.9	32.9	32.9	32.9	
GE 10000	33.4	33.6	33.9	34.1	34.3	34.4	34.5	34.7	34.7	34.8	34.8	34.8	34.8	
GE 9000	33.8	33.9	34.2	34.4	34.7	34.7	34.9	35.0	35.1	35.1	35.2	35.2	35.2	
GE 8000	35.1	35.3	35.6	35.8	36.1	36.2	36.3	36.5	36.5	36.6	36.6	36.6	36.6	
GE 7000	35.9	36.0	36.4	36.7	37.0	37.1	37.3	37.4	37.5	37.6	37.6	37.6	37.6	
GE 6000	36.3	36.5	36.9	37.2	37.5	37.6	37.8	37.9	38.0	38.1	38.1	38.1	38.1	
GE 5000	37.7	37.9	38.3	38.7	39.0	39.1	39.3	39.5	39.6	39.6	39.7	39.7	39.7	
GE 4500	38.3	38.5	39.0	39.3	39.7	39.9	40.1	40.2	40.3	40.4	40.4	40.4	40.5	
GE 4000	40.0	40.2	40.7	41.1	41.5	41.7	42.0	42.2	42.3	42.4	42.4	42.4	42.4	
GE 3500	41.0	41.3	41.8	42.3	42.7	42.9	43.3	43.5	43.6	43.7	43.7	43.7	43.7	
GE 3000	43.1	43.4	44.0	44.5	45.3	45.4	45.9	46.1	46.2	46.3	46.3	46.3	46.4	
GE 2500	47.7	48.1	49.0	49.5	50.5	50.8	51.4	51.7	51.9	52.1	52.1	52.1	52.2	
GE 2000	53.8	54.2	55.7	56.4	57.8	58.2	59.4	59.9	60.3	60.6	60.7	60.7	60.7	
GE 1800	56.7	57.2	58.8	59.6	61.2	61.5	63.0	63.6	64.0	64.4	64.4	64.4	64.5	
GE 1500	61.8	62.4	64.5	65.4	67.4	67.9	69.8	70.6	71.3	71.7	71.8	71.8	71.9	
GE 1200	64.1	64.8	67.4	68.4	70.7	71.3	73.4	74.5	75.1	75.6	75.8	75.9	76.0	
GE 1000	65.5	66.2	69.0	70.3	72.7	73.3	75.7	77.0	77.8	78.4	78.8	78.8	78.9	
GE 900	66.2	67.0	69.9	71.2	73.8	74.4	77.1	78.5	79.4	80.1	80.5	80.5	80.7	
GE 800	66.6	67.5	70.5	71.9	74.7	75.4	78.3	79.9	81.3	82.1	82.8	82.8	83.0	
GE 700	67.0	68.0	71.0	72.6	75.6	76.4	79.8	81.9	83.7	84.8	85.6	85.7	86.0	
GE 600	67.3	68.3	71.5	73.1	76.5	77.3	81.2	83.5	85.6	86.9	88.0	88.1	88.5	
GE 500	67.4	68.5	71.8	73.5	77.2	78.1	82.2	84.8	87.3	88.9	90.3	90.6	91.3	
GE 400	67.5	68.7	72.1	73.8	77.6	78.6	82.9	85.8	88.5	90.4	91.9	92.2	93.1	
GE 300	67.5	68.7	72.1	73.8	77.7	78.5	83.3	85.6	89.9	92.0	93.9	94.2	95.3	
GE 200	67.6	68.7	72.1	73.8	77.8	78.8	83.5	86.9	90.3	92.7	95.0	95.4	96.7	
GE 100	67.6	68.7	72.1	73.8	77.8	78.8	83.5	86.9	90.4	92.9	95.2	95.6	97.0	
GE 000	67.6	68.7	72.1	73.8	77.8	78.8	83.5	86.9	90.4	92.9	95.2	95.6	97.0	

TOTAL NUMBER OF OBSERVATIONS 7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC HOURS: ALL

	VISIBILITY IN STATUTE MILES											
	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
26.7	26.9	26.9	27.0	27.2	27.2	27.3	27.3	27.3	27.3	27.3	27.3	27.3
27.0	30.2	30.2	30.4	30.5	30.6	30.6	30.6	30.6	30.7	30.7	30.7	30.7
27.5	30.7	30.8	30.9	31.0	31.1	31.2	31.2	31.2	31.2	31.2	31.2	31.2
27.7	30.9	30.9	31.0	31.2	31.2	31.3	31.3	31.3	31.3	31.3	31.4	31.4
27.5	31.5	31.6	31.7	31.8	31.9	32.0	32.0	32.0	32.0	32.0	32.0	32.0
27.3	32.5	32.5	32.7	32.8	32.8	32.9	32.9	32.9	32.9	32.9	33.0	33.0
27.1	34.3	34.4	34.5	34.7	34.7	34.8	34.8	34.8	34.8	34.8	34.9	34.9
27.4	34.7	34.7	34.9	35.0	35.1	35.1	35.2	35.2	35.2	35.2	35.2	35.2
27.3	36.1	36.2	36.3	36.5	36.5	36.6	36.6	36.6	36.6	36.6	36.7	36.7
27.7	37.0	37.1	37.3	37.4	37.5	37.6	37.6	37.6	37.6	37.6	37.6	37.6
27.2	37.5	37.5	37.8	37.9	38.0	38.1	38.1	38.1	39.1	38.1	38.1	38.1
27.7	39.0	39.1	39.3	39.5	39.6	39.6	39.7	39.7	39.7	39.7	39.7	39.7
27.3	39.7	39.9	40.1	40.2	40.3	40.4	40.4	40.4	40.5	40.5	40.5	40.5
27.1	41.5	41.7	42.0	42.2	42.3	42.4	42.4	42.4	42.4	42.4	42.5	42.5
27.3	42.7	42.9	43.3	43.5	43.6	43.7	43.7	43.7	43.7	43.7	43.8	43.8
27.0	45.3	45.4	45.9	46.1	46.2	46.3	46.3	46.3	46.4	46.4	46.4	46.4
27.0	50.5	50.8	51.4	51.7	51.9	52.1	52.1	52.1	52.2	52.2	52.2	52.2
27.4	57.8	58.2	59.4	59.9	60.3	60.6	60.7	60.7	60.7	60.7	60.8	60.8
27.5	61.2	61.5	63.0	63.6	64.0	64.4	64.4	64.4	64.5	64.5	64.5	64.5
27.4	67.4	67.9	69.8	70.6	71.3	71.7	71.8	71.8	71.9	71.9	72.0	72.0
27.4	70.7	71.3	73.4	74.5	75.1	75.6	75.8	75.9	76.0	76.0	76.0	76.0
27.3	72.7	73.3	75.7	77.0	77.8	78.4	78.8	78.8	78.9	78.9	79.0	79.0
27.2	73.8	74.4	77.1	78.5	79.4	80.1	80.5	80.5	80.7	80.7	80.8	80.8
27.7	74.7	75.4	78.3	79.9	81.3	82.1	82.8	82.8	83.0	83.0	83.2	83.2
27.5	75.6	76.4	79.8	81.9	83.7	84.8	85.6	85.7	86.0	86.2	86.4	86.4
27.1	75.5	77.3	81.2	83.5	85.5	86.9	88.0	88.1	88.5	88.6	88.8	88.9
27.5	77.2	78.1	82.2	84.8	87.3	88.9	90.3	90.6	91.3	91.4	91.7	91.8
27.5	77.6	78.6	82.9	85.8	88.5	90.4	91.9	92.2	93.1	93.3	93.6	93.8
27.5	77.7	78.8	83.3	86.6	89.9	92.0	93.9	94.2	95.3	95.6	96.0	96.4
27.8	77.8	78.8	83.5	86.9	90.3	92.7	95.0	95.4	96.7	97.2	97.8	98.6
27.7	77.8	78.8	83.5	86.9	90.4	92.9	95.2	95.6	97.0	97.6	98.6	100.0
27.8	77.8	78.8	83.5	86.9	90.4	92.9	95.2	95.6	97.0	97.6	98.7	100.0

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: ALL HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES												
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2
NO CEIL	38.9	39.3	39.8	40.1	40.5	40.6	40.7	40.8	40.9	41.0	41.0	41.0	41.1
GE 20000	43.9	44.4	45.0	45.3	45.8	45.9	46.0	46.2	46.2	46.3	46.4	46.4	46.4
GE 18000	44.2	44.7	45.3	45.7	46.2	46.3	46.4	46.6	46.6	46.7	46.8	46.8	46.8
GE 16000	44.4	44.9	45.5	45.8	46.3	46.4	46.5	46.7	46.8	46.8	46.9	46.9	47.0
GE 14000	45.2	45.7	46.3	46.7	47.1	47.3	47.4	47.6	47.6	47.7	47.8	47.8	47.8
GE 12000	46.4	46.9	47.6	47.9	48.5	48.6	48.8	48.9	49.0	49.1	49.1	49.1	49.2
GE 10000	48.7	49.2	50.0	50.4	50.9	51.1	51.2	51.4	51.5	51.5	51.6	51.6	51.7
GE 9000	49.2	49.8	50.5	50.9	51.5	51.6	51.8	52.0	52.0	52.1	52.2	52.2	52.2
GE 8000	51.3	51.8	52.7	53.1	53.7	53.9	54.1	54.3	54.3	54.4	54.5	54.5	54.5
GE 7000	52.4	53.0	53.9	54.3	55.0	55.1	55.4	55.6	55.6	55.7	55.8	55.8	55.8
GE 6000	53.3	53.9	54.8	55.3	56.0	56.1	56.4	56.6	56.6	56.7	56.8	56.8	56.9
GE 5000	55.1	55.8	56.8	57.4	58.1	58.3	58.6	58.8	58.9	59.0	59.0	59.0	59.1
GE 4500	56.1	56.9	57.9	58.5	59.3	59.5	59.8	60.0	60.1	60.2	60.2	60.2	60.3
GE 4000	58.2	59.0	60.2	60.8	61.8	62.0	62.3	62.6	62.7	62.8	62.8	62.9	62.9
GE 3500	59.6	60.4	61.6	62.3	63.3	63.5	63.9	64.1	64.3	64.4	64.4	64.4	64.5
GE 3000	61.8	62.6	63.9	64.7	65.8	66.0	66.5	66.8	66.9	67.0	67.0	67.1	67.1
GE 2500	64.4	65.3	66.8	67.6	69.9	69.2	69.7	70.0	70.2	70.3	70.4	70.4	70.5
GE 2000	67.7	68.7	70.4	71.4	72.9	73.3	74.0	74.5	74.7	74.9	75.0	75.0	75.1
GE 1800	68.9	69.9	71.7	72.7	74.4	74.8	75.6	76.1	76.3	76.5	76.6	76.6	76.7
GE 1500	71.2	72.3	74.4	75.5	77.4	77.9	78.9	79.6	79.9	80.2	80.4	80.4	80.5
GE 1200	72.8	73.9	76.2	77.4	79.5	80.0	81.2	82.0	82.4	82.7	82.9	83.0	83.1
GE 1000	73.8	75.0	77.4	78.7	81.0	81.5	82.9	83.8	84.3	84.6	84.9	85.0	85.2
GE 900	74.3	75.6	78.1	79.5	81.9	82.5	83.9	84.9	85.4	85.8	86.1	86.2	86.4
GE 800	74.8	76.1	78.7	80.2	82.7	83.3	84.9	86.0	86.6	87.1	87.5	87.5	87.7
GE 700	75.2	76.5	79.2	80.8	83.5	84.2	85.9	87.1	87.8	88.4	88.9	88.9	89.2
GE 600	75.5	76.8	79.6	81.3	84.3	85.1	86.9	88.3	89.2	89.8	90.3	90.4	90.7
GE 500	75.7	77.1	80.1	81.9	85.1	86.0	88.1	89.8	90.8	91.6	92.3	92.4	92.8
GE 400	75.9	77.3	80.3	82.2	85.5	86.5	89.0	90.9	92.1	93.0	93.8	94.0	94.4
GE 300	75.9	77.4	80.5	82.4	85.9	86.9	89.6	91.8	93.4	94.5	95.5	95.7	96.3
GE 200	75.9	77.4	80.5	82.4	86.0	87.1	89.8	92.2	94.0	95.3	96.5	96.7	97.6
GE 100	75.9	77.4	80.5	82.4	86.0	87.1	89.8	92.2	94.0	95.4	96.6	96.9	97.8
GE 000	75.9	77.4	80.5	82.4	86.0	87.1	89.8	92.2	94.0	95.4	96.6	96.9	97.8

TOTAL NUMBER OF OBSERVATIONS: 87667

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: ALL HOURS: ALL

VISIBILITY IN STATUTE MILES

GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
40.1	40.5	40.6	40.7	40.8	40.9	41.0	41.0	41.0	41.1	41.1	41.1	41.1
45.3	45.8	45.9	46.0	46.2	46.2	46.3	46.4	46.4	46.4	46.4	46.5	46.5
45.7	46.2	46.3	46.4	46.6	46.6	46.7	46.8	46.8	46.8	46.8	46.9	46.9
45.3	46.3	46.4	46.5	46.7	46.8	46.8	46.9	46.9	47.0	47.0	47.0	47.0
46.7	47.1	47.3	47.4	47.6	47.6	47.7	47.8	47.8	47.8	47.8	47.9	47.9
47.9	48.5	48.6	48.8	48.9	49.0	49.1	49.1	49.1	49.2	49.2	49.2	49.3
50.4	50.9	51.1	51.2	51.4	51.5	51.5	51.6	51.6	51.7	51.7	51.7	51.8
50.9	51.5	51.6	51.8	52.0	52.0	52.1	52.2	52.2	52.2	52.2	52.3	52.3
53.1	53.7	53.9	54.1	54.3	54.3	54.4	54.5	54.5	54.5	54.6	54.6	54.6
54.3	55.0	55.1	55.4	55.6	55.6	55.7	55.8	55.8	55.8	55.9	55.9	55.9
55.3	56.0	56.1	56.4	56.6	56.7	56.7	56.8	56.8	56.9	56.9	56.9	57.0
57.4	58.1	58.3	58.6	58.8	58.9	59.0	59.0	59.0	59.1	59.1	59.2	59.2
58.5	59.3	59.5	59.8	60.0	60.1	60.2	60.2	60.2	60.3	60.3	60.4	60.4
60.8	61.8	62.0	62.3	62.5	62.7	62.8	62.8	62.9	62.9	62.9	63.0	63.0
62.3	63.3	63.5	63.9	64.1	64.3	64.4	64.4	64.4	64.5	64.5	64.6	64.6
64.7	65.8	66.0	66.5	66.8	66.9	67.0	67.0	67.1	67.1	67.2	67.2	67.2
67.6	69.9	69.2	69.7	70.0	70.2	70.3	70.4	70.4	70.5	70.5	70.6	70.6
71.4	72.9	73.3	74.0	74.5	74.7	74.9	75.0	75.0	75.1	75.2	75.2	75.2
72.7	74.4	74.8	75.6	76.1	76.3	76.5	76.6	76.6	76.7	76.8	76.8	76.9
75.5	77.4	77.9	78.9	79.5	79.9	80.2	80.4	80.4	80.5	80.6	80.6	80.7
77.4	79.5	80.0	81.2	82.0	82.4	82.7	82.9	83.0	83.1	83.2	83.2	83.3
74.7	81.0	81.5	82.9	83.8	84.3	84.6	84.9	85.0	85.2	85.3	85.3	85.4
77.5	81.9	82.5	83.9	84.9	85.4	85.8	86.1	86.2	86.4	86.4	86.5	86.6
80.2	82.7	83.3	84.9	86.0	86.6	87.1	87.5	87.5	87.7	87.8	87.9	88.0
80.8	83.5	84.2	85.9	87.1	87.8	88.4	88.9	88.9	89.2	89.3	89.4	89.5
81.3	84.3	85.1	86.9	88.3	89.2	89.8	90.3	90.4	90.7	90.9	91.0	91.1
81.9	85.1	86.0	88.1	89.8	90.8	91.6	92.3	92.4	92.8	93.0	93.1	93.3
82.2	85.5	86.5	89.0	90.9	92.1	93.0	93.8	94.0	94.4	94.6	94.9	95.0
82.4	85.9	86.9	89.6	91.8	93.4	94.5	95.5	95.7	96.3	96.6	96.9	97.1
82.4	86.0	87.1	89.8	92.2	94.0	95.3	96.5	96.7	97.6	98.0	98.6	99.0
82.4	86.0	87.1	89.8	92.2	94.0	95.4	96.6	96.9	97.8	98.3	99.1	99.9
82.4	86.0	87.1	89.8	92.2	94.0	95.4	96.6	96.9	97.8	98.3	99.1	100.0

47657

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: JAN HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	14.6	14.3	15.5	47.7	7.8	71.1	8.3	930
03-05	13.5	14.8	14.2	50.4	7.0	71.6	7.1	930
06-08	8.9	16.6	18.9	47.2	8.4	74.5	7.6	930
09-11	3.0	20.6	23.9	43.8	8.7	76.3	10.0	930
12-14	3.1	21.0	27.5	40.2	8.2	75.9	7.2	930
15-17	2.2	22.7	26.2	42.0	6.9	75.2	5.9	930
18-20	7.3	20.6	21.9	42.4	7.8	72.0	6.1	930
21-23	12.8	14.7	16.9	47.1	8.5	72.5	6.8	930
ALL HOURS	8.0	18.0	20.0	45.0	7.0	73.0	7.0	7440

MONTH: FEB HOURS: ALL

00-02	15.6	14.8	14.8	46.4	7.3	68.6	5.8	849
03-05	15.0	16.6	17.0	43.2	8.2	69.4	7.7	849
06-08	9.8	19.3	20.5	41.2	9.2	70.9	6.6	849
09-11	3.2	19.6	27.8	39.8	9.7	77.3	7.7	849
12-14	2.2	19.4	30.0	42.2	6.1	78.3	7.9	849
15-17	1.9	20.3	30.7	42.3	4.8	77.9	5.3	849
18-20	3.4	25.6	22.6	43.9	4.5	71.0	4.8	849
21-23	11.1	22.0	15.9	45.7	5.3	66.9	6.5	849
ALL HOURS	7.9	19.7	22.4	43.1	6.9	72.4	6.6	6792

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN HOURS: ALL

AIRWAY CLASSES

BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
15.5	47.7	7.8	71.1	8.3	930
14.2	50.4	7.0	71.6	7.1	930
13.9	47.2	8.4	74.5	7.6	930
23.9	43.8	8.7	76.3	10.0	930
27.5	40.2	8.2	75.9	7.2	930
26.2	42.0	6.9	75.2	5.9	930
21.3	42.4	7.8	72.0	6.1	930
16.9	47.1	8.5	72.5	6.8	930
20.0	45.0	7.0	73.0	7.0	7440

MONTH: FEB HOURS: ALL

14.8	46.7	7.3	68.6	5.8	849
17.0	43.2	8.2	68.4	7.7	849
20.5	41.2	9.2	70.9	6.6	849
27.8	39.8	9.7	77.3	7.7	849
30.0	42.2	6.1	78.3	7.9	849
30.7	42.3	4.8	77.9	5.3	849
22.6	43.9	4.5	71.0	4.8	849
15.9	45.7	5.3	66.9	6.5	849
22.4	43.1	6.9	72.4	6.6	6792

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: MAR HOURS: ALL

HOURS (LST)	CLEAR	SCATTERED	BROKEN	AIRWAY CLASSES		GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
				OVERCAST	TOTAL OBSCURATION			
00-02	21.0	15.4	14.7	41.6	7.3	63.7	5.2	930
03-05	17.8	15.5	14.2	43.8	8.7	66.7	5.7	930
06-08	8.4	22.2	19.0	42.0	8.4	69.5	8.1	930
09-11	5.5	19.7	25.9	40.4	8.5	74.8	8.7	930
12-14	3.1	22.7	25.2	42.9	6.1	74.2	6.0	930
15-17	3.1	25.3	23.4	41.7	6.5	71.6	4.9	930
18-20	4.7	27.7	19.0	41.5	7.0	67.5	4.3	930
21-23	19.0	21.1	13.4	39.0	7.4	59.9	4.2	930
ALL HOURS	10.0	21.0	19.0	41.0	7.0	68.0	5.0	7440

MONTH: APR HOURS: ALL

00-02	25.4	20.4	14.8	34.9	4.4	54.1	2.3	900
03-05	22.6	20.9	15.2	34.7	6.7	56.6	4.1	900
06-08	8.7	26.6	24.4	33.7	6.7	64.8	4.2	900
09-11	7.3	24.4	26.9	36.4	4.9	68.2	4.2	900
12-14	4.4	26.4	27.8	38.8	2.6	69.1	3.3	900
15-17	4.6	32.2	24.2	36.7	2.3	63.2	2.4	900
18-20	5.0	32.1	24.3	35.9	2.7	62.9	2.3	900
21-23	16.8	28.9	16.3	33.9	4.1	54.3	3.1	900
ALL HOURS	11.8	26.5	21.8	35.6	4.3	61.7	3.3	7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR HOURS: ALL

AIRWAY CLASSES

FILTERED	BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
15.4	14.7	41.6	7.3	63.7	5.2	930
15.5	14.2	43.8	8.7	66.7	5.7	930
22.2	19.0	42.0	8.4	69.5	8.1	930
19.7	25.9	40.4	8.5	74.8	8.7	930
22.7	25.2	42.9	6.1	74.2	6.0	930
25.3	23.4	41.7	6.5	71.6	4.9	930
17.7	19.0	41.5	7.0	67.5	4.3	930
11.1	13.4	39.0	7.4	59.9	4.2	930
21.0	19.0	41.0	7.0	68.0	5.0	7440

MONTH: APR HOURS: ALL

20.4	14.8	34.9	4.4	54.1	2.3	900
20.9	15.2	34.7	6.7	56.6	4.1	900
20.6	24.4	33.7	6.7	64.8	4.2	900
24.4	26.9	36.4	4.9	68.2	4.2	900
25.4	27.8	38.8	2.6	69.1	3.3	900
22.2	24.2	36.7	2.3	63.2	2.4	900
22.1	24.3	35.9	2.7	62.9	2.3	900
25.9	16.3	33.9	4.1	54.3	3.1	900
20.5	21.8	35.6	4.3	61.7	3.3	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAY HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	26.6	23.9	16.5	30.0	3.1	49.6	2.8	930
03-05	19.6	28.4	19.1	29.0	3.9	52.0	2.9	930
06-08	8.6	27.7	30.0	31.3	2.4	63.7	2.8	930
09-11	7.8	26.5	31.7	32.7	1.3	65.7	2.6	930
12-14	4.6	30.1	31.1	34.0	.2	65.3	2.5	930
15-17	3.2	34.3	32.6	29.6	.3	62.5	2.2	930
18-20	4.0	37.1	31.0	27.1	.9	58.9	1.9	930
21-23	11.9	37.3	24.0	24.1	2.7	50.8	1.9	930
ALL HOURS	10.0	30.0	26.0	29.0	1.0	58.0	2.0	7440

MONTH: JUN HOURS: ALL

00-02	26.1	28.1	17.0	26.1	2.7	45.8	1.6	900
03-05	16.1	35.3	20.3	24.9	2.9	48.6	1.2	900
06-08	10.0	34.2	27.2	22.9	1.7	51.3	1.9	900
09-11	4.8	38.9	33.0	22.1	1.2	56.3	1.0	900
12-14	1.8	35.1	36.3	26.3	.4	63.1	.7	900
15-17	1.1	33.3	40.7	24.6	.3	65.6	.7	900
18-20	4.2	38.1	32.7	24.2	.8	57.7	.9	900
21-23	8.4	39.1	26.1	25.2	1.1	52.4	1.6	900
ALL HOURS	9.1	35.8	29.2	24.5	1.4	55.2	1.2	7200

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY HOURS: ALL

AIRWAY CLASSES

BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
16.5	30.0	3.1	49.6	2.8	930
19.1	29.0	3.9	52.0	2.9	930
30.0	31.3	2.4	63.7	2.8	930
31.7	32.7	1.3	65.7	2.6	930
31.1	34.0	.2	65.3	2.5	930
32.6	29.6	.3	62.5	2.2	930
31.0	27.1	.9	58.9	1.9	930
24.0	24.1	2.7	50.8	1.9	930
26.0	29.0	1.0	58.0	2.0	7440

MONTH: JUN HOURS: ALL

17.0	26.1	2.7	45.8	1.6	900
20.3	24.9	2.9	48.6	1.2	900
27.2	22.9	1.7	51.3	1.9	900
33.0	22.1	1.2	56.3	1.0	900
36.3	26.3	.4	63.1	.7	900
40.7	24.6	.3	65.6	.7	900
32.7	24.2	.8	57.7	.9	900
26.1	25.2	1.1	52.4	1.6	900
29.2	24.5	1.4	55.2	1.2	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUL HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	25.9	35.7	16.0	20.1	2.3	38.4	3.4	930
03-05	18.5	37.4	21.1	20.6	2.4	44.1	6.5	930
06-08	7.8	38.4	31.0	20.2	2.6	53.8	7.5	930
09-11	5.3	39.8	33.1	21.4	.4	54.9	2.8	930
12-14	1.1	39.5	37.8	21.6		59.5	1.6	930
15-17	.3	36.5	41.9	20.6	.2	62.8	1.1	930
18-20	1.2	45.4	33.8	19.5	.1	53.4	1.6	928
21-23	7.0	47.6	24.8	20.1	.5	45.4	3.0	927
ALL HOURS	8.0	40.0	29.0	20.0	1.0	51.0	3.0	7435

MONTH: AUG HOURS: ALL

00-02	26.9	25.6	15.7	25.3	6.6	47.5	5.6	930
03-05	21.6	26.9	15.4	27.5	8.7	51.6	6.5	930
06-08	4.9	36.9	24.2	28.7	5.3	58.2	9.0	930
09-11	4.3	30.6	35.1	28.2	1.8	65.1	4.2	930
12-14	2.4	30.4	40.5	26.5	.2	67.2	1.7	930
15-17	1.4	38.6	33.2	26.7	.1	60.0	1.3	930
18-20	2.3	43.1	29.1	24.5	.4	54.1	1.5	930
21-23	14.6	38.0	19.8	25.1	2.6	47.4	3.5	930
ALL HOURS	9.9	33.8	26.6	26.5	3.2	56.4	4.2	7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL HOURS: ALL

AIRWAY CLASSES

BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
16.0	20.1	2.3	38.4	3.4	930
21.1	20.6	2.4	44.1	6.5	930
31.0	20.2	2.6	53.8	7.5	930
33.1	21.4	.4	54.9	2.8	930
37.8	21.6		59.5	1.6	930
41.9	20.6	.2	62.8	1.1	930
33.8	19.5	.1	53.4	1.6	928
24.8	20.1	.5	45.4	3.0	927
29.0	20.0	1.0	51.0	3.0	7435

MONTH: AUG HOURS: ALL

15.7	25.3	6.6	47.5	5.6	930
15.4	27.5	8.7	51.6	6.5	930
24.2	28.7	5.3	58.2	9.0	930
35.1	28.2	1.8	65.1	4.2	930
40.5	26.5	.2	67.2	1.7	930
33.2	26.7	.1	60.0	1.3	930
29.1	24.5	.4	54.1	1.5	930
19.8	25.1	2.6	47.4	3.5	930
26.6	26.5	3.2	56.4	4.2	7440

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: SEP HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	24.3	22.2	14.0	33.7	5.8	53.4	5.2	900
03-05	19.6	24.9	14.4	34.6	6.6	55.6	5.8	900
06-08	5.1	29.4	27.4	33.1	4.9	65.4	8.8	900
09-11	4.6	26.4	32.2	34.2	2.6	69.0	5.3	900
12-14	2.6	25.4	35.0	36.1	.9	72.0	2.8	900
15-17	1.8	23.6	37.0	31.9	.8	59.7	2.4	900
18-20	3.3	33.9	30.7	29.2	2.9	62.8	2.1	900
21-23	18.1	28.3	17.7	30.9	5.0	53.6	3.4	900
ALL HOURS	9.0	27.0	26.0	32.0	3.0	62.0	4.0	7200

MONTH: OCT HOURS: ALL

00-02	15.4	18.1	17.7	45.9	2.9	66.6	5.3	930
03-05	13.1	17.8	18.0	47.2	3.9	69.0	6.6	930
06-08	6.0	23.5	26.1	40.6	3.7	70.4	7.6	930
09-11	3.3	22.5	32.5	38.7	3.0	74.2	4.9	930
12-14	1.3	22.2	33.4	40.4	2.2	76.0	2.5	930
15-17	2.3	23.4	33.1	40.4	.8	74.3	1.9	930
18-20	4.5	27.7	23.9	43.1	.8	67.7	2.9	930
21-23	14.2	19.7	17.2	47.2	1.7	66.1	4.0	930
ALL HOURS	7.6	21.9	25.2	43.0	2.4	70.6	4.5	7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP HOURS: ALL

HOUR	AIRWAY CLASSES		TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	BROKEN	OVERCAST				
14.0	33.7	5.8	53.4	5.2	900	
14.4	34.6	6.6	55.6	5.8	900	
27.4	33.1	4.9	65.4	8.8	900	
32.2	34.2	2.6	69.0	5.3	900	
35.0	36.1	.9	72.0	2.8	900	
37.0	31.9	.8	69.7	2.4	900	
30.7	29.2	2.9	62.8	2.1	900	
17.7	30.9	5.0	53.6	3.4	900	
25.0	32.0	3.0	62.0	4.0	7200	

MONTH: OCT HOURS: ALL

17.7	45.9	2.9	66.6	5.3	930
18.0	47.2	3.9	69.0	6.6	930
26.1	40.6	3.7	70.4	7.6	930
32.5	38.7	3.0	74.2	4.9	930
33.4	40.4	2.2	76.0	2.5	930
33.1	40.4	.8	74.3	1.9	930
23.9	43.1	.8	67.7	2.9	930
17.2	47.2	1.7	66.1	4.0	930
25.2	43.0	2.4	70.6	4.5	7440

OPERATING LOCATION: WAW
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG
 MONTH: NOV HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	13.0	12.8	17.1	52.9	4.3	74.2	6.2	900
03-05	12.2	12.2	16.0	54.0	5.6	75.6	6.0	900
06-08	8.4	16.9	17.9	50.6	7.1	75.6	6.1	900
09-11	2.6	15.9	26.9	47.6	7.1	61.6	5.9	900
12-14	1.9	17.1	29.0	46.4	5.6	61.0	4.6	900
15-17	1.9	19.1	23.3	46.3	3.9	79.0	5.1	900
18-20	5.6	19.9	22.3	48.1	4.1	74.6	3.4	900
21-23	19.6	16.6	17.7	51.2	4.0	72.9	4.4	900
ALL HOURS	7.0	16.0	21.0	49.0	5.0	76.0	5.0	7200

MONTH: DEC HOURS: ALL

00-02	11.4	10.4	17.0	51.5	9.5	79.0	7.1	930
03-05	11.2	14.1	15.5	50.9	8.4	74.7	5.4	930
06-08	4.4	17.0	15.5	50.5	7.3	74.4	7.6	930
09-11	3.7	13.4	25.0	43.5	8.4	74.0	10.0	930
12-14	2.0	18.0	28.3	44.0	6.9	79.1	8.7	930
15-17	1.1	22.7	20.0	40.9	6.3	76.2	6.0	930
18-20	5.2	21.1	20.9	44.3	8.6	73.8	4.4	930
21-23	9.5	14.4	15.6	49.9	10.3	75.8	4.5	930
ALL HOURS	6.7	17.0	21.1	46.9	8.2	76.3	6.7	7440

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV HOURS: ALL

WIND KTS	AIRWAY CLASSES					TOTAL OBS
	BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	
17.1	52.8	4.3	74.2	6.2	900	
16.0	54.0	5.6	75.6	6.0	900	
17.9	50.6	7.1	75.6	6.1	900	
26.9	47.6	7.1	81.6	5.9	900	
29.0	46.4	5.6	81.0	4.6	900	
23.3	46.3	3.9	79.0	5.1	900	
22.3	43.1	4.1	74.6	3.4	900	
17.7	51.2	4.0	72.9	4.4	900	
21.0	49.0	5.0	76.0	5.0	7200	

MONTH: DEC HOURS: ALL

17.0	51.5	9.5	78.0	7.1	930
15.5	50.9	8.4	74.7	5.4	930
16.6	50.5	7.3	74.4	7.6	930
26.0	43.5	3.4	73.0	10.0	930
28.3	44.0	6.9	79.1	8.7	930
27.0	40.9	6.3	76.2	6.0	930
20.9	44.3	8.6	73.8	4.4	930
15.6	49.9	10.3	75.8	4.5	930
21.1	45.9	3.2	76.3	6.7	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: ALL HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02	20.6	20.2	15.9	34.0	5.3	59.2	4.9	1095
03-05	16.7	22.1	16.7	38.4	6.1	61.2	5.4	1095
06-08	7.7	25.0	23.6	30.8	5.6	66.1	6.5	1095
09-11	4.6	25.3	29.6	35.7	4.8	70.1	5.6	1095
12-14	2.7	25.7	31.8	36.6	3.3	71.7	4.1	1095
15-17	2.1	24.1	31.7	35.3	2.8	69.2	3.3	1095
18-20	4.3	31.1	26.0	35.3	3.4	64.7	3.0	1095
21-23	12.9	27.3	18.3	36.6	4.4	59.8	3.9	1095
ALL HOURS	9.0	25.7	24.3	36.6	4.5	65.3	4.6	8766

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 TO UTC: + 5 MONTH: ALL HOURS: ALL

AIRWAY CLASSES					
BROKEN	OVERCAST	TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
15.2	38.0	5.3	59.2	4.9	10959
16.7	38.4	6.1	61.2	5.4	10959
23.6	30.8	5.6	66.1	6.5	10959
29.6	35.7	4.8	70.1	5.6	10959
31.8	36.6	3.3	71.7	4.1	10959
31.7	35.3	2.8	69.2	3.3	10959
26.0	35.3	3.4	64.7	3.0	10957
18.3	36.6	4.4	59.3	3.9	10956
24.3	36.6	4.5	65.3	4.6	87667

pppppppp	AAAAAA	RRRRRRRR	TTTTTTTTT	EEEEEEEEEE
pppppppp	AAAAAAAA	RRRRRRRR	TTTTTTTTT	EEEEEEEEEE
pp pp	AA AA	RR RR	TT	EE
pp pp	AA AA	RR RR	TT	EE
pppppppp	AA AA	RRRRRRRR	TT	EEEEEE
pppppppp	AAAAAAAAAA	RRRRRRRR	TT	EEEEEE
pp	AAAAAAAAAA	RR RR	TT	EE
pp	AA AA	RR RR	TT	EE
pp	AA AA	RR RR	TT	EEEEEEEEEE
pp	AA AA	RR RR	TT	EEEEEEEEEE

PART E

TEMPERATURE AND RELATIVE HUMIDITY SUMMARIES

TEMPERATURE--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (PDF).

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA AND GIVE CUMULATIVE PDF FOR MAXIMUM, MINIMUM, AND MEAN TEMPERATURES, RESPECTIVELY. DATA IS SUMMARIZED BY MONTH FOR ALL YEARS COMBINED. TOTALS ARE GIVEN FOR THE WHOLE YEAR. DATA IS DISPLAYED USING 5-DEGREE FAHRENHEIT INCREMENTS (GE 0, GE 5, GE 10, ETC).. THERE IS ONE SPECIAL THRESHOLD FOR "GE 33" DEGREES. MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN.

NOTE 1. BEGINNING IN JANUARY 1946, DAILY MAXIMUM AND MINIMUM TEMPERATURES CAME ROUTINELY FROM HOURLY OBSERVATIONS ON AWS FORMS 10/10A OR FROM AUTOMATED DATA COLLECTION FROM ALL USAF-OPERATED STATIONS. REFER TO THE "STATION HISTORY" PAGE FOR DETAILED INFORMATION ON REPORTING PRACTICES.

MONTHLY TEMPERATURES.

ALSO FROM SUMMARY OF DAY DATA, THE TABLES GIVE MONTHLY MAXIMUM AND MINIMUM TEMPERATURES BY MONTH AND BY YEAR. THE YEARLY AMOUNT ONLY APPEARS WHEN ALL MONTHS FOR THAT YEAR ALSO APPEAR. MONTHLY RECORD TEMPERATURES (MAX AND MIN) ARE GIVEN, ALONG WITH TOTAL OBSERVATIONS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF DATA ARE AVAILABLE.

MEAN MONTHLY TEMPERATURE.

ALSO FROM SUMMARY OF DAY DATA, GIVES MONTHLY MEAN TEMPERATURE BY MONTH, FOR ALL MONTHS, AND FOR ALL YEARS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF DATA ARE AVAILABLE.

DRY BULB, WET BULB, AND DEW POINT TEMPERATURES.

THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS--DATA IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN. THE MEAN NUMBER OF HOURS WITH TEMPERATURES FOR VARIOUS THRESHOLDS ALSO APPEAR AS SPECIFIED IN EACH SUMMARY AND IN ACCORDANCE WITH AFM 88-29, "ENGINEERING WEATHER DATA," AND AWSP 105-56, "METEOROLOGICAL TECHNIQUES."

NOTE 1. WINTER WET BULB AND DEW POINT MEAN TEMPERATURES FOR VERY COLD STATIONS MUST BE USED WITH CAUTION. WHEN THE DRY BULB TEMPERATURE IS BELOW -35 DEGREES F, WET BULB TEMPERATURES ARE NOT REPORTED (FMH-18). AS A RESULT, WINTER MEAN DEW POINTS (AND MORE FREQUENTLY, WINTER MEAN WET BULB TEMPERATURES) ARE ACTUALLY LOWER THAN SHOWN IN THE TABLES. IN SOME HOUR GROUPS, IN FACT, MEAN WET BULB TEMPERATURES MAY ACTUALLY BE SHOWN AS EXCEEDING THE MEAN DRY BULB TEMPERATURES.

TEMPERATURE CONVERSION: $F = 1.8C + 32$

$C = K - 273.0$ (BEFORE 5 APRIL 77)

$C = K - 273.2$ (SINCE 5 APRIL 77)

RELATIVE HUMIDITY--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (POF).
CREATED FROM HOURLY OBSERVATIONS, THESE TABLES GIVE POF OF RELATIVE
HUMIDITY FOR 10% INCREMENTS. MEANS AND TOTAL OBSERVATION COUNTS ARE ALSO PROVIDED.
THE DATA IS SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MAXIMUM TEMPERA
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: +05

PERIOD OF RECORD
 MONTH: ALL HO

TEMP (DFG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
GE 100						.1	.2			
GE 95						.2	1.1			
GE 90					.7	2.3	3.9	1.9		.3
GE 85					2.6	7.6	13.2	7.6		1.7
GE 80				.3	8.0	17.7	33.5	23.1		5.9
GE 75				2.1	15.1	33.3	56.6	42.0		15.1
GE 70				5.6	26.4	63.2	77.8	64.9		27.3
GE 65			.1	10.3	39.9	70.9	90.8	82.6		44.2
GE 60			.9	16.8	52.9	84.9	98.2	94.1		63.3
GE 55		.1	1.9	26.6	65.3	93.9	99.7	99.4		81.2
GF 50		.6	5.7	30.3	73.3	98.7	100.0	100.0		94.0
GF 45	.2	1.9	11.2	53.7	91.2	99.9				99.1
GE 40	2.3	6.0	22.7	59.1	96.9	100.0				100.0
GE 35	7.6	13.9	40.5	84.3	99.0					96.3
GE 33	12.3	18.5	49.8	89.4	99.9					98.3
GE 30	20.0	27.5	61.2	95.5	100.0					99.9
GE 25	33.4	45.5	80.3	98.7						100.0
GE 20	52.1	64.6	90.4	99.8						
GE 15	69.8	74.7	97.2	100.0						
GE 10	83.1	90.0	99.2							
GE 5	91.9	96.1	100.0							
GE 0	97.3	98.8								
GE -5	99.3	99.5								
GE -10	99.9	100.0								
GE -15	100.0									

MEAN	19.9	23.3	32.6	47.0	60.9	70.2	75.8	72.8	63.6	52.7
SD	10.39	10.45	9.90	12.34	12.45	9.81	8.07	8.27	9.71	10.59
TOTAL DBS	911	845	930	916	961	930	961	930	900	930

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MINIMUM TEMPERAT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD
MONTH: ALL HOU

TEMP (DEG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
GE 70							.5	.6		
GE 65					.3	1.3	7.0	3.2	1.7	.1
GE 60					1.5	7.7	23.4	17.6	5.6	.6
GE 55				.1	5.8	18.9	46.5	39.2	15.1	1.9
GE 50				1.3	13.0	41.0	70.1	64.5	30.9	6.5
GE 45				4.3	26.2	63.7	88.2	83.0	51.8	17.0
GE 40			.3	9.9	42.0	82.9	98.0	95.2	71.7	31.1
GE 35		.6	2.9	20.7	61.7	94.3	99.8	99.2	86.7	49.0
GE 33	.2	.9	4.9	28.3	69.1	96.6	99.9	99.8	92.3	59.5
GE 30	1.4	3.7	10.1	44.7	83.0	99.4	100.0	100.0	97.9	77.0
GF 25	5.4	7.8	26.0	70.4	95.0	100.0			99.3	94.0
GE 20	12.7	17.0	42.5	84.4	99.5				100.0	98.6
GE 15	23.1	27.2	56.3	92.9	100.0					99.7
GE 10	36.0	41.3	69.4	97.3					100.0	
GE 5	49.8	54.2	78.0	99.2						
GE 0	63.3	65.4	86.3	99.9						
GF -5	76.2	77.5	94.1	100.0						
GE -10	85.8	88.4	96.9							
GE -15	93.1	95.2	99.4							
GE -20	97.7	98.7	99.7							
GE -25	99.9	99.9	100.0							
GE -30	100.0	100.0								

MEAN	4.3	5.8	15.1	23.3	38.3	47.4	53.7	52.1	45.0	35.7	2.
SD	12.77	13.14	12.44	9.96	9.24	8.04	7.27	7.49	8.86	8.37	9
TOTAL OBS	911	843	930	916	961	930	961	930	900	930	

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: +05

PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
MONTH: ALL HOURS: ALL

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
		.3	1.3	7.0	3.2	1.7	.1			.1
		1.5	7.7	23.4	17.6	5.6	.6			4.8
	.1	5.8	18.9	46.5	39.2	15.1	1.9			10.9
	1.3	13.0	41.0	70.1	54.5	30.9	6.5	.2		19.3
	4.3	26.2	63.7	88.2	83.0	51.8	17.0	.7	.1	28.4
.3	9.9	42.0	82.9	98.0	95.2	71.7	31.1	5.0	.2	37.0
2.9	20.7	61.7	94.3	99.8	99.2	86.7	49.0	11.2	.9	44.6
4.9	28.3	69.1	96.6	99.9	99.8	92.3	59.5	16.2	2.3	48.2
10.1	44.7	83.0	99.4	100.0	100.0	97.9	77.0	30.8	6.9	55.3
26.0	70.4	95.0	100.0			99.3	94.0	56.3	15.5	64.9
42.5	84.4	99.5				100.0	98.6	72.8	28.4	72.0
56.3	92.9	100.0					99.7	84.9	44.6	77.9
69.4	97.3						100.0	92.4	60.3	83.5
78.0	99.2							97.1	71.7	87.8
86.3	99.9							98.9	83.7	91.7
94.1	100.0							99.9	91.9	95.1
96.9								100.0	97.7	97.5
99.4									99.3	98.9
99.7									99.9	99.7
100.0									100.0	100.0
										100.0

15.1	23.3	38.3	47.4	53.7	52.1	45.0	35.7	24.5	12.0	30.5
12.44	9.96	9.24	8.04	7.27	7.49	8.86	8.37	9.49	11.72	19.75
930	916	961	930	961	930	900	930	900	912	11029

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MEAN TEMPERATURE
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD:
LST TO UTC: +05 MONTH: ALL HOUR

TEMP (DEG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV
85							.2				
80						.3	1.9	.3			
75					.6	2.8	8.4	4.6	1.6		
70				.1	2.9	10.3	25.5	17.8	4.7	.3	
65				.2	9.7	25.7	52.9	41.0	12.6	1.3	
60				2.6	18.1	47.2	76.9	65.8	28.6	4.7	
55				6.2	31.0	69.1	94.9	86.8	48.3	13.3	
50			.4	11.4	47.6	87.0	99.5	98.1	69.0	27.4	1
45		.1	1.7	22.6	66.2	97.4	100.0	99.9	88.6	46.5	7
40		.5	5.6	40.3	84.5	99.9		100.0	98.1	69.5	16
35	.3	3.1	14.5	51.8	95.8	100.0			99.8	88.9	34
33	2.1	5.1	21.4	70.6	97.8				99.8	93.5	45
30	6.5	9.4	32.6	81.0	99.9				100.0	97.3	59
25	15.5	20.9	51.7	92.9	100.0					99.7	78
20	27.7	36.1	67.3	97.7						100.0	89
15	43.2	51.3	80.6	99.6							96
10	59.3	65.0	91.5	100.0							98
5	74.3	81.6	96.3								99
0	84.4	92.8	98.7								100
-5	93.5	96.6	99.9								
-10	98.7	99.2	100.0								
-15	99.6	100.0									
-20	99.9										
-25	100.0										

MEAN	12.2	14.7	24.1	37.9	49.8	59.0	64.9	62.7	54.6	44.5	31
SD	11.20	11.12	10.22	9.66	9.86	8.01	6.86	6.97	9.43	8.55	8.
TOTAL OBS	911	843	930	916	961	930	961	930	900	930	9

ACCUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION: K. I. SAWYER AFB MI
ALTI: +05

PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
MONTH: ALL HOURS: ALL

	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
			.3	.2						.0
		.6	1.9	.3						.2
		2.8	8.4	4.6	1.6					1.5
.1	2.9	10.3	25.5	17.8	4.7		.3			5.3
.2	8.7	25.7	52.9	41.0	12.6	1.3				12.1
2.6	18.1	47.2	76.9	65.8	28.6	4.7				20.8
5.2	31.0	69.1	94.9	86.8	48.3	13.3		.2		29.7
11.4	47.6	87.0	99.5	98.1	69.0	27.4	1.4	.2		37.5
22.6	66.2	97.4	100.0	99.9	88.8	46.5	7.3	.4		44.9
40.3	84.5	99.9		100.0	98.1	69.5	16.1	1.1		52.1
51.8	95.8	100.0			99.8	88.9	34.7	3.3		59.3
70.5	97.8				99.8	93.5	45.1	7.5		62.7
81.0	99.9				100.0	97.3	59.1	13.4		67.3
92.9	100.0					99.7	78.6	30.5		74.7
97.7						100.0	89.7	49.3		81.1
99.6							96.1	67.1		86.9
100.0							98.9	81.7		91.8
							99.7	92.0		95.5
							100.0	96.9		97.7
								99.3		99.1
								100.0		99.8
										100.0
										100.0
										100.0

37.9	49.8	59.0	64.9	62.7	54.6	44.5	31.1	18.8	39.9
9.65	9.86	3.01	6.86	5.97	4.43	8.55	8.93	9.78	20.45
916	961	930	961	930	900	930	900	912	11029

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: +05

PERIOD OF
 MONTH: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
57	36*	41	52	79	80	90	83	93	81
58				77*	81	37	86	94	81
59									
60	38	38	50	73	77	84	88	84	87
61	44	52	51	66	83	90	86	93	87
62	35	38	53	72	90	89	86	86	80
63	35	32	62	70	81	102	99	86	79
64	40	47	49	73	92	91	92	87	90
65	39	38	42	78	85	90	85	93	74
66	33	39	55	62	83	92	95	87	86
67	44	33	63	70	76	84	86	84	82
68	39	41	61	83	77	83	90	90	81
69	40	33	51	65	94	80	87	93	82
70	34	42	49	76	85	94	91	86	80
71	31	46	42	63	78	91	82	87	87
72	37	35	43	60	91	84	80	84	69
73	47	39	58	73	74	83	93	95	86
74	37	40	50	71	80	82	93	81	76
75	43	42	45	63	85	87	96	89	73
76	31	55	59	76	73	87	85	95	94
77	24	37	53	79	84	88	89	85	72
78	22	29	45	67	86	84	83	80	80
79	24	38	45	70	76	88	87	81	84
80	42	35	49	81	88	92	91	87	81
81	42	54	60	70	80	79	91	81	78
82	28	37	49	77	81	83	88	84	85
83	34	42	45	69	70	80	95	92	91
84	34	53	42	63	79	83	83	87	78
85	33	47	51	73	83	79	83	83	83
86	42	31	50	78	91	80	95	87	78
87	42	43	48	84	85	81	94	86	84
88	32	45	50	67	81	97	101		

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

W. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
+05 MONTH: ALL HOURS: ALL

APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
79	80	90	88	93	81	68	55	34*	93*
77*	81	87	86	94	81	71			94*
							45	48	48*
73	77	84	88	84	87	81	54	48	88
66	83	90	86	93	87	79	64	54	93
72	90	89	86	88	80	78	53	57	90
70	81	102	99	86	79	80	55	39	102
73	92	91	92	87	90	75	63	37	92
78	85	90	85	93	74	79	66	41	93
62	83	92	95	87	86	79	47	40	95
70	76	84	86	84	82	78	57	47	86
83	77	88	90	90	81	80	58	41	90
65	94	80	87	93	82	67	58	40	94
76	85	94	91	86	80	72	55	44	94
63	78	91	82	87	87	78	54	36	91
60	91	84	80	84	69	67	46	34	91
73	74	83	93	95	86	75	51	41	95
71	80	82	93	81	76	68	60	40	93
63	85	87	96	89	73	68	69	40	96
76	73	87	85	95	94	80	52	36	95
79	84	88	99	85	72	66	55	38	99
67	86	84	83	89	80	76	68	32	89
70	76	88	87	81	84	65	55	44	88
81	88	92	91	67	81	67	52	38	92
70	80	79	91	81	78	63	66	36	91
77	81	83	88	84	85	72	56	57	88
69	70	88	95	92	91	76	55	32	95
63	79	83	83	87	78	64	50	46	87
73	83	79	83	83	83	69	50	29	83
78	91	80	95	87	78	72	54	43	95
84	85	81	94	86	84	69	60	39	94
67	91	97	101						101*

7A

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD
MONTH: ALL

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT
.....

.....
GREATEST 47 55 68 84 94 102 101 95 94 81

.....
TOTAL OBS 711 849 930 916 961 930 961 930 900 930
.....

THE GREATEST VALUE OF 102 OCCURRED ON 06/30/63

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

NAME: K. I. SAWYER AFB MI
UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL

84 94 102 101 95 94 81 69 57 102

915 961 930 961 930 900 930 900 912 11029

102 OCCURRED ON 06/30/63

BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD:
MONTH: ALL HOURS

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
57	-24*	-13	-12	5	22	31	40	40	23	25
58				10*	17	29	40	36	30	27
59										
60	-7	-8	-12	3	20	36	39	37	33	23
61	-18	-15	1	14	25	34	43	42	23	23
62	-21	-20	-21	9	26	29	40	38	33	24
63	-27	-20	-15	18	23	34	43	33	28	29
64	-12	-13	-3	-3	26	25	43	36	26	21
65	-25	-20	-12	6	27	30	36	36	21	18
66	-25	-25	-4	15	21	34	43	42	33	12
67	-21	-23	-13	13	21	37	34	33	30	23
68	-22	-14	-3	9	19	34	35	33	35	19
69	-10	-14	-2	17	22	31	41	40	36	12
70	-19	-25	-5	13	21	31	42	37	31	22
71	-19	-23	-12	7	23	31	40	30	32	28
72	-24	-21	-22	2	25	27	32	33	27	14
73	-17	-14	13	7	24	36	39	38	28	29
74	-21	-20	-15	5	19	36	42	38	23	18
75	-11	-16	-7	4	29	34	40	43	24	21
76	-18	-8	-10	14	18	34	42	32	28	19
77	-20	-13	5	6	23	33	41	36	37	22
78	-14	-15	-14	17	24	31	38	38	31	22
79	-17	-30	-5	6	22	33	40	37	31	21
80	-18	-16	-16	13	31	32	43	45	29	23
81	-8	-21	5	19	22	39	41	40	30	19
82	-24	-14	-13	6	30	32	47	38	31	25
83	-4	-5	-3	16	16	35	39	48	33	26
84	-18	1	-14	17	24	41	40	36	30	18
85	-12	-22	-4	14	28	34	38	42	31	24
86	-9	-12	-5	17	21	25	40	37	32	27
87	-8	4	5	10	26	35	42	44	34	20
88	-18	-15	-14	16	24	32	37			

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
TO UTC: +05 MONTH: ALL HOURS: ALL

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
-12	5 10*	22 17	31 29	40 40	40 36	23 30	25 27	0	0*	-24* 10*
-12	3	20	36	39	37	33	23	12	-14	-6* -14
1	14	25	34	43	42	23	23	5	-8	-18
-21	9	26	29	40	38	33	24	17	-13	-21
-15	18	23	34	43	33	28	29	12	-11	-27
-3	-3	26	25	43	36	26	21	3	-10	-13
-12	6	27	30	36	36	21	18	13	-3	-25
-4	15	21	34	43	42	33	12	4	-9	-25
-13	13	21	37	34	33	30	23	2	-14	-23
-3	9	19	34	35	33	35	19	15	-17	-22
-2	17	22	31	41	40	36	12	5	-4	-14
-5	13	21	31	42	37	31	22	7	-9	-25
-12	7	23	31	40	30	32	28	6	-4	-23
-22	2	25	27	32	33	27	14	2	-17	-24
13	7	24	36	39	38	28	29	9	-17	-17
-15	5	19	36	42	38	23	18	9	3	-21
-7	4	29	34	40	43	24	21	4	-11	-16
-10	14	18	34	42	32	28	19	-5	-23	-23
5	6	23	33	41	36	37	22	2	-13	-20
-14	17	24	31	38	38	31	22	-3	-8	-15
-5	5	22	33	40	37	31	21	-2	-6	-30
-15	13	31	32	43	45	29	23	12	-7	-18
5	19	22	39	41	40	30	19	4	-4	-21
-13	6	30	32	47	38	31	25	1	-3	-24
-3	16	18	35	39	48	33	26	16	-20	-20
-14	17	24	41	40	36	30	18	0	-6	-18
-4	14	28	34	38	42	31	24	-1	-9	-22
-5	17	21	25	40	37	32	27	3	0	-12
5	10	26	35	42	44	34	20	9	-6	-8
-14	16	24	32	37						-18*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD
MONTH: ALL HOI

YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT

.....
LEAST -27 -30 -22 -3 17 25 32 30 21 12
.....
TOTAL OBS 911 848 930 916 961 930 961 930 900 930
.....

THE LEAST VALUE OF -30 OCCURRED ON 02/17/79

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

.....
MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL
.....

.....
-32 -3 17 25 32 30 21 12 -6 -23 -30
.....

.....
130 916 961 930 961 930 900 930 900 912 11029
.....

-30 OCCURRED ON 02/17/79

BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
 USAFETAC, ASHEVILLE NC

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
 FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: +05

PERIOD OF RECORD:
 MONTH: ALL HOUR

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
57	9*	15	23	39	49	60	66	62	53	44
58				41*	46	54	63	62	55	46
59										
60	18	19	17	39	50	59	63	64	56	46
61	11	21	23	38	49	61	67	66	58	46
62	10	11	27	37	55	58	62	63	52	48
63	5	6	24	40	48	63	57	60	55	54
64	20	17	21	38	54	53	66	60	53	44
65	10	10	18	36	52	57	59	60	50	43
66	8	16	27	35	46	63	69	63	55	44
67	16	7	24	38	44	60	63	60	56	42
68	14	12	28	40	47	58	63	62	59	48
69	17	17	20	39	49	53	65	66	57	41
70	7	11	21	39	46	60	66	63	55	46
71	7	13	19	35	45	62	60	60	57	51
72	9	10	19	31	54	56	61	60	50	39
73	16	15	32	36	44	59	63	65	54	49
74	12	10	22	38	46	57	66	62	49	42
75	15	18	22	32	55	61	67	65	50	45
76	10	21	24	40	46	62	64	64	53	39
77	5	15	30	41	56	53	65	59	55	43
78	12	11	22	34	52	58	62	63	56	43
79	7	7	23	36	46	59	66	60	55	40
80	14	13	22	39	54	59	66	65	54	40
81	16	20	29	39	47	60	55	64	53	42
82	4	12	23	35	57	56	67	61	55	46
83	20	23	27	34	45	61	70	68	58	45
84	9	25	19	41	48	62	63	65	53	48
85	13	13	26	41	51	56	61	61	55	45
86	15	16	27	42	53	56	67	61	55	45
87	22	27	33	46	56	65	69	64	59	39
88	11	11	24	39	54	63	69			

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712, 5804-5810, 5911-8807
MONTH: ALL HOURS: ALL

IV	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
	23	39	49	60	66	62	53	44	30	16*	42*
		41*	46	54	63	62	55	46			53*
	17	39	50	59	63	64	56	46	23	26	25*
									34	15	40
	23	38	49	61	67	66	58	46	32	18	41
	27	37	55	58	62	63	52	48	34	19	40
	24	40	48	63	67	60	55	54	35	13	39
	21	38	54	58	66	60	53	44	33	16	40
	18	36	52	57	59	60	50	43	31	24	38
	27	35	46	63	69	63	55	44	30	20	40
	24	38	44	60	63	60	56	42	27	20	39
	24	40	47	58	63	62	59	48	31	19	40
	20	39	49	53	65	68	57	41	30	20	40
	21	39	46	60	66	63	55	46	31	18	39
	19	35	45	62	60	60	57	51	31	20	38
	19	31	54	56	61	60	50	39	28	14	36
	32	36	44	59	63	65	54	49	31	18	40
	22	33	46	57	66	62	49	42	32	23	38
	22	32	55	61	67	65	50	45	34	17	40
	24	40	46	62	64	64	53	39	27	11	38
	30	41	58	58	65	59	55	43	31	18	40
	22	34	52	58	62	63	56	43	30	14	38
	23	35	46	59	66	60	55	40	29	24	38
	22	39	54	59	66	65	54	40	32	19	40
	29	39	47	60	65	64	53	42	36	21	41
	23	35	57	56	67	61	55	46	31	24	39
	27	34	45	61	70	68	58	45	34	12	41
	19	41	48	62	63	65	53	48	33	21	41
	25	41	51	56	61	61	55	45	28	12	39
	27	42	53	56	67	61	55	45	29	25	41
	33	45	56	66	69	64	59	39	33	24	45
	24	39	54	63	69						39*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +05

PERIOD OF RECORD:
MONTH: ALL HOURS

.....
YEAR JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV

.....
MEAN 12.2 14.7 24.1 37.9 49.8 59.0 64.9 62.7 54.6 44.5 31.1
.....
TOTAL OBS 311 348 330 316 361 330 361 330 300 330 301
.....

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: +05

PERIOD OF RECORD: 5701-5712,5804-5810,5911-8807
MONTH: ALL HOURS: ALL

.....
 MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ANNUAL

.....
 24.1 37.9 49.8 59.0 64.9 62.7 54.6 44.5 31.1 18.8 39.9

.....
 730 916 961 730 961 930 900 930 900 912 11029

IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 7
 LST TO UTC: + 5 MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 0	LE 32	GE 65	GE 30	GE
00-02	12.0	12.177	930	176	899	0	0	
03-05	11.4	12.301	930	194	913	0	0	
06-08	10.9	12.747	930	215	912	0	0	
09-11	12.2	12.216	930	171	904	0	0	
12-14	17.0	10.391	930	57	860	0	0	
15-17	17.8	10.304	930	44	851	0	0	
18-20	14.9	11.125	930	110	884	0	0	
21-23	12.7	11.738	930	163	897	0	0	
ALL HOURS	13.6	11.494	7440	1130	7120	0	0	

MONTH: FEB

00-02	14.3	13.417	849	169	785	0	0	
03-05	13.3	13.714	849	120	793	0	0	
06-08	12.6	13.996	849	127	800	0	0	
09-11	15.6	13.127	849	108	767	0	0	
12-14	21.1	11.805	849	30	672	0	0	
15-17	22.3	11.703	849	16	653	0	0	
18-20	19.3	12.220	849	60	706	0	0	
21-23	16.3	13.033	849	112	757	0	0	
ALL HOURS	16.8	13.366	6792	862	5933	0	0	

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
LST TO UTC: + 5 MONTH: JAN

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
930	176	899	0	0	0	930
930	194	913	0	0	0	930
930	215	912	0	0	0	930
930	171	904	0	0	0	930
930	57	860	0	0	0	930
930	44	851	0	0	0	930
930	110	884	0	0	0	930
930	163	897	0	0	0	930
7440	1130	7120	0	0	0	7440

MONTH: FEB

849	169	785	0	0	0	849
849	180	793	0	0	0	849
849	187	800	0	0	0	849
849	108	767	0	0	0	849
849	30	672	0	0	0	849
849	16	653	0	0	0	849
849	60	706	0	0	0	849
849	112	757	0	0	0	849
6792	862	5933	0	0	0	6792

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 0	LE 32	GE 65	GE 80	GE
00-02	22.9	10.868	930	46	778	0	0	
03-05	21.7	11.384	930	58	818	0	0	
06-08	20.9	11.554	930	73	815	0	0	
09-11	25.5	10.177	930	13	713	0	0	
12-14	29.8	10.268	930	1	573	1	0	
15-17	30.9	10.515	930	0	534	1	0	
18-20	28.3	9.969	930	1	631	0	0	
21-23	24.9	10.169	930	25	744	0	0	
ALL HOURS	25.6	11.152	7440	217	5606	2	0	

MONTH: APR

00-02	34.4	8.911	900	0	392	0	0	
03-05	33.0	8.825	900	0	431	0	0	
06-08	33.6	9.828	900	0	399	0	0	
09-11	40.6	10.382	900	0	205	21	0	
12-14	44.8	12.277	900	0	134	73	2	
15-17	45.4	12.543	900	0	117	82	2	
18-20	42.1	11.381	900	0	179	38	0	
21-23	37.0	9.505	900	0	318	1	0	
ALL HOURS	38.9	11.465	7200	0	2174	215	4	

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: MAR

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
930	46	778	0	0	0	930
930	58	818	0	0	0	930
930	73	815	0	0	0	930
930	13	713	0	0	0	930
930	1	573	1	0	0	930
930	0	534	1	0	0	930
930	1	631	0	0	0	930
930	25	744	0	0	0	930
7440	217	5606	2	0	0	7440

MONTH: APR

900	0	392	0	0	0	900
900	0	431	0	0	0	900
900	0	399	0	0	0	900
900	0	205	21	0	0	900
900	0	134	73	2	0	900
900	0	117	82	2	0	900
900	0	178	38	0	0	900
900	0	318	1	0	0	900
7200	0	2174	215	4	0	7200

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 0	LE 32	GE 65	GE 80	GE
00-02	44.2	9.576	930	0	107	18	0	
03-05	42.5	9.524	930	0	159	11	0	
06-08	45.4	9.500	930	0	82	21	0	
09-11	54.5	10.936	930	0	7	176	11	
12-14	58.9	12.492	930	0	3	326	53	
15-17	59.0	12.455	930	0	4	346	54	
18-20	55.1	11.426	930	0	5	203	20	
21-23	48.3	9.998	930	0	47	64	0	
ALL HOURS	51.0	12.471	7440	0	414	1165	138	

MONTH: JUN

00-02	53.2	8.667	900	0	5	104	0	
03-05	51.3	8.715	900	0	8	59	0	
06-08	54.7	8.286	900	0	1	109	0	
09-11	63.3	9.024	900	0	0	379	44	
12-14	67.3	9.685	900	0	0	550	100	
15-17	67.3	9.710	900	0	0	536	99	
18-20	64.0	9.190	900	0	0	413	46	
21-23	57.3	8.470	900	0	0	176	5	
ALL HOURS	59.8	10.329	7200	0	14	2326	294	

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECDRD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: MAY

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
930	0	107	18	0	0	930
930	0	159	11	0	0	930
930	0	82	21	0	0	930
930	0	7	176	11	0	930
930	0	3	326	53	0	930
930	0	4	346	54	0	930
930	0	5	203	20	0	930
930	0	47	64	0	0	930
7440	0	414	1165	138	0	7440

MONTH: JUN

900	0	5	104	0	0	900
900	0	8	59	0	0	900
900	0	1	109	0	0	900
900	0	0	379	44	0	900
900	0	0	550	100	3	900
900	0	0	536	99	6	900
900	0	0	413	46	2	900
900	0	0	176	5	0	900
7200	0	14	2326	294	11	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 0	LE 32	GE 65	GE 80	GE 90
00-02	59.6	7.599	930	0	0	253	2	
03-05	57.5	7.603	930	0	0	182	0	
06-08	60.4	7.090	930	0	0	264	2	
09-11	69.7	7.437	930	0	0	684	87	
12-14	74.3	8.446	930	0	0	811	248	1
15-17	74.4	8.541	930	0	0	810	260	2
18-20	70.9	8.170	928	0	0	727	142	1
21-23	64.2	7.424	927	0	0	440	21	
ALL HOURS	66.4	10.068	7435	0	0	4171	762	4

MONTH: AUG

00-02	58.1	7.054	930	0	0	182	0	
03-05	56.6	7.175	930	0	0	131	1	
06-08	57.5	6.748	930	0	0	135	0	
09-11	65.4	6.462	930	0	0	497	16	
12-14	70.0	7.483	930	0	0	714	95	
15-17	70.5	7.694	930	0	0	726	120	
18-20	66.9	7.222	930	0	0	575	40	
21-23	61.0	6.587	930	0	0	297	2	
ALL HOURS	63.2	8.851	7440	0	0	3257	274	

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
ST TO UTC: + 5 MONTH: JUL

TOTAL DBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
930	0	0	253	2	0	930
930	0	0	182	0	0	930
930	0	0	264	2	0	930
930	0	0	684	87	1	930
930	0	0	811	248	16	930
930	0	0	810	260	21	930
928	0	0	727	142	10	928
927	0	0	440	21	0	927
7435	0	0	4171	762	48	7435

MONTH: AUG

930	0	0	182	0	0	930
930	0	0	131	1	0	930
930	0	0	135	0	0	930
930	0	0	497	16	0	930
930	0	0	714	95	0	930
930	0	0	726	120	0	930
930	0	0	575	40	0	930
930	0	0	297	2	0	930
7440	0	0	3257	274	0	7440

OPERATING LOCATION #A#
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES D				
				LE 0	LE 32	GE 65	GE 80	GE 9
00-02	51.2	8.748	900	0	8	59	0	
03-05	50.0	8.833	900	0	19	40	0	
06-08	49.9	8.467	900	0	21	36	0	
09-11	56.5	7.950	900	0	0	157	3	
12-14	61.1	9.349	900	0	0	298	25	
15-17	61.3	9.611	900	0	0	315	36	
18-20	57.2	8.851	900	0	0	192	9	
21-23	52.7	8.482	900	0	0	86	0	
ALL HOURS	55.0	9.789	7200	0	48	1183	73	

MONTH: OCT

00-02	40.1	8.201	930	0	176	0	0	
03-05	39.2	8.178	930	0	207	0	0	
06-08	38.8	8.064	930	0	218	0	0	
09-11	43.7	7.449	930	0	57	1	0	
12-14	48.2	8.476	930	0	15	24	0	
15-17	48.6	8.845	930	0	19	41	0	
18-20	44.4	8.036	930	0	48	5	0	
21-23	41.3	8.030	930	0	129	0	0	
ALL HOURS	43.0	8.959	7440	0	868	71	0	

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP

TOTAL HOURS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
900	0	8	59	0	0	900
900	0	19	40	0	0	900
900	0	21	36	0	0	900
900	0	0	157	3	0	900
900	0	0	298	25	0	900
900	0	0	315	36	0	900
900	0	0	192	9	0	900
900	0	0	86	0	0	900
7200	0	48	1183	73	0	7200

MONTH: OCT

930	0	176	0	0	0	930
930	0	207	0	0	0	930
930	0	218	0	0	0	930
930	0	57	1	0	0	930
930	0	15	24	0	0	930
930	0	19	41	0	0	930
930	0	48	5	0	0	930
930	0	129	0	0	0	930
7440	0	868	71	0	0	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG				
				LE 0	LE 32	GE 65	GE 80	GE 93
00-02	30.1	9.263	900	0	537	0	0	0
03-05	29.5	9.597	900	1	560	0	0	0
06-08	28.9	9.856	900	9	583	0	0	0
09-11	31.3	9.423	900	0	515	0	0	0
12-14	35.2	9.412	900	0	361	5	0	0
15-17	35.5	9.563	900	0	350	7	0	0
18-20	32.4	8.810	900	0	459	0	0	0
21-23	30.5	8.947	900	3	523	0	0	0
ALL HOURS	31.7	9.601	7200	13	3888	12	0	0

MONTH: DEC

00-02	18.8	10.906	930	64	851	0	0	0
03-05	18.1	11.314	930	30	863	0	0	0
06-08	17.5	11.677	930	87	860	0	0	0
09-11	18.7	11.080	930	59	858	0	0	0
12-14	22.6	9.298	930	11	803	0	0	0
15-17	23.2	9.191	930	7	776	0	0	0
18-20	20.5	9.977	930	27	838	0	0	0
21-23	19.2	10.448	930	49	849	0	0	0
ALL HOURS	19.8	10.712	7440	383	6698	0	0	0

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
LT TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
900	0	537	0	0	0	900
900	1	560	0	0	0	900
900	9	583	0	0	0	900
900	0	515	0	0	0	900
900	0	361	5	0	0	900
900	0	350	7	0	0	900
900	0	459	0	0	0	900
900	3	523	0	0	0	900
7200	13	3888	12	0	0	7200

MONTH: DEC

930	64	851	0	0	0	930
930	30	863	0	0	0	930
930	87	860	0	0	0	930
930	59	858	0	0	0	930
930	11	803	0	0	0	930
930	7	776	0	0	0	930
930	27	838	0	0	0	930
930	48	849	0	0	0	930
7440	383	6698	0	0	0	7440

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 79
MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 0	LE 32	GE 65	GE 80	GE 90
00-02	36.7	19.034	10959	455	4538	616	2	
03-05	35.4	18.803	10959	513	4771	423	1	
06-08	36.0	19.768	10959	571	4691	565	2	
09-11	41.5	22.003	10959	351	4026	1915	161	
12-14	46.0	22.042	10959	99	3421	2402	523	1
15-17	46.5	21.846	10959	57	3304	2864	571	2
18-20	43.1	21.383	10957	198	3749	2153	257	1
21-23	38.9	19.783	10956	351	4263	1064	28	
ALL HOURS	40.5	21.030	37667	2605	32743	12402	1545	5

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: ALL

TOTAL HOURS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 0	LE 32	GE 65	GE 80	GE 93	
10959	455	4538	616	2	0	10959
10959	513	4771	423	1	0	10959
10959	571	4691	565	2	0	10959
10959	351	4026	1915	161	1	10959
10959	99	3421	2802	523	19	10959
10959	67	3304	2864	571	27	10959
10957	198	3749	2153	257	12	10957
10956	351	4263	1064	28	0	10956
87667	2605	32763	12402	1545	59	87667

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES				
				LE 32	GE 50	GE 67	GE 73	GE
00-02	11.0	11.803	930	920	0	0	0	
03-05	10.5	11.926	929	924	0	0	0	
06-08	10.0	12.352	930	919	0	0	0	
09-11	11.2	11.853	929	918	0	0	0	
12-14	15.3	9.956	930	897	0	0	0	
15-17	15.9	9.799	930	883	0	0	0	
18-20	13.5	10.708	930	909	0	0	0	
21-23	11.5	11.435	930	913	0	0	0	
ALL HOURS	12.4	11.443	7438	7293	0	0	0	

MONTH: FEB

00-02	13.3	12.987	849	813	0	0	0	
03-05	12.3	13.336	849	812	0	0	0	
06-08	11.7	13.591	849	817	0	0	0	
09-11	14.3	12.640	848	798	0	0	0	
12-14	18.8	10.960	849	743	0	0	0	
15-17	13.7	10.715	849	732	0	0	0	
18-20	17.4	11.486	849	772	0	0	0	
21-23	15.0	12.578	849	803	0	0	0	
ALL HOURS	15.3	12.631	6791	6290	0	0	0	

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN

TOTAL DEG F	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
930	920	0	0	0	0	930
929	924	0	0	0	0	929
930	919	0	0	0	0	930
929	918	0	0	0	0	929
930	897	0	0	0	0	930
930	883	0	0	0	0	930
930	909	0	0	0	0	930
930	913	0	0	0	0	930
7438	7293	0	0	0	0	7438

MONTH: FEB

849	813	0	0	0	0	849
849	812	0	0	0	0	849
849	817	0	0	0	0	849
848	798	0	0	0	0	848
849	743	0	0	0	0	849
849	732	0	0	0	0	849
849	772	0	0	0	0	849
849	803	0	0	0	0	849
6791	6290	0	0	0	0	6791

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN	NUMBER OF HOURS WITH TEMPERATURES DEG	LE 32	GE 50	GE 67	GE 73	GE 80
00-02	21.4	10.475	930	832	0	0	0	0	0	
03-05	20.3	11.035	930	848	0	0	0	0	0	
06-08	19.7	11.238	930	846	0	0	0	0	0	
09-11	23.5	9.614	930	732	0	0	0	0	0	
12-14	26.5	8.985	930	703	5	0	0	0	0	
15-17	27.2	8.915	930	683	6	0	0	0	0	
18-20	25.5	8.976	930	749	3	0	0	0	0	
21-23	23.1	9.719	930	802	1	0	0	0	0	
ALL HOURS	23.4	10.269	7440	6245	15	0	0	0	0	

MONTH: APR

00-02	31.8	8.319	900	512	29	0	0	0	0
03-05	30.8	8.410	900	549	19	0	0	0	0
06-08	31.3	8.263	900	532	20	0	0	0	0
09-11	35.9	8.469	900	324	68	0	0	0	0
12-14	38.2	9.133	900	259	110	2	0	0	0
15-17	38.4	9.271	900	245	112	1	0	0	0
18-20	36.4	9.057	900	332	83	0	0	0	0
21-23	33.5	8.610	900	441	45	0	0	0	0
ALL HOURS	34.5	9.170	7200	3194	486	3	0	0	0

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAR

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
930	832	0	0	0	0	930
930	848	0	0	0	0	930
930	846	0	0	0	0	930
930	732	0	0	0	0	930
930	703	5	0	0	0	930
930	683	6	0	0	0	930
930	749	3	0	0	0	930
930	802	1	0	0	0	930
7440	6245	15	0	0	0	7440

MONTH: APR

900	512	29	0	0	0	900
900	549	19	0	0	0	900
900	532	20	0	0	0	900
900	324	68	0	0	0	900
900	259	110	2	0	0	900
900	245	112	1	0	0	900
900	332	83	0	0	0	900
900	441	45	0	0	0	900
7200	3194	486	3	0	0	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78 -
MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DE				
				LE 32	GE 50	GE 67	GE 73	GE 80
00-02	40.7	9.182	930	197	177	0	0	0
03-05	39.6	9.194	930	232	157	0	0	0
06-08	41.8	8.794	930	133	195	1	0	0
09-11	47.1	8.790	930	34	355	16	0	0
12-14	49.1	9.200	930	21	438	30	2	0
15-17	49.1	9.393	930	20	420	26	5	0
18-20	46.9	9.284	930	39	354	15	0	0
21-23	43.3	9.190	930	116	246	2	0	0
ALL HOURS	44.7	9.791	7440	792	2342	90	7	0

MONTH: JUN

00-02	49.5	8.299	900	8	448	17	0	0
03-05	48.2	8.403	900	25	393	7	0	0
06-08	50.5	7.566	900	4	472	8	0	0
09-11	55.1	7.300	900	0	696	78	3	0
12-14	56.8	7.392	900	0	756	97	12	0
15-17	56.7	7.361	900	0	739	98	19	0
18-20	55.1	7.539	900	0	665	79	11	0
21-23	51.9	7.762	900	1	535	35	0	0
ALL HOURS	53.0	8.354	7200	38	4704	419	45	0

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: MAY

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
930	197	177	0	0	0	930
930	232	157	0	0	0	930
930	133	195	1	0	0	930
930	34	355	16	0	0	930
930	21	438	30	2	0	930
930	20	420	26	5	0	930
930	39	354	15	0	0	930
930	116	246	2	0	0	930
7440	792	2342	90	7	0	7440

MONTH: JUN

900	8	448	17	0	0	900
900	25	393	7	0	0	900
900	4	472	8	0	0	900
900	0	696	78	3	0	900
900	0	756	97	12	0	900
900	0	739	98	19	0	900
900	0	665	79	11	0	900
900	1	535	35	0	0	900
7200	38	4704	419	45	0	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES			
				LE 32	GE 50	GF 67	GE 73
00-02	56.2	7.160	930	0	752	61	3
03-05	54.7	7.447	930	0	702	35	2
06-08	56.8	6.667	930	0	793	59	3
09-11	61.7	5.955	930	0	910	184	29
12-14	63.4	6.005	930	0	920	289	51
15-17	63.4	6.025	930	0	919	287	56
18-20	62.0	6.334	928	0	901	237	40
21-23	59.0	6.665	927	0	846	129	13
ALL HOURS	59.6	7.318	7435	0	6743	1281	197

MONTH: AUG

00-02	55.5	7.222	930	0	735	48	0
03-05	54.4	7.402	930	0	669	29	0
06-08	55.1	7.013	930	0	724	31	0
09-11	59.7	5.956	930	0	883	115	14
12-14	61.4	6.161	930	0	896	181	25
15-17	61.6	6.189	930	0	898	218	30
18-20	60.1	6.255	929	0	879	153	16
21-23	57.4	6.660	930	0	811	75	3
ALL HOURS	58.2	7.178	7439	0	6495	850	88

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL

DATE	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
930	0	752	61	3	0	930
930	0	702	35	2	0	930
930	0	793	59	3	0	930
930	0	910	184	29	0	930
930	0	920	289	51	2	930
930	0	919	287	56	1	930
928	0	901	237	40	0	928
927	0	846	129	13	0	927
935	0	6743	1281	197	3	7435

MONTH: AUG

930	0	735	48	0	0	930
930	0	669	29	0	0	930
930	0	724	31	0	0	930
930	0	883	115	14	0	930
930	0	896	181	25	0	930
930	0	898	218	30	0	930
929	0	879	153	16	0	929
930	0	811	75	3	0	930
929	0	6495	850	88	0	7439

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES D				
				LE 32	GE 50	GE 67	GE 73	GE 8
00-02	48.8	8.551	900	27	422	12	0	
03-05	48.0	8.695	900	38	396	7	0	
06-08	48.0	8.430	900	37	373	8	0	
09-11	52.3	7.354	900	0	559	33	0	
12-14	54.5	7.916	900	0	633	72	13	
15-17	54.7	7.963	900	0	647	77	17	
18-20	52.5	7.971	900	0	559	44	7	
21-23	49.9	8.212	900	7	448	20	0	
ALL HOURS	51.1	8.534	7200	109	4037	273	37	

MONTH: OCT

00-02	38.0	8.148	930	268	96	0	0	
03-05	37.3	8.118	929	303	82	0	0	
06-08	36.9	8.070	930	303	81	0	0	
09-11	40.5	7.232	930	128	113	0	0	
12-14	42.8	7.542	930	69	179	0	0	
15-17	42.8	7.574	930	69	185	0	0	
18-20	40.6	7.617	930	127	129	0	0	
21-23	38.8	7.954	930	206	99	0	0	
ALL HOURS	39.7	8.108	7439	1473	964	0	0	

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
UTC: + 5 MONTH: SEP

TEMPERATURES	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
00	27	422	12	0	0	900
10	38	396	7	0	0	900
20	37	373	8	0	0	900
30	0	559	33	0	0	900
40	0	633	72	13	0	900
50	0	647	77	17	0	900
60	0	559	44	7	0	900
70	7	448	20	0	0	900
80	109	4037	273	37	0	7200

MONTH: OCT

50	268	96	0	0	0	930
22	303	82	0	0	0	929
53	303	81	0	0	0	930
45	128	113	0	0	0	930
60	69	179	0	0	0	930
30	69	185	0	0	0	930
30	127	129	0	0	0	930
30	206	99	0	0	0	930
19	1473	964	0	0	0	7439

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
 MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES D				
				LE 32	GE 50	GE 67	GE 73	GE 80
00-02	28.1	8.941	900	637	15	0	0	
03-05	27.6	9.285	900	654	15	0	0	
06-08	27.1	9.585	900	665	15	0	0	
09-11	29.0	8.930	900	625	14	0	0	
12-14	31.7	8.432	900	528	23	0	0	
15-17	31.8	8.446	900	524	21	0	0	
18-20	29.8	8.392	900	544	16	0	0	
21-23	28.4	8.684	900	617	14	0	0	
ALL HOURS	29.2	9.020	7200	4834	133	0	0	

MONTH: DEC

00-02	17.7	10.826	930	873	3	0	0	
03-05	17.0	11.130	930	886	3	0	0	
06-08	16.5	11.520	928	884	4	0	0	
09-11	17.6	10.949	930	885	3	0	0	
12-14	20.9	9.189	923	848	4	0	0	
15-17	21.2	9.085	930	844	4	0	0	
18-20	19.1	9.853	930	871	3	0	0	
21-23	18.0	10.318	930	878	3	0	0	
ALL HOURS	18.5	10.507	7436	6969	27	0	0	

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
LST TO UTC: + 5 MONTH: NOV

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
900	637	15	0	0	0	900
900	654	15	0	0	0	900
900	665	15	0	0	0	900
900	625	14	0	0	0	900
900	528	23	0	0	0	900
900	524	21	0	0	0	900
900	584	16	0	0	0	900
900	617	14	0	0	0	900
7200	4834	133	0	0	0	7200

MONTH: DEC

930	873	3	0	0	0	930
930	886	3	0	0	0	930
928	884	4	0	0	0	928
930	885	3	0	0	0	930
928	848	4	0	0	0	928
930	844	4	0	0	0	930
930	871	3	0	0	0	930
930	878	3	0	0	0	930
7436	6969	27	0	0	0	7436

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 1
 MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN	NUMBER OF HOURS WITH TEMPERATURES	LE 32	GE 50	GE 67	GE 73	GE
00-02	34.4	18.191	10959		5087	2677	138	3		
03-05	33.5	18.152	10957		5271	2436	78	2		
06-08	33.9	18.844	10957		5140	2677	107	3		
09-11	37.4	19.516	10957		4494	3601	426	46		
12-14	40.1	18.591	10957		4053	3954	671	103		
15-17	40.3	18.370	10957		4005	3951	707	127		
18-20	39.3	18.676	10956		4383	3592	528	74		
21-23	35.9	18.432	10956		4737	3049	261	16		
ALL HOURS	36.7	18.772	87658		37237	25946	2916	374		

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: ALL

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
	LE 32	GE 50	GE 67	GE 73	GE 80	
10959	5087	2677	138	3	0	10959
10957	5271	2436	78	2	0	10957
10957	5140	2677	107	3	0	10957
10957	4494	3601	426	46	0	10957
10957	4068	3954	671	103	2	10957
10959	4005	3951	707	127	1	10959
10956	4383	3592	528	74	0	10956
10956	4789	3048	261	16	0	10956
87658	37237	25946	2916	374	3	87658

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES			
				LE 27	GE 37	LE 55	GE 65
00-02	5.2	14.254	930	883	0	930	0
03-05	4.7	14.333	929	896	1	929	0
06-08	4.2	14.674	930	895	3	930	0
09-11	5.2	14.300	929	893	1	929	0
12-14	8.2	12.853	930	880	0	930	0
15-17	8.3	12.834	930	875	0	930	0
18-20	7.0	13.412	930	892	0	930	0
21-23	5.8	13.885	930	889	0	930	0
ALL HOURS	6.1	13.951	7438	7094	5	7438	0

MONTH: FEB

00-02	7.3	15.278	849	758	3	849	0
03-05	7.0	15.594	849	764	5	849	0
06-08	6.3	15.906	849	770	6	849	0
09-11	8.6	14.657	848	753	5	848	0
12-14	11.3	13.196	849	744	7	849	0
15-17	11.6	13.057	849	741	6	849	0
18-20	10.7	13.639	849	746	8	849	0
21-23	9.2	14.514	849	753	5	849	0
ALL HOURS	9.1	14.662	6791	6034	46	6791	0

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
ST TO UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
930	883	0	930	0	930
929	896	1	929	0	929
930	895	3	930	0	930
929	893	1	929	0	929
930	880	0	930	0	930
930	876	0	930	0	930
930	882	0	930	0	930
930	889	0	930	0	930
7430	7094	5	7438	0	7438

MONTH: FEB

849	758	3	849	0	849
849	764	5	849	0	849
849	770	6	849	0	849
849	758	5	848	0	849
849	744	7	849	0	849
849	741	6	849	0	849
849	746	8	849	0	849
849	753	6	849	0	849
6791	6034	46	6791	0	6791

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURE			
				LE 27	GE 37	LE 55	GE 65
00-02	16.5	12.505	930	757	23	930	0
03-05	15.7	13.190	930	774	20	930	0
06-08	15.1	13.521	930	775	12	930	0
09-11	17.3	11.727	930	733	19	930	0
12-14	18.9	11.114	930	734	38	930	0
15-17	19.2	10.866	930	741	47	930	0
18-20	18.9	11.018	930	733	40	930	0
21-23	17.8	11.772	930	745	29	930	0
ALL HOURS	17.5	12.103	7440	5992	228	7440	0

MONTH: APR

00-02	27.0	9.904	900	492	155	900	0
03-05	26.5	9.904	900	511	141	900	0
06-08	27.0	9.713	900	477	138	900	0
09-11	28.9	9.847	900	430	186	893	0
12-14	29.1	10.317	900	432	180	890	0
15-17	28.5	10.485	900	455	177	888	0
18-20	27.8	10.639	900	459	170	888	0
21-23	27.6	10.312	900	466	170	891	0
ALL HOURS	27.8	10.209	7200	3722	1317	7150	0

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 98
TIME ZONE: UTC + 5 MONTH: MAR

TOTAL HRS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
930	757	23	930	0	930
930	774	20	930	0	930
930	775	12	930	0	930
930	733	19	930	0	930
930	734	38	930	0	930
930	741	47	930	0	930
930	733	40	930	0	930
930	745	29	930	0	930
7440	5992	228	7440	0	7440

MONTH: APR

900	492	155	900	0	900
900	511	141	900	0	900
900	477	138	900	0	900
900	430	186	893	0	900
900	432	180	890	0	900
900	455	177	888	0	900
900	459	170	888	0	900
900	456	170	891	0	900
7200	3722	1317	7150	0	7200

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
 FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
 MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES			
				LE 27	GE 37	LE 55	GE 65
00-02	36.2	10.711	930	217	439	901	0
03-05	35.7	10.593	930	216	428	906	0
06-08	37.3	10.232	930	173	474	898	0
09-11	39.0	11.055	930	160	534	872	7
12-14	39.1	11.605	930	169	513	862	10
15-17	38.8	11.975	930	182	497	844	11
18-20	39.0	11.969	930	204	487	849	8
21-23	37.4	11.160	930	212	472	882	3
ALL HOURS	37.7	11.255	7440	1533	3844	7014	39

MONTH: JUN

00-02	45.9	9.346	900	16	740	755	21
03-05	45.2	9.247	900	23	717	770	10
06-08	46.7	8.493	900	4	783	753	12
09-11	48.3	9.157	900	4	801	695	41
12-14	48.4	9.526	900	8	793	677	44
15-17	48.0	9.718	900	12	783	692	44
18-20	47.4	9.931	900	23	767	704	51
21-23	46.9	9.226	900	12	778	731	34
ALL HOURS	47.1	9.427	7200	102	6162	5777	257

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
DTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY

TOTAL HRS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
930	217	439	901	0	930
930	216	428	906	0	930
930	173	474	898	0	930
930	160	534	872	7	930
930	169	513	862	10	930
930	182	497	844	11	930
930	204	487	849	8	930
930	212	472	882	3	930
7440	1533	3844	7014	39	7440

MONTH: JUN

900	16	740	755	21	900
900	23	717	770	10	900
900	4	783	753	12	900
900	4	801	695	41	900
900	8	793	677	44	900
900	12	783	692	44	900
900	23	767	704	51	900
900	12	778	731	34	900
7200	102	6162	5777	257	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURE			
				LE 27	GE 37	LE 55	GE 65
00-02	53.6	7.863	930	0	912	546	66
03-05	52.6	8.074	930	0	904	564	49
06-08	54.2	7.391	930	0	920	504	71
09-11	56.2	7.360	930	0	926	411	120
12-14	56.3	7.631	930	0	928	420	146
15-17	56.2	7.238	930	0	923	425	142
18-20	55.9	8.029	928	0	919	426	142
21-23	55.2	7.632	927	0	920	474	114
ALL HOURS	55.0	7.874	7435	0	7352	3770	850

MONTH: AUG

00-02	53.5	8.018	930	0	902	540	74
03-05	52.6	8.223	930	0	897	561	61
06-08	53.2	7.859	930	1	909	546	59
09-11	55.5	7.508	930	0	919	455	105
12-14	55.6	7.330	930	0	920	450	124
15-17	55.5	8.066	930	2	918	461	131
18-20	55.4	7.793	927	1	916	462	115
21-23	54.7	7.722	930	0	914	491	92
ALL HOURS	54.5	7.989	7439	4	7295	3966	761

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MT
D UTG: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
930	0	912	546	66	930
930	0	904	564	49	930
930	0	920	504	71	930
930	0	926	411	120	930
930	0	928	420	146	930
930	0	923	425	142	930
928	0	919	426	142	928
927	0	920	474	114	927
7435	0	7352	3770	850	7435

MONTH: AUG

930	0	902	540	74	930
930	0	897	561	61	930
930	1	909	546	59	930
930	0	919	455	105	930
930	0	920	450	124	930
930	2	918	461	131	930
927	1	916	462	115	930
930	0	914	491	92	930
7439	4	7295	3966	761	7439

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 7
MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES			
				LE 27	GE 37	LE 55	GE 65
00-02	46.6	9.232	900	13	749	741	13
03-05	46.0	9.407	900	24	735	751	12
06-08	46.1	9.166	900	16	746	748	14
09-11	48.7	8.493	900	0	836	685	33
12-14	49.0	9.482	900	3	810	648	57
15-17	49.1	9.346	900	0	822	662	57
18-20	48.5	9.018	900	0	818	690	39
21-23	47.3	8.942	900	2	782	727	21
ALL HOURS	47.7	9.244	7200	58	6298	5652	246

MONTH: OCT

00-02	35.0	9.313	930	204	373	911	0
03-05	34.5	9.234	929	215	366	912	0
06-08	34.2	9.156	930	237	352	916	0
09-11	36.3	8.770	930	144	442	916	0
12-14	36.3	9.588	930	166	429	913	0
15-17	35.7	9.710	930	187	413	912	0
18-20	35.9	9.230	930	170	395	907	0
21-23	35.4	9.235	930	180	382	907	0
ALL HOURS	35.4	9.329	7439	1503	3152	7294	0

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP

TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
600	13	749	741	13	900
900	24	735	751	12	900
900	16	746	748	14	900
900	0	836	685	33	900
900	3	810	648	57	900
900	0	822	662	57	900
900	0	818	690	39	900
900	2	782	727	21	900
900	58	6298	5652	246	7200

MONTH: OCT

930	204	373	911	0	930
930	215	366	912	0	930
930	237	352	916	0	930
930	144	442	916	0	930
930	166	429	913	0	930
930	187	413	912	0	930
930	170	395	907	0	930
930	180	382	907	0	930
939	1503	3152	7294	0	7439

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78
LST TO UTC: + 5 MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES D			
				LE 27	GE 37	LE 55	GE 65
00-02	23.8	10.402	900	576	95	900	0
03-05	23.4	10.694	900	593	80	900	0
06-08	23.1	10.943	900	599	80	900	0
09-11	24.4	10.350	900	567	102	899	0
12-14	25.5	10.183	900	544	127	897	0
15-17	25.1	10.320	900	548	110	897	0
18-20	24.4	10.150	900	557	104	898	0
21-23	23.3	10.223	900	583	100	900	0
ALL HOURS	24.2	10.466	7200	4567	798	7191	0

MONTH: DEC

00-02	12.3	13.203	930	630	13	930	0
03-05	12.2	13.493	930	832	15	928	0
06-08	11.7	13.798	928	832	13	928	0
09-11	12.3	13.194	930	819	12	930	0
12-14	15.0	11.844	923	801	13	928	0
15-17	14.9	11.932	930	803	11	930	0
18-20	13.7	12.349	930	820	7	930	0
21-23	13.0	12.643	930	828	6	930	0
ALL HOURS	13.3	12.887	7436	6565	90	7434	0

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: + 5 MONTH: NOV

F S	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
0	576	95	900	0	900
0	593	80	900	0	900
0	599	80	900	0	900
0	567	102	899	0	900
0	544	127	897	0	900
0	548	110	897	0	900
0	557	104	898	0	900
0	583	100	900	0	900
0	4567	798	7191	0	7200

MONTH: DEC

0	830	13	930	0	928
0	832	15	928	0	928
0	832	13	928	0	928
0	819	12	930	0	928
0	801	13	928	0	928
0	803	11	930	0	928
0	820	7	930	0	928
0	828	6	930	0	928
0	6565	90	7434	0	7436

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN	NUMBER OF HOURS WITH TEMPERATURES	LE 27	GE 37	LE 55	GE 65
00-02	30.4	20.008	10959	4746	4404	9833	174		
03-05	29.8	20.047	10957	4848	4309	9900	132		
06-08	30.0	20.593	10957	4779	4436	9802	156		
09-11	31.9	20.509	10957	4508	4783	9463	306		
12-14	32.8	19.617	10957	4481	4758	9394	381		
15-17	32.7	19.575	10959	4547	4707	9420	385		
18-20	32.1	19.854	10956	4595	4631	9463	355		
21-23	31.3	20.012	10956	4670	4559	9642	264		
ALL HOURS	31.4	20.061	87658	37174	36587	76917	2153		

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: ALL

TOTAL HOURS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
	LE 27	GE 37	LE 55	GE 65	
959	4746	4404	9833	174	10959
957	4848	4309	9900	132	10957
957	4779	4436	9802	156	10957
957	4508	4783	9463	306	10957
957	4481	4758	9394	381	10957
959	4547	4707	9420	385	10959
956	4595	4631	9463	355	10956
956	4670	4559	9642	264	10956
958	37174	36587	76917	2153	87658

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: JAN

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN	TOT
	10%	20%	30%	40%	50%	60%	70%	80%	90%		
00-02	100.0	100.0	99.9	99.4	91.9	78.6	59.6	32.3	11.8	72.0	
03-05	100.0	100.0	100.0	99.9	93.8	78.9	59.8	32.0	11.1	72.3	
06-08	100.0	100.0	99.9	99.5	93.7	79.3	60.6	33.8	12.5	72.4	
09-11	100.0	100.0	100.0	99.8	92.1	79.7	59.3	29.5	12.1	71.5	
12-14	100.0	100.0	99.6	95.9	82.9	67.7	44.6	19.0	5.9	66.2	
15-17	100.0	100.0	99.9	93.5	77.6	64.6	39.9	18.6	5.2	64.3	
18-20	100.0	100.0	100.0	98.0	87.2	71.8	53.0	25.5	7.1	68.9	
21-23	100.0	100.0	100.0	99.2	92.0	77.8	57.1	29.6	10.3	71.2	
ALL HOURS	100.0	100.0	99.9	98.0	88.9	74.3	54.1	27.5	9.5	71.2	7

MONTH: FEB

00-02	100.0	100.0	99.9	99.9	94.0	83.0	61.0	34.6	13.3	73.3	
03-05	100.0	100.0	100.0	100.0	95.9	81.7	65.3	35.9	14.3	74.0	
06-08	100.0	100.0	100.0	100.0	94.9	81.7	64.8	35.5	15.3	74.0	
09-11	100.0	100.0	99.9	99.4	95.0	80.0	58.7	28.2	11.7	71.9	
12-14	100.0	99.9	99.5	95.1	79.5	61.5	38.8	16.1	5.5	64.1	
15-17	100.0	100.0	98.8	89.9	74.7	56.5	37.0	15.7	3.9	62.1	
18-20	100.0	100.0	99.9	96.2	85.4	69.5	47.7	23.4	6.3	67.4	
21-23	100.0	100.0	100.0	99.9	93.8	80.7	56.7	32.4	9.9	71.8	
ALL HOURS	100.0	100.0	99.7	97.4	89.1	74.3	53.7	27.7	10.1	71.8	6

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME TO UTC: + 5 MONTH: JAN

.....								
RELATIVE HUMIDITY GREATER THAN OR EQUAL TO								
30%	40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
.....								
99.9	99.4	91.9	78.6	59.6	32.3	11.9	72.0	930
99.9	99.9	93.3	78.9	59.8	32.0	11.1	72.3	929
99.9	99.5	93.7	78.5	60.6	33.8	12.5	72.4	930
99.9	99.8	92.1	79.7	59.3	29.5	12.1	71.5	929
99.5	95.9	82.9	67.7	44.6	19.0	5.9	66.2	930
99.9	93.5	77.6	64.6	39.9	18.6	5.2	64.3	930
99.9	98.0	87.2	71.3	53.0	25.5	7.1	68.9	930
99.9	99.2	92.0	77.8	57.1	29.6	10.3	71.2	930
99.9	94.0	88.9	74.3	54.1	27.5	9.5	71.2	7438

MONTH: FEB

.....								
99.9	99.9	94.0	83.0	61.0	34.6	13.3	73.3	849
99.9	100.0	95.9	81.7	65.3	35.9	14.3	74.0	849
99.9	100.0	94.9	81.7	64.8	35.5	15.3	74.0	849
99.9	99.4	95.0	80.0	58.7	28.2	11.7	71.9	848
99.9	95.1	79.5	61.5	38.8	16.1	5.5	64.1	849
99.9	99.9	74.7	56.5	37.0	15.7	3.9	62.1	849
99.9	96.2	85.4	69.5	47.7	23.4	6.3	67.4	849
99.9	94.9	83.8	80.7	56.7	32.4	9.9	71.8	849
99.9	97.4	89.1	74.3	53.7	27.7	10.1	71.8	6791

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: MAR

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOT
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02	100.0	100.0	99.9	99.0	94.5	85.3	66.8	39.8	16.2	74.8	
03-05	100.0	100.0	100.0	99.6	95.3	87.3	69.5	45.3	19.5	76.1	
06-08	100.0	100.0	100.0	99.1	95.6	99.1	71.0	44.4	18.0	76.5	
09-11	100.0	100.0	100.0	97.1	92.4	77.4	55.2	31.7	12.9	71.3	
12-14	100.0	99.9	97.2	90.4	73.7	58.2	38.2	21.1	8.9	63.3	
15-17	100.0	99.6	96.1	85.9	70.8	55.2	37.5	20.1	8.9	61.9	
18-20	100.0	99.9	98.7	93.0	83.0	67.6	45.8	25.2	10.8	67.1	
21-23	100.0	100.0	99.7	98.0	92.9	82.3	60.1	35.6	14.8	73.1	
ALL HOURS	100.0	99.9	99.0	95.3	87.3	75.4	55.5	32.9	13.6	73.1	7

MONTH: APR

00-02	100.0	100.0	99.7	97.4	92.0	82.4	60.3	39.8	19.4	74.1	
03-05	100.0	100.0	100.0	98.8	94.7	86.3	70.1	45.3	20.6	76.6	
06-08	100.0	100.0	100.0	98.1	94.0	85.3	67.7	46.1	23.4	76.6	
09-11	100.0	99.6	96.3	88.4	76.7	59.4	42.2	25.6	13.4	65.1	
12-14	100.0	97.8	90.2	74.8	58.4	43.3	30.2	20.4	8.4	57.2	
15-17	100.0	96.8	88.1	70.4	53.8	39.2	27.4	16.3	7.0	54.8	
18-20	100.0	98.9	92.9	80.2	64.6	48.3	31.9	17.7	9.4	59.1	
21-23	100.0	100.0	98.6	93.4	85.8	71.9	49.4	30.0	13.7	69.2	
ALL HOURS	100.0	99.1	95.8	87.7	77.5	64.5	47.4	30.4	14.4	69.2	7

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: MAR

.....								
RELATIVE HUMIDITY GREATER THAN OR EQUAL TO								
	40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
.....								
99.9	99.0	94.5	86.3	66.8	39.8	16.2	74.8	930
99.0	99.6	95.3	87.3	69.5	45.3	18.5	76.1	930
98.0	99.1	95.6	89.1	71.0	44.4	18.0	76.5	930
97.0	97.1	92.4	77.4	55.2	31.7	12.9	71.3	930
96.0	90.4	73.7	58.2	38.2	21.1	8.9	63.3	930
95.0	85.9	70.8	55.2	37.5	20.1	8.9	61.9	930
94.0	93.0	83.0	57.6	45.8	25.2	10.8	67.1	930
93.0	98.0	92.9	82.3	60.1	35.6	14.8	73.1	930
92.0	95.3	87.3	75.4	55.5	32.9	13.6	73.1	7440
.....								

MONTH: APR

.....								
99.7	97.4	92.0	82.4	60.3	39.8	19.4	74.1	900
99.0	98.8	94.7	86.3	70.1	45.3	20.6	76.6	900
98.0	95.1	94.0	85.3	67.7	46.1	23.4	76.6	900
97.0	88.4	76.7	59.4	42.2	25.6	13.4	65.1	900
96.0	74.8	53.4	43.3	30.2	20.4	8.4	57.2	900
95.0	70.4	53.8	39.2	27.4	15.3	7.0	54.8	900
94.0	40.2	64.6	48.3	31.9	17.7	9.4	59.1	900
93.0	93.4	85.8	71.9	49.4	30.0	13.7	69.2	900
92.0	87.7	77.5	64.5	47.4	30.4	14.4	69.2	7200

OPERATING LOCATION *AM*
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 -
LST TO UTC: + 5 MONTH: MAY

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOTAL
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02	100.0	100.0	100.0	98.8	94.4	81.7	63.4	37.4	15.2	73.8	93
03-05	100.0	100.0	99.9	99.6	97.0	89.2	72.5	46.0	17.5	77.1	93
06-08	100.0	100.0	99.5	97.5	92.7	83.3	66.0	41.6	15.2	74.3	93
09-11	100.0	98.2	93.0	80.0	65.5	48.7	31.6	18.4	8.2	59.0	93
12-14	100.0	97.0	83.4	65.9	52.6	36.0	23.1	13.7	5.6	52.2	93
15-17	100.0	96.9	82.6	65.7	47.4	33.8	21.3	11.3	4.9	50.8	93
18-20	100.0	98.5	90.0	74.7	58.3	42.4	28.0	14.6	6.2	55.8	93
21-23	100.0	100.0	99.4	93.8	82.5	65.4	46.8	27.6	10.2	67.4	93
ALL HOURS	100.0	98.9	93.5	84.5	73.8	60.1	44.1	26.3	10.4	67.4	744

MONTH: JUN

00-02	100.0	100.0	100.0	99.9	98.0	92.3	72.0	44.9	16.2	76.9	90
03-05	100.0	100.0	100.0	100.0	99.3	96.2	83.3	56.9	18.1	80.2	90
06-08	100.0	100.0	100.0	99.4	96.3	88.8	67.6	42.4	14.1	75.6	90
09-11	100.0	100.0	98.1	89.9	73.1	48.8	27.4	13.9	6.7	60.2	90
12-14	100.0	99.6	93.7	78.4	54.0	34.2	18.3	8.9	3.7	53.5	90
15-17	100.0	99.7	93.2	74.2	51.7	32.1	19.2	9.2	3.3	52.8	90
18-20	100.0	99.8	95.7	85.0	62.6	42.2	26.8	13.3	3.9	57.5	90
21-23	100.0	100.0	99.9	98.2	90.4	73.1	51.1	29.7	9.8	69.8	90
ALL HOURS	100.0	99.9	97.6	90.6	78.2	63.5	45.7	27.4	9.5	69.8	720

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TO UTC: + 5 MONTH: MAY

RELATIVE HUMIDITY GREATER THAN OR EQUAL TO								
	40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
0.0	98.8	94.4	81.7	63.4	37.4	15.2	73.8	930
0.2	99.6	97.0	89.2	72.5	46.0	17.5	77.1	930
0.5	97.5	92.7	83.3	66.0	41.6	15.2	74.3	930
1.0	80.0	65.5	48.7	31.6	18.4	8.2	59.0	930
1.4	65.9	52.6	36.0	23.1	13.7	5.6	52.2	930
1.6	65.7	47.4	33.8	21.3	11.3	4.9	50.8	930
2.0	74.7	58.3	42.4	28.0	14.6	6.2	55.8	930
2.4	93.8	82.5	65.4	46.8	27.6	10.2	67.4	930
2.5	34.5	73.8	60.1	44.1	26.3	10.4	67.4	7440

MONTH: JUN

0.0	99.8	98.0	92.3	72.0	44.9	16.2	76.9	900
0.1	100.0	99.3	96.2	83.3	56.9	18.1	80.2	900
0.3	99.4	96.3	88.8	67.6	42.4	14.1	75.6	900
0.4	89.9	73.1	48.8	27.4	13.9	6.7	60.1	900
0.7	78.4	54.0	34.2	18.3	8.9	3.7	53.5	900
0.8	74.2	51.7	32.1	19.2	9.2	3.3	52.8	900
0.7	85.0	62.6	42.2	26.8	13.3	3.9	57.5	900
0.9	93.2	90.4	73.1	51.1	29.7	9.8	69.8	900
1.6	90.6	78.2	63.5	45.7	27.4	9.5	69.8	7200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435 STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG
LST TO UTC: + 5 MONTH: JUL

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN
	10%	20%	30%	40%	50%	60%	70%	80%	90%	
00-02	100.0	100.0	100.0	100.0	99.8	97.2	84.9	57.8	25.4	81.0
03-05	100.0	100.0	100.0	100.0	100.0	99.7	93.3	71.3	31.9	84.2
06-08	100.0	100.0	100.0	100.0	99.1	96.0	83.9	59.0	24.5	80.7
09-11	100.0	100.0	99.7	95.7	82.2	60.5	36.6	17.6	6.7	64.2
12-14	100.0	100.0	96.7	86.9	59.1	37.7	19.5	8.9	3.4	55.7
15-17	100.0	99.7	96.1	84.5	60.5	37.6	19.5	9.9	3.9	55.7
18-20	100.0	100.0	98.8	91.3	74.9	51.5	28.9	15.0	6.9	61.2
21-23	100.0	100.0	100.0	99.5	97.0	35.7	62.2	33.5	13.9	73.7
ALL HOURS	100.0	100.0	98.9	94.7	84.1	70.7	53.6	34.1	14.6	73.7

MONTH: AUG										
HOURS	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN
00-02	100.0	100.0	100.0	100.0	100.0	99.7	94.5	75.2	37.7	85.2
03-05	100.0	100.0	100.0	100.0	100.0	99.9	95.5	79.5	44.8	86.7
06-08	100.0	100.0	100.0	100.0	100.0	99.0	94.7	78.3	41.4	86.1
09-11	100.0	100.0	100.0	99.4	92.9	78.7	56.1	33.5	16.2	72.0
12-14	100.0	100.0	99.9	94.7	76.9	53.1	30.9	16.3	6.9	62.3
15-17	100.0	100.0	99.5	92.2	71.0	52.5	32.7	15.6	7.0	61.3
18-20	100.0	100.0	100.0	97.5	87.8	69.6	49.5	25.0	9.6	68.3
21-23	100.0	100.0	100.0	100.0	99.9	95.9	83.2	57.5	25.3	80.5
ALL HOURS	100.0	100.0	99.9	98.0	91.1	81.1	67.1	47.6	23.6	80.5

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
LST TO UTC: + 5 MONTH: JUL

RELATIVE HUMIDITY GREATER THAN OR EQUAL TO

30% 40% 50% 60% 70% 80% 90% MEAN TOTAL OBS

100.0 100.0 99.8 97.2 84.9 57.8 25.4 81.0 930

100.0 100.0 100.0 99.7 93.3 71.3 31.9 84.2 930

100.0 100.0 99.1 96.0 83.9 59.0 24.5 80.7 930

99.7 95.7 82.2 60.5 36.6 17.6 6.7 64.2 930

96.7 86.9 59.1 37.7 19.5 8.9 3.4 55.7 930

96.1 84.5 60.5 37.6 19.5 9.9 3.9 55.7 930

98.8 91.3 74.9 51.5 28.9 15.0 6.9 61.2 928

100.0 99.5 97.0 85.7 62.2 33.5 13.9 73.7 927

98.9 94.7 84.1 70.7 53.6 34.1 14.6 73.7 7435

MONTH: AUG

100.0 100.0 100.0 99.7 94.5 75.2 37.7 85.2 930

100.0 100.0 100.0 99.9 95.5 79.5 44.8 86.7 930

100.0 100.0 100.0 99.0 94.7 78.3 41.4 86.1 930

100.0 99.4 92.9 78.7 56.1 33.5 16.2 72.0 930

99.9 94.7 76.9 53.1 30.9 16.3 6.9 62.3 930

99.5 92.2 71.0 52.5 32.7 15.6 7.0 61.3 930

100.0 97.5 87.8 69.6 49.5 25.0 9.6 68.3 929

100.0 100.0 99.9 95.9 83.2 57.5 25.3 80.5 930

99.9 98.0 91.1 81.1 67.1 47.6 23.6 80.5 7439

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: SEP

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN
	10%	20%	30%	40%	50%	60%	70%	80%	90%	
00-02	100.0	100.0	100.0	100.0	100.0	99.1	94.6	72.0	32.7	84.9
03-05	100.0	100.0	100.0	100.0	100.0	99.8	96.6	77.3	38.2	86.4
06-08	100.0	100.0	100.0	100.0	100.0	99.8	97.1	80.1	42.2	86.9
09-11	100.0	100.0	100.0	99.8	97.1	87.7	67.4	42.3	22.1	76.2
12-14	100.0	100.0	99.6	94.8	81.7	64.4	43.1	26.4	12.6	66.6
15-17	100.0	100.0	99.4	94.1	80.9	64.2	42.7	25.4	12.2	66.5
18-20	100.0	100.0	99.9	99.2	95.3	83.7	62.8	33.6	16.9	74.2
21-23	100.0	100.0	100.0	100.0	100.0	98.1	87.1	63.6	26.4	82.4
ALL HOURS	100.0	100.0	99.9	98.5	94.4	87.1	73.9	53.2	25.4	82.4

MONTH: OCT

00-02	100.0	100.0	100.0	99.7	99.1	96.3	86.1	64.2	25.9	82.0
03-05	100.0	100.0	100.0	100.0	99.4	97.0	87.6	66.8	29.0	83.2
06-08	100.0	100.0	100.0	100.0	99.6	98.4	88.7	64.9	27.1	83.2
09-11	100.0	100.0	100.0	99.4	96.6	86.8	67.0	43.0	17.8	76.0
12-14	100.0	100.0	98.9	92.7	79.7	60.6	39.1	23.5	9.8	65.0
15-17	100.0	99.2	95.0	89.2	74.8	59.1	36.7	19.7	8.3	63.1
18-20	100.0	100.0	99.8	98.4	92.7	80.4	61.6	35.8	13.4	73.0
21-23	100.0	100.0	100.0	99.4	98.5	93.7	81.4	53.9	21.8	79.9
ALL HOURS	100.0	100.0	99.6	97.2	92.5	84.0	68.5	46.5	19.1	79.8

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
 UTC: + 5 MONTH: SEP

RELATIVE HUMIDITY GREATER THAN OR EQUAL TO							
40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
100.0	100.0	99.1	94.6	72.0	32.7	84.9	900
100.0	100.0	99.8	96.6	77.3	38.2	86.4	900
100.0	100.0	99.8	97.1	80.1	42.2	86.9	900
99.8	97.1	87.7	67.4	42.3	22.1	76.2	900
94.8	81.7	64.4	43.1	26.4	12.6	66.6	900
94.1	80.9	64.2	42.7	25.4	12.2	66.5	900
79.2	95.3	83.7	62.8	33.6	16.9	74.2	900
100.0	100.0	98.1	87.1	63.6	26.4	82.4	900
83.5	94.4	87.1	73.9	53.2	25.4	82.4	7200

MONTH: OCT

79.7	99.1	96.3	86.1	64.2	25.9	82.0	930
100.0	99.4	97.0	87.6	66.8	29.0	83.2	929
100.0	99.6	98.4	88.7	64.9	27.1	83.2	930
99.4	96.6	86.8	67.0	43.0	17.8	76.0	930
92.7	79.7	60.6	39.1	23.5	9.8	65.0	930
98.2	74.8	59.1	36.7	19.7	8.3	63.1	930
98.4	92.7	80.4	61.6	35.8	13.4	73.0	930
97.4	98.5	93.7	81.4	53.9	21.8	79.8	930
97.2	92.5	84.0	68.5	46.5	19.1	79.8	7439

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 78
MONTH: NOV

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN	TOTAL
	10%	20%	30%	40%	50%	60%	70%	80%	90%		
00-02	100.0	100.0	100.0	99.4	96.3	89.9	68.7	41.3	17.3	76.2	9
03-05	100.0	100.0	100.0	99.4	97.7	90.6	72.4	42.2	16.8	76.7	9
06-08	100.0	100.0	100.0	99.3	98.2	91.9	73.7	46.4	19.3	77.7	9
09-11	100.0	100.0	99.8	98.9	97.2	85.1	66.2	38.9	14.3	74.9	9
12-14	100.0	99.6	98.9	96.0	87.0	66.6	44.4	26.0	11.3	67.7	9
15-17	99.9	99.7	98.1	92.4	82.4	63.3	41.9	25.0	10.9	66.1	9
18-20	100.0	100.0	99.6	97.9	90.8	78.4	55.0	33.2	13.1	71.8	9
21-23	100.0	100.0	100.0	99.2	95.4	87.4	64.6	38.2	14.7	74.8	9
ALL HOURS	100.0	99.9	99.5	97.8	93.1	81.7	59.9	35.4	14.7	74.8	72

MONTH: DEC

00-02	100.0	100.0	100.0	99.9	97.5	86.2	65.4	38.1	19.4	75.5	9
03-05	100.0	100.0	100.0	99.7	98.1	88.3	67.6	41.4	17.3	75.9	9
06-08	100.0	100.0	100.0	99.8	98.4	88.1	68.2	41.4	17.3	76.1	9
09-11	100.0	100.0	100.0	100.0	98.0	87.8	66.8	39.5	16.7	75.7	9
12-14	100.0	100.0	99.8	98.7	91.8	75.4	53.4	26.8	12.4	70.5	9
15-17	100.0	100.0	99.8	97.6	88.8	69.7	49.4	25.2	12.2	69.0	9
18-20	100.0	100.0	100.0	99.2	94.9	80.3	60.9	33.3	14.4	73.0	9
21-23	100.0	100.0	100.0	99.4	96.7	85.4	65.4	37.6	13.0	74.9	9
ALL HOURS	100.0	100.0	99.9	99.3	95.5	82.7	62.1	35.4	15.9	74.9	74

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TIME ZONE: UTC + 5 MONTH: NOV

RELATIVE HUMIDITY GREATER THAN OR EQUAL TO

40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
99.4	96.3	89.9	68.7	41.3	17.3	76.2	900
99.4	97.7	90.6	72.4	42.2	16.8	76.7	900
99.3	98.2	91.9	73.7	46.4	19.3	77.7	900
98.9	97.2	85.1	66.2	38.9	14.3	74.9	900
96.0	87.0	66.6	44.4	26.0	11.3	67.7	900
92.4	82.4	63.3	41.9	25.0	10.9	66.1	900
97.9	90.8	78.4	55.0	33.2	13.1	71.8	900
99.2	95.4	87.4	64.6	38.2	14.7	74.8	900
97.3	93.1	81.7	59.9	35.4	14.7	74.8	7200

MONTH: DEC

99.9	97.5	86.2	65.4	38.1	19.4	75.5	930
99.7	98.1	88.3	67.6	41.4	17.3	75.9	930
99.8	98.4	88.1	68.2	41.4	17.3	76.1	928
100.0	98.0	97.8	66.8	39.5	16.7	75.7	930
98.7	91.8	75.4	53.4	26.8	12.4	70.5	928
97.6	88.8	69.7	49.4	25.2	12.2	69.0	930
99.2	94.9	80.8	60.9	33.3	14.4	73.0	930
99.4	96.7	85.4	65.4	37.6	18.0	74.9	930
99.3	95.5	82.7	62.1	35.4	15.9	74.9	7436

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG
MONTH: ALL

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN
00-02	100.0	100.0	99.9	99.4	96.5	89.4	73.2	48.2	20.9	77.5
03-05	100.0	100.0	100.0	99.7	97.6	91.3	77.9	53.4	23.2	79.1
06-08	100.0	100.0	99.9	99.4	96.9	90.1	75.4	51.3	22.6	78.4
09-11	100.0	99.9	98.9	95.5	88.2	73.4	52.8	30.2	13.2	69.3
12-14	100.0	99.5	96.4	88.7	73.1	54.9	35.3	18.9	7.9	62.0
15-17	100.0	99.3	95.8	85.7	69.5	52.3	33.7	17.7	7.3	60.7
18-20	100.0	99.7	97.9	92.5	81.5	65.5	46.0	25.2	9.9	66.4
21-23	100.0	100.0	99.8	98.2	93.7	83.1	63.8	39.1	15.8	74.1
ALL HOURS	100.0	99.8	98.5	94.9	87.1	75.0	57.3	35.5	15.1	71.0

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STN NAME: K. I. SAWYER AFB MI PERIOD OF RECORD: AUG 78 - JUL 88
TZ UTC: + 5 MONTH: ALL

.....								
RELATIVE HUMIDITY GREATER THAN OR EQUAL TO								
	40%	50%	60%	70%	80%	90%	MEAN	TOTAL OBS
.....								
7	99.4	96.5	89.4	73.2	48.2	20.9	77.5	10959
0	99.7	97.6	91.3	77.9	53.4	23.2	79.1	10957
9	99.4	96.9	90.1	75.4	51.3	22.6	78.4	10957
4	95.5	89.2	73.4	52.8	30.2	13.2	69.9	10957
4	88.7	73.1	54.9	35.3	18.9	7.9	62.0	10957
5	85.7	69.5	52.3	33.7	17.7	7.3	60.7	10959
7	82.5	81.5	65.5	46.0	25.2	9.9	66.4	10956
8	98.2	93.7	83.1	63.8	39.1	15.8	74.1	10956
5	94.9	97.1	75.0	57.3	35.5	15.1	71.0	97658

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

SEA LEVEL PRESSURE IN MILLIBARS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
0100	MEAN	1016.4	1018.3	1016.3	1014.5	1014.3	1013.7	1015.0	1015.8	1016.2	1016.3
	SD	9.785	9.409	8.845	8.137	6.883	6.092	4.772	5.411	6.408	8.547
	TOT OBS	310	283	310	300	310	300	310	310	300	310
0400	MEAN	1016.4	1018.2	1016.0	1014.2	1014.7	1013.6	1014.8	1015.7	1016.0	1016.1
	SD	9.879	9.506	7.003	8.476	7.048	6.333	4.949	5.508	6.569	8.729
	TOT OBS	310	283	310	300	310	300	310	310	300	310
0700	MEAN	1016.4	1018.5	1016.4	1014.8	1015.4	1014.3	1015.4	1016.3	1016.6	1016.5
	SD	10.077	9.670	9.150	8.921	7.162	6.418	5.057	5.616	6.730	8.927
	TOT OBS	310	283	310	300	310	300	310	310	300	310
1000	MEAN	1016.9	1019.0	1016.8	1015.0	1015.4	1014.4	1015.4	1016.5	1016.3	1016.9
	SD	10.193	9.786	9.233	8.877	7.231	6.381	5.069	5.554	6.792	9.006
	TOT OBS	310	282	310	300	310	300	310	310	300	310
1300	MEAN	1016.3	1018.4	1016.4	1014.7	1015.0	1014.1	1015.1	1016.2	1016.3	1016.4
	SD	9.994	9.800	9.173	8.567	7.113	6.116	4.879	5.408	6.711	8.739
	TOT OBS	310	283	310	300	310	300	310	310	300	310
1600	MEAN	1016.9	1017.6	1015.9	1014.1	1014.4	1013.7	1014.6	1015.6	1015.6	1015.9
	SD	9.713	9.630	9.925	8.156	6.911	5.846	4.709	5.228	6.478	8.443
	TOT OBS	310	283	310	300	309	300	310	310	300	310
1900	MEAN	1016.7	1018.4	1016.1	1014.5	1014.4	1013.6	1014.4	1015.5	1015.9	1016.6
	SD	9.596	9.432	8.839	7.781	6.758	5.691	4.556	5.108	6.367	8.285
	TOT OBS	310	283	310	300	310	300	309	310	300	310
2200	MEAN	1016.8	1018.5	1016.4	1015.0	1014.9	1014.1	1014.9	1016.0	1016.4	1016.8
	SD	9.663	9.415	8.809	7.674	6.729	5.778	4.478	5.155	6.282	8.420
	TOT OBS	310	283	310	300	310	300	309	309	300	309
ALL HOURS	MEAN	1016.5	1018.4	1016.2	1014.6	1014.9	1013.9	1014.9	1015.9	1016.2	1016.4
	SD	9.869	9.589	9.005	8.328	6.991	6.095	4.825	5.387	6.554	8.646
	TOT OBS	2480	2263	2480	2400	2479	2400	2478	2479	2400	2479

SEA LEVEL PRESSURE IN MILLIBARS
FROM HOURLY OBSERVATIONS

STATION: K. I. SAWYER AFB MI

PERIOD OF RECORD: AUG 78 - JUL 88

+ 5

	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
1014.5	1014.3	1013.7	1015.0	1015.8	1016.2	1016.3	1016.7	1016.0	1015.8	
8.137	6.883	6.092	4.772	5.411	6.408	8.547	9.344	9.749	8.039	
300	310	300	310	310	300	310	300	310	3653	
1014.2	1014.7	1013.6	1014.8	1015.7	1016.0	1016.1	1016.6	1016.1	1015.7	
8.476	7.048	6.333	4.949	5.508	6.569	8.729	9.393	9.820	8.185	
300	310	300	310	310	300	310	300	310	3653	
1014.8	1015.4	1014.3	1015.4	1016.3	1016.6	1016.5	1016.7	1016.2	1016.1	
8.821	7.162	6.418	5.057	5.616	6.730	8.927	9.594	10.013	8.338	
300	310	300	310	310	300	310	300	310	3653	
1015.0	1015.4	1014.4	1015.4	1015.5	1016.3	1016.9	1017.2	1016.7	1016.4	
8.877	7.231	6.381	5.069	5.554	6.792	9.006	9.782	10.083	8.424	
300	310	300	310	310	300	310	300	310	3652	
1014.7	1015.0	1014.1	1015.1	1016.2	1016.3	1016.4	1016.4	1016.0	1015.9	
8.567	7.113	6.116	4.879	5.408	6.711	8.739	9.789	10.192	8.302	
300	310	300	310	310	300	310	300	310	3653	
1014.1	1014.4	1013.7	1014.6	1015.6	1015.6	1015.9	1015.9	1015.6	1015.4	
8.156	6.911	5.846	4.709	5.228	6.479	8.443	9.618	10.037	8.069	
300	309	300	310	310	300	310	300	310	3652	
1014.5	1014.4	1013.6	1014.4	1015.5	1015.9	1016.6	1016.6	1016.3	1015.7	
7.781	6.758	5.691	4.556	5.108	6.367	8.285	9.483	10.030	7.969	
300	310	300	309	310	300	310	300	310	3652	
1015.0	1014.9	1014.1	1014.9	1016.0	1016.4	1016.8	1016.7	1016.3	1016.1	
7.674	6.729	5.778	4.478	5.155	6.282	8.420	9.430	9.867	7.928	
300	310	300	309	309	300	309	299	310	3649	
1014.6	1014.9	1013.9	1014.9	1015.9	1016.2	1016.4	1016.6	1016.1	1015.9	
8.328	5.991	6.095	4.825	5.387	6.554	8.646	9.561	9.979	8.164	
2400	2479	2400	2478	2479	2400	2479	2399	2480	29217	

pppppppp	aaaaaa	rrrrrrrr	TTTTTTTTT	FFFFFFFFF
pppppppp	aaaaaaaa	rrrrrrrr	TTTTTTTTT	FFFFFFFFF
pp pp	aa aa	rr rr	TT	FF
pp pp	aa aa	rr rr	TT	FF
pppppppp	aa aa	rrrrrrrr	TT	FFFFF
pppppppp	aaaaaaaaaa	rrrrrrrr	TT	FFFFF
pp	aaaaaaaaaa	rr rr	TT	FF
pp	aa aa	rr rr	TT	FF
pp	aa aa	rr rr	TT	FF
pp	aa aa	rr rr	TT	FF

PART F

PRESSURE SUMMARIES

ALL PRESSURE DATA IN PART F IS TAKEN FROM HOURLY OBSERVATIONS. IT IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD SYNOPTIC REPORTING TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

SEA LEVEL PRESSURE.

IN MILLIBARS, TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS. THIS SUMMARY IS NOT AVAILABLE FOR METAR REPORTING SITES.

ALTIMETER SETTING.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS.

STATION PRESSURE.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS AND TOTAL OBSERVATION COUNTS.

PRESSURE CONVERSIONS ARE: 1 MILLIBAR = 0.02953 INCHES OF MERCURY (HG).

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

ALTIMETER SETTING IN INCHES
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG 1

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
0100	MEAN	29.94	30.00	29.96	29.93	29.95	29.93	29.98	30.00	30.00	29.99
	SD	.278	.266	.253	.236	.197	.175	.137	.155	.181	.246
	TOT OBS	310	283	310	300	310	300	310	310	300	310
0400	MEAN	29.94	30.00	29.95	29.92	29.95	29.93	29.97	30.00	30.00	29.98
	SD	.281	.269	.256	.245	.202	.181	.142	.157	.187	.252
	TOT OBS	310	283	310	300	310	300	310	310	299	310
0700	MEAN	29.94	30.00	29.95	29.93	29.97	29.95	29.99	30.01	30.01	29.99
	SD	.286	.273	.261	.256	.206	.185	.146	.160	.191	.258
	TOT OBS	310	283	310	300	310	299	310	310	300	310
1000	MEAN	29.95	30.02	29.97	29.94	29.97	29.95	29.99	30.02	30.02	30.00
	SD	.289	.273	.264	.257	.209	.185	.148	.160	.194	.261
	TOT OBS	310	281	310	300	310	300	310	310	300	310
1300	MEAN	29.94	30.00	29.96	29.93	29.96	29.94	29.98	30.01	30.00	29.99
	SD	.285	.277	.264	.248	.205	.177	.141	.155	.191	.253
	TOT OBS	310	282	310	300	310	300	310	310	300	310
1600	MEAN	29.93	29.98	29.94	29.92	29.94	29.93	29.97	29.99	29.98	29.97
	SD	.278	.273	.256	.236	.198	.169	.135	.150	.185	.244
	TOT OBS	309	283	310	300	309	300	310	310	300	310
1900	MEAN	29.95	30.00	29.95	29.92	29.94	29.93	29.96	29.99	29.99	29.99
	SD	.273	.266	.253	.224	.194	.164	.131	.146	.181	.239
	TOT OBS	310	283	310	300	310	300	309	310	300	309
2200	MEAN	29.95	30.00	29.95	29.94	29.95	29.94	29.98	30.00	30.00	30.00
	SD	.274	.265	.253	.222	.194	.166	.130	.148	.179	.243
	TOT OBS	310	283	310	300	310	300	309	310	300	310
ALL HOURS	MEAN	29.94	30.00	29.95	29.93	29.95	29.94	29.98	30.00	30.00	29.99
	SD	.281	.271	.258	.241	.201	.176	.139	.154	.187	.250
	TOT OBS	2479	2261	2480	2400	2479	2399	2478	2480	2399	2479

ALTIMETER SETTING IN INCHES
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88

	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
20	29.96	29.93	29.95	29.93	29.98	30.00	30.00	29.99	29.98	29.94	29.97
21	.253	.236	.197	.175	.137	.155	.181	.246	.268	.280	.229
22	310	300	310	300	310	310	300	310	300	310	3653
23	29.95	29.92	29.95	29.93	29.97	30.00	30.00	29.98	29.98	29.94	29.96
24	.256	.245	.202	.191	.142	.157	.187	.252	.269	.283	.233
25	310	300	310	300	310	310	299	310	299	310	3651
26	29.95	29.93	29.97	29.95	29.99	30.01	30.01	29.99	29.98	29.94	29.97
27	.261	.256	.206	.185	.146	.160	.191	.258	.275	.287	.238
28	310	300	310	299	310	310	300	310	300	310	3652
29	29.97	29.94	29.97	29.95	29.99	30.02	30.02	30.00	29.99	29.96	29.98
30	.264	.257	.209	.185	.148	.160	.194	.261	.281	.289	.241
31	310	300	310	300	310	310	300	310	300	310	3651
32	29.96	29.93	29.96	29.94	29.98	30.01	30.00	29.99	29.97	29.94	29.97
33	.264	.248	.205	.177	.141	.155	.191	.253	.282	.293	.238
34	310	300	310	300	310	310	300	310	300	310	3652
35	29.94	29.92	29.94	29.93	29.97	29.99	29.98	29.97	29.96	29.93	29.95
36	.256	.236	.198	.169	.135	.150	.185	.244	.277	.289	.231
37	310	300	309	300	310	310	300	310	300	310	3651
38	29.95	29.92	29.94	29.93	29.96	29.99	29.99	29.99	29.97	29.95	29.96
39	.253	.224	.194	.164	.131	.146	.181	.239	.272	.288	.226
40	310	300	310	300	309	310	300	309	300	310	3651
41	29.95	29.94	29.95	29.94	29.98	30.00	30.00	30.00	29.98	29.94	29.97
42	.253	.222	.194	.166	.130	.148	.179	.243	.271	.283	.226
43	310	300	310	300	309	310	300	310	299	310	3651
44	29.95	29.93	29.95	29.94	29.98	30.00	30.00	29.99	29.98	29.94	29.97
45	.258	.241	.201	.176	.139	.154	.187	.250	.274	.286	.233
46	2430	2400	2479	2399	2478	2480	2399	2479	2398	2480	29212

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

STATION PRESSURE IN INCHES
FROM HOURLY OBSERVATIONS

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD: AUG

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
0100	MEAN	28.63	28.69	28.65	28.62	28.65	28.63	28.67	28.69	28.69	28.6
	SD	.268	.256	.245	.227	.190	.169	.132	.150	.175	.23
	TOT OBS	310	283	310	300	310	300	310	310	300	31
0400	MEAN	28.63	28.69	28.64	28.61	28.64	28.62	28.67	28.69	28.69	28.6
	SD	.271	.259	.248	.236	.194	.175	.136	.152	.181	.24
	TOT OBS	310	283	310	300	310	300	310	310	299	31
0700	MEAN	28.63	28.69	28.65	28.62	28.66	28.64	28.68	28.70	28.70	28.6
	SD	.276	.263	.252	.246	.198	.179	.141	.155	.185	.25
	TOT OBS	310	283	310	300	310	299	310	310	300	31
1000	MEAN	28.65	28.71	28.66	28.63	28.65	28.65	28.68	29.71	28.71	28.6
	SD	.279	.268	.256	.248	.202	.178	.142	.155	.188	.25
	TOT OBS	310	281	310	300	310	300	310	310	300	31
1300	MEAN	28.63	28.70	28.65	28.63	28.65	28.64	28.67	28.70	28.69	28.6
	SD	.276	.267	.256	.240	.197	.171	.136	.150	.185	.24
	TOT OBS	310	282	310	300	310	300	310	310	300	31
1600	MEAN	28.62	28.67	28.63	28.61	28.63	28.63	28.66	28.68	28.67	28.6
	SD	.268	.263	.248	.227	.191	.163	.130	.145	.178	.23
	TOT OBS	309	283	310	300	309	300	310	310	300	31
1900	MEAN	28.64	28.69	28.64	28.62	28.63	28.62	28.66	28.68	28.68	28.6
	SD	.263	.256	.245	.216	.187	.158	.127	.141	.175	.23
	TOT OBS	310	283	310	300	310	300	309	310	300	30
2200	MEAN	28.64	28.70	28.65	28.63	28.65	28.64	28.67	28.69	28.69	28.6
	SD	.254	.256	.245	.214	.187	.161	.125	.143	.173	.23
	TOT OBS	310	283	310	300	310	300	309	310	300	31
ALL HOURS	MEAN	28.63	28.69	28.65	28.62	28.65	28.63	28.67	28.69	28.69	28.6
	SD	.271	.261	.249	.232	.194	.170	.134	.149	.180	.24
	TOT OBS	2479	2261	2480	2400	2479	2399	2478	2480	2399	247

STATION PRESSURE IN INCHES
FROM HOURLY OBSERVATIONS

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88

MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
28.65	28.62	28.65	28.63	28.67	28.69	28.69	28.68	28.67	28.63	28.66
.245	.227	.190	.169	.132	.150	.175	.238	.258	.270	.221
310	300	310	300	310	310	300	310	300	310	3653
28.64	28.61	28.64	28.62	28.67	28.69	28.69	28.67	28.67	28.64	28.65
.248	.236	.194	.175	.136	.152	.181	.244	.259	.272	.225
310	300	310	300	310	310	299	310	299	310	3651
28.65	28.62	28.66	28.64	28.68	28.70	28.70	28.68	28.67	28.64	28.66
.252	.246	.198	.179	.141	.155	.185	.250	.265	.277	.230
310	300	310	299	310	310	300	310	300	310	3652
28.66	28.63	28.66	28.65	28.68	28.71	28.71	28.69	28.68	28.65	28.67
.256	.249	.202	.178	.142	.155	.188	.253	.271	.279	.233
310	300	310	300	310	310	300	310	300	310	3651
28.65	28.63	28.65	28.64	28.67	28.70	28.69	28.68	28.66	28.63	28.66
.256	.240	.197	.171	.136	.150	.185	.245	.272	.282	.230
310	300	310	300	310	310	300	310	300	310	3652
28.63	28.61	28.63	28.63	28.66	28.68	28.67	28.67	28.65	28.62	28.65
.243	.227	.191	.163	.130	.145	.178	.236	.267	.279	.223
310	300	309	300	310	310	300	310	300	310	3651
28.64	28.62	28.63	28.62	28.66	28.68	28.68	28.68	28.67	28.64	28.65
.245	.216	.187	.158	.127	.141	.175	.231	.262	.277	.219
310	300	310	300	309	310	300	309	300	310	3651
28.65	28.63	28.65	28.64	28.67	28.69	28.69	28.69	28.67	28.64	28.66
.245	.214	.187	.161	.125	.143	.173	.236	.261	.273	.218
310	300	310	300	309	310	300	310	299	310	3651
28.65	28.62	28.65	28.63	28.67	28.69	28.69	28.68	28.67	28.64	28.66
.249	.232	.194	.170	.134	.149	.180	.242	.265	.276	.225
2480	2400	2479	2399	2478	2480	2399	2479	2398	2480	29212

PPPPPPP	AAAAAA	RRRRRRR	TTTTTTTTT	GGGGGG
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TTTTTTTTT	GGGGGGG
PP PP	AA AA	RR RR	TT	GG GG
PP PP	AA AA	RR RR	TT	GG
PPPPPPPP	AA AA	RRRRRRRR	TT	GG
PPPPPPPP	AAAAAAAAA	RRRRRRR	TT	GG GGG
PP	AAAAAAAAA	RR RR	TT	GG GGGG
PP	AA AA	RR RR	TT	GG GG
PP	AA AA	RR RR	TT	GGGGGGG
PP	AA AA	RR RR	TT	GGGGG

PART G

CROSSWIND SUMMARY

CROSSWIND SUMMARIES.

THESE TABLES ARE CREATED FROM HOURLY AND SPECIAL OBSERVATIONS (INCLUDING PEAK GUST REMARKS). THE TABLES ARE SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY MONTH (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).

THE TABLES GIVE PERCENT OCCURRENCE FREQUENCY (POF) OF THE "CROSS-RUNWAY WIND COMPONENT" FOR THE WIND SPEED CLASSES SPECIFIED IN THE TABLE HEADINGS. THERE ARE TWO COMPONENT CATEGORIES:

THE FIRST COMPONENT IS COMPUTED FROM THE REPORTED WIND DIRECTION AND WIND SPEED FROM HOURLY RECORD OR RECORD-SPECIAL OBSERVATIONS.

THE SECOND COMPONENT IS COMPUTED FROM THE HIGHEST REPORTED WIND SPEED AND DIRECTION FROM ALL OBSERVATIONS INCLUDING REMARKS, GUSTS, AND SPECIAL OBSERVATIONS.

OBSERVATION COUNTS INCLUDE CALM WINDS.

VARIABLE WINDS ARE CONSIDERED A DIRECT CROSSWIND IF THE SPEED EQUALS OR EXCEEDS THE SPECIFIED THRESHOLD WIND SPEED VALUE(S).

A TOTAL OBSERVATION COUNT IS INCLUDED.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNW

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF REC
MONTH: JAN

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES +

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	5.4			930	5.4	.1		930	4.7	.3		930
CATEGORY B	8.0	1.4	.1	1005	7.9	2.3	.1	1010	6.3	2.0	.3	1022

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	11.2	.8		930	9.1	.5		930	4.9	.3		930
CATEGORY B	15.0	3.2	.7	1021	15.1	3.8	.3	1044	8.8	1.9	.2	1040

TIME (LST)	0600 - 2000				ALL HOURS		
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25
CATEGORY A	7.1	.5		4650	6.5	.3	
CATEGORY B	10.9	2.7	.4	5189	9.8	2.4	.3

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-199

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JAN

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

OBS	0300 - 0500				0600 - 0800				0900 - 1100			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	5.4	.1		930	4.7	.3		930	5.7	.4		930
1005	7.9	2.3	.1	1010	5.3	2.0	.3	1022	9.3	2.4	.6	1062

OBS	1500 - 1700				1800 - 2000				2100 - 2300			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	9.1	.5		930	4.9	.3		930	5.7	.3		930
1021	15.1	3.8	.3	1044	8.8	1.9	.2	1040	7.6	2.0	.3	999

OBS	0600 - 2000				ALL HOURS			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
444	7.1	.5		4650	6.5	.3		7440
203	10.9	2.7	.4	5189	9.8	2.4	.3	8203

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD
MONTH: FEB

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SP
.....

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0900			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	2.3	.1		349	2.1			349	2.6			849
CATEGORY B	3.3	1.3	.1	911	3.3	.3		900	3.5	.9		915

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	3.4	.1		249	7.1	.5		849	3.9	.2		849
CATEGORY B	10.0	3.4		909	9.3	2.6	.3	923	5.5	1.9	.2	910

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	5.2	.2		4245	4.3	.1		6
CATEGORY B	6.3	2.1	.1	4569	5.6	1.8	.1	7

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

STATION: K. I. SAWYER AFB MI
ZONAL TIME: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: FEB

TYPE A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

TYPE B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

	0300 - 0500				0600 - 0800				0900 - 1100			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
05												
06	2.1			849	2.6			849	4.1	.1		849
11	3.3	.3		900	3.5	.9		915	5.8	1.6	.1	912

	1500 - 1700				1800 - 2000				2100 - 2300			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
05												
09	7.1	.5		849	3.9	.2		849	3.3	.1		849
04	9.3	2.6	.3	923	5.5	1.9	.2	910	4.2	2.0	.1	913

	0600 - 2000				ALL HOURS			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
	5.2	.2		4245	4.3	.1		6792
	6.3	2.1	.1	4569	5.6	1.8	.1	7293

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
 FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD
 MONTH: MAR

.....
 CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
 CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + S)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
SPEED (KTS)												
CATEGORY A	1.9	.3		930	2.2	.1		930	2.5	.1		930
CATEGORY B	4.0	.6	.3	993	4.3	1.1	.1	988	4.3	1.0	.1	1011

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
SPEED (KTS)												
CATEGORY A	7.3	.8		930	6.7	1.3	.1	930	3.8	.2		930
CATEGORY B	12.9	4.3	.8	1021	12.0	4.1	.9	1007	6.5	1.3	.3	994

TIME (LST)	0600 - 2000				ALL HOURS		
	GE10	GE17	GE25	OBS	GE10	GE17	GE25
SPEED KTS							
CATEGORY A	4.9	.6	.0	4550	3.9	.4	.0
CATEGORY B	8.8	2.6	.5	5058	7.2	2.0	.3

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

NAME: K. I. SAWYER AFB MI
ZCZC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAR

.....
BY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
BY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

	0300 - 0500				0600 - 0800				0900 - 1100			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	2.2	.1		930	2.5	.1		930	4.3	.5		930
993	4.3	1.1	.1	943	4.3	1.0	.1	1011	8.0	2.2	.2	1035

	1500 - 1700				1800 - 2000				2100 - 2300			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	6.7	1.3	.1	930	3.3	.2		930	2.6	.2		930
991	12.0	4.1	.9	1007	6.5	1.3	.3	994	5.1	1.1	.1	995

	0600 - 2000				ALL HOURS			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
	4.9	.6	.0	4650	4.9	.4	.0	7440
	1.8	2.5	.1	5054	7.2	2.0	.3	8044

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HE

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: +5

PERIOD OF RECORD:
MONTH: APR

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPEC

.....

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	2.0	.6		900	1.8	.7		900	2.2	.7		900
CATEGORY B	3.2	1.4	.6	952	2.7	1.6	.8	953	3.9	1.3	.5	959

.....

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	5.2	.6		900	7.1	.7		900	3.3	.3		900
CATEGORY B	12.0	4.1	.6	944	11.8	4.2	.5	950	7.1	1.9	.1	949

.....

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	5.0	.5		4500	3.3	.5		720
CATEGORY B	8.3	2.9	.4	4758	6.7	2.3	.4	750

.....

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

NAME: K. I. SAWYER AFB MI
E: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: APR

TRY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

TRY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

	0300 - 0500				0600 - 0800				0900 - 1100			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
900	1.8	.7		900	2.2	.7		900	5.4	.1		900
952	2.7	1.6	.4	953	3.9	1.3	.5	959	9.2	2.8	.1	956

	1500 - 1700				1800 - 2000				2100 - 2300			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
900	7.1	.7		900	3.8	.3		900	1.7	.1		900
944	11.8	4.2	.5	950	7.1	1.9	.1	949	3.6	.9	.1	939

	0600 - 2000				ALL HOURS			
WAS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
	5.0	.5		4500	3.8	.5		7200
	3.3	2.9	.4	4758	6.7	2.3	.4	7602

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

STATION: K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: MAY

BY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

BY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

0300 - 0500				0600 - 0800				0900 - 1100			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
1.4			930	1.0			930	4.0			930
2.0	.8	.1	980	2.4	.3	.1	999	7.7	1.5		996

1500 - 1700				1800 - 2000				2100 - 2300			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
3.8	.4		930	1.9			930	.6			930
6.4	2.1	.4	971	3.3	1.1		972	1.2	.2		972

0600 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
2.9	.1		4650	2.3	.1		7440
5.6	1.4	.1	4915	4.2	1.1	.1	7838

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

NAME: K. I. SAWYER AFB MI
: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUN

CRITERIA: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CRITERIA: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

	0300 - 0500				0600 - 0800				0900 - 1100			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
AS												
900	.3			900	2.0			900	3.9	.1		900
949	.6			945	3.1	.8	.1	963	7.9	1.6	.3	940

	1500 - 1700				1800 - 2000				2100 - 2300			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
AS												
900	6.7	.4		900	3.2	.2		900	.2			900
941	10.9	3.7	.4	945	6.1	1.7	.5	924	.6	.1		927

0600 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
4.5	.3		4500	2.9	.2		7200
3.2	2.3	.4	4713	5.4	1.5	.2	7534

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

STATION NAME: K. I. SAWYER AFB MI
UTC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: JUL

THEORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

THEORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

		0300 - 0500			0600 - 0800			0900 - 1100				
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	.1			930	.1			930	3.2			930
993	.2			1012	.5			1024	5.5	.2		989

		1500 - 1700			1800 - 2000			2100 - 2300				
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	4.2			930	2.6			928	.6			927
1002	6.9	1.0		992	3.0	.3		967	1.2	.4	.1	970

0600 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
3.2			4643	2.1			7435
5.2	.7		4974	3.4	.5	.0	7949

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
 FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD
 MONTH: AUG

.....
 CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
 CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SP

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	.4			930	.3			930	.6			930
CATEGORY B	.7			999	1.0	.2		1003	1.3	.3		1029

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	7.4	.1		930	7.5			930	2.4	.2		930
CATEGORY B	13.5	2.5	.1	998	11.5	2.7		986	4.2	1.0	.1	990

TIME (LST)	0600 - 2000				ALL HOURS		
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25
CATEGORY A	4.3	.1		4650	2.8	.1	
CATEGORY B	7.4	1.5	.0	5017	5.0	1.0	.0

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

AIRFIELD NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: AUG

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

0200		0300 - 0500				0600 - 0800				0900 - 1100			
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	
930	.3			930	.6			930	3.4	.1		930	
999	1.0	.2		1003	1.3	.3		1029	6.7	1.0		1014	

1400		1500 - 1700				1800 - 2000				2100 - 2300			
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	
930	7.5			930	2.4	.2		930	.4			930	
999	11.5	2.7		986	4.2	1.0	.1	990	1.1	.1		985	

0600 - 2000					ALL HOURS			
GE10	GE17	GE25	OBS		GE10	GE17	GE25	OBS
4.3	.1		4650		2.8	.1		7440
7.4	1.5	.0	5017		5.0	1.0	.0	8004

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD
MONTH: SEP

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + S

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
SPEED (KTS)												
CATEGORY A	1.0			900	.7			900	.3			900
CATEGORY B	2.1	.2		974	1.4			1001	2.2	.2		1016

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
SPEED (KTS)												
CATEGORY A	7.9	.1		900	6.6	.3		900	2.0	.1		900
CATEGORY B	13.1	2.4	.4	987	10.0	3.3	.2	992	3.5	.8	.1	979

TIME (LST)	0500 - 2000				ALL HOURS		
	GE10	GE17	GE25	OBS	GE10	GE17	GE25
SPEED KTS							
CATEGORY A	4.3	.1		4500	3.1	.1	7
CATEGORY B	7.5	1.6	.2	4972	5.4	1.1	.1 7

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

AIRFIELD: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: SEP

CRITERIA: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CRITERIA: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

GROSS	0300 - 0500				0600 - 0800				0900 - 1100			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
100	.7			900	.3			900	4.3	.1		900
174	1.4			1001	2.2	.2		1016	8.3	1.2	.1	998

GROSS	1500 - 1700				1800 - 2000				2100 - 2300			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
160	6.6	.3		900	2.0	.1		900	1.6	.1		900
177	10.0	3.3	.2	992	3.6	.8	.1	979	2.3	.5	.1	969

0500 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
4.3	.1		4500	3.1	.1		7200
7.5	1.6	.2	4972	5.4	1.1	.1	7916

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNET

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD
MONTH:

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLY OBS ONLY)

.....
TIME (LST) 0300 - 0200 0300 - 0500 0600 -
SPEED (KTS) GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS GE10 GE17 GE25
CATEGORY A 1.6 .1 .930 1.5 .1 .930 2.0
CATEGORY B 4.0 .4 .1 1006 2.1 1.1 .1 1005 3.2 .4
.....

.....
TIME (LST) 1200 - 1400 1500 - 1700 1800 -
SPEED (KTS) GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS GE10 GE17 GE25
CATEGORY A 9.2 .4 .930 7.3 .2 .930 2.0 .1
CATEGORY B 14.2 4.2 .4 1009 11.1 3.1 .1 1000 4.9 1.3
.....

.....
TIME (LST) 0500 - 2000 ALL
SPEED KTS GE10 GE17 GE25 OBS GE10 GE17
CATEGORY A 4.9 .2 .0 4550 3.5 .2
CATEGORY B 3.4 2.2 .2 5036 5.5 1.6
.....

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: OCT

A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

0300 - 0500

0600 - 0800

0900 - 1100

GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
1.5	.1		930	2.0			930	4.9	.3	.1	930
2.1	1.1	.1	1005	3.2	.8		1037	8.9	1.8	.3	1038

1500 - 1700

1800 - 2000

2100 - 2300

GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
7.3	.2		930	2.0	.1		930	1.3			930
11.1	3.1	.1	1000	4.9	1.3		1002	3.5	.5		1000

0500 - 2000

ALL HOURS

GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
4.9	.2	.0	4650	3.6	.2	.0	7440
6.4	2.2	.2	5086	6.5	1.6	.1	8097

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD
MONTH: NOV

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES +
.....

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	4.7	.1		900	4.4	.3		900	3.8			900
CATEGORY B	6.1	2.4	.2	967	6.6	1.9	.5	977	4.7	1.9	.1	1027

.....
.....

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	10.2	.2		900	6.9	.1		900	5.0	.1		900
CATEGORY B	15.4	4.3	.3	1027	11.7	3.7		987	7.1	2.7	.1	969

.....
.....

TIME (LST)	0600 - 2000				ALL HOURS		
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25
CATEGORY A	6.4	.1		4500	5.3	.2	
CATEGORY B	9.6	3.0	.2	5026	3.4	2.7	.2

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

NAME: K. I. SAWYER AFB MI
TC: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: NOV

QUERY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

QUERY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

	0300 - 0500				0600 - 0800				0900 - 1100			
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
900	4.4	.3		900	3.8			900	5.9	.1		900
957	6.6	1.9	.5	977	4.7	1.9	.1	1027	9.0	2.6	.3	1016

	1500 - 1700				1800 - 2000				2100 - 2300			
OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
900	6.9	.1		900	5.0	.1		900	5.2	.2		900
927	11.7	3.7		987	7.1	2.7	.1	969	6.4	2.0	.1	957

0600 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
6.4	.1		4500	5.3	.2		7200
3.6	3.0	.2	5026	3.4	2.7	.2	7927

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD
MONTH: DEC

.....
CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

.....
CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SP
.....

.....
TIME (LST) 0000 - 0200 0300 - 0500 0600 - 0800
SPEED (KTS) GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS
CATEGORY A 5.1 .1 930 3.9 930 3.1 930
CATEGORY B 6.2 1.8 .1 970 5.7 1.9 .1 964 4.7 .7 963
.....

.....
TIME (LST) 1200 - 1400 1500 - 1700 1800 - 2000
SPEED (KTS) GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS GE10 GE17 GE25 OBS
CATEGORY A 11.5 .6 930 9.6 .4 930 6.2 .3 930
CATEGORY B 15.3 3.8 .2 967 14.3 3.5 .2 960 9.8 2.4 .4 980
.....

.....
TIME (LST) 0600 - 2000 ALL HOURS
SPEED KTS GE10 GE17 GE25 OBS GE10 GE17 GE25
CATEGORY A 7.2 .3 4650 5.2 .2 7
CATEGORY B 10.5 2.4 .2 4838 9.0 2.2 .2 7
.....

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

NAME: K. I. SAWYER AFB MI
Z: + 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: DEC

CRITERIA: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CRITERIA: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

WINDS	0300 - 0500				0600 - 0800				0900 - 1100			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	3.9			930	3.1			930	5.3			930
970	5.7	1.9	.1	964	4.7	.7		963	7.9	1.5		968

WINDS	1500 - 1700				1800 - 2000				2100 - 2300			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
930	9.6	.4		930	6.2	.3		930	4.7	.1		930
977	14.3	3.5	.2	960	9.8	2.4	.4	980	7.5	2.3	.3	964

WINDS	0600 - 2000				ALL HOURS			
	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
	7.2	.3		4650	6.2	.2		7440
	10.5	2.4	.2	4938	9.0	2.2	.2	7736

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
 FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HE

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
 LST TO UTC: + 5

PERIOD OF RECORD:
 MONTH: ALL

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPEC

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	2.2	.1		10959	2.0	.1		10959	2.1	.1		10959
CATEGORY B	3.5	.0	.1	11690	3.2	.9	.2	11738	3.3	.8	.1	11965

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000			
SPEED (KTS)	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	7.9	.4		10959	6.9	.4	.0	10959	3.5	.2		10957
CATEGORY B	12.9	3.3	.3	11803	11.0	3.2	.3	11757	5.8	1.5	.2	11676

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
CATEGORY A	5.0	.2	.0	54793	3.9	.2	.0	8766
CATEGORY B	3.2	2.1	.2	59125	6.4	1.7	.2	9414

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 009-189

STATION: K. I. SAWYER AFB MI
+ 5

PERIOD OF RECORD: AUG 78 - JUL 88
MONTH: ALL

REMARKS: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

REMARKS: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

0300 - 0500				0600 - 0800				0900 - 1100			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
2.0	.1		10959	2.1	.1		10959	4.6	.2	.0	10959
3.2	.9	.2	11738	3.3	.8	.1	11965	7.9	1.7	.2	11924

1500 - 1700				1800 - 2000				2100 - 2300			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
5.9	.4	.0	10959	3.5	.2		10957	2.3	.1		10956
11.0	3.2	.3	11757	5.8	1.5	.2	11676	3.7	1.0	.1	11590

0600 - 2000				ALL HOURS			
GE10	GE17	GE25	OBS	GE10	GE17	GE25	OBS
5.0	.2	.0	54793	3.9	.2	.0	87667
4.2	2.1	.2	59125	6.4	1.7	.2	94143

pppppppp	AAAAAA	RRRRRRRR	TTTTTTTTT	HH	HH
ppppppppp	AAAAAAAAA	RRRRRRRRR	TTTTTTTTT	HH	HH
pp pp	AA AA	RR RR	TT	HH	HH
pp pp	AA AA	RR RR	TT	HH	HH
ppppppppp	AA AA	RRRRRRRRR	TT	HHHHHHHHHH	HHHHHHHHHH
ppppppppp	AAAAAAAAA	RRRRRRRR	TT	HHHHHHHHHH	HHHHHHHHHH
pp	AAAAAAAAA	RR RR	TT	HH	HH
pp	AA AA	RR RR	TT	HH	HH
pp	AA AA	RR RR	TT	HH	HH
pp	AA AA	RR RR	TT	HH	HH

PART H

DEGREE DAY SUMMARIES

DEGREE DAYS.

CREATED FROM HOURLY OBSERVATIONS (MAX+MIN/2 WHEN AVAILABLE), THESE TABLES GIVE THE THE NUMBER OF DEGREE DAYS FOR EACH MONTH IN EACH YEAR OF THE AVAILABLE PERIOD OF RECORD.

INCLUDED BENEATH EACH SUMMARY ARE STATISTICS BASED ON A 30-YEAR (1951-1980) POR (IF AVAILABLE). THE 30-YEAR POR PROVIDES AWS USERS WITH A SUMMARY CONSISTENT WITH OTHER STANDARD CLIMATIC PUBLICATIONS, NOTABLY THOSE OF THE NATIONAL CLIMATIC DATA CENTER (NCDC). NOTE THAT THE 30-YEAR POR WILL CHANGE TO 1961-1990 AS SOON AS DATA FOR DECEMBER 1990 HAS BEEN PROCESSED.

ASTERISKS (****) DENOTE A MISSING MONTH WITH A DAY (OR DAYS) THAT CANNOT BE CALCULATED AUTOMATICALLY.

HEATING DEGREE DAYS.

ONE "HEATING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE MEAN TEMPERATURE FALLS BELOW A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE ON A GIVEN DAY IS 57 DEGREES, THAT DAY IS SAID TO HAVE 8 HEATING DEGREE DAYS.

COOLING DEGREE DAYS.

ONE "COOLING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE TEMPERATURE RISES ABOVE A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE FOR A GIVEN DAY IS 73 DEGREES, THAT DAY IS SAID TO HAVE 8 COOLING DEGREE DAYS.

*65 DEGREES FAHRENHEIT HAS BEEN SELECTED AS THE NATIONWIDE STANDARD "BASE TEMPERATURE" AT WHICH (AT LEAST THEORETICALLY) NO HEATING OR COOLING IS REQUIRED. IF ANOTHER BASE TEMPERATURE IS USED IN THESE TABLES, IT WAS SPECIALLY REQUESTED BY THE STATION, AND IS NOTED.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

HEATING DEGREE DAYS
FROM HOURLY OBSERVATIONS

BASE TEMPERATURE

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI
LST TO UTC: + 5

PERIOD OF RECORD

YEARS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1957	841	1376	1299	769	502	199	51	133	357	628	1000	1000
1958				386	574	313	81	137	285	503	1000	1000
1959										310	1000	1000
1960	1429	1333	1467	779	447	195	99	90	284	587	1000	1000
1961	1653	1206	1124	791	493	163	41	48	260	579	1000	1000
1962	1687	1496	1157	831	360	228	117	109	368	538	1000	1000
1963	1334	1533	1264	742	507	152	60	166	300	327	1000	1000
1964	1369	1383	1365	793	353	261	66	204	347	633	1000	1000
1965	1675	1539	1448	878	405	261	201	191	440	663	1000	1000
1966	1743	1357	1167	590	576	145	28	115	298	657	1000	1000
1967	1498	1559	1261	800	635	154	121	147	268	706	1000	1000
1968	1531	1524	1120	748	538	237	127	166	198	545	1000	1000
1969	1475	1338	1371	784	515	358	74	23	263	745	1000	1000
1970	1767	1598	1344	773	593	192	81	124	323	534	1000	1000
1972								194	437	791	1000	1000
1973	1499	1376	1014	866	643	132	107	94	375	484	1000	1000
1974	1616	1522	1314	807	580	245	55	120	475	593	1000	1000
1975	1526	1302	1330	969	344	172	74	71	440	607	1000	1000
1976	1636	1277	1274	753	588	122	77	124	376	813	1000	1000
1977	1337	1396	1057	699	231	213	51	189	294	662	1000	1000
1978	1620	1497	1325	903	404	241	126	102	290	662	1000	1000
1979	1726	1612	1294	850	595	198	73	155	309	763	1000	1000
1980	1578	1511	1332	747	340	215	36	40	321	748	1000	1000
1981	1494	1240	1091	756	540	163	76	71	344	714	1000	1000
1982	1355	1460	1279	899	259	273	26	149	313	567	1000	1000
1983	1382	1169	1160	903	615	186	30	33	237	612	1000	1000

HEATING DEGREE DAYS
FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: JAN 57 - JUL 88

YEAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
1957	769	502	189	61	133	357	628	1030	464	7669
1958	386	574	319	81	137	285	508	310	1111	2405
1959	779	447	195	99	90	284	587	929	1530	2674
1960	791	493	165	41	42	260	579	972	1448	8783
1961	631	360	222	117	109	368	538	926	1381	9198
1962	742	507	152	60	166	300	327	882	1591	9458
1963	793	353	261	66	204	347	633	945	1541	9265
1964	872	405	261	201	131	440	663	1020	1279	10001
1965	690	576	146	28	116	298	657	1046	1335	9374
1966	400	635	154	121	137	268	706	1129	1350	9668
1967	748	538	237	127	166	198	545	998	1415	9197
1968	784	515	358	74	29	263	745	1040	1393	9386
1969	773	593	192	81	124	323	534	1006	1382	9677
1970	666	643	182	107	194	437	791	1087	1612	4121
1971	407	530	246	55	94	378	484	999	1381	9023
1972	969	344	172	74	71	440	607	914	1492	9261
1973	753	588	122	77	124	376	813	1136	1609	9845
1974	699	231	213	61	139	294	662	1013	1466	9120
1975	903	404	241	126	102	230	662	1049	1593	9803
1976	350	595	198	73	158	309	763	1060	1286	9984
1977	747	340	215	36	49	321	748	962	1390	9229
1978	756	540	163	76	71	344	714	845	1329	8663
1979	899	259	273	26	149	313	567	985	1251	9321
1980	903	615	156	30	33	237	612	906	1621	8854

1984	1698	1143	1404	720	515	110	84	66	350	523
1985	1586	1447	1129	699	429	270	130	141	312	613
1986	1526	1360	1181	693	377	270	69	133	303	608
1987	1311	1057	977	576	331	71	42	84	188	774
1988	1644	1541	1256	777	373	154	27			
.....										
MEAN	1381	1224	1087	706	426	185	70	108	292	582
SD	564.04	489.82	434.44	254.29	178.27	85.32	43.86	59.75	115.90	191.54

404	720	515	110	84	66	350	523	953	1341	8907
129	699	429	270	130	141	312	613	1082	1633	9471
181	693	377	270	69	133	303	608	1063	1246	8829
977	576	331	71	42	84	188	774	952	1244	7607
256	777	373	154	27						5772

087	706	426	185	70	108	292	582	910	1257	
44	254.29	178.27	85.32	43.86	59.75	115.90	191.54	308.47	442.94	

OPERATING LOCATION "A"
 USAFETAC, ASHEVILLE NC

COOLING DEGREE DAYS
 FROM HOURLY OBSERVATIONS

BASE TEMPERATU

STATION NUMBER: 727435

STATION NAME: K. I. SAWYER AFB MI

PERIOD OF RECC

LST TO UTC: + 5

YEARS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
1957						41	108	56	14	
1958					2	5	50	66	10	
1960						17	62	67	31	
1961						46	111	104	57	
1962					43	21	33	48	4	6
1963						97	126	35	3	1
1964					19	50	110	43	6	
1965					7	19	27	34		3
1966						81	161	54	16	
1967						22	51	30	17	
1968						23	68	77	12	18
1969					14	12	76	138	19	
1970						43	107	50	18	
1972								29		
1973						11	50	98	38	3
1974					5	9	92	32	4	
1975					28	50	149	70		
1976						44	49	102	31	
1977					30	24	106	23		
1978					24	21	44	57	25	
1979						15	107	26	15	
1980					17	52	93	73	6	
1981					1	10	93	49	6	
1982					11	4	102	49	30	
1983						78	200	130	53	
1984					2	29	43	85		

COOLING DEGREE DAYS
FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

STATION NAME: K. I. SAWYER AFB MI
TIME ZONE: + 5

PERIOD OF RECORD: JAN 57 - JUL 88

YEAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
		2	41 5 17	108 50 62	56 66 67	14 10 31				219 133 177
			46 21 97	111 33 126	104 48 35	57 4 3				318 155 262
		19 7	50 19	110 27	43 38	6				228 94
			81 22 23	161 51 68	54 30 77	16 17 12				312 120 198
		14	12 43	76 107	138 60	19 18		18		259 228
					29 98 32					29 200 142
		5 28	11 9 50	50 92 149	70	38 4		3		297
			44 24 21	49 106 44	102 23 57	31 25				226 183 171
		30 24 17	24 21 15 52	107 93	26 73	15 6				163 246
			10 4 78	93 102 200	49 49 130	6 30 53				159 196 461
		1 11 2	10 4 29	93 102 43	49 49 85					159 196 461 159

[Redacted header area]

1985		2	6	35	39	22	
1986		12	14	131	27	2	
1987	4	49	101	166	74	19	
1988		28	92	144			
.....							
MEAN	0	9	32	84	55	14	0
SD	.13	13.63	29.66	50.87	34.21	15.31	3.32

[Redacted footer area]

	2	6	35	39	22		104
--	---	---	----	----	----	--	-----

	12	14	131	27	2		186
4	49	101	166	74	19		413
	28	92	144				264

.....

0	9	32	84	55	14		0
---	---	----	----	----	----	--	---

.13	13.63	29.66	50.87	34.21	15.31		3.32
-----	-------	-------	-------	-------	-------	--	------

A W S STATION NAME: K. I. SAWYER AFB MI
 CLIMATIC BRIEF LATITUDE/LONGITUDE: 46 21 N 087 24 W
 HOURLY OBS POR: AUG 78 - JUL 88
 SUMMARY OF DAY POR: OCT 56 - DEC 57, APR 58 - OCT 58, OCT 59 - JUL 88
 HOURS SUMMARIZED: 0000 - 2300 LST
 MAR 89 LST TO UTC: +05

MONTH	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
EXTRM MAX TEMP (F)	47	55	68	84	94	102	101	95	94
MEAN MAX TEMP (F)	19.9	23.3	32.6	47.0	60.9	70.2	75.8	72.8	63.6
MEAN TEMP (F)	12.2	14.7	24.1	37.9	49.8	59.0	64.9	62.7	54.6
MEAN MIN TEMP (F)	4.3	5.8	15.1	28.3	38.3	47.4	53.7	52.1	45.0
EXTRM MIN TEMP (F)	-27	-30	-22	-3	17	25	32	30	21
D/W TEMP GE 30 (F)	0	0	0	#	2	5	10	7	2
D/W TEMP GE 75 (F)	0	0	0	1	5	10	18	13	5
D/W TEMP LT 33 (F)	31	29	29	22	10	1	#	#	2
D/W TEMP LT 0 (F)	11	10	4	#	0	0	0	0	0
HEATING DEGREE DAYS	1381	1224	1087	706	426	185	70	108	292
COOLING DEGREE DAYS				#	9	32	84	55	14
MEAN DEWPOINT TEMP (F)	6.1	9.1	17.5	27.8	37.7	47.1	55.0	54.5	47.7
MEAN WET BULB TEMP (F)	12.4	15.3	23.4	34.5	44.7	53.0	59.6	58.2	51.1
99.95% WCPA (FT)	2050	1950	1950	1900	1800	1700	1550	1600	1700
MEAN REL HUM 07 LST(%)	72.4	74.0	76.5	76.6	74.3	75.6	80.7	86.1	86.9
MEAN REL HUM 13 LST(%)	66.2	64.1	63.3	57.2	52.2	53.5	55.7	62.3	66.6
MAX 24HR PRECIP (IN)	1.76	1.44	1.80	2.20	2.39	2.63	3.29	2.74	2.31
MAX PRECIP (IN)	4.96	3.45	4.81	5.99	6.87	9.29	9.00	7.82	7.66
MEAN PRECIP (IN)	2.07	1.80	2.33	2.68	2.96	3.24	3.42	3.52	4.02
MIN PRECIP (IN)	.81	.31	.48	.65	.10	.49	1.06	.34	1.23
D/W PRECIP GE .01 (IN)	17	14	13	11	12	12	10	11	13
D/W PRECIP GT .50 (IN)	1	1	1	1	2	2	2	2	3
MAX 24HR SNFL (IN)	23.8	17.9	21.0	9.9	3.0	#	#	#	3.0
MAX SNFL (IN)	92.8	48.1	45.6	25.6	4.9	#	#	#	3.4
MEAN SNFL (IN)	30.6	23.8	22.9	7.6	.9	#	#	#	.1
D/W SNFL GE .1 (IN)	17	13	11	5	1	0	0	0	#
D/W SNFL GE 1.5 (IN)	6	5	4	1	1	0	0	0	#
MAX DLY SNO DEPTH (IN)	50	43	39	30	4	0	0	0	4
MEAN SFC WND DIR (DEG)	330	360	360	360	030	180	\$210	210	210
MEAN WND SPD (KTS)	7.5	6.7	8.2	7.7	6.5	6.4	5.5	5.7	6.4
MAX WND SPD (KTS)	58	56	53	59	60	54	56	43	43
SKY COVER GT 1/2 (%)	73.0	72.4	68.0	61.7	58.0	55.2	51.0	56.4	62.0
D/W THUNDERSTORMS	#	#	1	1	3	6	7	6	4
D/W FOG (VSBY LT 7 MI)	10	9	12	11	11	12	13	15	17

LEGEND: ANN = ANNUAL POR/YOR = PERIOD/YEARS OF RECORD
 D/W = MEAN NUMBER OF DAYS WITH WCPA = WORST CASE MAXIMUM PRESSURE
 & = BASED ON LESS THAN FULL MONTHS # = LESS THAN 0.5 DAYS OR TRACE
 ** = INSTANTANEOUS PEAK WINDS \$ = PERCENTAGE OF CALM WINDS GREATER
 * = DATA NOT AVAILABLE WIND DIRECTION

I. SAWYER AFB MI
 : 46 21 N 087 24 W
 : OCT 78 - JUL 88
 : OCT 56 - DEC 57, APR 58 - OCT 58, OCT 59 - JUL 88
 : 0000 - 2300 LST

FIELD ELEV: 1220 FT
 STATION MSC: 727435
 CALL SIGN: KSAW

SUPERCEDES: NOV 84

	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	YOR
55	68	84	94	102	101	95	94	81	69	57	102	30
23.3	32.6	47.0	60.9	70.2	75.8	72.8	63.6	52.7	37.2	25.2	48.8	30
14.7	24.1	37.9	49.8	59.0	64.9	62.7	54.6	44.5	31.1	18.8	39.9	30
5.8	15.1	28.3	38.3	47.4	53.7	52.1	45.0	35.7	24.5	12.0	30.5	30
30	-22	-3	17	25	32	30	21	12	-6	-23	-30	30
0	0	#	2	5	10	7	2	1	0	0	27	30
0	0	1	5	10	18	13	5	1	0	0	53	30
0	29	22	10	1	#	#	2	13	25	30	191	30
10	4	#	0	0	0	0	0	0	1	5	31	30
24	1087	706	426	195	70	108	292	582	910	1257	8228	30
		#	9	32	84	55	14	#			194	30
7.1	17.5	27.3	37.7	47.1	55.0	54.5	47.7	35.4	24.2	13.3	31.4	10
5.3	23.4	34.5	44.7	53.0	59.6	58.2	51.1	39.7	29.2	18.5	36.7	10
150	1950	1900	1800	1700	1550	1600	1700	1900	2000	2050	1850	10
0.0	76.5	76.6	74.3	75.6	80.7	86.1	86.9	83.2	77.7	76.1	78.4	10
7.1	63.3	57.2	52.2	53.5	55.7	62.3	66.6	65.0	67.7	70.5	62.0	10
14.44	1.80	2.20	2.39	2.63	3.29	2.74	2.31	2.71	2.56	1.70	3.29	30
95.45	4.81	5.99	6.87	9.29	9.00	7.82	7.66	7.14	7.04	5.83	47.61	30
2.40	2.33	2.68	2.96	3.24	3.42	3.52	4.02	2.95	2.72	2.50	34.75	30
3.31	.48	.65	.10	.49	1.06	.34	1.23	.91	.98	.72	25.41	30
4	13	11	12	12	10	11	13	13	14	17	157	30
1	1	1	2	2	2	2	3	1	1	1	18	30
9	21.0	9.9	3.0	#	#	#	3.0	5.1	11.8	16.2	23.8	30
1	45.6	25.6	4.9	#	#	#	3.4	14.8	40.6	70.9	248.4	30
3	22.9	7.6	.9	#	#	#	.1	3.2	16.8	31.1	137.0	30
3	11	5	1	0	0	0	#	3	10	16	76	30
6	4	1	1	0	0	0	#	1	3	6	27	30
3	39	30	4	0	0	0	4	6	27	38	50	30
30	360	360	030	180	\$210	210	210	210	210	210	210	10
7	8.2	7.7	6.5	6.4	5.5	5.7	6.4	6.7	7.2	7.2	6.8	10
5	53	59	60	54	56	43	43	54	57	49	60	27
4	68.0	61.7	58.0	55.2	51.0	56.4	62.0	70.6	76.0	76.3	65.3	10
7	1	1	3	6	7	6	4	1	1	#	30	30
0	12	11	11	12	13	15	17	15	13	11	149	30

POR/YOR = PERIOD/YEARS OF RECORD
 WCPA = WORST CASE MAXIMUM PRESSURE ALTITUDE
 # = LESS THAN 0.5 DAYS OR TRACE AS APPLICABLE
 \$ = PERCENTAGE OF CALM WINDS GREATER THAN OR EQUAL TO MEAN WIND DIRECTION

		PERCENT OCCURRENCE FREQUENCY OF CEILING AND VISIBIL									
MONTH		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT
.....											
LST											
	00 - 02	53.0	42.3	41.0	24.8	19.9	15.3	11.4	22.7	32.6	35.
	03 - 05	51.1	43.3	45.2	29.2	23.2	16.2	18.5	30.6	36.0	39.
CIG	06 - 08	54.7	46.2	47.0	32.9	24.3	18.4	20.1	33.0	37.1	42.
LT 3000 FT	09 - 11	55.3	47.1	47.4	33.2	24.7	18.0	16.5	30.4	37.4	42.
AND	12 - 14	49.8	45.2	45.8	29.7	20.0	14.0	11.2	23.4	34.3	39.
VSBY	15 - 17	44.9	41.1	41.1	24.4	16.7	11.8	8.8	20.5	29.6	36.
LT 3 MI	18 - 20	44.1	40.8	38.4	24.0	14.6	9.6	8.6	17.5	27.3	31.
	21 - 23	47.6	40.0	38.8	23.1	14.9	11.7	9.4	19.4	29.8	32.
	ALL	50.1	43.3	43.1	27.7	19.8	14.4	13.1	24.7	33.0	37.
.....											
	00 - 02	33.2	30.4	29.2	18.2	16.3	12.0	10.2	18.8	25.3	24.
	03 - 05	32.4	31.9	31.3	21.8	17.4	11.7	16.1	26.8	27.6	27.
CIG	06 - 08	33.8	33.2	34.5	25.4	16.3	13.0	18.1	29.0	29.9	30.
LT 1500 FT	09 - 11	38.7	35.0	35.9	23.9	16.2	11.1	10.8	21.9	27.6	28.
AND	12 - 14	34.0	31.1	31.9	18.3	12.4	7.6	6.3	13.2	20.3	21.
VSBY	15 - 17	29.2	24.0	28.6	14.1	9.5	5.7	5.8	11.7	18.0	16.
LT 3 MI	18 - 20	30.3	22.1	27.1	14.3	10.1	6.6	5.4	11.7	20.2	17.
	21 - 23	30.1	26.1	27.4	17.0	11.4	8.9	7.3	13.5	22.4	21.
	ALL	32.7	29.2	30.8	19.1	14.0	9.6	10.0	18.3	23.9	23.
.....											
	00 - 02	23.4	21.9	24.3	15.9	13.8	10.1	9.0	17.1	21.8	18.
	03 - 05	23.0	23.8	26.6	18.0	15.2	9.6	12.8	23.3	24.8	21.
CIG	06 - 08	25.1	23.9	27.5	20.6	12.7	9.4	13.8	23.8	25.1	24.
LT 1000 FT	09 - 11	27.7	25.2	29.2	19.6	12.3	7.6	6.0	17.0	21.3	21.
AND	12 - 14	24.3	20.4	24.9	14.4	9.9	4.8	3.4	8.4	15.4	13.
VSBY	15 - 17	20.0	16.8	21.8	10.8	7.3	3.3	3.5	6.6	13.8	10.
LT 2 MI	18 - 20	20.9	15.8	20.8	10.4	7.7	4.1	3.6	9.1	16.1	13.
	21 - 23	21.2	18.1	22.2	13.4	9.0	6.4	5.6	11.9	19.1	14.
	ALL	23.2	20.7	24.7	15.4	11.0	6.9	7.1	14.5	19.7	17.
.....											
	00 - 02	1.9	2.4	3.7	3.6	2.6	1.3	2.2	4.6	4.2	2.
	03 - 05	1.5	3.2	4.1	5.6	2.7	2.0	3.3	7.3	4.7	2.
CIG	06 - 08	2.3	4.1	3.9	5.7	2.3	1.7	2.9	4.8	4.4	4.
LT 200 FT	09 - 11	4.1	4.2	5.4	3.2	1.0	.4	.2	.6	1.6	2.
AND	12 - 14	3.0	3.7	4.7	1.0	.1	.4	.0	.2	.8	1.
VSBY	15 - 17	3.9	2.1	4.1	1.1	.0	.4	.0	.0	.6	.
LT 1/2 MI	18 - 20	2.0	2.6	4.0	1.8	.4	.3	.2	.3	2.0	.
	21 - 23	1.6	1.5	3.4	2.4	1.8	.7	.5	.9	3.2	1.
	ALL	2.5	3.0	4.2	3.0	1.4	.9	1.2	2.4	2.7	1.
.....											
HURRICANE/TROPICAL STORMS OBSERVED FOR THE PERIOD : NONE											

A/B	JAN	FEB	MAR	APR	MAY	JUN
60NM	/	/	/	/	/	/
120NM	/	/	/	/	/	/

A/B	JUL	AUG	SEP	OCT	NOV	DEC	JAN
60NM	/	/	/	/	/	/	/
120NM	/	/	/	/	/	/	/

PERCENT OCCURRENCE FREQUENCY OF CEILING AND VISIBILITY

FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	YOR
42.3	41.0	24.8	19.9	15.3	11.4	22.7	32.6	35.2	49.9	55.9	33.7	10
43.3	45.2	29.2	23.2	16.2	12.5	30.6	36.0	39.8	50.1	56.2	37.0	10
46.2	47.0	32.9	24.3	18.4	20.1	33.0	37.1	42.7	54.1	58.2	39.5	10
47.1	47.4	33.2	24.7	18.0	16.5	30.4	37.4	42.2	54.3	56.1	39.0	10
45.2	45.8	29.7	20.0	14.0	11.2	23.4	34.3	39.8	49.3	54.8	35.2	10
41.1	41.1	24.4	16.7	11.8	8.8	20.5	29.6	36.8	46.6	51.5	31.4	10
40.8	38.4	24.0	14.6	9.6	8.6	17.5	27.3	31.5	44.8	51.4	29.6	10
40.0	38.8	23.1	14.9	11.7	9.4	19.4	29.8	32.8	46.3	53.8	30.9	10
43.3	43.1	27.7	19.8	14.4	13.1	24.7	33.0	37.6	49.4	54.7	34.2	10
30.4	29.2	18.2	16.3	12.0	10.2	18.8	25.3	24.4	27.3	31.9	25.9	10
31.9	31.3	21.8	17.4	11.7	16.1	26.8	27.6	27.7	27.4	30.9	28.3	10
33.2	34.5	25.4	18.3	13.0	18.1	29.0	29.9	30.0	30.9	34.6	30.9	10
35.0	35.9	23.9	16.2	11.1	10.8	21.9	27.6	28.1	31.2	36.1	29.6	10
31.1	31.9	18.3	12.4	7.6	6.3	13.2	20.3	21.4	28.2	34.6	24.5	10
24.0	28.6	14.1	9.5	5.7	5.8	11.7	18.0	16.6	26.4	31.0	21.0	10
22.1	27.1	14.3	10.1	6.6	5.4	11.7	20.2	17.6	27.1	30.8	21.1	10
25.1	27.4	17.0	11.4	8.9	7.3	13.5	22.4	21.6	25.0	30.9	22.7	10
29.2	30.8	19.1	14.0	9.6	10.0	18.3	23.9	23.4	28.0	32.6	22.6	10
21.9	24.3	15.9	13.8	10.1	9.0	17.1	21.8	18.2	20.8	25.1	20.5	10
23.8	26.6	18.0	15.2	9.5	12.8	23.3	24.8	21.8	20.6	23.3	22.6	10
23.9	27.5	20.6	12.7	9.4	13.8	23.8	25.1	24.0	22.3	25.6	23.7	10
25.2	29.2	19.6	12.3	7.6	6.0	17.0	21.3	21.2	23.0	27.8	22.3	10
20.4	24.9	14.4	9.9	4.8	3.4	8.4	15.4	13.8	21.8	25.7	17.6	10
15.3	21.8	10.8	7.3	3.3	3.5	6.6	13.8	10.9	21.0	21.2	14.8	10
15.3	20.8	10.4	7.7	4.1	3.6	8.1	16.1	13.3	18.4	21.9	15.2	10
13.1	22.2	13.4	9.0	6.4	5.6	11.9	19.1	14.9	18.3	23.5	17.2	10
20.7	24.7	15.4	11.0	6.9	7.1	14.5	19.7	17.3	20.8	24.3	17.1	10
2.4	3.7	3.6	2.6	1.3	2.2	4.6	4.2	2.5	2.3	2.6	4.5	10
3.2	4.1	5.6	2.7	2.0	3.3	7.3	4.7	2.3	3.1	3.2	5.5	10
4.1	3.9	5.7	2.3	1.7	2.9	4.8	4.4	4.3	3.2	3.4	5.6	10
4.2	5.4	3.2	1.0	.4	.2	.6	1.6	2.8	4.3	4.3	4.5	10
3.7	4.7	1.0	.1	.4	.0	.2	.8	1.0	2.6	3.8	3.2	10
2.1	4.1	1.1	.0	.4	.0	.0	.6	.6	1.2	2.8	2.6	10
2.6	4.0	1.8	.4	.3	.2	.3	2.0	.3	.7	2.7	2.7	10
1.5	3.4	2.4	1.8	.7	.5	.9	3.2	1.2	1.6	3.2	3.3	10
3.0	4.2	3.0	1.4	.9	1.2	2.4	2.7	1.9	2.4	3.3	2.4	10

REMOVED FOR THE PERIOD : NONE

JAN	FEB	MAR	APR	MAY	JUN
/	/	/	/	/	/
/	/	/	/	/	/

JUL	AUG	SEP	OCT	NOV	DEC	ANN
/	/	/	/	/	/	/
/	/	/	/	/	/	/