1. GENERAL

Princeton Mine

The only active property in the district, the Princeton Mine produced a tonnage of 269,041 tons of Cambridge grade ore and shipped 235,009 tons during 1945. These production and shipment tonnages exceeded all previous Princeton yearly figures.

An average of 146 men were employed with 44 men an surface work and 102 occupied underground as compared with a yearly average of 162 men employed during the previous year.

Maintenance and repair of the District water supply system and of the Gwinn Townsite sewer system was done by Princeton Mine surface employees.

The full time services of a doctor were obtained this year for the employees of the Company who live in the district and who work in the Ishpeming and Negaunee mines and Princeton. This acquisition was greatly appreciated by Gwinn District residents.

Schools

The enrollment of the Gwinn school for 1945 was as follows:

Elementary	Grades	8,	257
Junior and	High S	School,	211
Total		and the state	468

An increase of 14 for 1945. A large school bus transports pupils daily from Wells Township to Gwinn, a distance of over twenty miles.

Townsite

No major improvements or changes were made during the past year in the townsite. Furchasers of company houses continued remodeling and painting of the structures to the limits of availability of materials. A branch supply house of the Consolidated Fuel & Lumber Company of Ishpeming was established in the old depot building in anticipation of increased demand for general building materials.

Red Cross Funds Drive

Excellent support was given the Red Cross drive by employees of the Princeton Mine who subscribed a total amount of \$593.50 or an average of \$3.69 per man which was the highest average contribution of any Company Mine or Department on the Marguette range.

House and Lot Sales

At the beginning of the year a total of 16 sides of Company houses were unsold in Gwinn, and 2 in Austin location, the Princeton houses being disposed of in 1944.

1. GENERAL (Cont.)

House and Lot Sales (Cont.)

1

Of the Gwinn houses eleven were sold during the year leaving a balance of five unsold as of December 31, 1945. The two remaining Austin structures were sold. A total of seven lots were also sold during the year in Gwinn Townsite.

The bank building in Gwinn was sold to the Gwinn State Savings Bank in October, the transaction was handled by the Ishpeming office.

Details of Gwinn Townsite transactions are given below:

Street	House No.	Lot	Block	and the second sec	Amount
Pine	188	10	28	John E. Erickson,	800.00
Ash	242	29	26	Mose St. Aubin,	500.00
	240	28	26		500.00
	243	4	26	Hartley Ohlsen,	548.00
Maple	213	11	26	Ernest J. LaFave,	548.00
	139	7	17	Patrick K. Lane,	568.00
Birch	103	9	15	Melio E. Arrieri,	540.00
Maple	235	6	26	Emma D. Dambrosio,	508.00
Elm	184	4	29	Phyllis Locke,	528.00
Ash	232	26	26	John H. Pelkola,	540.00
Maple	242	32	27	Elma L. Granholm,	450.00

All of the above sales were for cash, and amounts remitted to Land Department for execution of deed.

During 1945 the following lots in Gwinn Townsite were sold:

ot	No.	10	of	Block	No.	14	to	Julius Koski,	\$ 100.00
		2	of			29	to	John Stein,	62.50
		13	of			28	to	Arthur Nylander,	100.00
		1	of			28	to	Wilfred Tous ignant,	125.00
=		14	of	-		12	to	John Bond,	125.00
=		12	of			12	to	A. LaFreniere,	125.00
=		8	of			13	to	Alfred Coran,	162.50

Following is a detail of Austin Houses sold:

No. 11 to Mrs. Gustina Storti, \$200.00 Cash No. 65 to Rudolph O. Ketola, 360.00 "

8.	Statement	Showing	Total Or	e Produced j	n District by	C.C.I.Co.,	1903 to 1945 In	nel.
the second se								the second se

YEAR	AUSTIN	PRINCETON	STEPHENSON	GWINN	FRANCIS	GARDNER MACKINAW	TOTAL
Total to 1945,	1, 589, 018	2, 113, 131	3, 835, 157	988, 665	504, 667	1, 289, 118	10,319,756
1945 Product, To Date,	1,589,018	269,041 2,382,172	3, 835, 157	988, 665	504, 667	1, 289, 118	269,041 10,588,797

1. GENERAL (Cont.

b. Statement Showing Ore Shipments by C.C.I.Co., from 1905 to 1944

YEAR	AUSTIN	PRINCETON	STEPHENSON	GWINN	FRANCIS	GARDNER MACKINAW	TOTAL	Concession of the
Total to 1945, 1945,	1, 589, 017	1,958,009	3, 845, 027	1,017,334*	502,131	1, 326, 439	10, 237, 958 235, 009	COLUMN NOT THE ROAD
To Date,	1, 589, 018	2, 193, 018	3, 845, 027	1,017,334*	502, 131	1, 326, 439	10, 472, 967	AV 209

* Included in the shipments from Gwinn Mine is 29,009 tons of Foundry Stockpile ore purchased from the Clement Quinn Company and shipped by the Cleveland Cliffs Iron Company in 1942.

c. Ore in Stock at Mines December 31, 1945

Princeton,

189,194 tons

356

10. TAXES

The following statement gives the taxes in detail for 1945 and 1944 for all company properties in the district. The mine taxes in the summary show totals only, as the detail for each mine is included in the mine report.

The summary also includes the taxes paid by Cliffs Power and Light Company in order to show the total taxes paid in Forsyth Township by the company. exclusive of those paid by the Land Department.

	1945			1	1944			
Forsyth Township	Valuation			Taxes	Valua	tion	Taxes	
Mineral Lands, Gwinn	1	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		L	A		1	
SW1 of SW1 of Sec. 26-45-25, 40 A.	\$	100	\$	2.52	\$ 10	00	2.03	
NET of SET of Sec. 28-45-25, 40A		100		2.52	1	00	2.03	
No of NET " " 34-45-25, 80 A.		200		5.04	21	00	4.05	
SB1 of NB1 of Sec. 34_45_25, 40 A.		100		2.52	1	00	2.03	
NET of NWT of " 34-45-25, 38.05 A.		100		2.52	1	00	2.03	
NET of SEA of " 34-45-25, 36.3 A.		100		2.52	1	00	2.03	
NW1 of Section 35-45-25, 160 A.		400		10.08	4	00	8.10	
Lots 1, 2 and 3 of Sec. 36-45-25 .53 A.		125		3.15	1	25	2.53	
Lots 7, 8 and 9 of Sec. 36-45-25 98.92 A.		260		6.55	21	50	5.28	
Lot 11 of Sec. 36-45-25, 13.3 A.	•	25		.63		25	.51	
Und. 1 of S1 of NB1 of Sec. 28-45-25 80	A.	150	an	3.78	1	50	3.04	
Total,	\$ 1,	660	\$	41.83	\$ 1,6	50 \$	33.66	
Collection fee,				.42		-	.34	
Total Taxes,	and the second		\$	42.25	1 de .	\$	34.00	

10. TAXES (Cont.)

			1945			1944				
			Valuatio	on	Taxes	1	Valuatio	n	Taxes	
Gwinn Townsite - Surface Only		\$		\$		\$		\$		
Lat 2. Sec. 21_45_25.	43.75 4		100		2.52		100		2.03	
WEL of GEL of Soc 21045025.		1								
Mag of Swg of Sec. 2 2000			100		9.59		100		2.03	
Included in plat,	37 64	1	150	12	2 70	322	150		3.04	
NE4 Of NW4 Of Sec. 21-40-20,	11.04 4	Le.	190		0.10		100		0+02	
St of NW4 of Sec. 21-45-25 no	v					1				
included in Plat of Gwinn,	25.01 4	L.	200		5.04		200		4.00	
He of SH4 of Sec. 21-45-25,	65.84	le .	150		3.78		150		3.04	
Whe of SB4 of Sec. 21-45-25,	38.80 A	lo	300		7,56		300		6.08	
Gwinn Townsite Plat,			20,280		511.13		41,160		833.29	
Supts. Res. W2 of SB1 of Sec.	21 1.2 4	1.	1,800		45.35		1,500		30.38	
NW1 of NB1 of Sec. 21-45-25										
except for five acres,		100	100		2.52		100		2.03	
St of NE1 of Sec. 21-45-25,	50.88 A	1.	300		7.56		300		6.08	
Total.	4 mil 10 mil	\$	23,480	\$	591.76	\$	44,060	\$	892.05	
Collection fee.		~	1977 - 1975 1977 - 1975 1977 - 1975	1	5.92	1			8.92	
Total Taxas.			a south to	\$	597.68		A Coloradore	*	900.97	
TOTAL TAROST				*						
Gwinn Townsite Group Divided	by Accour	its							n Maria au	
From Tax Statement,		\$	23,480	\$	597.68	\$	44,060	\$	900.97	
Gwinn Club House, Lot 8. Blk.	17,		500		12.60		500		10.23	
Hospital, Lot 9. Blk. 25.			1.000		25.19		1.000		20.45	
Rented Buildings.			8.420		212.59		28.710		587.19	
Gwinn Townsite, Unsold Lots.			13.560		347.30		13.850		283.10	
Total Group as per state	ment,	3	23,480	\$	597.68	\$	44,060	\$	900.97	
Gardner Mackinaw				A	10.00		-		10.10	
Ng of NB4 of Sec. 35-45-25	87.35 4	1. 🏺	500	\$	12.60	4	500	4	10.13	
Collection fee,		1	and the second	-	.12	-	- Berry general	-	.10	
Total Taxes,				\$	12.72			\$	10,23	
Machinery in Wersharse			900		22.67	*	900	\$	18.40	
Gentrel Weter Blant Mail of WE	1	*		*	~~~~	Ŧ		*		
vontral actor riant May of Ma	4			1			100			
	·	1	-		10 00		EOO		10.05	
Personal - District Office,		1.5	900		12.10		500		10.20	
District Crusher, Ng of NH4	The second									
of Sec. 27-45-25,	-	-	1,000		25,44		1,000	-	20.45	
Total,		\$	2,400	\$	60.84	\$	2,500	\$	51.13	
Austin Location					1.1					
Part of Lot 5, SW1 of NB1 of :	Sec. 20_4	5-25	, 50	\$	1.26	\$	3,500	\$	72.87	
NW1 of SH1 of Sec. 20-45-25.			200	-	5.04	-	3,500		70.87	
NET of SW1 of Sec. 20-45-25.	1. A.		260		6.55		260		5.27	
Total.		\$	510	*	12.85	\$	7.260	\$	147.01	
Collection fee.					13				1.47	
Total taxes.				*	12.98	-	****	4	148.48	
								100 March 100		

0. TAXES (Cont.		1944						
	Va	luati	on	Taxes	Val	uati	on	Taxes
Summary	See.							
Machinery in Warehouse,	Ş	900	\$	22.90	Ŧ	900		18.41
Stephenson Mine,							-	
Princeton Mine,	42	2,450	10,	749.28	411	,260	8,	411.02
Francis Mine,	1		199		Sec.			
Gardner Mackinaw Mine,		2,500		63.61	2	, 500		51.13
Austin Location,		510		12.98	7	,260		148.48
Mineral Lands,		1,660		42.25	1	,660		34.00
Gwinn Townsite,	. 2	3,480		497.68	44	,060		900.97
Gardner Mackinaw Location,	and we want	500		12.72		500		10.23
Central Water Plant,						100		2.05
Personal - District Office		500		12.73	1	500		10.23
District Crusher,		1,000		25.44	-	,000		20.45
Total C.Cll. Co.,	45	3, 500	11,	539.59	469	,740	9,	606.97
Cliffs Power & Light Co.	14	8,150	3,	769.71	148	,150	3,	030.04
Total taxes (Including 1%)	60	1,650	15,	309.30	617	,890	12,	637.01
Princeton - Personal Property	34	0,000	8,	651.35	320	,000	6,	544.58
Taxes Levied - Forsyth Township								
Forsyth Township Valuation,	1,12	3, 860			1,111	,835		1 100
Rate per \$100 of Valuation,	2.	51932			2.0	2493		
Amount of Tex Roll		4 . L .						
School Sinking Fund Tax.	5.6	19.30				4		
County Tax.	6.1	81.23			6,22	6.28		and the
County Road,	1,5	73.40		1000	2,22	3.67		1
Township Tax,	2,2	47.72			2,22	3.67		
Township Debt Service,	2,7	00.00			2,70	0.00		
School,	6, 8	55.55			6,00	3.91		
School Debt Service,	3, 1	36.41		1. A.	3,13	6.41		Sec. And
Rejected Tax,	diam'r.	78.32			1	2.25		in the
Total,	28, 3	91.93			22, 52	6.29		
Amount Paid by C.C.I.Co	11,5	39.59			9,60	6.97		
Amount Paid by C.P. & L.Co.	3'	76.97		1999 - 19	3,03	0.09		
Total	15, 30	09.30	1	Contraction of the	12,63	7.06		1000
Percent Paid by C.C.I.Co. & C.P.&L.,		53.9%			5	6.1%		

16. WATER SUPPLY - GWINN DISTRICT

Under E&A CC-139 a new 500 gpm Layne-Northwest pump was installed and put into operation in May of this year. The old unit, a 500 gpm Cameron, was useless because of the lowering of the water level below the suction capacity of the pump.

A statement of the completed E&A follows:

	Amount Authorized	((Labor	Supp. & Expenses	Total)	Unexpended Balance
Pump Complete,	736.00		694.15	694.15	41.85
Installation,	800.00	326.19	108.86	435.05	364.95
Social Security Taxes,	Concernence stan	All and some	7.39	7.39	7.39
	1536.00	326.19	810,40	1136.59	399.41

16. WATER SUPPLY - GWINN DISTRICT (Cont.)

Following is a comparative cost statement for operating the Pump Station for the years 1945 and 1944:

	1945	1944	Increase	Decrease
General Expense,	\$ 293.66	\$ 66.40	\$ 227.26	-
Maintenance,	444.30	1398.36		954.06
Operating,	477.28	566.23		88.95
Electric Power Kidder Station,	3212.69	4960.27		1747.58
" " Booster "	964.43	815.48	148.95	
E&A Depreciation,	1331.16	1047.01	284.15	and an alter
Total Cost,	6723.52	8853.75		2130.23
" Revenue Credit	5939.11	4798.21	1 martine	
Deficit,	784.41	4055.54		1140.90

A reduction of \$1747.58 in power cost was effected this year because of the increased efficency abtained through the use of the new unit as compared to the power consumption necessary to operate the 1000 gpm Layne Western spare unit throttled down to 500 gpm to prevent bursting of the old wood mains. The reduction in power cost alone compares favorably with the cost of installation of the new unit.

Hydrants

Fire hydrant rental revenue from Forsyth Township continued as last year, namely, 40 hydrants @ \$35.00 per hydrant equalling \$1,400.00. Cost of upkeep of hydrants, including painting and repairs and hydrant boxes, amounted to \$50.20, as compared to cost of \$227.41 in 1944.

16a. SEWER SYSTEM

In addition to the water supply system the Company has maintained the Gwinn townsite sewer system. During the past seven years the yearly expenditure for this work was as follows:

1939	\$ 722.37
1940	 710.69
1941	598.10
1942	336.40
1943	581.06
1944	610.10
1945	842.25

As mentioned in the annual report for last year, maintenance work is becoming increasingly more costly because of the fact that the roots of the now large bordering trees are entering the sewer pipes causing widespread constriction.

17. CONDITION OF PREMISES

The rents accrued, collected, and repair expense for the company houses in Gwinn and Austin locations follows:

	1945	1944	1943	1942	1941
Gwinn Townsite,		87 617 07		\$11. 576 FA	411.417 AS
Repair Expense,	929.74	1,043.92	2, 308.51	8,032.71	5, 320.12
Accrued rents over repair cost	, 857.44	2,570.05	8,181.41	3, 543, 83	6,096.91
Actual rent collected*,	1,698.51	4,103.38	10,942.36	11, 520.13	11, 198.62

Cash collected	for	regular running	accounts,	Year 1945	1, 599.51
Cash collected	for	old charged off	accounts,		99.00
				Total,	\$ 1,698.51

During the year 11 houses (sides) were sold as per detail on other sheet, leaving five houses (sides) of the regular double houses, unsold as of Dec. 31, 1945.

		1945	1944	1943	1942	1941
Au	Rents Accrued,	\$ 44.50	\$1,774.04	\$2,275.83	\$2,231.00	\$2,177.08
	Repair Expense,	80.69	424.59	514.11	417.52	856.35
	Accrued rents over repair cost,	36.19	1,349.45	1,761.72	1,813.48	1, 320.73
	Actual rent collected*	127.57	1,865.25	2, 316, 42	2,449.52	2,152.92
	Cash collected for regular runn	ing accoun	ts, Year 19	45,		80.12
	Cash collected for old charged	off account	its, "	",		47.45

The two houses at Austin Location remaining unsold as of December 31, 1944 were sold during 1945.

Total,

19. EXPLORATION

A brief program of diamond drill exploration under E&A CC 156 was carried out during the fall of this year in the northeast quarter of Section 19, 45-25 to test an area between the Princeton No. 2 and Austin ore bodies in which no previous information had been obtained. The area was considered to possess excellent ore bearing possibilities and should ore have been encountered the present Princeton facilities would have served as the only available means of extraction.

Two comparatively shallow holes were put down but neither showed any enrichment beyond insignificant streaks contained in the jasper formation. Hole No. 51 was drilled vertically to a depth of 530 feet. A penetration of 42 feet into the arkose footwall was made to this finished depth. Hole No. 52 was drilled approximately 500 feet west of No. 51, at the center of the northeast quarter but results were similarly negative.

127.57

19. GWINN ASSOCIATION

The clubhouse is maintained through the financial assistance of the Cleveland-Cliffs Iron Company, the Cliffs Power and Light Company, the Township Board of Education and membership fees received from residents of the community.

The average monthly membership was 246 a decrease of 18 over last year: 190 members were employed at the different mines; the remainder were employed elsewhere or held complimentary memberships as retired employees or members of the armed services.

Activities at the building covered bowling leagues for men and women; card playing facilities for adults; a library, receiving 7 weekly and 21 monthly magazines and daily and weekly newspapers; a library with popular fiction; a recreation room with pool, billiard and table tennis tables; the gymnasium equipped for class work or recreation, such as, basketball, volleyball, handball, badminton, boxing, wrestling and also used for dancing. Separate showers and locker rooms are provided for men and women. Meeting rooms are provided for scout organizations, the American Legion and the different churches and other groups.

Total number of meetings of a business, social, educational or recreational nature was 356; of this number 6 were annual events, Church organizations used the building on 131 occasions, scout troops held 66 meetings, 45 dances were held; federal agencies, women's organizations, rehearsals for plays and musical events, sportsmen's meetings and legion and committee meetings totalled 114. Equipment in the club kitchen was used on 90 occasions and equipment loaned for outside events 38 times.

The gymnasium was used 415 periods for supervised class work or for recreational activities by high school students or adults. There were 123 scheduled basketball games, including league games for boys and girls.

Outdoor activities covered softball, hardball, touch football, and horseshoe pitching. Equipment was furnished by the club for the above. The estimated attendance including participants for all outdoor activities and cottage at Bass Lake was 8,500.

During the year fuel, supplies and equipment were purchased to keep all departments functioning properly and the usual attention was given to the building to keep it in good repair. Arrangements are now underway whereby the local post of the American Legion will take over rooms formerly used as Red Cross quarters for general meetings and social activities.

Employees of the club expect an increase in attendance and activities during the coming year, due to the fact that many former members are being discharged from the armed forces and are returning to the district.

Building

The Clubhouse continues to operate under the same financial arrangements as in previous years. The Cleveland-Cliffs Iron Company renders financial assistance and supervision, the Cliffs Power and Light Company grants free service and the local Board of Education under a contract agreement pays rental for the use of the building and equipment for their physical training program and for social activities including dancing.

19. GWINN ASSOCIATION (Cont.)

The usual amount of attention was given the building, such as, varnishing floors in the lobby, recreation room and community maeting room to keep them in good condition. The gymnasium was given a special coat of gym seal. Bowling alleys were re-finished and new pins purchased. Janitor supplies and fuel were purchased.

Arrangements are being completed to permit members of the American Legion to use rooms as quarters for their meetings and also to provide space for a small kitchen.

The financial condition of the Club is at the lowest point in many years but those in charge hope to correct this situation to some extent due to the fact that the Club will secure from the local Board of Education some fuel to off-set work being done for them in supervising their physical training program. The membership should also increase the coming year as many men that were in service are returning home.

1. GENERAL

Production and costs at the Princeton mine show a considerable improvement for 1945 over past records. The year's production of 269,041 tons was the highest in the history of the property as was also the average daily product of 900 tons per day. Likewise, the tons per man per day figure of 6.20 tons surpassed previous figures. Consequently, the cost of production at the mine was reduced by \$.332 per ton this year as compared to 1944.

The average number of men employed this past year again dropped for the second consecutive year to a figure for 1945 of 146 which was 15 less men than in 1944. A reduction of \$0.19 per ton labor cost, however, was made this year over last.

Labor supply was the important factor in 1945 production and the influence of a shortage during the latter part of the year will be projected into the coming operating season. This phase of operations has been discussed in monthly reports on the property and repetitive statements are needless. A summation, however, would emphasize the fact that mining is now becoming concentrated in the No. 3 plastic orebody wherein a larger number of men is required for development and mining and that the status of development is not as advanced as a balanced operation would demand.

A number of general improvements were made in 1945 which have produced a beneficial effect on allround efficiency. These improvements were, of course, of the type wherein a quick return of the cost involved could be expected and the benefits of lower cost operating be immediately felt. Other possible major improvements are evident, but the return on the investment would, in all probability, coincide with the life of the mine and nothing would be gained.

The accomplishment of single greatest importance was the completion of the 7th Level drift and No. 3 Shaft to that elevation. Without this development work it would be no overstatement, as subsequent maintenance requirements have shown, to say that the property would not have produced any ore in the last few months of 1945. A section of this drift immediately under the orebody, a length of approximately 350 feet, was driven through a very soft, slickensided type of arkose. An excellent description of the rock is given by the observation that auger steel was employed in drilling this stretch of drift and mud was formed in the bottom of the scraper trough in mucking operations. This arkose, at the flattening zone of the dip, filled with slips and cracks produced a dead weight on the timber support. In the months of November and December it was necessary to put a crew of 16 men, working midnight shift, to supplement the regular timber repair gang in maintaining this section.

The south end of this main level drift, the remaining 450 feet to the No. 3 Shart and the plat is in fairly hard arkose and has given no trouble in maintenance. Necessity of working the extra crew in the troublesome section, however, meant the equivalent of four double shift mining or development gangs lost for that retimbering period of several months.

The scraping transfer drift method of loading cars underground has proven superior with the soft tenacious Princeton ore to the heretofore conventional raise and loading chute system. Use of the latter system incurred much loss of time and labor in dislodging ore stuck in the raise and also introduced a safety hazard when drainage water became impounded behind the wedged ore. The sudden slump of the mass often became uncontrollable endangering the chutemen loading cars and causing much delay especially in main drifts because of hand mucking in the clean-up.

In the top timber transfer method the ore is dropped down the mining raise freely to the floor of a drift driven more or less at right angles from a haulage cross-cut at a height of 2 to 8 feet over the back of the cross-cut. The ore is then scraped directly into the cars. The apparent slowness of loading cars one scraperful at a time is actually faster than blowing clear a chute full of sticky ore.

The ore raises in the "heavy" section of the 7th Level drift were to have been replaced when crushed beyond usefullness by top timber transfer drifts but, of course, the necessity of close retimbering prevented their construction. Instead, it was possible to drive the drifts parallel to the main drift from cross-cuts to the north and south of the crushing section. This sidestepped the difficulty to a major extent but produced the undesirable feature of having several crews of miners working above the same transfer which entailed overlapping in delivery of timber, supplies and delays from blasting smoke. Counteracting desirable results, however, have been the use of one scraper hoist to load the ore produced by the several contracts rather than having to use a separate unit for each individual drift and contract and less interference on the haulage line by the use of one chute for loading.

A second loading trench at the No. 2 hoisting shaft was excavated and put into use during the year. Much needed flexibility of tramming methods was obtained by this trench which actually serves as a storage or surge bin. The property possessed ten 52 cubic feet capacity underground ore cars excluding the obsolete second-hand type which was available for purchase at the time of re-opening. It was obviously rather difficult to handle 900 tons of ore per day as set up by production estimates by 10 three-ton cars. Seven additional old 65 foot capacity cars were purchased from other Company mines, repaired and put into service to augment the original string of ten. The use of the trenches for storage, either for ore or rock, releases the cars for further loading enabling the miners to proceed without delays caused by ore pile interference to timbering and drilling. Skip loading under this method proceeds at a regular rate when ore production is high.

A labor wasting operation which was eliminated this year was the bucket method of cleaning skip pit. With the bucket procedure four men required a minimum time of one half a shift to remove the accumulation in the shaft bottom. An inclined raise was brought up from the bottom of the shaft to the inside edge of the storage trench and a short slide cut from the mouth of the raise to the side of the trench. A specially designed scraper brings the accumulation of spillage, regardless of the consistency, up the planked bottom of the raise to the slide at which point the self dumping scraper discharges its load into the trench. The mud is mixed with a small amount of dry ore and via a newly constructed measuring pocket is loaded into the skip. By this method one man can empty the skip pit in one and a half hours which is less than one tenth of the previously needed man hours.

The spillage problem had occasioned much concern and has been eased to a great extent. Because of the sticky characteristic of the ore, the corners of the skip had been fitted with fillet pieces to approximate a circular cross-section which would offer less area for sticking. Heavy chains were also fixed to the skip bottom in an attempt to force the dumping of the ore load. The bulk of the ore that stuck in the skip was concentrated at the bottom sticking the heaviest chain

that could be applied and the net result of the fillet pieces was a reduction in the capacity of the skip, to the point where a 65 cubic foot car produced a heaping load. Manual blowing of compressed air provided the only sure way of completely ridding the skip of its load, and the removal of the fillets provided a margin of a foot from the top of a maximum-fill car load to the lip of the skip when the load was hoisted.

The physical arrangement of the 7th Level loading station at the No. 2 Shaft is unique inasmuch as it is necessary to load the skip over the high side or lip. Obviously, the hoisting rope stretch at load impact offers opportunity for spillage from the tail end of the car load. This condition was most severe when chunky stope ore was being loaded. A splash or "rebound" plate was placed against the shaft timbers behind and at close clearance to the skip which causes most of the overflow stream to glance back into the skip.

Adequate facilities for underground repair of cars and motors were obtained during the year by the cutting of a repair station in the arkose from the 7th Level drift midway between the No. 3 Shaft and the orebody. This feature has aided indirectly to efficiency for the reason that the No. 3 Headframe was not constructed high enough to permit heavy or bulky objects such as cars or haulage motors to be slung below the cage. The cage is of small design and does not have the dimensions to carry large supplies. When it was necessary to bring bulky equipment underground it was necessary to lower it through the No. 2 hoisting shaft below the skip. To eliminate interference to hoisting and offer opportunity to remove dump bars and other apparatus at the underground station, the supply job had to be scheduled for overtime or week-end work when possible. Workmanlike repairs can now be made for the most part in the new station to any piece of underground equipment.

2. PRODUCTION, SHIPMENTS & INVENTORIES

8.	Production by Grade) <u>8</u>			1.1.1.1		
	and the second s	PRI	NCETON	SEC.	. 19 LEASE	· · · · · · · · · · · · · · · · · · ·	OTAL
		1945	1944	194	5 1944	1945	1944
	Cambridge, Total,	<u>245, 355</u> 245, 355	<u>195,005</u> 195,005	23,680	6 <u>21,507</u> 6 <u>21,507</u>	<u>269,041</u> 269,041	216, 512 216, 512
ъ.	Shipmen ts						
		1945	1944	Deci		Increase	Total Increase
	Cambridge,	235,009	192,658			42,351	42, 351
e.	Stockpile Inventori	es					
		1945	1944				
	Cambbidge Sec. 19,	24, 826	19,117	Tons			
	" " 20,	164,368	136,045				
	Total,	189, 194	155,162	Tons			
е.	Production by month	<u>19</u>					
			Sec. 19		Sec. 20		
			Cambridge		Cambbidge	<u>.</u>	otal
-	January,		1,586		20,138	21	724
	February.		200		26. 263	10	659

PRINCET	ON	MINE
ANNUAL	R	EPORT
YEAR	1	945

2, PRODUCTION, SHIPMENTS & INVENTORIES (Cont.)

e. Production by months (Cont.)

	Sec. 19 <u>Gambridge</u>	Sec. 20 Cambridge	Total	
		0E 147	95 147	
March,	7	25,147	20,141	
April,	-	21,588	21, 588	
May,	•	22, 886	22,886	
June,		23,024	23,024	
July.	997	20, 122	21,119	
August,	1,477	15,259	16,736	
September,	2, 984	24, 147	27,131	
October,	4,605	19,909	24, 514	
November,	4,605	14, 566	19,171	
December,	7,043	12,306	19, 349	
Total,	23, 686	245, 355	269,041	
	the second se		the second s	

f. Ore Statement

	Cambridge	Cambridge	Total
On hand Jan. 1, 1945,	19,117	136,045	155, 162
Output for year,	23,686	245, 355	269,041
Transfers,	17,977	17,977	100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100 - 100
Overrun,	· areas		- 2
. Total,	24, 826	399, 377	424, 203
Shipments,		235,009	235,009
Balance on hand			
Dec. 31, 1945,	24,826	164, 368	189, 194

3. ANALYSIS

a. Stockpile Analysis

Grade	Tons		Iron	Phos.	<u>Sil.</u>	Mang.	A1.	Lime	Mag.	Sul.	Loss	Moist.
Cambridge,	164,368	Dry	60.14	.795	4.17	.999	.90	3.83	.57	.019	1.16	and the second
	24, 826	Natl.	51.315	.678	3.56	.853	.77	3.27	.49	.016	.990	14.66

The total tonnage in stock consists of 164,368 tons of Cambridge, and 24,826 tons of Cambridge Section 19 ore.

b. Average Analysis - 1945 Shipments

Grade	Tons	Iron	Phos.	<u>sil.</u>	Mang.	_A1.	Lime	Mag.	Sul.	Loss
Cambridge	235,009	60.90	.776	4.08	.87	.90	2.83	.58	.019	1.16

4. ESTIMATE OF ORE RESERVES

a. Developed Ore

Assumption: 12 cu. ft. equals 1 ton Less 10% for mining and rock

PRINCET	ON MINE
ANNUAL	REPORT
YEAR	1945

4. ESTIMATE OF ORE RESERVES (Cont.)

a. Developed Ore (Cont.)

Princeport	Camb Secti	ridge on 20	Cambridge Sec. 20	Cambridge		
Sec.20	No. 2 Shaft	- No. 3 Shaft	Total	Sec. 19	Total	
25,058	164, 514	498,900	663, 414	40, 913	729, 385	

This total tonnage includes 145,380 net estimated tonnage below 7th Level elevation at Nos. 2 and 3 Shafts.

c. Estimated Analysis

Grade	Trade Name	Tons	Iron	Phos.	Sil.	Mang.	Alum	Lime	Mag.	Sul.	Loss	Moist.
Non-Bessemer	Princeport	25,058	50.60	.256	6.57	1.032	.429	1.365	.882	.020	1.90	15.90
Non-Bessemer	Cambridge	704, 327	51.36	.694	3.29	.85	.97	3.41	.47	.017	1.70	14.97

d. Estimated Tonnage as Required by State Tax Commission

	Prince- port Sec. 20	Cambri Sec. #2 Shaft -	dge 20 #3 Shaft	Cambridge Sec. 20 Total	Cambridge Sec. 19	Total Tons
Above 5th Level (1921 est.)				and the second s	and the second	and the second second
No. 2 Shaft,	27, 842	147,944		147,944	1	175,786
Above 6th Level,			42, 522	42, 522	5,837	48,359
Between 6th & 7th Levels,		28,102	370, 699	398,801	47,448	446,249
Below 7th Level.		7,971	153, 562	161, 533	the second	161, 533
Gross Total Nov. 30, 1945,	27,842	184,017	566,783	750,800	53,285	831, 927
Less December Production,		1,101	11,205	12,306	7,043	19,349
Gross Total Dec. 31, 1945,	27,842	182,916	555, 578	738,494	46,242	812, 578
Less 10% for Mining and Rock,	2,784	18,402	56, 678	75,080	5, 329	83, 193
Net Total Dec. 31, 1945,	25,058	164, 514	498,900	663,414	40,913	729, 385

5. LABOR & WAGES

b. Comparative Statement of Wages and Product

Product, Number of Shifts & Hours,	1945 269,041 6 2-8 hr.	1944 216,512 5 2-8 hr. 1 1-8 hr.	<u>Increase</u> 52, 529	Decrease
AVG. NUMBER OF MEN WORKING Surface, Underground, Total,	44 <u>1021</u> 146 2	43 <u>1181</u> 161 2	1	<u>16</u> 15

PRINCET	ON I	AINE
ANNUAL	RE	PORT
YEAR	19	15

5. LABOR & WAGES (Cont.)

b. Comparative Statement of Wages and Product (Cont.)

	1945	1944	Increase	Decrease
AVG. WAGES PER DAY				
Surface,	7.64	6.90	.74	
Underground,	9.23	8.18	1.05	
Total,	8.74	7.83	. 93	
AVG. WAGES PER MONTH OF 24 DAYS	and the agent			
Surface,	183,36	165.60	17.76	Section of the
Underground,	221.52	196.32	25.20	Alexandrate
Total,	209.76	187.44	22.32	
PRODUCT PER MAN PER DAY			and the second	
Surface,	20.02	18.25	1.77	
Underground,	8.98	6.68	2.30	Service and the
Total,	6.20	4.89	1.31	
LABOR COST PER TON				
Surface,	.382	.378	.004	
Underground,	1.028	1.225	State of the second	.197
Total,	1.410	1.603		.193
AVG. PRODUCT MINING				
Stoping,	256, 882	158,633	98, 249	
Ore Development,	12,159	57, 879	- manual -	45,720
Total,	269,041	216, 512	52, 529	
AVG. WAGES CONTRACT LABOR	9.99	8.97	1.02	
	Ŧ			
TUTAL NUMBER OF DEIS	12 4221	11.9663	1. 5708	
Duriade,	20,0551	32.408	1,0104	2.4531
Total,	43, 3924	44, 275		8824
ANOINT FOR LAROR				
Surface.	102.726.35	10.319.18	20. 810. 32	
Inderground.	276. 730. 56	265.176.35	11.554.21	
Total,	379, 456.89	347,092.36	32, 364.53	
PROPORTION OF SURFACE TO UNDERGR	OUND MEN			Santa J
1945. 1 to 2 35 - 2 9 hr	ahifta		and the second second	

1944, 1 to 2.75 - 2-8 hr. shifts

AVG. WAGES PER MO. BASED ON ME	N CARRIED ON MINE	PAYROLL		
Surface,	183.36	165.60	17.76	
Underground,	221.52	196.32	25.20	Size Land
To tal,	209.76	187.44	22.32	

5. LABOR & WAGES (Cont.)

LABOR

The working force available at the property was 10% less in 1945 as compared with the previous year. This situation, of course, resulted in an ultimate reduction of mining and development crews, and as mentioned previously, the long range effect has been to place the development status behind schedule.

6. SURFACE

a. Buildings, Repairs

Several improvements designed to improve efficiency and enhance the safety program were made at the No. 2 Shaft this past year. Steps to the skip blowing platform from the landing were installed to replace the dangerous ladder access previously used. The steps were later continued to the top sheave station which eliminates the necessity of a man crawling up the outside iron ladder which, in cold and sleety weather, is a distinct hazard.

At the pocket, a loading platform and steps were built, and additional lighting installed to make it possible for the pocket men to work in safety with increased efficiency.

In addition to these improvements, a tool and supply room was built on the landing to house portable equipment and supplies in a neat fashion, eliminating temporary loss of the equipment under heavy snow fall and providing quick access to frequently used supplies such as wooden spools, brackets and sheaves.

At the No. 3 Shaft locality, a fire lane was ploughed around the long banks of poles and lagging placed in a field of heavy grass which sets up a fire hazard in the dry months from the fact that it borders a state highway.

Much cooperation has been given the Princeton by the personnel of other Company properties on the range. Two specific surface improvements, a device to more efficiently oil hoisting ropes was demonstrated here by Athens mine supervisors and assistance given to produce a similar device in the Princeton shops. From the Cliffs Shaft mine several surface employees supervised the construction here of an A-frame to speed up construction of wooden stocking trestles.

b. Stockpiles

Removal of a rock outcrop in the southeast area of the No. 2 grounds by drilling, blasting and bull dezer work provided stocking space for approximately 100,000 additional tons of ore.

Bull dozer work on the stockpiles was continued throughout the year levelling the crests producing practically a uniform height of bank for shovel loading. Consequently, the shovel loading efficiency rose and 112,000 tons were shipped at a reduction of \$.02 per ton as compared to the previous year when this system was not employed.

The stocking and shipping was so planned this past year that a stockpile on both north and south sides of the shaft were shipped and two replacement trestles erected. This permits stocking with no interference with shovel loading and also provides separate trestles, with of course separate top tram cars, for use during the winter. Failure of a trestle or car, with this flexibility, does not suspend hoisting.

6. SURFACE (Cont.)

b. Stockpiles (Cont.)

An all steel top tram car was built in the Princeton shops early in the year to replace a car, originally from the Gardner-Mackinaw, which was completely worn out. The new car is slightly larger in capacity because of eliminating the thick wooden framework of the old type, and has given satisfadory service.

c. Trestles

The second and third trestles erected this year were built with an A-frame instead of the gin pole as heretofore used in this district. Instructions in the efficient and safe use of the frame were given Princeton men by Cliff-Shaft surface employees. Trestle erection has been considerably speeded up by this method.

Coal for steam-shovel use had been unloaded from cars by hand in the past at this property and had the effect of tying-up a crew of four or five several days. This inefficient set-up was eliminated by the construction at odd intervals during the year of a low coal dock at the end of the pocket track. The material used was scrap timbers recovered from old trestles. Unloading coal is now a matter of a few hours and the dock track now gives the added advantage of permitting five extra ore cars on the pocket track. Previously, pocket loading was suspended during a shift simply because no cars were available. The extra cars now serve to carry over during loading periods.

d. General

A new caving break through to the surface occurred during July at a point 550 feet south of the No. 2 Shaft off the end of the rock pile. The subsidence was on the nature of a circular section about 20 feet in diameter which dropped 25 feet forming a dirt pile, the sides of which, in three directions, sloped downwards into an open stope. Light smoke from the cave was determined to be the result of combustion of pyrites occurring in the jasper near the surface. No indication has been observed of any connection from the cave to the present open mine workings.

Because of this caving, however, it was necessary to bring in a new water supply line from the main a distance of approximately 800 feet to the No. 2 engine house.

Excavation of a surface drainage ditch was carried on intermittently during the year when either men or equipment was available. An attempt to curb the drainage of surface water to the general caving area overlying the No. 3 orebody by grouting was unsuccessful. The grouting was done in two churn drill holes that had been put down in 1944 to provide information on the drainage problem, but apparently the cement grout under pressure was finding release in one or more loose seams in the sandstone.

7. UNDERGROUND

Mining at the property consists of operations in two ore bodies distinct as to placement and also by the physical characteristics of the ore. Reference will be made in this report to the Nos. 2 and 3 separately and in that order. 370

7. UNDERGROUND (Cont.)

No. 2 Shaft

The No. 2 orebody lying between the 6th and 7th Levels as of the start of the year 1945 contained about 15,000 tons of mixed rubbly and plastic ore, mostly plastic type, at the north end immediately below 6th level elevation. The center and south portion had been stoped out, leaving pillars along the hanging wall side.

Mining of the north portion was economically unjustified because of several reasons, the chief predisposing factor being the drainage water. Operations in this area was therefore abandoned.

The hanging wall ore at the south and central areas were developed for stoping and mining carried on in balance with the progress of mining in the No. 3 area. When slicing or caving production dropped temporarily because of raise cutting or repairing, emphasis could be placed on stoping to maintain optimum activity in haulage and hoisting.

Periodic observation was maintained, however, on the north end and when it became apparent that the removal of the ore down the dip of the orebody to the south had caused a re-routing of much of the drainage water, another attempt at mining the north area was indicated. The timing of events was fortunate inasmuch as a general labor shortage coupled with the necessity of placing a large number of repair crews in the 7th Level No. 3 main drift had caused a serious lag in the development of working places in the No. 3 area. Raises and cross-cuts in the previously abandoned area were in generally good shape and mining was resumed with little delay.

Except for drift pillars along the 7100 cross-cut the south end of the No. 2 orebody is mined out. Crushing of the 7100 cross-cut occurred during the middle of the year presumably because of heavy caving from the worked out stopes higher up the dip, but it is planned to recover much of the drift pillar ore.

No. 2 Shaft

885' Sub-level

Section 20

Stoping Contract No. 4 mined a pillar of ore on this elevation from old workings on the east a distance of approximately 80 feet west toward the main cross-cut. Development Contract No. 5 brought up a single raise from the 6th Level drive to connect with a previously driven small drift to provide safe access to the stope.

867' Sub-level

Stoping Contract No. 4 recovered a supporting pillar of ore immediately above and on the footwall side of the 6th Level haulage drift. This mining on the south side of the straight drift from No. 2 Shaft was done in the latter part of the year. The contract had previously recovered similar supporting pillars on the north or No. 1 Shaft side of the straight drift approach. In both cases mining was accomplished by working from transfer drifts driven at top timber height from 6th Level haulage drifts.

7. UNDERGROUND (Cont.)

No. 2 Shaft (Cont.)

6th Level

Section 20

Stoping Contract No. 4, from the stub end of the straight drift southwest from No. 2 Shaft, mined two pillars north and south of the drift. Considerable lean ore and jasper was encountered against the arkose footwall which limited the extent of stoping work at this elevation.

Stoping Contract No. 10, working from Raise #721 on the 825' Sub-level, caved the supporting pillar surrounding this former timber transfer raise.

835' Sub-level

Section 19

Raise #7401, Contract No. 12, completed two slices southeast of the raise against the arkose footwall. Mining in this area, containing plastic ore, was seriously hampered by wide-spread in filtration of drainage water.

Stoping Contract No. 10, mining from Raise #7302, recovered a grade of ore intermediate in character between the plastic and rubbly types against the west ore contact. A lean transition jasper material below the true hanging wall caused high silica dilution in this stope. It was possible, however, to operate this stope because of the fact that a much larger tonnage of currently mined ore contained an extremely low silica analysis.

Stoping Contract No. 4, working from a transfer drift driven south from Raise #7301 on the 825' Sub-level, broke into a previously mined stope and recovered ore of excellent analysis in retreating to the raise.

Section 20

Raise #721, Stoping Contract No. 10, drove a timber drift east and upwards on the arkose footwall to make connection with the 6th Level former haulage drift. The contract mined this supporting pillar by stoping methods to within 20 feet of the raise and caved the major portion of the remaining ore to the 7th Level.

Stoping Contract No. 1, working from top timber elevation from the northwest extension of the 7100 cross-cut, mined a narrow pillar of ore which had been left from stoping operations in the previous year.

Raise #702A. Contract No. 9, attempted recovery of two small pillars of rubbly ore lying on the footwall northeast of the raise but the lean nature of the ore made this operation uneconomical.

825' Sub-level

Section 19

Raise #7302, Stoping Contract No. 10, drove two transfer drifts west from the raise and employed stoping methods to mine a rubbly type ore along the west

7. UNDERGROUND (Cont.)

No. 2 Shaft (Cont.)

825' Sub-level (Cont.)

boundary of the orebody. A third transfer drift was driven north from the raise at the end of the year in an attempt to recover a pillar of plastic ore on the 6th Level elevation by caving procedure.

Raise #7301, Stoping Contract No. 4, drove a small sized drift south from the raise 40 feet in arkose and extended the drift an additional 135 feet full sized in ore to the jasper hanging wall. Despite the great length of scrape, excellent recovery was obtained from this operation.

Section 20

Stoping Contract No. 1, working as previously described from the 7100 cross-cut, made excellent recovery of ore pillars left on this elevation from previous stoping work.

At the junction of the Nes. 2 and 3 erebedies, stoping Contract No. 11 mined the ore face in successive stages towards the south.

800' Sub-level

Section 20

Stoping Contract No. 1, mining from three successive top timber transfers over the 7100 cross-cut lying immediately underneath the jasper hanging wall, stoped a large area north and east to the arkose.

Raise #722, Stoping Contract No. 10, drove a small drift south through the footwall and mined a small stope along the arkose.

Raise #7103, Slicing Contract No. 9, caved a pillar of ore north of the raise.

Raise #702A, Stoping Contract No. 11, retreated the stope face to the south from small sized transfer drifts driven to the hanging wall.

785' Sub-level

Raise #720A was brought up to this elevation in arkose by Contract No. 1 and a small drift driven due west towards the 7100 cross-cut extension to recover mining equipment when severe and rapid crushing of the cross-cut made removal impossible at the time of crushing. The equipment was successfully recovered and also a considerable quantity of ore mined by the contract from the small drift.

Raise #7103, Stoping Contract No. 9, mined a small stope approximately 50 feet in cross-sectional area on the footwall side of the orebody. A stoping limit was set approximately 20 feet from the rib of the 7th Level drift to leave a protective pillar. This ore, of course, will be mined when the cross-cut can serve no further haulage purposes.

7. UNDERGROUND (Cont.)

No. 2 Shaft (Cont.)

7th Level

Section 19

The 7300 cross-cut was extended 70 feet southwest to obtain position for Raise #7302 and also to provide loading track.

Section 20

Raise #702A was put by Contract No. 1 from the south rib of the main level drift to recover equipment, as mentioned previously.

From the south rib of the 7100 cross-cut near the jasper contact, a timbered transfer drift was driven at a sharp degree downwards following the arkose footwall. The purpose of this work was to determine the extent of the ore below 7th Level elevation in the southeast tip of the No. 2 orebody. The drift was halted at a distance of 70 feet by the convergence of the foot and hanging wall. The small amount of ore remaining was then recovered by stoping from the exploratory drift.

Raises 702A and 704 were put up through the arkose footwall from the west rib of the main level drift to gain access to the ore at the junction of the Nos. 2 and 3 orebodies.

No. 3 Shaft

Mining in the comparatively large central area of the No. 3 orebody followed a pattern of top slicing or sub-level caving methods. The 6th Level had been left irregular in height because in places it was possible to mine the 6th sublevel by construction of scraper slides, but this procedure was inexpedient in other areas because of lack of tail track, and interference to main line haulage and in these latter cases, the pillars were mined from the raises at one sub-level above the 6th Level elevation. When progress of the 7th Level main footwall drift was sufficient, raises to the central area were immediately put up and cut out at one sub-level interval below 6th Level.

It is planned to extend the 7900 cross-cut to the south and west to get in position to mine the several sub-levels of ore left above the 6th Level in the extreme southwest wing. Mud and drainage water had forced abandonment of mining late in 1943. The 7900 cross-cut extension will provide position for top timber scraping drifts from which raises will be put up to this area; and the drift will also serve to explore, develop and mine the southwest ore area at 7th Level elevation and above.

7. UNDERGROUND (Cont.)

No. 3 Shaft

885' Sub-level

Section 20

Two small pillars at the fringes of previous slicing operations were recovered from 6th Level elevation.

875' Sub-level

Raise #701B, Contract No. 18, mined a 120 foot section of the orebody which, in this area, is of an elongated, extremely narrow shape. Mining in the central portion of the No. 3 orebody was done from raises brought up from the 7th Level elevation and which were cut out on the 835' Sub-level. The work consisted of redovering scattered pillars left from previous mining attempts from 6th Level elevation prior to the completion of the main 7th Level footwall drift.

6th Level

Raise #701A, Contract No. 18, working in the narrow north portion of the orebody, mined a narrow lense of ore approximately 80 feet long.

The central portion of the crebody was treated in a similar manner as described for the 875' Sub-level; with scattered ore pillars being recovered by caving methods from the 835' Sub-level.

Two small development projects were accomplished on the hanging wall side of the 6th Level and consisted of small sized drifts connecting to the 6th Level hanging wall drift for ventilation purposes.

835' Sub-level

Contracts No. 7 and 12 in the north off-set portion of the orebody, brought stoping work against old 6th Level workings from the 800 elevation.

Raise #701, Contract No. 18, completed mining of the north tip of the No. 3 orebody on this elevation by a combination of stoping and sub-level caving methods.

The central part of the No. 3 orebody was mined by top slicing and sub-level caving methods from Raises #709, 711, 715, and 717.

825' Sub-level

Exploration work at the supposed junctions of the Nos. 2 and 3 orebodies developed an ore area approximately 300 feet in length with an average width of 50 feet. This entire length of orebody was mined during the year by stoping methods employed by Contracts No. 7, 11 and 12.

Raise #701, Contract No. 18, mined the remaining one at the north tip of the orebody by top slicing and sub-level caving. A jasper horse of great extent has been encountered at the north end of the orebody which apparently segregates the plastic type ore from the rubbly ore, characteristic of the No. 2 body.

7. UNDERGROUND (Cont.)

No. 3 Shaft (Cont.)

825' Sub-level

Raise #7801, Contract No. 7, mined a small section of ore against the jasper horse west of the raise.

Raise #708, Contract No. 18, employing the sub-level caving method, mined the available ore on this sub-level north and east of the raise to the arkose footwall.

Raise #709, Contract No. 17, mined an area east of the raise to the arkose footwall during the latter part of the year. Considerable water drainage has been encountered in this area and failure of the raise by crushing resulted. Further mining from the raise was then suspended until access to this area could be obtained from scraping drifts to be driven at top timber height from the 7th Level cross-cuts.

At the south end of the orebody a small amount of mining was done from Raises #7901 and #715. In this area a thick cross-dike and two consecutive jasper intrusions were encountered which cut down considerably the ore area previously assumed for this area. Extraction was unavoidably complicated which resulted in a reduced mining efficiency in this locality.

800' Sub-level

Stoping Contracts No. 7 and 12 working from raises in the 7700 cross-cut north of the 7710 scraping drift, completed mining of the rubbly ore north of the large jasper intrusion.

Raise #7811, Contract No. 9, drove two connecting drifts at plus 817 elevation to raises 709 on the north and 7901A on the south.

Raise #7902, Contract 16, cut out the raise in the jasper hanging wall at plus 808 elevation and drove a small sized drift 40 feet west in an endeavor to collect drainage water coming from the hanging wall and divert it along the 7th Level footwall drift.

785' Sub-level

Top timber scraping drift 7710, which had been started in 1944 but discontinued at that time because of excess amounts of drainage water, was completed this year to a distance of 90 feet northwest from the 7700 cross-cut. Convergence of the arkose and jasper halted drifting at this distance. The scraping drift was then extended from the south rib of the cross-cut and in this direction was stopped at a distance of 70 feet by the large jasper horse cutting northeast-southwest through the No. 3 orebody. A second scraper drift over the 7700 cross-cut was completed by Contract No. 17.

At top timber height above the 7800 cross-cut, a scraping drift was driven by Contract No. 9. North of the cross-cut the drift was stopped by the jasper intrusion and the south extension was completed at a point directly above the main footwall drift. 376

7. UNDERGROUND (Cont.)

No. 3 Shaft (Cont.)

785' Sub-level (Cont.)

Raise #7901, Contract No. 3, drove a scraper drift northwest from the raise immediately above 7th Level elevation for a total length of 120 feet and put up Raise #7901A from the north rib of the transfer drift.

7th Level

Extension of the 7700 cross-cut southwest through the orebody was made during the year by Contract No. 10. An advance of 110 feet was made at this time. Drifting was halted by the influx of drainage water from the hanging wall. The drainage water was collected and piped across the orebody and discharged into the drainage ditches in the rock section of the cross-cut. Diamond drill hole No. 13 was then completed from the north rib of the cross-cut near the breast and apparently served to drain the hanging wall in this area. Continuance of drifting was then attempted and an additional 70 feet of cross-cut was accomplished turning to the south. However, the drainage water problem again became acute causing failure of the timber support in this stretch and a turnout was made into the hanging wall. It was planned to continue the cross-cut then in jasper to the south. The project, however, was suspended temporarily because of the lack of manpower.

An extension of 90 feet was made during the latter part of the year in the 7900 cross-cut. This drift was advanced to the south in arkose to provide access to ore in the extreme south wing of the orebody lying on and extending several sub-levels above the 6th Level.

At a point approximately midway between the orebody on 7th Level and the No. 3 supply shaft, a cut-out was made in the south rib of the 7th Level drift to provide a repair station for underground haulage motors and cars.

Extension of the main arkose footwall drift an additional 160 feet to the south early in the year provided the means of connecting the No. 3 Shaft with 7th Level operations.

Raise construction from the main level in the No. 3 area for the year included the completion of Raise #717 to 6th Level elevation; Raise #7702 a single compartment raise in rock to the 800' Sub-level; Raise #7903 a single compartment raise in the hanging wall for water drainage purposes and also three ore chutes from the level to top timber scraping transfer drifts.

PRINCET	ON	MINE	1
ANNUAL	RI	PORT	1
YEAR	19	945	

7. UNDERGROUND (Cont.)

d. Timbering

KIND	LINEAL FT.	AVG. PRICE PER FT.	AMOUNT 1945	AMOUNT 1944
6" x 8" Cribbing Timber,	14,044	.0500	\$ 772.45	\$ 2,703.03
8" x 10" Stull "	3,419	.0988	337.84	804.46
10"x 12" " "	22,491	.1273	2,863.79	4,294.79
12"x 14" " "	19,448	.1985	3,861.81	4,209.95
14"& Up " "	8,707	.2000	1,741.88	912.39
Total timber 1945,	68,109	.1406	\$ 9,577.77	
" " 1944,			and the second	\$12,924.62
		Per 100 Ft.	1	1.00
7' Lagging,	424, 533	1.3878	\$ 5,891.86	\$ 7,821.23
91' Poles,	263, 376	2.0872	5,497.30	7,885.30
Total 1945,	687,909		\$11, 389.16	
Total 1944,	A CARLES AND A CARLES	Congramme Cycle	The state of the s	\$15,706.53
GRAND TOTAL 1945.			\$20, 966, 93	A
GRAND TOTAL 1944,				\$28,631.15

Produ	act - Tons	269,041	216, 512
Feet	of Timber per ton of ore - Stulls & Cribbing,	.2531	.5722
	" Stull Timber only per ton of ore,	.2009	.3271
	" Lagging per ton of ore,	1.5779	2.6622
	" Poles per ton of ore,	.9789	1.7723
	" Wire Fencing per ton of ore,	· · · ·	-
	" Lagging per foot of timber,	6.2331	4.6525
	" Poles " " " "	3.8669	3.0973
Cost	per ton for timber,	.0356	.0597
	" " " Lagging,	.0219	.0361
	" " " Wire Fencing,		· · ·
	" " " Poles,	.0204	.0364
	" " " All Timber,	.0779	.1322
Equiv	valent of stull timber to board measure,	235, 661	307,761
Feet	of board measure per ton of ore,	.8759	1.4214

Total cost for Timber, Lagging, Poles, etc:

Year	Amount	Cost per Ton
1945,	\$20, 966.93	.0779
1944,	28, 631.15	.1322
1943,	26,408.73	.1162

7. UNDERGROUND (Cont.)

e. Drifting & Raising

Development work was carried on during the year in very close dovetailing with production, because of the fact that with eight to ten contracts working the loss of one or two from ore output to rock work resulted in a high percentage loss of product. In the few periods when the contracts were fully manned, the several extra miners were put on development work. This method, of course, was far from satisfactory and the actual procedure resolved itself into a sequence of a contract developing its own ore producing working place, mining the ore and developing another.

The development footages for the year are given below:

	Drif	ting	Rais	ing	
	Ore	Rock	Ore	Rock	Total
1945,	803	383	782	226	14902

f. Explosives, Drilling and Blasting

Explosive Statement - Year 1945 - Stoping, Slicing & Ore Development

Kind	Quantity Pounds	 Average Price	Amount 1945	Amount 1944
1 1/8" 45% Gelax #2 1 1/4" 60% Special Gelax 2 x 16 40% " "	90, 615 8, 059	\$ 11.50	\$ 10,420.80 926.79	\$ 9,034.74 42.00
Total Powder - 1945, Total Powder - 1944,	98, 674	\$ 11.50	\$ 11,347.59	\$ 9,076.74
Fuse - M /t. No. 6 Blasting Caps - M Ft.	345, 216 50, 024	5.15 12.50	1,777,90 610.30	1,727.87 600.29
Electric Blasting Caps - C Powder Bags - Large " " - Small	11	3.45	37.95-	.56 58.65 7.00
Tamping Bags - M Fuse Lighters- M	8,000	6.75	53.99	11.00 66.40
#14 Dupler Blasting Wire - M Ft. #20 Connecting Wire - M Ft. Master Fuse Lighters - M Ft.	210	2.62	.55	1.01
Miscellaneous Total Fuse, Caps, etc. 1945,		\$ 	\$ 2542.82	53.79
" " " " 1944, Total All explosives - 1945,			13, 890.41	2, 526.57
" " " <u>-</u> 1944,				11,603.31
Product - Tons	- a ;		269,041	216, 512
Pounds Powder per Ton of Ore Cost per Ton for Powder			.3667	.3647
Cost per ton for Fuse, Caps, etc.,			.0095	.0116

379

PRINCET	ON	MINE
ANNUAL	R	EPORT
YEAR	1	945

7. UNDERGROUND (Cont.)

f. Explosives, Drilling and Blasting (Cont.)

Rock Development & Filling	Quantity Pounds	Average Price	12	Amount 1945	Amount 1944
and a second		\$	\$		
1 1/8" 45% Gelax #2	-	-		\$	1, 381.39
1 1/4" 60% Special Gelax	7,173	11.50		824.92	
1 1/4" 80% " "	and the second	and the second			A A A A A A A A A A A A A A A A A A A
Total Powder - 1945,	7,173	\$ 11.50	\$	824.92	
" "				\$	2,192.02
Fuse - M ft.	26,600	5.15		136.98	309.43
No. 6 Blasting Caps - M ft.	3,800	12.20		46.35	107.22
Electric Blasting Caps - C	75	10.40		7.80	7.22
Powder Bags - Large	2	3.45		6.90	10.35
" " - Small	-	-		-	4.20
Tamping Bags - M	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	-		-	5.50
Fuse Lighters - M	1,500	6.75		10.14	23.63
Master Fuse Lighters - M				100	.91
Miscellaneous		-		6.59	41.10
Total Fuse, Caps, Etc 1945,	-		\$	214.76	
" " " " _ 1944,	LUND SHARES	and the second	a for a start	\$	509.56
Total all Explosives - 1945,				1,039,68	and the second second
" " - 1944,	- Contract on the			(1) National Antonio (1) National Antonio (1)	2,701.58
Total Explosives Used at Mine - 1	945,		\$1	4,930.09 \$	and the second second
	944.	1			14.304.89

i. Ventilation

Discussion of the ventilation for the mine in last year's report hinged mainly on the statement that as a positive source of fresh air the No. 1 Shaft was a poor risk. This shaft and immediate locality is the key to proper ventilation of the Princeton and from underground inspection in 1945 it was believed that the shaft had failed to function as a fresh air supply. To remove the reinforced concrete capping and entangled mass of timbers that had been dumped into the mouth of the shaft prior to the re-opening in what was an attempt to keep it from caving, entailed a great deal of labor and extreme care to maintain safe procedure.

Ultimately, observation of the shaft was possible from surface and the answer was seen in the fact that the shaft was blocked by fallen timber at a distance of 190 feet below the collar, or at a height of 70 feet above the 5th Level which was the highest opening into the mine. The 70 odd feet of debris was so tightly packed that standing water was present on the upper surface.

Tests made by introducing stench fluid into the limited flow of fresh air entering the mine through the surface cave adjacent to the No. 1 Shaft, indicated that an interval of over four hours elapsed until the air reached the 7th Level workings. Further, the stench laden air entered the 7th Level air stream through raises on the No. 3 side of the main level drift from No. 3 Shaft and did not enter the air current induced by the fan.

It will be necessary to provide a positive means of admitting fresh air to the mine as early as possible.

381

7. UNDERGROUND (Cont.)

k. Pumping

Excavation of the surface ditch to intercept surface drainage water overlying the No. 3 orebody was resumed early in the summer using a tractor and bulldozer borrowed from the Cliffs Shaft property. A great deal of the rough work was accomplished in a month and a half until the Cliffs Shaft called for the return of the unit. With the acquisition of a new tractor and bulldozer for the Princeton in the middle of the year it was possible to continue excavation, but the work was interrupted because of the fact that the use of the bulldozer was necessary in the handling of ore in stocking and loading.

At the close of the shipping season, labor was available and drilling and blasting in a 30 foot length of the ditch bettom through several water bearing seams was accomplished. It is hoped that actual pumping can be done in the spring.

A comparison of the gallons pumped and total cost by months for the years 1945 and 1944 is given below:

		Completion 1 and	Average	Mo. '44
	Average	Total	Gal/Min	Total
Mo. 1945	Gal/Min	Cost	Mo. '44	Cost
January,	165	\$1276.76	209	\$ 821.50
February,	171	906.16	195	908.87
March,	184	912.82	176	924.87
April	178	1483.29	202	1534.10
May,	283	2231.57	208	891.99
June,	286	1308.94	224	1027.29
July,	280	1515.96	199	927.90
August,	243	1479.05	211	921.90
September,	238	1287.71	198	1155.04
October,	227	1331.81	187	2068.72
November,	228	1178.91	200	1269.42
December,	242	1931.56	187	1534.10
Avg. for		1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		
year,	227	\$1403.79	198	\$1114.63

PRINCET	ON MINE
ANNUAL	REPORT
YEAR	1945

8. COST OF OPERATING

a. Mining Costs

	1945	1944	Increase	Decrease
Product	269,041	216, 512	52, 529	
Underground Costs	1.480	1.811		.331
Surface Costs	.309	.300	.009	
General Mine Accounts	.327	.337	a serie la sorre des	.010
Cost of Production	2.116	2.448		.332
Depreciation - Plant Account	.058	.050	.008	
Depreciation - Development	.001	.001		
Taxes	.040	.039	.001	and the second
Cost on Stockpile	.099	.090	.009	
Loading and Shipping	.075	.097	and an and the	.022
TOTAL COST ON CARS	2.290	2.635		.345
Number of Days Operating	299	.283	16	
Number of Shifts and Hours	2-8 hr.	2-8 hr.	and the second second	
Average Daily Product	900	765	76	
Cost of Production				
Tehor	1.458	1.682		. 244
Sumplies	.678	.766		.088
Total	2.116	2.448		.332

b. Detailed Cost

Days Per Week	6	5 & 51	
Shifts and Hours	2-8 hr.	2-8 hr.	and the second
Production, Tons	269,041	216, 512	52, 529
Average Daily Production, Tons	900	765	76
Number of Days Worked	299	283	16

PRINCET	ON	MIN	H
ANNUAL	RE	PORT	
YEAR	1	945	1.123

8. COST OF OPERATING (Cont.)

b. Detailed Cost (Cont.)

UNDERGROUND COSTS	1945		1944		Increase		Decrease	
	4	Per	· · · · · · · · ·	Per	1	Per		Per
	Amount	Ton	Amount	Ton	Amount	Ton	Amount	Ton
Exploring in Mine	7896.89	.029	5329.80	.025	2567.09	.004		
Sinking in Shaft	4900.86	.018	2686.09	.012	2214.77	1006		
Development in Rock	14783.22	.055	31942.19	.148			17158.97	.093
Development in Ore	8912.90	.033	56148.72	.259			47235.82	.226
Staning	134413.86	.500	80303.68	.371	54110.18	.129		
Timbering	85436.74	.318	86069.89	.397			633.15	.079
Reaming	61193.29	.227	59173.96	.275	2019.33			046
Vantilation	1050.49	.004	1665.08	.008			614.59	004
Dundag	19137 57	.045	10114.86	.047	2022.71			002
Company and Air Dimos	8131.57	.030	6044 95	028	2086.62	000		.002
Back Filling	0101-01		00110.30	.050		.002	AND COM	
Undergroudn Superintendence	9851.18	.037	12455.77	.058			2604.59	.021
Maint: Compressors & Power Dr:	1118 863.15	.003	448.34	.002	414.81	.001		
" Scrapers & Mech. Loade:	rs 25184.72	.094	18485.63	.085	6699.09	.009		
" Electric Tram Equip.	18816.10	.070	17919.25	.083	896.85			.013
" Pumping Machinery	4706.97	.017	3258.42	.015	1448.55	.002	and the second second	and the second
Total Underground Costs,	398279.51	1.480	392046.63	1.811	6232.88			.331
SURFACE COSTS				-				
Hoisting	20420.54	.076	17412.70	.081	3007.84			.005
Stocking Ore	25464.98	.095	18699.90	.086	6765.08	.009		
Dry House	7119.94	.026	6552.21	.030	567.73			.004
General Surface Expense	11218.06	.042	11624.82	.054			406.76	.012
Maint: Hoisting Equipment	5191.78	.019	4198.31	.019	993.47			
" Shaft	5078.98	.018	1781.60	.008	3297.38	.010		
" Top Tram Equipment	4194.24	.016	2341.84	.011	1852.40	.005		
" Docks, Trestles, Pocket	ts 278.67	.001	268.37	.001	10.30	1		
Mine Buildings	4291.30	.016	2172.36	.010	2118.94	.006	i sola i	
Total Surface Costs,	83258.49	.309	65052.11	.300	18206.38	.009		-
GENERAL MINE EXPENSE								
Employee's Vacation Pay,	11961.53	.045	6364.35	:029	5597.18	016		
Group Annuity Premium	403.72	.001	752.86	.003			349.14	.002
Insurance	1978.11	.007	1815.20	.008	162.91			.001
Mining Engineering	3300.50	.012	3803.86	.018			503.36	.006
Mech. & Elec. Engineering	852.33	.003	712.46	.003	139.87			· · · .
Analysis and Grading	9502.93	.035	8967.07	.041	535.86			.006
Personal Injury	14435.07	.054	9220.56	.043	5214.51	.011		
Safety Department	1058.16	.004	1005.73	.005	52.43			.001
Telephones & Safety Devices	2509.13	.009	2640.21	.012			131.08	.003
Local & General Welfare	1604.36	.006	1479.25	.007	125.11		ACREACE.	.001
Special Exp., Pensions, Allow.	4006.04	.015	3654.69	.017	351.35			.002
Ishpeming Office	10715.75	.040	9475.12	.044	1240.63			.004
Social Security Teres	8698.74	.032	8221.32	.038	477.42			.006
Mine Office	16864.73	.064	14888.42	.069	1976.31			.005
Total General Mine Ryn	87891.10	397	73001.10	337	14890.00	10 - P. C.	and where the second	.010
COST OF PRODUCTION	569429.10	2,116	530099 84	2.448	39329.26			.339
Taxas	10749.29	.040	8411.02	.039	2338.26	.007	and the second second	1006
Total Cost	580178.39	2.156	538510.84	2.487	41667 . 52	1001		.531
10001 0000	000110.00	NOTOO	000010.00	No 301				

PRINCET	ON MINI	9
ANNUAL	REPORT	ł
YEAR	1945	

8. COST OF OPERATING (Cont.)

b. Detailed Cost (Cont.)

	<u>19</u>	<u>145</u> <u>194</u>		144 Increa		se Decrease		ase
		Per		Per		Per	-	Per
	Amount	Ton	Amount	Ton	Amount	Ton	Amount	Ton
General Supplies	24405.62	.091	16888.50	.078	7517.12	.013		and i
Iron and Steel	4045.95	.015	5162.14	.024	and the second		1116.19	.009
Oil and Grease	2069.40	.008	1892.62	.009	176.78			.001
Machinery Supplies	6559.34	.024	4659.57	.022	1899.77	.002	a start	
Explosives	15475.38	.058	14523.68	.067	951.70			.009
Lumber and Timber	27475.98	.102	32727.17	.151			5251.19	.049
Fuel	3510.71	.013	3131.97	.014	378.74			.001
Electric Power	32520.22	.121	32050.44	.148	469.78			.027
Sundries	18869.30	.070	16751.98	.077	2117.32		and the second	.007
Other Mines and Accounts	486.18	.002	488.33	.002	2.15			
Supply Inv. Adi.	8.96		106.52	.001			97.56	.001
Total Cost per Cost Sheet,	134454.68	.500	127406.26	.589	7048.42			.089
Comparative Supply Balance								
General Supplies	6048.89		6610.48		-		561.59	
Iron & Steel	2065.39		1644.07		421.32			
011 & Grease	703.19		620.62		82.57	the state of	and the second	
Machinery Supplies	1129.96		1259.78				129.82	A second
Explosives	226.72		383.78				157.06	
Lumber & Timber	12575.13	alter to	24299.99				11724.86	
Fuel	1281.12		1381.82				100.70	
	24030.40		36200.54			The second	12170.14	

The fact that the year 1945 showed an increase of 52,529 tons over the 1944 production, which is a 24.2% gain, produced a net decrease in underground operating costs of \$.33 per ton for the year 1945.

Surface costs were not reduced in all accounts, several in fact showing increases. Only one item however, showed an increase as high as one cent per ton, that being the Shaft account. This increase was caused by the expenditures incurred in the excavation and construction of a new measuring pocket and storage trench on the 7th Level underground loading plat. The expense, however, is chargeable to "Shaft". Much of the surface improvement, including the erection of four stocking trestles, a new top tram car, coal dock, etc., were designed to effect a condition eapable of handling any peak in underground production, in contrast with prior years when delays were accasioned to hoisting simply because stocking facilities were inadequate. The cost of improvements were, of course, chargeable to surface accounts.

9. EXPLORATION AND FUTURE EXPLANATION

Diamond drill hole No. 13 was started from the north rib of the 7700 cross-cut near the northwest jasper contact of the No. 3 orebody. The hole was drilled on a course of South $66^{\circ}-06^{\circ}$ West at an inclination of $+6^{\circ}-45^{\circ}$. A total distance of 750 feet was traversed through the jasper with only insignificant seams of enrichment encountered. The hole was planned to test an area unexplored by surface drifting, and to determine if the shallow seam-like orebody possesed an upturn in the west extremity.

A higher valuation was placed on the property for the year 1945. The increase in taxes totalled \$2,338.26 which resulted in an increase of \$.001 in the cost per ton.

10. TAXES

					19	945	19	44
					Valuation	Taxes	Valuation	Taxes
NET of NET of	Sec. 1	9, 45-	.25					
C&NW Lea	se #29,			1			10,000	202.49
158.27 acres	in Sec.	18, 4	5-25,	1	80,000	2015.46	15,000	303.74
160 acres NW	of Sec	. 20,	45-25,	1			65,000	1316.20
Personal Prop	erty.				340,000	8565.69	320,000	6479.78
Total,					420,000	10581.15	410,000	8302.21
Collecti	ons fee	8,				105.81	the second second second	83.02
TOTAL TAL	XES,				£	10686.96		8385.23
Lot 3-NET of	SB1 18,	45-25		·7A,	350	8.82		
WE of SEL			80.	",	840	21.15		
NW1 of NET	19,	45-25	540.	#,	420	10.58	420	8.51
SWA of NEA		**	40.	",	420	10.58	420	8.51
SEA of NEA			40.	",	420	10.58	420	8.51
Total,					2,450	61.71	1,260	25.53
Collecti	on Fees				Assessment	.61	can a la characteria	.26
TOTAL TA	XES,					62.32		25.79
TOTAL PR	INCETON	MINE,			422,450	10749.28	411,260	8411.02
	and the second	And the second sec			and the second se			the second se

386

11. ACCIDENTS AND PERSONAL INJURY

More ore was produced by fewer men in 1945 than in the past and the results of the accident prevention program as shown in the following table were very encouraging. Of the seven compensable accidents, two were caused by mud being splashed in the eye, two were due to haulage mishaps, one caused by a substitute cage tender riding in the cage with tools; and two accidents in mining places caused by chunks falling with scraper ropes directly involved in the mishaps.

Statistical comparison of accidents for the past three years is given below:

	Days of Labor	Hours of Labor	Tons of Ore Mined	Number of Compensable Accidents	Fatal- ities	Days Lost	Frequency Rate	Severity Rate
945,	44614	356, 916	269,041	7	-	318	19.61	0.89
944,	457135	365,708	216, 512	11	-	652	30.08	1.78
943,	51503 ¹ / ₂	412,028	227,185	25	-	1558	60.61	3.78

15. POWER

The detail of Power used in 1945 and 1944 follows:

		Kilowatt	Kilowatt Hours Used				
	1945	1944	Increase	Decrease			
Hoist No. 2 Shaft,	273,400	207,890	65, 510				
	61, 320	45,680	15,640	1. A.			
Compressors,	805,200	966,100		160,900			
Haulage Set No. 1,	304,900	271,000	33,900	the state			
	258,170	193,190	64,980				
Pump No. 2 Shaft,	262,000	181,000	81,000				
Shops - Power,	8, 229	12,000		3,771			
Shops - Light,	7,042	6,725	317				
Lights and Signal System,	23, 369	20,707	2,662				
Top Tram,	14,300	68, 300		54,000			
Surface Diamond Drill (E&A CC)	156) 235	The second s	235	and the second			
Total,	2,018,165	1, 972, 592	45, 573				
In Cash,	\$ 32, 523.75	\$ 32,053.44	\$ 470.31				
Cost per KWH,	.0161	.0162		.0001			

6	71	0	14	y
6	3	C	Ι	1

PRINCET	ON	MI	NE
ANNUAL	R	IPO.	RT
YEAR	1	945	-line

18. NATIONALITY REPORT

As to Parentage	1945	\$	1944	1/2
Finnish.	53	35.8	54	35.1
Italian.	33	21.7	35	22.7
American.	22	14.4	24	15.6
Swedish.	12	7.9	12	7.8
French.	10	6.6	9	5.9
Norwegian.	10	6.6	8	5.2
English.	7	4.6	6	3.9
German.	2	1.2	2	1.3
Austrian.	1	.6	1	.6
Polish.	i	.6	1	.6
Irish.	North State	-	2	1.3
Total,	151	100.0	154	100.0

	Tot	al	Americ	an Born	Foreig	n Born
As to Birth	1945	1944	1945	1944	1945	1944
Finnish,	53	54	35	33	18	21
Italian,	33	35	20	20	13	15
American,	22	24	22	24	-	-
Swedish,	12	12	8 ·	8	4	4
French.	10	9	8	7	2	2
Norwegian,	10	8	7	5	3	3
English	7	6	6	5	1	1
German,	2	2	2	2	-	-
Austrian,	1	2 1	÷	-	1	1
Polish.	1	1	1	1	-	-
Irish,		2		2	19 - 10 C	
Total,	151	154	109	107	42	47

Percentages,

72.2 69.5

27.8

30.5

SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945

1. General

The production from the Virgil Lease was 29,371 tons and operations were abandoned in this property in September due to depletion of reserves. A substantial tonnage of reserves have been left in the Virgil Lease but this pillar of ore is unavailable due to the fire caused by exidation of the surrounding slate formation. Several attempts to mine the pillar have been unsuccessful because of the abnormally high temperatures encountered. In depleting the mineable reserves, operations were hindered by numerous delays arising from ventilation difficulties and caving from eld adjacent stopes and both of these factors account for the high cost of mining in 1945. Before operations were abandoned some additional diamond drilling was done to explore the area north of the Virgil deposit, but no ore was encountered and the program was discontinued after completing two holes.

Development in the Spies East Deposit has been the major program throughout the year and after mining was completed in the Virgil Lease, the entire labor force was concentrated on this work. A production of 7,636 tons was obtained from the development and preliminary mining. A serious water problem has been encountered in the new development and this has not only delayed the program but has created a pumping problem. At the close of the year, about 550 G.P.M. were draining from the orebody and the volume was gradually increasing as the development expanded. It became evident that a water drainage project must be instituted to enable mining to be conducted with a favorable cost. Late in the year, work was started on an underground drainage project and briefly, this will consist of raising to an elevation of 300° above the 4th Level and advance a drift along the east side of the orebody following the strike. A number of holes will be drilled from the drift across the formation above the orebody to intercept the water before it reaches the stopes at a lower elevation. The water will then be pumped directly to surface from the drift elevation through a pipe line installed in a churn drill hole.

A surface drilling program has been continued to further explore the Spies East Deposit and also an area in the NW1 of Section 24. Drilling in the latter area failed to disclose ore and consequently was discontinued. The drilling for extensions of the Spies East Deposit was not very encouraging but a continuation of this program is warranted on the basis of favorable structure and formation. The Johnson Lease was further explored by drilling from the 4th Level but no additional ore was discovered. On the basis of the drilling done on this property to date, the known reserves consist of the upper extension of the East Deposit and from an economic standpoint, this ore is unavailable due to its close proximity to ledge and the water bearing material overlying the ledge. In view of this, early consideration can be given to cancellation of the Johnson Lease. However, this action must await completion of a satisfactory drainage project.

Shipments from the mine were considerably less due to the smaller product. All the Hi-sulphur grade in stock was cleaned out before the close of the season and there was less than 4,000 tons of Virgil grade on hand at the end of the year. A token shipment of Spies ore was made from the pocket before the close of the shipping season. YEAR 1945

1. General (Cont.)

There was a shortage of labor about the middle of the year due to men quitting, but after "V-J" Day, the labor force was built to normal strength by hiring new men. Operation of the mine was continued on a schedule of five days per week until January 27th and then the schedule was increased to six days per week. The latter schedule was maintained to the end of the year, with mining conducted on 2-8 hour shifts per day and hoisting on 1-8 hour shift per day.

SPIES-VIRGIL MINE ANNUAL REPORT 389

In addition to the six regular holidays observed, a two-day national holiday was observed on August 15th and 16th in observance of "V-J" Day and there were no operations on December 24th. Vacations were allowed all eligible employees in August and these were arranged so the mine could operate on a one-shift basis during this two-week period.

In accordance with the new contract with the Union, a retroactive wage adjustment for shift differential and vacations was paid in December. In both cases, the adjustments were made retroactive to January 4th, 1944. The vacation adjustments were made on the basis of new eligibility requirements, namely one week vacation pay for employees with one year of service and two weeks for employees with five years or more. Effective August 21st, time and one-half was paid for work done on the 7th consecutive day in contrast to payment of double time for this work prior to this date.

Mining in the Virgil Lease consisted of recovering two supporting pillers between old stopes above the 8th Level and the bulk of the product from each of the areas was Virgil grade. One of the pillars was completely recovered early in the year and the product during the remaining months until September, was dependent on the mining in the remaining pillar. The product from the Spies East Deposit was mostly from the ore development but late in the year development had been completed so one stope could be started and a small tonnage was obtained from this operation in December.

2. PRODUCTION, SHIPMENTS AND INVENTORIES

a. Production by Grades

	1945	1944
Virgil	23,995	16,307
Virgil Hi-Sulphur	5,376	51,330
Total Virgil Lease	29,371	67,637
Spies	6,886	797
Spies Hi-Sulphur	750	and any constraint of the state of the
Grand Total	37,007	68,434

Production from the Virgil Lease decreased 38,266 tons due to depletion of mineable reserves. The product from the Spies East Deposit was obtained almost entirely from the ore development and a small amount was produced by the first stope operation.
SPI	ES-VI	RGIL MI	NE
A	NNUAL	REPORT	
	YEAR	1945	

2. PRODUCTION, SHIPMENTS AND INVENTORIES (Cont.)

h. Shinmante

Grade	Pocket	Stockpile	Total	Last Year
Virgil	18,282	54,492	52,774	21,274
Virgil Hi-Sulphur	Sugar to press the stand and	29,932	29,932	80,544
Total Virgil	18,282	64,424	82,706	101,818
Spies	367		367	
Total	19,649	64,424	83,073	101,818
Total Last Year	6,508	95,310	101,818	· AND S (POTTAGE) + CT - AL
Difference	13,141	30,886	18,745	and the second state

There was a material decrease in total shipments from the mine due to the smaller product. The shipments of Hi-Sulphur grade were considerably less due to the small production and small inventory of this grade in stock. Before the close of the shipping season all the Hi-Sulphur ore was loaded out and a prior year's stockpile over-run of 2,802 tons was realized. The Virgil grade shipments were larger than in 1944 because of the large inventory of prior year's stockpile over-run on hand. A total of 27,729 tons of Virgil grade over-run was loaded from the stockpile and a small balance of over-run remained on hand at the close of the year.

c. Stockpile Inventories

Grade	Tons
Virgil	
Spies	6,749
Spies Hi-Sulphur	1,317
Total	8.066

The stockpile inventory at the end of the year is one of the smallest in the history of the mine. The book figures of Virgil grade in stockpile have been wiped out but there is slightly less than 4,000 tons of additional over-run of this grade remaining on hand.

d. Division of Product by Levels

The product from the Virgil Lease, similarly as in the previous year, was mined between the 6th and 8th Levels and trammed on the latter level. In the Spies East Deposit all the development and initial mining was conducted above the 4th Level. 390

31,427

18,745

15,535

SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945

2. PRODUCTION, SHIPMENTS AND INVENTORIES (Cont.)

e. Production by Months

Month	Virgil Ore	Virgil Hi-Sulphur Ore	Spies Ore	Hi-Sul. Ore	Total Ore	Tons Per Man Per Day	Tons Rock
Jan.	2,218	597	148	363	3,326	3,02	1,280
Feb.	1,911	442	826	173	3,352	2.37	136
Mare	1,368	3,691	346	168	5,573	4.38	1,048
April	3,512	459	465	46	4,482	4.41	1,188
May	3,481	126	472		4,079	4.56	1,668
June	3,943	61	380	•	4,384	5,58	1,204
July	2,227		614		2,841	3.09	1,012
Aug.	2,010	•	509		2,519	3.03	908
Sept.	3,325		374	-	3,699	4.91	1,400
Oct.	0		753		753	#	804
Nov.	-	#	978		978		1,052
Dec.	anna i 🍎 🖉		1,021	Same Contained	1,021	Chan a star and share a star	840
Total	23,995	5,376	6,886	750	37,007	3,85	12,540

f. Ore Statement

	Virgil	Virgil <u>Hi-Sulphur</u>	Spies	Spies Hi-Sulphur	Total	Total Last Year
On Hand Jan, 1, 1945	1,050	21,754	797		23,601	56,985
Output for Year	23,995	5,376	6,886	750	37,007	68,434
Transfers	1,788	1,788	567	567		
Over-runs	27,729	2,802	a aya diga a 🗮 aya		30,531	en e
Total	54,562	28,144	7,116	1,317	91,139	125,419
Shipments	54,562	28,144	367		83,073	101,818
Balance on Hand	•	a a the second	6,749	1,517	8,066	23,601

Decrease in Output Decrease in Shipments Decrease in Ore on Hand

The operating schedule for the past five years follows:

1941 - 2-8 Hr. Shifts 5 days per week Jan. 1 to Dec. 31.

1942 - 2-8 Hr. Shifts 5 days per week Jan. 1 to Oct. 16. 2-8 Hr. Shifts 5¹/₂ days per week Oct. 17 to Dec. 31.

1943 - 2-8 Hr. Shifts 52 days per week Jan. 1 to Dec. 31.

 1944 - 2-8 Hr. Shifts 5¹/₂ days per week Jan. 1 to July 1.
2-8 Hr. Shifts mining and 1-8 Hr. Shift hoisting 5 days per week July 1 to Dec. 31.

1945 - 2-8 Hr. Shifts mining and 1-8 Hr. Shift hoisting 5 days per week Jan. 1 to Jan. 27. 2-8 Hr. Shifts mining and 1-8 Hr. Shift hoisting 6 days per week Jan. 27 to Dec. 31. ANNUAL REPORT YEAR 1945

2. PRODUCTION, SHIPMENTS AND INVENTORIES (Cont.)

g. Delays

There were three delays of significance that occurred during the year, two of which were of a major character. One of the major delays was caused by ventilation difficulties when operations in the Virgil property were still underway and this resulted in seriously delaying the completion of operations in this property. The other delay was caused by pumping difficulties arising from the break-down of one of the main pumps. In this case all work had to be abandoned in the Spies East Deposit when it became necessary to close the dam on the 4th Level to provide storage for the accumulated water until the repairs were completed. The delays are listed in detail as follows:

On March 31st a delay to operations occurred due to a break-down of a bearing on the compressor. Two operating shifts were lost while the repairs were made and the loss in product on this account was 200 tons.

On July 23rd operations in the Virgil property were suspended and the crew was transferred to work building brattices to control and direct the course of the ventilating air. The ventilation in this part of the mine was disrupted when caving above old stopes in inaccessible parts of the mine short-circuited the air through a fire area and resulted in high temperature air being exhausted through the Virgil shaft. To reestablish the old ventilating circuit and prevent air from reaching the fire area, it was necessary to construct a number of brattices on the 8th Level and subs above. This work was completed so operations could be resumed in the Virgil Lease on August 9th. The delay resulted in postponing for three weeks the date that operations in this property could be completed.

On October 27th the pump on the 3rd Level broke down and before the newly installed pump on the 6th Level could be put into satisfactory operation it became necessary to close the dam on the 4th Level to provide storage capacity for the accumulating water. Operations in the East Deposit were suspended on this account until November 5th, after the pump was put into steady operation and the water drained from behind the dam. One week of operations in the new deposit was lost on this account.

3. ANALYSIS

Average Mine Analysis on Output

The average analysis on the output from the Virgil Lease shows a slight increase in the iron content and a smaller sulphur content. The average analysis on the output from the Spies East Deposit improved considerably as compared to last year in both iron and sulphur content, both of which vary over a wide range because of the spotty nature of these elements in the ore. ANNUAL REPORT TEAR 1945

3. ANALYSIS (Cont.)

a. Average Mine Analysis on Output (Cont.)

Grade	Tons	Iron	Phos.	Silica	Sulphur
Virgil	23,995	59.03	.371	3.68	.069
Virgil Hi-Sul.	5,376	57.87	.362	3,38	.173
Spies	6,886	57.72	.259	6.21	.077
Spies Hi-Sul.	750	57.24	.287	5.95	.125

b. Analysis of Ore in Stock

Grade	Iron	Phos.	Sil.	Mang.	Alum.	Lime	Mag.	Sul.	Loss	Moist.
Spies Dried Spies Nat'l	57.48 51.24	.261	6.52 5.81	.19 .17	1.64	•58 •52	•26 •23	.093 .065	7.46 6.65	10,86
Hi-Sul. Dried Hi-Sul. Nat'l	57.23 51.52	.287	5.95	.19 .17	1.84	.60 .54	.21 .19	.125	7.80	9.98

c. Analysis of Shipments

Grade	Iron	Phos.	Sil.	Mang.	Alum.	Lime	Mag.	Sul.	Loss
Virgil	58,30	.366	4.64	.16	1.90	.47	,28	.072	7.98
Hi-Sulphur	56.75	.343	7.31	.15	1.90	.64	.25	.168	7.58
Spies	58.40	.284	5,26			1		.059	10.86

d. High-Sulphur Ore

In contrast to the previous year production of Hi-Sulphur ore constituted the smaller propertion of the total product. Mining in the Hi-Sulphur part of the orebody was completed in the previous year and the small amount produced in 1945 was obtained from the development and mining whenever the sulphur content increased beyond the limits established for the Virgil grade.

A small amount of Hi-Sulphur ore was produced by the development in the Spies East Deposit. The development in the new orebody suggests an average sulphur content ranging from .075% to.080% and it is very likely that one grade of ore can be produced within these sulphur limits after regular mining operations are started. 393

. ESTIMATE OF ORE RESERVES

a. Developed Ore

The following is an estimate of ore reserves made as of December 31, 1945 using a factor of 12 cubic feet per ton:

		Virgil Lease	
	Virgil	Hi-Sulphur	Total
Between 6th & 8th Levels Gross Tons	17,571	28,598	46,169
Less 10% foss for mining & rock	1,757	2,860	4,617
Net tons as of Dec. 31, 1945	15,814	25,738	41.552

The estimated reserves in the Virgil Lease consist of a number of supporting pillars between old stopes and from an economic standpoint, this ore is unavailable because the pillars are too small in size to be mined profitably. It was proven in 1945 that small size pillars between old stopes can not be recovered with favorable cost under present wage rates. The high development cost in proportion to the tons recovered and the limited productive capacity of small stopes are inherent factors incident to mining small areas. Another handicap to mining small pillars is caused by caving from adjacent rock filled stopes, resulting in dilution and small percentage of recovery.

	A CHARTER OF	Spies East Depos	It
	Spies	Johnson Lease	Total
Above 6th Level Gross Tons	1,447,552	208,750	1,656,302
Less December Production	1,021	•	1.021
Gross tons as of Dec. 31, 1945	1,446,531	208,750	1,655,281
Less 30% loss for pillars and		and the second	
nonavailable ore in Johnson Lease	434,266	208,750	643,016
Net tons as of Dec. 31, 1945	1,012,265		1,012,265

The estimate of reserves in the Spies East Deposit is based on the estimate made in the previous year and deducting the tonnage produced from the deposit in 1945. The outline of the orebody as determined by the development has disclosed no additional information that warrants a change in the estimate based on the diamond drill holes from surface. However, the water problem encountered in the development of this deposit has resulted in reducing the tonnage that will be mineable above the 4th Level. The proven ore in the Johnson Lease consists of the upper extension of the East Deposit and this apparently extends to ledge. The over-lying surface material above ledge is water bearing and test holes and diamond drill holes have proven a substantial thickness of course gravel containing a flat extensive water table. To mine the ore in the Johnson Lease would entail an elaborate surface drainage program but the tonnage of proven reserves is not sufficient to warrant this added cost. Further, the upper extension of the ore is narrow in width and lies at a relatively flat angle and would necessitate a higher than normal development cost. In view of the above factors, the ore in the Johnson Lease is considered economically unavailable and the estimated tonnage is taken as a deduction from the reserves in the Spies East Deposit.

4. ESTIMATE OF ORE RESERVES (Cont.)

a. Developed Ore (Cont.)

Another substantial deduction that is warranted is the tonnage of ore that will be left in supporting pillars to assure that mining in the East Deposit will not induce a cave extending to ledge and the water bearing material. Therefore it will be necessary to leave a series of pillars between the stopes and these will constitute about 30% of the estimated reserves. The tonnage not mineable because of the above factors results in substantially reducing the total reserves in the East Deposit as compared with the estimate of last year. There is a good possibility however that development to the south along the strike will disclose a substantial tonnage that presently is not included in the estimate.

Diamond drilling from both surface and underground has failed to disclose new extensions of the East Deposit. At the close of the year drilling was underway in one hole on the 4th Level and based on present knowledge of the structure, this hole will crosscut the iron formation at the 6th Level elevation.

b. Estimated Analysis of Ore Reserves

Grade	Iron	Phos.	Sil.	Mang.	Alum.	Lime	Mag.	Sul.	Loss	Moist
Virgil Dried	57,49	.360	7.51	.21	1,90	.58	.26	.081	7.54	
Virgil Nat'l	58,38	.328	6.83	.19	1.73	.53	.24	.074	6.86	9.00
Virgil Hi-Sul Dried	56.49	.360	8.00	.21	1.90	.60	.21	.300	7.25	1 1
Virgil Hi-Sul Nat'l	51,41	.328	7.28	.19	1.73	.55	.19	.273	6.60	9.00
Spies Dried	57.70	.295	6.00	.20	2.17	.25	.38	.080	6.70	1
Spies Nat'l	51.64	.264	5.37	.18	1.94	.22	.34	.072	6.00	10.50

5. LABOR AND WAGES

a. General

The general attitude of the employees has not been entirely satisfactory and this was brought about largely by the Union demand in the latter part of the year for an increase in wages. On November 28, the Union called a strike vote throughout the industry to support their demand for a \$2.00 per day increase in wages. Approximately 90% of the employees at the mine cast their vote for a majority of 5 to 1 in favor of the strike action. The date of the strike was set for January 14, 1946 but was later postponed to February 7, 1946.

5. LABOR AND WAGES (Cont.)

a. General (Cont.)

The labor turn-over was not quite as severe as in 1944. During a part of the year there was an acute shortage of labor but as the supply of labor increased the force was built to normal strength by hiring. There were 82 employees on the payroll at the end of the year compared with 74 at the end of 1944. A total of 14 employees quit, one was retired and one died. There were 82 men hired, resulting in a net increase of eight men on the payroll.

After operations in the Virgil Lease were completed, additional men were transferred to development work in the Spies East Deposit and the entire labor force was then concentrated on this work. The wet conditions in the new orebody account for a part of the labor turn-over to maintain the crew at full strength. Protective clothing is provided each man working in wet areas but good working conditions in the East Deposit and the best efficiency cannot be realized until a satisfactory water drainage project has been completed.

b. Statement of Wages and Prod	uct	5
--------------------------------	-----	---

PRODUCT NUMBER OF SHIFTS AND HOURS	1945 29,371 2-6	67,637 2-8
Average No. of Men Working		a la
Surface	13	20
Underground	18	32
Total	31	58
Averages Wages Per Day		
Surface	8,23	6,97
Undergrouhd	9.46	7.90
Total	8,95	7.55
Average Wages Per Month of 22 Days		
Surface	181.06	153.34
Underground	208.12	173.80
Total	196.90	166.10
Product per Man per Day		
Surface	9,39	12.11
Underground	6.53	7.44
Total	3,85	4.61
Labor Cost Per Ton		
Surface	.8766	.5759
Underground	1.4461	1.0615
Total	8,3827	1.6374
Average Product Breaking and Tramming	20.60	37,46
Average Wage Contract Miners	9.02	8.508

ANNUAL REPORT YEAR 1945

5. LABOR AND WAGES (Cont.)

b. Statement of Wages and Product (Cont.)	1945	1944
Total Number of Days Surface Underground Total	3128 44981 76262	5585 ¹ / ₂ 9084 ² / ₂ 14670 ⁴ / ₄
Amount for Labor Surface Underground Total	25,747.13 42,478.61 66,219,74	38,950.91 71,794.60 110,745.51

Proportion Surface to Underground Men

1945	1	to	1.38
1944	1	to	1.60
1943	1	to	1.78
1942	1	to	2.16
1941	1	to	2.12

6. SURFACE

a. Buildings

There was no new building construction and the repairs that were made were of a minor nature. All of the buildings except the engine house are obsolete and early consideration must be given to remodeling and replacement of several buildings when sufficient reserves have been proven to warrant it. In the coming year a new asphalt roofing will have to be placed on the engine house and it will be necessary to renew some of the rotted lumber sheeting on the roof before the roofing is laid.

Shortly before operations in the Virgil Lease were completed the fan was removed from the collar of the Virgil shaft and the small building that housed the fan was moved to the new ventilation shaft site. The building was reserved here and will temporarily serve as a dry house and storage building while shaft sinking is underway.

b. Stockpiles

The stockpile of Hi-Sulphur grade to the northwest of the shaft was all loaded out by shovel operations and the solar in this area was thoroughly cleaned by the bull-dozer before the last shipment was made. A small amount of Virgil grade remains in stock and the solar surrounding this pile has also been cleaned with the bull-dozer. No stocking trestle was erected in the area where the latter grades of ore have been stocked but after all the Virgil grade has been loaded out some trestle will be erected for stocking Spies grade.

6. SURFACE (Cont)

b. Stockpiles (Cont.)

Work was completed grading the stocking area directly north of the shaft. A portion of this area was graded in the previous year so that a small amount of trestle could be erected for stocking Spies are during the winter of 1944-45. The balance of the grading, and most of it, consisted of moving a large amount of rock from a nearby pile to obtain the desired width and a large amount of sand and gravel was moved from the solar to reach the desired grade. Upon completing the grading, 12 additional bents of trestle were erected, extending the original trestle farther north.

In the near future it will be necessary to rebuild the approaches to the treatles north of the shaft. The permanent part of the treatle is badly rotted and will need to be rebuilt before treatle is again erected in the area to the northwest of the shaft.

7. UNDERGROUND

a. Shaft Sinking

There was no shaft sinking done but preparations to start sinking the ventilation shaft near the Spies East Deposit were completed late in December. In the previous year, 95' of shaft with an inside diameter of 7' was sunk to the ledge and a 15" diameter churn drill hole was drilled from the bottom of the shaft to connect with a raise put up from the 4th Level. Brilling of the hole was started late in 1944 and completed in May, 1945. This work was done on a contract basis by the Layne Northwest Company. The balance of the shaft sinking will be done by stripping the bore hole. The broken material will be dropped through the 15" diameter hole to the 4th Level where it will be tranmed and hoisted to surface. It will be necessary to sink for a distance of 430' from the bottom of the present shaft to complete a connection to the top of the raise put up from the 4th Level.

The preliminary work for the shaft job consisted of installing air and water lines extending from the Spies shaft to the new shaft site. Also, 3,500' of transmission line was erected to provide power and lighting. The building that formerly housed the fan at the collar of the Virgil shaft was moved and rebuilt to serve as a dry house and storage shed while the work is underway. A churn drill rig has been loaned from the Company's Tilden Mine and will be used in conjunction with the shaft sinking operation. Concrete was poured around the steel casing for the entire depth of the shaft and a concrete collar was poured around the shaft at surface elevation.

b. Development

Development in the Spies East Deposit was the major program during the year and due to the extent of this work it will be described under the various sub level headings. ANNUAL REPORT YEAR 1945

7. UNDERGROUND (Cont.)

b. Development (Cont.)

4th Level

Late in the previous year the first crosscut was started branching to the northeast and this was continued in lean ore and jasper for a distance of 170' until slate was encountered. A short test drift was driven to the east and west to determine the width of the orebody and a width of only 10* of ore was proven along the east side adjacent to the slate. A test drift was also driven from the end of the crosscut and advanced to the southeast for a distance of 70°. This drift disclosed a width of 35° of ore near the Bates Boundary and also a sharp change in the strike which results in the the orebody crossing the east boundary into the Bates Mine property. No. 402 Raise was cut out about midway in the crosscut and advanced to a height of 25' in ore where it was cut out for a transfer drift. No. 410 Raise was put up in ore from the main drift to a similar height above the level and also cut out for a transfer drift. In the latter months of the year a short crosscut was driven to the southeast from the main jaulage drift west of the orebody for a distance of 170' in slate and a diamond drill station was cut out near the end of the drift. No. 420 Raise was cut out along the east side of the crosscut and advanced to a height of 20' above the level in slate. This raise is part of the rock development that will be done for ventilation above the 4th Level to connect the new ventilation shaft with the orebody.

A raise that will be connected to the small size shaft from surface for ventilation was put up from the northeast crosscut west of the orebody to a height of 95° in slate. This raise holed to the 15" diameter churn drill hole that was put down from surface and it will be used for handling the broken material when stripping of the bore hole is started.

Development on the 4th Level indicated the presence of a large amount of water within the orebody and the rock formation adjacent to the orebody. The water problem gradually became more serious as the development was carried to higher elevations and expanded laterally. It became evident that a means of controlling and draining the water from the mining areas would have to be provided before mining can be conducted with a favorable cost. An underground drainage project has been planned and in December work was started on this program under E & A CC-165. The project will consist of putting up a raise from the 4th Level in an ore pillar between two proposed stopes to a height of approximately 300* vertically above the 4th Level. At the latter elevation about 400' of drift will be driven to the north and south along the east side of the orebody and a number of large size diamond drill holes will be drilled across the formation to the east and west above an elevation to which mining will be conducted. The drill holes will serve to intercept a bulk of the water before it reaches mining areas at a lower elevation and by means of several automatically operated pumps installed in the drift the water will be pumped to surface through a discharge line in a churn drill hole. Work will be concentrated on this project so the balance of the development and future mining can be conducted under better working conditions.

7. UNDERGROUND (Cont.)

b. Development (Cont.)

1050' Sub Level

Upon completion of two raises to this elevation from the 4th Level drifting was conducted along the strike of the orebody for a distance of 520°. Transfer drifts were driven to the northeast from No. 402 Raise to the north limits of the ore and to the south from No. 410 Raise for a distance of 170° in ore. A test drift 50° in length was driven to the west from the latter transfer to determine the width of the orebody. A drift 220° in length was advanced to connect the raises and approximately half of this connecting drift was driven in jasper. The development and exploration outlined a narrow width to the orebody at the north end but more favorable width was proven in the most southerly development. Two mill raises were put up from the transfer at the north end of the deposit and each advanced to the jasper hanging which was encountered at a height of 75° in the most northerly mill and 160° in the other mill. A third mill raise was put up directly above the main raise and advanced to a height of 190° to the jasper hanging. The latter mill was started in the slate footwall and advanced in this material for a distance of 50° before it entered the ore.

SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945

Two mill raises were cut out along the east side of the transfer that connects No. 402 and No. 410 Raises. Both of the mill raises were advanced to a height of 190' above the transfer and the most southerly of the two mills was extended, later in the year, an additional 30' in ore to reach the highest elevation to which development was carried in the new deposit. Four mill raises were cut out in the transfer south of No. 410 Raise and the most southerly two mills advanced to a height of 75' in ore. In December, the most southerly mill was put up an additional 25' in ore.

Work in putting up the mill raises was done under difficult conditions due to the water that was encountered. It was often necessary to abandon work temporarily in advancing a mill until the adjacent mill reached a corresponding elevation and a connecting drift was driven between the mills. The worst water conditions have been experienced in putting up the two mills in the central part of the area that is being developed and this is due to the development in this area being conducted in advance of the other work.

1075' Sub Level

In the northerly part of the orebody a drift for sub level stope development was advanced for a distance of 250' along the strike to connect a series of five mill raises. About 70' of the drift was advanced in slate near the north end of the orebody and a small amount of jasper was encountered near the most southerly mill. The balance of the drift was in ore including 50' of test drift that was advanced to the west to explore the width of the orebody. In the development farthest south, 70' of small drift was advanced in ore to connect a series of three mill raises.

7. UNDERGROUND (Cont.)

b. Development (Cont.)

1100' Sub Level

A drift for sub level stope development was advanced for a distance of 350' in ore following along the strike of the deposit to connect a series of six mill raises. The drift extends from the north limits of the ore near the Bates boundary south to a mill put up directly above No. 410 Raise. In the most southerly development about 40' of small drift was advanced in ore to connect two mill raises.

SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945 401

1125' Sub Level

A total of 500° of small drift was advanced in ore following along the strike of the deposit and extending from the north limits of the ore south to the most southerly mill. A series of eight mill raises are connected by this drift. Test drifts were advanced to the east and west at various points to determine the width of the orebody and two short Gopher Drill holes were drilled near the north end to outline the orebody more completely.

1150' Sub Level

In the north half of the orebody that is being developed, a small drift for stope development was advanced for a distance of 220' in ore following along the strike to connect a series of four mill raises. From the most southerly mill about 50' of small drift was advanced to the west to explore the width of the deposit.

This is the highest elevation to which the development farthest south has reached and one mill was completed to this elevation by the end of the year. About 25' of small drift was advanced in one to the east and west from the mill to explore the width of ore.

1180' Sub Level

About 300° of small drift was advanced in ore for stope development to connect four mill raises. The drift extended from the north limits of the ore south along the strike to a mill put up directly above the main raise from the 4th Level.

1210' Sub Level

In the northerly part of the deposit about 220' of small drift was advanced in ore to connect a series of four mill raises. From the most southerly mill about 60' of small drift was advanced to the east and west to explore the width of the ore and with the exception of 30' of the drift to the east, the balance of the test drift was in jasper. A width of 30' of ore was disclosed at this point compared with 40' to 50' at lower elevations.

7. UNDERGROUND (Cont.)

b. Development (Cont.)

1240' Sub Level

About 160° of small drift was advanced along the strike to connect three mill raises and about 40° of the drift extending beyond the most northerly mill was in jasper and lean ore. From the latter mill, 40° of test drift was advanced to the east and west to explore the width of the orebody and with the exception of 20° of the drift to the west, the balance was in jasper.

1270' Sub Level

This is the highest elevation to which development had reached by the end of the year. One mill raise had been completed to this elevation and about 65' of drift was advanced to the east and west to explore the width of the orebody. This exploration disclosed a width of 60' of ore which is about the maximum width that has been proven by the exploration to date.

The following table shows a classification of the development footage in the Spies East Deposit under E&A CC-138 and E&A CC-116A:

	Drii	ting	ing Raising		Raising				
	Ore	Rock	Ore	Rock	Total				
Small Size	3,154*	26*	1,267*	62'	4,509'				
Large Size	362*	133*	30*	50*	595*				
Total	3,536'	159'	1,297'	112'	5,104'				

6th Level

Due to the large increase in mine water additional pumping capacity was needed and a 600 G.P.M. pump was purchased from the Oliver Mining Company and installed on the 6th Level. A large capacity sump was excavated along the northest side of the plat and a pump house was constructed at the north end near the shaft. Installation of the pump and excavating the sump was completed in November and the plant was put into operation. The pumping capacity was increased by 33-1/3% by the addition of this pump and the steady increase in mine water since its installation has necessitated quite steady operation of this unit.

The following table shows a classification of the rock development for the pump house and sump on the 6th Level under E&A CC-145:

Equivalent	Rock Dr	ift		-	-	-	-	-	-	-	514 .	
Small Rock	Raise				-	-	-		-	-	17'	
Total			2			18-2		95	-		531'	

402

7. UNDERGROUND (Cont.)

b. Development (Cont.)

In the Virgil Lease some development was done for the two stope operations that depleted the mineable reserves. Both of the stopes were developed in supporting pillars near the central part of the orebody above the 8th Level. The major part of the development for one of the stopes was completed in the previous year but additional development was required as mining progressed so the stope could be extended to the ore limits. Development for the stope in the largest pillar consisted of three mill raises that were put up to a height of 75' above the transfer and intermediate sub level drifts were driven to connect the mills. Some rock drift was also advanced to connect the stope with a nearby airway for ventilation.

The following table shows a classification of the development footage in the Virgil Lease:

	Drif	Drifting		Raising		
	Ore	Rock	Ore	Rock	Total	
Small Size	508*	50*	785 *	60*	1401*	
Large Size	56*	and the second			56*	
Total	564*	50*	783 '	60*	1457'	

c. Stoping

Spies East Deposit

In the Spies East Deposit the first stope operation was started in December at the north end of the deposit. Mining commenced from the most northerly mill and this was enlarged to about 15' in diameter to a height of about 50' above the transfer drift. Only a small product was produced by stoping before the end of the year. Due to a change in the strike of the orebody at the north end, a part of the orebody extends directly underneath a county road on surface that follows along the section line. On this account a pillar will be left to support the roadway and a mining limit has been established parallel to the east boundary of Section 24 at a distance of 33' east of the boundary.

Virgil Lease

Mining in the Virgil Lease was confined to the two stope operations that depleted the mineable reserves. Mining was completed in one of the stopes early in the year and the product during the balance of the year until September was obtained from one stope. Two contracts were employed in the Virgil property and the work was divided between developing and stoping.

The following is a detailed description of stoping operations in the Virgil Property:

Subs Above the 8th Level

In the central part of the deposit along the footwall side, an area 120' x 50' was mined by No. 3 Contract. This was the top sub level of the stope that was

- SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945
- 7. UNDERGROUND (Cont.)

c. Stoping(Cont.)

-50* Sub Level (Cont.)

developed in a relatively large supporting pillar and upon completing the mining in this stope, operations in the Virgil Lease were abandoned. Caving from old adjacent workings filled the stope with rock before all the pillar could be mined. Additional development would have been necessary to mine the small amount of remaining ore but the small tonnage did not warrant the cost of the development.

+25' Sub Level

An area 80' x 50' was mined by No. 3 Contract in the stope along the footwall side. Stoping was started at the west end of the pillar adjacent to the slate footwall and mining was retreated east to the traveling raise.

00' Sub Level

A smell amount of mining was done by No. 3 Contract at this elevation and an area about 55' x 20' was mined. Most of the development on this sub level was in lean ore and slate and consequently there was only a small amount of mineable ore at this elevation.

-50' Sub Level

In the south half of the orebody along the Sherwood boundary, an area 130' x 50' was mined by No. 6 Contract. This sub level which is directly under old workings was the top elevation of the stope in the second pillar that was mined.

-75' Sub Level

The transfer drift northeast of No. 832 Raise was advanced an additional 45° in ore to the north following along the Sherwood boundary. Three additional mills were cut out and put up to a height of 25° as development for the stope described in the preceding paragraph. 404

7. UNDERGROUND (Cont.)

d. Timbering

The consumption of timber was less due to completion of mining in the Virgil Lease. In the development for one of the stopes an extension to one of the transfer drifts was driven and this was the only development that required timbering. Some repairs were made in the timbered drifts on the 8th Level and one of the mining raises that was subjected to heavy crushing. Some repairs were also made on the 4th Level in a portion of the drift that has been maintained for ventilation. Late in the year, substantial increases were made in the price of timber, poles and lagging but the total expense for timbering was less because a smaller amount was used.

SPIES-VIRGIL MINE ANNUAL REPORT YEAR 1945

The following is a comparative timber statement for the past two years:

	Lineal	Avg. Price	Amount	Amount
Kind	Feet	Per Foot	1945	1944
6" to 8" Cribbing	2,030	.0580	117.89	116.22
8" to 10" Stull Timber	1,385	.0989	136.87	250.66
10" to 12" Stull Timber	1,007	.1285	129.41	194.38
Total Timber	4,422	.0868	384.17	561.26
7' Ceder Lagging	19,926	.0135	269.41	696.48
Poles	14.000	.0213	297.86	305.47
Total Lagging & Poles			567.27	1,001.95
Product			29,371	67,637
Feet of Timber Per Ton of On			.1505	.1025
Feet of Lagging Per Foot of	Timber		4.5061	8,6577
Cost Per Ton for Timber			.0131	.0083
Cost Per Ton for Lagging			.0092	.0103
Cost Per Ton for Poles			.0101	.0045
Cost Per Ton for Timber, Po.	.0324	.0231		
Equivalent of Stull Timber	to Board Mea	sure	6,484	10,254
Feet of Board Measure Per To	on of Ore		.2208	.1516
Cost of Timber, Lagging & Po	oles	a strange and the second	951.44	1,563.21

Most of the development, drifting and raising, in the Spies East Deposit required no timbering. A portion of the northeast crosscut that is in lean ore and jasper required timbering as did the transfer drift to the northeast from No. 402 Raise. The balance of the drift that was driven for transfer purposes is untimbered and with the exception of one mill raise that was advanced for some distance in footwall slate, all the stope development above the transfer elevation was done without timbering.

7. UNDERGROUND (Cont.)

d. Timbering (Cont.)

The following table shows the total cost for timbering under E&A CC-138:

6" to 8" Cribbing	2,030 Ft.	\$117.89
8" to 10" Stull Timber	710 *	69.40
10" to 12" Stull Timber	979 *	128.37
12" to 14" Stull Timber	418 *	71.14
Total	4,137 *	\$386,80
7' Cedar Lagging	19,926 Ft.	269.42
Poles	17,200 *	423.57
Total Lagging and Poles		692,99
Grand Total	an the second second second	\$1,079.79

e. Explosives, Drilling and Blasting

The cost per ton for explosives increased due to the large amount of development required in proportion to the tons recovered. The total explosives cost decreased nearly in the same proportion as the decrease in production.

The cost of explosives used in the development of the Spies East Deposit was considerably less than in the previous year because the development was mostly in ore in contrast to rock development in 1944. Electric blasting has been continued in all the development and good results have been obtained. The wet conditions in the development headings has made it advisable to continue electric blasting as it reduces the occurrence of miss-holes more so than if blasting with conventional fuse and caps. Another factor favoring the use of electric blasting is the smaller amount of smoke and gases that are produced and this is important from a ventilation standpoint.

Statement of Explosives Used

		Avera	ge	Amount	Amount
Ore Development & Stoping	Quantity	Pric	8	1945	1944
No. 1 Gelamite 60%	15,528	.115	O Lb.	1785,73	3610,20
Fuse (Feet)	33,682	5.15	M	173.41	426,35
No. 6 Blasting Caps	4,849	12.20	M	59.16	145,34
Hot Wire Lighters	1,963	6.70	M	13,15	27.68
Master Lighters		•			10.34
Powder Bags No. 1	7	1.40	Ea.	9.80	12.60
Tamping Bags	3,600	2.15	M	7.74	20.44
. Total Fuse, Caps. Etc.				263.26	642.75
Total Expense Breaking Ore				2048.99	4252.95
Production, Tons				29,371	67,637
Lbs. Powder Per Ton of Ore				.5287	.4641
Cost Per Ton for Powder				.0608	.0534
Cost Per Ton for All Explosives				.0697	.0629

7. UNDERGROUND (Cont.)

f. Explosives, Drilling and Blasting (Cont.)

Statement of Explosives Used (Cont.)

Rock Development

		Quantity	Price	1945	1944
No. 1 Gelamite 60%		673	.1150 lb.	17.40	307.51
Fuse (Feet)		2,848	5.1509 M.	14.67	56.65
No. 6 Blasting Caps		443	12.20 M.	5.40	17.42
Hot Wire Lighters		•			1.02
Powder Bags	4				2.80
Tamping Bags			and a statement of the statement of	and the second	. 2.22
Total Expense		THE PARTY OF THE P		97.47	387.62

E&A Development

No. 1 Gelamite 60%	42,959	.1150	16.	4940.24	8026.77
Fuse (Feet)	30,269	5.1509	Mo	155.69	105.83
No. 6 Blasting Caps	4,068	12.20	Mo	49.63	33,30
Electric Caps	16,085	11.9198		1917.31	1821.91
Hot Wire Lighters	755	6.70	M.	5.06	3.38
Powder Bags	13	1.40	Ea.	18,20	4.20
Tamping Bags	1,697	2.15	M.	3.65	.54
Tamping Shells	550	6.00	Mo	3.30	81.00
Duplex Wire					4.50
Connecting Wire	1,100	. 55¢	1b.	605.00	288.75
Total Fuse, Caps, etc.			141.00	2757,84	2343.41
Total Explosives E&A Development	Participant and and	in the second	15 Jan 1	7698.08	10370,18
Total All Explosives Used in Mine			100	9844.54	15010.75

g. Ventilation

Before mining operations in the Virgil Lease could be completed, ventilation difficulties arose and resulted in a serious delay to operations. The course of the ventilating air through old workings was changed by caving above old stopes in inexcessible parts of the mine, allowing the ventilating air to enter a fire area. It is apparent that caving extended to the old 1st Level of the Virgil Mine and this short circuit reduced the resistance to the flow of air through the mine and the total mine volume was more than doubled on this account. All the air was passing through an old fire area and exhausting through the Virgil shaft where a temperature of 160° was measured. To re-establish the old ventilating circuit, and seal the fire area, a number of brattices were constructed on the 8th Level and sub levels above. Upon completing this work, the volume of air was reduced to the desired amount and work was resumed in the mining places but due to the cave extending to the old 1st Level the ventilating circuit could not be re-established in this part of the mine and the fire area completely sealed off. To prevent damage to the fan it was removed from the collar of the Virgil shaft and the natural ventilation provided a sufficient volume of air to continue operations and deplete the mineable ore.

ANNUAL REPORT YEAR 1945

7. UNDERGROUND (Cont.)

g. Ventilation (Cont.)

After operations in the Virgil Lease were abandoned, concrete seals were constructed on each of the levels to completely seal off the Virgil workings. To ventilate the Spies development, a high pressure fan is employed to exhaust the air through the skip roads through a 14" diameter metal pipe which extends from the development headings in the orebody to the shaft. A plank casing seals the skip roads from the cage compartment so that the latter compartment serves as a down-cast for the air entering the mine. This system of ventilation has proved very satisfactory despite the fact that a volume of only 3,000 c.f.m. is being delivered. The new workings will be ventilated in this manner until completion of a small size ventilation shaft from surface.

8. COST OF OPERATING

a. Comparative Mining Costs

	1945	1944	Incr.	Decr.
Product	29,371	67,637	and the second	38, 266
Underground Costs	2.112	1.815	.297	
Surface Costs	.648	.583	.065	
General Mine Expense	.814	.654	.160	and the second
Cost of Production	3.574	3.052	.522	
Depreciation & Depletion	.918	.236	.676	
Taxes	.167	.157	.010	
Loading & Shipping	.245	.142	.103	and south las
Total Cost at Mine	4.898	3.587	1,311	
Budget Estimated Cost at Mine	4.281	3,028	1.253	
Number of Operating Days	215	273		58
Number of Shifts and Hours	and the second	150 1-8 Hr.		
	215 2-8 Hr.	123 2-8 Hr.		
Average Daily Product	136	282		146

8. COST OF OPERATING (Cont.)

	Detailed Cost Comparison	1	945	1944		
			Per		Per	
	Underground Costs	Amount	Ton	Amount	Ton	
1.	Exploring in Mine	3665.99	.125	8556.31	127	
3.	Development in Rock	495.81	.017	993.98	.015	
4.	Development in Ore	5053.48	178	13385.18	198	
5.	Stoning	17995.90	.618	51640-56	468	
8	Pimbering	6250.50	. 215	11013.85	165	
7	Thomas is	7745.07	284	14004.94	207	
	Wantil ation	9774 17	005	4900.07	069	
0.	Venetiación	AAOS DI	1.55	19590.97	105	
10	Funping	4290071	100	1000000	120	
10.	Compressors and Air Lines	4799.07	150	0491 45	190	
TE.	Underground Supt.	4402.10	2010	60.1.00	OLGO	
14.	Compressors and Power Drills	10.200	\$100	994.90	.010	
15.	Scrapers	812.80	.028	1214-14	°01a	
16.	Electric Tram Equipment	903.12	.031	3824.73	.057	
17.	Pumping Machinery	2188,25	075	2756.43	.041	
	Total Underground Costs	62040.23	2,112	122759.15	1,815	
	Surface Costs					
18.	Hoisting	5135.57	.175	9302.07	.138	
19.	Stocking Ore	1819.97	.062	4798.76	.071	
20.	Screening-Crushing at Mine	1532.67	.052	2682.64	.040	
21.	Dry House	3578.02	\$122	5588,15	.083	
22.	General Surface Expense	3066.04	.104	6167.00	.091	
23.	Hoisting Equipment	509,36	.017	2757.83	.041	
24.	Shaft	1584.06	.054	4071.59	.060	
25.	Top Tram Equipment	677.56	.023	2428.05	.036	
26.	Docks, Trestles & Pockets	107.24	.004	41.01	.000	
27.	Mine Buildings	1027.39	.035	1599.50	.023	
	Total Surface Costs	19037.88	•648	39430.60	.583	
	General Mine Expense					
28.	Insurance	888.85	.030	762.47	.011	
29.	Mining Engineering	927.29	.032	2262.42	.033	
30.	Mechanical & Electrical Engre	130.78	.004	230.48	.003	
31.	Analysis and Grading	1657.25	.056	3355.86	.050	
32.	Personal In jury	841.59	.028	12676.69	.188	
33.	Safety Department	389,91	.013	660.56	.010	
34.	Telephones and Safety Devices	531.03	.018	1012.95	.015	
35.	Local and General Welfare	653.91	.022	798.67	.012	
36	Special Ern. Pensons & Allow.	1600.91	.055	2099.33	.031	
37	Tehneming Office	1926.24	.066	3023.94	.045	
80	Social Security Ter	1582.52	.054	2729.33	.041	
	Funlawase Vesstian Day	6339.26	.216	4784.84	.070	
	Change the state of the state o	570.72	.019	825.88	.012	
-	Group Annul of Frentans	7540 55	257	9039.49	133	
34.	WING OILIGS	23915,63	.814	44856.85	.654	
	COOP OF DEALESTICAN	104993 94	3.574	206446.00	5-052	
-	Mara a	4900.00	.167	10647-61	157	
40	Matal Cost	100803.74	3.741	217094-21	3,209	
	Budget Estimated Cost		3,970	And the state of the	2.623	
	Transfer The ATTING AGA CAPA				and the second s	

ANNUAL REPORT YEAR 1945

8. COST OF OPERATING (Cont.)

b. Detailed Cost Comparison (Conto)

		19	45	1944		
		Amount	Per Ton	Amount	Per Ton	
41.	General Supplies	2546.84	.087	4344.43	.064	
42.	Iron and Steel	375.00	.013	800.58	.012	
43.	Oil and Grease	705,39	.084	1242.79	.018	
44.	Machinery Supplies	812.02	.028	4822.03	.071	
45.	Explosives	2189.03	.075	4400.98	.065	
46.	Lumber and Timber	1788.46	.061	1944.51	.029	
47.	Fuel	3486.50	.119	4305.55	.064	
48.	Electric Power	15186.67	.517	26364.11	.390	
49.	Sundries	13699.91	.466	17034.47	.252	
50.	Michigan State Tax	11.37	.000	9.92	.000	
	Supply Inv. Adjustment	9722.79	.331	6266.38	.093	
	Total per Cost Sheet	31078.40	1.059	59002.99	.872	

The following are explanations of cost accounts that show significant variations compared with the previous year:

1. Exploring in Mine

Decrease in expenditure is due to smaller drilling program which was completed early in the year.

4. Development in Ore

Decrease is due to smaller stope development program.

5. Stoping

The decrease in total expense is due to a smaller underground operation and the large increase in cost per ton is due to mining confined to recovery of small pillars. Labor cost also increased by payment of shift differential.

6. Timbering

7. Tramming

The total expense for these accounts is less due to smaller underground operation and large increase in cost per ton is due to small product.

8. Ventilation

The increase in cost per ton is due to constructing brattices to control the ventilation.

9. Pumping

The decrease is due to a large portion of this expense charged to E&A CC-138.

12. Underground Superintendence

The increase in cost per ton is due to payment of \$125.00 bonus to each foreman on monthly salary.

411

8. COST OF OPERATING (Cont.)

b. Detailed Cost Comparison (Cont.)

16. Maint: Electric Tram Equipment

The decrease is due to major part of the cost of repairs and overhauling charged to E&A CC-138.

17. Maint: Pumping Machinery

The large expense is due to the replacement of a broken pump casting with a new one.

18. Hoisting

Increase in cost per ton is due to small product and increase in labor cost due to payment of shift differential.

21. Dry House

The large expense is due to the increase in labor cost on account of payment of shift differential. There has been no decrease in this expense in the same proportion as in other accounts because full time operation of dry house facilities has been necessary.

22. General Surface Expense

The total expense was less due to small underground operation but the cost per ton increased due to small production and higher labor cost on account of payment of shift differential.

28 - 39 Inclusive

The total expenditures in these accounts with two exceptions were less because of the reduction in the size of the Virgil Lease operations and the higher cost per ton is due to the small product.

Employees vacation pay was considerably larger on account of payment of retroactive vacation adjustment.

40. Taxes

The decrease is due to smaller valuation and large proportion of taxes charged to Spies East Deposit development account.

9. EXPLORATIONS AND FUTURE EXPLORATIONS

a. Underground

Some additional drilling was done in the Virgil Lease before operations were abandoned in this property. Two holes were drilled to the north and northwest from the main level haulage drift on the 8th Level to further explore the area north of the Virgil orebody. No ore was encountered in the drilling and the program was abandoned early in the year.

Diamond drilling was done in the Spies East Deposit for the purpose of outlining the orebody and three short holes were drilled on subs above the 4th Level near the north end of the deposit. A relatively large amount of exploration has been done by drifting across the formation at various elevations and due to the narrow width of ore, this method has proven more economical than diamond drilling. However, when exploration involving longer distances is necessary, diamond drilling will be employed.

A drilling program under contract with the E. J. Longyear Company was conducted from the 4th Level to explore the Johnson Lease property. Three holes were drilled from the end of the 4th Level drift to the east and southeast but no ore was discovered in the drilling. Favorable runs of iron formation were encountered in each of the holes and in one of the holes a small amount of lean ore was penetrated. The program was abandoned before one of the holes was completed to the desired depth. A large volume of water was encountered in this hole and due to the serious water problem in the Spies East Deposit, it became advisable to stop drilling and seal the hole.

Late in the year, preparations were made to conduct additional drilling to explore the extension of the east deposit below the 4th Level. A drilling station was cut out near the end of the short southeast crosscut and the first inclined hole will be drilled from this point. Based on present knowledge of the structure, the hole will penetrate the iron formation at the 6th Level elevation.

The following is a log of the underground drilling in the Virgil Lease:

D.D.	H. No. 129	D.D.H. No. 130
8th Level	N34 E Dip 0º	8th Level Due North Dip 0°
0" - 598"	Grey Slate	0' - 77' Grey Slate
		77" - 563' Banded Grey Slate
		563' · 625' Dark Grey Slate

The following is a log of the underground drilling in the Spies East Deposit:

D.D.H. 1050' Sub - M	No. 14.	Ath Level S38	10. 15. 3°E Dip 0°
0" - 15"	Lean Ore	0* - 593*	Slate
15' - 132'	Jasper & Slate	593* - 650*	Oxidized Chert & Slate
132' - 161'	Slate	650' - 685'	Cherty Iron Form.
		685* - 690*	Jasper
		690* - 695*	Cherty Iron Form.
		695* - 700*	Lean Ore
		700* - 720*	Cherty Iron Form.
		720* - 725*	Lean Ore
		725' - 756'	Cherty Iron Form.

756" - 870"

Jasper

412

SPIESOVIE	RGIL MINE
ANNUAL	REPORT
YEAR	1945

9. EXPLORATIONS AND FUTURE EXPLORATIONS (Cont.)

a. Underground (Cont.)

D.D.H. No. 16.					
41	th	Level	Due East - Dip 0°		
0.		1077*	Slate		
1077*	-	1246*	Jasper Iron Forma		
1246'	-	1300*	Gray Slate		
1300*		1306*	Jasper Iron Form.		
1306*	-	1394*	Slate		

D.D.H.	No. 18.
4th Level S	68°E Dip 0°
0" - 543"	Slate
543' - 558'	Dike
558* - 700*	Gray Slate
700* - 710*	Black Slate
710* - 907*	Iron Carb. & Gray Slat
907* - 1259*	Dark Gray Slate
1259' - 1285'	Cherty Iron Carb.
1285' - 1292'	Jasper
1292' - 1305'	Gray Slate
1305* - 1383*	Jasper
1383' - 1393'	Gray Slate
1393' - 1513'	Jasper
1513* - 1575*	Grav Slate

		D.D.	H. No. 17.
112	5*	Sub	- N45°W Dip 00
0.	-	231	Jasper
231	-	271	Slate
271	-	571	Jasper Iron Form
571		621	Lean Ore
621	-	871	Slate
1000		- Call Con	and the second sec

	D.D.	H. No. 19.
1125'	Sub	Due West - Dip 0º
0	251	Ore
25' -	30*	Second Class Ore
301 -	44'	Jasper
44' -	65*	Gray Slate

b. Surface

A surface drilling program under contract with E. J. Longyear Company has been continued in Section 24. The results of this program have been very disappointing as no ore was encountered in any of the holes. A hole that was started the previous year in the SW1 of the section was completed and failed to disclose any extension to the Spies East Deposit. Another hole was started late in the year to explore the same area but considerable trouble was experienced in driving the casing to ledge and after three separate attempts had failed another location was selected.

Two test holes were drilled to ledge to determine the elevation of the water table above the Spies East Deposit. The holes are about 300° apart and they were drilled near the east boundary of the property directly above the orebody. In addition to these two holes, several old diamond drill holes in which the casing has been left permits measuring the ground water level and determining what effect if any, continued draining through underground workings may have on the water table.

Some drilling was also done in the NW1 of Section 24 to explore the favorable structure developed in the adjoining property to the west. Three holes were drilled in this area but no ore was discovered and the program was abandoned.

9. EXPLORATIONS AND FUTURE EXPLORATIONS (Cont.)

b. Surface (Cont.)

The following is a log of the surface drilling:

		D.D.	H. No. 71.			D.D.H.	No. 72.
	SE	- Sec.	24 - Dip 60°S.	NW2	Se	ac. 24	- Dip 90°
.0.	-	248'	Surface Material	0.		47*	Surface Material
248*	-	541'	Cherty Grey Sl. & Iron Carb.	47*	-	340*	Cherty Grey Slate
541*		643'	Slate & Iron Seams	340*		630*	Banded Grey Slate
643'		665'	Iron Formation	630*		8371	Slate & Greywacke
665*		899*	Dark Grey Slate	837 .	-	1068	Grey Slate
899"		1040*	Jasper & Iron Forme	890*		1027*	Cherty Iron Carb.
1040*		1045*	Chert & Grey Slate	1027*	-	1047*	Grey Slate
1045'		1089*	Dark Grev Slate	1047 *	-	1060*	Lean Ore
1089*	-	1123*	Chert	1060*	-	1322'	Grey Slate
1123'	-	1216'	Slate	1322*		1567'	Slate & Greywacke
				1567'		1611'	Cherty Iron Carb.
				1611*		1827'	Slate

D.H. No. 75.

DeDeE	L. NOO TO.	DeDen	NO. 100
NW1 Sec. 24	Due North Dip 70°	NW1 Sec. 24	Due North Dip 65°
0' - 42'	Surface Material	0' - 48'	Surface Material
42" - 55"	Black Slate	48' - 51'	Broken Ledge
551 - 751	Cherty Iron Carb.	51' - 124'	Dark Grey Slate
75' - 316'	Grey Slate	124' - 335'	Cherty Iron Carb.
316* - 893*	Grev Slate & Iron Carb.	335' - 485'	Grey Slate & Greywacke
and a sub-		4951 - 9451	Chanty Tron Cash & Sl.

D.D.H. No. 77. SE1 Sec. 24 Due South Dip 60° 0' - 216' Surface Material (Abandoned)

The following is a log of the water level test holes:

	D.D.I	I. No. 73.	D.D.H. No. 74.			
	Sec. 24	- Dip 90°	Sec. 24 - Dip 90			
0*	- 110'	Surface Material	0' - 143' Surface Material			
110*	- 113*	Broken Ledge	143' - 144' Slate Ledge			

10. TAXES

The following shows a comparison of taxes paid in 1945 and 1944 in Iron County:

		1945	1	944
Description	Valuation	Taxes	Valuation	Taxes
Iron County				
Iron River Township				
NE4 of NW4 of Sec. 24, 43-35 40A)				
SE4 OF NW4 of Sec. 24, 43-35 40A)				
Virgil Lease		and the second		
SW2 of NW2 of Sec. 24, 43-35 40A)	110,000	2,452.88	50,000	1,110.00
Stockpile, Supplies & Equipment	90,000	2,006.91	160,000	3,552,00
Total Spies Virgil	200,000	4,459,79	210,000	4,662.00
Spies Dwellings	3,000	66.90	7,500	166.50
Total Iron River Township	203,000	4.526.69	217,500	4,828.50
Rate		2,2299		2, 220
Village of Mineral Hills				
Spies Lease				
NEt of NW2 of Sec. 24, 43-35 40A)				
SEA of NWA of Sec. 24, 43-35 40A)				
Virgil Lease	and a first of a			- Andrews
SW1 of NW1 of Sec. 24, 43-35 40A)	110,000	481.07	50,000	216.87
Stockpile, Supplies & Equipment	90,000	393.60	160,000	693,98
Total Spies Virgil	200,000	874.67	210,000	910,85
Spies Dwellings	3,000	13.12	7,500	32.53
Total Village of Mineral Hills	203.000	887.79	217,500	943.38
Rate		4.373305		4.337
City of Iron River				
Spies-Johnson (East Deposit)				and the second second
SEt of NEt of Sec. 24, 43-35 40A)	107,500	3,848,50	70,000	2,516.50
NET of SET of Sec. 24, 43-35 40A	107,500	3,848.50	70,000	2,516.50
Mineral Lands				
NET of NET of Sec. 24, 43-55 40A	2,000	71.60	2,000	71.90
NWA of NEL of Sec. 24, 43-35 40A	1,600	57.28	1,600	57.52
NW1 of NW1 of Sec. 24, 43-35 40A	2,000.	71.60	2,000	71.90
NW1 of SE1 of Sec. 24, 43-35 40A	1,600	57.28	1,600	57.28
NET of SWI of Sec. 24, 43-35 254	1,400	50.12	1,400	22.55
(Except Carlson's Maple Valley Add.	1	1. al 1.	Street Store	
Lots in Carlson's Maple Valley Add.	1,025	36.90	375	6.43
Total	224,625	8,041.78	148,975	5,320.82
Collection Fees		80.40		53,21
Total City of Iron River		8,122,18		5,374,03
Paid in August 1945		4.537.43		2,973.44
Paid in January 1946	and the second second	3.584.75	The shares a second	2,400.59
Total	- des est disets	8,122,18	and the second	5,374.03
Tax Rate		3,580		3.595
Bates Township				N. C.
Spies East Depost t				
Mineral rights only:				
SWL of Sec. 19, 43-34	35.000	1.155.00		
Collection Fees		11.55		and the second
Total	a strange	1.166.55	a second second second	
- and -				

Note: Iron River Township & Village of Mineral Hills taxes are assessed on the same valuation.

11. ACCIDENTS AND PERSONAL INJURY

The accident frequency and severity rate improved considerably as compared with the previous year. There was one lost time accident which resulted in 59 days lost time. There was very little difference in the total man days worked; the total in 1945 was 22,446 compared with 22,810 in the previous year. The good accident record put the mine into first place among the Company's underground mines and the mine was awarded the safety banner for the coming year.

The following table shows a comparison of the accident severity and frequency rates for the past two years.

Frequency Rate		Severity Rate
1945	5.57	.329
1944	43.83	43.42

Frequency Rate - Number of accidents per 1,000,000 man hours. Severity Rate - Number of days lost per 1,000 man hours.

Accident No. 164 - April 9th, 1945. David Tarsi, Company Account Miner. While tamping fresh concrete that was being poured for a pump motor base, Tarsi suffered a strained back. Lost time - 59 days.

12. NEW CONSTRUCTION AND PROPOSED NEW CONSTRUCTION

There was no new building construction other than moving the small size building that housed the fan at the Virgil shaft to the new shaft site where it was recrected to serve as a dry house and storage shed. The most important new construction was the installation of a 2,300 volt transmission line that extends from the Spies shaft east to the ventilation shaft site near the Spies East Deposit. The line runs for its entire length of 3,500' on Company property and it was necessary to clear a large amount of brush and trees for the route. All the work except erecting the poles and hanging the lines was done with mine labor. The balance was let on contract to a transmission line crew that is employed with the Wisconsin, Michigan Power Company.

Air and water lines extending for the same distance and following the same route as the transmission line were laid to the ventilation shaft. A 2" water line was laid and approximately half of the air line was 4" diameter and the balance 2". Both of the lines were laid in a relatively shallow ditch that was excavated with the bull-dozer and back filled to prevent freezing.

Some stocking treatle was erected in the area where Spies ore is stocked north of the shaft. A total of 12 bents were erected extending the treatle farther north. No important new construction is contemplated for 1945.

13. EQUIPMENT AND PROPOSED EQUIPMENT

There was a large amount of additional new equipment purchased, most of which was charged to E&A's. The largest expenditure for new equipment was the new pump and accessories that was installed on the 6th Level to increase the mine pumping capacity. A large amount of new equipment such as scraper hoists, drill machines and electrical equipment and other accessories were purchased for use in connection with developing the Spies East Deposit for mining.

13. EQUIPMENT AND PROPOSED EQUIPMENT (Cont.)

Additional pumping equipment is on order for delivery in the coming year for use in the drainage project in the Spies East Deposit. Three centrifugal pumps, each having a capacity of 250 G.P.M. will be purchased and electrical accessories such as transformers, switches and other controls will be purchased. A large size churn drill hole will be drilled from surface to connect to the development for the drainage project at a depth of about 300' from surface and a discharge line and power line will be installed in the hole. A short extension will be erected to the new transmission line from the ventilation shaft to the churn drill hole and power for the pumping equipment will be obtained from this source.

The following is a list of the important items of new equipment added to the inventory:

Item	Number of Items	Cost	
10 KVA. Transformer	8	\$ 208.56	(8)
Unit Heater #35	m 4	252.48	(1)
Stoper - R-48	1	366.17	(1)
Gate Valve 10"	1	76.94	(1)
Toledo Hand Threader	1	98.77	(3)
Stoper - S-91	1	365,00	(1)
Aldrich Pump, 7" x 12"	1	5,206.35	(2)
Jack-Leg JL - 3	8	171.44	(1)
Vertical Hot Water Tank	1	141.35	
Water Heater	1	137.20	
Hot Water Circulator	1	30,66	
Jackhanmer, JA-55	1	215,92	(1)
Mang. Track Frogs	8	148.16	(1)
Armoured Shaft Cable - 1738'	1	1,791.88	(1)(2)
Temperature Regulator	1	69.51	
Cable - 3 Conductor	1	69.72	(2)
Subway Box - 4 way	1	291.60	(2)
Scraper Hoist I.R. 25 h.p.	1	1,823.89	(1)
Utility Hoist - HU	1	475.00	(1)
Double Drum Utility Hoist	. 1	603.00	(1)
Sludge Pump, C.P.	1	181.93	(1)
Transmission Line	1	158,22	-116-A
Prescott Pump Pot	8	2,306.00	
Scraper Hoist Drum	1	50.00	
Compressor Discharge Valves	6	309.93	the second
Leather Pump Belt	1	428,55	
Bullgrader Blade Edge	1	22.05	
Track Jack	1	24.66	(1)
Valve S&R	1	75.00	(1)
Oil Circuit Breaker Type F.G11	1	90.90	(1)
Column Arm & Clamp	8	103,90	(1)
Column Arm & Clamp	2 sharrod to FAL CC-138.	103.90	

New Equipment charged to E&A CC-138.
New Equipment charged to E&A CC-145.
New Equipment charged to E&A CC-133.

417

14. MAINTENANCE AND REPAIRS

a. Mine

The maintenance expense charged to operating decreased in proportion to the decrease in the size of the underground operation but a large proportion of the maintenance work was charged to the E&A's under which development of the new deposit is being done. One of the largest expenses for maintenance has been the pumping equipment which has been operating near full capacity due to the large increase in mine water. The pot castings on each of the 8th Level pumps broke and were replaced with new castings. After the second-hand pump that was purchased from the Oliver Mining Company was installed and placed in operation, a large amount of maintenance and some replacement of parts was necessary to maintain the pump in operating condition. Another large maintenance expense has been the discharge line in the shaft. Frequent leaks have broken out at various points along the length of the column, necessitating a large amount of work to maintain it in condition. The leaks have occurred mostly in the cast iron flanges and as leaks break out at these points the flanges are being removed and a welded connection made.

One underground locomotive that has seen many years of service in the Virgil operation was overhauled and put into good condition before it was put to use for tramming from the Spies East Deposit. The small size tram cars that were used in the Virgil operation are nearly completely worn out and several of these will be repaired and rebuilt from accumulated parts and will be used in cleaning the skip pit and track cleaning on the 4th Level.

Shaft maintenance has been less due to the small product that was hoisted. Regular inspections have been continued however and several worn out runners have been replaced in the skip roads and hardwood wearing strips fastened to the sides of the runners.

One of the top tram larry cars fell off the trestle when a fir stringer broke as the loaded car was passing over it. The car was not seriously damaged as it fell only a short distance and it was repaired and put back into service in a short time.

Some major repairs were made to the coal dock and these consisted of replacing a number of rotted fir stringers and cap pieces. Several rotted timber legs were also replaced and some new planking and guard railing was placed on top of the trestle.

B. Location

Nine cottages and the four-family apartment house were sold in 1945. One cottage and the captain's residence are the only two dwellings that were not sold. In each case the cottages were sold to the tenants who are employees at the mine. Eight of the cottages were sold for \$800.00 and one for \$875.00 and a discount of 10% was allowed in each case for a cash purchase. The apartment house was sold for \$2,500.00 with the same discount applied for a cash purchase.

Extensive exterior repairs were made to both the captain's house and the cottage that has been retained. Siding that was in poor condition was replaced with new material and some repairs made to the porches and sheds and then both houses were given two coats of paint. The two houses were put in good condition and attractive appearance and will require very little maintenance expense for a number of years. This work was let on contract to a local contractor.

14. MAINTENANCE AND REPAIRS (Cont.)

b. Location (Cont.)

MAINTENANCE EXPENSE		1045	AMOUNT	1944
	Labor	Supplies	Total	Total
Interior Decorating, Repairs				- v
and Painting Captain's House and Cottage No. 1.	194.98	538.86	733.84	315.37

15. There was a further increase in power consumption and this is due entirely to the , larger volume of water that was pumped. This resulted in a large increase in the cost per ton because of the small product. There were no delays to operations during the year due to lack of power which is purchased from the Wisconsin, Michigan Power Company.

Year	Average Maximum Demand	Rate Per K. W. H.	Total K. W. H.	Cost Per Ton
1945	498	\$.0130	2,349,980	\$.517
1944	470	.0137	2,013,233	.176

16. WATER SUPPLY

The water supply that is furnished by the Homer Mine has been satisfactory throughout the year. Water for underground drilling has continued to be obtained from the 3rd Level sump and this source has been very satisfactory for this purpose.

17. CONDITION OF PREMISES

The premises have been kept in neat condition by routine cleaning and in a similar manner, the premises around the location have been kept in good condition by the Village.

18. NATIONALITY OF EMPLOYEES

	American Born	Foreign Born	Total	Percent
English	10	8	18	22
Finnish	8	6	14	18
Swedish	. 9	0	9	11
Danes	3	0	3	4
Italian	4	7	11	14
Polish	5.	4	9	11
French	3	8	5	6
Austrian	0	8	2)	
Irish	5	0	3)	
Belgian	1	1	2)	
German	1	8	3)	14
Welsh	1	0	1)	
Lithuanian	1	0	1)	a statistical and
Total	49	32	81	100

THE CLEVELAND-CLIFFS IRON COMPANY OPERATING AGENT FOR CANISTEO MINING COMPANY CANISTEO MINE ANNUAL REPORT YEAR 1945

1. GENERAL:

Operations, involving stripping and the mining of ore, were continuous throughout the year. Employees were granted one day leaves on the holidays and there were about two days of enforced layoffs during the stripping periods, due to heavy snow storms. Working schedules of five days per week were carried during the first and last two months of the year, and six days per week during the intervening nine months.

Operating equipment was repaired when necessary and overhauled completely whenever units could be spered.

Washing plant repairs were continued from the first of the year to the beginning of the ore season, and started anew at the close of the ore season and carried on through the end of the year.

The stripping program in progress at the beginning of the year, on the north side of the pit, in the Mid-Snyder forty, was completed on April 13th, after which the equipment was moved to the pit bottom along the East Snyder and South Bovey line, where waste and lean material was removed until the end of the stripping program, on April 27th.

Subsequent to the 1945 ore season, stripping operations were resumed on October 15th, in the south side of the pit. The removal of paintrock and other lean formation was started on the pit bottom in the South Bovey forty while, simultaneously, excavations were conducted in developing a new approach up the south bank. By the middle of November, the equipment was moved up the new approach to push back the south limits of the South Bovey forty. This surface stripping program was in progress at the close of the year.

During the seven work days, from April 28th to May 5th, inclusive, a clean-up program was effected whereby slough and silt was removed to expose the underlying ore, and the sump area was improved, preparatory to ore operations.

Ore operations were started on May 7th, and continued through October 13th. A working schedule of two 8-hour shifts per day and six days per week was maintained until October 8th, when a single 8-hour shift per day became effective. Ore wes mined from all three leases, however, the amount taken from the Hemmens was confined to a small tonnage available above the sump level.

The washing plant was operated on the same schedule as that established for ore operations in the pit. The low weight recovery of the crude ore treated was reflected in production, nevertheless, the plant operated quite satisfactorily, as very few mechanical delays were encountered.

CANISTI	EO MINE
ANNUAL	REPORT
YEAR	1945

1. GENERAL: (continued)

Pumping was carried on continuously throughout the year from the water basin in the east end of the pit.

Exploratory and sample drilling was conducted throughout the year. Exploration holes were drilled in the Snyder and Bovey forties, on the north and south side of the pit, to justify stripping extensions in these directions, and sample drilling was subsequently done in the same forties to guide the ore operations.

2. PRODUCTION, SHIPMENTS & INVENTORIES:

duction by Grade

•	Treaterion by Grades.					
	Snyder Crude,	(121,000	tons		
	Bovey Crude,			3	67,562	"
	Hemmens Crude,				44,843	
	Total Crude Ore,			1,2	34,205	n
	Snyder Non-Bessemer C	oncentrates,		2	58,281	n
	Snyder Bessemer Concer	atrates,		1	76,997	n
	Bovey Non-Bessemer Con	ncentrates,			79.840	
	Bovey Bessemer Concen	trates,		1	22.081	
	Hemmens Non-Bessemer	Concentrates			17.933	
	Hemmens Bessemer Conce	entrates,			4,704	n
	Total Production - 19	45,		6	59,836	n
	Shipments:					
	Snyder Non-Bessemer Co	oncentrates.		1	93.052	
	Snyder Bessemer Concer	ntrates		1	76.997	
	Bovey Non-Bessemer Con	centrates.			79.840	
	Boyey Bessemer Concent	trates		1	22.081	=
	Hemmens Non-Bessemer (Concentrates.			17.933	
	Hemmens Bessemer Conce	entrates,			4,704	
	Total Shipments - 194	5,		5	94,607	n
	Stockpile Inventories:			·		
	Snyder Concentrates in	n Stockpile,	January 1,19	46,-	68,958	n
	Production by Months:	and the set of				
		SNYDER	BOVEY	HEMMENS		TOTAL
	(1) Crude Ore:					
	May,	128,601	32.573	41.257		202.431
	June,	179.444	84.024	_		263.468
	July	169.825	64.416	2.227		236.468
	August,	139,146	92.664	1,359		233,169
	September	138,905	93,885	-,,,,,		232,790
	October,	65,879		-		65,879
	TOTAL.	821.800	367.562	44,843	1.	234,205

CANISTEO N	INE
ANNUAL REP	PORT
YEAR 194	15
A CONTRACTOR OF A CONTRACTOR O	201

2. PRODUCTION, SHIPMENTS & INVENTORIES: (continued)

e. Production by Months: (continued)

SNYDER	BOVEY	HEMMENS	TOTAL
66,336	18,440	20,982	105,758
91,624	46,491		138,115
94,813	35,766	1,036	131,615
74,317	49,559	619	124,495
75,245	51,665		126,910
32,943			32,943
435,278	201,921	22,637	659,836
	SNYDER 66,336 91,624 94,813 74,317 75,245 32,943 435,278	SNYDER BOVEY 66,336 18,440 91,624 46,491 94,813 35,766 74,317 49,559 75,245 51,665 32,943 - 435,278 201,921	SNYDER BOVEY HEMMENS 66,336 18,440 20,982 91,624 46,491 - 94,813 35,766 1,036 74,317 49,559 619 75,245 51,665 - 32,943 - - 435,278 201,921 22,637

f. Ore Statement:

A balance of 3,729 tons of Snyder concentrates was shown in stockpile as of January 1, 1945. Stocking concentrates during periods of empty car shortage in the shipping season and for an additional eight shifts after the completion of the season's shipments, added 65,229 tons of concentrates, making a total of 68,958 tons in stockpile as of January 1, 1946.

g. Delays:

An accumulation of delays reported during the ore season amounted to 56 hours and 25 minutes, of which, ten hours and thirty-five minutes were power shortages caused by electrical storms. Mechanical and electrical failures on the shovels showed a total delay of 27 hours and 30 minutes, which had only a partial effect on production, as all shovels were never down for repairs at the same time. Delays of the washing plant amounted to 18 hours and 20 minutes, of which, about one-half were entailed by electrical and mechanical failures of the machinery, the remainder being due to plugged rock chutes, railroad yard plugged with loads, and such.

3. ANALYSIS:

a. Mine Analysis of Production:

Snudon N B	Tons	Iron	Phos.	sil.	Mang.	Alu.	Moist.	Fe.Nat.
Concts.	258,281	56.83	.071	11.01	.31	.58	8.12	52.22
Snyder Bess. Concts.	176,997	57.37	.037	10.86	.27	.58	8.14	52.70
Bovey N. B. Concts.	79,840	56.86	.064	11.57	.36	.59	7.91	52.36
Bovey Bess. Concts.	122,081	56.88	.036	11.53	.31	.55	7.94	52.36
Hemmens N.B. Concts.	17,933	57.58	.053	11.45	.45	.75	8.42	52.73
Hemmens Bess. Concts.	4,704	57.93	.039	11.31	.22	.82	8.41	53.07
TOTAL,	659,836	57.02	.054	11.15	.31	.58	8.08	52.41

CANIST	EO MINE
ANNUAL	REPORT
YEAR	1945

3. ANALYSIS: (Continued)

b.	Mine Analysis of	Shipment	s:						
		Tons	Ire	on Pho	s. Sil.	. Mang	. Alu.	Moist.	Fe.Nat.
-1-	Snyder N.B.					5			
	Concts.	193,052	56.	.91 .06	9 10.99	• • 33	.61	8.19	52.25
	Snyder Bess.	176 007		70 07	1 10 00		.0	9.14	50 70
	BOTET N B	110,771	21.	.57 .05	1 10.00	• • • • • •	• 20	0.14	22.10
	Concts.	79.840	56	86 .06	4 11.5	7 .36	.59	7.91	52.36
	Bovey Bess.	,,,					•	1	12.10
	Concts.	122,081	56.	.88 .03	6 11.53	3 .31	.55	7.94	52.36
	Hemmens N.B.								
	Concts.	17,933	57.	.58 .05	3 11.49	.45	.75	8.42	52.73
	Hemmens Bess.						0.0	0	
	CONCES.	4,704	51.	93 .03	9 11.31	.22	.02	8.41	53.07
	TOTAL,	594,607	57.	.06 .05	1 11.19	5 .31	.59	8.09	52.44
	Analysis of ma	in Stoolen	11			*			
••	Analysis of Ore	Tons	Tro	n Pho	s. Sil.	Mang	. Alu.	Moist.	Fe Nat.
	Snyder 1944.	3.729	55.	07 .03	8 12.23	.72	47	8.07	TooMade
	1945,	65,229	56.	60 .07	7 11.07	.26	.50	7.91	
15	Total,	68,958	56.	52 .07	5 11.13	.28	.50	7.92	52.04
a.,	Analysis of Crud	e Ore Pro	ductio	n.		· · · ·			
	Lease	Ton	8	Iron	Phos.	Silica			
	Snyder,	821,80	00	42.61	.046	33.28	and the		1. 5. 5.
	Bovey,	367,5	62	42.11	.043	34.24			
	Hemmens,	44,8	43	42.78	.044	34.26			
	Total,	1,234,20	05	42.47	.045	33.60			
e.	Complete Analysi	s of Seas	on's S	hipment	5:				
		Iron	Phos.	Sil.	Mang.	Alu.	Lime	Mag. Sul	. Loss
	Snyder N.B.								
	Conets.	56.91	.069	10.99	.33	.61	.27	.20 .01	1 5.92
	Snyder Bess.					-0	-0		
	CONCES.	57.57	.037	10.86	.27	.58	.28	.19 .01	1 5.58
	Bovey N.B.	56 86	064	11 57	76	50	06	18 01	
	Bovev Bess.	90.00	.004	11.21	. 20	• 27	.20	.10 .01	. 2042
	Concts.	56.88	.036	11.53	. 31	.55	.27	.17 .01	2 5.62
	Hemmens N.B.								- ///
	Concts.	57.58	.053	11.45	.45	.75	.28	.19 .01	2 4.22
	Hemmens Bess.					No.			
	Concts.	57.93	.039	11.31	.22	.82	.29	.18 .01	.2 4.15
									ŕ

CANISTEO MINE ANNUAL REPORT YEAR 1945

4. ESTIMATE OF ORE RESERVES:

30

n

a. Developed: Ore: Factors Used: All Leases:

Class of Material	Rock Deduction	Cu. Ft. Per Ton	% Recovery
Wash Ore,	10%	14	60%
Lean Wash Ore,	10% .	14	50%
Low Grade Wash Ore,	10%	15	60%
Lean Low Grade Wash Ore,	10%	15	50%
Rocky Wash Ore,	20%	14	60%

			RESERVE	MINED		DEVELOPED	RESERVE
	LEASE		JAN.1,1945	1945	BALANCE	BY DRILLING	JAN.1,1946
	Bovey:			1000	and the second second		
	St-NE-	Sec.30,	116,744	-	116,744		116,744
	NW-SE-	Sec.30,	235,100		235,100		235,100
	NE-SE-	Sec.30,	447,898		447,898		447,898
	NE-NE-	Sec.31,	622,633	201,921	420,712		420,712
	Total	Bovey,	1,422,375	201,921	1,220,454		1,220,454
	Hemmens:						
	SW-SW-	Sec.29,	1,560,790	22,637	1,538,153		1,538,153
	Snyder:					The second second	
1714	SE-SW-	Sec. 30,	1,091,685	-	1,091,685	-	1,091,685
	SW-SE-	Sec.30,	1,042,545	375,620	666,925		666, 925
	SE-SE-	Sec.30,	1,078,155	59,658	1,018,497		1,018,497
	Total	Snyder,	3,212,385	435,278	2,777,107		2,777,107
	GRAND	TOTAL,	6,195,550	659,836	5,535,714	-	5,535,714

c. Estimated Analyses: The following tabulation shows the estimated analyses of the reserve ore for the several leases:

Lease	Tons	Iron	Phos.	Sil.	Mang.	Alu.
Bovey:						
Bessemer Concs.	185,718	58.10	.033	9.47	.26	.46
Non-Bess.Concs.	1,034,736	56.76	.080	11.20	.29	.49
Hemmens:	4					
Bessemer Concs.	637.573	58.44	.034	9.87	.22	.52
Non-Bess.Concs.	900,580	56.78	.053	12.08	.27	.57
Snyder:						
Bessemer Concs.	1.075.979	60.68	.039	8.66	.20	.37
Non-Bess.Concs.	1,701,128	58.34	.060	10.25	.28	.45
Total Bess.Conc.	1,899,270	59.68	.037	9.16	.21	.43
Total Non-" "	3,636,444	57.50	.064	10.97	.28	.49
GRAND TOTAL,	5,535,714	58.25	.055	10.35	. 26	.47

CANISTEO MINE ANNUAL REPORT YEAR 1945

5. LABOR AND WAGES:

a. Comments:

The labor shortage prevailed throughout the year and, at times, was so acute that it was necessary to conduct the lean and waste ore operations on the third shift, with partial crews. With the return of some veterans, towards the end of the year, the situation was eased considerably.

In accordance with a directive order of the War Labor Board, adjustments in shift differential and vacation pay became effective during the year. The adjustments, retroactive to January 4th, of 1944, were granted in December and paid currently thereafter. Several petty grievances, presented by the union during the year, were readily settled to the satisfaction of labor and management. However, labor unrest and threats of strike reached acute stages at the close of 1945.

b. Comparative Statement of Wages and Product:

PRODUCTION:			
Direct Shipping,	1		
Concentrates Shipped,		594,607	tons
Concentrates in Stock 12-31-45,		65,229	11
Concentrates in Stock 12-31-44,		3,729	=
Total Production,		659,836	
Number of Days Operated,	2 2	134	
(128 days two 8-hour shifts;			
6 days one 8-hour shift)			- *
Average Daily Product,	1. 1	4,942	
Average Wages Paid Per Day,		8.03	
Amount paid for Labor,		\$ 137,605.13	

6. SURFACE:

a. Buildings, Repairs:

Aside from two small shelter shacks for dumpmen, there was nothing but ordinary maintenance work on mine buildings and dwellings during the year.

c. Roads, Transmission Lines, etc:

About 1,600 feet of road was built in the development of a new approach up the south bank of the pit. The lower 400 feet of the road was developed by rock-filling a mined out area of the pit bottom, the intermediate 700 feet by excavation through lean formation, and the upper 500 feet by cleaning up slough along the toe of the old surface slope.

Two power poles, with about 500 feet of transmission line, were removed and replaced in the North Bovey part of the pit to facilitate some ore-scramming operations in the old pit bottom.
CANIST	SO	MI	NE
INNUAL	RI	EPO	RT
YEAR	19	945	-

7. OPEN PIT:

a. Stripping:

The stripping operations during 1945 were conducted on the north side of the Mid-Snyder forty, extending the pit limits in the vicinity of the old approach; in the pit bottom on the south side, in the East Snyder and South Bovey forties, and in the south bank of the pit; extending the pit limits southward in the Two 3-1/4-yard electric shovels and seven South Bovey lease. to nine 15 and 20-ton rear-dump trucks were used during the greater However, this was cut to one shovel and six part of the season. to seven trucks during the short time allowed for shovel repairs. In January, November and December, the work was all conducted on a 40-hour per week basis, three 8-hour shifts per day and five days per week. During the balance of the year, the basis was 48 hours per week, or three 8-hour shifts per day and six days per week. A total of 965,545 cubic yards of surface and waste and lean ore materials was removed in 192 days. This did not include 30.755 cubic yards of clean-up work in the pit bottom, just previous to the ore season, and charged to ore operations. In view of the pit operating conditions and of the fact that the equipment had not had a thorough overhauling for several years, satisfactory stripping costs were secured.

The pit extension in the north side of the Mid-Snyder forty, which was started in December, 1944, was carried forward from the Two shovels were used until first of the year until April 13th. March 12th, when one was taken to the shop for some badly needed The work in this area was then completed with one shovel. repairs. The material was hauled to the stripping dump on the North Bovey, a short distance north of the concentrating plant. Operating conditions were tough, for a heavy layer of blue clay, spotted with water pockets, was encountered immediately under the sand and gravel Haulage conditions in the newly-stripped area of the upper lift. were soft and slippery, and considerable difficulty was encountered in handling the wet material in both the shovel bucket and truck boxes during freezing weather. In addition, there were numerous shovel delays, due to working in tough frost conditions, with shovels badly in need of repair. Approximately 4,000 tons of low grade painty merch. ore were taken from a thin layer in the paintrock horizon and stocked near the washing plant. A total of 289,926 cubic yards of surface and 193,795 cubic yards of waste ore material was hauled to the north dump. In addition, 38,485 tubic yards of lean ore were hauled to the lean ore dump in the pit, making a total of 520,206 cubic yards of stripping removed from the area during the year.

On completion of the work in the North Snyder, the shovel was moved to the pit bottom, where up until April 27th, 57,196 cubic yards of lean and waste material were removed and hauled to the proper dump in the pit. This developed underlying ore areas and completed



7. OPEN PIT:

a. Stripping: (continued)

a water channel for pit drainage in that area. 20,300 cubic yards of waste ore material and 6,216 yards of lean ore were taken from the south side of the East Snyder and 12,270 cubic yards of waste and 18,410 yards of lean ore from the north side of the South Bovey. With but one shovel in operation and wet haulage conditions, the progress was slow.

Clean-up operations in the pit bottom were then conducted for a week, just previous to the ore season, and 30,755 cubic yards of waste and lean ore material were removed from the South Bovey and East Snyder bottoms. Of this amount, 1,278 cubic yards of lean ore were taken from the former, 17,551 yards of waste material and 7,371 yards of lean ore from the latter.

Upon completion of the ore program, stripping was resumed October 15th, on a 3 shift, 6 day per week basis, until November 1st, when a 4C-hour per week basis was put into effect on all the Mesaba Range properties operated by the company. Two shovels and eight trucks were used in removing waste and lean ore materials to develop underlying ore in the East Snyder and South Bovey pit bottoms, and in building an approach to the surface stripping operations in the south bank. The approach was completed on November 12th, and one shovel was moved up to develop the surface stripping The second shovel continued in the pit bottom until operations. November 24th, when it likewise was moved up to the south bank. 174,209 cubic yards of material were removed from the area. This consisted of 102,099 cubic yards of waste and 61,493 yards of lean ore from the South Bovey; 7,492 yards of waste material and 3,125 yards of lean ore from the East Snyder. This material was all taken to the proper dump in the pit.

The surface stripping operation carried forward from November 12th to the end of the year, was an extension of the pit limits in the southwest side of the South Bovey. This carried the stripping to the ultimate pit limits in this area. The work was conducted with two shovels and eight or nine trucks, on a 40-hour per week basis, three 8-hour shifts per day and five days per week. Digging was tough, working conditions cramped in a restricted area, and it was necessary to use a 10% grade out of the pit. However, despite these conditions, and numerous shovel breakdowns, good progress was made and 213,934 cubic yards of surface material were removed and hauled to the south dump.

The following tabulation show, by leases, the yardages of the various materials stripped during 1945 at the Canisteo Mine:

CANIST	EO	MINE	
ANNUAL	R	EPORT	
YEAR	19	945	

7. OPEN PIT:

a. Stripping: (Continued)

LEASE	SURFACE	WASTE	LEAN ORE	TOTAL
Snyder,	289,926	221,587	45,826	557,339
Bovey,	213,934	114,369	79,903	408,206
Total (Cu.Yds.)	503,860	335,956	125,729	965,545

f. Explosives, Drilling and Blasting:

Statement of Explosives Used:

ORE OPERATIONS: 25% duPont Quarry Gel. 5 x 16 40% duPont R. C. Extra 5 x 14	QUANTITY 66,400# 56,250#	PRICE \$10.00 10.00	AMOUNT \$6,640.00 5,625.00
Total and Average,	122,650#	\$10.00	\$12,265.00
Plain Primacord,	30,0001	32.00	960.00
Total Caps, Fuse, etc.			\$ 960.00
TOTAL ORE OPERATIONS,			\$13,225.00
STRIPPING OPERATIONS.			
25% duPont Quarry Gel. 5 x 16	65.350#	10.00	\$ 6.535.00
40% duPont R.C. Extra 5 x 14	61,250#	10.00	6.125.00
No. 4 Bag Powder,	1,000#	10.00	100.00
Total and Average,	127,600#	10.00	\$12,760.00
No.14 Leading Wire,	7501	18.00	13.50
Plain Primacord,	57,500 *	32.00	1,840.00
Total Caps, Fuse, etc.	and the state of the state		\$ 1,853.50
TOTAL STRIPPING OPERATIONS,			\$14,613.50
GRAND TOTAL EXPLOSIVES, 1945,			\$27,838.50

g. Open pit Mining and Loading:

Ore production was started in the pit on May 7th, and continued through October 13th. Shipments were completed on September 26th and, thereafter, the concentrates were placed on stockpile. Ore operations, throughout the period, were conducted on a 6-day per week basis and two 8-hour shifts per day, except during the last week, when production was curtailed to a single 8-hour shift per day. A total of 1,234,205 tons of crude ore was mined and washed, to produce 659,836 tons of concentrates, showing an average weight recovery of 53.46%. The low recovery resulted from large proportions

7. OPEN PIT: (continued)

g. Open Pit Mining and Loading: (continued)

of limonitic ores absorbed in the mixture to counteract the high silica of the hematite ores. Two shovels were operated simultaneously for mixing ores at varying proportions, to meet the grading requirements. In addition to the two 3-1/4-yard Canisteo shovels, a 2-yard Marion was rented from the Mesaba-Cliffs. The spare shovel simplified grading problems in providing a third source of ore, and minimized shovel moving, with a resulting increase in efficiency.

To facilitate ore operations, a small crew made shovel moves and sorted and removed lean and waste materials from the working areas on the third shift. Due to the manpower shortage, it was necessary to eliminate this operation for a two weeks period, in August.

Mining operations were conducted in the North and South Bovey forties, in the East and Mid-Snyder forties and in the west end of the Hemmens. In addition, about 85,000 tons of concentrates were secured from the Bovey and Snyder lean ore stockpiles in the pit. Here, the upper layers were mined off to remove crude ore which had some natural concentration, as the blocky materials rolled to the bottom of the pile, leaving the higher grade fines at the top of The 435,279 tons of Snyder concentrates produced dureach lift. ing the season consisted of 17,000 tons taken from the lean ore pile and the remainder mined in about equal proportions from the East and Mid-Snyder forties. In the Bovey, 68,000 tons of concentrates were secured from the lean ore pile, 128,629 tons from the South Bovey and 5, 292 tons from a scram operation in the bottom of the North Bovey pit.

In the Snyder operations in the bottom of the East forty, low grade limonitic ores were mined from the upper horizon, immediately below the paintrock, and higher grade hematite was mined along the taconite bottom. Considerable clean-up work was completed along the bottom taconite, in the southwest corner of the East forty, and carried over the line into the mid-forty. This necessitated considerable drainage work and the operation of a secondary sump. In the newly-stripped area, on the north side of the Mid-Snyder, the lean upper ores were all mined and the high grade lower hematite was used sparingly in grading, conserving as much as possible for later years. The usual grading problems were encountered, but satisfactory concentrates were secured.

In the South Bovey, the bulk of the crude ore was mined above the paintrock layer, mixing upper lean limonitic material with higher grade intermediate hematite ore. Some high grade crude ore was secured from a concentrated trough in the blocky paintrock horizon,

7. OPEN PIT: (Continued)

g. Open Pit Mining and Loading: (continued)

where the low grade material at either side of the trough required considerable sorting of rock.

In the North Bovey, scram operations cleaned up a small trough of ore in the taconite bottom, immediately east of the pit pocket. The crude ore salvaged from the lean ore dump in the North Bovey was largely limonitic, with a low phosphorous and a fairly low silica content. This material was used in the production of Bessemer concentrates. The crude ore mined in the Hemmens was secured from an enriched area in the blocky formation in the southeast corner and from the upper lean ores immediately below the paintrock.

Both Bessemer and Non-Bessemer grades were produced in all of the areas worked. The spotty nature of the ore necessitated constant changes in the mix for grading. The use of a spare shovel, rented for that purpose, kept shovel moves at a minimum.

k. Drainage:

As during the previous year, the water level of the main sump, in the east end, was maintained at about the 490 foot elevation. On the other side of the main haulage road, the secondary sump was sunk and pumped to the 467 elevation, to facilitate bottom clean-up in that vicinity. The berm and ditch, retained along the south side of the secondary sump, bypassed most of the south side seepage and run-off through the water channel and into the main sump, reducing considerably the volume of secondary pumping.

With future developments of the South Bovey forty to its permanent southerly limits, the secondary sump regions will afford a more suitable location for the main sump.

8. COST OF OPERATION:

a. Comparative Mining Costs:

	BUDGET	COST PER TON	COST PER TON
	ESTIMATE	1945	1944
PRODUCT: Concentrates, (tons)	600,000	659,836	567,146
Average Tons Per Shift,		2,528	2,344
Tons Per Man Per Day,		38.49	34.74
Days Operated,		134	125

CANISTI	EO MINE
ANNUAL	REPORT
YEAR	1945

8. COST OF OPERATION:

(Continued)

a. Comparative Mining Costs: (continued)

•	BUDGET ESTIMATE	PER TON 1945	PER TON 1944
COST:	and the second second		
Open Pit Mining,	\$.171	\$.182	\$.171
General Pit Expense,	.143	.112	.168
Concentrating,	.128	.135	.113
Stocking & Loading Concentrate	es, .003	.002	.003
General Mine Expense,	.082	.077	.076
Idle and Winter Expense,	.170	.154	.171
Cost of Production,	\$.697	\$.662	\$.702
Depreciation- Plant & Equipme	nt,	.115	.116
Depreciation- Motorized Equip	ment,	.066	.041
Amortization-Stripping,	and the second of	.260	.250
Taxes - Ad Valorem,		.132	.141
Taxes - Occupational,		.076	.072
Taxes - Royalty,		.037	.031
Total Cost at Mine,		\$1.348	\$1.353
Administrative Expense,	and the second second	.050	.050
Miscellaneous Expense and Inco	ome,	.003	.035
GRAND TOTAL,		\$ 1.395	\$ 1.368

d. Detailed Cost Comparison:

(1) Product:

The similarity of operations during the seasons of 1944 and 1945 afforded a good basis for cost comparisons, although the latter was favored in general, due to the advantage of greater production. On the other hand, the two-year retroactive pay, of revised vacations and shift differentials, was all absorbed in the 1945 costs, creating an increase of \$.030 per ton of concentrate, which was prorated throughout the various captions in that year's cost setup. The budget estimate for 1945 was based, largely, on the previous year's costs and showed an anticipated slight net saving for the total cost of production. The actual saving was substantially greater than anticipated, even though the 1945 costs ebsorbed the additional burden of retroactive pay; however, a slight advantage in the actual was presented by an increase in production over the estimate.

8. COST OF OPERATION: (Continued)

d. Detailed Cost Comparison:

(2) Open Pit Mining:

In mining crude ore, the budget was set up equivalent to the 1944 costs and proved adequate for the 1945 operations, until the adjustment of the retroactive pay was applied, which resulted in an excess of \$.007 per ton of crude ore mined. This excess cost was further magnified in the conversion of the crude ore to a concentrate basis, resulting in an actual cost of \$.182, as compared with \$.171 per ton of the budget and the 1944 costs. Under this main heading, an increase in "Power Shovel Maintenance" during 1945 was more than offset by a saving in "Trucks Operating".

(3) General Pit Expense:

Under this heading, a budget cost of \$.143 per ton, as compared with \$.168 in 1944, was set up in anticipation of a smaller clean-up program. The 1945 actual cost amounted to \$.112 per ton of concentrates, including a six mill proration of retroactive pay. The saving occurred mainly in "Pit Clean-up" and "Stocking Lean Materials". There was also a lesser saving in the other captions under this main heading.

(4) Concentrating:

The previous year's concentrating cost of \$.113 was increased to \$.128 in the budget estimate, due to the anticipation of some additional cost in experimenting with new selective media concentrators. The application of the retroactive pay raised the final cost for 1945 to \$.135.

(5) Stocking and Loading Concentrates:

The 1945 cost for Stocking and Loading concentrates was \$.002 per ton, as compared with a budget cost of \$.003, based on a similar figure for the previous year.

(6) General Mine Expense:

The budget for 1945, under this heading, was estimated at \$.082, as compared with \$.076 in 1944, due to an anticipated increase in the "Analyses and Grading" for the experimental work with the new concentrators. The actual 1945 cost amounted to \$.077 per ton, including the distribution of the retroactive pay.

(7) Winter and Idle Expense:

Under this caption, the cost of \$.170 was estimated, as compared with the previous year's figure of \$.171 per ton. The actual cost of \$.154 per ton which was realized, was due mainly to increased production.

9. EXPLORATIONS AND FUTURE EXPLORATIONS:

> The total of 3,657 feet of structure drilling completed during the year, consisted of 1,987-1/2 feet of exploratory work, and 1,669-1/2 feet of sample drilling. In the former, there was 875 feet in the Snyder lease and 1,112-1/2 feet in the Bovey. One Snyder hole was sunk through barren formation to quartzite, west of the shops, to prove up a barren area for dump space. The balance of the Snyder exploratory work was conducted in the middle forty to justify the extension of the ore body to the north. The Bovey explorations were scattered on the north and south sides of the pit. On the north side, two barren holes were drilled to quartzite, in the NW1 of the NE1, to justify the disposal of waste on this area, and one hole was put down in the NW2 of the SE2, just across the line, while probing possible extension of the Mid-Snyder north limits. On the south side, several holes were put down at the extreme south limits of the pit, in an effort to outline the ultimate pit limits. These holes proved marginal, and with the drilling completed in 1944, proved that it will be necessary to shift the Great Northern and D. M. & I. R. tracks, either in 1946 or 1947. on the whole, the exploratory program will indicate a gain in tonnage, proving up a pit extension in the Mid-Snyder and ore at depth in the South Bovey.

The sample drilling conducted during the year was merely used as a guide in mining and grading operations.

Future drilling will outline the ore boundaries of the Hemmens and the possibility of an ore extension in the East Bovey to the Oliver Iron Mining Company line.

10. TAXES:

The following statement shows the Canisteo Mine taxes and the average annual rates for 1945 and 1944:

Canisteo Mine, Washing Plant Lands, Personal Property,	1 9 4 5 \$ 82,868.60 595.60 3,211.29	1 9 4 4 \$75,473.34 525.08 2,473.56	Increase \$7,395.26 70.52 737.73	Decrease
Total,	\$ 86,675.49	\$ 78,471.98	\$8,203.51	17 - 1 - 1 1
Village Lots,	216.54	191.59	24.95	1
GRAND TOTAL,	\$ 86,892.03	\$ 78,663.57	\$8,228.46	
Average Tax Rate,	122.23	108.14	14.09	

The general increase in 1945 was due to a higher rate of taxation, and a revised estimate, showing an additional tonnage of ore in the S_2^1 of SE_4^1 of Section 30, 56-24.

11. ACCIDENTS AND PERSONAL INJURY:

> There were two lost-time accidents at the Canisteo Mine during the year. These are described as follows:

NAME: CAUSE: Anselm Luoma Date: September 24th. It was understood shovel #48 would be moved after loading a few more trucks. Luoma, shovel oiler, had stepped off the shovel and was standing on the ground, at the rear of the machine, for the purpose of throwing in the clutch, which is the customary duty of the oiler when the shovel is to be moved. Evidently, he leaned against the crawling mechanism of the shovel and caught off guard when the shovel revolved while the operator was loading a truck, he was caught between the shovel house and the "cats" of the crawling mechanism, a space of approximately 7 or 8 inches. He was squeezed somewhat.

NATURE:

Contusion of upper right chest. No fracture. Difficulty in breathing. Possible internal injuries.

TIME LOST: Forty-one days.

COMPENSATION: \$ 164.00

NAME:

Arthur T. Forrest

Date: October 5th.

CAUSE:

Forrest, together with a fellow workman, was engaged in moving the 12-ton traveling crane from the front end of the shop, to the rear of the shop, where they were to use same in turning over a shovel dipper for repair. The traveling crane is manually-operated by hand chains on either side. The traveling crane is also equipped with a 2-ton hoist and a 12-ton hoist. As the crane neared its destination, Forrest saw that the load chain hook on the 2-ton hoist was about to "snag" a lamp cord which was being used on a tractor nearby, and in order to save the extension cord from being damaged, he hurriedly moved toward the tractor to move the load chain. In so doing, he stepped into the hand chain of the 12-ton hoist and fell to the ground, causing injury to his right foot. The loop of the hand chain was 4" above the ground.

NATURE: Fracture of lateral malleolus of fibula- (right).

TIME LOST: Seventy-five days.

COMPENSATION: \$ 300.00.

12. <u>NEW CONSTRUCTION</u> AND PROPOSED NEW CONSTRUCTION:

> No new construction took place during the year, and none is planned for the near future.

13. EQUIPMENT AND PROPOSED EQUIPMENT:

> New equipment received during 1945 consisted of a mechanical stoker for the shop boiler, two 20-ton Euclid trucks, a 600-gallon self-priming Carver mud pump, and a new 125-B Bucyrus electric shovel, which was being erected at the close of the year. A secondhand conveyor and loader were also purchased during the year to handle stoker coal from the car to the pocket. Two selective media concentrators were purchased for experimental work, but proved unsatisfactory and were dismantled and removed from the plant.

> The equipment recommended for purchase and delivery early in 1946 will consist of a 5-yard heavy duty "International" dump truck for rock rejects at the washing plant, a Willys jeep for general use between the shops and the pit, two additional 20-ton haulage trucks and a new 1,000-gallon self-priming pump for use in pit drainage.

14. MAINTENANCE AND REPAIRS:

The two 85-B electric shovels were given some much needed repairs alternately, over a two-month period during the spring and clean-up operations. The 2-yard spare shovel required considerable maintenance during the operating season. Maintenance and repair work on all motorized equipment was carried on continuously during the ore and stripping seasons.

The churn drills were overhauled completely during the winter and spring months.

The usual overhauling of the washing plant machinery and equipment was completed during the winter months, preparatory to the 1945 ore season, and post-season repairs were again started in the fall.

19. WASHING PLANT OPERATIONS:

> The washing plant was operated a total of 134 days, from May 7th to October 13th, inclusive, the schedule coinciding with the pit operations. The plant worked on a 48-hour per week basis, two 8hour shifts per day until October 8th, when a single shift per day

19. WASHING PLANT OPERATIONS: (Continued)

> became effective. Of the 262 shifts of plant activities, only one shift was devoted to emergency repairs.

A total of 1,234,205 tons of crude ore was washed during the year, to produce 659,836 tons of concentrates, showing an average weight recovery of 53.46%. The comparatively low recovery was the result of using a large proportion of limonitic ore in the crude mixtures. Plant production was retarded somewhat by the low recovery and by the handling of wet ores from the pit bottom. There were but few machinery delays during the entire season and, on the whole, the plant operation was very satisfactory.

Two selective media concentrators were installed, experimentally, in a comparative test with Akins classifiers. However, they proved that their operation was not applicable to wash ores. At the end of the season, they were again removed from the washing plant.

In order to avoid operating delays, concentrates were stocked during periods of empty car shortages and, at the end of the shipping season, concentrates were mined and stocked for eighteen shifts, in order to build up a reserve stockpile for spring shipments. A total of 65,229 tons of Snyder concentrates was added to the stockpile during the year, bringing the total on hand at the end of the year, up to 68,958 tons.

The tonnage and analyses of the plant rejects for the season are compiled below:

		5 x 14 Ser	een Reject	S
Lease:	Tons	Iron	Phos.	Silica
Snyder,	16,731	30.27	.040	51.82
Bovey,	9,208	30.75	.036	51.07
Hemmens,	1,737	32.02	.029	50.58
Total,	27,676	30.54	.038	51.49
	36" Belt Rejects			
Lease:	Tons	Iron	Phos.	Silica
Snyder,	5,556	27.53	.041	56.45
Bovey,	5,067	27.55	.034	56.32
Hemmens,	1,104	29.38	.037	53.48
Total,	11,727	27.71	.038	56.11

CANISTEO MINE
ANNUAL REPORT
YEAR 1945
YEAR 1945

-19. WASHING PLANT OPERATIONS: (Continued)

Tabulated below is the pit rock sorted at the shovels and hauled to the waste dump:

Lease:	Cubic Yards	Tons	Iron
Snyder,	3,884	6,796	31.53
Bovey,	1,358	2,377	28.47
Total,	5,242	9,173	30.74

Compiled below are the totals of lean materials and slough sorted and removed from the ore areas during the ore season and the spring clean-up period:

	Le	Lean Ore			
Lease	Cubic Yards	Tons	Iron		
Snyder,	26,223	45,887	38.71		
Bovey,	7,550	13,209	38.64		
Hemmens,	2,458	4,301	36.48		
Total,	36,231	63,397	38.54		
the second se					

	Waste Materials						
	Surface	Waste Ore	Total				
Lease	Cu.Yds.	Cu.Yds.	Cu. Yds.				
Snyder,	20,307	35,776	56,083				
Bovey,	1,374	5,377	6,751				
Hemmens,		23,270	23,270				
Total,	21,681	64,423	86,104				

Snyder Mill Machines.

The analyses of products from the various mill machines for the year 1945, were as follows:

	Service and the service of the	in the second second	
Tag Weaker	Iron	Phos.	Silica
rog wasner,	20.22	.030	12.09
Classifier,	56.71	.053	11.80
Tailings,	21.66		
Bovey Mill Machines:			
Log Washer,	56.20	.053	12.29
Classifier,	56.73	.048	11.94
Tailings,	21.50		
Hemmens Mill Machines:		Service .	
Log Washer,	56.56	.045	12.19
Classifier,	55.93	.046	12.16
Tailings,	19.55		

19. WASHING PLANT OPERATIONS: (Continued)

Materials removed in	Tonnage	% of Total Mined	% Dried Iron	Tonnage Recovery	Iron Unit Recovery
mining operations, (exclusive of surface, stripping and waste)	1,334,451	100.00	41.96		
Less: Lean ore stocked in mining,	63,397	4.75	38.54		
	1,271,054	95.25	42.13		
Less: Pit rock wasted,	9,173	.69	30.74		
Total transported to mill,	1,261,881	94.56	42.20		
Less: Rock rejects in screening plant,	27,676	2.07	30.54		
Crude ore entering mill,	1,234,205	92.49	42.47		
Concentrates produced,	659,836	49.45	57.02	53.46	71.77
Rock rejects on mill picking belt,	11,727	.88	27.71		
Tailings (by deduction)	562,642	42.16	25.71		
Total heads, as above (Entering Mill)	1,234,205	92.49	42.47		
Total pit rock, screening plant re- jects and lean ore,	100,246	7.51	35.62		
Total,	1,334,451	100.00	41.96		

1. GENERAL:

Operations at this property were conducted during the year 1945 in the same cycle as in previous years. Mining, concentrating, and stripping were carried on in their respective seasons with maintenance, pumping, and explorations carried on continuously.

The 1945 ore season started with the loading of Bingham direct ore from the pit and concentrates from stockpile, on April 2nd. Direct ore was loaded intermittently throughout the ore season. Stockpile loading was completed for the season in April.

The mining and washing of ore was started on May 1st and continued until October 27th. These operations were conducted on a schedule of two 8-hour shifts per day, six days per week. All ore was produced from Bingham lease until the last week in September, when operations were transferred to the Holman-Brown No. 2 pit bottom.

Concentrating of ore in the washing plant was carried forward on the same schedule as ore operations in the pit. Due to inadequate railroad service, it was necessary to stockpile on numerous occasions.

Stripping operations, carried forward from 1944, were confined to the Bingham lease from the first of the year until the ore season. This stripping consisted of moving surface, lean ore and waste ore which occurred over the wash ore. During the summer, an attempt was made to carry on a surface stripping program in the east end of the Brown No. 2 pit, but a lack of truck drivers caused suspension of this work until the end of the ore season, when this operation was carried forward on a 20-shift per week basis, with swing crew, until the end of the year.

Sample and exploratory drilling was carried on during the entire year, under contract, with both exploratory and sample holes on the Bingham lease and exploratory holes only on the Brown No. 1, Brown No. 2 and Holman leases.

All pit equipment and washing plant equipment was overhauled during the year.

2. PRODUCTION, SHIPMENTS & INVENTORIES:

8.

b.

c.

Production by	Grades:				
Holman Crude				58,203	tons
Brown Crude,				150,679	
Bingham Crude	0,			1,027,817	
TOTAL CRUDE,				1,236,699	
Production by (Grades:				
Holman-Non-B	essemer Concentrate	8,		13,722	tons
Holman Besser	mer Concentrates, -			23,377	
Brown Non-Be	ssemer Concentrates.			24,024	
Brown Bessen	er Concentrates,			71,824	
Bingham Non-	Bessemer Concentrate			254,668	
Bingham Besse	emer Concentrates.			393,149	
Bingham Non-	Bessemer Direct,			69.056	-
Bingham Bess	emer Direct,			29,945	
TOTAL PRODUCT	rion,			879,765	
Shipments:					
Holman Non-Be	essemer Concentrates	8,		13,722	tons
Holman Bessen	ner Concentrates,			23,377	
Brown Non-Bes	ssemer Concentrates,			24,024	
Brown Besseme	er Concentrates,			71,824	
Bingham Non-I	Bessemer Concentrate			201,737	
Bingham Besse	amer Concentrates, .			416,169	
Bingham Non-I	Bessemer Direct,			69.056	-
Bingham Besse	emer Direct,			29,945	
TOTAL SHIPME	NTS,			849,854	
Stockpile Inver	atories:				
Bingham Non-I	Bessemer Concentrate			71,468	
The follow	ving is a statement	of the le	an mater	ials	
Conce	entrating Material a	bove 25%			
	Tons	Iron	Phos.	Silica	
Holman,	26,096	32.16			
Brown,	256,908	30.85			
North Star,	20,658	26.29	.046	49.24	
Bingham,	234,873	31.67	.036	49.09	

Coarse Non-Concentrating Material Above 40%

	Tons	Iron	Phos.	Silica
North Star,	585	48.89	.044	24.50

HOLMAN-CI	LIFFS	MINE
ANNUAL	REPOR	TS
YEAR	1945	

2. FRODUCTION, SHIPMENTS & INVENTORIES: (Continued)

c. Stockpile Inventories: (Continued)

Pai	nt Rock Abov	e 25%			
Bingham,	Tons 52,797	Iron 47.22	Phos.	Silica 25.87	
e. Production by M	onths:				
May,	HOL	MAN	BROWN	BINGHAM 230,198	TOTAL 230, 198
June, July,			3,506	242,157 213,434	242,157 216,940
August, September,	10,	269	34,224	207,352 132,111	207,352 176,604
October,	47,	934 1	12,949	2,565	163,448

(2) Concentrates and Direct Ore:

	HOLMAN CONCTS.	EROWN CONCTS.	BINGHAM CONCTS.	BINGHAM	TOTAL
April,		and the second	2,635	34,235	36,870
May,			150,221		150,221
June,			155,821		155,821
July,	100 Mar	2,251	135,336	26,031	163,618
August,		and the second second	123,973	9,668	133,641
September,	6,375	22,368	78,427	4,995	112,165
October,	30,724	71,225	1,404	24,072	127,425
November,		4			
TOTAL,	37,099	95,848	647,817	99,001	879,765

f. Ore Statement:

On January 1st, 1945, there were 41,557 tons of Bingham concentrate remaining in stockpile. These were loaded out in April and 71,468 tons of Bingham concentrate placed in stock during the 1945 season, making a stockpile balance on December 31st, 1945, of 71,468 tons of Bingham concentrate.

g. Delays:

The following is a statement, on a cumulative basis, of the delays during the year 1945:

2. PRODUCTION, SHIPMENTS & INVENTORIES: (Continued)

g. Delays: (continued)

Time	Lost	and the second
Hours 14	Minutes 50	<u>Cause:</u> Inadequate railroad service on empty cars and loads.
23	•	Transportation troubles, derailment, track and locomotive repairs.
1.	-	Power failure due to storms and mechanical trouble.
3	15	Pit Ramp, repairs and material lodged in pocket.
7	-	Repairing washing plant equipment.
5	-	Washing plant operating delays, sticky ore and low power during storms.
60	05	

The notes giving cause of delays are self-explanatory.

3. ANALYSIS:

h

	Tons	Iron	Phos.	sil.	Mang.	Alu.	Moist.	Fe. Nat
Holman N.B.	17 000		~	10 07			1 00	E7 00
Concts.	13,722	57.01	.041	12.75	•11	.47	0.92	52.07
Holman Bess.	07 700	57 86	076	10 04	15	40	4	54 07
Ducing M D	23,311	21.00	.030	12024	.13	• 47	0.33	24.01
Concs.	24 0.24	57.28	.046	12.62	.15	.49	7.00	53. 27
Brown Bess.	24,024	21020		TLOOL		•••	1.00	,,,-,
Cones.	71.824	57.98	.037	12.23	.14	.48	6.58	54.17
Bingham N.B.								
Concs.	254,668	57.62	.046	12.92	.18	.66	7.54	53.28
Bingham								
Bess.Concs.	393,149	58.18	.035	12.47	.15	.62	7.14	54.03
Bingham N.B.								
Direct,	69,056	57.26	.050	11.71	.21	2.49	13.47	49.55
Bingham Bess.								
Direct,	29,945	58.15	.041	10.85	.20	2.34	13.54	50.28
TOTAL,	879,765	57.88	.039	12.47	.17	.82	7.90	53.31
ne Analysis (of Shipmen	ats:						-
Holman N.B.			1					
Concs.	13,722	57.01	.047	12.73	.17	.49	6.92	53.07
Holman Bess.								
Concs.	23.377	57.86	.036	12.24	.15	.49	6.55	54.07

3. ANALYSIS: (Continued)

b. Mine Analysis of Shipments: (continued)

	Tons	Iron	Phos.	sil.	Mang.	Alu.	Moist.	Fe.Nat.
Brown N.B. Concts.	24,024	57.28	.046	12.62	.15	.49	7.00	53.27
Brown Bess. Concts.	71,824	57.98	.037	12.23	.14	.48	6.58	54.17
Bingham N.B. Concts.	201,737	57.74	.046	12.44	.20	.70	7.60	53.35
Bingham Bess. Concts.	416, 169	58.19	.035	12.44	.16	.63	7.16	54.02
Bingham N.B. Direct,	69,056	57.26	.050	11.71	.21	2.49	13.47	49.55
Bingham Bess. Direct,	29,945	58.15	.041	10.85	.20	2.34	13.54	50.28
TOTAL,	849,854	57.94	.040	12.31	.17	.83	7.93	53.35

c. Mine Analysis of Ore in Stockpile:

Bingham Concentrates, 71,468 57.30 .036 13.78 .16 .59 7.39 53.07

d. Average Analysis of Crude Ore Production:

Holman.	Tons 58,203	1ron 45.38	Phos.	Silica 30,50
Brown, Bingham,	150,679 1,027,817	44.65 45.18	.032 .030	31.34 31.43
Total,	1,236,699	45.13	.030	31.38

e. Complete Analyses of Season's Shipments:

	Iron	Phos.	Sil.	Mang.	Alu.	Lime	Mag.	Sul.	Loss
Holman N.B.									-
Concts.	57.01	.047	12.73	.17	.49	.27	.18	.011	4.46
Holman Bess.									
Concts.	57.86	.036	12.24	.15	.49	.27	.17	.012	3.80
Brown N.B.					1				
Concts.	57.28	.046	12.62	.15	.49	.30	.15	.011	4.22
Brown Bess.					-				
Concts.	57.98	.037	12.23	.14	.48	.29	.15	.010	3.66
Bingham N.B.		-							
Concts.	57.74	.046	12.44	.20	.70	.31	.20	.010	3.40
Bingham Bess.				24					
Concts.	58.19	.035	12.44	.16	.63	.32	.19	.011	2.91
Bingham N.B.									
Direct,	57.26	.050	11.71	.21	2.49	.33	.19	.011	2.99
Bingham Bess.				-					
Direct,	58.15	.041	10.85	.20	2.34	.34	.18	.012	2.77